
* STAAD.Pro
* Version 2004 Bld 1001.INDIA
* Proprietary Program of
* Research Engineers, Intl.
* Date= DEC 12, 2012
* Time= 14:18:58
* USER ID: Snow Panther [120]

INPUT FILE: Structural.STD
1. STAAD PLANE
2. START JOB INFORMATION
3. ENGINEER DATE 11-DEC-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 0 0; 2 1.4 0 0; 3 2.8 0 0; 4 4.2 0 0; 5 5.6 0 0
9. MEMBER INCIDENCES
10. 1 1 2; 2 2 3; 3 3 4; 4 4 5
11. START USER TABLE
12. TABLE 1
13. UNIT METER KN
14. WIDE FLANGE
15. 203X102
16. 0.0037812 0.102 0.0062 0.203 0.008 7.52078E-006 1.11556E-005 7.61227E-008 -
17. 0.0006324 0.00216533
18. END
19. DEFINE MATERIAL START
20. ISOTROPIC STEEL
21. E 2.05E+008
22. POISSON 0.3
23. DENSITY 76.8195
24. ALPHA 1.2E-005
25. DAMP 0.03
26. END DEFINE MATERIAL
27. MEMBER PROPERTY AMERICAN
28. 1 TO 4 UPTABLE 1 203X102
29. CONSTANTS
30. MATERIAL STEEL MEMB 1 TO 4
31. SUPPORTS
32. 1 TO 5 PINNED
33. LOAD 1 DL
34. SELFWEIGHT Y -1
35. LOAD 2 LL
36. MEMBER LOAD
37. 2 CON GY -123 0.385
38. 2 CON GY -123 1.015
39. LOAD COMB 3 1.0(DL+LL)
40. 1 1.0 2 1.0

STAAD PLANE

41. LOAD COMB 4 1.4(DL+LL)
42. 1 1.4 2 1.4
43. PERFORM ANALYSIS

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER/ELEMENTS/SUPPORTS = 5/ 4/ 5
ORIGINAL/FINAL BAND-WIDTH= 1/ 1/
TOTAL PRIMARY LOAD CASES = 2, TOTAL DEGREES OF FREEDOM = 5
SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
REQD/AVAIL. DISK SPACE = 12.0/ 11094.2 MB, EXMEM = 615.2 MB

44. PARAMETER
45. CODE BS4950
46. PY 275000 ALL
47. PRINT SUPPORT REACTION