

```

*****
*
*          STAAD.Pro
*          Version 2004    Bld 1001.INDIA
*          Proprietary Program of
*          Research Engineers, Intl.
*          Date=    DEC 27, 2008
*          Time=    8: 8:22
*
*          USER ID: Snow Panther [LZ0]
*****

```

INPUT FILE: STEEL SUPPORT FOR MOVEO PARTITIONS.STD

```

1. STAAD SPACE FRAME1
2. START JOB INFORMATION
3. ENGINEER DATE 23-DEC-08
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT MMS NEWTON
7. JOINT COORDINATES
8. 1 0 0 0; 2 1244 0 0; 3 2994 0 0; 4 4306 0 0; 5 5619 0 0; 6 6944 0 0
9. 7 8803 0 0; 8 -1405 1620 0; 9 1466 1631 0; 10 473 0 0; 11 473 -3300 0
10. 12 8803 -3300 0; 13 0 1625 0; 14 1802 1631 0; 15 1244 1631 0; 16 2994 1624 0
11. 17 4306 1615 0; 18 4666 1615 0; 19 5619 1598 0; 20 5002 1615 0; 21 6944 1567 0
12. 22 7849 1546 0; 25 6944 1567 2064; 26 7849 1546 2064; 27 6944 0 1000
13. 28 8803 0 1000; 29 8803 -3300 1000; 30 6944 0 2064; 31 5002 1615 2064
14. 32 7890 0 0; 33 7890 0 1000; 34 8803 -1650 0; 35 8803 -1650 1000
15. MEMBER INCIDENCES
16. 1 1 10; 2 2 3; 3 3 4; 4 4 5; 5 5 6; 6 6 32; 7 10 2; 8 11 10; 9 12 34; 10 8 13
17. 11 13 15; 12 1 13; 13 15 9; 14 2 15; 15 14 16; 16 16 17; 17 17 18; 18 3 16
18. 19 4 17; 20 20 19; 21 19 21; 22 5 19; 23 6 21; 24 21 22; 25 25 26; 26 27 33
19. 27 29 35; 28 6 27; 29 27 30; 30 30 25; 31 31 25; 32 32 7; 33 33 28; 34 33 32
20. 35 7 28; 36 34 7; 37 35 28; 38 35 34
21. DEFINE MATERIAL START
22. ISOTROPIC STEEL
23. E 205000
24. POISSON 0.3
25. DENSITY 7.68195E-005
26. ALPHA 1.2E-005
27. DAMP 0.03
28. END DEFINE MATERIAL
29. CONSTANTS
30. BETA 90 MEMB 8 9 12 14 18 19 22 23 27 30 36 37
31. MATERIAL STEEL MEMB 1 TO 38
32. MEMBER PROPERTY BRITISH
33. 10 TO 25 30 31 TABLE ST UC152X152X23
34. 1 TO 7 26 28 29 32 TO 34 TABLE ST UC203X203X46
35. 8 9 27 35 TO 38 TABLE ST TUB1501006.0
36. SUPPORTS
37. 11 12 29 FIXED
38. 8 9 14 18 20 22 26 31 PINNED
39. MEMBER RELEASE
40. 26 28 34 START MX MY MZ

```

41. 29 34 END MX MY MZ
 42. LOAD 1 DL1-SELF WEIGHT
 43. SELFWEIGHT Y -1
 44. LOAD 2 DL2-WEIGHT OF FIXED PARTITION ABOVE STEEL BEAM
 45. MEMBER LOAD
 46. 1 TO 7 32 UNI GY -1.089
 47. LOAD 3 DL3-WEIGHT OF MOVABLE PARTITION
 48. MEMBER LOAD
 49. 1 TO 7 32 UNI GY -0.764
 50. LOAD 4 DL4-WEIGHT OF FOLDED MOVABLE PARTITION
 51. MEMBER LOAD
 52. 32 33 UNI GY -3.406
 53. LOAD 5 IL-IMPOSED LOAD
 54. MEMBER LOAD
 55. 1 TO 7 32 UNI GZ -0.36
 56. LOAD COMB 6 DL1+DL2+DL3+IL
 57. 1 1.0 2 1.0 3 1.0 5 1.0
 58. LOAD COMB 7 DL1+DL2+DL4
 59. 1 1.0 2 1.0 4 1.0
 60. LOAD COMB 8 DL1+DL2+DL3+IL
 61. 1 1.4 2 1.4 3 1.4 5 1.6
 62. LOAD COMB 9 DL1+DL2+DL4
 63. 1 1.4 2 1.4 4 1.4
 64. PERFORM ANALYSIS

PROBLEM STATISTICS

 NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 33/ 38/ 11
 ORIGINAL/FINAL BAND-WIDTH= 25/ 5/ 33 DOF
 TOTAL PRIMARY LOAD CASES = 5, TOTAL DEGREES OF FREEDOM = 156
 SIZE OF STIFFNESS MATRIX = 6 DOUBLE KILO-WORDS
 REQD/AVAIL. DISK SPACE = 12.1/ 15454.2 MB, EXMEM = 1783.1 MB

ZERO STIFFNESS IN DIRECTION 6 AT JOINT 27 EQN.NO. 102
 LOADS APPLIED OR DISTRIBUTED HERE FROM ELEMENTS WILL BE IGNORED.
 THIS MAY BE DUE TO ALL MEMBERS AT THIS JOINT BEING RELEASED OR
 EFFECTIVELY RELEASED IN THIS DIRECTION.

65. LOAD LIST 6 TO 9
 66. PRINT SUPPORT REACTION ALL

SUPPORT REACTIONS -UNIT NEWT MMS STRUCTURE TYPE = SPACE

JOINT	LOAD	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM Z
11	6	-1.200E+01	4.074E+03	1.106E+03	3.262E+06	-2.141E+05	2.438E+04
	7	15.21	3012.25	-3.88	-11457.66	2748.74	-21891.64
	8	-2.230E+01	5.757E+03	1.770E+03	5.221E+06	-3.429E+05	4.300E+04
	9	21.29	4217.14	-5.44	-16040.72	3848.24	-30648.30
12	6	-371.25	8656.56	909.90	932629.88	383150.94	326324.28
	7	-149.57	6096.23	6.80	11329.70	-2027.70	161734.72
	8	-5.651E+02	1.293E+04	1.455E+03	1.490E+06	6.120E+05	4.904E+05
	9	-209.40	8534.72	9.52	15861.58	-2838.77	226428.62
29	6	312.09	-2800.33	902.93	928872.06	382677.59	-386461.94
	7	-151.46	3912.81	-2.06	6576.78	-2064.00	162177.97
	8	5.262E+02	-4.783E+03	1.445E+03	1.484E+06	6.112E+05	-6.472E+05
	9	-212.05	5477.93	-2.88	9207.49	-2889.61	227049.16
8	6	-60.79	74.74	78.90	0.00	0.00	0.00
	7	45.42	60.50	-0.25	0.00	0.00	0.00
	8	-103.02	113.38	126.28	0.00	0.00	0.00
	9	63.58	84.70	-0.35	0.00	0.00	0.00
9	6	-224.99	4775.40	156.46	0.00	0.00	0.00
	7	59.66	3563.17	-0.54	0.00	0.00	0.00
	8	-359.34	6648.00	250.42	0.00	0.00	0.00
	9	83.53	4988.44	-0.76	0.00	0.00	0.00
14	6	-440.44	734.99	4.20	0.00	0.00	0.00
	7	-222.60	468.93	-0.01	0.00	0.00	0.00
	8	-641.29	1041.61	6.73	0.00	0.00	0.00
	9	-311.63	656.51	-0.02	0.00	0.00	0.00
18	6	584.28	7035.41	4.72	0.00	0.00	0.00
	7	603.65	5480.49	-0.05	0.00	0.00	0.00
	8	776.93	9831.23	7.56	0.00	0.00	0.00
	9	845.11	7672.68	-0.07	0.00	0.00	0.00
20	6	-1084.90	3678.95	6.42	0.00	0.00	0.00
	7	-785.22	2873.67	-0.06	0.00	0.00	0.00
	8	-1559.28	5176.07	10.28	0.00	0.00	0.00
	9	-1099.30	4023.14	-0.08	0.00	0.00	0.00
22	6	402.46	2139.06	-0.09	0.00	0.00	0.00
	7	491.81	2153.27	0.06	0.00	0.00	0.00
	8	528.91	2981.67	-0.17	0.00	0.00	0.00
	9	688.53	3014.58	0.08	0.00	0.00	0.00
26	6	662.20	1598.56	0.00	0.00	0.00	0.00
	7	147.94	1320.54	0.00	0.00	0.00	0.00
	8	1035.81	2342.10	0.00	0.00	0.00	0.00
	9	207.11	1848.75	0.00	0.00	0.00	0.00
31	6	233.33	194.30	0.00	0.00	0.00	0.00
	7	-54.84	713.78	0.00	0.00	0.00	0.00
	8	382.48	187.56	0.00	0.00	0.00	0.00
	9	-76.77	999.30	0.00	0.00	0.00	0.00

***** END OF LATEST ANALYSIS RESULT *****

67. PARAMETER
68. CODE BS5950
69. PY 275 MEMB 1 TO 38
70. RATIO 1 MEMB 1 TO 38
71. CHECK CODE MEMB 1 TO 38

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.9_5950-1_2000