

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    MAR 26, 2013                  *
*          Time=    15: 0:48                      *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L  *
*****

```

```

1. STAAD SPACE
INPUT FILE: Level 2.5m R1 Section.STD
2. START JOB INFORMATION
3. ENGINEER DATE 23-MAR-13
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 2 2.132 0 0; 3 0 2.35 0; 4 2.132 2.35 0; 5 0 2.35 0.657; 6 2.132 1.735 0
9. 7 2.132 1.735 -0.6
10. MEMBER INCIDENCES
11. 2 3 4; 3 2 6; 4 3 5; 5 6 4; 6 7 6
12. START USER TABLE
13. TABLE 1
14. UNIT METER KN
15. WIDE FLANGE
16. UB250X125X29
17. 0.003642 0.25 0.006 0.125 0.009 3.89293E-005 2.93386E-006 7.7454E-008 -
18. 0.0015 0.00225
19. END
20. DEFINE MATERIAL START
21. ISOTROPIC STEEL
22. E 2.05E+008
23. POISSON 0.3
24. DENSITY 76.8195
25. ALPHA 1.2E-005
26. DAMP 0.03
27. TYPE STEEL
28. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
29. END DEFINE MATERIAL
30. MEMBER PROPERTY BRITISH
31. 6 TABLE ST CH150X75X18
32. MEMBER PROPERTY
33. 2 TO 5 UPTABLE 1 UB250X125X29
34. CONSTANTS
35. MATERIAL STEEL ALL
36. SUPPORTS
37. 2 5 FIXED
38. *MEMBER RELEASE
39. *2 START MPY 0.99 MPZ 0.99
40. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT

```

```

41. SELFWEIGHT Y -1
42. LOAD 2 LOADTYPE LIVE TITLE LOAD CASE 2 LIVE LOAD ( PIPE FY )
43. MEMBER LOAD
44. 2 CON GY -19.8 0.6
45. 2 CON GY -11.5 1.6
46. 6 CON GY -2.23 0.14
47. LOAD 3 LOADTYPE LIVE TITLE LOAD CASE 3 LIVE LOAD ( PIPE FZ )
48. MEMBER LOAD
49. 2 CON GZ 3.31 0.6
50. 2 CON GZ 1.92 1.6
51. 6 CON GX 0.22 0.14
52. *LOAD 4 LOADTYPE NONE TITLE LOAD CASE 4 HNLZ
53. *NOTIONAL LOAD
54. *1 X 0.007 2 X 0.008
55. LOAD COMB 5 COMBINATION LOAD CASE 4 1.0DL+1.0LL(FY)
56. 1 1.0 2 1.0
57. LOAD COMB 6 COMBINATION LOAD CASE 5 1.4DL+1.6LL(FY) +1.0LL(FZ)
58. 1 1.4 2 1.6 3 1.0
59. *LOAD COMB 7 COMBINATION LOAD CASE 7 1.4DL + 1.6LL (FY)+ 1.0HNLZ
60. *1 1.4 2 1.6 4 1.0
61. PERFORM ANALYSIS

```

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 6/ 5/ 2

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH=	4/	4/	12 DOF	
TOTAL PRIMARY LOAD CASES =	3,	TOTAL DEGREES OF FREEDOM =		24
SIZE OF STIFFNESS MATRIX =	1 DOUBLE KILO-WORDS			
REQRD/AVAIL. DISK SPACE =	12.0/	0.0 MB		

62. PARAMETER 2
63. CODE BS5950
64. KY 1.5 MEMB 3 5
65. KZ 1.5 MEMB 3 5
66. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000