

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    MAR 26, 2013                  *
*          Time=    15:34:19                     *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L
*****

```

```

1. STAAD SPACE
INPUT FILE: Level 2.5m R2 Section ( R3 R4 Similar )_1.STD
2. START JOB INFORMATION
3. ENGINEER DATE 23-MAR-13
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 2 2.002 0 0; 3 0 2.375 0; 4 2.002 2.375 0; 5 0.8 2.375 0; 6 2.002 1.875 0
9. 9 0.8 1.875 0
10. MEMBER INCIDENCES
11. 2 3 5; 3 2 6; 4 5 4; 5 6 4; 8 9 6; 9 9 5
12. START USER TABLE
13. TABLE 1
14. UNIT METER KN
15. WIDE FLANGE
16. UB250X125X29.0
17. 0.003642 0.25 0.006 0.125 0.009 3.89293E-005 2.93386E-006 7.7454E-008 -
18. 0.0015 0.00225
19. END
20. DEFINE MATERIAL START
21. ISOTROPIC STEEL
22. E 2.05E+008
23. POISSON 0.3
24. DENSITY 76.8195
25. ALPHA 1.2E-005
26. DAMP 0.03
27. TYPE STEEL
28. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
29. END DEFINE MATERIAL
30. MEMBER PROPERTY
31. 2 TO 5 8 9 UPTABLE 1 UB250X125X29.0
32. CONSTANTS
33. MATERIAL STEEL ALL
34. SUPPORTS
35. 2 3 FIXED
36. *MEMBER RELEASE
37. *2 START MPY 0.99 MPZ 0.99
38. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT
39. SELFWEIGHT Y -1
40. LOAD 2 LOADTYPE LIVE TITLE LOAD CASE 2 LIVE LOAD ( PIPE FY )

```

STAAD SPACE

-- PAGE NO. 2

41. MEMBER LOAD
 42. 2 CON GY -19.8 0.6
 43. 4 CON GY -11.5 0.8
 44. 8 CON GY -2.23 0.245
 45. LOAD 3 LOADTYPE LIVE TITLE LOAD CASE 3 LIVE LOAD (PIPE FZ)
 46. MEMBER LOAD
 47. 2 CON GZ 3.31 0.6
 48. 4 CON GZ 1.92 0.8
 49. 8 CON GY 0.22 0.245
 50. *LOAD 4 LOADTYPE NONE TITLE LOAD CASE 4 HNLZ
 51. *NOTIONAL LOAD
 52. *1 X 0.007 2 X 0.008
 53. LOAD COMB 5 COMBINATION LOAD CASE 4 1.0DL+1.0LL(FY)
 54. 1 1.0 2 1.0
 55. LOAD COMB 6 COMBINATION LOAD CASE 5 1.4DL+1.6LL(FY) +1.0LL(FZ)
 56. 1 1.4 2 1.6 3 1.0
 57. *LOAD COMB 7 COMBINATION LOAD CASE 7 1.4DL + 1.6LL (FY)+ 1.0HNLZ
 58. *1 1.4 2 1.6 4 1.0
 59. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 6/ 6/ 2

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 4/ 4/ 18 DOF
 TOTAL PRIMARY LOAD CASES = 3, TOTAL DEGREES OF FREEDOM = 24
 SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
 REQD/AVAIL. DISK SPACE = 12.0/ 0.0 MB

60. PARAMETER 2
 61. CODE BS5950
 62. KY 1.5 MEMB 3 5
 63. KZ 1.5 MEMB 3 5
 64. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000