

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    JAN 30, 2013                  *
*          Time=    16:46:52                      *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L
*****

```

```

1. STAAD SPACE
INPUT FILE: 199-PF-04.STD
2. START JOB INFORMATION
3. ENGINEER DATE 24-NOV-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 0 0 0; 3 2 1.65 0; 6 0 0 0.8; 7 2 1.65 0.8; 8 5.3 1.65 0.8; 10 2 0 0
9. 12 2 0 0.8; 13 5.3 0 0.8; 14 6.1 1.65 0; 15 6.1 0 0; 18 6.71421 0 2.21421
10. 20 5.86569 1.65 0.234314; 21 7.2799 0 1.64852
11. MEMBER INCIDENCES
12. 2 1 3; 3 3 14; 5 6 7; 6 7 8; 8 10 3; 9 12 7; 11 13 8; 12 3 7; 14 15 14
13. 15 8 20; 18 18 8; 21 20 14; 25 21 20
14. DEFINE MATERIAL START
15. ISOTROPIC STEEL
16. E 2.05E+008
17. POISSON 0.3
18. DENSITY 76.8195
19. ALPHA 1.2E-005
20. DAMP 0.03
21. TYPE STEEL
22. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
23. END DEFINE MATERIAL
24. MEMBER PROPERTY BRITISH
25. 3 6 8 9 11 12 14 15 21 TABLE ST UC152X152X23
26. 2 5 18 25 TABLE ST CH200X75X23
27. CONSTANTS
28. BETA 90 MEMB 8 9
29. BETA 45 MEMB 11 14
30. MATERIAL STEEL ALL
31. MEMBER RELEASE
32. 2 5 18 25 END MPY 0.99 MPZ 0.99
33. SUPPORTS
34. 1 6 10 12 13 15 18 21 PINNED
35. DEFINE WIND LOAD
36. TYPE 1 WIND 1
37. INT 0.337 HEIG 1.65
38. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT
39. SELFWEIGHT Y -1
40. LOAD 2 LOADTYPE DEAD TITLE LOAD CASE 2 SDL

```

STAAD SPACE

-- PAGE NO. 2

41. ONEWAY LOAD

42. YRANGE 0 1.65 ONE -0.75 GY

****WARNING** about Floor/OneWay Loads/Weights.**

Please note that depending on the shape of the floor you may have to break up the FLOOR/ONEWAY LOAD into multiple commands. For details please refer to Technical Reference Manual Section 5.32.4 Note 6.

43. MEMBER LOAD

44. 2 5 18 UNI GY -0.3

45. LOAD 3 LOADTYPE LIVE REDUCIBLE TITLE LOAD CASE 3 LIVE LOAD

46. ONEWAY LOAD

47. YRANGE 0 1.65 ONE -5 GY

48. MEMBER LOAD

49. 2 5 18 UNI GY -1.6

50. LOAD 4 LOADTYPE WIND TITLE LOAD CASE 4 WIND LOAD X

51. WIND LOAD X 1 TYPE 1 XR 2 2.01 YR 0 1.65 OPEN

52. LOAD 5 LOADTYPE WIND TITLE LOAD CASE 5 WIND LOAD Z

53. WIND LOAD Z 1 TYPE 1 XR 0 6.1 YR 0 1.65 ZR 0 0.1 OPEN

54. LOAD 6 LOADTYPE NONE TITLE LOAD CASE 6 NOTIONAL LOAD X

55. NOTIONAL LOAD

56. 1 X 0.007 2 X 0.007 3 X 0.008

57. LOAD 7 LOADTYPE NONE TITLE LOAD CASE 7 NOTIONAL Z

58. NOTIONAL LOAD

59. 1 Z 0.007 2 Z 0.007 3 Z 0.008

60. LOAD COMB 8 COMBINATION LOAD CASE 8 1.0DL+1.0LL

61. 1 1.0 2 1.0 3 1.0

62. LOAD COMB 9 COMBINATION LOAD CASE 9 1.4DL+1.6LL

63. 1 1.4 2 1.4 3 1.6

64. LOAD COMB 10 COMBINATION LOAD CASE 10 1.4DL+1.6LL+1.0WLX

65. 1 1.4 2 1.4 3 1.6 4 1.0

66. LOAD COMB 11 COMBINATION LOAD CASE 11 1.4DL+1.6LL+1.0WLZ

67. 1 1.4 2 1.4 3 1.6 5 1.0

68. LOAD COMB 12 COMBINATION LOAD CASE 12 1.4DL+1.6LL+1.0NLX

69. 1 1.4 2 1.4 3 1.6 6 1.0

70. LOAD COMB 13 COMBINATION LOAD CASE 13 1.4DL+1.6LL+1.0NLZ

71. 1 1.4 2 1.4 3 1.6 7 1.0

72. LOAD COMB 14 COMBINATION LOAD CASE 14 1.0DL+1.4WLX

73. 1 1.0 2 1.0 4 1.4

74. LOAD COMB 15 COMBINATION LOAD CASE 15 1.0DL+1.4WLZ

75. 1 1.0 2 1.0 5 1.4

76. LOAD COMB 16 COMBINATION LOAD CASE 16 1.0DL+1.4NLX

77. 1 1.0 2 1.0 6 1.4

78. LOAD COMB 17 COMBINATION LOAD CASE 17 1.0DL+1.4NLZ

STAAD SPACE

-- PAGE NO. 3

79. 1 1.0 2 1.0 7 1.4
 80. LOAD COMB 18 COMBINATION LOAD CASE 18 1.2DL+1.2LL+1.2WLX
 81. 1 1.2 2 1.2 3 1.2 4 1.2
 82. LOAD COMB 19 COMBINATION LOAD CASE 19 1.2DL+1.2LL+1.2WLZ
 83. 1 1.2 2 1.2 5 1.2
 84. LOAD COMB 20 COMBINATION LOAD CASE 20 1.2DL+1.2LL+1.2NLX
 85. 1 1.2 2 1.2 3 1.2 6 1.2
 86. LOAD COMB 21 COMBINATION LOAD CASE 21 1.2DL+1.2LL+1.2NLZ
 87. 1 1.2 2 1.2 3 1.2 7 1.2
 88. LOAD COMB 100 COMBINATION LOAD CASE 100
 89. 1 1.0 2 1.0
 90. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 13/ 13/ 8

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 7/ 5/ 27 DOF
 TOTAL PRIMARY LOAD CASES = 7, TOTAL DEGREES OF FREEDOM = 54
 SIZE OF STIFFNESS MATRIX = 2 DOUBLE KILO-WORDS
 REQ'D/AVAIL. DISK SPACE = 12.0/ 202319.4 MB

91. PARAMETER 2
 92. CODE BS5950
 93. KY 1.5 MEMB 8 9 11 14
 94. KZ 1.5 MEMB 8 9 11 14
 95. CHECK CODE MEMB 2 3 5 6 8 9 11 12 14 15 18 21

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000