

```
*****
*
*          STAAD.Pro
*          Version  2007    Build 01
*          Proprietary Program of
*          Research Engineers, Intl.
*          Date=    NOV 30, 2011
*          Time=    11:32:58
*
*          USER ID: xyz
*****

1. STAAD SPACE DXF IMPORT OF 20111021_PR251-PR273A.DXF
INPUT FILE: 20111127 PR251-PR273A RF.STD
2. START JOB INFORMATION
3. ENGINEER DATE 01-NOV-11
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 -3 3.8 9; 2 -3 3.8 0; 3 0 3.8 9; 4 0 3.8 0; 5 -3 3.8 13; 6 0 3.8 13; 7 0 0 0
9. 8 0 0 9; 9 0 0 13; 10 -3 0 0; 11 -3 0 9; 12 -3 0 13; 13 2 0 13; 14 2 3.8 13
10. 15 2 3.8 10; 16 2 0 10; 17 8 0 13; 18 8 3.8 13; 19 8 3.8 10; 20 8 0 10
11. 21 14 3.8 13; 22 14 3.8 10; 23 14 0 10; 24 14 0 13; 25 20 3.8 13; 26 20 3.8 10
12. 27 20 0 10; 28 20 0 13; 29 26 3.8 13; 30 26 3.8 10; 31 26 0 10; 32 26 0 13
13. 33 32 3.8 13; 34 32 3.8 10; 35 32 0 10; 36 32 0 13; 37 38 3.8 13; 38 38 3.8 10
14. 39 38 0 10; 40 38 0 13; 41 44 3.8 13; 42 44 3.8 10; 43 44 0 10; 44 44 0 13
15. 45 50 3.8 13; 46 50 3.8 10; 47 50 0 10; 48 50 0 13; 49 53.5 3.8 13
16. 50 53.5 3.8 10; 51 53.5 0 13; 52 53.5 0 10; 53 53.5 0 18.9484
17. 54 53.5 3.8 18.9484; 55 50 0 18.9484; 56 50 3.8 18.9484; 57 50 0 24.9484
18. 58 50 3.8 24.9484; 59 53.5 0 24.9484; 60 53.5 3.8 24.9484; 61 50 0 32.4484
19. 62 50 3.8 32.4484; 63 53.5 0 32.4484; 64 53.5 3.8 32.4484; 65 50 0 39.7531
20. 66 50 3.8 39.7531; 67 53.5 0 39.7531; 68 53.5 3.8 39.7531; 69 53.5 0 14.9484
21. 70 53.5 3.8 14.9484; 71 50 0 14.9484; 72 50 3.8 14.9484; 73 -3 3.8 10
22. 74 0 3.8 10; 75 50 3.8 21.9484; 76 53.5 3.8 21.9484; 77 -3 3.8 4.5
23. 78 0 3.8 4.5; 79 50 3.8 36.1031; 80 53.5 3.8 36.1031; 81 50 3.8 28.6984
24. 82 53.5 3.8 28.6984
25. MEMBER INCIDENCES
26. 1 7 4; 2 9 6; 3 10 2; 4 12 5; 5 13 14; 6 16 15; 7 17 18; 8 20 19; 9 23 22
27. 10 24 21; 11 27 26; 12 28 25; 13 31 30; 14 32 29; 15 35 34; 16 36 33; 17 39 38
28. 18 40 37; 19 44 41; 20 47 46; 21 48 45; 22 52 50; 23 53 54; 24 55 56; 25 57 58
29. 26 61 62; 27 63 64; 28 65 66; 29 67 68; 30 69 70; 31 71 72; 32 6 74; 33 2 4
30. 34 18 19; 35 21 22; 36 25 26; 37 29 30; 38 33 34; 39 37 38; 40 41 42; 41 45 49
31. 42 3 1; 43 72 70; 44 56 54; 45 75 76; 47 62 64; 48 66 68; 49 74 73; 50 1 77
32. 51 3 78; 52 5 73; 53 5 6; 54 15 19; 55 14 18; 56 18 21; 57 19 22; 58 21 25
33. 59 22 26; 60 25 29; 61 26 30; 62 29 33; 63 30 34; 64 33 37; 65 34 38; 66 37 41
34. 67 38 42; 68 41 45; 69 42 46; 70 49 50; 71 46 50; 72 6 14; 73 15 74; 74 73 1
35. 75 74 3; 76 72 45; 77 56 72; 78 70 49; 79 54 70; 80 76 54; 81 8 3; 82 11 1
36. 83 43 42; 84 51 49; 85 59 60; 86 60 76; 87 77 2; 88 78 4; 89 77 78; 90 14 15
37. 91 45 46; 92 56 75; 93 75 58; 94 68 80; 95 80 64; 96 64 82; 97 82 60; 98 66 79
38. 99 79 62; 100 62 81; 101 81 58; 102 81 82; 103 79 80; 104 45 50; 105 46 49
39. 106 77 4; 107 2 78; 108 78 1; 109 77 3; 110 6 8; 111 3 9; 112 5 11; 113 1 12
40. 114 50 47; 115 46 52; 116 49 48; 117 45 51; 122 18 13; 123 14 17; 124 19 16
41. 125 15 20; 126 25 24; 127 21 28; 128 26 23; 129 22 27; 130 33 32; 131 29 36
42. 132 34 31; 133 30 35; 134 41 40; 135 37 44; 136 42 39; 137 38 43; 138 66 61
43. 139 62 65; 140 68 63; 141 64 67; 142 58 55; 143 56 57; 146 56 71; 147 72 55
44. 148 54 69; 149 70 53; 150 58 60; 151 60 53; 152 54 59
45. DEFINE MATERIAL START
46. ISOTROPIC STEEL
47. E 2.05E+008
48. POISSON 0.3
49. DENSITY 76.8195
50. ALPHA 1.2E-005
51. DAMP 0.03
52. END DEFINE MATERIAL
53. MEMBER PROPERTY JAPANESE
54. 5 TO 31 34 TO 41 43 TO 45 47 48 54 TO 73 76 TO 80 83 TO 86 90 TO 103 -
55. 150 TABLE ST H200X200X8
56. 104 TO 117 122 TO 143 146 TO 149 151 152 TABLE ST C100X50X5
57. 1 TO 4 32 33 42 49 TO 53 74 75 81 82 87 TO 89 TABLE ST H250X250X9
58. CONSTANTS
59. BETA 90 MEMB 5 TO 19 83 104 TO 109
60. MATERIAL STEEL ALL
61. SUPPORTS
62. 7 8 10 11 13 16 17 20 23 24 27 28 31 32 35 36 39 40 43 44 47 48 51 TO 53 55 -
63. 57 59 61 63 65 67 69 71 PINNED
64. 9 12 FIXED BUT MX MZ KMY 0.001
```

```
66. 32 45 49 TO 69 71 TO 73 76 TO 79 86 92 94 96 98 100 102 103 START MY MZ
67. 45 49 53 TO 69 71 TO 80 87 88 93 95 97 99 101 TO 103 END MY MZ
68. 89 START MY MZ
69. 89 END MY MZ
70. MEMBER TENSION
71. 104 TO 117 122 TO 143 146 TO 149 151 152
72. LOAD 1 LOADTYPE NONE TITLE DL
73. MEMBER LOAD
74. 33 UNI GY -6.58
75. 42 49 89 UNI GY -10.65
76. 32 UNI GY -9.47
77. 34 TO 40 90 91 UNI GY -14.2
78. 41 UNI GY -10.01
79. 43 TO 45 47 48 102 103 UNI GY -10.69
80. SELFWEIGHT Y -1
81. LOAD 2 LOADTYPE NONE TITLE FL
82. MEMBER LOAD
83. 33 UNI GZ -1.22
84. 42 49 89 UNI GZ -1.98
85. 32 UNI GX -1.76
86. 34 TO 40 90 91 UNI GX -2.64
87. 41 UNI GZ -1.86
88. 43 TO 45 47 48 102 103 UNI GZ -2.04
89. LOAD 3 LOADTYPE NONE TITLE WLX
90. MEMBER LOAD
91. 1 TO 40 42 50 TO 52 70 74 TO 101 UNI GX -0.21
92. 110 TO 113 138 TO 143 146 TO 149 151 152 UNI GX -0.13
93. LOAD 4 LOADTYPE NONE TITLE WLZ
94. MEMBER LOAD
95. 1 TO 31 33 41 TO 45 47 TO 49 53 TO 69 71 TO 73 81 TO 85 89 102 103 -
96. 150 UNI GZ -0.21
97. 114 TO 117 122 TO 137 UNI GZ -0.13
98. LOAD 5 LOADTYPE NONE TITLE NLX
99. SELFWEIGHT X -0.015
100. MEMBER LOAD
101. 33 UNI GX -0.1
102. 42 49 89 UNI GX -0.16
103. 32 UNI GX -0.14
104. 34 TO 40 90 91 UNI GX -0.21
105. 41 UNI GX -0.15
106. 43 TO 45 47 48 102 103 UNI GX -0.16
107. LOAD 6 LOADTYPE NONE TITLE NLZ
108. SELFWEIGHT Z -0.015
109. MEMBER LOAD
110. 33 UNI GZ -0.1
111. 42 49 89 UNI GZ -0.16
112. 32 UNI GZ -0.14
113. 34 TO 40 90 91 UNI GZ -0.21
114. 41 UNI GZ -0.15
115. 43 TO 45 47 48 102 103 UNI GZ -0.16
116. LOAD COMB 7 1.0DL+1.0FL
117. 1 1.0 2 1.0
118. LOAD COMB 8 1.0DL+1.0FL+1.0WLX
119. 1 1.0 2 1.0 3 1.0
120. LOAD COMB 9 1.0DL+1.0FL+1.0WLZ
121. 1 1.0 2 1.0 4 1.0
122. LOAD COMB 10 1.0DL+1.0FL+1.0NLX
123. 1 1.0 2 1.0 5 1.0
124. LOAD COMB 11 1.0DL+1.0FL+1.0NLZ
125. 1 1.0 2 1.0 6 1.0
126. LOAD COMB 12 1.0DL+1.4FL
127. 1 1.0 2 1.4
128. LOAD COMB 13 1.4DL+1.4FL
129. 1 1.4 2 1.4
130. LOAD COMB 14 1.0DL+1.4FL+1.4WLX
131. 1 1.0 2 1.4 3 1.4
132. LOAD COMB 15 1.0DL+1.4FL+1.4WLZ
133. 1 1.0 2 1.4 4 1.4
134. LOAD COMB 16 1.0DL+1.4FL+1.4NLX
135. 1 1.0 2 1.4 5 1.4
136. LOAD COMB 17 1.0DL+1.4FL+1.4NLZ
137. 1 1.0 2 1.4 6 1.4
138. PERFORM ANALYSIS
```

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 82/ 145/ 36
TOTAL PRIMARY LOAD CASES = 6, TOTAL DEGREES OF FREEDOM = 384
SIZE OF STIFFNESS MATRIX = 3 DOUBLE KILO-WORDS

Friday, December 02, 2011, 01:27 PM

Friday, December 02, 2011, 01:27 PM

REQRD/AVAIL. DISK SPACE = 12.3/ 52913.9 MB

**START ITERATION NO. 2
 **START ITERATION NO. 3
 **START ITERATION NO. 4
 **START ITERATION NO. 5

**NOTE-Tension/Compression converged after 5 iterations, Case= 1

**START ITERATION NO. 2

**NOTE-Tension/Compression converged after 2 iterations, Case= 2

**START ITERATION NO. 2
 **START ITERATION NO. 3
 **START ITERATION NO. 4

**NOTE-Tension/Compression converged after 4 iterations, Case= 3

**START ITERATION NO. 2

**NOTE-Tension/Compression converged after 2 iterations, Case= 4

**START ITERATION NO. 2
 **START ITERATION NO. 3
 **START ITERATION NO. 4

**NOTE-Tension/Compression converged after 4 iterations, Case= 5

**START ITERATION NO. 2
 **START ITERATION NO. 3

**NOTE-Tension/Compression converged after 3 iterations, Case= 6

139. LOAD LIST 7 TO 11
 140. PRINT JOINT DISPLACEMENTS ALL

JOINT DISPLACEMENT (CM RADIANS) STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
1	7	-0.0146	-0.0113	-0.0582	-0.0002	0.0003	-0.0003
	8	-0.0768	-0.0115	-0.0431	-0.0001	0.0004	-0.0002
	9	-0.0132	-0.0119	-0.0710	-0.0001	0.0003	-0.0003
	10	-0.0291	-0.0114	-0.0554	-0.0001	0.0003	-0.0003
	11	-0.0139	-0.0116	-0.0639	-0.0002	0.0003	-0.0003
2	7	-0.0065	-0.0050	-0.0598	-0.0002	0.0002	-0.0002
	8	-0.1747	-0.0056	-0.0438	-0.0001	0.0003	0.0000
	9	-0.0083	-0.0050	-0.0730	-0.0001	0.0002	-0.0002
	10	-0.0405	-0.0051	-0.0568	-0.0001	0.0002	-0.0001
	11	-0.0086	-0.0050	-0.0657	-0.0002	0.0002	-0.0002
3	7	-0.0147	-0.0133	-0.0560	-0.0001	-0.0003	0.0003
	8	-0.0771	-0.0137	-0.0702	-0.0002	-0.0002	0.0003
	9	-0.0134	-0.0139	-0.0699	-0.0001	-0.0003	0.0003
	10	-0.0292	-0.0133	-0.0586	-0.0002	-0.0003	0.0003
	11	-0.0141	-0.0136	-0.0627	-0.0002	-0.0003	0.0003
4	7	-0.0066	-0.0049	-0.0574	-0.0002	-0.0002	0.0002
	8	-0.1749	-0.0043	-0.0714	-0.0002	-0.0001	0.0003
	9	-0.0084	-0.0049	-0.0716	-0.0001	-0.0002	0.0002
	10	-0.0407	-0.0048	-0.0599	-0.0002	-0.0002	0.0002
	11	-0.0087	-0.0049	-0.0642	-0.0002	-0.0002	0.0002
5	7	-0.0389	-0.0017	-0.0584	-0.0002	0.0000	0.0001
	8	-0.0459	-0.0023	-0.0439	-0.0001	0.0000	0.0001
	9	-0.0389	-0.0017	-0.0714	-0.0001	0.0000	0.0001
	10	-0.0421	-0.0018	-0.0557	-0.0001	0.0000	0.0001

11	-0.0389	-0.0017	-0.0641	-0.0002	0.0000	0.0001
6	7	-0.0389	-0.0054	-0.0561	-0.0001	0.0000
	8	-0.0458	-0.0054	-0.0704	-0.0002	0.0000
	9	-0.0388	-0.0054	-0.0703	-0.0001	0.0000
	10	-0.0421	-0.0054	-0.0587	-0.0002	0.0000
	11	-0.0389	-0.0054	-0.0629	-0.0002	0.0000
7	7	0.0000	0.0000	0.0000	-0.0002	-0.0001
	8	0.0000	0.0000	0.0000	-0.0002	-0.0001
	9	0.0000	0.0000	0.0000	-0.0003	-0.0002
	10	0.0000	0.0000	0.0000	-0.0002	-0.0002
	11	0.0000	0.0000	0.0000	-0.0002	-0.0002
8	7	0.0000	0.0000	0.0000	-0.0001	-0.0003
	8	0.0000	0.0000	0.0000	-0.0002	-0.0002
	9	0.0000	0.0000	0.0000	-0.0002	-0.0003
	10	0.0000	0.0000	0.0000	-0.0002	-0.0003
	11	0.0000	0.0000	0.0000	-0.0002	-0.0003
9	7	0.0000	0.0000	0.0000	-0.0001	0.0000
	8	0.0000	0.0000	0.0000	-0.0002	0.0000
	9	0.0000	0.0000	0.0000	-0.0002	0.0000
	10	0.0000	0.0000	0.0000	-0.0002	0.0000
	11	0.0000	0.0000	0.0000	-0.0002	0.0000
10	7	0.0000	0.0000	0.0000	-0.0002	0.0002
	8	0.0000	0.0000	0.0000	-0.0001	0.0003
	9	0.0000	0.0000	0.0000	-0.0003	0.0002

JOINT DISPLACEMENT (CM RADIANS) STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
10	0.0000	0.0000	0.0000	-0.0001	0.0002	0.0002	
11	11	0.0000	0.0000	0.0000	-0.0002	0.0002	
	7	0.0000	0.0000	0.0000	-0.0002	0.0003	
	8	0.0000	0.0000	0.0000	-0.0001	0.0004	
	9	0.0000	0.0000	0.0000	-0.0003	0.0003	
	10	0.0000	0.0000	0.0000	-0.0001	0.0003	
	11	0.0000	0.0000	0.0000	-0.0002	0.0003	
12	7	0.0000	0.0000	0.0000	-0.0002	0.0000	
	8	0.0000	0.0000	0.0000	-0.0001	0.0000	
	9	0.0000	0.0000	0.0000	-0.0003	0.0000	
	10	0.0000	0.0000	0.0000	-0.0001	0.0000	
	11	0.0000	0.0000	0.0000	-0.0002	0.0000	
13	7	0.0000	0.0000	0.0000	0.0004	0.0009	
	8	0.0000	0.0000	0.0000	0.0004	0.0010	
	9	0.0000	0.0000	0.0000	-0.0014	0.0009	
	10	0.0000	0.0000	0.0000	0.0004	0.0010	
	11	0.0000	0.0000	0.0000	0.0000	0.0009	
14	7	-0.0385	-0.0089	0.0000	-0.0008	0.0009	
	8	-0.0453	-0.0092	-0.0006	-0.0008	0.0010	
	9	-0.0384	-0.0076	-0.4884	-0.0012	0.0009	
	10	-0.0416	-0.0090	-0.0002	-0.0008	0.0010	
	11	-0.0385	-0.0086	-0.1039	-0.0009	0.0009	
15	7	-0.0330	-0.0088	0.0004	0.0008	-0.0009	
	8	-0.0501	-0.0096	-0.0002	0.0008	-0.0010	
	9	-0.0320	-0.0101	-0.4880	0.0004	-0.0009	
	10	-0.0391	-0.0091	0.0002	0.0008	-0.0010	
	11	-0.0327	-0.0091	-0.1036	0.0007	-0.0009	
16	7	0.0000	0.0000	0.0000	-0.0004	-0.0009	
	8	0.0000	0.0000	0.0000	-0.0004	-0.0010	
	9	0.0000	0.0000	0.0000	-0.0021	-0.0009	
	10	0.0000	0.0000	0.0000	-0.0004	-0.0010	
	11	0.0000	0.0000	0.0000	-0.0007	-0.0009	
17	7	0.0000	0.0000	0.0000	0.0004	0.0009	
	8	0.0000	0.0000	0.0000	0.0004	0.0010	
	9	0.0000	0.0000	0.0000	-0.0018	0.0009	
	10	0.0000	0.0000	0.0000	0.0004	0.0010	
	11	0.0000	0.0000	0.0000	0.0000	0.0009	
18	7	-0.0391	-0.0076	-0.0002	-0.0008	0.0009	
	8	-0.0461	-0.0076	-0.0002	-0.0008	0.0010	
	9	-0.0391	-0.0061	-0.6046	-0.0013	0.0009	
	10	-0.0424	-0.0076	-0.0002	-0.0008	0.0010	
	11	-0.0391	-0.0074	-0.1082	-0.0009	0.0009	
19	7	-0.0338	-0.0076	0.0002	0.0008	-0.0009	
	8	-0.0492	-0.0076	0.0002	0.0008	-0.0010	
	9	-0.0329	-0.0092	-0.6043	0.0003	-0.0009	
	10	-0.0395	-0.0076	0.0002	0.0008	-0.0010	
	11	-0.0335	-0.0079	-0.1078	0.0007	-0.0009	
20	7	0.0000	0.0000	0.0000	-0.0004	-0.0009	