

Friday, December 02, 2011, 05:02 PM

PAGE NO. 1

```
*****
*
*      STAAD.Pro
*      Version 2007   Build 04
*      Proprietary Program of
*      Research Engineers, Intl.
*      Date=   DEC 2, 2011
*      Time=   17: 1:48
*
*      USER ID:
*****
```

```
1. STAAD SPACE DXF IMPORT OF PR301-PR308.DXF
INPUT FILE: 20111127 PR301-PR308 RF.STD
2. START JOB INFORMATION
3. ENGINEER DATE 25-OCT-11
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 0.000298 0 -51.2; 2 0.000298 0 -41.2; 3 0.000298 0 -28.2; 4 0.000298 0 -21.9
9. 5 0.000298 0 -15.8; 6 0.000298 0 -10.1; 7 0.000298 0 -4.5
10. 8 0.000298 0 -9.92E-005; 9 0.000298 5.2 -51.2; 10 0.000298 5.2 -46.2
11. 11 0.000298 5.2 -41.2; 12 0.000298 5.2 -34.7; 13 0.000298 5.2 -28.2
12. 14 0.000298 5.2 -21.9; 15 0.000298 5.2 -15.8; 16 0.000298 5.2 -10.1
13. 17 0.000298 5.2 -4.5; 18 0.000298 5.2 -9.92E-005; 19 0.000298 7.82 -51.2
14. 20 0.000298 7.82 -46.2; 21 0.000298 7.82 -41.2; 22 0.000298 7.82 -34.7
15. 23 0.000298 7.82 -28.2; 24 0.000298 7.82 -21.9; 25 0.000298 7.82 -15.8
16. 26 0.000298 7.82 -10.1; 27 0.000298 7.82 -4.5; 28 0.000298 7.82 -9.92E-005
17. 29 5 5.2 -51.2; 30 5 5.2 -46.2; 31 5 5.2 -41.2; 32 5 7.82 -51.2
18. 33 5 7.82 -46.2; 34 5 7.82 -41.2; 35 10 0 -51.2; 36 10 0 -41.2; 37 10 0 -28.2
19. 38 10 0 -21.9; 39 10 0 -15.8; 40 10 0 -10.1; 41 10 0 -4.5; 42 10 0 -9.92E-005
20. 43 10 5.2 -51.2; 44 10 5.2 -46.2; 45 10 5.2 -41.2; 46 10 5.2 -34.7
21. 47 10 5.2 -28.2; 48 10 5.2 -21.9; 49 10 5.2 -15.8; 50 10 5.2 -10.1
22. 51 10 5.2 -4.5; 52 10 5.2 -9.92E-005; 53 10 7.82 -51.2; 54 10 7.82 -46.2
23. 55 10 7.82 -41.2; 56 10 7.82 -34.7; 57 10 7.82 -28.2; 58 10 7.82 -21.9
24. 59 10 7.82 -15.8; 60 10 7.82 -10.1; 61 10 7.82 -4.5; 62 10 7.82 -9.92E-005
25. 63 5 7.82 -28.2; 64 5 7.82 -21.9; 65 5 5.2 -21.9; 66 5 5.2 -28.2
26. 67 5 5.2 -34.7; 68 5 7.82 -34.7; 69 0.000298 5.2 -38; 70 0.000298 7.82 -38
27. 71 0.000298 7.82 -31.5; 72 0.000298 5.2 -31.5; 73 10 7.82 -38; 74 10 5.2 -38
28. 75 10 7.82 -31.5; 76 10 5.2 -31.5
29. MEMBER INCIDENCES
30. 1 35 43; 2 1 9; 3 2 11; 4 37 47; 5 3 13; 6 4 14; 7 38 48; 8 5 15; 9 39 49
31. 10 6 16; 11 40 50; 12 7 17; 13 41 51; 14 8 18; 15 42 52; 16 43 53; 17 45 55
32. 18 9 19; 19 11 21; 20 47 57; 21 13 23; 22 14 24; 23 48 58; 24 15 25; 25 49 59
33. 26 16 26; 27 50 60; 28 17 27; 29 51 61; 30 18 28; 31 52 62; 32 19 32; 33 9 29
34. 34 13 66; 35 23 63; 36 24 64; 37 15 49; 38 25 59; 39 16 50; 40 26 60; 41 17 51
35. 42 27 61; 43 18 52; 44 28 62; 45 14 65; 46 22 68; 47 21 34; 48 12 67; 49 11 31
36. 50 45 44; 51 55 54; 52 11 10; 53 21 20; 54 23 71; 55 47 76; 56 57 75; 57 28 27
37. 58 62 61; 59 52 51; 60 18 17; 61 24 23; 62 14 13; 63 15 14; 64 25 24; 65 26 25
38. 66 16 15; 67 27 26; 68 17 16; 69 61 60; 70 51 50; 71 60 59; 72 50 49; 73 59 58
39. 74 49 48; 75 58 57; 76 48 47; 77 22 70; 78 46 74; 79 56 73; 80 12 69; 81 13 72
40. 82 44 43; 83 54 53; 84 10 9; 85 20 19; 86 20 33; 87 10 30; 88 31 45; 89 29 43
```

Friday, December 02, 2011, 05:02 PM

DXF IMPORT OF PR301-PR308.DXF -- PAGE NO. 2

```
41. 90 34 55; 91 32 53; 92 30 44; 93 33 54; 94 34 33; 95 33 32; 96 31 30; 97 30 29
42. 98 52 41; 99 51 42; 100 18 7; 101 17 8; 102 16 5; 103 15 6; 104 50 39
43. 105 49 40; 106 14 3; 107 13 4; 108 48 37; 109 47 38; 110 45 36; 111 45 35
44. 112 43 36; 113 11 1; 114 9 2; 115 63 57; 116 64 58; 117 65 48; 118 66 47
45. 119 66 65; 120 63 64; 121 63 24; 122 23 64; 123 57 64; 124 63 58; 125 66 14
46. 126 13 65; 127 47 65; 128 66 48; 173 67 46; 174 68 56; 175 63 68; 176 66 67
47. 177 68 34; 178 67 31; 179 22 12; 180 56 46; 181 69 11; 182 70 21; 183 71 22
48. 184 72 12; 185 73 55; 186 74 45; 187 75 56; 188 76 46; 189 70 69; 190 71 72
49. 191 73 74; 192 75 76; 193 55 74; 194 73 46; 195 75 46; 197 57 76; 197 21 69
50. 198 70 12; 199 71 12; 200 23 72; 201 21 68; 202 68 57; 203 55 68; 204 68 23
51. 205 45 67; 206 67 13; 207 11 67; 208 67 47; 209 19 33; 210 33 55; 211 53 33
52. 212 33 21; 213 43 30; 214 30 11; 215 9 30; 216 30 45
53. START USER TABLE
54. TABLE 1
55. UNIT METER KN
56. WIDE FLANGE
57. H428X407
58. 0.04997 0.428 0.06 0.407 0.035 0.00133238 0.000399722 3.74094E-005 -
59. 0.02568 0.02849
60. TABLE 2
61. UNIT METER KN
62. WIDE FLANGE
63. H428X407X65X50
64. 0.05095 0.448 0.04 0.407 0.045 0.00164638 0.000507553 3.23626E-005 -
65. 0.01792 0.03663
66. END
67. DEFINE MATERIAL START
68. ISOTROPIC STEEL
69. E 2.05E+008
70. POISSON 0.3
71. DENSITY 76.8195
72. ALPHA 1.2E-005
73. DAMP 0.03
74. END DEFINE MATERIAL
75. MEMBER PROPERTY JAPANESE
76. 98 TO 109 111 TO 114 121 TO 128 201 TO 216 TABLE ST C150X75X6.5
77. 34 51 TO 53 83 TO 85 118 TABLE ST H400X400X13
78. MEMBER PROPERTY JAPANESE
79. 35 TO 46 55 78 80 81 87 92 115 TO 117 174 181 184 186 188 TABLE ST H400X400X13
80. 4 TO 15 20 TO 31 54 56 77 79 182 183 185 187 TABLE ST H388X402X15
81. 57 TO 76 86 93 119 120 175 TO 178 TABLE ST H250X250X9
82. 1 TO 3 16 TO 19 110 TABLE ST H400X400X13
83. 179 180 189 TO 200 TABLE ST H150X150X7
84. 32 33 47 49 50 82 88 TO 91 94 TO 97 TABLE ST H900X300X16
85. 48 173 TABLE ST H414X405X18
86. CONSTANTS
87. BETA 90 MEMB 121 TO 128 201 TO 216
88. MATERIAL STEEL ALL
89. SUPPORTS
90. 1 TO 8 35 TO 42 PINNED
91. MEMBER RELEASE
92. 50 TO 53 57 TO 60 62 TO 76 94 96 175 TO 178 START MY MZ
93. 57 TO 76 82 TO 85 95 97 175 TO 178 END MY MZ
94. 86 START MY MZ
95. 86 END MY MZ
96. 93 START MY MZ
```

Friday, December 02, 2011, 05:02 PM

DXF IMPORT OF PR301-PR308.DXF

-- PAGE NO. 3

97. 93 END MY MZ
98. 87 START MY MZ
99. 92 END MY MZ
100. 46 START MY MZ
101. 174 END MY MZ
102. 48 START MY MZ
103. 173 END MY MZ
104. 119 120 START MY MZ
105. 119 120 END MY MZ
106. 61 START MY MZ
107. 181 END MY MZ
108. 186 END MY MZ
109. 182 END MY MZ
110. 185 END MY MZ
111. 81 START MY MZ
112. 55 START MY MZ
113. 54 START MY MZ
114. 56 START MY MZ
115. 87 END MY MZ
116. 92 START MY MZ
117. MEMBER TENSION
118. 98 TO 109 111 TO 114
119. MEMBER TENSION
120. 121 TO 128
121. MEMBER TENSION
122. 98 TO 109 111 TO 114 121 TO 128 201 TO 208
123. MEMBER TENSION
124. 111 TO 114 209 TO 216
125. MEMBER TRUSS
126. 179 180 189 TO 200
127. LOAD 1 LOADTYPE NONE TITLE DL
128. SELFWEIGHT Y -1
129. MEMBER LOAD
130. 49 87 88 92 UNI GY -44.78
131. 50 82 96 97 UNI GY -37.87
132. 34 37 39 41 43 45 48 117 118 173 UNI GY -43.81
133. 47 86 90 93 UNI GY -30.62
134. 51 83 94 95 UNI GY -27.45
135. 35 36 38 40 42 44 46 115 116 174 UNI GY -31.8
136. LOAD 2 LOADTYPE NONE TITLE FL
137. MEMBER LOAD
138. 49 87 88 92 UNI GZ -4.36
139. 50 82 96 97 UNI GX -3.63
140. 34 37 39 41 43 45 48 117 118 173 UNI GZ -4.24
141. 47 86 90 93 UNI GZ -2.18
142. 51 83 94 95 UNI GX -1.87
143. 35 36 38 40 42 44 46 115 116 174 UNI GZ -2.19
144. 34 CON GZ -87.5 4.99
145. 45 CON GZ -87.5 4.99
146. 36 CON GZ -87.5 4.99
147. 35 CON GZ -87.5 4.99
148. LOAD 3 LOADTYPE NONE TITLE WLX
149. MEMBER LOAD
150. 4 TO 31 UNI GX -0.35
151. 1 UNI GX -0.35 4.2 5.2
152. 1 UNI GX -0.35 0 4.2

Friday, December 02, 2011, 05:02 PM

DXF IMPORT OF PR301-PR308.DXF

-- PAGE NO. 4

153. 110 UNI GX -0.35 1 5.2
154. 110 UNI GX -0.35 0 1
155. 3 UNI GX -0.35 4.2 5.2
156. 3 UNI GX -0.35 0 4.2
157. 2 UNI GX -0.35 4.2 5.2
158. 2 UNI GX -0.35 0 4.2
159. 50 TO 85 94 TO 97 175 TO 178 181 TO 188 UNI GX -0.35
160. 98 TO 109 111 TO 114 UNI GX -0.13
161. LOAD 4 LOADTYPE NONE TITLE WLZ
162. MEMBER LOAD
163. 87 92 UNI GZ -0.21
164. 4 TO 49 86 88 TO 91 93 115 TO 118 173 174 UNI GZ -0.35
165. 1 UNI GZ -0.35 4.2 5.2
166. 1 UNI GZ -0.35 0 4.2
167. 110 UNI GZ -0.35 1 5.2
168. 110 UNI GZ -0.35 0 1
169. 3 UNI GZ -0.35 4.2 5.2
170. 3 UNI GZ -0.35 0 4.2
171. 2 UNI GZ -0.35 4.2 5.2
172. 2 UNI GZ -0.35 0 4.2
173. LOAD 5 LOADTYPE NONE TITLE NLX
174. SELFWEIGHT X -0.015
175. MEMBER LOAD
176. 49 87 88 92 UNI GX -0.67
177. 50 82 96 97 UNI GX -0.57
178. 34 37 39 41 43 45 48 117 118 173 UNI GX -0.66
179. 47 86 90 93 UNI GX -0.46
180. 51 83 94 95 UNI GX -0.41
181. 35 36 38 40 42 44 46 115 116 174 UNI GX -0.48
182. LOAD 6 LOADTYPE NONE TITLE NLZ
183. SELFWEIGHT Z -0.015
184. MEMBER LOAD
185. 49 87 88 92 UNI GZ -0.67
186. 50 82 96 97 UNI GZ -0.57
187. 34 37 39 41 43 45 48 117 118 173 UNI GZ -0.66
188. 47 86 90 93 UNI GZ -0.46
189. 51 83 94 95 UNI GZ -0.41
190. 35 36 38 40 42 44 46 115 116 174 UNI GZ -0.48
191. LOAD COMB 7 1.0DL+1.0FL
192. 1 1.0 2 1.0
193. LOAD COMB 8 1.0DL+1.0FL+1.0WLX
194. 1 1.0 2 1.0 3 1.0
195. LOAD COMB 9 1.0DL+1.0FL+1.0WLZ
196. 1 1.0 2 1.0 4 1.0
197. LOAD COMB 10 1.0DL+1.0FL+1.0NLX
198. 1 1.0 2 1.0 5 1.0
199. LOAD COMB 11 1.0DL+1.0FL+1.0NLZ
200. 1 1.0 2 1.0 6 1.0
201. LOAD COMB 12 1.0DL+1.4FL
202. 1 1.0 2 1.4
203. LOAD COMB 13 1.4DL+1.4FL
204. 1 1.4 2 1.4
205. LOAD COMB 14 1.0DL+1.4FL+1.4WLX
206. 1 1.0 2 1.4 3 1.4
207. LOAD COMB 15 1.0DL+1.4FL+1.4WLZ
208. 1 1.0 2 1.4 4 1.4

Friday, December 02, 2011, 05:02 PM

DXF IMPORT OF PR301-PR308.DXF

-- PAGE NO. 5

209. LOAD COMB 16 1.0DL+1.4FL+1.4NLX
210. 1 1.0 2 1.4 5 1.4
211. LOAD COMB 17 1.0DL+1.4FL+1.4NLZ
212. 1 1.0 2 1.4 6 1.4
213. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 76/ 172/ 16

SOLVER USED IS THE IN-CORE ADVANCED SOLVER

TOTAL PRIMARY LOAD CASES = 6, TOTAL DEGREES OF FREEDOM = 408

**START ITERATION NO. 2
**START ITERATION NO. 3
**START ITERATION NO. 4
**START ITERATION NO. 5

**NOTE-Tension/Compression converged after 5 iterations, Case= 1

**START ITERATION NO. 2
**START ITERATION NO. 3

**NOTE-Tension/Compression converged after 3 iterations, Case= 2

**START ITERATION NO. 2
**START ITERATION NO. 3
**START ITERATION NO. 4

**NOTE-Tension/Compression converged after 4 iterations, Case= 3

**START ITERATION NO. 2

**NOTE-Tension/Compression converged after 2 iterations, Case= 4

**START ITERATION NO. 2
**START ITERATION NO. 3
**START ITERATION NO. 4

**NOTE-Tension/Compression converged after 4 iterations, Case= 5

Friday, December 02, 2011, 05:02 PM

DXF IMPORT OF PR301-PR308.DXF

-- PAGE NO. 6

**START ITERATION NO. 2

**NOTE-Tension/Compression converged after 2 iterations, Case= 6

214. LOAD LIST 7 TO 11
215. PRINT JOINT DISPLACEMENTS ALL