

```
*****
*
*      STAAD.Pro
*      Version 2007   Build 04
*      Proprietary Program of
*      Research Engineers, Intl.
*      Date=   JAN 31, 2013
*      Time=   11:31:28
*
*      USER ID:
*****
```

```
1. STAAD SPACE
INPUT FILE: 20130131 T-Goal Post 003-005 FR.STD
2. START JOB INFORMATION
3. ENGINEER DATE 12-MAY-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 2 5 1 -5.73; 3 5 4.69 -4.93; 4 5 4.69 -5.73; 6 5 4.69 -6.53
9. MEMBER INCIDENCES
10. 1 4 3; 3 2 4; 5 6 4
11. DEFINE MATERIAL START
12. ISOTROPIC STEEL
13. E 2.05E+008
14. POISSON 0.3
15. DENSITY 76.8195
16. ALPHA 1.2E-005
17. DAMP 0.03
18. END DEFINE MATERIAL
19. MEMBER PROPERTY JAPANESE
20. 1 5 TABLE ST H428X407X20
21. 3 TABLE ST H428X407X20
22. CONSTANTS
23. BETA 90 MEMB 3
24. MATERIAL STEEL ALL
25. SUPPORTS
26. 2 FIXED
27. ***** DEAD LOAD *****
28. LOAD 1 LOADTYPE NONE TITLE DL
29. SELFWEIGHT Y -1
30. JOINT LOAD
31. 4 FY -177
32. ***** FRICTIONAL LOAD *****
33. LOAD 2 LOADTYPE NONE TITLE FL
34. JOINT LOAD
35. 4 FX -16
36. ***** WIND LOAD X-DIRECTION*****
37. LOAD 3 LOADTYPE NONE TITLE WLX
38. MEMBER LOAD
39. 1 5 UNI GX -0.364
40. 3 UNI GX -0.364
41. ***** WIND LOAD Z-DIRECTION*****
42. LOAD 4 LOADTYPE NONE TITLE WLZ
43. MEMBER LOAD
44. 3 UNI GZ -0.364
45. ***** NOTIONAL LOAD X-DIRECTION*****
46. LOAD 5 LOADTYPE NONE TITLE NLX
47. SELFWEIGHT X -0.015
48. JOINT LOAD
49. 4 FX -2.655
50. *****NOTIONAL LOAD Z-DIRECTION*****
51. LOAD 6 LOADTYPE NONE TITLE NLZ
52. SELFWEIGHT Z -0.015
53. JOINT LOAD
```

```
54. 4 FZ -2.655
55. ***** LOAD COMBINATION - SERVICE *****
56. LOAD COMB 7 1.0DL+1.0FL
57. 1 1.0 2 1.0
58. LOAD COMB 8 1.0DL+1.0FL+1.0WLX
59. 1 1.0 2 1.0 3 1.0
60. LOAD COMB 9 1.0DL+1.0FL+1.0WLX
61. 1 1.0 2 1.0 4 1.0
62. LOAD COMB 10 1.0DL+1.0FL+1.0NLX
63. 1 1.0 2 1.0 5 1.0
64. LOAD COMB 11 1.0DL+1.0FL+1.0NLZ
65. 1 1.0 2 1.0 6 1.0
66. ***** LOAD COMBINATION - ULTIMATE *****
67. LOAD COMB 12 1.0DL+1.4FL
68. 1 1.0 2 1.4
69. LOAD COMB 13 1.4DL+1.4FL
70. 1 1.4 2 1.4
71. LOAD COMB 14 1.0DL+1.4FL+1.4WLX
72. 1 1.0 2 1.4 3 1.4
73. LOAD COMB 15 1.0DL+1.4FL+1.4WLZ
74. 1 1.0 2 1.4 4 1.4
75. LOAD COMB 16 1.0DL+1.4FL+1.4NLX
76. 1 1.0 2 1.4 5 1.4
77. LOAD COMB 17 1.0DL+1.4FL+1.4NLZ
78. 1 1.0 2 1.4 6 1.4
79. PERFORM ANALYSIS
```

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER/ELEMENTS/SUPPORTS = 4/ 3/ 1

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 2/ 2/ 12 DOF
TOTAL PRIMARY LOAD CASES = 6, TOTAL DEGREES OF FREEDOM = 18
SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
REQD/AVAIL. DISK SPACE = 12.0/ 455903.6 MB

80. LOAD LIST 7 TO 11
81. PRINT JOINT DISPLACEMENTS ALL

JOINT DISPLACEMENT (CM RADIANS) STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
2	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
3	7	-0.3357	-0.0095	0.0000	0.0000	0.0000	0.0013
	8	-0.3580	-0.0095	0.0000	0.0000	0.0000	0.0014
	9	-0.3357	-0.0085	-0.0038	0.0000	0.0000	0.0013
	10	-0.3940	-0.0095	0.0000	0.0000	0.0000	0.0016
	11	-0.3357	-0.0033	-0.0206	-0.0001	0.0000	0.0013
4	7	-0.3357	-0.0093	0.0000	0.0000	0.0000	0.0013
	8	-0.3580	-0.0093	0.0000	0.0000	0.0000	0.0014
	9	-0.3357	-0.0093	-0.0038	0.0000	0.0000	0.0013
	10	-0.3940	-0.0093	0.0000	0.0000	0.0000	0.0016

6	7	-0.3357	-0.0095	0.0000	0.0000	0.0000	0.0013
	8	-0.3580	-0.0095	0.0000	0.0000	0.0000	0.0014
	9	-0.3357	-0.0105	-0.0038	0.0000	0.0000	0.0013
	10	-0.3940	-0.0095	0.0000	0.0000	0.0000	0.0016
	11	-0.3357	-0.0157	-0.0206	-0.0001	0.0000	0.0013

***** END OF LATEST ANALYSIS RESULT *****

82. PRINT SUPPORT REACTION ALL

SUPPORT REACTIONS -UNIT KN METE STRUCTURE TYPE = SPACE

JOINT	LOAD	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM Z
2	7	16.00	191.66	0.00	0.00	0.00	-59.04
	8	17.86	191.66	0.00	0.00	0.00	-63.54
	9	16.00	191.66	1.34	2.48	0.00	-59.04
	10	18.87	191.66	0.00	0.00	0.00	-69.37
	11	16.00	191.66	2.87	10.33	0.00	-59.04

***** END OF LATEST ANALYSIS RESULT *****

83. LOAD LIST 12 TO 17
84. PRINT MEMBER FORCES ALLMEMBER END FORCES STRUCTURE TYPE = SPACE

ALL UNITS ARE -- KN METE (LOCAL)

MEMBER	LOAD	JT	AXIAL	SHEAR-Y	SHEAR-Z	TORSION	MOM-Y	MOM-Z
1	12	4	0.00	2.22	0.00	0.00	0.00	0.89
		3	0.00	0.00	0.00	0.00	0.00	0.00
13	4	0.00	3.10	0.00	0.00	0.00	0.00	1.24
		3	0.00	0.00	0.00	0.00	0.00	0.00
14	4	0.00	2.22	-0.41	0.00	0.00	0.16	0.89
		3	0.00	0.00	0.00	0.00	0.00	0.00
15	4	0.00	2.22	0.00	0.00	0.00	0.00	0.89
		3	0.00	0.00	0.00	0.00	0.00	0.00
16	4	0.00	2.22	-0.05	0.00	0.02	0.89	0.89
		3	0.00	0.00	0.00	0.00	0.00	0.00
17	4	0.05	2.22	0.00	0.00	0.00	0.00	0.89
		3	0.00	0.00	0.00	0.00	0.00	0.00
3	12	2	191.66	0.00	22.40	0.00	-82.66	0.00
		4	-181.43	0.00	-22.40	0.00	0.00	0.00
13	2	268.32	0.00	22.40	0.00	-82.66	0.00	0.00
		4	-254.01	0.00	-22.40	0.00	0.00	0.00
14	2	191.66	0.00	25.00	0.00	-88.96	0.00	0.00
		4	-181.43	0.00	-23.22	0.00	0.00	0.00
15	2	191.66	1.88	22.40	0.00	-82.66	3.47	0.00
		4	-181.43	0.00	-22.40	0.00	0.00	0.00
16	2	191.66	0.00	26.42	0.00	-97.11	0.00	0.00
		4	-181.43	0.00	-26.21	0.00	0.00	0.00
17	2	191.66	4.02	22.40	0.00	-82.66	14.46	0.00
		4	-181.43	-3.81	-22.40	0.00	0.00	0.00

	4	0.00	2.22	0.00	0.00	0.00	-0.89
13	6	0.00	0.00	0.00	0.00	0.00	0.00
	4	0.00	3.10	0.00	0.00	0.00	-1.24
14	6	0.00	0.00	0.00	0.00	0.00	0.00
	4	0.00	2.22	-0.41	0.00	-0.16	-0.89
15	6	0.00	0.00	0.00	0.00	0.00	0.00
	4	0.00	2.22	0.00	0.00	0.00	-0.89
16	6	0.00	0.00	0.00	0.00	0.00	0.00
	4	0.00	2.22	-0.05	0.00	-0.02	-0.89
17	6	0.00	0.00	0.00	0.00	0.00	0.00
	4	0.05	2.22	0.00	0.00	0.00	-0.89

***** END OF LATEST ANALYSIS RESULT *****

85. LOAD LIST ALL
86. PARAMETER 1
87. CODE BS5950
88. BEAM 2 ALL
89. CHECK CODE ALLSTAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.12_5950-1_2000

ALL UNITS ARE - KN METE (UNLESS OTHERWISE NOTED)

MEMBER	TABLE	RESULT/ FX	CRITICAL COND/ MY	RATIO/ MZ	LOADING/ LOCATION
1 ST	H428X407X20	PASS	BS-4.2.3-(Y)	0.002	13
		0.00	0.00	1.24	0.00
3 ST	H428X407X20	PASS	ANNEX I.1	0.128	16
		191.66 C	97.11	0.00	-
5 ST	H428X407X20	PASS	BS-4.2.3-(Y)	0.002	13
		0.00	0.00	-1.24	0.80

***** END OF TABULATED RESULT OF DESIGN *****

90. FINISH

***** END OF THE STAAD.Pro RUN *****

**** DATE= JAN 31,2013 TIME= 11:31:29 ****

* For questions on STAAD.Pro, please contact *

* Research Engineers Offices at the following locations *

* Telephone Email *

* USA: +1 (714)974-2500 support@bentley.com *

* CANADA +1 (905)632-4771 detech@odandetech.com *

* UK +44(1454)207-000 support@bentley.com *

* NORWAY +47 67 57 21 30 staad@edr.no *

* SINGAPORE +65 6225-6158 support@bentley.com *

* INDIA +91(033)4006-2021 support@bentley.com *

* JAPAN +81(03)5952-6500 eng-eye@crc.co.jp *

* CHINA +86(411)8479-1166 support@bentley.com *

* THAILAND +66(0)2645-1018/19 support@bentley.com *

* * *