

DNF IMPORT OF TRANSFER_2F7.SK.DNF

97. 2C300X98X2.0
98. 3258 300 6 196 3 4.416E+007 6.5968E+006 100000 294408 68736 2136 1800 -
99. 9.29441E+006 68736 100000 300
100. TABLE 13
101. UNIT MMS KN
102. TUBE
103. SHS125X4.5-CF
104. 2120 125 125 4.5 5.06E+006 5.06E+006 8.04E+006 1125 750
105. TABLE 35
106. UNIT MMS KN
107. TUBE
108. RSH150X100X4.5-CF
109. 2120 150 110 4.5 6.58E+006 3.52E+006 7.36E+006 900 900
110. END
111. MEMBER PROPERTY AMERICAN
112. 30 TO 49 OPTABLE 9 SHS75X3-CF
113. UNIT METER KN
114. MEMBER PROPERTY AMERICAN
115. 1 TO 29 OPTABLE 13 SHS125X4.5-CF
116. UNIT MMS KN
117. SUPPORTS
118. 14 FINNED
119. 1 13 26 FIXED BUT FX MX MY MZ
120. MEMBER TRUSS
121. 30 TO 49
122. UNIT METER KN
123. LOAD 1 LOADTYPE DEAD TITLE S/M
124. SELFWEIGHT Y -1
125. LOAD 2 LOADTYPE DEAD TITLE DL
126. JOINT LOAD
127. 4 FY -6.9
128. 7 10 FY -6.9
129. LOAD 3 LOADTYPE LIVE TITLE LL
130. JOINT LOAD
131. 4 FY -47.62
132. 7 10 FY -31
133. LOAD COMB 4 1.4DL + 1.5LL
134. 1 1.4 2 1.4 3 1.6
135. LOAD COMB 5 SERVICE
136. 1 1.0 2 1.0 3 1.0
137. PERFORM ANALYSIS

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER-ELEMENTS/SUPPORTS = 26/ 49/ 4

DNF IMPORT OF TRANSFER_2F7.SK.DNF

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER
ORIGINAL/FINAL BAND-WIDTH= 14/ 4/ 15 DOF
TOTAL PRIMARY LOAD CASES = 3, TOTAL DEGREES OF FREEDOM = 73
SIZE OF STIFFNESS MATRIX = 2 DOUBLE KILO-WORDS
REQD/AVAIL. DISK SPACE = 12.1/ 32865.3 MB

138. PARAMETER 1
139. CODE BSS950
140. CHECK CODE ALL

STRAID.FTO CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.10_5950-1_2000