

```

*****
*
*      STAAD.Pro
*      Version 2007   Build 04
*      Proprietary Program of
*      Research Engineers, Intl.
*      Date=   AUG 3, 2011
*      Time=   9:40:23
*
*      USER ID: RNS _ASSOCIATES
*****

```

```

1. STAAD SPACE
INPUT FILE: 20110803_Bracket support.STD
2. START JOB INFORMATION
3. ENGINEER DATE 25-JUL-11
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 7 0 0 0.59; 8 1 0 0.59; 9 0 -0.5 0.59; 10 0 -0.155 0.59; 11 0 -0.31 0.59
9. 12 0 -0.465 0.59
10. MEMBER INCIDENCES
11. 9 7 8; 10 8 9; 11 7 10; 12 10 11; 13 11 12; 14 12 9
12. START USER TABLE
13. TABLE 1
14. UNIT METER KN
15. ANGLE
16. L150X75X8
17. 0.15 0.075 0.008 0.0163126 0.0008 0.0004
18. END
19. DEFINE MATERIAL START
20. ISOTROPIC STEEL
21. E 2.05E+008
22. POISSON 0.3
23. DENSITY 76.8195
24. ALPHA 1.2E-005
25. DAMP 0.03
26. END DEFINE MATERIAL
27. MEMBER PROPERTY AMERICAN
28. 9 TO 14 UPTABLE 1 L150X75X8
29. CONSTANTS
30. BETA 75 MEMB 9 11 TO 14
31. MATERIAL STEEL ALL
32. MEMBER RELEASE
33. 10 START MY MZ
34. SUPPORTS
35. 7 10 11 PINNED
36. 12 FIXED BUT KMX 0.01 KMY 0.01 KMZ 0.01
37. LOAD 1 LOADTYPE NONE TITLE DEAD LOAD
38. SELFWEIGHT Y -1 LIST 9 TO 14
39. MEMBER LOAD
40. 9 UNI GY -0.12
41. 9 UNI GY -4.5 0 0.5
42. LOAD 2 LOADTYPE NONE TITLE LIVE LOAD
43. MEMBER LOAD
44. 9 UNI GY -1.94
45. LOAD COMB 3 1.0DL + 1.0LL
46. 1 1.0 2 1.0
47. LOAD COMB 4 2DL + 2LL
48. 1 2.0 2 2.0
49. PERFORM ANALYSIS

```

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 6/ 6/ 4

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 3/ 3/ 18 DOF
TOTAL PRIMARY LOAD CASES = 2, TOTAL DEGREES OF FREEDOM = 24
SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
REQRD/AVAIL. DISK SPACE = 12.0/ 995.5 MB