

```

*****
*
*          STAAD.Pro V8i SELECTseries5
*          Version  20.07.10.64
*          Proprietary Program of
*          Bentley Systems, Inc.
*          Date=    JAN  6, 2016
*          Time=    9:16:55
*
*          USER ID: GB
*****

```

```

1. STAAD SPACE
INPUT FILE: 160104 Rail Removing Gantry.STD
2. START JOB INFORMATION
3. ENGINEER DATE 15-SEP-14
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 -0.67 -0.1 -2.7; 2 -0.67 -0.1 -2.55; 3 -0.67 -0.1 0; 4 -0.67 -0.1 2.55
9. 5 -0.67 0.35 -2.55; 6 -0.67 0.35 0; 7 -0.67 0.35 2.55; 8 -0.67 1.35 -2.55
10. 9 -0.67 1.35 0; 10 -0.67 1.35 2.55; 11 -0.67 1.95 -2.55; 12 -0.67 1.95 0
11. 13 -0.67 1.95 2.55; 14 0.67 -0.1 -2.7; 15 0.67 -0.1 -2.55; 16 0.67 -0.1 0
12. 17 0.67 -0.1 2.55; 18 0.67 0.35 -2.55; 19 0.67 0.35 0; 20 0.67 0.35 2.55
13. 21 0.67 1.35 -2.55; 22 0.67 1.35 0; 23 0.67 1.35 2.55; 24 0.67 1.95 -2.55
14. 25 0.67 1.95 0; 26 0.67 1.95 2.55; 27 0 1.95 0; 28 0 1.95 2.55; 29 0 1.95 5.75
15. 30 -0.67 -0.1 -1.3; 31 0.67 -0.1 -1.3; 32 -0.67 -0.1 1.3; 33 0.67 -0.1 1.3
16. MEMBER INCIDENCES
17. 1 1 2; 2 2 30; 3 3 32; 4 14 15; 5 15 31; 6 16 33; 7 5 6; 8 6 7; 9 18 19
18. 10 19 20; 11 8 9; 12 9 10; 13 21 22; 14 22 23; 15 2 5; 16 5 8; 17 8 11; 18 3 6
19. 19 6 9; 20 9 12; 21 16 19; 22 19 22; 23 22 25; 24 4 7; 25 7 10; 26 10 13
20. 27 17 20; 28 20 23; 29 23 26; 30 15 18; 31 18 21; 32 21 24; 33 12 27; 34 27 25
21. 35 13 28; 36 28 26; 37 27 28; 38 28 29; 39 30 3; 40 31 16; 41 32 4; 42 33 17
22. 43 11 24; 44 8 6; 45 6 10; 46 21 19; 47 19 23
23. START USER TABLE
24. TABLE 1
25. UNIT METER KN
26. WIDE FLANGE
27. 250X125X55.5
28. 6870 250 10 125 19 7.14492E+007 6.20256E+006 642250 2500 3166.67 125 19
29. END
30. DEFINE MATERIAL START
31. ISOTROPIC STEEL
32. E 2.05E+008
33. POISSON 0.3
34. DENSITY 76.8195
35. ALPHA 1.2E-005
36. DAMP 0.03
37. TYPE STEEL
38. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2

```

STAAD SPACE

-- PAGE NO. 2

```

39. END DEFINE MATERIAL
40. MEMBER PROPERTY BRITISH
41. 44 TO 47 TABLE ST UA75X75X6
42. MEMBER PROPERTY AMERICAN
43. 37 38 TABLE ST W8X21
44. 1 TO 36 39 TO 43 TABLE ST W4X13
45. CONSTANTS
46. MATERIAL STEEL ALL
47. SUPPORTS
48. 30 TO 33 PINNED
49. MEMBER TRUSS
50. 44 TO 47
51. MEMBER TENSION
52. 44 TO 47
53. LOAD 1 LOADTYPE NONE TITLE DEAD LOAD
54. SELFWEIGHT Y -1
55. LOAD 2 LOADTYPE NONE TITLE POINT LOAD
56. JOINT LOAD
57. 29 FY -10
58. LOAD 10 LOADTYPE NONE TITLE 1.0 DL + 1.0 POINT LOAD
59. REPEAT LOAD
60. 1 1.0 2 1.0
61. LOAD 11 LOADTYPE NONE TITLE 1.4 DL + 1.6 POINT LOAD
62. REPEAT LOAD
63. 1 1.4 2 1.6
64. PERFORM ANALYSIS

```

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS	33	NUMBER OF MEMBERS	47
NUMBER OF PLATES	0	NUMBER OF SOLIDS	0
NUMBER OF SURFACES	0	NUMBER OF SUPPORTS	4

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

```

ORIGINAL/FINAL BAND-WIDTH= 29/ 5/ 36 DOF
TOTAL PRIMARY LOAD CASES = 4, TOTAL DEGREES OF FREEDOM = 186
TOTAL LOAD COMBINATION CASES = 0 SO FAR.
SIZE OF STIFFNESS MATRIX = 7 DOUBLE KILO-WORDS
REQRD/AVAIL. DISK SPACE = 12.2/ 66345.7 MB

```

**START ITERATION NO. 2

**NOTE-Tension/Compression converged after 2 iterations, Case= 1

**START ITERATION NO. 2