

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    MAR 26, 2013                  *
*          Time=    19:19:31                      *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L  *
*****

```

```

1. STAAD SPACE
INPUT FILE: Level 2.5m R5 Section.STD
2. START JOB INFORMATION
3. ENGINEER DATE 23-MAR-13
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 3 0 2.35 0; 4 2.132 2.35 0; 8 2.132 0 0.7; 9 2.132 2.35 0.7
9. MEMBER INCIDENCES
10. 2 3 4; 7 8 9; 9 4 9
11. START USER TABLE
12. TABLE 1
13. UNIT METER KN
14. WIDE FLANGE
15. UB250X125X29
16. 0.003642 0.25 0.006 0.125 0.009 3.89293E-005 2.93386E-006 7.7454E-008 -
17. 0.0015 0.00225
18. END
19. DEFINE MATERIAL START
20. ISOTROPIC STEEL
21. E 2.05E+008
22. POISSON 0.3
23. DENSITY 76.8195
24. ALPHA 1.2E-005
25. DAMP 0.03
26. TYPE STEEL
27. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
28. END DEFINE MATERIAL
29. MEMBER PROPERTY BRITISH
30. 2 7 9 UPTABLE 1 UB250X125X29
31. CONSTANTS
32. MATERIAL STEEL ALL
33. SUPPORTS
34. 3 8 FIXED
35. *MEMBER RELEASE
36. *2 START MPY 0.99 MPZ 0.99
37. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT
38. SELFWEIGHT Y -1 LIST ALL
39. LOAD 2 LOADTYPE LIVE TITLE LOAD CASE 2 LIVE LOAD ( PIPE FY )
40. MEMBER LOAD

```

STAAD SPACE

-- PAGE NO. 2

41. 2 CON GY -19.8 0.6
 42. 2 CON GY -11.5 1.6
 43. LOAD 3 LOADTYPE LIVE TITLE LOAD CASE 3 LIVE LOAD (PIPE FZ)
 44. MEMBER LOAD
 45. 2 CON GZ 3.31 0.6
 46. 2 CON GZ 1.92 1.6
 47. *LOAD 4 LOADTYPE NONE TITLE LOAD CASE 4 HNLZ
 48. *NOTIONAL LOAD
 49. *1 X 0.007 2 X 0.008
 50. LOAD COMB 5 COMBINATION LOAD CASE 4 1.0DL+1.0LL(FY)
 51. 1 1.0 2 1.0
 52. LOAD COMB 6 COMBINATION LOAD CASE 5 1.4DL+1.6LL(FY) +1.0LL(FZ)
 53. 1 1.4 2 1.6 3 1.0
 54. *LOAD COMB 7 COMBINATION LOAD CASE 7 1.4DL + 1.6LL (FY)+ 1.0HNLZ
 55. *1 1.4 2 1.6 4 1.0
 56. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 4/ 3/ 2

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 2/ 2/ 12 DOF
 TOTAL PRIMARY LOAD CASES = 3, TOTAL DEGREES OF FREEDOM = 12
 SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
 REQ'D/AVAIL. DISK SPACE = 12.0/ 0.0 MB

57. PARAMETER 2
 58. CODE BS5950
 59. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000