

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    DEC 11, 2012                  *
*          Time=    7:42:34                      *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L
*****

```

```

1. STAAD SPACE
INPUT FILE: 172-PF-02.STD
2. START JOB INFORMATION
3. ENGINEER DATE 12-NOV-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 0 0 0; 2 0 1.2 0; 3 0 0 0.7; 4 0 1.2 0.7; 5 3.34 0 0; 6 3.34 1.2 0
9. 7 3.34 0 0.7; 8 3.34 1.2 0.7; 9 6.7 0 0; 10 6.7 1.2 0; 11 6.7 0 0.7
10. 12 6.7 1.2 0.7; 13 8.12 0 0; 14 8.12 0 0.7; 15 0 1.2 -0.25; 16 3.34 1.2 -0.25
11. 17 6.7 1.2 -0.25; 18 0 1.2 0.95; 19 3.34 1.2 0.95; 20 6.7 1.2 0.95
12. 21 0 1.2 0.35; 22 3.34 1.2 0.35; 23 6.7 1.2 0.35
13. MEMBER INCIDENCES
14. 1 1 2; 2 3 4; 3 5 6; 4 7 8; 5 9 10; 6 11 12; 11 2 21; 12 6 22; 13 10 23
15. 14 13 10; 15 14 12; 16 15 2; 17 4 18; 18 16 6; 19 8 19; 20 17 10; 21 12 20
16. 22 15 16; 23 16 17; 24 18 19; 25 19 20; 26 21 4; 27 22 8; 28 23 12; 29 21 22
17. 30 22 23
18. DEFINE MATERIAL START
19. ISOTROPIC STEEL
20. E 2.05E+008
21. POISSON 0.3
22. DENSITY 76.8195
23. ALPHA 1.2E-005
24. DAMP 0.03
25. TYPE STEEL
26. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
27. END DEFINE MATERIAL
28. MEMBER PROPERTY BRITISH
29. 1 TO 6 11 TO 13 16 TO 30 TABLE ST UC152X152X23
30. 14 15 TABLE ST CH200X75X23
31. CONSTANTS
32. BETA 90 MEMB 1 TO 6
33. MATERIAL STEEL ALL
34. SUPPORTS
35. 1 3 5 7 9 11 13 14 PINNED
36. MEMBER RELEASE
37. 14 15 END MPY 0.99 MPZ 0.99
38. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT
39. SELFWEIGHT Y -1
40. LOAD 2 LOADTYPE DEAD TITLE LOAD CASE 2 SDL

```

STAAD SPACE

-- PAGE NO. 2

41. ONEWAY LOAD
 42. YRANGE 0 2 ONE -0.75 GY

****WARNING**** about Floor/OneWay Loads/Weights.

Please note that depending on the shape of the floor you may have to break up the FLOOR/ONEWAY LOAD into multiple commands. For details please refer to Technical Reference Manual Section 5.32.4 Note 6.

43. MEMBER LOAD
 44. 14 15 UNI GY -0.375
 45. LOAD 3 LOADTYPE LIVE TITLE LOAD CASE 3 LL
 46. ONEWAY LOAD
 47. YRANGE 0 2 ONE -5 GY
 48. MEMBER LOAD
 49. 14 15 UNI GY -2.5
 50. LOAD 4 LOADTYPE LIVE TITLE LOAD CASE 4 WL(X)
 51. JOINT LOAD
 52. 2 4 FX 1.36
 53. LOAD 5 LOADTYPE LIVE TITLE LOAD CASE 5 WL(Z)
 54. JOINT LOAD
 55. 15 TO 17 FZ 0.162
 56. LOAD COMB 6 COMBINATION LOAD CASE 6 1.0DL+1.0LL
 57. 1 1.0 2 1.0 3 1.0
 58. LOAD COMB 7 COMBINATION LOAD CASE 7 1.4DL+1.6LL+WL(X)
 59. 1 14.0 2 1.4 3 1.6 4 1.0
 60. LOAD COMB 8 COMBINATION LOAD CASE 8 1.0DL+1.4WL(X)
 61. 1 1.0 2 1.0 4 1.4
 62. LOAD COMB 9 COMBINATION LOAD CASE 9 1.2DL+1.2LL+1.2WL(X)
 63. 1 1.2 2 1.2 3 1.2 4 1.2
 64. LOAD COMB 10 COMBINATION LOAD CASE 10 1.4DL+1.6LL+WL(Z)
 65. 1 1.4 2 1.4 3 1.6 5 1.0
 66. LOAD COMB 11 COMBINATION LOAD CASE 11 1.0DL+1.4WL(Z)
 67. 1 1.0 2 1.0 5 1.4
 68. LOAD COMB 12 COMBINATION LOAD CASE 12 1.2DL+1.2LL+1.2WL(Z)
 69. 1 1.2 2 1.2 3 1.2 5 1.2
 70. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 23/ 26/ 8

STAAD SPACE

-- PAGE NO. 3

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 19/ 6/ 39 DOF
TOTAL PRIMARY LOAD CASES = 5, TOTAL DEGREES OF FREEDOM = 114
SIZE OF STIFFNESS MATRIX = 5 DOUBLE KILO-WORDS
REQRD/AVAIL. DISK SPACE = 12.1/ 268298.0 MB

71. PARAMETER 1
72. CODE BS5950
73. UNL 1.2 MEMB 11 TO 13 16 TO 21 26 TO 28
74. KY 1.5 MEMB 1 TO 6
75. KZ 1.5 MEMB 1 TO 6
76. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000