

```

*****
*
*          STAAD.Pro V8i SELECTseries3          *
*          Version  20.07.08.22                  *
*          Proprietary Program of                 *
*          Bentley Systems, Inc.                  *
*          Date=    JAN 30, 2013                  *
*          Time=    16:38:37                      *
*
*          USER ID: JCUBE ENGINEERING SERVICES PTE L
*****

```

```

1. STAAD SPACE
INPUT FILE: 199-PF-02.STD
2. START JOB INFORMATION
3. ENGINEER DATE 24-NOV-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 0 0 0; 3 1.85 1.55 0; 4 5.15 1.55 0; 5 7 0 0; 6 0 0 0.8; 7 1.85 1.55 0.8
9. 8 5.15 1.55 0.8; 9 7 0 0.8; 10 1.85 0 0; 11 5.15 0 0; 12 1.85 0 0.8
10. 13 5.15 0 0.8
11. MEMBER INCIDENCES
12. 2 1 3; 3 3 4; 4 5 4; 5 6 7; 6 7 8; 7 9 8; 8 10 3; 9 12 7; 10 11 4; 11 13 8
13. 12 3 7; 13 4 8
14. DEFINE MATERIAL START
15. ISOTROPIC STEEL
16. E 2.05E+008
17. POISSON 0.3
18. DENSITY 76.8195
19. ALPHA 1.2E-005
20. DAMP 0.03
21. TYPE STEEL
22. STRENGTH FY 253200 FU 407800 RY 1.5 RT 1.2
23. END DEFINE MATERIAL
24. MEMBER PROPERTY BRITISH
25. 3 6 8 TO 13 TABLE ST UC152X152X23
26. 2 4 5 7 TABLE ST CH200X75X23
27. CONSTANTS
28. BETA 90 MEMB 8 TO 11
29. MATERIAL STEEL ALL
30. MEMBER RELEASE
31. 2 4 5 7 END MPY 0.99 MPZ 0.99
32. SUPPORTS
33. 1 5 6 9 TO 13 PINNED
34. DEFINE WIND LOAD
35. TYPE 1 WIND 1
36. INT 0.337 HEIG 1.55
37. LOAD 1 LOADTYPE DEAD TITLE LOAD CASE 1 SELF WEIGHT
38. SELFWEIGHT Y -1
39. LOAD 2 LOADTYPE DEAD TITLE LOAD CASE 2 SDL
40. ONEWAY LOAD

```

STAAD SPACE

-- PAGE NO. 2

41. YRANGE 0 1.6 ONE -0.75 GY

****WARNING** about Floor/Oneway Loads/Weights.**

Please note that depending on the shape of the floor you may have to break up the FLOOR/ONEWAY LOAD into multiple commands. For details please refer to Technical Reference Manual Section 5.32.4 Note 6.

42. MEMBER LOAD

43. 2 4 5 7 UNI GY -0.3

44. LOAD 3 LOADTYPE LIVE REDUCIBLE TITLE LOAD CASE 3 LIVE LOAD

45. ONEWAY LOAD

46. YRANGE 0 1.6 ONE -5 GY

47. MEMBER LOAD

48. 2 4 5 7 UNI GY -1.6

49. LOAD 4 LOADTYPE WIND TITLE LOAD CASE 4 WIND LOAD X

50. WIND LOAD X 1 TYPE 1 XR 1.85 1.86 YR 0 1.55 OPEN

51. LOAD 5 LOADTYPE WIND TITLE LOAD CASE 5 WIND LOAD Z

52. WIND LOAD Z 1 TYPE 1 XR 0 7.8 YR 0 1.55 ZR 0 0.1 OPEN

53. LOAD 6 LOADTYPE NONE TITLE LOAD CASE 6 NOTIONAL LOAD X

54. NOTIONAL LOAD

55. 1 X 0.007 2 X 0.007 3 X 0.008

56. LOAD 7 LOADTYPE NONE TITLE LOAD CASE 7 NOTIONAL Z

57. NOTIONAL LOAD

58. 1 Z 0.007 2 Z 0.007 3 Z 0.008

59. LOAD COMB 8 COMBINATION LOAD CASE 8 1.0DL+1.0LL

60. 1 1.0 2 1.0 3 1.0

61. LOAD COMB 9 COMBINATION LOAD CASE 9 1.4DL+1.6LL

62. 1 1.4 2 1.4 3 1.6

63. LOAD COMB 10 COMBINATION LOAD CASE 10 1.4DL+1.6LL+1.0WLX

64. 1 1.4 2 1.4 3 1.6 4 1.0

65. LOAD COMB 11 COMBINATION LOAD CASE 11 1.4DL+1.6LL+1.0WLZ

66. 1 1.4 2 1.4 3 1.6 5 1.0

67. LOAD COMB 12 COMBINATION LOAD CASE 12 1.4DL+1.6LL+1.0NLX

68. 1 1.4 2 1.4 3 1.6 6 1.0

69. LOAD COMB 13 COMBINATION LOAD CASE 13 1.4DL+1.6LL+1.0NLZ

70. 1 1.4 2 1.4 3 1.6 7 1.0

71. LOAD COMB 14 COMBINATION LOAD CASE 14 1.0DL+1.4WLX

72. 1 1.0 2 1.0 4 1.4

73. LOAD COMB 15 COMBINATION LOAD CASE 15 1.0DL+1.4WLZ

74. 1 1.0 2 1.0 5 1.4

75. LOAD COMB 16 COMBINATION LOAD CASE 16 1.0DL+1.4NLX

76. 1 1.0 2 1.0 6 1.4

77. LOAD COMB 17 COMBINATION LOAD CASE 17 1.0DL+1.4NLZ

78. 1 1.0 2 1.0 7 1.4

STAAD SPACE

-- PAGE NO. 3

79. LOAD COMB 18 COMBINATION LOAD CASE 18 1.2DL+1.2LL+1.2WLX
 80. 1 1.2 2 1.2 3 1.2 4 1.2
 81. LOAD COMB 19 COMBINATION LOAD CASE 19 1.2DL+1.2LL+1.2WLZ
 82. 1 1.2 2 1.2 5 1.2
 83. LOAD COMB 20 COMBINATION LOAD CASE 20 1.2DL+1.2LL+1.2NLX
 84. 1 1.2 2 1.2 3 1.2 6 1.2
 85. LOAD COMB 21 COMBINATION LOAD CASE 21 1.2DL+1.2LL+1.2NLZ
 86. 1 1.2 2 1.2 3 1.2 7 1.2
 87. LOAD COMB 100 COMBINATION LOAD CASE 100 1.0SW+1.0SDL
 88. 1 1.0 2 1.0
 89. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 12/ 12/ 8

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 7/ 5/ 27 DOF
 TOTAL PRIMARY LOAD CASES = 7, TOTAL DEGREES OF FREEDOM = 48
 SIZE OF STIFFNESS MATRIX = 2 DOUBLE KILO-WORDS
 REQ'D/AVAIL. DISK SPACE = 12.0/ 202321.5 MB

90. PARAMETER 2
 91. CODE BS5950
 92. KY 1.5 MEMB 8 TO 11
 93. KZ 1.5 MEMB 8 TO 11
 94. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.13_5950-1_2000