

```
*****
*
*      STAAD.Pro
*      Version 2007   Build 04
*      Proprietary Program of
*      Research Engineers, Intl.
*      Date=   JAN 18, 2013
*      Time=    9: 7:53
*
*      USER ID:
*****
```

```
1. STAAD SPACE DXF IMPORT OF DRAWING2.DXF
INPUT FILE: 20121213 ST33 Platform A.FR.STD
2. START JOB INFORMATION
3. ENGINEER DATE 25-MAY-12
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT METER KN
7. JOINT COORDINATES
8. 1 12853.1 0 -27496.3; 2 12853.1 0 -27495.5; 11 12857.7 0 -27496.3
9. 12 12857.7 0 -27495.5; 15 12859.5 0 -27496.3; 16 12859.5 0 -27495.5
10. 24 12859.5 0 -27490.3; 25 12850.4 0 -27496.3; 26 12850.4 0 -27495.5
11. 27 12863 0 -27496.3; 28 12863 0 -27495.5; 29 12863 0 -27490.3
12. 30 12863 0 -27489.3; 31 12853.1 2 -27496.3; 32 12853.1 2 -27495.5
13. 33 12854 2 -27496.3; 34 12854.8 2 -27496.3; 35 12855.7 2 -27496.3
14. 36 12856.5 2 -27496.3; 37 12857.7 2 -27496.3; 38 12857.7 2 -27495.5
15. 39 12854 2 -27497; 40 12854.8 2 -27497; 41 12855.7 2 -27497
16. 42 12856.5 2 -27497; 43 12858.7 2.4 -27496.3; 44 12858.7 2.4 -27495.5
17. 45 12859.5 2.4 -27496.3; 46 12859.5 2.4 -27495.5; 47 12858.7 2.4 -27489.3
18. 48 12859.5 2.4 -27489.3; 49 12859.5 2.4 -27490.3; 50 12858.7 0 -27496.3
19. 51 12858.7 0 -27490.3; 52 12858.7 2.4 -27490.3; 53 12862.1 0 -27490.3
20. 54 12862.1 0.493 -27490.3; 55 12862.1 0.625304 -27490.3
21. 56 12862.1 0.493 -27489.3; 57 12862.1 0.625401 -27489.3; 58 12854 2 -27495.5
22. 59 12854.8 2 -27495.5; 60 12855.7 2 -27495.5; 61 12856.5 2 -27495.5
23. MEMBER INCIDENCES
24. 39 1 31; 40 2 32; 41 12 38; 42 11 37; 51 31 32; 52 37 38; 53 31 33; 54 33 34
25. 55 34 35; 56 35 36; 57 36 37; 58 32 58; 61 39 33; 62 40 34; 63 41 35; 64 42 36
26. 65 43 44; 66 45 46; 67 43 45; 68 44 46; 69 47 48; 70 47 52; 71 46 49; 72 49 48
27. 75 15 45; 76 16 46; 79 24 49; 80 25 31; 81 26 32; 82 27 45; 83 28 46; 84 29 55
28. 85 30 57; 86 37 43; 87 38 44; 88 50 43; 89 52 44; 90 52 49; 91 51 52; 92 55 49
29. 93 53 54; 94 54 55; 95 57 48; 96 54 56; 97 56 57; 98 58 59; 99 59 60
30. 100 60 61; 101 61 38; 102 33 58; 103 34 59; 104 35 60; 105 36 61
31. DEFINE MATERIAL START
32. ISOTROPIC STEEL
33. E 2.05E+008
34. POISSON 0.3
35. DENSITY 76.8195
36. ALPHA 1.2E-005
37. DAMP 0.03
38. END DEFINE MATERIAL
39. MEMBER PROPERTY JAPANESE
40. 39 TO 42 75 76 79 88 91 93 TABLE ST H200X200X8
41. 53 TO 58 67 TO 69 90 96 98 TO 101 TABLE ST H200X200X8
42. 51 52 65 66 70 TO 72 89 TABLE ST H200X200X8
43. 80 TO 87 92 95 TABLE ST C200X90X8
44. 94 97 TABLE ST C150X75X6.5
45. 61 TO 64 102 TO 105 TABLE ST C100X50X5
46. CONSTANTS
47. BETA 90 MEMB 75 76 79 88 91 93
48. BETA 180 MEMB 80 83 85 95
49. MATERIAL STEEL ALL
50. SUPPORTS
51. 15 16 24 TO 28 50 51 PINNED
52. 1 2 11 12 53 FIXED
53. MEMBER RELEASE
```

```
54. 80 TO 83 END MY MZ
55. 86 87 START MY MZ
56. 86 87 END MY MZ
57. 51 52 START MY MZ
58. 51 52 END MY MZ
59. 67 TO 69 90 START MY MZ
60. 67 TO 69 90 END MY MZ
61. 92 95 END MY MZ
62. ***** DEAD LOAD *****
63. MEMBER OFFSET
64. 61 TO 64 102 TO 105 START 0 0.15 0
65. 61 TO 64 102 TO 105 END 0 0.15 0
66. LOAD 1 LOADTYPE NONE TITLE DL
67. SELFWEIGHT Y -1 LIST 39 TO 42 51 TO 58 61 TO 72 75 76 79 TO 105
68. MEMBER LOAD
69. 102 TO 105 UNI GY -0.425
70. 61 TO 64 UNI GY -0.2
71. 65 66 70 TO 72 89 UNI GY -0.25
72. 51 UNI GY -0.225
73. 52 UNI GY -0.25
74. 80 TO 87 92 95 UNI GY -0.2
75. ***** LIVE LOAD *****
76. LOAD 2 LOADTYPE NONE TITLE LL
77. MEMBER LOAD
78. 102 TO 105 UNI GY -4.25
79. 61 TO 64 UNI GY -2
80. 65 66 70 TO 72 89 UNI GY -2.5
81. 51 UNI GY -2.25
82. 52 UNI GY -2.5
83. 80 TO 87 92 95 UNI GY -2.5
84. ***** WIND LOAD X-DIRECTION 1*****
85. LOAD 3 LOADTYPE NONE TITLE WLX1
86. MEMBER LOAD
87. 39 TO 42 75 76 79 88 91 UNI GX -0.17
88. 51 52 65 66 70 TO 72 89 UNI GX -0.17
89. 80 TO 85 92 95 UNI GX -0.0765
90. 61 TO 64 102 TO 105 UNI GX -0.085
91. ***** WIND LOAD X-DIRECTION 2*****
92. LOAD 4 LOADTYPE NONE TITLE WLX2
93. MEMBER LOAD
94. 39 TO 42 75 76 79 88 91 UNI GX 0.17
95. 51 52 65 66 70 TO 72 89 UNI GX 0.17
96. 80 TO 85 92 95 UNI GX 0.0765
97. 61 TO 64 102 TO 105 UNI GX 0.085
98. ***** WIND LOAD Z-DIRECTION 1*****
99. LOAD 5 LOADTYPE NONE TITLE WLZ1
100. MEMBER LOAD
101. 39 TO 42 75 76 79 88 91 UNI GZ -0.17
102. 53 TO 58 67 TO 69 90 98 TO 101 UNI GZ -0.17
103. 80 TO 85 92 95 UNI GZ -0.17
104. ***** WIND LOAD Z-DIRECTION 2*****
105. LOAD 6 LOADTYPE NONE TITLE WLZ2
106. MEMBER LOAD
107. 39 TO 42 75 76 79 88 91 UNI GZ 0.17
108. 53 TO 58 67 TO 69 90 98 TO 101 UNI GZ 0.17
109. 80 TO 85 92 95 UNI GZ 0.17
110. ***** NOTIONAL LOAD X-DIRECTION 1*****
111. LOAD 7 LOADTYPE NONE TITLE NLX1
112. SELFWEIGHT X -0.015 LIST 39 TO 42 51 TO 58 61 TO 72 75 76 79 TO 105
113. MEMBER LOAD
114. 102 TO 105 UNI GX -0.006375
115. 61 TO 64 UNI GX -0.003
116. 65 66 70 TO 72 89 UNI GX -0.00375
117. 51 UNI GX -0.003375
118. 52 UNI GX -0.00375
119. 80 TO 87 92 95 UNI GX -0.003
120. ***** NOTIONAL LOAD X-DIRECTION 2*****
121. LOAD 8 LOADTYPE NONE TITLE NLX2
122. SELFWEIGHT X 0.015 LIST 39 TO 42 51 TO 58 61 TO 72 75 76 79 TO 105
123. MEMBER LOAD
```

Friday, January 18, 2013, 09:16 AM

Friday, January 18, 2013, 09:16 AM

124. 102 TO 105 UNI GX 0.006375
125. 61 TO 64 UNI GX -0.003
126. 65 66 70 TO 72 89 UNI GX 0.00375
127. 51 UNI GX 0.003375
128. 52 UNI GX 0.00375
129. 80 TO 87 92 95 UNI GX 0.003
130. *****NOTIONAL LOAD Z-DIRECTION 1*****
131. LOAD 9 LOADTYPE NONE TITLE NLZ1
132. SELFWEIGHT Z -0.015 LIST 39 TO 42 51 TO 58 61 TO 72 75 76 79 TO 105
133. MEMBER LOAD
134. 102 TO 105 UNI GZ -0.006375
135. 61 TO 64 UNI GZ -0.003
136. 65 66 70 TO 72 89 UNI GZ -0.00375
137. 51 UNI GZ -0.003375
138. 52 UNI GZ -0.00375
139. 80 TO 87 92 95 UNI GZ -0.003
140. *****NOTIONAL LOAD Z-DIRECTION 2*****
141. LOAD 10 LOADTYPE NONE TITLE NLZ2
142. SELFWEIGHT Z 0.015 LIST 39 TO 42 51 TO 58 61 TO 72 75 76 79 TO 105
143. MEMBER LOAD
144. 102 TO 105 UNI GZ 0.006375
145. 61 TO 64 UNI GZ 0.003
146. 65 66 70 TO 72 89 UNI GZ 0.00375
147. 51 UNI GZ 0.003375
148. 52 UNI GZ 0.00375
149. 80 TO 87 92 95 UNI GZ 0.003
150. ***** LOAD COMBINATION - SERVICE *****
151. LOAD COMB 11 1.0DL+1.0LL
152. 1 1.0 2 1.0
153. LOAD COMB 12 1.0DL+1.0LL+1.0WLX1
154. 1 1.0 2 1.0 3 1.0
155. LOAD COMB 13 1.0DL+1.0LL+1.0WLX2
156. 1 1.0 2 1.0 4 1.0
157. LOAD COMB 14 1.0DL+1.0LL+1.0WLZ1
158. 1 1.0 2 1.0 5 1.0
159. LOAD COMB 15 1.0DL+1.0LL+1.0WLZ2
160. 1 1.0 2 1.0 6 1.0
161. LOAD COMB 16 1.0DL+1.0LL+1.0NLX1
162. 1 1.0 2 1.0 7 1.0
163. LOAD COMB 17 1.0DL+1.0LL+1.0NLX2
164. 1 1.0 2 1.0 8 1.0
165. LOAD COMB 18 1.0DL+1.0LL+1.0NLZ1
166. 1 1.0 2 1.0 9 1.0
167. LOAD COMB 19 1.0DL+1.0LL+1.0NLZ2
168. 1 1.0 2 1.0 10 1.0
169. ***** LOAD COMBINATION - ULTIMATE *****
170. LOAD COMB 20 1.4DL+1.6LL
171. 1 1.4 2 1.6
172. LOAD COMB 21 1.2DL+1.2LL+1.2WLX1
173. 1 1.2 2 1.2 3 1.2
174. LOAD COMB 22 1.2DL+1.2LL+1.2WLX2
175. 1 1.2 2 1.2 4 1.2
176. LOAD COMB 23 1.2DL+1.2LL+1.2WLZ1
177. 1 1.2 2 1.2 5 1.2
178. LOAD COMB 24 1.2DL+1.2LL+1.2WLZ2
179. 1 1.2 2 1.2 6 1.2
180. LOAD COMB 25 1.2DL+1.2LL+1.2NLX1
181. 1 1.2 2 1.2 7 1.2
182. LOAD COMB 26 1.2DL+1.2LL+1.2NLX2
183. 1 1.2 2 1.2 8 1.2
184. LOAD COMB 27 1.2DL+1.2LL+1.2NLZ1
185. 1 1.2 2 1.2 9 1.2
186. LOAD COMB 28 1.2DL+1.2LL+1.2NLZ2
187. 1 1.2 2 1.2 10 1.2
188. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 44/ 53/ 14

SOLVER USED IS THE IN-CORE ADVANCED SOLVER

TOTAL PRIMARY LOAD CASES = 10, TOTAL DEGREES OF FREEDOM = 207

189. LOAD LIST 7 TO 19
190. PRINT JOINT DISPLACEMENTS ALL

JOINT DISPLACEMENT (CM RADIANS) STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
1	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	12	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	13	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	14	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	15	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	16	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	17	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	18	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	19	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
2	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	12	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	13	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	14	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	15	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	16	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	17	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	18	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	19	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
11	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	12	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	13	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	14	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	15	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	16	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	17	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	18	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	19	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
12	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	12	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	13	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	14	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	15	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000