

```
*****
*
*          STAAD.Pro
*          Version 2007   Build 04
*          Proprietary Program of
*          Research Engineers, Intl.
*          Date=   MAY 31, 2012
*          Time=   17:41:49
*
*          USER ID: Parsons Brinckerhoff
*****
```

```
1. STAAD SPACE
INPUT FILE: 120531_ST34 PR 801-806.STD
2. START JOB INFORMATION
3. ENGINEER DATE 14-MAY-12
4. JOB NAME JRC PR801-PR806
5. END JOB INFORMATION
6. INPUT WIDTH 79
7. UNIT METER KN
8. JOINT COORDINATES
9. 1 37 0 -38.2; 2 37 0 -35.2; 3 37 0 -26.7; 4 37 0 -22.2; 5 37 2.5 -38.2
10. 6 37 2.5 -35.2; 7 37 2.5 -32.2; 8 37 2.5 -29.2; 9 37 2.5 -26.7
11. 10 37 2.5 -24.45; 11 37 2.5 -22.2; 12 37 6.5 -22.2; 13 37 6.5 -18.7
12. 14 37 6.5 -15.2; 15 37 6.5 -11.7; 16 40 0 -38.2; 17 40 0 -35.2; 18 40 0 -26.7
13. 19 40 0 -22.2; 20 40 2.5 -38.2; 21 40 2.5 -35.2; 22 40 2.5 -32.2
14. 23 40 2.5 -29.2; 24 40 2.5 -26.7; 25 40 2.5 -24.45; 26 40 2.5 -22.2
15. 27 40 5.2 -35.2; 28 40 5.2 -32.37; 29 40 5.2 -29.53; 30 40 5.2 -26.7
16. 31 40 5.2 -25; 32 40 6.5 -22.2; 33 40 6.5 -18.7; 34 40 6.5 -15.2
17. 35 40 6.5 -11.7; 36 40 7.82 -35.2; 37 40 7.82 -32.37; 38 40 7.82 -29.53
18. 39 40 7.82 -26.7; 40 40 7.82 -25; 41 42.5 2.5 -38.2; 42 42.5 2.5 -35.2
19. 43 42.5 2.5 -26.7; 44 42.5 5.2 -35.2; 45 42.5 5.2 -26.7; 46 42.5 7.82 -35.2
20. 47 42.5 7.82 -25; 48 45 0 -38.2; 49 45 0 -35.2; 50 45 0 -26.7; 51 45 2.5 -38.2
21. 52 45 2.5 -35.2; 53 45 2.5 -26.7; 54 45 5.2 -35.2; 55 45 5.2 -32.37
22. 56 45 5.2 -30.5; 57 45 5.2 -29.53; 58 45 5.2 -26.7; 59 45 5.2 -25
23. 60 45 7.82 -35.2; 61 45 7.82 -32.37; 62 45 7.82 -30.5; 63 45 7.82 -29.53
24. 64 45 7.82 -26.7; 65 45 7.82 -25; 66 48 2.5 -38.2; 67 48 2.5 -35.2
25. 68 51 0 -38.2; 69 51 0 -35.2; 70 51 0 -30.5; 71 51 2.5 -38.2; 72 51 2.5 -35.2
26. 73 51 4 -35.2; 74 51 4 -30.5; 75 51 5.2 -35.2; 76 51 5.2 -30.5
27. 77 51 6.5 -35.2; 78 51 6.5 -30.5; 79 51 7.82 -35.2; 80 51 7.82 -30.5
28. 81 51 9 -35.2; 82 51 9 -30.5; 83 54.5 2.5 -38.2; 84 54.5 2.5 -35.2
29. 85 58 2.5 -38.2; 86 58 2.5 -35.2; 87 61.5 0 -38.2; 88 61.5 0 -35.2
30. 89 61.5 0 -31.7; 90 61.5 2.5 -38.2; 91 61.5 2.5 -35.2; 92 61.5 2.5 -31.7
31. 93 61.5 6.5 -35.2; 94 61.5 6.5 -31.7; 95 61.5 6.5 -31; 96 63.5 2.5 -38.2
32. 97 63.5 2.5 -35.2; 98 63.5 2.5 -31.7; 99 65.5 0 -38.2; 100 65.5 0 -35.2
33. 101 65.5 0 -31.7; 102 65.5 2.5 -38.2; 103 65.5 2.5 -35.2; 104 65.5 2.5 -31.7
34. 105 65.5 6.5 -35.2; 106 65.5 6.5 -31.7; 107 69 0 -38.2; 108 69 0 -35.2
35. 109 69 2.5 -38.2; 110 69 2.5 -35.2
36. MEMBER INCIDENCES
37. 1000 1 5; 1001 2 6; 1002 3 9; 1003 4 11; 1004 11 12; 1005 16 20; 1006 17 21
38. 1007 18 24; 1008 19 26; 1009 21 27; 1010 24 30; 1011 26 32; 1012 27 36
39. 1013 31 40; 1014 48 51; 1015 49 52; 1016 50 53; 1017 52 54; 1018 53 58
40. 1019 54 60; 1020 59 65; 1021 68 71; 1022 69 72; 1023 70 74; 1024 72 73
```

```
41. 1025 73 75; 1026 74 76; 1027 75 77; 1028 76 78; 1029 77 79; 1030 78 80
42. 1031 79 81; 1032 80 82; 1033 87 90; 1034 88 91; 1035 89 92; 1036 91 93
43. 1037 92 94; 1038 99 102; 1039 100 103; 1040 101 104; 1041 103 105
44. 1042 104 106; 1043 107 109; 1044 108 110; 2000 5 20; 2001 6 21; 2002 7 22
45. 2003 8 23; 2004 9 24; 2005 11 26; 2006 12 32; 2007 13 33; 2008 14 34
46. 2009 20 41; 2010 21 42; 2011 24 43; 2012 44 27; 2013 45 30; 2014 46 36
47. 2015 47 40; 2016 55 28; 2017 57 29; 2018 59 31; 2019 61 37; 2020 63 38
48. 2021 64 39; 2022 41 51; 2023 42 52; 2024 43 53; 2025 54 44; 2026 58 45
49. 2027 60 46; 2028 65 47; 2029 51 66; 2030 52 67; 2031 54 75; 2032 56 76
50. 2033 60 79; 2034 62 80; 2035 66 71; 2036 67 72; 2037 71 83; 2038 72 84
51. 2039 83 85; 2040 84 86; 2041 85 90; 2042 86 91; 2043 90 96; 2044 91 97
52. 2045 92 98; 2046 93 105; 2047 94 106; 2048 96 102; 2049 97 103; 2050 98 104
53. 2051 102 109; 2052 103 110; 3000 5 6; 3001 6 7; 3002 7 8; 3003 8 9; 3004 9 10
54. 3005 10 11; 3006 12 13; 3007 13 14; 3008 14 15; 3009 20 21; 3010 21 22
55. 3011 22 23; 3012 23 24; 3013 24 25; 3014 25 26; 3015 27 28; 3016 28 29
56. 3017 29 30; 3018 30 31; 3019 32 33; 3020 33 34; 3021 34 35; 3022 36 37
57. 3023 37 38; 3024 38 39; 3025 40 39; 3026 51 52; 3027 54 55; 3028 55 56
58. 3029 56 57; 3030 57 58; 3031 58 59; 3032 60 61; 3033 61 62; 3034 62 63
59. 3035 63 64; 3036 64 65; 3037 66 67; 3038 71 72; 3039 73 74; 3040 77 78
60. 3041 81 82; 3042 83 84; 3043 85 86; 3044 90 91; 3045 93 94; 3046 94 95
61. 3047 102 103; 3048 105 106; 3049 109 110; 4000 3 10; 4001 4 10; 4002 18 25
62. 4003 19 25; 4004 16 41; 4005 17 42; 4006 21 44; 4007 24 45; 4008 27 46
63. 4009 31 47; 4010 48 41; 4011 49 42; 4012 52 44; 4013 53 45; 4014 54 46
64. 4015 59 47; 4016 87 96; 4017 88 97; 4018 89 98; 4019 99 96; 4020 100 97
65. 4021 101 98; 4022 7 21; 4023 7 23; 4024 9 23; 4025 32 13; 4026 34 13
66. 4027 34 15; 4028 83 72; 4029 83 86; 4030 90 86; 4031 54 28; 4032 28 57
67. 4033 57 30; 4034 30 59; 4035 60 37; 4036 37 63; 4037 63 39; 4038 39 65
68. 5000 3 24; 5001 18 9; 5002 19 11; 5003 4 26; 5004 26 12; 5005 11 32
69. 5006 91 105; 5007 103 93; 5008 92 106; 5009 104 94
70. DEFINE PMEMBER
71. 2037 2039 2041 PMEMBER 1
72. 3001 TO 3003 PMEMBER 2
73. 3010 TO 3012 PMEMBER 3
74. 3006 TO 3008 PMEMBER 4
75. 3019 TO 3021 PMEMBER 5
76. 3015 TO 3018 PMEMBER 6
77. 3027 TO 3031 PMEMBER 7
78. 3032 TO 3036 PMEMBER 8
79. 2038 2040 2042 PMEMBER 9
80. DEFINE MATERIAL START
81. ISOTROPIC STEEL
82. E 2.05E+008
83. POISSON 0.3
84. DENSITY 76.8195
85. ALPHA 1.2E-005
86. DAMP 0.03
87. END DEFINE MATERIAL
88. MEMBER PROPERTY JAPANESE
89. 1003 1004 1006 TO 1012 1015 TO 1019 1022 TO 1032 1034 TO 1037 1039 TO 1041 -
90. 1042 TABLE ST H350X350X12
91. 1000 TO 1002 1005 1013 1014 1020 1021 1033 1038 1043 1044 TABLE ST H300X300X10
92. 2001 TO 2008 TABLE ST H294X200X8
93. 2011 TO 2021 2024 TO 2028 2031 TO 2034 TABLE ST H250X250X9
94. 2000 2009 2010 2022 2023 2043 TO 2052 TABLE ST H300X150X6.5
95. 2029 2030 2035 TO 2042 TABLE ST H482X300X11
96. 3001 TO 3003 3006 TO 3008 3010 TO 3012 3019 TO 3021 TABLE ST H482X300X11
```

STAAD SPACE -- PAGE NO. 3

```
97. 3015 TO 3018 3022 TO 3025 3027 TO 3036 TABLE ST H582X300X12
98. 3039 TO 3041 3045 3046 3048 TABLE ST H350X350X12
99. 3000 3009 3026 3037 3038 3042 TO 3044 3047 3049 TABLE ST H294X200X8
100. 3004 3005 3013 3014 TABLE ST H300X150X6.5
101. 4000 TO 4021 TABLE ST H194X150X6
102. 4031 TO 4038 TABLE ST H200X200X8
103. 4022 TO 4030 TABLE ST L130X130X9
104. 5000 TO 5009 TABLE ST C150X75X6.5
105. CONSTANTS
106. BETA 90 MEMB 1003 TO 1044
107. MATERIAL STEEL ALL
108. SUPPORTS
109. 1 TO 4 16 TO 19 48 TO 50 68 TO 70 87 TO 89 99 TO 101 107 108 PINNED
110. 15 35 ENFORCED BUT FZ MX MY MZ
111. MEMBER RELEASE
112. 2005 2006 2028 2031 TO 2034 2045 TO 2047 3000 3001 3010 3013 4000 TO 4017 -
113. 4019 4020 4022 TO 4030 START MY MZ
114. 2005 2006 2018 2031 TO 2034 2046 2047 2050 3000 3012 3014 4000 TO 4029 -
115. 4030 END MY MZ
116. 2002 2003 2007 TO 2011 2016 TO 2021 2025 TO 2027 2029 2030 2037 2038 2043 -
117. 2044 2051 2052 3004 3006 3019 3037 3042 3043 4031 TO 4038 START MY MZ
118. 2002 2003 2007 2008 2012 TO 2017 2019 TO 2024 2035 2036 2041 2042 2048 2049 -
119. 2051 2052 3003 3005 3037 3042 3043 4031 4032 4034 TO 4036 4038 END MY MZ
120. 2000 END MY MZ
121. 2001 END MY MZ
122. MEMBER TENSION
123. 5000 TO 5009
124. LOAD 1 LOADTYPE NONE TITLE DL
125. SELFWEIGHT Y -1 LIST 1000 TO 1044 2000 TO 2052 3000 TO 3049 4000 TO 4038 5000 -
126. 5001 TO 5009
127. MEMBER LOAD
128. *PR 421-422 (SIDE BEAM)
129. *ROW GA-GB
130. *PR 422
131. *ROW HA-HB
132. *INTERMEDIATE BEAM
133. *ROW HA-HB
134. *INTERMEDIATE BEAM
135. *ROW HA-HB
136. *INTERMEDIATE BEAM
137. *ROW HA-HB
138. *PR 423
139. *ROW HA-HB
140. *PR 801
141. *ROW HF-HE
142. 3049 CON GY -33.7 0.785
143. 3049 UNI GY -17.22 0.785 3
144. *PR 802
145. *ROW HF-HE
146. 3044 CON GY -22.5 0.785
147. 3044 UNI GY -24.6 0.785 3
148. 3045 CON GY -126.3 1.957
149. 3045 CON GY -174.4 3.5
150. *PR 803
151. *ROW HF-HE
152. 3038 CON GY -22.5 0.785
```

STAAD SPACE -- PAGE NO. 4

25

```
153. 3038 UNI GY -21.32 0.785 3
154. 3039 CON GY -78.6 2.2
155. 3039 CON GY -78.6 3.2
156. 3040 CON GY -147.3 1.957
157. 3041 CON GY -78.6 1.2
158. 3041 CON GY -78.6 2.2
159. 3041 CON GY -78.6 3.2
160. 3041 CON GY -78.6 4.2
161. *PR 804
162. *ROW HF-HE
163. 3026 CON GY -22.5 0.785
164. 3026 UNI GY -22.96 0.785 3
165. 3027 CON GY -44.9 2.2
166. 3028 CON GY -44.9 0.37
167. 3028 CON GY -44.9 1.37
168. 3029 CON GY -44.9 0.500001
169. 3030 CON GY -44.9 0.5
170. 3030 CON GY -116.3 1.9
171. 3031 CON GY -44.9 0.775
172. 3032 CON GY -44.9 1.2
173. 3032 CON GY -44.9 2.2
174. 3033 CON GY -44.9 0.37
175. 3033 CON GY -44.9 1.37
176. 3034 CON GY -44.9 0.500001
177. 3035 CON GY -44.9 0.37
178. 3035 CON GY -44.9 1.37
179. 3036 CON GY -44.9 0.775
180. *INTERMEDIATE BEAMS
181. *ROW HF-HE
182. 3037 3042 3043 3047 CON GY -22.5 0.785
183. 3037 3042 3043 3047 UNI GY -24.6 0.785 3
184. *PR 805
185. *ROW HE-HF
186. 3009 UNI GY -34.44 0.785 3
187. 3009 CON GY -33.7 0.785
188. *PR 805
189. *ROW HA-HB
190. *PR 806
191. *ROW HA-HB
192. *PR 424
193. *ROW HA-HB
194. *HB, HC, HD, HE
195. 2001 2004 TO 2006 CON GY -33.7 0.785
196. 2001 2004 TO 2006 UNI GY -17.22 0.785 3
197. *INTERMEDIATE BEAMS
198. *ROW HB-HC, HD-HE
199. 2002 2003 2007 2008 CON GY -22.5 0.785
200. 2002 2003 2007 2008 UNI GY -22.96 0.785 3
201. LOAD 2 LOADTYPE NONE TITLE FL
202. *PR 421-422 (SIDE BEAM)
203. *ROW GA-GB
204. MEMBER LOAD
205. *PR 422
206. *ROW HA-HB
207. *INTERMEDIATE BEAM
208. *ROW HA-HB
```

STAAD SPACE -- PAGE NO. 5

```
209. *INTERMEDIATE BEAM
210. *ROW HA-HB
211. *INTERMEDIATE BEAM
212. *ROW HA-HB
213. *PR 423
214. *ROW HA-HB
215. *PR 801
216. *ROW HF-HE
217. 3049 CON GX -3.37 0.785
218. 3049 UNI GX -1.722 0.785 3
219. *PR 802
220. *ROW HF-HE
221. 3044 CON GX -5.232 0.785
222. 3044 UNI GX -2.46 0.785 3
223. 3045 CON GX -12.63 1.957
224. 3045 CON GX -17.44 3.5
225. *PR 803
226. *ROW HF-HE
227. 3038 CON GX -4.419 0.785
228. 3038 UNI GX -2.132 0.785 3
229. 3039 CON GX -7.86 2.2
230. 3039 CON GX -7.86 3.2
231. 3040 CON GX -14.73 1.957
232. 3041 CON GX -7.86 1.2
233. 3041 CON GX -7.86 2.2
234. 3041 CON GX -7.86 3.2
235. 3041 CON GX -7.86 4.2
236. *PR 804
237. *ROW HF-HE
238. 3026 CON GX -3.489 0.785
239. 3026 UNI GX -2.289 0.785 3
240. 3027 CON GX -4.49 2.2
241. 3028 CON GX -4.49 0.37
242. 3028 CON GX -4.49 1.37
243. 3029 CON GX -4.49 0.500001
244. 3030 CON GX -4.49 0.5
245. 3030 CON GX -11.63 1.9
246. 3031 CON GX -4.49 0.775
247. 3032 CON GX -4.49 1.2
248. 3032 CON GX -4.49 2.2
249. 3033 CON GX -4.49 0.37
250. 3033 CON GX -4.49 1.37
251. 3034 CON GX -4.49 0.500001
252. 3035 CON GX -4.49 0.37
253. 3035 CON GX -4.49 1.37
254. 3036 CON GX -4.49 0.775
255. *INTERMEDIATE BEAMS
256. *ROW HF-HE
257. 3037 3042 3043 3047 CON GX -5.232 0.785
258. 3037 3042 3043 3047 UNI GX -2.46 0.785 3
259. *PR 805
260. *ROW HE-HF
261. 3009 UNI GX -3.444 0.785 3
262. 3009 CON GX -3.37 0.785
263. *PR 805
264. *ROW HA-HB
```

STAAD SPACE -- PAGE NO. 6

26

```
265. *PR 806
266. *ROW HA-HB
267. *PR 424
268. *ROW HA-HB
269. *HB, HC, HD, HE
270. 2001 2004 TO 2006 CON GZ -3.37 0.785
271. 2001 2004 TO 2006 UNI GZ -1.722 0.785 3
272. *INTERMEDIATE BEAMS
273. *ROW HB-HC, HD-HE
274. 2002 2003 2007 2008 CON GZ -2.25 0.785
275. 2002 2003 2007 2008 UNI GZ -2.296 0.785 3
276. LOAD 3 LOADTYPE NONE TITLE WLX
277. MEMBER LOAD
278. 1000 TO 1002 1005 1014 1021 1033 1038 1039 1043 1044 3000 3004 3005 3009 3013 -
279. 3014 3026 3038 3044 3047 3049 UNI GX 0.4
280. 3001 TO 3003 3006 TO 3008 3010 TO 3012 3019 TO 3021 UNI GX 0.65
281. 1004 1009 TO 1013 1017 TO 1020 1024 TO 1032 1036 1037 1041 1042 3039 TO 3041 -
282. 3045 3046 3048 UNI GX 0.55
283. 4000 TO 4003 UNI GX 0.26
284. 1003 1006 TO 1008 1015 1016 1022 1023 1034 1035 1040 UNI GX 0.47
285. 3015 TO 3018 3022 TO 3025 3027 TO 3036 UNI GX 0.9
286. JOINT LOAD
287. 6 TO 10 12 TO 14 FX 1.3
288. LOAD 4 LOADTYPE NONE TITLE WLZ
289. MEMBER LOAD
290. 1000 TO 1003 1005 TO 1008 1014 TO 1016 1021 1033 1038 1043 1044 2000 2001 -
291. 2004 TO 2006 2009 TO 2015 2022 TO 2028 2031 TO 2034 2043 TO 2051 -
292. 2052 UNI GZ 0.4
293. 2029 2030 2035 TO 2042 UNI GZ 0.65
294. 1022 1023 1034 1035 1039 1040 UNI GZ 0.47
295. 4004 4005 4010 4011 4016 TO 4021 UNI GZ 0.26
296. 1004 1009 TO 1013 1017 TO 1020 1024 TO 1032 1036 1037 1041 1042 UNI GZ 0.55
297. 4006 TO 4009 4012 TO 4015 UNI GZ 0.3
298. 5004 TO 5009 UNI GZ 0.24
299. JOINT LOAD
300. 5 20 41 51 66 71 83 85 90 102 109 FZ 1.3
301. 93 FZ 8.7
302. 81 FZ 4.9
303. 73 77 FZ 4.2
304. 54 60 FZ 8.8
305. LOAD 5 LOADTYPE NONE TITLE NLX
306. SELFWEIGHT X -0.015 LIST 1000 TO 1044 2000 TO 2052 3000 TO 3049 4000 TO 4038 -
307. 5002 TO 5009
308. MEMBER LOAD
309. *PR 421-422 (SIDE BEAM)
310. *ROW GA-GB
311. *PR 422
312. *ROW HA-HB
313. *INTERMEDIATE BEAM
314. *ROW HA-HB
315. *INTERMEDIATE BEAM
316. *ROW HA-HB
317. *INTERMEDIATE BEAM
318. *ROW HA-HB
319. *PR 423
320. *ROW HA-HB
```

STAAD SPACE -- PAGE NO. 7

321. \*PR 801  
322. \*ROW HF-HE  
323. 3049 CON GX -0.5 0.785  
324. 3049 UNI GX -0.3 0.785 3  
325. \*PR 802  
326. \*ROW HF-HE  
327. 3044 CON GX -0.3 0.785  
328. 3044 UNI GX -0.4 0.785 3  
329. 3045 CON GX -1.6 1.957  
330. 3045 CON GX -2.6 3.5  
331. \*PR 803  
332. \*ROW HF-HE  
333. 3038 CON GX -0.3 0.785  
334. 3038 UNI GX -0.3 0.785 3  
335. 3039 CON GX -1.2 2.2  
336. 3039 CON GX -1.2 3.2  
337. 3040 CON GX -2.2 1.957  
338. 3041 CON GX -1.2 1.2  
339. 3041 CON GX -1.2 2.2  
340. 3041 CON GX -1.2 3.2  
341. 3041 CON GX -1.2 4.2  
342. \*PR 804  
343. \*ROW HF-HE  
344. 3026 CON GX -0.3 0.785  
345. 3026 UNI GX -0.3 0.785 3  
346. 3027 CON GX -0.7 2.2  
347. 3028 CON GX -0.7 0.37  
348. 3028 CON GX -0.7 1.37  
349. 3029 CON GX -0.7 0.500001  
350. 3030 CON GX -0.7 0.5  
351. 3030 CON GX -1.7 1.9  
352. 3031 CON GX -0.7 0.775  
353. 3032 CON GX -0.7 1.2  
354. 3032 CON GX -0.7 2.2  
355. 3033 CON GX -0.7 0.37  
356. 3033 CON GX -0.7 1.37  
357. 3034 CON GX -0.7 0.500001  
358. 3035 CON GX -0.7 0.37  
359. 3035 CON GX -0.7 1.37  
360. 3036 CON GX -0.7 0.775  
361. \*INTERMEDIATE BEAMS  
362. \*ROW HF-HE  
363. 3037 3042 3043 3047 CON GX -0.3 0.785  
364. 3037 3042 3043 3047 UNI GX -0.4 0.785 3  
365. \*PR 805  
366. \*ROW HE-HF  
367. 3009 UNI GX -0.5 0.785 3  
368. 3009 CON GX -0.5 0.785  
369. \*PR 805  
370. \*ROW HA-HB  
371. \*PR 806  
372. \*ROW HA-HB  
373. \*PR 424  
374. \*ROW HA-HB  
375. \*HB, HC, HD, HE  
376. 2001 2004 TO 2006 CON GX -0.5 0.785

STAAD SPACE -- PAGE NO. 8

27

377. 2001 2004 TO 2006 UNI GX -0.3 0.785 3  
378. \*INTERMEDIATE BEAMS  
379. \*ROW HB-HC, HD-HE  
380. 2002 2003 2007 2008 CON GX -0.3 0.785  
381. 2002 2003 2007 2008 UNI GX -0.3 0.785 3  
382. LOAD 6 LOADTYPE NONE TITLE NLZ  
383. SELFWEIGHT Z -0.015 LIST 1000 TO 1044 2000 TO 2052 3000 TO 3049 4000 TO 4038 -  
384. 5002 TO 5009  
385. MEMBER LOAD  
386. \*PR 421-422 (SIDE BEAM)  
387. \*ROW GA-GB  
388. \*PR 422  
389. \*ROW HA-HB  
390. \*INTERMEDIATE BEAM  
391. \*ROW HA-HB  
392. \*INTERMEDIATE BEAM  
393. \*ROW HA-HB  
394. \*INTERMEDIATE BEAM  
395. \*ROW HA-HB  
396. \*PR 423  
397. \*ROW HA-HB  
398. \*PR 801  
399. \*ROW HF-HE  
400. 3049 CON GZ -0.5 0.785  
401. 3049 UNI GZ -0.3 0.785 3  
402. \*PR 802  
403. \*ROW HF-HE  
404. 3044 CON GZ -0.3 0.785  
405. 3044 UNI GZ -0.4 0.785 3  
406. 3045 CON GZ -1.6 1.957  
407. 3045 CON GZ -2.6 3.5  
408. \*PR 803  
409. \*ROW HF-HE  
410. 3038 CON GZ -0.3 0.785  
411. 3038 UNI GZ -0.3 0.785 3  
412. 3039 CON GZ -1.2 2.2  
413. 3039 CON GZ -1.2 3.2  
414. 3040 CON GZ -2.2 1.957  
415. 3041 CON GZ -1.2 1.2  
416. 3041 CON GZ -1.2 2.2  
417. 3041 CON GZ -1.2 3.2  
418. 3041 CON GZ -1.2 4.2  
419. \*PR 804  
420. \*ROW HF-HE  
421. 3026 CON GZ -0.3 0.785  
422. 3026 UNI GZ -0.3 0.785 3  
423. 3027 CON GZ -0.7 2.2  
424. 3028 CON GZ -0.7 0.37  
425. 3028 CON GZ -0.7 1.37  
426. 3029 CON GZ -0.7 0.500001  
427. 3030 CON GZ -0.7 0.5  
428. 3030 CON GZ -1.7 1.9  
429. 3031 CON GZ -0.7 0.775  
430. 3032 CON GZ -0.7 1.2  
431. 3032 CON GZ -0.7 2.2  
432. 3033 CON GZ -0.7 0.37

STAAD SPACE -- PAGE NO. 9

433. 3033 CON GZ -0.7 1.37  
434. 3034 CON GZ -0.7 0.500001  
435. 3035 CON GZ -0.7 0.37  
436. 3035 CON GZ -0.7 1.37  
437. 3036 CON GZ -0.7 0.775  
438. \*INTERMEDIATE BEAMS  
439. \*ROW HF-HE  
440. 3037 3042 3043 3047 CON GZ -0.3 0.785  
441. 3037 3042 3043 3047 UNI GZ -0.4 0.785 3  
442. \*PR 805  
443. \*ROW HE-HF  
444. 3009 UNI GZ -0.5 0.785 3  
445. 3009 CON GZ -0.5 0.785  
446. \*PR 805  
447. \*ROW HA-HB  
448. \*PR 806  
449. \*ROW HA-HB  
450. \*PR 424  
451. \*ROW HA-HB  
452. \*HB, HC, HD, HE  
453. 2001 2004 TO 2006 CON GZ -0.5 0.785  
454. 2001 2004 TO 2006 UNI GZ -0.3 0.785 3  
455. \*INTERMEDIATE BEAMS  
456. \*ROW HB-HC, HD-HE  
457. 2002 2003 2007 2008 CON GZ -0.3 0.785  
458. 2002 2003 2007 2008 UNI GZ -0.3 0.785 3  
459. \*SERVICE LOAD COMBINATIONS  
460. LOAD 7 LOADTYPE NONE TITLE 1.0DL+1.0FL  
461. REPEAT LOAD  
462. 1 1.0 2 1.0  
463. LOAD 8 LOADTYPE NONE TITLE 1.0DL+1.0FL+1.0WLX  
464. REPEAT LOAD  
465. 1 1.0 2 1.0 3 1.0  
466. LOAD 9 LOADTYPE NONE TITLE 1.0DL+1.0FL+1.0WLZ  
467. REPEAT LOAD  
468. 1 1.0 2 1.0 4 1.0  
469. LOAD 10 LOADTYPE NONE TITLE 1.0DL+1.0FL+1.0NLX  
470. REPEAT LOAD  
471. 1 1.0 2 1.0 5 1.0  
472. LOAD 11 LOADTYPE NONE TITLE 1.0DL+1.0FL+1.0NLZ  
473. REPEAT LOAD  
474. 1 1.0 2 1.0 6 1.0  
475. LOAD 12 LOADTYPE NONE TITLE 1.0DL-1.0FL  
476. REPEAT LOAD  
477. 1 1.0 2 -1.0  
478. LOAD 13 LOADTYPE NONE TITLE 1.0DL-1.0FL +1.0WLX  
479. REPEAT LOAD  
480. 1 1.0 2 -1.0 3 1.0  
481. LOAD 14 LOADTYPE NONE TITLE 1.0DL-1.0FL-1.0WLX  
482. REPEAT LOAD  
483. 1 1.0 2 -1.0 3 -1.0  
484. LOAD 15 LOADTYPE NONE TITLE 1.0DL-1.0FL+1.0WLZ  
485. REPEAT LOAD  
486. 1 1.0 2 -1.0 4 1.0  
487. LOAD 16 LOADTYPE NONE TITLE 1.0DL-1.0FL-1.0WLZ  
488. REPEAT LOAD

STAAD SPACE -- PAGE NO. 10

28

489. 1 1.0 2 -1.0 4 -1.0  
490. LOAD 17 LOADTYPE NONE TITLE 1.0DL-1.0FL+1.0 NLX  
491. REPEAT LOAD  
492. 1 1.0 2 -1.0 5 1.0  
493. LOAD 18 LOADTYPE NONE TITLE 1.0DL-1.0FL-1.0 NLX  
494. REPEAT LOAD  
495. 1 1.0 2 -1.0 5 -1.0  
496. LOAD 19 LOADTYPE NONE TITLE 1.0DL-1.0FL+1.0 NLZ  
497. REPEAT LOAD  
498. 1 1.0 6 1.0 2 -1.0  
499. LOAD 20 LOADTYPE NONE TITLE 1.0DL-1.0FL-1.0 NLZ  
500. REPEAT LOAD  
501. 2 -1.0 6 -1.0 1 1.0  
502. LOAD 21 LOADTYPE NONE TITLE 1.0DL+1.0FL-1.0 WLX  
503. REPEAT LOAD  
504. 1 1.0 2 1.0 3 -1.0  
505. LOAD 22 LOADTYPE NONE TITLE 1.0DL+1.0FL-1.0 WLZ  
506. REPEAT LOAD  
507. 4 -1.0 1 1.0 2 1.0  
508. LOAD 23 LOADTYPE NONE TITLE 1.0DL+1.0FL-1.0 NLX  
509. REPEAT LOAD  
510. 1 1.0 2 1.0 5 -1.0  
511. LOAD 24 LOADTYPE NONE TITLE 1.0DL+1.0FL-1.0 NLZ  
512. REPEAT LOAD  
513. 6 -1.0 1 1.0 2 1.0  
514. \*ULTIMATE LOAD COMBINATIONS  
515. LOAD 25 LOADTYPE NONE TITLE 1.0DL+1.4FL  
516. REPEAT LOAD  
517. 1 1.0 2 1.4  
518. LOAD 26 LOADTYPE NONE TITLE 1.4DL+1.4FL  
519. REPEAT LOAD  
520. 1 1.4 2 1.4  
521. LOAD 27 LOADTYPE NONE TITLE 1.4DL+1.4FL+1.4WLX  
522. REPEAT LOAD  
523. 1 1.4 2 1.4 3 1.4  
524. LOAD 28 LOADTYPE NONE TITLE 1.4DL+1.4FL+1.4WLZ  
525. REPEAT LOAD  
526. 1 1.4 2 1.4 4 1.4  
527. LOAD 29 LOADTYPE NONE TITLE 1.4DL+1.4FL+1.4NLX  
528. REPEAT LOAD  
529. 1 1.4 2 1.4 5 1.4  
530. LOAD 30 LOADTYPE NONE TITLE 1.4DL+1.4FL+1.4NLZ  
531. REPEAT LOAD  
532. 1 1.4 2 1.4 6 1.4  
533. LOAD 31 LOADTYPE NONE TITLE 1.0DL-1.4FL  
534. REPEAT LOAD  
535. 1 1.0 2 -1.4  
536. LOAD 32 LOADTYPE NONE TITLE 1.4DL-1.4FL  
537. REPEAT LOAD  
538. 1 1.4 2 -1.4  
539. LOAD 33 LOADTYPE NONE TITLE 1.4DL-1.4FL+1.4 WLX  
540. REPEAT LOAD  
541. 1 1.4 3 1.4 2 -1.4  
542. LOAD 34 LOADTYPE NONE TITLE 1.4DL-1.4FL-1.4 WLX  
543. REPEAT LOAD  
544. 2 -1.4 3 -1.4 1 1.4

STAAD SPACE -- PAGE NO. 11

545. LOAD 35 LOADTYPE NONE TITLE 1.4DL-1.4FL+1.4 WLZ  
546. REPEAT LOAD  
547. 1 1.4 4 1.4 2 -1.4  
548. LOAD 36 LOADTYPE NONE TITLE 1.4DL-1.4FL-1.4 WLZ  
549. REPEAT LOAD  
550. 2 -1.4 4 -1.4 1 1.4  
551. LOAD 37 LOADTYPE NONE TITLE 1.4DL-1.4FL+1.4 NLX  
552. REPEAT LOAD  
553. 1 1.4 5 1.4 2 -1.4  
554. LOAD 38 LOADTYPE NONE TITLE 1.4DL-1.4FL-1.4 NLX  
555. REPEAT LOAD  
556. 2 -1.4 5 -1.4 1 1.4  
557. LOAD 39 LOADTYPE NONE TITLE 1.4DL-1.4FL+1.4 NLZ  
558. REPEAT LOAD  
559. 1 1.4 6 1.4 2 -1.4  
560. LOAD 40 LOADTYPE NONE TITLE 1.4DL-1.4FL-1.4 NLZ  
561. REPEAT LOAD  
562. 2 -1.4 6 -1.4 1 1.4  
563. LOAD 41 LOADTYPE NONE TITLE 1.4DL+1.4FL-1.4 WLX  
564. REPEAT LOAD  
565. 1 1.4 2 1.4 3 -1.4  
566. LOAD 42 LOADTYPE NONE TITLE 1.4DL+1.4FL-1.4 WLZ  
567. REPEAT LOAD  
568. 4 -1.4 1 1.4 2 1.4  
569. LOAD 43 LOADTYPE NONE TITLE 1.4DL+1.4FL-1.4 NLX  
570. REPEAT LOAD  
571. 1 1.4 2 1.4 5 -1.4  
572. LOAD 44 LOADTYPE NONE TITLE 1.4DL+1.4FL-1.4 NLZ  
573. REPEAT LOAD  
574. 6 -1.4 1 1.4 2 1.4  
575. PERFORM ANALYSIS

## P R O B L E M S T A T I S T I C S

-----

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 110/ 197/ 24

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

ORIGINAL/FINAL BAND-WIDTH= 29/ 13/ 81 DOF  
TOTAL PRIMARY LOAD CASES = 44, TOTAL DEGREES OF FREEDOM = 594  
SIZE OF STIFFNESS MATRIX = 49 DOUBLE KILO-WORDS  
REQRD/AVAIL. DISK SPACE = 13.5/ 77473.3 MB

\*\*START ITERATION NO. 2  
\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 1

\*\*START ITERATION NO. 2

STAAD SPACE -- PAGE NO. 12

29

\*\*NOTE-Tension/Compression converged after 2 iterations, Case= 2

\*\*START ITERATION NO. 2

\*\*NOTE-Tension/Compression converged after 2 iterations, Case= 3

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 4

\*\*START ITERATION NO. 2

\*\*NOTE-Tension/Compression converged after 2 iterations, Case= 5

\*\*START ITERATION NO. 2

\*\*NOTE-Tension/Compression converged after 2 iterations, Case= 6

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 7

\*\*START ITERATION NO. 2

\*\*NOTE-Tension/Compression converged after 2 iterations, Case= 8

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 9

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 10

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3

\*\*NOTE-Tension/Compression converged after 3 iterations, Case= 11

\*\*START ITERATION NO. 2

\*\*START ITERATION NO. 3