

```
*****  
*****  
***** SUAPAD.Pro *****  
***** Version 2003 Rld 1001.US *****  
***** Proprietary Program of *****  
***** Research Engineers, Inc. *****  
***** Dates JUL 17, 2009 *****  
***** Time= 18:55: 8 *****  
***** USER ID: *****  
*****
```

1 STEAD PLANE DXF IMPORT OF 2FGK.DXF

1. START JOB INFORMATION
2. JOB NAME 2F 6K X 28X
3. JOB NAME 2F 6K X 28X
4. JOB CLIENT ACI
5. ENGINEER NAME RCZ
6. APPROVED NAME LCK
7. ENGINEER DATE 28-MAY-07
8. END JOB INFORMATION
9. INPUT WIDTH 79
0. UNIT MMS KN
1. JOINT COORDINATES
2. 1 473.35 71.4294 0; 2 473.35 2610.43 0; 3 473.35 3210.43 0; 4 473.35 5822.43 0
3. 5 11393.4 71.4294 0; 6 11393.4 2760.43 0; 7 11393.4 3210.43 0
4. 8 11393.4 5822.43 0; 10 5933 2760.43 0; 11 5933.25 3210.43 0
5. 12 1383.35 6032.52 0; 13 2293.35 6242.61 0; 14 3203.35 6452.7 0
6. 15 4113.35 6862.79 0; 16 5023.35 6972.88 0; 17 5933.35 7082.97 0
7. 18 6843.35 6872.88 0; 19 7753.35 5662.79 0; 20 8663.35 6452.7 0
8. 21 9573.35 6242.61 0; 22 10483.4 6032.52 0; 23 1383.35 5822.43 0
9. 24 2293.35 5822.43 0; 25 3203.35 5822.43 0; 26 4113.35 5822.43 0
10. 27 5023.35 5822.43 0; 28 5933.35 5822.43 0; 29 6843.35 5822.43 0
11. 30 7753.35 5822.43 0; 31 8663.35 5822.43 0; 32 9573.35 5822.43 0
12. 33 10483.4 5822.43 0; 34 68 5933.35 71 0; 71 473.35 5475.43 0
13. 77 973.35 3210.43 0; 78 5433.35 3210.43 0; 79 6433.35 3210.43 0
14. 80 473.35 2760.43 0; 81 928.35 5822.43 0; 82 11393.4 5480.43 0
15. 83 1383.35 3210.43 0; 84 3933.35 3210.43 0; 85 7933.35 3210.43 0

36.	MEMBER INCIDENTS	1 1 2: 2 2 80: 3 71: 4 5 6: 5 6 7: 6 7 82: 9 4 12: 10 12 13: 11 13 14
37.		12 14 15: 13 15 16: 14 16 17: 15 17 18: 16 18 19: 17 19 20: 18 20 21: 19 21 22
38.		20 22 8: 21 4 81: 22 23 24: 23 24 25: 24 25 26: 25 26 27: 26 27 28: 27 28 29
39.		28 29 30: 29 30 31: 30 31 32: 31 32 33: 32 33 8: 33 17 28: 34 23 12: 35 12 24
40.		36 24 13: 37 13 25: 38 25 14: 39 14 26: 40 26 15: 41 15 27: 42 27 16: 43 16 28
41.		44 28 13: 45 18 23: 46 29 19: 47 19 30: 48 30 20: 49 20 31: 50 31 21: 51 21 32
42.		52 32 22: 53 22 33: 54 3 77: 72 11 79: 129 68 10: 130 10 11: 133 71 4
43.		144 77 84: 145 78 11: 146 79 85: 147 80 3: 148 80 77: 151 81 23: 152 71 23
44.		153 10 78: 154 10 79: 155 11 28: 156 82 8: 157 83 7: 158 82 33: 159 6 83
45.		160 84 78: 161 85 83
46.	DEFINE MATERIAL START	
47.	ISOTROPIC STEEL	
48.	E 205	
49.	POISSON 0.3	
50.	DENSITY 7.68195E-008	

DXF IMPORT OF 2F6K.DXF

42.	ALPHA 1.2E-005
43.	DMP 0.03
44.	END DEFINE MATERIAL
45.	START USER TABLE
46.	TABLE 1
47.	UNIT MMS KN
48.	GENERAL
49.	C38X38
50.	252 38 2.3 38 2.3 38072 62913 100000 1557 3311 87 175 1557 3311 100000 38
51.	TABLE 2
52.	UNIT MMS KN
53.	GENERAL
54.	2C75X45
55.	1098 75 6 90 3 938192 638334 100000 26218 14185 450 270 26218 14185 100000 75
56.	TABLE 3
57.	UNIT MMS KN
58.	GENERAL
59.	C100X50
60.	653 50 3 100 3 229000 990000 1E+006 7270 19800 300 343 11600 23600 1E+006 48
61.	TABLE 4
62.	UNIT MMS KN
63.	GENERAL
64.	C75X45
65.	518 45 3 75 3 138000 449000 100000 4940 12000 270 315 4940 12000 100000 40
66.	TABLE 5
67.	UNIT MMS KN
68.	TUBE
69.	S4S75X3-CF
70.	841 75 75 3 716000 716000 1.15E+006 450 300
71.	TABLE 6
72.	UNIT MMS KN
73.	TUBE
74.	S4S38X3-CF
75.	397 38 38 3 78500 78500 133000 228 152
76.	TABLE 7
77.	UNIT MMS KN
78.	TUBE
79.	S4S50X3-CF
80.	541 50 50 3 195000 195000 321000 300 200
81.	TABLE 8
82.	UNIT MMS KN
83.	ANGLE
84.	VA38X38X3
85.	38 38 3 14.5 114 114
86.	TABLE 9
87.	UNIT MMS KN
88.	GENERAL
89.	2C30CX98X3.0
90.	3258 300 6 196 3 4.416E-007 6.5986E+006 100000 294408 68736 2136 1800 -
91.	9.29441E+006 68736 100000 300
92.	TABLE 10
93.	UNIT MMS KN
94.	TUBE
95.	S4S150X4.5CF
96.	2570 150 150 4.5 8.96E+006 8.96E+006 1.411E+007 1350 900
97.	TABLE 16

DXF IMPORT OF 2F6K.DXF

98. UNIT RMS KN
 99. TUBE
 100. SHS75X6-CF
 101. 1560 75 75 6 1.2E+006 1.2E+006 1.97105E+006 900 600
 102. TABLE 17
 103. UNIT RMS KN
 104. TUBE
 105. SHS75X4.5-CF
 106. 970 75 75 4.5 986000 986000 1.63E+006 675 450
 107. END
 108. *COLD-FORMED SECTIONS
 109. UNIT METER KN
 110. MEMBER PROPERTY BRITISH
 111. 1 TO 6 133 147 156 UPTABLE 2 2C75X45
 112. 54 72 144 TO 146 157 160 161 UPTABLE 9 2C300X98X3.0
 113. 148 153 154 158 159 UPTABLE 7 SHS50X3-CF
 114. MEMBER PROPERTY BRITISH
 115. 9 TO 33 151 UPTABLE 4 C75X45
 116. MEMBER PROPERTY BRITISH
 117. 129 130 155 UPTABLE 10 SHS150X4.5CF
 118. 34 TO 53 152 UPTABLE 6 SHS38X3-CF
 119. MEMBER TRUSS
 120. 33 TO 53
 121. CONSTANTS
 122. MATERIAL STEEL ALL
 123. SUPPORTS
 124. 1 5 68 PINNED
 125. MEMBER RELEASE
 126. 9 21 54 72 START MK MY MZ
 127. 20 32 145 157 END MX MY MZ
 128. LOAD 1 S/W
 129. SELFWEIGHT Y -1
 130. LOAD 2 DL
 131. MEMBER LOAD
 132. 9 TO 20 UNI GY -1.27
 133. 54 72 144 TO 146 157 160 161 UNI GY -0.76
 134. JOINT LOAD
 135. 11 FY -10
 136. 11 FY 10
 137. 28 FY -13.86
 138. LOAD 3 EL
 139. MEMBER LOAD
 140. 9 TO 20 UNI GY -1.82
 141. 54 144 157 161 UNI GY -4.55
 142. *(1.82/2 X 4.0 = 3.64)
 143. JOINT LOAD
 144. 11 FY -35.9
 145. 11 FY -58.4
 146. 28 FY -14.4
 147. MEMBER LOAD
 148. 72 145 146 160 UNI GY -9.1
 149. LOAD 4 WL
 150. MEMBER LOAD
 151. 9 TO 20 UNI GY 1
 152. JOINT LOAD
 153. 28 FY 5.1

DXF IMPORT OF 2F6K.DXF

154. LOAD COMB 6 ULTIMATE S/W+DL+LL
 155. 1 1.4 2 1.4 3 1.6
 156. LOAD COMB 7 ULTIMATE DL+WL
 157. 1 1.0 2 1.0 4 1.4
 158. LOAD COMB 9 SERVICE DL+LL FOR DEFLECTION
 159. 2 1.0 3 1.0
 160. LOAD COMB 10 SERVICE S/W+DL+LL FOR FOUNDATION DESIGN
 161. 1 1.0 2 1.0 3 1.0
 162. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER-ELEMENTS/SUPPORTS = 43/ 72/ 3
 ORIGINAL/FINAL BAND-WIDTH= 36/ 5/ 18 DOF
 TOTAL PRIMARY LOAD CASES = 4, TOTAL DEGREES OF FREEDOM = 123
 SIZE OF STIFFNESS MATRIX = 3 DOUBLE KILLO-WORDS
 RECORD/AVAIL. DISK SPACE = 12.1/ 32685.4 MB, EXMEM = 261.2 MB

163. PARAMETER 1
 164. CODE BSS950
 165. UNL 1 MEMB 144 146 157 160 161
 166. CHECK CODE ALL

STAAD.PG CODE CHECKING - (BSI)

PROGRAM CODE REVISION V2.4_5950-1_2000