

PAGE NO.
1

STAAD.Pro
Version 2006 Bld 1005.US
Proprietary Program of
Research Engineers, Intl.
Date= MAR 27, 2008
Time= 17:53:59

USER ID: MIPL

1. STAAD PLANE RAS B16 SECURITY OFFICE FRAME 1
INPUT FILE: Ras B16 Security Office Frame-1.STD

2. START JOB INFORMATION

3. ENGINEER DATE MAR-08

4. END JOB INFORMATION

5. INPUT WIDTH 79

6. UNIT METER KN

7. JOINT COORDINATES

8. 101 0 0

9. 201 0 3.3 0

10. 102 1.06 0 0

11. 202 1.06 3.3 0

12. MEMBER INCIDENCES

13. 101 101 201

14. 102 102 202

15. 2001 201 202

16. MEMBER PROPERTY

17. 101 PRI ZD 0.3 YD 0.25

18. 102 PRI ZD 0.3 YD 0.25

19. 2001 PRI ZD 0.2 YD 0.3

20. CONSTANTS

21. E 2.5E+007 MEMB 101 102 2001

22. POISSON 0.2 MEMB 101 102 2001

23. DENSITY 24 MEMB 101 102 2001

24. SUPPORTS

25. 101 102 FIX

26. LOAD 1 SELFWEIGHT

27. SELFWEIGHT Y -1

28. LOAD 2 SDL

29. JOINT LOAD

30. 201 202 FY -49.93

31. LOAD 3 LL

32. JOINT LOAD

33. 201 202 FY -16.86

35. LOAD 21 EQ (EARTHQUAKE LOAD)

36. MEMBER LOAD

37. 101 UNI Y 6.7

38. 102 UNI Y 6.7

40. LOAD COMB 1001

41. 1 1.4 2 1.4 3 1.6

42. LOAD COMB 1021 1.2DL + 0.5LL + 1.0EQ

RAS B16 SECURITY OFFICE FRAME 1

2

43. 1 1.2 2 1.2 3 0.5 21 1.0

44. LOAD COMB 1121 1.2DL + 0.5LL - 1.0EQ

45. 1 1.2 2 1.2 3 0.5 21 -1.0

46. LOAD COMB 1221 0.9DL + 1.0EQ

47. 1 0.9 2 0.9 21 1.0

48. LOAD COMB 1321 0.9DL - 1.0EQ
49. 1 0.9 2 0.9 21 -1.0
51. LOAD COMB 2001 1.0DL + 1.0LL
52. 1 1.0 2 1.0 3 1.0
53. LOAD COMB 2002 1.0DL + 0.5LL
54. 1 1.0 2 1.0 3 0.5
56. PERFORM ANALYSIS

PROBLEM STATISTICS

NUMBER OF JOINTS/MEMBERELEMENTS/SUPPORTS = 4/ 2/ 3/ 2
ORIGINAL/FINAL BAND-WIDTH= 2/ 6 DOF
TOTAL PRIMARY LOAD CASES = 4, TOTAL DEGREES OF FREEDOM = 6
SIZE OF STIFFNESS MATRIX = 1 DOUBLE KILO-WORDS
REORD/AVAIL. DISK SPACE = 12.0/ 134460.4 MB

57. PRINT MAXFORCE ENV
MAXFORCE ENV J
RAS B16 SECURITY OFFICE FRAME 1
3

-- PAGE NO.

MEMBER FORCE ENVELOPE

ALL UNITS ARE KN METE

MAX AND MIN FORCE VALUES AMONGST ALL SECTION LOCATIONS

MEMB	FY/ FZ LD	DIST DIST LD	LD	MZ/ MY LD	DIST DIST LD	LD	FX	DIST
101 MAX	22.09	0.00	1321	25.15	0.00	1321	106.26	C 0.00
	0.00	0.00	1	0.00	0.00	1		
MIN	-22.14	0.00	1021	-25.20	0.00	1021	0.76	C 3.30
	0.00	3.30	2002	0.00	3.30	2002		
102 MAX	22.14	0.00	1121	25.20	0.00	1121	106.26	C 0.00
	0.00	0.00	1	0.00	0.00	1		
MIN	-22.11	0.00	21	-25.17	0.00	21	21.33	T 3.30
	0.00	3.30	2002	0.00	3.30	2002		
2001 MAX	22.25	0.00	1021	11.36	0.00	1021	0.03	C 0.00
	0.00	0.00	1	0.00	0.00	1		
MIN	-22.25	1.06	1121	-11.31	1.06	21	0.00	1.06
	0.00	1.06	2002	0.00	1.06	2002		

***** END OF FORCE ENVELOPE FROM INTERNAL STORAGE *****

59. LOAD LIST ALL
60. PRINT SUPPORT REACTIONS ALL