

CS 201 Data Structures Library Phase 1 Due 9/18

For phase 1 of the CS201 programming project, we will start with a dynamic array class and extend it to implement some of the algorithms discussed in class.

Your dynamic array class should be called `CircularDynamicArray`. The `CircularDynamicArray` class should manage the storage of an array that can grow and shrink. The class should be implemented using templates. As items are added and removed from both the front and the end of the array, the items will always be referenced using indices `0...size-1`.

The public methods of your class should include the following (elmttype indicates the type from the template):

Function	Description	Runtime
<code>CircularDynamicArray();</code>	Default Constructor. The array should be of capacity 2 and size 0.	$O(1)$
<code>CircularDynamicArray(int s);</code>	For this constructor the array should be of capacity and size s.	$O(1)$
<code>~CircularDynamicArray();</code>	Destructor for the class.	$O(1)$
<code>elmttype& operator[](int i);</code>	Traditional [] operator. Should print a message if i is out of bounds and return a reference to value of type elmttype stored in the class for this purpose.	$O(1)$
<code>void addEnd(elmttype v);</code>	increases the size of the array by 1 and stores v at the end of the array. Should double the capacity when the new element doesn't fit.	$O(1)$ amortized
<code>void addFront(elmttype v);</code>	increases the size of the array by 1 and stores v at the beginning of the array. Should double the capacity when the new element doesn't fit. The new element should be the item returned at index 0.	$O(1)$ amortized
<code>void delEnd();</code>	reduces the size of the array by 1 at the end. Should shrink the capacity when only 25% of the array is in use after the delete.	$O(1)$ amortized
<code>void delFront();</code>	reduces the size of the array by 1 at the beginning of the array. Should shrink the capacity when only 25% of the array is in use after the delete.	$O(1)$ amortized
<code>int length();</code>	returns the size of the array.	$O(1)$
<code>int capacity();</code>	returns the capacity of the array.	$O(1)$
<code>void clear();</code>	Frees any space currently used and starts over with an array of capacity 2 and size 0.	$O(1)$
<code>Elmttype QuickSelect(int k);</code>	returns the k^{th} smallest element in the array using the quickselect algorithm.	$O(\text{size})$ expected
<code>Elmttype WCSelect(int k);</code>	returns the k^{th} smallest element in the array using the worst case $O(N)$ time algorithm.	$O(\text{size})$
<code>void stableSort();</code> MergeSort	Sorts the values in the array using a comparison based $O(N \lg N)$ algorithm. The sort must be stable.	$O(\text{size} \lg \text{size})$
<code>int linearSearch(elmttype e)</code>	Performs a linear search of the array looking for the item e. Returns the index of the item if found or -1 otherwise.	$O(\text{size})$

<code>int binSearch(elmttype e)</code>	Performs a binary search of the array looking for the item e. Returns the index of the item if found or -1 otherwise. Assumes that the array is in sorted order.	$O(\lg \text{size})$
--	--	----------------------

Your class should include proper memory management, including a destructor, a copy constructor, and a copy assignment operator.

For submission, all the class code should be in a file named `CircularDynamicArray.cpp`. Create a makefile for the project that compiles the file `Phase1Main.cpp` and creates an executable named **Phase1**. A sample makefile is available on Blackboard. **Only the compiler flag should be changed in the makefile.** Place both `CircularDynamicArray.cpp` and makefile into a zip file and upload the file to Blackboard.

- ☐ Create your `CircularDynamicArray` class
- ☐ Modify the makefile to work for your code (changing compiler flags is all that is necessary)
- ☐ Test your `CircularDynamicArray` class with the sample main provided on the cs-intro server
- ☐ Make sure your executable is named **Phase1**
- ☐ Develop additional test cases with different types, and larger arrays
- ☐ Create the zip file with only your source code (**`CircularDynamicArray.cpp` and makefile**)
- ☐ Upload your zip file to Blackboard