

Cpp concept project

Generated by Doxygen 1.8.20



# Chapter 1

## C++ concepts project

See the [Documentation!](#)

### 1.1 Idea

This project serves as sample/concept project for further projects :thumbsup:

### 1.2 Related documents

- [Notes](#)
- [Markdown cheatsheet](#)
- [Project structure](#)
- [Unit testing](#)

### 1.3 Structure

#### 1.3.1 Folders

- **bin**: output executables go here (for the app, tests and spikes)
- **build**: containing all the object files (removed by clean)
- **doc**: documentation files
- **ideas**: smaller classes or files to test technologies or ideas
- **include**: all project header files, all necessary third-party header files (which are not in /usr/local/include)
- **lib**: any library that get compiled by the project, third party or any needed in development
- **resources**: resources
- **src**: the application and application's source files
- **test**: all test code files

## 1.4 Content (Concepts)

### 1.4.1 Programming concepts

- Classes
  - Inheritance
- Templates
- ...

### 1.4.2 Documentation

The documentation is intrinsically implemented using [doxygen](#). In order to do that:

- specify path to doxygen binary in the Makefile
- execute *make doc*

The [README.md](#) file is used for the Mainpage of the documentation. Set the settings for doxygen in *doc/Doxyfile*.

### 1.4.3 Makefile

Following targets are implemented:

- **all** default make
- **remake**
- **clean**
- **cleaner**
- **resources**
- **sources**
- **directories**
- **ideas**
- **tester**
- **doc**

## Chapter 2

# CMake

### 2.1 Links

- [Repository](#)
- [Awesome-CMake list](#)

#### 2.1.1 Documentation

- [CMake official documentation](#)
- [The Architecture of Open Source Applications](#)

#### 2.1.2 Tutorials & Instructions

- [Effective Modern CMake \(Dos & Don'ts\)](#)
- [GitBook: Introduction to Modern CMake](#)
- [CMake Cookbook](#)
- [CMake Primer](#)

#### 2.1.3 Videos

- [Intro to CMake](#)
- [Using Modern CMake Patterns to Enforce a Good Modular Design](#)
- [Effective CMake](#)
- [Embracing Modern CMake](#)

## 2.2 Basics

### 2.2.1 CMake Version

```
#minimum CMake version
cmake_minimum_required(VERSION 3.12)
if(${CMAKE_VERSION} VERSION_LESS 3.12)
    cmake_policy(VERSION ${CMAKE_MAJOR_VERSION}.${CMAKE_MINOR_VERSION})
endif()
```

### 2.2.2 VARIABLES

```
# Local variable
set(MY_VARIABLE "value")
set(MY_LIST "one" "two")
# Cache variable
set(MY_CACHE_VARIABLE "VALUE" CACHE STRING "Description")
# Environmental variables
set(ENV{variable_name} value) #access via $ENV{variable_name}
```

### 2.2.3 PROPERTIES

```
set_property(TARGET TargetName PROPERTY CXX_STANDARD 11)
set_target_properties(TargetName PROPERTIES CXX_STANDARD 11)
get_property(ResultVariable TARGET TargetName PROPERTY CXX_STANDARD)
```

### 2.2.4 Output folders

```
# set output folders
set(PROJECT_SOURCE_DIR)
set(CMAKE_SOURCE_DIR ...)
set(CMAKE_BINARY_DIR ${CMAKE_SOURCE_DIR}/bin)
set(EXECUTABLE_OUTPUT_PATH ${CMAKE_BINARY_DIR})
set(LIBRARY_OUTPUT_PATH ${CMAKE_BINARY_DIR})
```

### 2.2.5 Sources

```
# set sources
set(SOURCES example.cu)
file(GLOB SOURCES *.cu)
```

### 2.2.6 Executables & targets

Add executable/create target:

```
#add_executable(example ${PROJECT_SOURCE_DIR}/example.cu)
add_executable(miluphcuda ${SOURCES})
# add include directory to target
target_include_directories(miluphcuda PUBLIC include) #PUBLIC/PRIVATE/INTERFACE
# add compile feature to target
target_compile_features(miluphcuda PUBLIC cxx_std_11)
# chain targets (assume "another" is a target)
add_library(another STATIC another.cpp another.h)
target_link_libraries(another PUBLIC miluphcuda)
```

## 2.2.7 PROGRAMMING IN CMAKE

Keywords:

- NOT
- TARGET
- EXISTS
- DEFINED
- STREQUAL
- AND
- OR
- MATCHES
- ...

### 2.2.7.1 Control flow

```
if(variable)
    # If variable is 'ON', 'YES', 'TRUE', 'Y', or non zero number
else()
    # If variable is '0', 'OFF', 'NO', 'FALSE', 'N', 'IGNORE', 'NOTFOUND', '', or ends in '-NOTFOUND'
#endif()
```

### 2.2.7.2 Loops

- `foreach(var IN ITEMS foo bar baz) ...`
- `foreach(var IN LISTS my_list) ...`
- ``foreach(var IN LISTS my_list ITEMS foo bar baz) ...`

### 2.2.7.3 Generator expression

```
target_include_directories(
    MyTarget
    PUBLIC
    $<BUILD_INTERFACE:${CMAKE_CURRENT_SOURCE_DIR}/include>
    $<INSTALL_INTERFACE:include>
)
```

### 2.2.7.4 Functions (& macros)

```
function(SIMPLE REQUIRED_ARG)
    message(STATUS "Simple arguments: ${REQUIRED_ARG}, followed by ${ARGV}")
    set(${REQUIRED_ARG} "From SIMPLE" PARENT_SCOPE)
endfunction()
simple(This)
message("Output: ${This}")
```

## 2.2.8 COMMUNICATION WITH CODE

### 2.2.8.1 Configure File

```
configure_file()
...
```

### 2.2.8.2 Reading files

...

## 2.2.9 RUNNING OTHER PROGRAMS

### 2.2.9.1 command at configure time

```
find_package(Git QUIET)
if (GIT_FOUND AND EXISTS "${PROJECT_SOURCE_DIR}/.git")
    execute_process(COMMAND ${GIT_EXECUTABLE} submodule update --init --recursive
        WORKING_DIRECTORY ${CMAKE_CURRENT_SOURCE_DIR}
        RESULT_VARIABLE GIT_SUBMOD_RESULT)
    if (NOT GIT_SUBMOD_RESULT EQUAL "0")
        message(FATAL_ERROR "git submodule update --init failed with ${GIT_SUBMOD_RESULT}, please checkout
            submodules")
    endif()
endif()
```

### 2.2.9.2 command at build time

```
find_package(PythonInterp REQUIRED)
add_custom_command(OUTPUT "${CMAKE_CURRENT_BINARY_DIR}/include/Generated.hpp"
    COMMAND "${PYTHON_EXECUTABLE}" "${CMAKE_CURRENT_SOURCE_DIR}/scripts/GenerateHeader.py" --argument
    DEPENDS some_target)
add_custom_target(generate_header ALL
    DEPENDS "${CMAKE_CURRENT_BINARY_DIR}/include/Generated.hpp")
install(FILES ${CMAKE_CURRENT_BINARY_DIR}/include/Generated.hpp DESTINATION include)
```

## 2.3 Libraries

```
# make a library
add_library(one STATIC two.cpp three.h) # STATIC/SHARED/MODULE
```

## 2.4 Language/Package related

### 2.4.1 C

```
# set C compiler
set(CMAKE_C_COMPILER "/usr/bin/gcc-7")
execute_process (
    COMMAND bash -c "git describe --abbrev=4 --dirty --always --tags'"
    OUTPUT_VARIABLE GIT_VERSION
)
#set (CMAKE_BUILD_TYPE DEBUG)
set (CMAKE_C_FLAGS "-c -std=c99 -O3 -DVERSION=\"${GIT_VERSION}\" -fPIC")
#set (CMAKE_C_FLAGS_DEBUG "-O0 -ggdb")
#set (CMAKE_C_FLAGS_RELEASE "-O0 -ggdb")
```

### 2.4.2 C++

...

### 2.4.3 CUDA

See [Combining CUDA and Modern CMake](#)



### 2.4.3.1 Enable Cuda support

CUDA is not optional

```
project(MY_PROJECT LANGUAGES CUDA CXX)
```

CUDA is optional

```
enable_language(CUDA)
```

Check whether CUDA is available

```
include(CheckLanguage)
check_language(CUDA)
```

### 2.4.3.2 CUDA Variables

Exchange *CXX* with *CUDA*

E.g. setting CUDA standard:

```
if(NOT DEFINED CMAKE_CUDA_STANDARD)
    set(CMAKE_CUDA_STANDARD 11)
    set(CMAKE_CUDA_STANDARD_REQUIRED ON)
endif()
```

### 2.4.3.3 Adding libraries / executables

As long as \*.cu\* is used for CUDA files, the procedure is as normal.

With separable compilation

```
set_target_properties(mylib PROPERTIES
    CUDA_SEPARABLE_COMPILATION ON)
```

### 2.4.3.4 Architecture

Use `CMAKE_CUDA_ARCHITECTURES` variable and the `CUDA_ARCHITECTURES` property on targets.

### 2.4.3.5 Working with targets

Compiler option

```
"${CMAKE_BUILD_INTERFACE}:${CMAKE_COMPILE_LANGUAGE:CXX}:-fopenmp>${CMAKE_BUILD_INTERFACE}:${CMAKE_COMPILE_LANGUAGE:CUDA}:-Xcompiler=-fopenmp"
```

Use a function that will fix a C++ only target by wrapping the flags if using a CUDA compiler

```
function(CUDA_CONVERT_FLAGS EXISTING_TARGET)
    get_property(old_flags TARGET ${EXISTING_TARGET} PROPERTY INTERFACE_COMPILE_OPTIONS)
    if(NOT "${old_flags}" STREQUAL "")
        string(REPLACE ";" " ", " CUDA_flags "${old_flags}")
        set_property(TARGET ${EXISTING_TARGET} PROPERTY INTERFACE_COMPILE_OPTIONS
            "${CMAKE_BUILD_INTERFACE}:${CMAKE_COMPILE_LANGUAGE:CXX}:${old_flags}>${CMAKE_BUILD_INTERFACE}:${CMAKE_COMPILE_LANGUAGE:CUDA}:-Xcompiler=${CMAKE_CXX_COMPILER}"
        )
    endif()
endfunction()
```

### 2.4.3.6 Useful variables

- CMAKE\_CUDA\_TOOLKIT\_INCLUDE\_DIRECTORIES: Place for built-in Thrust, etc
- CMAKE\_CUDA\_COMPILER: NVCC with location

```
set(CUDA_DIR "/usr/local/cuda-10.0")
set(CMAKE_CUDA_COMPILER ${CUDA_DIR}/bin/nvcc)
set(CMAKE_CUDA_FLAGS "-ccbin ${CC} -x cu -c -dc -O3 -Xcompiler \"-O3 -pthread\" -Wno-deprecated-gpu-targets
    -DVERSION=\"${GIT_VERSION}\" --ptxas-options=-v")
set(CMAKE_CUDA_FLAGS_DEBUG ...)
set(CMAKE_CUDA_HOST_COMPILER ...)
set(CMAKE_CUDA_EXTENSIONS ...)
set(CMAKE_CUDA_STANDARD ...)
set(CMAKE_CUDA_RUNTIME_LIBRARY ...)
...
```

## 2.4.4 OpenMP

### 2.4.4.1 Enable OpenMP support

```
find_package(OpenMP)
if(OpenMP_CXX_FOUND)
    target_link_libraries(MyTarget PUBLIC OpenMP::OpenMP_CXX)
endif()
```

## 2.4.5 Boost

The Boost library is included in the find packages that CMake provides.

(Common) Settings related to boost

- set(Boost\_USE\_STATIC\_LIBS OFF)
- set(Boost\_USE\_MULTITHREADED ON)
- `set(Boost\_USE\_STATIC\_RUNTIME OFF)

E.g.: using the Boost::filesystem library

```
set(Boost_USE_STATIC_LIBS OFF)
set(Boost_USE_MULTITHREADED ON)
set(Boost_USE_STATIC_RUNTIME OFF)
find_package(Boost 1.50 REQUIRED COMPONENTS filesystem)
message(STATUS "Boost version: ${Boost_VERSION}")
# This is needed if your Boost version is newer than your CMake version
# or if you have an old version of CMake (<3.5)
if(NOT TARGET Boost::filesystem)
    add_library(Boost::filesystem IMPORTED INTERFACE)
    set_property(TARGET Boost::filesystem PROPERTY
        INTERFACE_INCLUDE_DIRECTORIES ${Boost_INCLUDE_DIR})
    set_property(TARGET Boost::filesystem PROPERTY
        INTERFACE_LINK_LIBRARIES ${Boost_LIBRARIES})
endif()
```

## 2.4.6 MPI

### 2.4.6.1 Enable MPI support

```
find_package(MPI REQUIRED)
message(STATUS "Run: ${MPIEXEC} ${MPIEXEC_NUMPROC_FLAG} ${MPIEXEC_MAX_NUMPROCS} ${MPIEXEC_PREFLAGS}
    EXECUTABLE ${MPIEXEC_POSTFLAGS} ARGS")
target_link_libraries(MyTarget PUBLIC MPI::MPI_CXX)
```

## 2.5 Adding features

### 2.5.1 Set default build type

```
set(default_build_type "Release")
if(NOT CMAKE_BUILD_TYPE AND NOT CMAKE_CONFIGURATION_TYPES)
    message(STATUS "Setting build type to '${default_build_type}' as none was specified.")
    set(CMAKE_BUILD_TYPE "${default_build_type}" CACHE
        STRING "Choose the type of build." FORCE)
    # Set the possible values of build type for cmake-gui
    set_property(CACHE CMAKE_BUILD_TYPE PROPERTY STRINGS
        "Debug" "Release" "MinSizeRel" "RelWithDebInfo")
endif()
```

### 2.5.2 Meta compiler features

```
target_compile_features(myTarget PUBLIC cxx_std_11)
set_target_properties(myTarget PROPERTIES CXX_EXTENSIONS OFF)
set(CMAKE_CXX_STANDARD 11)
set(CMAKE_CXX_STANDARD_REQUIRED ON)
set(CMAKE_CXX_EXTENSIONS OFF)
set_target_properties(myTarget PROPERTIES
    CXX_STANDARD 11
    CXX_STANDARD_REQUIRED YES
    CXX_EXTENSIONS NO
)
```

### 2.5.3 Position independent code (-fPIC)

```
set(CMAKE_POSITION_INDEPENDENT_CODE ON)
# or target dependent
set_target_properties(lib1 PROPERTIES POSITION_INDEPENDENT_CODE ON)
```

### 2.5.4 Little libraries

```
find_library(MATH_LIBRARY m)
if(MATH_LIBRARY)
    target_link_libraries(MyTarget PUBLIC ${MATH_LIBRARY})
endif()
```

## 2.5.5 Modules

### 2.5.5.1 CMakeDependentOption

```
include(CMakeDependentOption)
cmake_dependent_option(BUILD_TESTS "Build your tests" ON "VAL1;VAL2" OFF)
```

which is equivalent to

```
if(VAL1 AND VAL2)
    set(BUILD_TESTS_DEFAULT ON)
else()
    set(BUILD_TESTS_DEFAULT OFF)
endif()
option(BUILD_TESTS "Build your tests" ${BUILD_TESTS_DEFAULT})
if(NOT BUILD_TESTS_DEFAULT)
    mark_as_advanced(BUILD_TESTS)
endif()
```

### 2.5.5.2 CMakePrintHelpers

```
cmake_print_properties
cmake_print_variables
```

### 2.5.5.3 CheckCXXCompilerFlag

Check whether flag is supported

```
include(CheckCXXCompilerFlag)
check_cxx_compiler_flag(-someflag OUTPUT_VARIABLE)
```

### 2.5.5.4 WriteCompilerDetectionHeader

Look for a list of features that some compilers support and write out a C++ header file that lets you know whether that feature is available

```
write_compiler_detection_header(
  FILE myoutput.h
  PREFIX My
  COMPILERS GNU Clang MSVC Intel
  FEATURES cxx_variadic_templates
)
```

### 2.5.5.5 try\_compile / try\_run

```
try_compile(
  RESULT_VAR
  bindir
  SOURCES
  source.cpp
)
```

## 2.6 Debugging

### 2.6.1 Printing variables

```
message(STATUS "MY_VARIABLE=${MY_VARIABLE}")
# or using module
include(CMakePrintHelpers)
cmake_print_variables(MY_VARIABLE)
cmake_print_properties(
  TARGETS my_target
  PROPERTIES POSITION_INDEPENDENT_CODE
)
```

### 2.6.2 Tracing a run

```
cmake -S . -B build --trace-source=CMakeLists.txt #--trace-expand
```

## 2.7 Including projects

### 2.7.1 Fetch

E.g.: download Catch2

```
FetchContent_Declare(
  catch
  GIT_REPOSITORY https://github.com/catchorg/Catch2.git
  GIT_TAG        v2.13.0
)
# CMake 3.14+
FetchContent_MakeAvailable(catch)
```

## 2.8 Testing

### 2.8.1 General

Enable testing and set a BUILD\_TESTING option

```
if(CMAKE_PROJECT_NAME STREQUAL PROJECT_NAME)
    include(CTest)
endif()
```

Add test folder

```
if(CMAKE_PROJECT_NAME STREQUAL PROJECT_NAME AND BUILD_TESTING)
    add_subdirectory(tests)
endif()
```

Register targets

```
add_test(NAME TestName COMMAND TargetName)
add_test(NAME TestName COMMAND ${TARGET_FILE:${TESTNAME}}>)
```

### 2.8.2 Building as part of the test

```
add_test(
    NAME
        ExampleCMakeBuild
    COMMAND
        "${CMAKE_CTEST_COMMAND}"
        --build-and-test "${My_SOURCE_DIR}/examples/simple"
                        "${CMAKE_CURRENT_BINARY_DIR}/simple"
        --build-generator "${CMAKE_GENERATOR}"
        --test-command "${CMAKE_CTEST_COMMAND}"
)
```

### 2.8.3 Testing frameworks

#### 2.8.3.1 GoogleTest

See [Modern CMake: GoogleTest](#) for reference.

Checkout GoogleTest as submodule

```
git submodule add --branch=release-1.8.0 ../../google/googletest.git extern/googletest
option(PACKAGE_TESTS "Build the tests" ON)
if(PACKAGE_TESTS)
    enable_testing()
    include(GoogleTest)
    add_subdirectory(tests)
endif()
```

#### 2.8.3.2 Catch2

```
# Prepare "Catch" library for other executables
set(CATCH_INCLUDE_DIR ${CMAKE_CURRENT_SOURCE_DIR}/extern/catch)
add_library(Catch2::Catch IMPORTED INTERFACE)
set_property(Catch2::Catch PROPERTY INTERFACE_INCLUDE_DIRECTORIES "${CATCH_INCLUDE_DIR}")
```

#### 2.8.3.3 Doctest

*Doctest* is a replacement for *Catch2* that is supposed to compile much faster and be cleaner. Just replace *Catch2* with *Doctest*.

## 2.9 Exporting and Installing

Allow others to use your library, via

- *Bad way*: Find module
- *Add subproject*: `add_library(MyLib::MyLib ALIAS MyLib)`
- *Exporting*: Using `*Config.cmake` scripts

### 2.9.1 Installing

See [GitBook: Installing](#) Basic target install command (executed by e.g. `make install`)

```
install(TARGETS MyLib
        EXPORT MyLibTargets
        LIBRARY DESTINATION lib
        ARCHIVE DESTINATION lib
        RUNTIME DESTINATION bin
        INCLUDES DESTINATION include
)
```

### 2.9.2 Exporting

See [GitBook: Exporting](#)

### 2.9.3 Packaging

See [GitBook: Packaging](#)

## Chapter 3

# Markdown cheatsheet

Short reference sheet for Markdown. Be aware that some things may not work properly in dependence of the used Markdown flavor.

### 3.1 Header 1

#### 3.1.1 Header 2

##### 3.1.1.1 Header 3

##### 3.1.1.1.1 Header 4

##### Header 5

### 3.2 Emphasis

Emphasis, aka italics, with *asterisks* or *underscores*.

Strong emphasis, aka bold, with **asterisks** or **underscores**.

Combined emphasis with ***asterisks and underscores***.

Strikethrough uses two tildes. ~~Scratch this.~~

### 3.3 Lists

1. First ordered list item
2. Another item
  - Unordered sub-list.

1. Actual numbers don't matter, just that it's a number
  - (a) Ordered sub-list

2. And another item.

You can have properly indented paragraphs within list items. Notice the blank line above, and the leading spaces (at least one, but we'll use three here to also align the raw Markdown).

To have a line break without a paragraph, you will need to use two trailing spaces. Note that this line is separate, but within the same paragraph. (This is contrary to the typical GFM line break behaviour, where trailing spaces are not required.)

- Unordered list can use asterisks
- Or minuses
- Or pluses

### 3.4 Links

`I'm an inline-style link`

`I'm an inline-style link with title`

`I'm a reference-style link`

`You can use numbers for reference-style link definitions`

Or leave it empty and use the `link text itself`.

URLs and URLs in angle brackets will automatically get turned into links. `http://www.example.com` or `http://www.example.com` and sometimes `example.com` (but not on Github, for example).

Some text to show that the reference links can follow later.

### 3.5 Images

Here's our logo (hover to see the title text):

Inline-style:

Reference-style:



## 3.6 Code and Syntax Highlighting

Inline code has back-ticks around it.

```
var s = "JavaScript syntax highlighting";
alert(s);
s = "Python syntax highlighting"
print(s)
No language indicated, so no syntax highlighting.
But let's throw in a <b>tag</b>.
```

## 3.7 Tables

Colons can be used to align columns.

Tables	Are	Cool
col 3 is	right-aligned	\$1600
col 2 is	centered	\$12
zebra stripes	are neat	\$1

There must be at least 3 dashes separating each header cell. The outer pipes (|) are optional, and you don't need to make the raw Markdown line up prettily. You can also use inline Markdown.

Markdown	Less	Pretty
<i>Still</i>	renders	<b>nicely</b>
1	2	3

## 3.8 Blockquotes

Blockquotes are very handy in email to emulate reply text. This line is part of the same quote.

Quote break.

This is a very long line that will still be quoted properly when it wraps. Oh boy let's keep writing to make sure this is long enough to actually wrap for everyone. Oh, you can *put* **Markdown** into a blockquote.

## 3.9 Inline HTML

You can also use raw HTML in your Markdown, and it'll mostly work pretty well.

**Definition list** Is something people use sometimes.

**Markdown in HTML** Does *not* work **very** well. Use HTML *tags*.

### 3.10 Horizontal

Three or more...

Hyphens

Asterisks

Underscores

### 3.11 YouTube Videos

They can't be added directly but you can add an image with a link to the video like this:

Or, in pure Markdown, but losing the image sizing and border:

Referencing a bug by #bugID in your git commit links it to the slip. For example #1.

## Chapter 4

# Project structure

### 4.1 Folders

- **bin**: output executables go here (for the app, tests and spikes)
- **build**: containing all the object files (removed by clean)
- **doc**: documentation files
- **include**: all project header files, all necessary third-party header files (which are not in /usr/local/include)
- **lib**: any library that get compiled by the project, third party or any needed in development
- **spike**: smaller classes or files to test technologies or ideas
- **src**: the application and application's source files
- **test**: all test code files

### 4.2 Files

- **Makefile**: Makefile
- **README.md**: Readme file in markdown syntax

CMake introduction: project structure

- project
  - .gitignore
  - README.md
  - LICENCE.md
  - CMakeLists.txt
  - cmake
    - \* FindSomeLib.cmake
    - \* something\_else.cmake
  - include
    - \* project
      - lib.hpp
  - src
    - \* CMakeLists.txt
    - \* lib.cpp
  - apps

- \* CMakeLists.txt
  - \* app.cpp
- tests
  - \* CMakeLists.txt
  - \* testlib.cpp
- docs
  - \* CMakeLists.txt
- extern
  - \* googletest
- scripts
  - \* helper.py

## Chapter 5

# Unit-Tests

### 5.1 Integrated in CLion

#### 5.1.1 Google Test

See Googletest - google Testing and Mocking Framework [Google test](#) on Github.

#### 5.1.2 Catch

See [Catch Org](#) and [Catch2](#) for a modern, C++ native, header only test framework for unit-tests, TDD and BDD.

#### 5.1.3 Boost.Test

See the [Boost.test](#) for the C++ Boost.Test library, providing both an easy to use and flexible set of interfaces for writing test programs, organizing tests into simple test cases and test suites, and controlling their runtime execution.

#### 5.1.4 Doctest

[Doctest](#) is a new C++ testing framework but is by far the fastest both in compile times (by orders of magnitude) and runtime compared to other feature-rich alternatives. It brings the ability of compiled languages such as D / Rust / Nim to have tests written directly in the production code thanks to a fast, transparent and flexible test runner with a clean interface.



## Chapter 6

# Bug List

Member **main** ()

Bugs ...





## Chapter 7

# Todo List

Member `main ()`

- add a
- add b
- add c

•



## Chapter 8

# Test List

Member `main ()`

Describing test case ...



## Chapter 9

# Namespace Index

### 9.1 Namespace List

Here is a list of all namespaces with brief descriptions:

[constants](#) . . . . . ??



## Chapter 10

# Hierarchical Index

### 10.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Array< T > . . . . .	??
Base . . . . .	??
Derived . . . . .	??
ConceptClass . . . . .	??
exception	
ArrayException . . . . .	??
Exceptions . . . . .	??
IntArray . . . . .	??
SampleClass . . . . .	??
SQRT . . . . .	??
StaticArray< T, size > . . . . .	??
Timer . . . . .	??





## Chapter 11

# Class Index

### 11.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">Array&lt; T &gt;</a>	??
<a href="#">ArrayException</a>	??
<a href="#">Base</a>	??
<a href="#">ConceptClass</a>	??
<a href="#">Derived</a>	??
<a href="#">Exceptions</a>	??
<a href="#">IntArray</a>	??
<a href="#">SampleClass</a>	??
<a href="#">SQRT</a>	??
<a href="#">StaticArray&lt; T, size &gt;</a>	??
<a href="#">Timer</a>	??



## Chapter 12

# File Index

### 12.1 File List

Here is a list of all files with brief descriptions:

include/ <a href="#">ConceptClass.h</a>	??
learningCpp/Basics/ <a href="#">Basics.cpp</a>	??
learningCpp/Basics/ <a href="#">BitManipulation.cpp</a>	??
learningCpp/Basics/ <a href="#">CommandLineArguments.cpp</a>	??
learningCpp/Basics/ <a href="#">Functions.cpp</a>	??
learningCpp/Basics/ <a href="#">Functions.h</a>	??
learningCpp/Basics/ <a href="#">Iterators.cpp</a>	??
learningCpp/Basics/ <a href="#">Macros.cpp</a>	??
learningCpp/Basics/ <a href="#">Pointers.cpp</a>	??
learningCpp/Basics/ <a href="#">ReferenceVariables.cpp</a>	??
learningCpp/Errors/ <a href="#">ErrorHandling.cpp</a>	??
learningCpp/Errors/ <a href="#">ErrorHandling.h</a>	??
learningCpp/Errors/ <a href="#">Exceptions.cpp</a>	??
learningCpp/Errors/ <a href="#">Exceptions.h</a>	??
learningCpp/Errors/ <a href="#">TestingExceptions.cpp</a>	??
learningCpp/OOP/ <a href="#">ConceptClass.cpp</a>	??
learningCpp/OOP/ <a href="#">constants.h</a>	??
learningCpp/OOP/ <a href="#">Inheritance.cpp</a>	??
learningCpp/OOP/ <a href="#">Inheritance.h</a>	??
learningCpp/OOP/ <a href="#">SampleClass.cpp</a>	??
learningCpp/OOP/ <a href="#">SampleClass.h</a>	??
learningCpp/OOP/ <a href="#">TemplateClass.h</a>	??
learningCpp/OOP/ <a href="#">TestInheritance.cpp</a>	??
learningCpp/OOP/ <a href="#">TestSampleClass.cpp</a>	??
learningCpp/OOP/ <a href="#">TestTemplateClass.cpp</a>	??
learningCpp/OOP/ <a href="#">Timer.cpp</a>	??
learningCpp/OOP/ <a href="#">Timer.h</a>	??
learningCpp/StandardLibrary/ <a href="#">SL_Basics.cpp</a>	??
src/ <a href="#">Main.cpp</a>	??
test/ <a href="#">tester.cpp</a>	??



## Chapter 13

# Namespace Documentation

### 13.1 constants Namespace Reference

#### Variables

- constexpr double [pi](#) { 3.141519 }
- constexpr double [avogadro](#) { 6.0221413e23 }

#### 13.1.1 Variable Documentation

##### 13.1.1.1 avogadro

constexpr double constants::avogadro { 6.0221413e23 } [constexpr]  
Definition at line [11](#) of file [constants.h](#).

##### 13.1.1.2 pi

constexpr double constants::pi { 3.141519 } [constexpr]  
Definition at line [10](#) of file [constants.h](#).



# Chapter 14

## Class Documentation

### 14.1 `Array< T >` Class Template Reference

```
#include "TemplateClass.h"
```

#### Public Member Functions

- `Array` (int length)
- `Array` (const `Array` &)=delete
- `Array & operator=` (const `Array` &)=delete
- `~Array` ()
- void `Erase` ()
- T & `operator[]` (int index)
- int `getLength` () const
- void `print` ()

#### Private Attributes

- int `m_length` {}
- T \* `m_data` {}

#### 14.1.1 Detailed Description

```
template<class T>  
class Array< T >
```

#### 14.1.2 Class templates

In order to create classes for different data types use **template classes**.

##### 14.1.2.1 Specialization

**14.1.2.1.1 Function specialization** It is possible to overwrite (individual) member function for

- different data types
- pointer (types)
- ...

**14.1.2.1.2 Class specialization** It is possible to overwrite an entire template class for specific data types. See `class specialization` for reference. Definition at line 36 of file `TemplateClass.h`.

### 14.1.3 Constructor & Destructor Documentation

#### 14.1.3.1 Array() [1/2]

```
template<class T >
Array< T >::Array (
    int length )
```

#### 14.1.3.2 Array() [2/2]

```
template<class T >
Array< T >::Array (
    const Array< T > & ) [delete]
```

#### 14.1.3.3 ~Array()

```
template<class T >
Array< T >::~~Array ( )
```

### 14.1.4 Member Function Documentation

#### 14.1.4.1 Erase()

```
template<class T >
void Array< T >::Erase ( )
```

#### 14.1.4.2 getLength()

```
template<class T >
int Array< T >::getLength ( ) const
```

#### 14.1.4.3 operator=()

```
template<class T >
Array& Array< T >::operator= (
    const Array< T > & ) [delete]
```

#### 14.1.4.4 operator[]()

```
template<class T >
T& Array< T >::operator[] (
    int index )
```

#### 14.1.4.5 print()

```
template<class T >
void Array< T >::print ( )
```



### 14.1.5 Member Data Documentation

#### 14.1.5.1 m\_data

```
template<class T >
T* Array< T >::m_data {} [private]
Definition at line 40 of file TemplateClass.h.
```


#### 14.1.5.2 m\_length

```
template<class T >
int Array< T >::m_length {} [private]
Definition at line 39 of file TemplateClass.h.
The documentation for this class was generated from the following file:
```


- learningCpp/OOP/TemplateClass.h

## 14.2 ArrayException Class Reference

```
#include "Exceptions.h"
Inheritance diagram for ArrayException:
```



Collaboration diagram for ArrayException:



## Public Member Functions

- [ArrayException](#) (std::string\_view error)
- const char \* [what](#) () const noexcept override

## Private Attributes

- std::string [m\\_error](#) {}

### 14.2.1 Detailed Description

### 14.2.2 Exceptions

[Exceptions](#) in C++ are implemented using three keywords that work in conjunction with each other:

- throw
- try
- catch

Exception handling is best used when all of the following are true:

- the error being handled is likely to occur only infrequently.
- the error is serious and execution could not continue otherwise.
- the error cannot be handled at the place where it occurs.
- there isn't a good alternative way to return an error code back to the caller.

#### 14.2.2.1 Throwing exceptions

A throw statement is used to signal that an exception or error case has occurred, e.g.:

```
{C++}
throw -1; // throw a literal integer value
throw ENUM_INVALID_INDEX; // throw an enum value
throw "Can not take square root of negative number"; // throw a literal C-style (const char*) string
throw dX; // throw a double variable that was previously defined
throw MyException("Fatal Error"); // Throw an object of class MyException
```

#### 14.2.2.2 Try blocks

**Try blocks** act as observers, looking for any exceptions that are thrown within the block, e.g.:

```
{C++}
try
{
    // Statements that may throw exceptions you want to handle go here
    throw -1; // here's a trivial throw statement
}
```

#### 14.2.2.3 Handling exceptions

Actually handling exceptions is the job of the catch block(s). The catch keyword is used to define a block of code (called a catch block) that handles exceptions for a single data type, e.g.:

```
{C++}
catch (int x)
{
    // Handle an exception of type int here
    std::cerr << "We caught an int exception with value" << x << '\n';
}
```

#### 14.2.2.4 Throwing exceptions outside a try-block

...

### 14.2.2.5 Catch all handler

To catch uncaught exceptions, not regarding the type of exception:

```
{C++}
catch (...) // catch-all handler
{
    std::cout << "We caught an exception of an undetermined type\n";
}
```

### 14.2.2.6 Exception classes

...

### 14.2.2.7 std::exception

Many of the classes and operators in the standard library throw exception classes on failure. For example, operator new can throw std::bad\_alloc if it is unable to allocate enough memory. A failed dynamic\_cast will throw std::bad\_cast. And so on. As of C++17, there are 25 different exception classes that can be thrown, with more being added in each subsequent language standard.

**It is possible to extend std::exception, by inheriting.**

### 14.2.2.8 Rethrowing

When rethrowing the same exception, use the *throw* keyword by itself.

### 14.2.2.9 noexcept

See [exception specifier](#).

It is possible to declare functions non-throwing using the **noexcept** specifier.

Definition at line 105 of file [Exceptions.h](#).

## 14.2.3 Constructor & Destructor Documentation

### 14.2.3.1 ArrayException()

```
ArrayException::ArrayException (
    std::string_view error )
```

Definition at line 8 of file [Exceptions.cpp](#).

```
00009         : m_error{error}
00010 {
00011 }
```

## 14.2.4 Member Function Documentation

### 14.2.4.1 what()

```
const char* ArrayException::what ( ) const [inline], [override], [noexcept]
```

Definition at line 113 of file [Exceptions.h](#).

```
00113         {
00114             return m_error.c_str();
00115     }
```

## 14.2.5 Member Data Documentation

#### 14.2.5.1 m\_error

```
std::string ArrayException::m_error {} [private]
```

Definition at line 108 of file [Exceptions.h](#).


The documentation for this class was generated from the following files:

- [learningCpp/Errors/Exceptions.h](#)
- [learningCpp/Errors/Exceptions.cpp](#)

### 14.3 Base Class Reference

```
#include "Inheritance.h"
```

Inheritance diagram for Base:



#### Public Member Functions

- [Base](#) (int id=0, int var\_private=0, int var\_protected=0, int var\_public=0)
- int [getId](#) () const
- virtual void [print](#) ()

#### Public Attributes

- int [m\\_public](#)

#### Protected Member Functions

- int [getPrivate](#) () const

#### Protected Attributes

- int [m\\_protected](#)

#### Private Attributes

- int [m\\_id](#)
- int [m\\_private](#)

#### 14.3.1 Detailed Description

#### 14.3.2 Inheritance

##### 14.3.2.1 Access specifiers

There are three access specifiers

- **public**: accessible from base and derived class, and from outside
- **protected**: accessible from base class and derived class
- **private**: accessible from base class

```
{C++}
class Derived: <access specifier> Base
{
}
```

#### 14.3.2.1.1 Public inheritance

- public --> public
- protected --> protected
- private --> inaccessible

#### 14.3.2.1.2 Protected inheritance

- public --> protected
- protected --> protected
- private --> inaccessible

#### 14.3.2.1.3 Private Inheritance

- public --> private
- protected --> private
- private --> inaccessible

#### 14.3.2.2 Multiple inheritance

C++ supports **multiple inheritance**, but many problems can occur. Since most of the problems solvable with multiple inheritance can be solved without multiple inheritance, prefer solutions without multiple inheritance.

**Avoid multiple inheritance unless alternatives lead to more complexity.**

#### 14.3.2.3 Virtual functions and Polymorphism

A **virtual function** is a special type of function that, when called, resolves to the most-derived version of the function that exists between the base and derived class. This capability is known as **polymorphism**.

**Attention:** Resolving a virtual function call takes longer than resolving a regular one. Furthermore, the compiler also has to allocate an extra pointer for each class object that has one or more virtual functions.

When dealing with inheritance, (overwritten) **destructors** should always be virtual!

#### 14.3.2.4 Override and final specifiers

To help address the issue of functions that are meant to be overrides but aren't, C++11 introduced the **override** specifier. The override specifier can be applied to any override function by placing the specifier in the same place const would go.

There may be cases where you don't want someone to be able to override a virtual function, or inherit from a class. The **final** specifier can be used to tell the compiler to enforce this. If the user tries to override a function or inherit from a class that has been specified as final, the compiler will give a compile error.

#### 14.3.2.5 Pure virtual functions, abstract base classes and interface classes

**14.3.2.5.1 Pure virtual functions** C++ allows to create a special kind of virtual function called a pure virtual function (or abstract function) that has no body at all! A pure virtual function simply acts as a placeholder that is meant to be redefined by derived classes.

**Any class with at least one pure virtual function becomes an abstract base class and cannot be instantiated**

**14.3.2.5.2 Abstract base classes** **Abstract base classes** can not be instantiated!

**14.3.2.5.3 Interface classes** An **interface class** has no member variables and only pure virtual (member) functions. Thus, interface classes are pure definitions and have no actual implementations.

Definition at line 99 of file [Inheritance.h](#).

## 14.3.3 Constructor & Destructor Documentation

### 14.3.3.1 Base()

```
Base::Base (
    int id = 0,
    int var_private = 0,
    int var_protected = 0,
    int var_public = 0 )
```

Definition at line 7 of file [Inheritance.cpp](#).

```
00008 : m_id{ id }, m_private{ var_private }, m_protected{ var_protected },
00009      m_public{ var_public }
00010 {
00011     std::cout << "Base constructor called ..." << std::endl;
00012 }
```

## 14.3.4 Member Function Documentation

### 14.3.4.1 getId()

```
int Base::getId ( ) const
```

Definition at line 14 of file [Inheritance.cpp](#).

```
00014 {
00015     return m_id;
00016 }
```

### 14.3.4.2 getPrivate()

```
int Base::getPrivate ( ) const [protected]
```

Definition at line 18 of file [Inheritance.cpp](#).

```
00018 {
00019     std::cout << "getPrivate() from Base" << std::endl;
00020     return m_private;
00021 }
```

### 14.3.4.3 print()

```
void Base::print ( ) [virtual]
```

Reimplemented in [Derived](#).

Definition at line 23 of file [Inheritance.cpp](#).

```
00023 {
00024     std::cout << "Print from Base class!" << std::endl;
00025 }
```

## 14.3.5 Member Data Documentation

#### 14.3.5.1 m\_id

```
int Base::m_id [private]
```

Definition at line 102 of file [Inheritance.h](#).

#### 14.3.5.2 m\_private

```
int Base::m_private [private]
```

Definition at line 103 of file [Inheritance.h](#).

#### 14.3.5.3 m\_protected

```
int Base::m_protected [protected]
```

Definition at line 105 of file [Inheritance.h](#).

#### 14.3.5.4 m\_public

```
int Base::m_public
```

Definition at line 108 of file [Inheritance.h](#).

The documentation for this class was generated from the following files:

- [learningCpp/OOP/Inheritance.h](#)
- [learningCpp/OOP/Inheritance.cpp](#)

## 14.4 ConceptClass Class Reference

```
#include "ConceptClass.h"
```

### Public Member Functions

- [ConceptClass](#) (int a, int b)

### Public Attributes

- int [member\\_a](#)
- int [member\\_b](#)

#### 14.4.1 Detailed Description

Definition at line 12 of file [ConceptClass.h](#).

#### 14.4.2 Constructor & Destructor Documentation

##### 14.4.2.1 ConceptClass()

```
ConceptClass::ConceptClass (  
    int a,  
    int b )
```

Constructor

Detailed description for constructor.

##### Parameters

<i>a</i>	
<i>b</i>	

Definition at line 3 of file [ConceptClass.cpp](#).

```
00003 {  
00004     member_a = a;  
00005     member_b = b;  
00006 }
```

### 14.4.3 Member Data Documentation

#### 14.4.3.1 member\_a

```
int ConceptClass::member_a
```

##### Parameters

<i>member</i>	a
---------------	---

Definition at line 22 of file [ConceptClass.h](#).

#### 14.4.3.2 member\_b

```
int ConceptClass::member_b
```

##### Parameters

<i>member</i>	b
---------------	---

Definition at line 24 of file [ConceptClass.h](#).


The documentation for this class was generated from the following files:

- [include/ConceptClass.h](#)
- [learningCpp/OOP/ConceptClass.cpp](#)

## 14.5 Derived Class Reference


```
#include "Inheritance.h"
```

Inheritance diagram for Derived:





Collaboration diagram for Derived:



## Public Member Functions

- [Derived](#) (double cost=0.0, int id=0, int var\_private=0, int var\_protected=0, int var\_public=0)
- double [getCost](#) () const
- double [getProtected](#) () const
- double [getPrivate](#) () const
- virtual void [print](#) ()

## Private Attributes

- double [m\\_cost](#)

## Additional Inherited Members

### 14.5.1 Detailed Description

Definition at line 117 of file [Inheritance.h](#).

### 14.5.2 Constructor & Destructor Documentation

#### 14.5.2.1 Derived()

```
Derived::Derived (  
    double cost = 0.0,  
    int id = 0,  
    int var_private = 0,  
    int var_protected = 0,  
    int var_public = 0 )
```

Definition at line 29 of file [Inheritance.cpp](#).

```
00030     : Base{ id, var_private, var_protected, var_public }, // Call Base(int) constructor with value  
    id!  
00031     m_cost{ cost }  
00032 {  
00033     std::cout << "Derived constructor called ..." << std::endl;  
00034 }
```

### 14.5.3 Member Function Documentation

#### 14.5.3.1 `getCost()`

```
double Derived::getCost ( ) const
```

Definition at line 36 of file [Inheritance.cpp](#).

```
00036     {  
00037         return m_cost;  
00038     }
```

#### 14.5.3.2 `getPrivate()`

```
double Derived::getPrivate ( ) const
```

Definition at line 44 of file [Inheritance.cpp](#).

```
00044     {  
00045         std::cout << "getPrivate() from Derived" << std::endl;  
00046         return Base::getPrivate();  
00047     }
```

Here is the call graph for this function:



#### 14.5.3.3 `getProtected()`

```
double Derived::getProtected ( ) const
```

Definition at line 40 of file [Inheritance.cpp](#).

```
00040     {  
00041         return m_protected;  
00042     }
```

#### 14.5.3.4 `print()`

```
void Derived::print ( ) [virtual]
```

Reimplemented from [Base](#).

Definition at line 49 of file [Inheritance.cpp](#).

```
00049     {  
00050         std::cout << "Print from Derived class!" << std::endl;  
00051     }
```

### 14.5.4 Member Data Documentation

#### 14.5.4.1 `m_cost`

```
double Derived::m_cost [private]
```

Definition at line 120 of file [Inheritance.h](#).

The documentation for this class was generated from the following files:

- [learningCpp/OOP/Inheritance.h](#)
- [learningCpp/OOP/Inheritance.cpp](#)

## 14.6 Exceptions Class Reference

```
#include "Exceptions.h"
```

### 14.6.1 Detailed Description

Definition at line 139 of file [Exceptions.h](#).

The documentation for this class was generated from the following file:

- learningCpp/Errors/[Exceptions.h](#)

## 14.7 IntArray Class Reference

```
#include "Exceptions.h"
```

### Public Member Functions

- [IntArray](#) ()
- int [getLength](#) () const
- int & [operator\[\]](#) (const int index)

### Private Attributes

- int [m\\_data](#) [3]

### 14.7.1 Detailed Description

Definition at line 118 of file [Exceptions.h](#).

### 14.7.2 Constructor & Destructor Documentation

#### 14.7.2.1 IntArray()

```
IntArray::IntArray ( ) [inline]
```

Definition at line 125 of file [Exceptions.h](#).

```
00125 {}
```

### 14.7.3 Member Function Documentation

#### 14.7.3.1 getLength()

```
int IntArray::getLength ( ) const
```

Definition at line 15 of file [Exceptions.cpp](#).

```
00015 {  
00016     return 3;  
00017 }
```

#### 14.7.3.2 operator[]()

```
int & IntArray::operator[] (   
                                const int index )
```

Definition at line 19 of file [Exceptions.cpp](#).

```
00020 {  
00021     if (index < 0 || index >= getLength())  
00022         throw ArrayException("Invalid index");  
00023 }
```

```
00024     return m_data[index];
00025 }
```

Here is the call graph for this function:



## 14.7.4 Member Data Documentation

### 14.7.4.1 m\_data

```
int IntArray::m_data[3] [private]
```

Definition at line 122 of file [Exceptions.h](#).

The documentation for this class was generated from the following files:

- [learningCpp/Errors/Exceptions.h](#)
- [learningCpp/Errors/Exceptions.cpp](#)

## 14.8 SampleClass Class Reference

```
#include "SampleClass.h"
```

### Public Types

- enum [FruitType](#) { [APPLE](#), [BANANA](#), [CHERRY](#) }

### Public Member Functions

- int [get\\_member\\_a](#) ()
- int [get\\_member\\_b](#) ()
- void [set\\_member\\_a](#) (int a)
- void [set\\_member\\_b](#) (int b)
- void [set\\_members\\_using\\_this](#) (int [member\\_a](#), int [member\\_b](#))
- void [const\\_member\\_function](#) () const
- [SampleClass](#) ()
- [SampleClass](#) (int a, int b=0)
- [SampleClass](#) (int a, int b, int c)
- [SampleClass](#) (const [SampleClass](#) &sample\_class)
- [~SampleClass](#) ()
- int [operator\(\)](#) (int i)

### Static Public Member Functions

- static void [static\\_member\\_function](#) ()

### Static Public Attributes

- static int [static\\_member\\_variable](#) = 5

## Private Attributes

- int `member_a` { 0 }
- int `member_b` { 0 }

## Friends

- void `friend_function` (`SampleClass` &sample\_class)
- `SampleClass` `operator+` (const `SampleClass` &s\_1, const `SampleClass` &s\_2)
- `std::ostream` & `operator<<` (`std::ostream` &out, const `SampleClass` &sample\_class)

### 14.8.1 Detailed Description

### 14.8.2 Classes - OOP

Use structs for data-only objects and classes otherwise!

#### 14.8.2.1 Properties

- member variables are private per default
  - public in case of structs
- if no constructor is given, a default constructor is created
- getter should either return by value or reference
- const class objects can only call const member functions

#### 14.8.2.2 Friend functions and classes

See [Friend functions and classes](#) for reference!

Classes keep your data private and encapsulated. However, in some situations you need to have classes and functions outside of those classes that need to work closely together.

For doing this, without exposing the function use the **friend** identifier.

It is possible to have

- friend functions
- friend member functions
- friend classes
- ...

#### 14.8.2.3 Overloading operators

[Overloading assignment operator](#)

#### 14.8.2.4 Shallow vs. deep copy

The default copy mechanism for classes is **memberwise** copy (also called **shallow copy**), which works for simple classes, without dynamically reserved memory, very good.

However, a **deep copy** allocates memory for the copy and then copies the actual value, so that the copy lives in distinct memory from the source. This requires to write copy constructors and overloaded assignment operators.

- The default copy constructor and default assignment operators do shallow copies, which is fine for classes that contain no dynamically allocated variables.
- Classes with dynamically allocated variables need to have a copy constructor and assignment operator that do a deep copy.
- Favor using classes in the standard library over doing your own memory management.

#### 14.8.2.5 Object relations

Property/type	Composition	Composition	Composition	Composition
relationship	whole/part	whole/part	unrelated	unrelated
members belong to multiple classes	No	Yes	Yes	Yes
members existence managed by class	Yes	No	No	No
directionality	Uni	Uni	Uni or bi	Uni
relationship verb	part-of	has-a	uses-a	depends-on

**14.8.2.5.1 Composition** To qualify as a composition, an object and a part must have the following relationship:

- The part (member) is part of the object (class)
- The part (member) can only belong to one object (class) at a time
- The part (member) has its existence managed by the object (class)
- The part (member) does not know about the existence of the object (class)

Therefore:

- Typically use normal member variables
- Can use pointer members if the class handles object allocation/deallocation itself
- Responsible for creation/destruction of parts

**14.8.2.5.2 Aggregation** To qualify as an aggregation, a whole object and its parts must have the following relationship:

- The part (member) is part of the object (class)
- The part (member) can belong to more than one object (class) at a time
- The part (member) does not have its existence managed by the object (class)
- The part (member) does not know about the existence of the object (class)

Therefore:

- Typically use pointer or reference members that point to or reference objects that live outside the scope of the aggregate class
- Not responsible for creating/destroying parts

**14.8.2.5.3 Association**

- To qualify as an association, an object and another object must have the following relationship:
- The associated object (member) is otherwise unrelated to the object (class)
- The associated object (member) can belong to more than one object (class) at a time
- The associated object (member) does not have its existence managed by the object (class)\*
- The associated object (member) may or may not know about the existence of the object (class)

### 14.8.2.6 Container classes

See [Container classes](#)

Container classes typically implement a fairly standardized minimal set of functionality. Most well-defined containers will include functions that:

- Create an empty container (via a constructor)
- Insert a new object into the container
- Remove an object from the container
- Report the number of objects currently in the container
- Empty the container of all objects
- Provide access to the stored objects
- Sort the elements (optional)

Definition at line 128 of file [SampleClass.h](#).

## 14.8.3 Member Enumeration Documentation

### 14.8.3.1 FruitType

enum [SampleClass::FruitType](#)

Enumerator

APPLE	
BANANA	
CHERRY	

Definition at line 172 of file [SampleClass.h](#).

```
00172     {
00173         APPLE,
00174         BANANA,
00175         CHERRY
00176     };
```

## 14.8.4 Constructor & Destructor Documentation

### 14.8.4.1 SampleClass() [1/4]

[SampleClass::SampleClass \( \)](#)

Definition at line 7 of file [SampleClass.cpp](#).

```
00007     {
00008         std::cout << "Default constructor was called ..." << std::endl;
00009         member_a = 0;
00010         member_b = 0;
00011     }
```

### 14.8.4.2 SampleClass() [2/4]

[SampleClass::SampleClass \(](#)

```
    int a,
    int b = 0 )
```

Definition at line 21 of file [SampleClass.cpp](#).

```
00022 : member_a{ a }, member_b{ b }
```



```

00023 {
00024     std::cout << "Constructor: SampleClass(" << a << ", " << b << ") ..." << std::endl;
00025 }

```

#### 14.8.4.3 SampleClass() [3/4]

```

SampleClass::SampleClass (
    int a,
    int b,
    int c )

```

Definition at line 27 of file [SampleClass.cpp](#).

```

00027 : SampleClass{ a, b } {
00028     std::cout << "Constructor: SampleClass(" << a << ", " << b << ", " << c << ") ..." << std::endl;
00029 }

```

#### 14.8.4.4 SampleClass() [4/4]

```

SampleClass::SampleClass (
    const SampleClass & sample_class )

```

Definition at line 36 of file [SampleClass.cpp](#).

```

00036 :
00037     member_a(sample_class.member_a), member_b(sample_class.member_b)
00038 {
00039     std::cout << "Copy constructor called\n"; // just to prove it works
00040 }

```

#### 14.8.4.5 ~SampleClass()

```

SampleClass::~~SampleClass ( )

```

Definition at line 32 of file [SampleClass.cpp](#).

```

00032 {
00033     std::cout << "Destructor was called" << std::endl;
00034 }

```

### 14.8.5 Member Function Documentation

#### 14.8.5.1 const\_member\_function()

```

void SampleClass::const_member_function ( ) const

```

Definition at line 65 of file [SampleClass.cpp](#).

```

00065 {
00066     std::cout << "This is a const member function!" << std::endl;
00067 }

```

#### 14.8.5.2 get\_member\_a()

```

int SampleClass::get_member_a ( )

```

Definition at line 42 of file [SampleClass.cpp](#).

```

00042 {
00043     return member_a;
00044 }

```

#### 14.8.5.3 get\_member\_b()

```

int SampleClass::get_member_b ( )

```

Definition at line 46 of file [SampleClass.cpp](#).

```

00046 {
00047     return member_b;
00048 }

```

#### 14.8.5.4 operator()

```
int SampleClass::operator() (
    int i )
```

Definition at line 92 of file [SampleClass.cpp](#).

```
00092     {
00093         return (member_a += i);
00094     }
```

#### 14.8.5.5 set\_member\_a()

```
void SampleClass::set_member_a (
    int a )
```

Definition at line 50 of file [SampleClass.cpp](#).

```
00050     {
00051         std::cout << "set member_a to: " << a << std::endl;
00052         member_a = a;
00053     }
```

#### 14.8.5.6 set\_member\_b()

```
void SampleClass::set_member_b (
    int b )
```

Definition at line 55 of file [SampleClass.cpp](#).

```
00055     {
00056         std::cout << "set member_b to: " << b << std::endl;
00057         member_b = b;
00058     }
```

#### 14.8.5.7 set\_members\_using\_this()

```
void SampleClass::set_members_using_this (
    int member_a,
    int member_b )
```

Definition at line 60 of file [SampleClass.cpp](#).

```
00060     {
00061         this->member_a = member_a;
00062         this->member_b = member_b;
00063     }
```

#### 14.8.5.8 static\_member\_function()

```
void SampleClass::static_member_function ( ) [static]
```

Definition at line 69 of file [SampleClass.cpp](#).

```
00069     {
00070         std::cout << "This is a static member function" << std::endl;
00071     }
```

### 14.8.6 Friends And Related Function Documentation

#### 14.8.6.1 friend\_function

```
void friend_function (
    SampleClass & sample_class ) [friend]
```

Definition at line 73 of file [SampleClass.cpp](#).

```
00073     {
00074         std::cout << "This is a friend function" << std::endl;
00075         std::cout << "Accessing private member member_a: " << sample_class.member_a << std::endl;
00076     }
```

### 14.8.6.2 operator+

```
SampleClass operator+ (
    const SampleClass & s_1,
    const SampleClass & s_2 ) [friend]
```

Definition at line 78 of file [SampleClass.cpp](#).

```
00078 {
00079     std::cout << "overloaded operator+ for SampleClass!" << std::endl;
00080     return SampleClass(s_1.member_a + s_2.member_a, s_1.member_b + s_2.member_b);
00081 }
```

### 14.8.6.3 operator<<

```
std::ostream& operator<< (
    std::ostream & out,
    const SampleClass & sample_class ) [friend]
```

Definition at line 83 of file [SampleClass.cpp](#).

```
00083 {
00084
00085     out << std::endl
00086         << "member_a = " << sample_class.member_a << std::endl
00087         << "member_b = " << sample_class.member_b << std::endl;
00088
00089     return out;
00090 }
```

## 14.8.7 Member Data Documentation

### 14.8.7.1 member\_a

```
int SampleClass::member_a { 0 } [private]
```

Definition at line 130 of file [SampleClass.h](#).

### 14.8.7.2 member\_b

```
int SampleClass::member_b { 0 } [private]
```

Definition at line 131 of file [SampleClass.h](#).

### 14.8.7.3 static\_member\_variable

```
int SampleClass::static_member_variable = 5 [static]
```

Definition at line 134 of file [SampleClass.h](#).

The documentation for this class was generated from the following files:

- [learningCpp/OOP/SampleClass.h](#)
- [learningCpp/OOP/SampleClass.cpp](#)

## 14.9 SQRT Class Reference

```
#include "Exceptions.h"
```

### Static Public Member Functions

- static double [mySqrt](#) (double x)

### 14.9.1 Detailed Description

Definition at line 133 of file [Exceptions.h](#).

## 14.9.2 Member Function Documentation

### 14.9.2.1 mySqrt()

```
double Sqrt::mySqrt (
    double x ) [static]
```

Definition at line 28 of file [Exceptions.cpp](#).

```
00028 {
00029     // If the user entered a negative number, this is an error condition
00030     if (x < 0.0)
00031         throw "Can not take sqrt of negative number"; // throw exception of type const char*
00032
00033     return sqrt(x);
00034 }
```

The documentation for this class was generated from the following files:

- [learningCpp/Errors/Exceptions.h](#)
- [learningCpp/Errors/Exceptions.cpp](#)

## 14.10 StaticArray< T, size > Class Template Reference

```
#include "TemplateClass.h"
```

### Public Member Functions

- T \* [getArray](#) ()
- T & [operator\[\]](#) (int index)

### Private Attributes

- T [m\\_array](#) [size]

### 14.10.1 Detailed Description

```
template<class T, int size>
class StaticArray< T, size >
```

Definition at line 63 of file [TemplateClass.h](#).

## 14.10.2 Member Function Documentation

### 14.10.2.1 getArray()

```
template<class T , int size>
T* StaticArray< T, size >::getArray ( )
```

### 14.10.2.2 operator[]()

```
template<class T , int size>
T& StaticArray< T, size >::operator[] (
    int index )
```

## 14.10.3 Member Data Documentation

### 14.10.3.1 m\_array

```
template<class T , int size>
T StaticArray< T, size >::m_array[size] [private]
```

Definition at line 67 of file [TemplateClass.h](#).

The documentation for this class was generated from the following file:

- [learningCpp/OOP/TemplateClass.h](#)

## 14.11 Timer Class Reference

```
#include "Timer.h"
```

### Public Member Functions

- [Timer](#) ()
- void [reset](#) ()
- double [elapsed](#) () const

### Private Types

- using [clock\\_t](#) = std::chrono::high\_resolution\_clock
- using [second\\_t](#) = std::chrono::duration< double, std::ratio< 1 > >

### Private Attributes

- std::chrono::time\_point< [clock\\_t](#) > [m\\_beg](#)

### 14.11.1 Detailed Description

Definition at line 11 of file [Timer.h](#).

### 14.11.2 Member Typedef Documentation

#### 14.11.2.1 clock\_t

```
using Timer::clock\_t = std::chrono::high_resolution_clock [private]
```

Definition at line 14 of file [Timer.h](#).

#### 14.11.2.2 second\_t

```
using Timer::second\_t = std::chrono::duration<double, std::ratio<1> > [private]
```

Definition at line 15 of file [Timer.h](#).

### 14.11.3 Constructor & Destructor Documentation

#### 14.11.3.1 Timer()

```
Timer::Timer ( )
```

Definition at line 7 of file [Timer.cpp](#).

```
00007         : m\_beg(clock_t::now())
00008 {
00009 }
```

## 14.11.4 Member Function Documentation

### 14.11.4.1 elapsed()

double Timer::elapsed ( ) const

Definition at line 16 of file [Timer.cpp](#).

```
00017 {  
00018     return std::chrono::duration_cast<second_t>(clock_t::now() - m_beg).count();  
00019 }
```

### 14.11.4.2 reset()

void Timer::reset ( )

Definition at line 11 of file [Timer.cpp](#).

```
00012 {  
00013     m_beg = clock_t::now();  
00014 }
```

## 14.11.5 Member Data Documentation

### 14.11.5.1 m\_beg

std::chrono::time\_point<[clock\\_t](#)> Timer::m\_beg [private]

Definition at line 17 of file [Timer.h](#).

The documentation for this class was generated from the following files:

- [learningCpp/OOP/Timer.h](#)
- [learningCpp/OOP/Timer.cpp](#)

## Chapter 15

# File Documentation

### 15.1 documents/CMakeIntroduction.md File Reference

### 15.2 documents/Markdown.md File Reference

### 15.3 documents/structure.md File Reference

### 15.4 documents/Unit-Tests.md File Reference

### 15.5 include/ConceptClass.h File Reference

#### Classes

- class [ConceptClass](#)


### 15.6 ConceptClass.h

```
00001 #ifndef CPP_CONCEPTS_PROJECT_CONCEPTCLASS_H
00002 #define CPP_CONCEPTS_PROJECT_CONCEPTCLASS_H
00003
00012 class ConceptClass {
00013 public:
00019     ConceptClass(int a,int b);
00020
00022     int member_a;
00024     int member_b;
00025 };
00026
00027
00028 #endif //CPP_CONCEPTS_PROJECT_CONCEPTCLASS_H
```

### 15.7 learningCpp/Basics/Basics.cpp File Reference

```
#include <iostream>
#include <cstdint>
#include <chrono>
#include <thread>
#include <array>
```

Include dependency graph for Basics.cpp:



## Functions

- int [main](#) ()

## Variables

- int [g\\_global\\_integer](#) { 1 }
- static int [g\\_x\\_1](#)
- const int [g\\_x\\_2](#) { 2 }

## 15.7.1 Function Documentation

### 15.7.1.1 main()

[int main \( \)](#)  
[include order Initialization](#)  
[Fundamental data types](#)  
[escape sequences](#)  
[Conditional operator](#)  
[Namespaces](#)  
[Static local variables](#)  
[Typedefs and type aliases](#)  
[Type conversion](#)  
[Enumerations](#)  
[Structs](#)  
[Control flows](#)  
[Arrays](#)

Definition at line 31 of file [Basics.cpp](#).

```

00031     {
00032
00033         // copy initialization
00034         int a = 1;
00035         // direct initialization
00036         int b(1);
00037         // list (uniform/brace) initialization
00038         //direct
00039         int c_1{1};
00040         //copy
00041         int c_2 = {1};
00042         // floating point
00043         float float_a = 3.14159; // at least 4 bytes
00044         double float_b = 3.14159; // at least 8 bytes
00045         long double float_c = 3.14159; // at least 8 bytes
00046         // Inf represents Infinity
00047         // NaN represents Not a Number
00048     }
  
```



```

00052
00053 // integral characters
00054 char char_a = 'c'; // always 1 byte
00055 wchar_t char_b = 'c'; // at least 1 byte
00056 //char8_t char_c = 'c'; // C++20
00057 //char16_t char_d = 'c'; // C++11 // at least 2 bytes
00058 //char32_t char_e = 'c'; // C++11 // at least 4 bytes
00059
00060 // 0b12 --> binary
00061 // 012 --> octal
00062 // 0x12 --> hexadecimal
00063 // use std::dec , std::oct , std::hex
00064
00065 // Integers
00066 short int_a = 1; // at least 2 bytes
00067 int int_b = 1; // at least 2 bytes
00068 long int_c = 1; // at least 4 bytes
00069 //long long int_d = 1; // C++11
00070
00071 // Boolean
00072 bool bool_a = true; // or false
00073
00074 // Null pointer
00075 //std::nullptr_t null_pointer = nullptr;
00076
00077 // void
00078
00079 // using cstdint
00080 //std::int8_t
00081 //std::uint8_t
00082 //std::int16_t
00083 //std::uint16_t
00084 //std::int32_t
00085 //std::uint32_t
00086 //std::int64_t
00087 //std::uint64_t
00088
00089 // there is also the std::int_fast#_t providing the fastest signed integer with at least # bits
00090 // there is also the std::int_least#_t providing the smallest signed integer with at least # bits
00091
00092 std::cout << "bool:\t\t" << sizeof(bool) << " bytes\n";
00093 std::cout << "char:\t\t" << sizeof(char) << " bytes\n";
00094 std::cout << "wchar_t:\t\t" << sizeof(wchar_t) << " bytes\n";
00095 std::cout << "char16_t:\t\t" << sizeof(char16_t) << " bytes\n"; // C++11 only
00096 std::cout << "char32_t:\t\t" << sizeof(char32_t) << " bytes\n"; // C++11 only
00097 std::cout << "short:\t\t" << sizeof(short) << " bytes\n";
00098 std::cout << "int:\t\t" << sizeof(int) << " bytes\n";
00099 std::cout << "long:\t\t" << sizeof(long) << " bytes\n";
00100 std::cout << "long long:\t\t" << sizeof(long long) << " bytes\n"; // C++11 only
00101 std::cout << "float:\t\t" << sizeof(float) << " bytes\n";
00102 std::cout << "double:\t\t" << sizeof(double) << " bytes\n";
00103 std::cout << "long double:\t\t" << sizeof(long double) << " bytes\n";
00104
00105 // use const
00106 //const int const_int = 1;
00107 // for variables that should not be modifiable after initialization
00108 // and whose initializer is NOT known at compile-time
00109
00110 // use constexpr
00111 //constexpr int constexpr_int = 1;
00112 // for variables that should not be modifiable after initialization
00113 // and whose initializer is known at compile-time
00114 for (int i = 0; i < 5; i++) {
00115     std::this_thread::sleep_for(std::chrono::milliseconds(250));
00116     std::cout << "\a"; // makes an alert
00117 }
00118
00119 std::cout << "Backspace \b" << std::endl;
00120 std::cout << "Formfeed \f" << std::endl;
00121 std::cout << "Newline \n" << std::endl;
00122 std::cout << "Carriage return \r" << std::endl;
00123 std::cout << "Horizontal \t tab" << std::endl;
00124 std::cout << "Vertical tab \v" << std::endl;
00125 std::cout << "Single quote \' or double quote \"" << std::endl;
00126 std::cout << "Octal number \12" << std::endl;
00127 std::cout << "Hex number \x14" << std::endl;
00128
00129 int x_1 = 2;
00130 int x_2 = 3;
00131 int max_x = (x_1 > x_2) ? x_1 : x_2;
00132
00133 // define a namespace
00134 namespace namespace_1 {
00135     // nested namespace
00136     namespace namespace_1_nested {
00137
00138     }
00139 }
00140
00141 // accessible using "::"

```

```

00148 // namespace alias
00149 // namespace nested_namespace = namespace_1::namespace_1_nested;
00154 // static local variables are not destroyed when out of scope (in contrast to automatic)
00155 static int var_1 { 1 };
00156 // AVOID using static variables unless the variable never needs to be reset
00161 typedef double distance_t; // define distance_t as an alias for type double
00162 //which is equivalent to: using distance_t = double;
00163 // The following two statements are equivalent:
00164 // double howFar; //equivalent to
00165 distance_t howFar;
00171 // IMPLICIT type conversion (coercion)
00172 float f_int { 3 }; // initializing floating point variable with int 3
00173
00174 // EXPLICIT type conversion
00175 // static_cast
00176 int i1 { 10 };
00177 int i2 { 4 };
00178 // convert an int to a float so we get floating point division rather than integer division
00179 float f { static_cast<float>(i1) / i2 };
00180
00184 enum Color
00185 {
00186     color_black, // assigned 0
00187     color_red, // assigned 1
00188     color_blue, // assigned 2
00189     color_green, // assigned 3
00190     color_white, // assigned 4
00191     color_cyan, // assigned 5
00192     color_yellow, // assigned 6
00193     color_magenta // assigned 7
00194 };
00195 Color paint{ color_white };
00196 std::cout << paint;
00197
00198 // enum classes (scoped enumerations)
00199 enum class Fruit
00200 {
00201     banana, // banana is inside the scope of Fruit
00202     apple
00203 };
00204 Fruit fruit{ Fruit::banana }; // note: banana is not directly accessible any more, we have to use
Fruit::banana
00208 struct Employee
00209 {
00210     short id;
00211     int age;
00212     double wage;
00213 };
00214
00215 Employee joe{ 1, 32, 60000.0 }; // joe.id = 1, joe.age = 32, joe.wage = 60000.0
00216 Employee frank{ 2, 28 }; // frank.id = 2, frank.age = 28, frank.wage = 0.0 (default
initialization)
00217
00218 //Employee joe; // create an Employee struct for Joe
00219 //joe.id = 14; // assign a value to member id within struct joe
00220 //joe.age = 32; // assign a value to member age within struct joe
00221 //joe.wage = 24.15; // assign a value to member wage within struct joe
00222
00223 //Employee frank; // create an Employee struct for Frank
00224 //frank.id = 15; // assign a value to member id within struct frank
00225 //frank.age = 28; // assign a value to member age within struct frank
00226 //frank.wage = 18.27; // assign a value to member wage within struct frank
00227
00228 // nested structs
00229 struct Company
00230 {
00231     Employee CEO; // Employee is a struct within the Company struct
00232     int numberOfEmployees;
00233 };
00234 Company myCompany{{ 1, 42, 60000.0 }, 5 };
00238 // halt (using <cstdlib>)
00239 //std::exit(0); // terminate and return 0 to operating system
00240 // ATTENTION: be aware of leaking resources
00241
00242 // Conditional branches
00243 if (true) {
00244
00245 } else if (false) {
00246
00247 } else {
00248
00249 }
00250 // init statements
00251 // if (std::string fullName{ firstName + ' ' + lastName }; fullName.length() > 20)
00252 // {
00253 //     std::cout << "'" << fullName << "\"is too long!\n";
00254 // }

```

```

00255     //     else
00256     //     {
00257     //         std::cout << "Your name is " << fullName << '\n';
00258     //     }
00259
00260     // Switch statements
00261     Color color {color_black};
00262     switch (color)
00263     {
00264     case Color::color_black:
00265         std::cout << "Black";
00266         break;
00267     case Color::color_white:
00268         std::cout << "White";
00269         break;
00270     case Color::color_red:
00271         std::cout << "Red";
00272         break;
00273         //[[fallthrough]];
00274     case Color::color_green:
00275         std::cout << "Green";
00276         break;
00277     case Color::color_blue:
00278         std::cout << "Blue";
00279         break;
00280     default:
00281         std::cout << "Unknown";
00282         break;
00283     }
00284     //[[fallthrough]] attribute can be added to indicate that the fall-through is intentional.
00285
00286     // Goto statements
00287     //tryAgain:
00288     //     goto tryAgain;
00289
00290     // While statements
00291     int while_counter{ 5 };
00292     while (while_counter < 10) {
00293         std::cout << "while_counter: " << while_counter << std::endl;
00294         ++while_counter;
00295     }
00296
00297     // Do while statements
00298     do {
00299         std::cout << "while_counter: " << while_counter << std::endl;
00300         ++while_counter;
00301     }
00302     while (while_counter < 15);
00303
00304     // For statements
00305     for (int count{ 0 }; count < 10; ++count)
00306         std::cout << count << ' ';
00307     int iii{};
00308     int jjj{};
00309     for (iii = 0, jjj = 9; iii < 10; ++iii, --jjj)
00310         std::cout << iii << ' ' << jjj << '\n';
00311     // return statement terminates the entire function the loop is within
00312     // break terminates the loop
00313     // continue jumps to the end of the loop body for the current iteration
00314     //int prime[5]{}; // hold the first 5 prime numbers
00315     //prime[0] = 2; // The first element has index 0
00316     //prime[1] = 3;
00317     //prime[2] = 5;
00318     //prime[3] = 7;
00319     //prime[4] = 11; // The last element has index 4 (array length-1)
00320     int prime[5]{ 2, 3, 5, 7, 11 }; // use initializer list to initialize the fixed array
00321     //int prime[] { 2, 3, 5, 7, 11 }; // works as well
00322     //std::cout << "The array has: " << std::size(prime) << " elements\n"; // C++17
00323     //sizeof() gives the array length multiplied by element size
00324
00325     // Multidimensional arrays
00326     int num_rows{3};
00327     int num_cols{5};
00328     int multi_dim_array[3][5] // cannot use num_rows or num_cols --> see dynamic memory allocation
00329     {
00330         { 1, 2, 3, 4, 5 }, // row 0
00331         { 6, 7, 8, 9, 10 }, // row 1
00332         { 11, 12, 13, 14, 15 } // row 2
00333     };
00334     for (int row{ 0 }; row < num_rows; ++row) // step through the rows in the array
00335     {
00336         for (int col{ 0 }; col < num_cols; ++col) // step through each element in the row
00337         {
00338             std::cout << multi_dim_array[row][col];
00339         }
00340     }
00341
00342
00343
00344

```

```

00345     // foreach loop
00346     for (auto &element: prime)
00347     {
00348         std::cout << element << std::endl;
00349     }
00352     return 0; // 0, EXIT_SUCCESS, EXIT_FAILURE
00353 }

```

## 15.7.2 Variable Documentation

### 15.7.2.1 g\_global\_integer

```
int g_global_integer { 1 }
```

Global variables

Definition at line 13 of file [Basics.cpp](#).

### 15.7.2.2 g\_x\_1

```
int g_x_1 [static]
```

Definition at line 18 of file [Basics.cpp](#).

### 15.7.2.3 g\_x\_2

```
const int g_x_2 { 2 } [extern]
```

## 15.8 Basics.cpp

```

00001 //
00002 // Created by Michael Staneker on 01.12.20.
00003 //
00004
00005 #include <iostream>
00006 #include <cstdint>
00007 #include <chrono>
00008 #include <thread>
00009 #include <array>
00010
00012 // global variables have file scope
00013 int g_global_integer { 1 };
00014 // AVOID using non-constant global variables!
00015
00016 // internal linkage --> limits the use of an identifier to a single file
00017 // non-constant globals have external linkage by default
00018 static int g_x_1; // adding static makes them internal linkage
00019 // const & constexpr globals have internal linkage by default
00020
00021 // external linkage --> "truly global"
00022 // functions have external linkage by default!
00023 extern const int g_x_2 { 2 }; // making const external
00027 // user-defined headers (alphabetically)
00028 // third-party library headers (alphabetically)
00029 // standard library header (alphabetically)
00030
00031 int main() {
00032
00034     // copy initialization
00035     int a = 1;
00036     // direct initialization
00037     int b(1);
00038     // list (uniform/brace) initialization
00039     //direct
00040     int c_1{1};
00041     //copy
00042     int c_2 = {1};
00046     // floating point
00047     float float_a = 3.14159; // at least 4 bytes
00048     double float_b = 3.14159; // at least 8 bytes
00049     long double float_c = 3.14159; // at least 8 bytes
00050     // Inf represents Infinity
00051     // NaN represents Not a Number
00052

```

```

00053 // integral characters
00054 char char_a = 'c'; // always 1 byte
00055 wchar_t char_b = 'c'; // at least 1 byte
00056 //char8_t char_c = 'c'; // C++20
00057 //char16_t char_d = 'c'; // C++11 // at least 2 bytes
00058 //char32_t char_e = 'c'; // C++11 // at least 4 bytes
00059
00060 // 0b12 --> binary
00061 // 012 --> octal
00062 // 0x12 --> hexadecimal
00063 // use std::dec , std::oct , std::hex
00064
00065 // Integers
00066 short int_a = 1; // at least 2 bytes
00067 int int_b = 1; // at least 2 bytes
00068 long int_c = 1; // at least 4 bytes
00069 //long long int_d = 1; // C++11
00070
00071 // Boolean
00072 bool bool_a = true; // or false
00073
00074 // Null pointer
00075 //std::nullptr_t null_pointer = nullptr;
00076
00077 // void
00078
00079 // using cstdint
00080 //std::int8_t
00081 //std::uint8_t
00082 //std::int16_t
00083 //std::uint16_t
00084 //std::int32_t
00085 //std::uint32_t
00086 //std::int64_t
00087 //std::uint64_t
00088
00089 // there is also the std::int_fast#_t providing the fastest signed integer with at least # bits
00090 // there is also the std::int_least#_t providing the smallest signed integer with at least # bits
00091
00092 std::cout << "bool:\t\t" << sizeof(bool) << " bytes\n";
00093 std::cout << "char:\t\t" << sizeof(char) << " bytes\n";
00094 std::cout << "wchar_t:\t" << sizeof(wchar_t) << " bytes\n";
00095 std::cout << "char16_t:\t" << sizeof(char16_t) << " bytes\n"; // C++11 only
00096 std::cout << "char32_t:\t" << sizeof(char32_t) << " bytes\n"; // C++11 only
00097 std::cout << "short:\t\t" << sizeof(short) << " bytes\n";
00098 std::cout << "int:\t\t\t" << sizeof(int) << " bytes\n";
00099 std::cout << "long:\t\t\t" << sizeof(long) << " bytes\n";
00100 std::cout << "long long:\t" << sizeof(long long) << " bytes\n"; // C++11 only
00101 std::cout << "float:\t\t\t" << sizeof(float) << " bytes\n";
00102 std::cout << "double:\t\t\t" << sizeof(double) << " bytes\n";
00103 std::cout << "long double:\t" << sizeof(long double) << " bytes\n";
00104
00105 // use const
00106 //const int const_int = 1;
00107 // for variables that should not be modifiable after initialization
00108 // and whose initializer is NOT known at compile-time
00109
00110 // use constexpr
00111 //constexpr int constexpr_int = 1;
00112 // for variables that should not be modifiable after initialization
00113 // and whose initializer is known at compile-time
00114 for (int i = 0; i < 5; i++) {
00115     std::this_thread::sleep_for(std::chrono::milliseconds(250));
00116     std::cout << "\a"; // makes an alert
00117 }
00118
00119 std::cout << "Backspace \b" << std::endl;
00120 std::cout << "Formfeed \f" << std::endl;
00121 std::cout << "Newline \n" << std::endl;
00122 std::cout << "Carriage return \r" << std::endl;
00123 std::cout << "Horizontal \t tab" << std::endl;
00124 std::cout << "Vertical tab \v" << std::endl;
00125 std::cout << "Single quote \' or double quote \"" << std::endl;
00126 std::cout << "Octal number \12" << std::endl;
00127 std::cout << "Hex number \x14" << std::endl;
00128
00129 int x_1 = 2;
00130 int x_2 = 3;
00131 int max_x = (x_1 > x_2) ? x_1 : x_2;
00132
00133 // define a namespace
00134 namespace namespace_1 {
00135     // //nested namespace
00136     namespace namespace_1_nested {
00137         // }
00138     }
00139 }
00140 // accessible using "::"
00141
00142 // namespace alias

```

```

00149 // namespace nested_namespace = namespace_1::namespace_1_nested;
00154 // static local variables are not destroyed when out of scope (in contrast to automatic)
00155 static int var_1 { 1 };
00156 // AVOID using static variables unless the variable never needs to be reset
00161 typedef double distance_t; // define distance_t as an alias for type double
00162 //which is equivalent to: using distance_t = double;
00163 // The following two statements are equivalent:
00164 // double howFar; //equivalent to
00165 distance_t howFar;
00171 // IMPLICIT type conversion (coercion)
00172 float f_int { 3 }; // initializing floating point variable with int 3
00173
00174 // EXPLICIT type conversion
00175 // static_cast
00176 int i1 { 10 };
00177 int i2 { 4 };
00178 // convert an int to a float so we get floating point division rather than integer division
00179 float f { static_cast<float>(i1) / i2 };
00180
00184 enum Color
00185 {
00186     color_black, // assigned 0
00187     color_red, // assigned 1
00188     color_blue, // assigned 2
00189     color_green, // assigned 3
00190     color_white, // assigned 4
00191     color_cyan, // assigned 5
00192     color_yellow, // assigned 6
00193     color_magenta // assigned 7
00194 };
00195 Color paint{ color_white };
00196 std::cout << paint;
00197
00198 // enum classes (scoped enumerations)
00199 enum class Fruit
00200 {
00201     banana, // banana is inside the scope of Fruit
00202     apple
00203 };
00204 Fruit fruit{ Fruit::banana }; // note: banana is not directly accessible any more, we have to use
Fruit::banana
00208 struct Employee
00209 {
00210     short id;
00211     int age;
00212     double wage;
00213 };
00214
00215 Employee joe{ 1, 32, 60000.0 }; // joe.id = 1, joe.age = 32, joe.wage = 60000.0
00216 Employee frank{ 2, 28 }; // frank.id = 2, frank.age = 28, frank.wage = 0.0 (default
initialization)
00217
00218 //Employee joe; // create an Employee struct for Joe
00219 //joe.id = 14; // assign a value to member id within struct joe
00220 //joe.age = 32; // assign a value to member age within struct joe
00221 //joe.wage = 24.15; // assign a value to member wage within struct joe
00222
00223 //Employee frank; // create an Employee struct for Frank
00224 //frank.id = 15; // assign a value to member id within struct frank
00225 //frank.age = 28; // assign a value to member age within struct frank
00226 //frank.wage = 18.27; // assign a value to member wage within struct frank
00227
00228 // nested structs
00229 struct Company
00230 {
00231     Employee CEO; // Employee is a struct within the Company struct
00232     int numberOfEmployees;
00233 };
00234 Company myCompany{{ 1, 42, 60000.0 }, 5 };
00238 // halt (using <cstdlib>)
00239 //std::exit(0); // terminate and return 0 to operating system
00240 // ATTENTION: be aware of leaking resources
00241
00242 // Conditional branches
00243 if (true) {
00244
00245 } else if (false) {
00246
00247 } else {
00248
00249 }
00250 // init statements
00251 // if (std::string fullName{ firstName + ' ' + lastName }; fullName.length() > 20)
00252 // {
00253 //     std::cout << "'" << fullName << "\"is too long!\n";
00254 // }
00255 // else

```

```

00256 // {
00257 //     std::cout << "Your name is " << fullName << '\n';
00258 // }
00259
00260 // Switch statements
00261 Color color {color_black};
00262 switch (color)
00263 {
00264     case Color::color_black:
00265         std::cout << "Black";
00266         break;
00267     case Color::color_white:
00268         std::cout << "White";
00269         break;
00270     case Color::color_red:
00271         std::cout << "Red";
00272         break;
00273         //[[fallthrough]];
00274     case Color::color_green:
00275         std::cout << "Green";
00276         break;
00277     case Color::color_blue:
00278         std::cout << "Blue";
00279         break;
00280     default:
00281         std::cout << "Unknown";
00282         break;
00283 }
00284 //[[fallthrough]] attribute can be added to indicate that the fall-through is intentional.
00285
00286 // Goto statements
00287 //tryAgain:
00288 //     goto tryAgain;
00289
00290 // While statements
00291 int while_counter{ 5 };
00292 while (while_counter < 10) {
00293     std::cout << "while_counter: " << while_counter << std::endl;
00294     ++while_counter;
00295 }
00296
00297 // Do while statements
00298 do {
00299     std::cout << "while_counter: " << while_counter << std::endl;
00300     ++while_counter;
00301 }
00302 while (while_counter < 15);
00303
00304 // For statements
00305 for (int count{ 0 }; count < 10; ++count)
00306     std::cout << count << ' ';
00307 int iii{};
00308 int jjj{};
00309 for (iii = 0, jjj = 9; iii < 10; ++iii, --jjj)
00310     std::cout << iii << ' ' << jjj << '\n';
00311 // return statement terminates the entire function the loop is within
00312 // break terminates the loop
00313 // continue jumps to the end of the loop body for the current iteration
00314 //int prime[5]{}; // hold the first 5 prime numbers
00315 //prime[0] = 2; // The first element has index 0
00316 //prime[1] = 3;
00317 //prime[2] = 5;
00318 //prime[3] = 7;
00319 //prime[4] = 11; // The last element has index 4 (array length-1)
00320 int prime[5]{ 2, 3, 5, 7, 11 }; // use initializer list to initialize the fixed array
00321 //int prime[] { 2, 3, 5, 7, 11 }; // works as well
00322 //std::cout << "The array has: " << std::size(prime) << " elements\n"; // C++17
00323 //sizeof() gives the array length multiplied by element size
00324
00325 // Multidimensional arrays
00326 int num_rows{3};
00327 int num_cols{5};
00328 int multi_dim_array[3][5] // cannot use num_rows or num_cols --> see dynamic memory allocation
00329 {
00330     { 1, 2, 3, 4, 5 }, // row 0
00331     { 6, 7, 8, 9, 10 }, // row 1
00332     { 11, 12, 13, 14, 15 } // row 2
00333 };
00334 for (int row{ 0 }; row < num_rows; ++row) // step through the rows in the array
00335 {
00336     for (int col{ 0 }; col < num_cols; ++col) // step through each element in the row
00337     {
00338         std::cout << multi_dim_array[row][col];
00339     }
00340 }
00341
00342 // foreach loop

```

```


00346     for (auto &element: prime)
00347     {
00348         std::cout << element << std::endl;
00349     }
00352     return 0; // 0, EXIT_SUCCESS, EXIT_FAILURE
00353 }

```

## 15.9 learningCpp/Basics/BitManipulation.cpp File Reference

#include <bitset>

Include dependency graph for BitManipulation.cpp:



### Functions

- int [main](#) ()

### 15.9.1 Function Documentation

#### 15.9.1.1 main()

```
int main ( )
```

Bitwise operators

Bit masks

Definition at line 7 of file [BitManipulation.cpp](#).

```

00007     {
00008
00009         std::bitset<8> bits{ 0b0000'0101 }; // we need 8 bits, start with bit pattern 0000 0101
00010         bits.set(3); // set bit position 3 to 1 (now we have 0000 1101)
00011         bits.flip(4); // flip bit 4 (now we have 0001 1101)
00012         bits.reset(4); // set bit 4 back to 0 (now we have 0000 1101)
00013
00014         std::cout << "All the bits: " << bits << '\n';
00015         std::cout << "Bit 3 has value: " << bits.test(3) << '\n';
00016         std::cout << "Bit 4 has value: " << bits.test(4) << '\n';
00017
00019         // x << y // left shift
00020         // x >> y // right shift
00021         // ~x // bitwise NOT
00022         // x & y // bitwise AND
00023         // x | y // bitwise OR
00024         // x ^ y // bitwise XOR
00025         // x <= < // left shift assignment
00026         // x >= y // right shift assignment
00027         // x |= y // bitwise OR assignment
00028         // x &= y // bitwise AND assignment
00029         // x ^= y // bitwise XOR assignment
00033         // since C++14
00034         constexpr std::uint_fast8_t mask0{ 0b0000'0001 }; // represents bit 0
00035         constexpr std::uint_fast8_t mask1{ 0b0000'0010 }; // represents bit 1
00036         constexpr std::uint_fast8_t mask2{ 0b0000'0100 }; // represents bit 2

```



```

00037     constexpr std::uint_fast8_t mask3{ 0b0000'1000 }; // represents bit 3
00038     constexpr std::uint_fast8_t mask4{ 0b0001'0000 }; // represents bit 4
00039     constexpr std::uint_fast8_t mask5{ 0b0010'0000 }; // represents bit 5
00040     constexpr std::uint_fast8_t mask6{ 0b0100'0000 }; // represents bit 6
00041     constexpr std::uint_fast8_t mask7{ 0b1000'0000 }; // represents bit 7
00042     // C++11 or earlier
00043     //     constexpr std::uint_fast8_t mask0{ 0x1 }; // hex for 0000 0001
00044     //     constexpr std::uint_fast8_t mask1{ 0x2 }; // hex for 0000 0010
00045     //     constexpr std::uint_fast8_t mask2{ 0x4 }; // hex for 0000 0100
00046     //     constexpr std::uint_fast8_t mask3{ 0x8 }; // hex for 0000 1000
00047     //     constexpr std::uint_fast8_t mask4{ 0x10 }; // hex for 0001 0000
00048     //     constexpr std::uint_fast8_t mask5{ 0x20 }; // hex for 0010 0000
00049     //     constexpr std::uint_fast8_t mask6{ 0x40 }; // hex for 0100 0000
00050     //     constexpr std::uint_fast8_t mask7{ 0x80 }; // hex for 1000 0000
00051     //     // or
00052     //     constexpr std::uint_fast8_t mask0{ 1 << 0 }; // 0000 0001
00053     //     constexpr std::uint_fast8_t mask1{ 1 << 1 }; // 0000 0010
00054     //     constexpr std::uint_fast8_t mask2{ 1 << 2 }; // 0000 0100
00055     //     constexpr std::uint_fast8_t mask3{ 1 << 3 }; // 0000 1000
00056     //     constexpr std::uint_fast8_t mask4{ 1 << 4 }; // 0001 0000
00057     //     constexpr std::uint_fast8_t mask5{ 1 << 5 }; // 0010 0000
00058     //     constexpr std::uint_fast8_t mask6{ 1 << 6 }; // 0100 0000
00059     //     constexpr std::uint_fast8_t mask7{ 1 << 7 }; // 1000 0000
00062     return 0;
00063 }

```

## 15.10 BitManipulation.cpp

```

00001 //
00002 // Created by Michael Staneker on 01.12.20.
00003 //
00004 //
00005 #include <bitset>
00006
00007 int main() {
00008
00009     std::bitset<8> bits{ 0b0000'0101 }; // we need 8 bits, start with bit pattern 0000 0101
00010     bits.set(3); // set bit position 3 to 1 (now we have 0000 1101)
00011     bits.flip(4); // flip bit 4 (now we have 0001 1101)
00012     bits.reset(4); // set bit 4 back to 0 (now we have 0000 1101)
00013
00014     std::cout << "All the bits: " << bits << '\n';
00015     std::cout << "Bit 3 has value: " << bits.test(3) << '\n';
00016     std::cout << "Bit 4 has value: " << bits.test(4) << '\n';
00017
00019     // x << y // left shift
00020     // x >> y // right shift
00021     // ~x // bitwise NOT
00022     // x & y // bitwise AND
00023     // x | y // bitwise OR
00024     // x ^ y // bitwise XOR
00025     // x <= < // left shift assignment
00026     // x >= y // right shift assignment
00027     // x |= y // bitwise OR assignment
00028     // x &= y // bitwise AND assignment
00029     // x ^= y // bitwise XOR assignment
00033     // since C++14
00034     constexpr std::uint_fast8_t mask0{ 0b0000'0001 }; // represents bit 0
00035     constexpr std::uint_fast8_t mask1{ 0b0000'0010 }; // represents bit 1
00036     constexpr std::uint_fast8_t mask2{ 0b0000'0100 }; // represents bit 2
00037     constexpr std::uint_fast8_t mask3{ 0b0000'1000 }; // represents bit 3
00038     constexpr std::uint_fast8_t mask4{ 0b0001'0000 }; // represents bit 4
00039     constexpr std::uint_fast8_t mask5{ 0b0010'0000 }; // represents bit 5
00040     constexpr std::uint_fast8_t mask6{ 0b0100'0000 }; // represents bit 6
00041     constexpr std::uint_fast8_t mask7{ 0b1000'0000 }; // represents bit 7
00042     // C++11 or earlier
00043     //     constexpr std::uint_fast8_t mask0{ 0x1 }; // hex for 0000 0001
00044     //     constexpr std::uint_fast8_t mask1{ 0x2 }; // hex for 0000 0010
00045     //     constexpr std::uint_fast8_t mask2{ 0x4 }; // hex for 0000 0100
00046     //     constexpr std::uint_fast8_t mask3{ 0x8 }; // hex for 0000 1000
00047     //     constexpr std::uint_fast8_t mask4{ 0x10 }; // hex for 0001 0000
00048     //     constexpr std::uint_fast8_t mask5{ 0x20 }; // hex for 0010 0000
00049     //     constexpr std::uint_fast8_t mask6{ 0x40 }; // hex for 0100 0000
00050     //     constexpr std::uint_fast8_t mask7{ 0x80 }; // hex for 1000 0000
00051     //     // or
00052     //     constexpr std::uint_fast8_t mask0{ 1 << 0 }; // 0000 0001
00053     //     constexpr std::uint_fast8_t mask1{ 1 << 1 }; // 0000 0010
00054     //     constexpr std::uint_fast8_t mask2{ 1 << 2 }; // 0000 0100
00055     //     constexpr std::uint_fast8_t mask3{ 1 << 3 }; // 0000 1000
00056     //     constexpr std::uint_fast8_t mask4{ 1 << 4 }; // 0001 0000
00057     //     constexpr std::uint_fast8_t mask5{ 1 << 5 }; // 0010 0000
00058     //     constexpr std::uint_fast8_t mask6{ 1 << 6 }; // 0100 0000
00059     //     constexpr std::uint_fast8_t mask7{ 1 << 7 }; // 1000 0000
00062     return 0;
00063 }


```

00064

## 15.11 learningCpp/Basics/CommandLineArguments.cpp File Reference

```
#include <iostream>
```

Include dependency graph for CommandLineArguments.cpp:



### Functions

- int [main](#) (int argc, char \*argv[])

### 15.11.1 Function Documentation

#### 15.11.1.1 main()

```
int main (
    int argc,
    char * argv[] )
```

#### 15.11.2 Command line arguments

In order to pass command line arguments to the program use

- int [main\(int argc, char \\*argv\[\]\)](#)
- int [main\(int argc, char\\*\\* argv\)](#) both are treated identically!
- **argc** is an integer parameter containing a count of the number of arguments passed to the program, whereas **argc** is always at least 1, since the first argument is always the name of the program itself
- **argv** is where the actual arguments are stored (within an array of C-style strings)

Definition at line 21 of file [CommandLineArguments.cpp](#).

```
00022 {
00023     std::cout << "There are " << argc << " arguments:\n";
00024
00025     // Loop through each argument and print its number and value
00026     for (int count{ 0 }; count < argc; ++count)
00027     {
00028         std::cout << count << ' ' << argv[count] << '\n';
00029     }
00030
00031     // handle numeric values
00032     //std::stringstream convert{ argv[1] }; // set up a stringstream variable named convert,
    initialized with the input from argv[1]
00033     //int myint();
```

```

00034     //if (!(convert » myint)) // do the conversion
00035     //    myint = 0; // if conversion fails, set myint to a default value
00036     //std::cout << "Got integer: " << myint << '\n';
00037
00038     return 0;
00039 }

```

## 15.12 CommandLineArguments.cpp

```


00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include <iostream>
00006
00021 int main(int argc, char *argv[])
00022 {
00023     std::cout << "There are " << argc << " arguments:\n";
00024
00025     // Loop through each argument and print its number and value
00026     for (int count{ 0 }; count < argc; ++count)
00027     {
00028         std::cout << count << ' ' << argv[count] << '\n';
00029     }
00030
00031     // handle numeric values
00032     //std::stringstream convert{ argv[1] }; // set up a stringstream variable named convert,
    initialized with the input from argv[1]
00033     //int myint{};
00034     //if (!(convert » myint)) // do the conversion
00035     //    myint = 0; // if conversion fails, set myint to a default value
00036     //std::cout << "Got integer: " << myint << '\n';
00037
00038     return 0;
00039 }

```

## 15.13 learningCpp/Basics/Functions.cpp File Reference

```
#include "Functions.h"
```

Include dependency graph for Functions.cpp:



### Functions

- void [pass\\_by\\_value](#) (int x)  
Function passing argument by value.
- void [pass\\_by\\_reference](#) (int &x)

- *Function passing argument by reference.*  
void [pass\\_by\\_address](#) (int \*ptr)
- *Function passing argument by address.*  
int [return\\_by\\_value](#) ()
- *Function returning value by value.*  
int & [return\\_by\\_reference](#) ()
- *Function returning value by reference.*  
int \* [return\\_by\\_address](#) ()
- *Function returning value by address.*  
int [overload\\_add](#) (int a, int b)
- *Function adding two values.*  
int [overload\\_add](#) (int a, int b, int c)
- *(Overloaded) Function adding three values*  
void [func\\_default\\_arg](#) (int x, int y)
- *Function with default argument (optional parameter)*  
void [countDown](#) (int count)
- *A simple recursive function.*  
void [lambda\\_example](#) (std::array< std::string\_view, 4 > arr)
- *A simple lambda function.*  
void [ellipsis\\_example](#) (int count,...)
- *A simple function using ellipsis.*  
template<typename T >  
T [max](#) (T x, T y)
- *A simple template function.*  
int [main](#) ()

## 15.13.1 Function Documentation

### 15.13.1.1 [countDown\(\)](#)

```
void countDown (
    int count )
```

A simple recursive function.

Definition at line 57 of file [Functions.cpp](#).

```
00058 {
00059     std::cout << "push " << count << '\n';
00060
00061     if (count > 1) // termination condition
00062         countDown(count-1);
00063
00064     std::cout << "pop " << count << '\n';
00065 }
```

Here is the call graph for this function:



### 15.13.1.2 ellipsis\_example()

```
void ellipsis_example (
    int count,
    ... )
```

A simple function using ellipsis.

Definition at line 83 of file [Functions.cpp](#).

```
00083                                     {
00084     double sum{ 0 };
00085
00086     // We access the ellipsis through a va_list, so let's declare one
00087     va_list list;
00088
00089     // We initialize the va_list using va_start. The first parameter is
00090     // the list to initialize. The second parameter is the last non-ellipsis
00091     // parameter.
00092     va_start(list, count);
00093
00094     // Loop through all the ellipsis arguments
00095     for (int arg{ 0 }; arg < count; ++arg)
00096     {
00097         // We use va_arg to get parameters out of our ellipsis
00098         // The first parameter is the va_list we're using
00099         // The second parameter is the type of the parameter
00100         sum += va_arg(list, int);
00101     }
00102
00103     // Cleanup the va_list when we're done.
00104     va_end(list);
00105
00106     std::cout << "average = " << sum / count << std::endl;
00107 }
```

### 15.13.1.3 func\_default\_arg()

```
void func_default_arg (
    int x,
    int y )
```

Function with default argument (optional parameter)

Definition at line 52 of file [Functions.cpp](#).

```
00052                                     {
00053     std::cout << "x = " << x << std::endl;
00054     std::cout << "y = " << y << std::endl;
00055 }
```

### 15.13.1.4 lambda\_example()

```
void lambda_example (
    std::array< std::string_view, 4 > arr )
```

A simple lambda function.

Definition at line 67 of file [Functions.cpp](#).

```
00067                                     {
00068     const auto found{ std::find_if(arr.begin(), arr.end(),
00069     [] (std::string_view str) // here's our lambda, no capture clause
00070     {
00071         return (str.find("nut") != std::string_view::npos);
00072     }) };
00073
00074     if (found == arr.end())
00075     {
00076         std::cout << "No nuts\n";
00077     }
00078     else {
00079         std::cout << "Found " << *found << '\n';
00080     }
00081 }
```

### 15.13.1.5 main()

```
int main ( )
calling a function through a function pointer
```

## calling a recursive function


Definition at line 114 of file Functions.cpp.

```

00114     {
00115
00116         int x = 5;
00117         pass_by_value(x);
00118
00119         pass_by_reference(x);
00120         std::cout << "after passed by reference: x = " << x << std::endl;
00121
00122         pass_by_address(&x);
00123         std::cout << "after passed by address x = " << x << std::endl;
00124
00125         int value = return_by_value();
00126         std::cout << "return by value: value = " << value << std::endl;
00127
00128         int *value_ptr = return_by_address();
00129         std::cout << "return by address: " << std::endl;
00130         std::cout << " value_ptr = " << value_ptr << std::endl;
00131         std::cout << "*value_ptr = " << *value_ptr << std::endl;
00132
00133         int value_ref = return_by_reference();
00134         std::cout << "return by reference: value = " << value_ref << std::endl;
00135
00136         int a = 1;
00137         int b = 2;
00138         int c = 3;
00139
00140         int result_1 = overload_add(a, b);
00141         std::cout << "result_1 = " << result_1 << std::endl;
00142         int result_2 = overload_add(a, b, c);
00143         std::cout << "result_2 = " << result_2 << std::endl;
00144
00145         std::cout << "func_default_arg(int x, int y=10) with x = 2" << std::endl;
00146         func_default_arg(2);
00147         std::cout << "func_default_arg(int x, int y=10) with x = 2 and y = 5" << std::endl;
00148         func_default_arg(2, 5);
00149
00150         void (*fcnPtr)(int, int){ &func_default_arg }; // Initialize fcnPtr
00151         std::cout << "call function through function pointer: " << std::endl;
00152         fcnPtr(5, 5); // call function
00153
00154         std::cout << "Calling a recursive function" << std::endl;
00155         countDown(5);
00156
00157         std::cout << "ellipsis_example(2, 1, 5)" << std::endl;
00158         ellipsis_example(2, 1, 5);
00159
00160         std::cout << "ellipsis_example(4, 1, 5, 7, 10)" << std::endl;
00161         ellipsis_example(4, 1, 5, 7, 10);
00162
00163         std::cout << "lambda_example()" << std::endl;
00164         std::array<std::string_view, 4> arr{ "apple", "banana", "walnut", "lemon" };
00165         lambda_example(arr);
00166
00167         int int_1 = 1;
00168         int int_2 = 2;
00169         int int_max = max(int_1, int_2);
00170         std::cout << "max integer = " << int_max << std::endl;
00171
00172         double double_1 = 4.7;
00173         double double_2 = 7.9;
00174         double double_max = max(double_1, double_2);
00175         std::cout << "max double = " << double_max << std::endl;
00176
00177         return 0;
00178     }

```

Here is the call graph for this function:



#### 15.13.1.6 max()

```
template<typename T >  
T max (  
    T x,  
    T y )
```

A simple template function.

Definition at line 109 of file [Functions.cpp](#).

```

00109                                     {
00110     return (x > y) ? x : y;
00111 }

```

#### 15.13.1.7 overload\_add() [1/2]

```

int overload_add (
    int a,
    int b )

```

Function adding two values.

Definition at line 42 of file [Functions.cpp](#).

```

00042     {
00043     std::cout << "overload_add(int a, int b)" << std::endl;
00044     return a + b;
00045 }

```

#### 15.13.1.8 overload\_add() [2/2]

```

int overload_add (
    int a,
    int b,
    int c )

```

(Overloaded) Function adding three values

Definition at line 47 of file [Functions.cpp](#).

```

00047     {
00048     std::cout << "overload_add(int a, int b, int c)" << std::endl;
00049     return a + b + c;
00050 }

```

#### 15.13.1.9 pass\_by\_address()

```

void pass_by_address (
    int * ptr )

```

Function passing argument by address.

Definition at line 18 of file [Functions.cpp](#).

```

00018     {
00019     std::cout << "func: pass_by_address(int *ptr)" << std::endl;
00020     std::cout << "ptr = 4" << std::endl;
00021     *ptr = 4;
00022 }

```

#### 15.13.1.10 pass\_by\_reference()

```

void pass_by_reference (
    int & x )

```

Function passing argument by reference.

Definition at line 12 of file [Functions.cpp](#).

```

00012     {
00013     std::cout << "func: pass_by_reference(int &x)" << std::endl;
00014     std::cout << "x += 1" << std::endl;
00015     x = x + 1;
00016 }

```

#### 15.13.1.11 pass\_by\_value()

```

void pass_by_value (
    int x )

```

Function passing argument by value.

Definition at line 7 of file [Functions.cpp](#).

```

00007     {
00008     std::cout << "func: pass_by_value(int x)" << std::endl;
00009     std::cout << "x = " << x << std::endl;

```



```
00010 }
```

### 15.13.1.12 return\_by\_address()

```
int* return_by_address ( )
```

Function returning value by address.

Definition at line 36 of file [Functions.cpp](#).

```
00036 {
00037     std::cout << "func: return_by_address()" << std::endl;
00038     int value{ 2 };
00039     return &value; // return value by address
00040 } // value destroyed here
```

### 15.13.1.13 return\_by\_reference()

```
int& return_by_reference ( )
```

Function returning value by reference.

Definition at line 30 of file [Functions.cpp](#).

```
00030 {
00031     std::cout << "func: return_by_reference()" << std::endl;
00032     int value{ 2 };
00033     return value; // return a reference to value
00034 }
```

### 15.13.1.14 return\_by\_value()

```
int return_by_value ( )
```

Function returning value by value.

Definition at line 24 of file [Functions.cpp](#).

```
00024 {
00025     std::cout << "func: return_by_value()" << std::endl;
00026     int value{ 2 };
00027     return value; // a copy of value will be returned
00028 } // value destroyed here
```

## 15.14 Functions.cpp

```
00001 //
00002 // Created by Michael Staneker on 08.12.20.
00003 //
00004
00005 #include "Functions.h"
00006
00007 void pass_by_value(int x) {
00008     std::cout << "func: pass_by_value(int x)" << std::endl;
00009     std::cout << "x = " << x << std::endl;
00010 }
00011
00012 void pass_by_reference(int &x) {
00013     std::cout << "func: pass_by_reference(int &x)" << std::endl;
00014     std::cout << "x += 1" << std::endl;
00015     x = x + 1;
00016 }
00017
00018 void pass_by_address(int *ptr) {
00019     std::cout << "func: pass_by_address(int *ptr)" << std::endl;
00020     std::cout << "ptr = 4" << std::endl;
00021     *ptr = 4;
00022 }
00023
00024 int return_by_value() {
00025     std::cout << "func: return_by_value()" << std::endl;
00026     int value{ 2 };
00027     return value; // a copy of value will be returned
00028 } // value destroyed here
00029
00030 int& return_by_reference() {
00031     std::cout << "func: return_by_reference()" << std::endl;
00032     int value{ 2 };
00033     return value; // return a reference to value
00034 }
00035
```

```

00036 int* return_by_address() {
00037     std::cout << "func: return_by_address()" << std::endl;
00038     int value{ 2 };
00039     return &value; // return value by address
00040 } // value destroyed here
00041
00042 int overload_add(int a, int b) {
00043     std::cout << "overload_add(int a, int b)" << std::endl;
00044     return a + b;
00045 }
00046
00047 int overload_add(int a, int b, int c) {
00048     std::cout << "overload_add(int a, int b, int c)" << std::endl;
00049     return a + b + c;
00050 }
00051
00052 void func_default_arg(int x, int y) {
00053     std::cout << "x = " << x << std::endl;
00054     std::cout << "y = " << y << std::endl;
00055 }
00056
00057 void countDown(int count)
00058 {
00059     std::cout << "push " << count << '\n';
00060
00061     if (count > 1) // termination condition
00062         countDown(count-1);
00063
00064     std::cout << "pop " << count << '\n';
00065 }
00066
00067 void lambda_example(std::array<std::string_view, 4> arr) {
00068     const auto found{ std::find_if(arr.begin(), arr.end(),
00069                                     [](std::string_view str) // here's our lambda, no capture clause
00070                                     {
00071                                         return (str.find("nut") != std::string_view::npos);
00072                                     }) };
00073
00074     if (found == arr.end())
00075     {
00076         std::cout << "No nuts\n";
00077     }
00078     else {
00079         std::cout << "Found " << *found << '\n';
00080     }
00081 }
00082
00083 void ellipsis_example(int count, ...) {
00084     double sum{ 0 };
00085
00086     // We access the ellipsis through a va_list, so let's declare one
00087     va_list list;
00088
00089     // We initialize the va_list using va_start. The first parameter is
00090     // the list to initialize. The second parameter is the last non-ellipsis
00091     // parameter.
00092     va_start(list, count);
00093
00094     // Loop through all the ellipsis arguments
00095     for (int arg{ 0 }; arg < count; ++arg)
00096     {
00097         // We use va_arg to get parameters out of our ellipsis
00098         // The first parameter is the va_list we're using
00099         // The second parameter is the type of the parameter
00100         sum += va_arg(list, int);
00101     }
00102
00103     // Cleanup the va_list when we're done.
00104     va_end(list);
00105
00106     std::cout << "average = " << sum / count << std::endl;
00107 }
00108
00109 template <typename T> T max(T x, T y) {
00110     return (x > y) ? x : y;
00111 }
00112
00113
00114 int main() {
00115
00116     int x = 5;
00117     pass_by_value(x);
00118
00119     pass_by_reference(x);
00120     std::cout << "after passed by reference: x = " << x << std::endl;
00121
00122     pass_by_address(&x);

```

```

00123     std::cout << "after passed by address x = " << x << std::endl;
00124
00125     int value = return_by_value();
00126     std::cout << "return by value: value = " << value << std::endl;
00127
00128     int *value_ptr = return_by_address();
00129     std::cout << "return by address: " << std::endl;
00130     std::cout << " value_ptr = " << value_ptr << std::endl;
00131     std::cout << "*value_ptr = " << *value_ptr << std::endl;
00132
00133     int value_ref = return_by_reference();
00134     std::cout << "return by reference: value = " << value_ref << std::endl;
00135
00136     int a = 1;
00137     int b = 2;
00138     int c = 3;
00139
00140     int result_1 = overload_add(a, b);
00141     std::cout << "result_1 = " << result_1 << std::endl;
00142     int result_2 = overload_add(a, b, c);
00143     std::cout << "result_2 = " << result_2 << std::endl;
00144
00145     std::cout << "func_default_arg(int x, int y=10) with x = 2" << std::endl;
00146     func_default_arg(2);
00147     std::cout << "func_default_arg(int x, int y=10) with x = 2 and y = 5" << std::endl;
00148     func_default_arg(2, 5);
00149
00154     void (*fcnPtr)(int, int){ &func_default_arg }; // Initialize fcnPtr
00155     std::cout << "call function through function pointer: " << std::endl;
00156     fcnPtr(5, 5); // call function
00157
00161     std::cout << "Calling a recursive function" << std::endl;
00162     countDown(5);
00163
00164     std::cout << "ellipsis_example(2, 1, 5)" << std::endl;
00165     ellipsis_example(2, 1, 5);
00166
00167     std::cout << "ellipsis_example(4, 1, 5, 7, 10)" << std::endl;
00168     ellipsis_example(4, 1, 5, 7, 10);
00169
00170
00171     std::cout << "lambda_example()" << std::endl;
00172     std::array<std::string_view, 4> arr{ "apple", "banana", "walnut", "lemon" };
00173     lambda_example(arr);
00174
00175     int int_1 = 1;
00176     int int_2 = 2;
00177     int int_max = max(int_1, int_2);
00178     std::cout << "max integer = " << int_max << std::endl;
00179
00180     double double_1 = 4.7;
00181     double double_2 = 7.9;
00182     double double_max = max(double_1, double_2);
00183     std::cout << "max double = " << double_max << std::endl;
00184
00185     return 0;
00186 }

```


## 15.15 learningCpp/Basics/Functions.h File Reference

```


#include <array>
#include <iostream>

```

Include dependency graph for Functions.h:



This graph shows which files directly or indirectly include this file:



## Functions

- void [pass\\_by\\_value](#) (int x)  
*Function passing argument by value.*
- void [pass\\_by\\_reference](#) (int &x)  
*Function passing argument by reference.*
- void [pass\\_by\\_address](#) (int \*x)  
*Function passing argument by address.*
- int [return\\_by\\_value](#) ()  
*Function returning value by value.*
- int & [return\\_by\\_reference](#) ()  
*Function returning value by reference.*
- int \* [return\\_by\\_address](#) ()  
*Function returning value by address.*
- int [overload\\_add](#) (int a, int b)  
*Function adding two values.*
- int [overload\\_add](#) (int a, int b, int c)  
*(Overloaded) Function adding three values*
- void [func\\_default\\_arg](#) (int x, int y=10)

- *Function with default argument (optional parameter)*
- void `countDown` (int count)  
*A simple recursive function.*
- void `ellipsis_example` (int count,...)  
*A simple function using ellipsis.*
- void `lambda_example` (std::array< std::string\_view, 4 > arr)  
*A simple lambda function.*
- template<typename T >  
T `max` (T x, T y)  
*A simple template function.*

### 15.15.1 Detailed Description

### 15.15.2 Function parameters and arguments

#### 15.15.2.1 Pass by value

By default, non-pointer arguments in C++ are passed by value. When an argument is **passed by value**, the argument's value is copied into the value of the corresponding function parameter. Therefore the original argument can not be modified by the function!

##### 15.15.2.1.1 Pros

- Arguments can be anything
- Arguments are never changed by the function (prevents possibly unwanted side effects)

##### 15.15.2.1.2 Cons

- Copying classes and structs can incur a significant performance penalty

##### 15.15.2.1.3 When to use

- When passing fundamental data type and enumerators, and the function does not need to change the argument.

##### 15.15.2.1.4 When not to use

- When passing structs or classes (including std::array, std::vector, and std::string)

#### 15.15.2.2 Pass by reference

To **pass** a variable **by reference**, simply declare the function parameters as references. When the function is called the function parameter becomes a reference to the argument being called with, so that any changes made to the reference are passed through to the argument!

Since functions can have only one return value, references or rather reference function parameters can be used to return multiple values.

**15.15.2.2.1 read-only pass by reference** If it is undesirable to change an argument, make it read-only by passing it as **const reference**, so that an error occurs if the function tries to change the argument.

That's useful, since

- It enlists the compilers help in ensuring values that shouldn't be changed aren't changed (the compiler will throw an error if you try, like in the above example).
- It tells the programmer that the function won't change the value of the argument. This can help with debugging.
- You can't pass a const argument to a non-const reference parameter. Using const parameters ensures you can pass both non-const and const arguments to the function.
- Const references can accept any type of argument, including non-const l-values, const l-values, and r-values.

#### 15.15.2.2.2 Pros

- References allow a function to change the value of the argument, which is sometimes useful. Otherwise, const references can be used to guarantee the function won't change the argument.
- Because a copy of the argument is not made, pass by reference is fast, even when used with large structs or classes.
- References can be used to return multiple values from a function (via out parameters).
- References must be initialized, so there's no worry about null values.

#### 15.15.2.2.3 Cons

- Because a non-const reference cannot be initialized with a const l-value or an r-value (e.g. a literal or an expression), arguments to non-const reference parameters must be normal variables.
- It can be hard to tell whether an argument passed by non-const reference is meant to be input, output, or both. Judicious use of const and a naming suffix for out variables can help.
- It's impossible to tell from the function call whether the argument may change. An argument passed by value and passed by reference looks the same. We can only tell whether an argument is passed by value or reference by looking at the function declaration. This can lead to situations where the programmer does not realize a function will change the value of the argument.

#### 15.15.2.2.4 When to use

- When passing structs or classes (const if read-only is wanted)
- When the function needs to modify an argument
- When the type information of a fixed array is required

#### 15.15.2.3 Pass by address

There is one more way to pass variables to functions, and that is by address. **Passing an argument by address** involves passing the address of the argument variable rather than the argument variable itself. Because the argument is an address, the function parameter must be a pointer. The function can then dereference the pointer to access or change the value being pointed to.

**Remember that fixed arrays decay into pointers when passed to a function**, therefore the length of the array has to be passed separately.

Addresses are actually passed by value, so by changing the function parameter itself, the original pointer argument will not be changed.

To change the address an argument points to, just pass the addresses by reference.

**15.15.2.3.1 read-only pass by address** If it is undesirable to change an argument, make it read-only by passing it as **const pointer**, so that an error occurs if the function tries to change the argument.

#### 15.15.2.3.2 Pros

- Pass by address allows a function to change the value of the argument, which is sometimes useful. Otherwise, const can be used to guarantee the function won't change the argument. (However, if you want to do this with a non-pointer, you should use pass by reference instead).
- Because a copy of the argument is not made, it is fast, even when used with large structs or classes.
- We can return multiple values from a function via out parameters.

#### 15.15.2.3.3 Cons

- Because literals (excepting C-style string literals) and expressions do not have addresses, pointer arguments must be normal variables.
- All values must be checked to see whether they are null. Trying to dereference a null value will result in a crash. It is easy to forget to do this.
- Because dereferencing a pointer is slower than accessing a value directly, accessing arguments passed by address is slower than accessing arguments passed by value.

#### 15.15.2.3.4 When to use

- When passing built-in arrays (if you're okay with the fact that they'll decay into a pointer).
- When passing a pointer and nullptr is a valid argument logically.

#### 15.15.2.3.5 When not to use

- When passing a pointer and nullptr is not a valid argument logically (use pass by reference).
- When passing structs or classes (use pass by reference).
- When passing fundamental types (use pass by value).

#### 15.15.2.4 Returning values by value, reference and address

This is quite similar to passing arguments to functions. In fact, returning values from a function to its caller by value, address or reference **works almost exactly the same way as passing arguments to a function, with the same upsides and downsides.**

**Attention:** Since local variables in a function go out of scope and are destroyed, this needs to be considered!

##### 15.15.2.4.1 Return by value To use, when

- returning variables that were declared inside the function
- returning function arguments that were passed by value

**Not to use, when**

- returning a built-in array or pointer (use return by address instead!)
- returning a large struct or class (use return by reference instead!)

##### 15.15.2.4.2 Return by address Not possible for literals or expressions (no address)!

To use, when

- returning dynamically allocated memory and there is no type to handle the allocation
- returning function arguments that were passed by address

**Not to use, when**

- returning variables declared inside the function or parameters passed by value (use return by value instead!)
- returning a large struct or class that was passed by reference (use return by reference instead!)

### 15.15.2.5 Return by reference

Not possible for literals or expressions (no address)!

To use, when

- returning a reference parameter
- returning a member of an object that was passed into the function by reference or address
- returning a large struct or class that will not be destroyed at the end of the function

**Not** to use, when

- returning variables declared inside the function or parameters passed by value (use return by value instead!)
- returning a built-in array or pointer value (use return by address)

### 15.15.2.6 Returning multiple values

To return multiple values

- a struct (or in principle a class)
- `std::tuple` can be used!

### 15.15.3 Function overloading

**Function overloading is a feature of C++ that allows us to create multiple functions with the same name, so long as they have different parameters.**

**Attention:** Function return types are not considered distinct!

### 15.15.4 Default arguments

A default argument is a default value provided for a function parameter. If the user does not supply an explicit argument for a parameter with a default argument, the default value will be used. If the user does supply an argument for the parameter, the user-supplied argument is used. Because the user can choose whether to supply a specific argument value, or use the default, a parameter with a default value provided is often called an optional parameter.

### 15.15.5 Function pointers

**Function pointers** point to functions!

- non-const function pointer: `int (fcnPtr)()`
- *const function pointer*: `int (*const fcnPtr)()`
- *use type aliases to make function pointers \*prettier*: using `ValidateFunction = bool (*)(int, int)`
- using `std::function` (from e.g. `<functional>`): `std::function<bool(int, int)> fcn`

Using function pointers, functions can be passed to other functions as arguments.

### 15.15.6 The stack and the heap

The memory a program uses is divided into:

- The code segment (also called a text segment), where the compiled program sits in memory. The code segment is typically read-only.
- The bss segment (also called the uninitialized data segment), where zero-initialized global and static variables are stored.
- The data segment (also called the initialized data segment), where initialized global and static variables are stored.
- The heap, where dynamically allocated variables are allocated from.
- The call stack, where function parameters, local variables, and other function-related information are stored.



### 15.15.6.1 Heap

The heap segment (also known as the “free store”) keeps track of memory used for dynamic memory allocation (when using *new* and *delete*).

### 15.15.6.2 Stack

The call stack (usually referred to as “the stack”) has a much more interesting role to play. The call stack keeps track of all the active functions (those that have been called but have not yet terminated) from the start of the program to the current point of execution, and handles allocation of all function parameters and local variables.

## 15.15.7 Recursion

Recursive functions are functions that call themselves.

## 15.15.8 Variable number of parameters - Ellipsis

All parameters a function will take must be known in advance (even if they have default values). However, there are certain cases where it can be useful to be able to pass a variable number of parameters to a function. C++ provides a special specifier known as ellipsis *\*...\**.

**Avoid using ellipsis, for many reasons ... !**

## 15.15.9 Lambdas - anonymous functions

See [Lambdas](#) for reference!

A **lambda expression** (also *lambda* or *closure*) allows to define an anonymous function inside another function.

The syntax is:

```
{C++}
[ captureClause ] ( parameters ) -> returnType
{
    statements;
}
```

Consequently a trivial lambda looks like: `[] () {}`.

In actuality, lambdas aren't functions (which is part of how they avoid the limitation of C++ not supporting nested functions). They're a special kind of object called a **functor**. **Functors** are objects that contain an overloaded operator() that make them callable like a function.

**Use auto when initializing variables with lambdas, and std::function if you can't initialize the variable with the lambda.**

## 15.15.10 Function templates

Definition in file [Functions.h](#).

## 15.15.11 Function Documentation

### 15.15.11.1 countDown()


```
void countDown (
    int count )
```

A simple recursive function.

Definition at line 57 of file [Functions.cpp](#).

```
00058 {
00059     std::cout << "push " << count << '\n';
00060
00061     if (count > 1) // termination condition
00062         countDown(count-1);
00063
00064     std::cout << "pop " << count << '\n';
00065 }
```

Here is the call graph for this function:



### 15.15.11.2 ellipsis\_example()

```
void ellipsis_example (
    int count,
    ... )
```

A simple function using ellipsis.

Definition at line 83 of file [Functions.cpp](#).

```
00083     {
00084         double sum{ 0 };
00085
00086         // We access the ellipsis through a va_list, so let's declare one
00087         va_list list;
00088
00089         // We initialize the va_list using va_start. The first parameter is
00090         // the list to initialize. The second parameter is the last non-ellipsis
00091         // parameter.
00092         va_start(list, count);
00093
00094         // Loop through all the ellipsis arguments
00095         for (int arg{ 0 }; arg < count; ++arg)
00096         {
00097             // We use va_arg to get parameters out of our ellipsis
00098             // The first parameter is the va_list we're using
00099             // The second parameter is the type of the parameter
00100             sum += va_arg(list, int);
00101         }
00102
00103         // Cleanup the va_list when we're done.
00104         va_end(list);
00105
00106         std::cout << "average = " << sum / count << std::endl;
00107     }
```

### 15.15.11.3 func\_default\_arg()

```
void func_default_arg (
    int x,
    int y = 10 )
```

Function with default argument (optional parameter)

Definition at line 52 of file [Functions.cpp](#).

```
00052     {
00053         std::cout << "x = " << x << std::endl;
00054         std::cout << "y = " << y << std::endl;
00055     }
```

### 15.15.11.4 lambda\_example()

```
void lambda_example (
    std::array< std::string_view, 4 > arr )
```

A simple lambda function.

Definition at line 67 of file [Functions.cpp](#).

```

00067     {
00068     const auto found{ std::find_if(arr.begin(), arr.end(),
00069     [](std::string_view str) // here's our lambda, no capture clause
00070     {
00071         return (str.find("nut") != std::string_view::npos);
00072     }) };
00073
00074     if (found == arr.end())
00075     {
00076         std::cout << "No nuts\n";
00077     }
00078     else {
00079         std::cout << "Found " << *found << '\n';
00080     }
00081 }

```

#### 15.15.11.5 max()

```

template<typename T >
T max (

```

```

    T x,
    T y )

```

A simple template function.

Definition at line 109 of file [Functions.cpp](#).

```

00109     {
00110     return (x > y) ? x : y;
00111 }

```

#### 15.15.11.6 overload\_add() [1/2]

```

int overload_add (
    int a,
    int b )

```

Function adding two values.

Definition at line 42 of file [Functions.cpp](#).

```

00042     {
00043     std::cout << "overload_add(int a, int b)" << std::endl;
00044     return a + b;
00045 }

```

#### 15.15.11.7 overload\_add() [2/2]

```

int overload_add (
    int a,
    int b,
    int c )

```

(Overloaded) Function adding three values

Definition at line 47 of file [Functions.cpp](#).

```

00047     {
00048     std::cout << "overload_add(int a, int b, int c)" << std::endl;
00049     return a + b + c;
00050 }

```

#### 15.15.11.8 pass\_by\_address()

```

void pass_by_address (
    int * x )

```

Function passing argument by address.

Definition at line 18 of file [Functions.cpp](#).

```

00018     {
00019     std::cout << "func: pass_by_address(int *ptr)" << std::endl;
00020     std::cout << "ptr = 4" << std::endl;
00021     *ptr = 4;
00022 }

```

**15.15.11.9 pass\_by\_reference()**

```
void pass_by_reference (
    int & x )
```

Function passing argument by reference.

Definition at line 12 of file [Functions.cpp](#).

```
00012     {
00013         std::cout << "func: pass_by_reference(int &x)" << std::endl;
00014         std::cout << "x += 1" << std::endl;
00015         x = x + 1;
00016     }
```

**15.15.11.10 pass\_by\_value()**

```
void pass_by_value (
    int x )
```

Function passing argument by value.

Definition at line 7 of file [Functions.cpp](#).

```
00007     {
00008         std::cout << "func: pass_by_value(int x)" << std::endl;
00009         std::cout << "x = " << x << std::endl;
00010     }
```

**15.15.11.11 return\_by\_address()**

```
int* return_by_address ( )
```

Function returning value by address.

Definition at line 36 of file [Functions.cpp](#).

```
00036     {
00037         std::cout << "func: return_by_address()" << std::endl;
00038         int value{ 2 };
00039         return &value; // return value by address
00040     } // value destroyed here
```

**15.15.11.12 return\_by\_reference()**

```
int& return_by_reference ( )
```

Function returning value by reference.

Definition at line 30 of file [Functions.cpp](#).

```
00030     {
00031         std::cout << "func: return_by_reference()" << std::endl;
00032         int value{ 2 };
00033         return value; // return a reference to value
00034     }
```

**15.15.11.13 return\_by\_value()**

```
int return_by_value ( )
```

Function returning value by value.

Definition at line 24 of file [Functions.cpp](#).

```
00024     {
00025         std::cout << "func: return_by_value()" << std::endl;
00026         int value{ 2 };
00027         return value; // a copy of value will be returned
00028     } // value destroyed here
```

**15.16 Functions.h**

```
00001 //
00002 // Created by Michael Staneker on 08.12.20.
00003 //
00004
00005 #include <array>
00006 #include <iostream>
00007
```

```

00008 #ifndef CPP_TEMPLATE_PROJECT_FUNCTIONS_H
00009 #define CPP_TEMPLATE_PROJECT_FUNCTIONS_H
00010
00273 // \fn void pass_by_value(int)
00274
00278 void pass_by_value(int x);
00279
00283 void pass_by_reference(int &x);
00284
00288 void pass_by_address(int *x);
00289
00290
00294 int return_by_value();
00295
00299 int& return_by_reference();
00300
00304 int* return_by_address();
00305
00309 int overload_add(int a, int b);
00310
00314 int overload_add(int a, int b, int c);
00315
00316
00320 void func_default_arg(int x, int y=10);
00321
00325 void countDown(int count);
00326
00330 void ellipsis_example(int count, ...);
00331
00335 void lambda_example(std::array<std::string_view, 4> arr);
00336
00340 template <typename T> T max(T x, T y);
00341
00342
00343
00344
00345 #endif //CPP_TEMPLATE_PROJECT_FUNCTIONS_H

```


## 15.17 learningCpp/Basics/Iterators.cpp File Reference

```

#include <array>
#include <cstdint>
#include <iostream>
#include <iterator>

```

Include dependency graph for Iterators.cpp:



### Functions

- int [main](#) ()

#### 15.17.1 Function Documentation

### 15.17.1.1 main()

```
int main ( )
```

#### Iterators

Definition at line 6 of file [Iterators.cpp](#).

```
00007 {
00008     // The type is automatically deduced to std::array<int, 7> (Requires C++17).
00009     // Use the type std::array<int, 7> if your compiler doesn't support C++17.
00010     std::array<int, 7> data{ 0, 1, 2, 3, 4, 5, 6 };
00011     std::size_t length{ std::size(data) };
00012
00013     // while-loop with explicit index
00014     std::cout << "While loop with explicit index" << std::endl;
00015     std::size_t index{ 0 };
00016     while (index != length)
00017     {
00018         std::cout << data[index] << ' ';
00019         ++index;
00020     }
00021     std::cout << '\n';
00022
00023     // for-loop with explicit index
00024     std::cout << "For loop with explicit index" << std::endl;
00025     for (index = 0; index < length; ++index)
00026     {
00027         std::cout << data[index] << ' ';
00028     }
00029     std::cout << '\n';
00030
00031     // for-loop with pointer (Note: ptr can't be const, because we increment it)
00032     std::cout << "For loop with pointer" << std::endl;
00033     for (auto ptr{ &data[0] }; ptr != (&data[0] + length); ++ptr)
00034     {
00035         std::cout << *ptr << ' ';
00036     }
00037     std::cout << '\n';
00038
00039     // ranged-based for loop
00040     std::cout << "Range based for loop" << std::endl;
00041     for (int i : data)
00042     {
00043         std::cout << i << ' ';
00044     }
00045     std::cout << '\n';
00046
00047     std::cout << std::endl;
00048
00049     // Pointers (simplest kind of Iterators)
00050     std::cout << "Iterator: Pointer..." << std::endl;
00051     auto begin{ &data[0] };
00052     // note that this points to one spot beyond the last element
00053     auto end{ begin + std::size(data) };
00054
00055     // for-loop with pointer
00056     for (auto ptr{ begin }; ptr != end; ++ptr) // ++ to move to next element
00057     {
00058         std::cout << *ptr << ' '; // Indirection to get value of current element
00059     }
00060     std::cout << '\n';
00061
00062     // Standard library iterators
00063     std::cout << "Standard library iterators..." << std::endl;
00064     // Ask our array for the begin and end points (via the begin and end member functions).
00065     begin = { data.begin() };
00066     end = { data.end() };
00067
00068     for (auto p{ begin }; p != end; ++p) // ++ to move to next element.
00069     {
00070         std::cout << *p << ' '; // Indirection to get value of current element.
00071     }
00072     std::cout << '\n';
00073
00074     //
00075     std::cout << "or..." << std::endl;
00076
00077     begin = { std::begin(data) };
00078     end = { std::end(data) };
00079
00080     for (auto p{ begin }; p != end; ++p) // ++ to move to next element
00081     {
00082         std::cout << *p << ' '; // Indirection to get value of current element
00083     }
00084     std::cout << '\n';
00085
00086     return 0;
00087 }
00088
00089
00090 }
```

## 15.18 Iterators.cpp

```

00001 #include <array>
00002 #include <cstdint>
00003 #include <iostream>
00004 #include <iterator>
00005
00006 int main()
00007 {
00008     // The type is automatically deduced to std::array<int, 7> (Requires C++17).
00009     // Use the type std::array<int, 7> if your compiler doesn't support C++17.
00010     std::array<int, 7> data{ 0, 1, 2, 3, 4, 5, 6 };
00011     std::size_t length{ std::size(data) };
00012
00013     // while-loop with explicit index
00014     std::cout << "While loop with explicit index" << std::endl;
00015     std::size_t index{ 0 };
00016     while (index != length)
00017     {
00018         std::cout << data[index] << ' ';
00019         ++index;
00020     }
00021     std::cout << '\n';
00022
00023     // for-loop with explicit index
00024     std::cout << "For loop with explicit index" << std::endl;
00025     for (index = 0; index < length; ++index)
00026     {
00027         std::cout << data[index] << ' ';
00028     }
00029     std::cout << '\n';
00030
00031     // for-loop with pointer (Note: ptr can't be const, because we increment it)
00032     std::cout << "For loop with pointer" << std::endl;
00033     for (auto ptr{ &data[0] }; ptr != (&data[0] + length); ++ptr)
00034     {
00035         std::cout << *ptr << ' ';
00036     }
00037     std::cout << '\n';
00038
00039     // ranged-based for loop
00040     std::cout << "Range based for loop" << std::endl;
00041     for (int i : data)
00042     {
00043         std::cout << i << ' ';
00044     }
00045     std::cout << '\n';
00046
00047     std::cout << std::endl;
00048
00049     // Pointers (simplest kind of Iterators)
00050     std::cout << "Iterator: Pointer..." << std::endl;
00051     auto begin{ &data[0] };
00052     // note that this points to one spot beyond the last element
00053     auto end{ begin + std::size(data) };
00054
00055     // for-loop with pointer
00056     for (auto ptr{ begin }; ptr != end; ++ptr) // ++ to move to next element
00057     {
00058         std::cout << *ptr << ' '; // Indirection to get value of current element
00059     }
00060     std::cout << '\n';
00061
00062     // Standard library iterators
00063     std::cout << "Standard library iterators..." << std::endl;
00064     // Ask our array for the begin and end points (via the begin and end member functions).
00065     begin = { data.begin() };
00066     end = { data.end() };
00067
00068     for (auto p{ begin }; p != end; ++p) // ++ to move to next element.
00069     {
00070         std::cout << *p << ' '; // Indirection to get value of current element.
00071     }
00072     std::cout << '\n';
00073
00074     //
00075     std::cout << "or..." << std::endl;
00076
00077     begin = { std::begin(data) };
00078     end = { std::end(data) };
00079
00080     for (auto p{ begin }; p != end; ++p) // ++ to move to next element
00081     {
00082         std::cout << *p << ' '; // Indirection to get value of current element
00083     }
00084     std::cout << '\n';
00085
00086


```

```
00089     return 0;  
00090 }
```

## 15.19 learningCpp/Basics/Macros.cpp File Reference

```
#include <iostream>
```

Include dependency graph for Macros.cpp:



### Macros

- `#define` [PI](#) 3.1415
- `#define` [EULER](#)

### Functions

- `int` [main](#) ()

## 15.19.1 Macro Definition Documentation

### 15.19.1.1 EULER

```
#define EULER
```

Definition at line [21](#) of file [Macros.cpp](#).

### 15.19.1.2 PI

```
#define PI 3.1415
```

Header guards (conditional compilation directive)

Definition at line [18](#) of file [Macros.cpp](#).

## 15.19.2 Function Documentation

### 15.19.2.1 main()

```
int main ( )
```

Definition at line [25](#) of file [Macros.cpp](#).

```
00025     {  
00026
```



```

00027 #ifdef PI // or if not defined use #ifndef
00028     std::cout << "PI is: " << PI << std::endl
00029 //elif
00030 //else
00031 #endif
00032
00033 #ifdef EULER
00034     std::cout << "EULER is defined, but not replaceable, or rather replaceable by empty"
00035 #endif
00036
00037     return 0;
00038 }

```

## 15.20 Macros.cpp

```


00001 //
00002 // Created by Michael Staneker on 01.12.20.
00003 //
00004
00005 #include <iostream>
00006
00008 //ifndef SOME_UNIQUE_NAME_HERE
00009 //define SOME_UNIQUE_NAME_HERE
00010 //
00011 //endif
00012
00013 // or alternatively use, but bit supported by all compilers
00014 //pragma once
00017 // define macro (with substitution text)
00018 #define PI 3.1415
00019
00020 // empty substitution text
00021 #define EULER
00022
00023
00024
00025 int main() {
00026
00027     #ifdef PI // or if not defined use #ifndef
00028         std::cout << "PI is: " << PI << std::endl
00029     //elif
00030     //else
00031     #endif
00032
00033     #ifdef EULER
00034         std::cout << "EULER is defined, but not replaceable, or rather replaceable by empty"
00035     #endif
00036
00037     return 0;
00038 }

```

## 15.21 learningCpp/Basics/Pointers.cpp File Reference

```
#include <iostream>
```

Include dependency graph for Pointers.cpp:



## Functions

- int `main` ()  
*Brief description.*

### 15.21.1 Function Documentation

#### 15.21.1.1 `main()`

```
int main ( )
```

Brief description.

#### 15.21.2 Introduction to Pointers

More detailed description

##### Author

Autor 1  
Autor 2

##### Version

Version number

##### Date

Date

##### Precondition

Preconditions ...

##### Postcondition

Postconditions ...

**Bug** Bugs ...

##### Warning

This is a warning ...

##### Attention

Attenzione Attenzione ...

##### Note

This is a note

##### Remarks

This is a remark

##### Copyright

GNU Public License.

Since

Since when ...

- Todo**
- add a
  - add b
  - add c

**Test** Describing test case ...

User defined paragraph

Contents of the paragraph.

New paragraph under the same heading

Example of a param command with a description consisting of two paragraphs


Parameters

$p$	First paragraph of the param description. Second paragraph of the param description.
-----	---

Rest of the comment block continues.

```
* Verbatim
* ...
* ...
*
```

The receiver will acknowledge the command by calling Ack().



formula example

$$x_s = \frac{2}{3} \cdot 2^4$$

**Some Markdown**

See url-reference: [LearnCpp](#)

List:

- a
- b
- c

**15.21.2.1 Address operator &**

**15.21.2.2 Indirection operator \***

**15.21.2.3 Pointers**

**15.21.2.3.1 pointer**

**15.21.2.3.2 Pointers**

**15.21.2.3.3 arithmetic**

```

*/
std::cout << &array[1] << '\n'; // print memory address of array element 1
std::cout << array+1 << '\n'; // print memory address of array pointer + 1
std::cout << array[1] << '\n'; // prints 7
std::cout << *(array+1) << '\n'; // prints 7 (note the parenthesis required here)

```

**15.21.2.3.4 memory allocation**

```

*/
//new int; // dynamically allocate an integer (and discard the result)
int *ptr_dyn{ new int }; // dynamically allocate an integer and assign the address to ptr so we can access
// it later
*ptr_dyn = 7;
// equivalent: int *ptr_dyn{ new int { 7 } }
std::cout << "ptr_dyn = " << ptr_dyn << std::endl;
std::cout << *ptr_dyn = " << *ptr_dyn << std::endl;
// delete
delete ptr_dyn; // return the memory pointed to by ptr to the operating system
ptr_dyn = 0; // set ptr to be a null pointer (use nullptr instead of 0 in C++11)
// Dynamically allocating arrays
int *dyn_array{ new int[5]{ 9, 7, 5, 3, 1 } }; // initialize a dynamic array since C++11
// To prevent writing the type twice, we can use auto. This is often done for types with long names.
//auto *array{ new int[5]{ 9, 7, 5, 3, 1 } };
delete [] dyn_array;

```

**15.21.2.3.5 pointers (generic pointer)**

```

*/
int nValue;
float fValue;
struct Something
{
    int n;
    float f;
};
Something sValue;
void *void_ptr;
void_ptr = &nValue; // valid
void_ptr = &fValue; // valid
void_ptr = &sValue; // valid
// ATTENTION: indirection is only possible using a cast

```

**15.21.2.3.6 Pointers**

```

*/
int value_for_pointer = 5;
int *primary_ptr = &value_for_pointer;
std::cout << "ptr = " << *primary_ptr << std::endl; // Indirection through pointer to int to get int value
int **ptrptr = &primary_ptr;
std::cout << "ptrptr = " << **ptrptr << std::endl; // first indirection to get pointer to int, second
// indirection to get int value
int **pointer_array = new int*[10]; // allocate an array of 10 int pointers

```

[top](#) [\["go to the top"\]](#)

Definition at line 76 of file [Pointers.cpp](#).

```

00076     {
00077
00078         int x{ 5 };
00079         std::cout << "    x = " << x << '\n'; // print the value of variable x
00080
00082         std::cout << "    &x = " << &x << '\n'; // print the memory address of variable x
00086         std::cout << "*(&x) = " << *(&x) << '\n'; // print the memory address of variable x
00090         //int *iPtr{}; // a pointer to an integer value
00091         //double *dPtr{}; // a pointer to a double value
00092         //int* iPtr2{}; // also valid syntax (acceptable, but not favored)
00093         //int * iPtr3{}; // also valid syntax (but don't do this, it looks like multiplication)
00094         //int *iPtr4{}, *iPtr5{}; // declare two pointers to integer variables (not recommended)
00095
00096         int var{ 5 };
00097         int *ptr{ &var }; // initialize ptr with address of variable v
00098         std::cout << "var = " << var << '\n'; // print the address of variable v
00099         std::cout << "var = " << &var << '\n'; // print the address of variable v
00100         std::cout << "ptr = " << ptr << '\n'; // print the address that ptr is holding
00101         std::cout << "*ptr = " << *ptr << '\n';
00102
00103         //    Pointers are good for:
00104         //    * dynamic arrays
00105         //    * dynamically allocate memory
00106         //    * pass large amount of data to a function (without copying)
00107         //    * pass a function as a parameter to another function
00108         //    * achieve polymorphism when dealing with inheritance
00109         //    * useful for advanced data structures
00113         //assigning it to the literal 0
00114         float *null_ptr { 0 }; // ptr is now a null pointer
00115         float *null_ptr2; // ptr2 is uninitialized
00116         null_ptr2 = 0; // ptr2 is now a null pointer
00117         float *null_ptr3 {nullptr}; // C++11
00121         int array[5]{ 9, 7, 5, 3, 1 };
00122         std::cout << *array << '\n'; // will print 9
00123         int *ptr_for_array{ array };

```

```

00124     std::cout << *ptr_for_array << '\n'; // will print 9
00125
00126     // ARRAYS DECAY INTO POINTERS WHEN PASSED TO FUNCTIONS !!!
00133     std::cout << &array[1] << '\n'; // print memory address of array element 1
00134     std::cout << array+1 << '\n'; // print memory address of array pointer + 1
00135     std::cout << array[1] << '\n'; // prints 7
00136     std::cout << *(array+1) << '\n'; // prints 7 (note the parenthesis required here)
00145     //new int; // dynamically allocate an integer (and discard the result)
00146     int *ptr_dyn{ new int }; // dynamically allocate an integer and assign the address to ptr so we
can access it later
00147     *ptr_dyn = 7;
00148     // equivalent: int *ptr_dyn{ new int { 7 } }
00149     std::cout << "ptr_dyn = " << ptr_dyn << std::endl;
00150     std::cout << "*ptr_dyn = " << *ptr_dyn << std::endl;
00151
00152     // delete
00153     delete ptr_dyn; // return the memory pointed to by ptr to the operating system
00154     ptr_dyn = 0; // set ptr to be a null pointer (use nullptr instead of 0 in C++11)
00155
00156
00157     // Dynamically allocating arrays
00158     int *dyn_array{ new int[5]{ 9, 7, 5, 3, 1 } }; // initialize a dynamic array since C++11
00159     // To prevent writing the type twice, we can use auto. This is often done for types with long
names.
00160     //auto *array{ new int[5]{ 9, 7, 5, 3, 1 } };
00161     delete [] dyn_array;
00171     int nValue;
00172     float fValue;
00173     struct Something
00174     {
00175         int n;
00176         float f;
00177     };
00178     Something sValue;
00179     void *void_ptr;
00180     void_ptr = &nValue; // valid
00181     void_ptr = &fValue; // valid
00182     void_ptr = &sValue; // valid
00183     // ATTENTION: indirection is only possible using a cast
00192     int value_for_pointer = 5;
00193
00194     int *primary_ptr = &value_for_pointer;
00195     std::cout << "ptr = " << *primary_ptr << std::endl; // Indirection through pointer to int to get int
value
00196
00197     int **ptrptr = &primary_ptr;
00198     std::cout << "ptrptr = " << **ptrptr << std::endl; // first indirection to get pointer to int, second
indirection to get int value
00199
00200     int **pointer_array = new int*[10]; // allocate an array of 10 int pointers
00205     return 0;
00206
00210 }

```

## 15.22 Pointers.cpp

```

00001 //
00002 // Created by Michael Staneker on 03.12.20.
00003 //
00004
00005 #include <iostream>
00006
00076 int main() {
00077
00078     int x{ 5 };
00079     std::cout << "    x = " << x << '\n'; // print the value of variable x
00080
00082     std::cout << "    &x = " << &x << '\n'; // print the memory address of variable x
00086     std::cout << "*(&x) = " << *(&x) << '\n'; // print the memory address of variable x
00090     //int *iPtr{}; // a pointer to an integer value
00091     //double *dPtr{}; // a pointer to a double value
00092     //int* iPtr2{}; // also valid syntax (acceptable, but not favored)
00093     //int * iPtr3{}; // also valid syntax (but don't do this, it looks like multiplication)
00094     //int *iPtr4{}, *iPtr5{}; // declare two pointers to integer variables (not recommended)
00095
00096     int var{ 5 };
00097     int *ptr{ &var }; // initialize ptr with address of variable v
00098     std::cout << "var = " << var << '\n'; // print the address of variable v
00099     std::cout << "var = " << &var << '\n'; // print the address of variable v
00100     std::cout << "ptr = " << ptr << '\n'; // print the address that ptr is holding
00101     std::cout << "*ptr = " << *ptr << '\n';
00102
00103     //    Pointers are good for:
00104     //    * dynamic arrays
00105     //    * dynamically allocate memory

```

```


00106 // * pass large amount of data to a function (without copying)
00107 // * pass a function as a parameter to another function
00108 // * achieve polymorphism when dealing with inheritance
00109 // * useful for advanced data structures
00113 //assigning it to the literal 0
00114 float *null_ptr { 0 }; // ptr is now a null pointer
00115 float *null_ptr2; // ptr2 is uninitialized
00116 null_ptr2 = 0; // ptr2 is now a null pointer
00117 float *null_ptr3 {nullptr}; // C++11
00121 int array[5]{ 9, 7, 5, 3, 1 };
00122 std::cout << *array << '\n'; // will print 9
00123 int *ptr_for_array{ array };
00124 std::cout << *ptr_for_array << '\n'; // will print 9
00125
00126 // ARRAYS DECAY INTO POINTERS WHEN PASSED TO FUNCTIONS !!!
00133 std::cout << &array[1] << '\n'; // print memory address of array element 1
00134 std::cout << array+1 << '\n'; // print memory address of array pointer + 1
00135 std::cout << array[1] << '\n'; // prints 7
00136 std::cout << *(array+1) << '\n'; // prints 7 (note the parenthesis required here)
00145 //new int; // dynamically allocate an integer (and discard the result)
00146 int *ptr_dyn{ new int }; // dynamically allocate an integer and assign the address to ptr so we
can access it later
00147 *ptr_dyn = 7;
00148 // equivalent: int *ptr_dyn{ new int { 7 } }
00149 std::cout << "ptr_dyn = " << ptr_dyn << std::endl;
00150 std::cout << "*ptr_dyn = " << *ptr_dyn << std::endl;
00151
00152 // delete
00153 delete ptr_dyn; // return the memory pointed to by ptr to the operating system
00154 ptr_dyn = 0; // set ptr to be a null pointer (use nullptr instead of 0 in C++11)
00155
00156
00157 // Dynamically allocating arrays
00158 int *dyn_array{ new int[5]{ 9, 7, 5, 3, 1 } }; // initialize a dynamic array since C++11
00159 // To prevent writing the type twice, we can use auto. This is often done for types with long
names.
00160 //auto *array{ new int[5]{ 9, 7, 5, 3, 1 } };
00161 delete [] dyn_array;
00171 int nValue;
00172 float fValue;
00173 struct Something
00174 {
00175     int n;
00176     float f;
00177 };
00178 Something sValue;
00179 void *void_ptr;
00180 void_ptr = &nValue; // valid
00181 void_ptr = &fValue; // valid
00182 void_ptr = &sValue; // valid
00183 // ATTENTION: indirection is only possible using a cast
00192 int value_for_pointer = 5;
00193
00194 int *primary_ptr = &value_for_pointer;
00195 std::cout << "ptr = " << *primary_ptr << std::endl; // Indirection through pointer to int to get int
value
00196
00197 int **ptrptr = &primary_ptr;
00198 std::cout << "ptrptr = " << **ptrptr << std::endl; // first indirection to get pointer to int, second
indirection to get int value
00199
00200 int **pointer_array = new int*[10]; // allocate an array of 10 int pointers
00205 return 0;
00206
00210 }
00211
00212
00213

```

## 15.23 learningCpp/Basics/ReferenceVariables.cpp File Reference

```
#include <iostream>
```

Include dependency graph for ReferenceVariables.cpp:



## Functions

- `int main()`

### 15.23.1 Function Documentation

#### 15.23.1.1 main()

```
int main ( )
```

Reference variables

Definition at line 7 of file [ReferenceVariables.cpp](#).

```

00007     {
00008
00009         int value {5};
00010
00012         int &reference{ value }; // "reference to" value
00013         //int& reference{ value }; // valid
00014         //int & reference{ value }; // valid
00015
00016         int x{ 5 }; // normal integer
00017         int &y{ x }; // y is a reference to x
00018         int &z{ y }; // z is also a reference to x
00019
00020         std::cout << " x = " << x << std::endl;
00021         std::cout << " y = " << y << std::endl;
00022         std::cout << " z = " << z << std::endl;
00023         std::cout << "&x = " << &x << std::endl;
00024         std::cout << "&y = " << &y << std::endl;
00025         std::cout << "&z = " << &z << std::endl;
00026
00027         // References cannot be reassigned !
00028         // reference = value; // not valid
00029
00030
00033         return 0;
00034     }
```

## 15.24 ReferenceVariables.cpp

```

00001 //
00002 // Created by Michael Staneker on 03.12.20.
00003 //
00004
00005 #include <iostream>
00006
00007 int main() {
00008
00009     int value {5};
00010
00012     int &reference{ value }; // "reference to" value
```

```

00013      //int& reference{ value }; // valid
00014      //int & reference{ value }; // valid
00015
00016      int x{ 5 }; // normal integer
00017      int &y{ x }; // y is a reference to x
00018      int &z{ y }; // z is also a reference to x
00019
00020      std::cout << " x = " << x << std::endl;
00021      std::cout << " y = " << y << std::endl;
00022      std::cout << " z = " << z << std::endl;
00023      std::cout << "&x = " << &x << std::endl;
00024      std::cout << "&y = " << &y << std::endl;
00025      std::cout << "&z = " << &z << std::endl;
00026
00027      // References cannot be reassigned !
00028      // reference = value; // not valid
00029
00030
00033      return 0;
00034 }
00035


```

## 15.25 learningCpp/Errors/ErrorHandler.cpp File Reference

```
#include "ErrorHandler.h"
```

```
#include <iostream>
```

Include dependency graph for ErrorHandler.cpp:



### Functions

- int [returning\\_error\\_code](#) ()
- void [write\\_error\\_message](#) ()
- void [exit\\_program](#) ()
- void [assert\\_example](#) (int x)
- int [main](#) ()

### 15.25.1 Function Documentation

#### 15.25.1.1 assert\_example()

```

void assert_example (
    int x )

```



Definition at line 22 of file [ErrorHandling.cpp](#).

```
00022     {
00023         std::cout << "assert() example" << std::endl;
00024         std::cout << "x = " << x << std::endl;
00025         //terminates if assert evaluates to true
00026         assert(x > 0);
00027     }
```

### 15.25.1.2 exit\_program()

```
void exit_program ( )
```

Definition at line 17 of file [ErrorHandling.cpp](#).

```
00017     {
00018         std::cout << "Exiting with error number 2 to OS" << std::endl;
00019         std::exit(2);
00020     }
```


### 15.25.1.3 main()

```
int main ( )
```

Definition at line 29 of file [ErrorHandling.cpp](#).

```
00029     {
00030
00031         int error_code = returning_error_code();
00032         std::cout << "error code received from returning_error_code: " << error_code << std::endl;
00033
00034         write_error_message();
00035
00036         // assert() evaluates to false if x <= 0
00037         assert_example(1);
00038
00039         //exit_program();
00040         //std::cout << "This shouldn't be printed!!!" << std::endl;
00041
00042         return 0;
00043
00044     }
```

Here is the call graph for this function:



### 15.25.1.4 returning\_error\_code()

```
int returning_error_code ( )
```

## 15.25.2 Error handling

Errors fall into two categories:

- **Syntax errors** occurring when a statement is not valid according to the grammar of the C++ language
- **Semantic errors** occurring when a statement is syntactically valid, but does not do what the programmer intended

### 15.25.2.1 Assert statements

An assert statement is a preprocessor macro that evaluates a conditional expression at runtime. If the conditional expression is true, the assert statement does nothing. If the conditional expression evaluates to false, an error message is displayed and the program is terminated. This error message contains the conditional expression that failed, along with the name of the code file and the line number of the assert.

**15.25.2.1.1 assert()** Include `<cstdlib>` for `assert()`, operating at runtime, which comes with a small performance cost that is incurred each time the assert condition is checked, which can be disabled by defining the **NDEBUG** macro.

**15.25.2.1.2 static\_assert()** Another type of assert is `static_assert<condition, diagnostic_message>`, designed to operate at compile time.

**Attention** There is no chance for cleanup after terminating with `exit()` or `assert()`!

Definition at line 9 of file [ErrorHandling.cpp](#).

```
00009 {
00010     return -1;
00011 }
```

### 15.25.2.2 write\_error\_message()

```
void write_error_message ( )
```

Definition at line 13 of file [ErrorHandling.cpp](#).

```
00013 {
00014     std::cerr << "This is an error message!" << std::endl;
00015 }
```

## 15.26 ErrorHandling.cpp

```
00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include "ErrorHandling.h"
00006
00007 #include <iostream>
00008
00009 int returning_error_code() {
00010     return -1;
00011 }
00012
00013 void write_error_message() {
00014     std::cerr << "This is an error message!" << std::endl;
00015 }
00016
00017 void exit_program() {
00018     std::cout << "exiting with error number 2 to OS" << std::endl;
00019     std::exit(2);
00020 }
00021
00022 void assert_example(int x) {
00023     std::cout << "assert() example" << std::endl;
00024     std::cout << "x = " << x << std::endl;
00025     //terminates if assert evaluates to true
00026     assert(x > 0);
00027 }
00028
00029 int main() {
00030
00031     int error_code = returning_error_code();
00032     std::cout << "error code received from returning_error_code: " << error_code << std::endl;
00033
00034     write_error_message();
00035
00036     // assert() evaluates to false if x <= 0
00037     assert_example(1);
```


```
00038
00039     //exit_program();
00040     //std::cout << "This shouldn't be printed!!!" << std::endl;
00041
00042     return 0;
00043
00044 }
```

## 15.27 learningCpp/Errors/ErrorHandling.h File Reference


```
#include <cstdlib>
```

```
#include <cassert>
```

Include dependency graph for ErrorHandling.h:



This graph shows which files directly or indirectly include this file:



### Macros

- `#define` [CPP\\_TEMPLATE\\_PROJECT\\_ERRORHANDLING\\_H](#)

### Functions

- `int` [returning\\_error\\_code](#) ()
- `void` [write\\_error\\_message](#) ()
- `void` [exit\\_program](#) ()
- `void` [assert\\_example](#) (int x)

## 15.27.1 Macro Definition Documentation

### 15.27.1.1 CPP\_TEMPLATE\_PROJECT\_ERRORHANDLING\_H

```
#define CPP_TEMPLATE_PROJECT_ERRORHANDLING_H
```

Definition at line 9 of file [ErrorHandling.h](#).

## 15.27.2 Function Documentation

### 15.27.2.1 assert\_example()

```
void assert_example (
    int x )
```

Definition at line 22 of file [ErrorHandling.cpp](#).

```
00022     {
00023         std::cout << "assert() example" << std::endl;
00024         std::cout << "x = " << x << std::endl;
00025         //terminates if assert evaluates to true
00026         assert(x > 0);
00027     }
```

### 15.27.2.2 exit\_program()

```
void exit_program ( )
```

Definition at line 17 of file [ErrorHandling.cpp](#).

```
00017     {
00018         std::cout << "exiting with error number 2 to OS" << std::endl;
00019         std::exit(2);
00020     }
```

### 15.27.2.3 returning\_error\_code()

```
int returning_error_code ( )
```

## 15.27.3 Error handling

Errors fall into two categories:

- **Syntax errors** occurring when a statement is not valid according to the grammar of the C++ language
- **Semantic errors** occurring when a statement is syntactically valid, but does not do what the programmer intended

### 15.27.3.1 Assert statements

An assert statement is a preprocessor macro that evaluates a conditional expression at runtime. If the conditional expression is true, the assert statement does nothing. If the conditional expression evaluates to false, an error message is displayed and the program is terminated. This error message contains the conditional expression that failed, along with the name of the code file and the line number of the assert.

**15.27.3.1.1 assert()** Include `<cstdlib>` for `assert()`, operating at runtime, which comes with a small performance cost that is incurred each time the assert condition is checked, which can be disabled by defining the **NDEBUG** macro.

**15.27.3.1.2 static\_assert()** Another type of assert is `static_assert<condition, diagnostic_message>`, designed to operate at compile time.

**Attention** There is no chance for cleanup after terminating with `exit()` or `assert()`!

Definition at line 9 of file [ErrorHandling.cpp](#).

```
00009      {
00010      return -1;
00011 }
```

### 15.27.3.2 write\_error\_message()

```
void write_error_message ( )
```

Definition at line 13 of file [ErrorHandling.cpp](#).

```
00013      {
00014      std::cerr << "This is an error message!" << std::endl;
00015 }
```


## 15.28 ErrorHandling.h

```
00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include <cstdlib> //for std::exit
00006 #include <cassert> //for assert()
00007
00008 #ifndef CPP_TEMPLATE_PROJECT_ERRORHANDLING_H
00009 #define CPP_TEMPLATE_PROJECT_ERRORHANDLING_H
00010
00040 int returning_error_code();
00041
00042 void write_error_message();
00043
00044 void exit_program();
00045
00046 void assert_example(int x);
00047
00048 #endif //CPP_TEMPLATE_PROJECT_ERRORHANDLING_H
```

## 15.29 learningCpp/Errors/Exceptions.cpp File Reference

```
#include "Exceptions.h"
```

Include dependency graph for Exceptions.cpp:



## 15.30 Exceptions.cpp

```
00001 //
00002 // Created by Michael Staneker on 10.12.20.
```

```

00003 //
00004
00005 #include "Exceptions.h"
00006
00007
00008 ArrayException::ArrayException(std::string_view error)
00009     : m_error{error}
00010 {
00011 }
00012
00013
00014
00015 int IntArray::getLength() const {
00016     return 3;
00017 }
00018
00019 int& IntArray::operator[] (const int index)
00020 {
00021     if (index < 0 || index >= getLength())
00022         throw ArrayException("Invalid index");
00023
00024     return m_data[index];
00025 }
00026
00027
00028 double Sqrt::mySqrt(double x) {
00029     // If the user entered a negative number, this is an error condition
00030     if (x < 0.0)
00031         throw "Can not take sqrt of negative number"; // throw exception of type const char*
00032
00033     return sqrt(x);
00034 }

```


## 15.31 learningCpp/Errors/Exceptions.h File Reference

```


#include <cmath>
#include <exception>
#include <iostream>
#include <string>
#include <string_view>

```

Include dependency graph for Exceptions.h:



This graph shows which files directly or indirectly include this file:



## Classes

- class [ArrayException](#)
- class [IntArray](#)
- class [SQRT](#)
- class [Exceptions](#)

## 15.32 Exceptions.h

```

00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00096 #ifndef CPP_TEMPLATE_PROJECT_EXCEPTIONS_H
00097 #define CPP_TEMPLATE_PROJECT_EXCEPTIONS_H
00098
00099 #include <cmath>
00100 #include <exception> // for std::exception
00101 #include <iostream>
00102 #include <string>
00103 #include <string_view>
00104
00105 class ArrayException : public std::exception
00106 {
00107 private:
00108     std::string m_error{};
00109
00110 public:
00111     ArrayException(std::string_view error);
00112     // return the std::string as a const C-style string
00113     const char* what() const noexcept override {
00114         return m_error.c_str();
00115     }
00116 };
00117
00118 class IntArray
00119 {
00120 private:
00121     int m_data[3]; // assume array is length 3 for simplicity
00122 public:
00123     IntArray() {}
00124
00125     int getLength() const;
00126
00127     int& operator[](const int index);
00128
00129 };
00130
00131
00132
00133 class SQRT {
00134 public:
00135     static double mySqrt(double x);
00136 };
  
```

```

00137
00138
00139 class Exceptions {
00140
00141 };
00142
00143
00144 #endif //CPP_TEMPLATE_PROJECT_EXCEPTIONS_H

```


## 15.33 learningCpp/Errors/TestingExceptions.cpp File Reference

```

#include "Exceptions.h"
#include <iostream>
#include <string>
#include <exception>

```

Include dependency graph for TestingExceptions.cpp:



### Functions

- int [main](#) ()

### 15.33.1 Function Documentation

#### 15.33.1.1 main()

```
int main ( )
```

Definition at line 11 of file [TestingExceptions.cpp](#).

```

00011     {
00012
00013     try
00014     {
00015         // Statements that may throw exceptions you want to handle go here
00016         throw -1; // here's a trivial example
00017     }
00018     catch (int x)
00019     {
00020         // Any exceptions of type int thrown within the above try block get sent here
00021         std::cerr << "We caught an int exception with value: " << x << '\n';
00022     }
00023     catch (double) // no variable name since we don't use the exception itself in the catch block
00024     below
00024     {
00025         // Any exceptions of type double thrown within the above try block get sent here
00026         std::cerr << "We caught an exception of type double" << '\n';
00027     }
00028     catch (const std::string &str) // catch classes by const reference
00029     {

```




```

00030         // Any exceptions of type std::string thrown within the above try block get sent here
00031         std::cerr << "We caught an exception of type std::string" << '\n';
00032     }
00033
00034     std::cout << "Continuing on our merry way\n";
00035
00036     double x{ -1 };
00037
00038
00039     try // Look for exceptions that occur within try block and route to attached catch block(s)
00040     {
00041         double d = SQRT::mySqrt(x);
00042         std::cout << "The sqrt of " << x << " is " << d << '\n';
00043     }
00044     catch (const char* exception) // catch exceptions of type const char*
00045     {
00046         std::cerr << "Error: " << exception << std::endl;
00047     }
00048
00049     try
00050     {
00051         // Your code using standard library goes here
00052         // We'll trigger one of these exceptions intentionally for the sake of example
00053         std::string s;
00054         s.resize(-1); // will trigger a std::length_error
00055     }
00056     // This handler will catch std::exception and all the derived exceptions too
00057     catch (const std::exception &exception)
00058     {
00059         std::cerr << "Standard exception: " << exception.what() << '\n';
00060     }
00061
00062     try
00063     {
00064         throw std::runtime_error("Bad things happened");
00065     }
00066     // This handler will catch std::exception and all the derived exceptions too
00067     catch (const std::exception &exception)
00068     {
00069         std::cerr << "Standard exception: " << exception.what() << '\n';
00070     }
00071
00072     IntArray array;
00073
00074     try
00075     {
00076         int value{ array[5] };
00077     }
00078     catch (const ArrayException &exception) // derived catch blocks go first
00079     {
00080         std::cerr << "An array exception occurred (" << exception.what() << ")\n";
00081     }
00082     catch (const std::exception &exception)
00083     {
00084         std::cerr << "Some other std::exception occurred (" << exception.what() << ")\n";
00085     }
00086
00087     return 0;
00088 }

```

Here is the call graph for this function:



## 15.34 TestingExceptions.cpp

```
00001 //
```

```

00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00005 #include "Exceptions.h"
00006
00007 #include <iostream>
00008 #include <string>
00009 #include <exception>
00010
00011 int main() {
00012
00013     try
00014     {
00015         // Statements that may throw exceptions you want to handle go here
00016         throw -1; // here's a trivial example
00017     }
00018     catch (int x)
00019     {
00020         // Any exceptions of type int thrown within the above try block get sent here
00021         std::cerr << "We caught an int exception with value: " << x << '\n';
00022     }
00023     catch (double) // no variable name since we don't use the exception itself in the catch block
00024     below
00025     {
00026         // Any exceptions of type double thrown within the above try block get sent here
00027         std::cerr << "We caught an exception of type double" << '\n';
00028     }
00029     catch (const std::string &str) // catch classes by const reference
00030     {
00031         // Any exceptions of type std::string thrown within the above try block get sent here
00032         std::cerr << "We caught an exception of type std::string" << '\n';
00033     }
00034     std::cout << "Continuing on our merry way\n";
00035
00036     double x{ -1 };
00037
00038     try // Look for exceptions that occur within try block and route to attached catch block(s)
00039     {
00040         double d = SQRT::mySqrt(x);
00041         std::cout << "The sqrt of " << x << " is " << d << '\n';
00042     }
00043     catch (const char* exception) // catch exceptions of type const char*
00044     {
00045         std::cerr << "Error: " << exception << std::endl;
00046     }
00047
00048     try
00049     {
00050         // Your code using standard library goes here
00051         // We'll trigger one of these exceptions intentionally for the sake of example
00052         std::string s;
00053         s.resize(-1); // will trigger a std::length_error
00054     }
00055     // This handler will catch std::exception and all the derived exceptions too
00056     catch (const std::exception &exception)
00057     {
00058         std::cerr << "Standard exception: " << exception.what() << '\n';
00059     }
00060
00061     try
00062     {
00063         throw std::runtime_error("Bad things happened");
00064     }
00065     // This handler will catch std::exception and all the derived exceptions too
00066     catch (const std::exception &exception)
00067     {
00068         std::cerr << "Standard exception: " << exception.what() << '\n';
00069     }
00070
00071     IntArray array;
00072
00073     try
00074     {
00075         int value{ array[5] };
00076     }
00077     catch (const ArrayException &exception) // derived catch blocks go first
00078     {
00079         std::cerr << "An array exception occurred (" << exception.what() << ")\n";
00080     }
00081     catch (const std::exception &exception)
00082     {
00083         std::cerr << "Some other std::exception occurred (" << exception.what() << ")\n";
00084     }
00085
00086     return 0;
00087


```

```
00088 }
00089
```

## 15.35 learningCpp/OOP/ConceptClass.cpp File Reference

```
#include "../include/ConceptClass.h"
```

Include dependency graph for ConceptClass.cpp:



## 15.36 ConceptClass.cpp

```
00001 #include "../include/ConceptClass.h"
00002
00003 ConceptClass::ConceptClass(int a, int b) {
00004     member_a = a;
00005     member_b = b;
00006 }
```

## 15.37 learningCpp/OOP/constants.h File Reference

### Namespaces

- [constants](#)

### Variables

- constexpr double [constants::pi](#) { 3.141519 }
- constexpr double [constants::avogadro](#) { 6.0221413e23 }

## 15.38 constants.h

```
00001 //
00002 // Created by Michael Staneker on 01.12.20.
00003 //
00004
00005 #ifndef CPP_TEMPLATE_PROJECT_CONSTANTS_H
00006 #define CPP_TEMPLATE_PROJECT_CONSTANTS_H
00007
00008 namespace constants {
00009
00010     constexpr double pi { 3.141519 };
00011     constexpr double avogadro { 6.0221413e23 };
00012
00013     //extern const double pi { 3.141519 };
00014     //extern const double avogadro { 6.0221413e23 };
00015
00016     // C++17 or newer
00017     //inline constexpr double pi { 3.14159 }; // inline constexpr is C++17 or newer only
00018     //inline constexpr double avogadro { 6.0221413e23 };
00019
```

```


00020     // #include "constants.h"
00021     //
00022     // double circumference { 2.0 * radius * constants::pi }
00023 }
00024
00025 #endif // CPP_TEMPLATE_PROJECT_CONSTANTS_H

```

## 15.39 learningCpp/OOP/Inheritance.cpp File Reference

```
#include "Inheritance.h"
```

Include dependency graph for Inheritance.cpp:



## 15.40 Inheritance.cpp

```

00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00005 #include "Inheritance.h"
00006
00007 Base::Base(int id, int var_private, int var_protected, int var_public)
00008     : m_id{ id }, m_private{ var_private }, m_protected{ var_protected },
00009     m_public{ var_public }
00010 {
00011     std::cout << "Base constructor called ..." << std::endl;
00012 }
00013
00014 int Base::getId() const {
00015     return m_id;
00016 }
00017
00018 int Base::getPrivate() const {
00019     std::cout << "getPrivate() from Base" << std::endl;
00020     return m_private;
00021 }
00022
00023 void Base::print() {
00024     std::cout << "Print from Base class!" << std::endl;
00025 }
00026
00027
00028
00029 Derived::Derived(double cost, int id, int var_private, int var_protected, int var_public)
00030     : Base{ id, var_private, var_protected, var_public }, // Call Base(int) constructor with value
00031     id!
00032     m_cost{ cost }
00033 {
00034     std::cout << "Derived constructor called ..." << std::endl;
00035 }
00036 double Derived::getCost() const {

```

```

00037     return m_cost;
00038 }
00039
00040 double Derived::getProtected() const {
00041     return m_protected;
00042 }
00043
00044 double Derived::getPrivate() const {
00045     std::cout << "getPrivate() from Derived" << std::endl;
00046     return Base::getPrivate();
00047 }
00048
00049 void Derived::print() {
00050     std::cout << "Print from Derived class!" << std::endl;
00051 }

```


## 15.41 learningCpp/OOP/Inheritance.h File Reference

```


#include <string>
#include <iostream>

```

Include dependency graph for Inheritance.h:



This graph shows which files directly or indirectly include this file:



### Classes

- class [Base](#)
- class [Derived](#)

## 15.42 Inheritance.h

```

00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00093 #ifndef CPP_TEMPLATE_PROJECT_INHERITANCE_H

```

```


00094 #define CPP_TEMPLATE_PROJECT_INHERITANCE_H
00095
00096 #include <string>
00097 #include <iostream>
00098
00099 class Base
00100 {
00101 private:
00102     int m_id;
00103     int m_private;
00104 protected:
00105     int m_protected;
00106     int getPrivate() const;
00107 public:
00108     int m_public;
00109
00110     Base(int id=0, int var_private=0, int var_protected=0, int var_public=0);
00111
00112     int getId() const;
00113
00114     virtual void print();
00115 };
00116
00117 class Derived: public Base
00118 {
00119 private:
00120     double m_cost;
00121
00122 public:
00123     Derived(double cost=0.0, int id=0, int var_private=0, int var_protected=0, int var_public=0);
00124     double getCost() const;
00125     double getProtected() const;
00126     double getPrivate() const;
00127
00128     virtual void print();
00129 };
00130
00131 #endif //CPP_TEMPLATE_PROJECT_INHERITANCE_H

```

## 15.43 learningCpp/OOP/SampleClass.cpp File Reference

#include "SampleClass.h"

Include dependency graph for SampleClass.cpp:



## Functions

- void [friend\\_function](#) ([SampleClass](#) &sample\_class)
- [SampleClass](#) operator+ (const [SampleClass](#) &s\_1, const [SampleClass](#) &s\_2)
- std::ostream & [operator<<](#) (std::ostream &out, const [SampleClass](#) &sample\_class)

## 15.43.1 Function Documentation

### 15.43.1.1 friend\_function()

```
void friend_function (
    SampleClass & sample_class )
```

Definition at line 73 of file [SampleClass.cpp](#).

```
00073     {
00074     std::cout << "This is a friend function" << std::endl;
00075     std::cout << "Accessing private member member_a: " << sample_class.member_a << std::endl;
00076 }
```

### 15.43.1.2 operator+()

```
SampleClass operator+ (
    const SampleClass & s_1,
    const SampleClass & s_2 )
```

Definition at line 78 of file [SampleClass.cpp](#).

```
00078     {
00079     std::cout << "overloaded operator+ for SampleClass!" << std::endl;
00080     return SampleClass(s_1.member_a + s_2.member_a, s_1.member_b + s_2.member_b);
00081 }
```

### 15.43.1.3 operator<<()

```
std::ostream& operator<< (
    std::ostream & out,
    const SampleClass & sample_class )
```

Definition at line 83 of file [SampleClass.cpp](#).

```
00083     {
00084
00085     out << std::endl
00086         << "member_a = " << sample_class.member_a << std::endl
00087         << "member_b = " << sample_class.member_b << std::endl;
00088
00089     return out;
00090 }
```

## 15.44 SampleClass.cpp

```
00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include "SampleClass.h"
00006
00007 SampleClass::SampleClass() {
00008     std::cout << "Default constructor was called ..." << std::endl;
00009     member_a = 0;
00010     member_b = 0;
00011 }
00012
00013 int SampleClass::static_member_variable = 5;
00014
00015 //SampleClass::SampleClass(int a, int b) {
00016 //     std::cout << "Constructor: SampleClass(" << a << ", " << b << ") ..." << std::endl;
00017 //     member_a = a;
00018 //     member_b = b;
00019 //}
00020 // equivalent implementation using an initialization list
00021 SampleClass::SampleClass(int a, int b)
00022 : member_a{ a }, member_b{ b }
00023 {
00024     std::cout << "Constructor: SampleClass(" << a << ", " << b << ") ..." << std::endl;
00025 }
00026
00027 SampleClass::SampleClass(int a, int b, int c): SampleClass{ a, b } {
00028     std::cout << "Constructor: SampleClass(" << a << ", " << b << ", " << c << ") ..." << std::endl;
00029 }
00030
```

```

00031 //Destructor
00032 SampleClass::~SampleClass() {
00033     std::cout << "Destructor was called" << std::endl;
00034 }
00035
00036 SampleClass::SampleClass(const SampleClass &sample_class) :
00037     member_a(sample_class.member_a), member_b(sample_class.member_b)
00038 {
00039     std::cout << "Copy constructor called\n"; // just to prove it works
00040 }
00041
00042 int SampleClass::get_member_a() {
00043     return member_a;
00044 }
00045
00046 int SampleClass::get_member_b() {
00047     return member_b;
00048 }
00049
00050 void SampleClass::set_member_a(int a) {
00051     std::cout << "set member_a to: " << a << std::endl;
00052     member_a = a;
00053 }
00054
00055 void SampleClass::set_member_b(int b) {
00056     std::cout << "set member_b to: " << b << std::endl;
00057     member_b = b;
00058 }
00059
00060 void SampleClass::set_members_using_this(int member_a, int member_b) {
00061     this->member_a = member_a;
00062     this->member_b = member_b;
00063 }
00064
00065 void SampleClass::const_member_function() const {
00066     std::cout << "This is a const member function!" << std::endl;
00067 }
00068
00069 void SampleClass::static_member_function() {
00070     std::cout << "This is a static member function" << std::endl;
00071 }
00072
00073 void friend_function(SampleClass &sample_class) {
00074     std::cout << "This is a friend function" << std::endl;
00075     std::cout << "Accessing private member member_a: " << sample_class.member_a << std::endl;
00076 }
00077
00078 SampleClass operator+(const SampleClass &s_1, const SampleClass &s_2) {
00079     std::cout << "overloaded operator+ for SampleClass!" << std::endl;
00080     return SampleClass(s_1.member_a + s_2.member_a, s_1.member_b + s_2.member_b);
00081 }
00082
00083 std::ostream& operator<< (std::ostream &out, const SampleClass &sample_class) {
00084
00085     out << std::endl
00086         << "member_a = " << sample_class.member_a << std::endl
00087         << "member_b = " << sample_class.member_b << std::endl;
00088
00089     return out;
00090 }
00091
00092 int SampleClass::operator() (int i) {
00093     return (member_a += i);
00094 }


```

## 15.45 learningCpp/OOP/SampleClass.h File Reference


```
#include <iostream>
```



Include dependency graph for SampleClass.h:



This graph shows which files directly or indirectly include this file:



## Classes

- class [SampleClass](#)

## 15.46 SampleClass.h

```

00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include <iostream>
00006
00007 #ifndef CPP_TEMPLATE_PROJECT_SAMPLECLASS_H
00008 #define CPP_TEMPLATE_PROJECT_SAMPLECLASS_H
00009
00128 class SampleClass {
00129 private:
00130     int member_a{ 0 };
00131     int member_b{ 0 };
00132 public:
00133     //static variables are shared by all objects/instants of the class
00134     static int static_member_variable;
00135     // getter
00136     int get_member_a();
00137     int get_member_b();
00138     // setter
00139     void set_member_a(int a);
00140     void set_member_b(int b);
00141
00142     void set_members_using_this(int member_a, int member_b);
00143
00144     // const member function that cannot change member variables
00145     // can be overwritten with a non const function
00146     void const_member_function() const;
00147
  
```

```

00148     // default constructor
00149     SampleClass();
00150     // constructor with arguments
00151     SampleClass(int a, int b = 0);
00152
00153     //example for delegating constructors
00154     SampleClass(int a, int b, int c);
00155
00156     // Copy constructor
00157     // prevent copies by making the copy constructor private
00158     SampleClass(const SampleClass &sample_class);
00159
00160     ~SampleClass();
00161
00162     static void static_member_function();
00163
00164     friend void friend_function(SampleClass &sample_class);
00165
00166     friend SampleClass operator+(const SampleClass &s_1, const SampleClass &s_2);
00167     friend std::ostream& operator<< (std::ostream &out, const SampleClass &sample_class);
00168
00169     int operator() (int i);
00170
00171     // it is possible to have nested types within classes
00172     enum FruitType {
00173         APPLE,
00174         BANANA,
00175         CHERRY
00176     };
00177 };
00178
00179
00180
00181 #endif //CPP_TEMPLATE_PROJECT_SAMPLECLASS_H

```


## 15.47 learningCpp/OOP/TemplateClass.h File Reference

```


#include <iostream>
#include <cassert>
#include "TemplateClass.inl"

```

Include dependency graph for TemplateClass.h:



This graph shows which files directly or indirectly include this file:



## Classes

- class `Array< T >`
- class `StaticArray< T, size >`

## 15.48 TemplateClass.h

```

00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00029 #ifndef CPP_TEMPLATE_PROJECT_TEMPLATECLASS_H
00030 #define CPP_TEMPLATE_PROJECT_TEMPLATECLASS_H
00031
00032 #include <iostream>
00033 #include <cassert>
00034
00035 template <class T>
00036 class Array
00037 {
00038 private:
00039     int m_length{};
00040     T *m_data{};
00041 public:
00042     Array(int length);
00043     Array(const Array&) = delete;
00044     Array& operator=(const Array&) = delete;
00045     ~Array();
00046     void Erase();
00047     T& operator[](int index);
00048     int getLength() const;
00049     void print();
00050 };
00051
00062 template <class T, int size> // size is the non-type parameter
00063 class StaticArray
00064 {
00065 private:
00066     // The non-type parameter controls the size of the array
00067     T m_array[size];
00068 public:
00069     T* getArray();
00070     T& operator[](int index);
  
```

```

00073 };
00074
00075 #include "TemplateClass.inl"
00076
00077 #endif //CPP_TEMPLATE_PROJECT_TEMPLATECLASS_H


```

## 15.49 learningCpp/OOP/TestInheritance.cpp File Reference

```
#include "Inheritance.h"
```

```
#include <iostream>
```

Include dependency graph for TestInheritance.cpp:



### Functions

- `int main ()`

### 15.49.1 Function Documentation

#### 15.49.1.1 `main()`

```
int main ( )
```


Definition at line 9 of file [TestInheritance.cpp](#).

```

00010 {
00011     Derived derived{ 1.3, 5, 1, 2, 3};
00012     std::cout << "Id: " << derived.getId() << '\n';
00013     std::cout << "Cost: " << derived.getCost() << '\n';
00014     //std::cout << "private: " << derived.m_private << '\n';
00015     std::cout << "private: " << derived.getPrivate() << '\n';
00016     std::cout << "protected: " << derived.getProtected() << '\n';
00017     std::cout << "public: " << derived.m_public << '\n';
00018
00019     Base &rBase{ derived };
00020     derived.print();
00021
00022
00023     return 0;
00024 }

```

Here is the call graph for this function:



## 15.50 TestInheritance.cpp

```


00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00005 #include "Inheritance.h"
00006
00007 #include <iostream>
00008
00009 int main()
00010 {
00011     Derived derived{ 1.3, 5, 1, 2, 3};
00012     std::cout << "Id: " << derived.getId() << '\n';
00013     std::cout << "Cost: " << derived.getCost() << '\n';
00014     //std::cout << "private: " << derived.m_private << '\n';
00015     std::cout << "private: " << derived.getPrivate() << '\n';
00016     std::cout << "protected: " << derived.getProtected() << '\n';
00017     std::cout << "public: " << derived.m_public << '\n';
00018
00019     Base &rBase{ derived };
00020     derived.print();
00021
00022
00023     return 0;
00024 }
  
```

## 15.51 learningCpp/OOP/TestSampleClass.cpp File Reference

```

#include "SampleClass.h"
#include "Timer.h"
#include <iostream>
  
```

Include dependency graph for TestSampleClass.cpp:



## Functions

- int [main](#) ()

### 15.51.1 Function Documentation

#### 15.51.1.1 main()

int main ( )

Definition at line 9 of file [TestSampleClass.cpp](#).

```


00009     {
00010
00011         Timer t;
00012
00013         // call default constructor
00014         //SampleClass sample_class;
00015
00016         // call constructor with arguments
00017         // copy direct initialization
00018         //SampleClass sample_class = SampleClass(5, 10); //equivalent to
00019         // copy list initialization
00020         //SampleClass sample_class = SampleClass{5, 10}; //equivalent to
00021         // direct initialization
00022         //SampleClass sample_class(5, 10); // equivalent to
00023         // list initialization
00024         SampleClass sample_class{5, 10};
00025
00026         SampleClass copy_sample_class(sample_class);
00027
00028         // call with default value for member_b
00029         //SampleClass sample_class{5};
00030
00031         // call with three arguments (ex. for delegating constructors)
00032         //SampleClass sample_class{5, 10, 15};
00033
00034         std::cout << "sample_class.member_a = " << sample_class.get_member_a() << std::endl;
00035         std::cout << "sample_class.member_b = " << sample_class.get_member_b() << std::endl;
00036
00037         sample_class.set_member_a(2);
00038         sample_class.set_member_b(4);
00039
00040         std::cout << "sample_class.member_a = " << sample_class.get_member_a() << std::endl;
00041         std::cout << "sample_class.member_b = " << sample_class.get_member_b() << std::endl;
00042
00043         // allocate a SampleClass dynamically
00044         SampleClass *dyn_sample_class { new SampleClass{ 1, 6}};
  
```

```

00045     std::cout << "dyn_sample_class.member_a = " << dyn_sample_class->get_member_a() << std::endl;
00046     std::cout << "dyn_sample_class.member_b = " << dyn_sample_class->get_member_b() << std::endl;
00047     //delete dyn_sample_class;
00048
00049     // set static counter
00050     std::cout << "(static) counter = " << SampleClass::static_member_variable << std::endl;
00051     std::cout << "(static) counter = " << sample_class.static_member_variable << std::endl;
00052
00053     SampleClass::static_member_function();
00054     sample_class.static_member_function();
00055
00056     friend_function(sample_class);
00057
00058     SampleClass s_1 {2, 2};
00059     SampleClass s_2 {4, 5};
00060     SampleClass s_3 = s_1 + s_2;
00061
00062     std::cout << "s_3: " << s_3 << std::endl;
00063
00064     std::cout << "s_3(10): " << s_3(10) << std::endl;
00065
00066     std::cout << "Time taken: " << t.elapsed() << " seconds\n";
00067
00068     return 0;
00069 }

```

Here is the call graph for this function:



## 15.52 TestSampleClass.cpp

```

00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include "SampleClass.h"
00006 #include "Timer.h"
00007 #include <iostream>
00008
00009 int main() {
00010
00011     Timer t;
00012
00013     // call default constructor
00014     //SampleClass sample_class;
00015
00016     // call constructor with arguments
00017     // copy direct initialization
00018     //SampleClass sample_class = SampleClass(5, 10); //equivalent to
00019     // copy list initialization
00020     //SampleClass sample_class = SampleClass{5, 10}; //equivalent to
00021     // direct initialization
00022     //SampleClass sample_class(5, 10); // equivalent to
00023     // list initialization
00024     SampleClass sample_class{5, 10};

```

```

00025
00026     SampleClass copy_sample_class(sample_class);
00027
00028     // call with default value for member_b
00029     //SampleClass sample_class{5};
00030
00031     // call with three arguments (ex. for delegating constructors)
00032     //SampleClass sample_class{5, 10, 15};
00033
00034     std::cout << "sample_class.member_a = " << sample_class.get_member_a() << std::endl;
00035     std::cout << "sample_class.member_b = " << sample_class.get_member_b() << std::endl;
00036
00037     sample_class.set_member_a(2);
00038     sample_class.set_member_b(4);
00039
00040     std::cout << "sample_class.member_a = " << sample_class.get_member_a() << std::endl;
00041     std::cout << "sample_class.member_b = " << sample_class.get_member_b() << std::endl;
00042
00043     // allocate a SampleClass dynamically
00044     SampleClass *dyn_sample_class { new SampleClass{ 1, 6}};
00045     std::cout << "dyn_sample_class.member_a = " << dyn_sample_class->get_member_a() << std::endl;
00046     std::cout << "dyn_sample_class.member_b = " << dyn_sample_class->get_member_b() << std::endl;
00047     //delete dyn_sample_class;
00048
00049     // set static counter
00050     std::cout << "(static) counter = " << SampleClass::static_member_variable << std::endl;
00051     std::cout << "(static) counter = " << sample_class.static_member_variable << std::endl;
00052
00053     SampleClass::static_member_function();
00054     sample_class.static_member_function();
00055
00056     friend_function(sample_class);
00057
00058     SampleClass s_1 {2, 2};
00059     SampleClass s_2 {4, 5};
00060     SampleClass s_3 = s_1 + s_2;
00061
00062     std::cout << "s_3: " << s_3 << std::endl;
00063
00064     std::cout << "s_3(10): " << s_3(10) << std::endl;
00065
00066     std::cout << "Time taken: " << t.elapsed() << " seconds\n";
00067
00068     return 0;
00069 }


```

## 15.53 learningCpp/OOP/TestTemplateClass.cpp File Reference

```
#include "TemplateClass.h"
```

```
#include <iostream>
```

Include dependency graph for TestTemplateClass.cpp:





## Functions

- int `main` ()

### 15.53.1 Function Documentation

#### 15.53.1.1 `main()`


int `main` ( )

Definition at line 9 of file [TestTemplateClass.cpp](#).

```

00010 {
00011     Array<int> intArray(12);
00012     Array<double> doubleArray(12);
00013
00014     for (int count{ 0 }; count < intArray.getLength(); ++count)
00015     {
00016         intArray[count] = count;
00017         doubleArray[count] = count + 0.5;
00018     }
00019
00020     for (int count{ intArray.getLength() - 1 }; count >= 0; --count)
00021         std::cout << intArray[count] << '\t' << doubleArray[count] << '\n';
00022
00023     intArray.print();
00024     doubleArray.print();
00025
00026     // declare an integer array with room for 12 integers
00027     StaticArray<int, 12> staticintArray;
00028
00029     // Fill it up in order, then print it backwards
00030     for (int count=0; count < 12; ++count)
00031         staticintArray[count] = count;
00032
00033     for (int count=11; count >= 0; --count)
00034         std::cout << staticintArray[count] << " ";
00035     std::cout << '\n';
00036
00037     // declare a double buffer with room for 4 doubles
00038     StaticArray<double, 4> staticdoubleArray;
00039
00040     for (int count=0; count < 4; ++count)
00041         staticdoubleArray[count] = 4.4 + 0.1*count;
00042
00043     for (int count=0; count < 4; ++count)
00044         std::cout << staticdoubleArray[count] << ' ';
00045
00046     return 0;
00047 }
```

Here is the call graph for this function:



## 15.54 TestTemplateClass.cpp

```

00001 //
00002 // Created by Michael Staneker on 10.12.20.
00003 //
00004
00005 #include "TemplateClass.h"
```


```

00006
00007 #include <iostream>
00008
00009 int main()
00010 {
00011     Array<int> intArray(12);
00012     Array<double> doubleArray(12);
00013
00014     for (int count{ 0 }; count < intArray.getLength(); ++count)
00015     {
00016         intArray[count] = count;
00017         doubleArray[count] = count + 0.5;
00018     }
00019
00020     for (int count{ intArray.getLength() - 1 }; count >= 0; --count)
00021         std::cout << intArray[count] << '\t' << doubleArray[count] << '\n';
00022
00023     intArray.print();
00024     doubleArray.print();
00025
00026     // declare an integer array with room for 12 integers
00027     StaticArray<int, 12> staticintArray;
00028
00029     // Fill it up in order, then print it backwards
00030     for (int count=0; count < 12; ++count)
00031         staticintArray[count] = count;
00032
00033     for (int count=11; count >= 0; --count)
00034         std::cout << staticintArray[count] << " ";
00035     std::cout << '\n';
00036
00037     // declare a double buffer with room for 4 doubles
00038     StaticArray<double, 4> staticdoubleArray;
00039
00040     for (int count=0; count < 4; ++count)
00041         staticdoubleArray[count] = 4.4 + 0.1*count;
00042
00043     for (int count=0; count < 4; ++count)
00044         std::cout << staticdoubleArray[count] << ' ';
00045
00046     return 0;
00047 }
00048

```

## 15.55 learningCpp/OOP/Timer.cpp File Reference

#include "Timer.h"  
 Include dependency graph for Timer.cpp:



## 15.56 Timer.cpp


```
00001 //
```

```
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include "Timer.h"
00006
00007 Timer::Timer() : m_beg(clock_t::now())
00008 {
00009 }
00010
00011 void Timer::reset()
00012 {
00013     m_beg = clock_t::now();
00014 }
00015
00016 double Timer::elapsed() const
00017 {
00018     return std::chrono::duration_cast<second_t>(clock_t::now() - m_beg).count();
00019 }
```


## 15.57 learningCpp/OOP/Timer.h File Reference

```
#include <chrono>
```

Include dependency graph for Timer.h:



This graph shows which files directly or indirectly include this file:



### Classes

- class [Timer](#)

### Macros

- #define [CPP\\_TEMPLATE\\_PROJECT\\_TIMER\\_H](#)

## 15.57.1 Macro Definition Documentation

### 15.57.1.1 CPP\_TEMPLATE\_PROJECT\_TIMER\_H

#define CPP\_TEMPLATE\_PROJECT\_TIMER\_H

Definition at line 8 of file [Timer.h](#).

## 15.58 Timer.h

```

00001 //
00002 // Created by Michael Staneker on 09.12.20.
00003 //
00004
00005 #include <chrono> // for std::chrono functions
00006
00007 #ifndef CPP_TEMPLATE_PROJECT_TIMER_H
00008 #define CPP_TEMPLATE_PROJECT_TIMER_H
00009
00010
00011 class Timer {
00012 private:
00013     // Type aliases to make accessing nested type easier
00014     using clock_t = std::chrono::high_resolution_clock;
00015     using second_t = std::chrono::duration<double, std::ratio<1> >;
00016
00017     std::chrono::time_point<clock_t> m_beg;
00018
00019 public:
00020
00021     Timer();
00022     void reset();
00023     double elapsed() const;
00024 };
00025
00026
00027
00028 #endif //CPP_TEMPLATE_PROJECT_TIMER_H

```


## 15.59 learningCpp/StandardLibrary/SL\_Basics.cpp File Reference

```

#include <iostream>
#include <array>
#include <vector>
#include <string>

```

Include dependency graph for SL\_Basics.cpp:



## Functions

- int [main](#) ()

## 15.59.1 Function Documentation

### 15.59.1.1 main()

```
int main ( )
```

## 15.59.2 Introduction to the standard library

The Standard library contains a collection of classes that provide templated containers, algorithms, and iterators. If you need a common class or algorithm, odds are the standard library has it. The upside is that you can take advantage of these classes without having to write and debug the classes yourself, and the standard library does a good job providing reasonably efficient versions of these classes. The downside is that the standard library is complex, and can be a little intimidating since everything is templated.

### 15.59.2.1 STL containers

There are three basic container categories:

- **Sequence containers** maintaining the ordering of elements within the container
  - `std::vector`: dynamic array capable of growing, fast insertion and removing at the end
  - `std::deque`: double-ended queue class, implemented as a dynamic array that can grow from both ends
  - `std::array`
  - `std::list`
  - `std::forward_list`
  - `std::basic_string`
- **Associative containers** automatically sorting the inputs when those inputs are inserted into the container
  - `set`: storing unique elements
  - `multiset`: duplicate elements allowed
  - `map` (or associative array): each element is a pair, called a key/value pair, key must be unique
  - `multimap` (or dictionary): map allowing duplicate keys
- **Container adapters**: are special predefined containers that are adapted to specific uses
  - `stack`: elements operate in a LIFO (Last In, First Out)
  - `queue`: elements operate in a FIFO (First In, First Out)
  - `priority queue`: elements are kept sorted (via `operator<`)

### 15.59.2.2 STL iterators

- **Operator\* \*\* Dereferencing the iterator returns the element that the iterator is currently pointing at**
- **\*\*Operator++** Moves the iterator to the next element in the container.
- Most iterators also provide `Operator--` to move to the previous element.
- `Operator==` and `Operator!=` – Basic comparison operators to determine if two iterators point to the same element. To compare the values that two iterators are pointing at, dereference the iterators first, and then use a comparison operator.
- `Operator=` – Assign the iterator to a new position (typically the start or end of the container's elements). To assign the value of the element the iterator is pointing at, dereference the iterator first, then use the assign operator.

Each container includes four basic member functions for use with **Operator=**:

- *begin()* returns an iterator representing the beginning of the elements in the container. *end()* returns an iterator representing the element just past the end of the elements. *cbegin()* returns a const (read-only) iterator representing the beginning of the elements in the container. *cend()* returns a const (read-only) iterator representing the element just past the end of the elements.

All containers provide (at least) two types of iterators:

- **container::iterator** provides a read/write iterator
- **container::const\_iterator** provides a read-only iterator

### 15.59.2.3 Formatting output

See [ostream](#)

### 15.59.2.4 File IO

See [Basic file IO](#)

### 15.59.2.5 std::array

### 15.59.2.6 std::vector

### 15.59.2.7 std::string

### 15.59.2.8 Algorithms

- **Inspectors** are used to view (not modify) data in container (including searching and counting)
- **Mutators** are used to modify data in a container (including sorting and shuffling)
- **Facilitators** are used to generate a result based on values of the data members

Definition at line 75 of file [SL\\_Basics.cpp](#).

```
00075     {
00077         //std::array<int, 5> myArray = { 9, 7, 5, 3, 1 }; // initializer list
00078         std::array<int, 5> my_array{9, 7, 5, 3, 1}; // list initialization
00079         my_array[0] = 10; // standard accessing
00080         my_array.at(1) = 8; // other possibility
00081         std::cout << "size of my_array: " << my_array.size() << std::endl;
00085         // dynamic arrays without the need of dynamically allocating memory
00086
00087         //std::vector<int> vec_array;
00088         //std::vector<int> vec_array = { 9, 7, 5, 3, 1 }; // use initializer list to initialize array
00089         (Before C++11)
00089         std::vector<int> vec_array { 9, 7, 5, 3, 1 }; // use uniform initialization to initialize array
00090         vec_array[0] = 10; // standard accessing
00091         vec_array.at(1) = 8; // other possibility
00092         std::cout << "size of vec_array: " << vec_array.size() << std::endl;
00093         // resize
00094         vec_array.resize(10);
00095         std::cout << "size of vec_array (after resize): " << vec_array.size() << std::endl;
00118         return 0;
00119     }
```

## 15.60 SL\_Basics.cpp

```
00001 //
00002 // Created by Michael Staneker on 03.12.20.
00003 //
00004
00005 #include <iostream>
00006
00007 #include <array> // C++ built in fixed arrays in a safer and more usable form
00008 #include <vector> // makes working with dynamic arrays safer and easier
00009 #include <string> //TODO: section about std::string
00075 int main() {
00077     //std::array<int, 5> myArray = { 9, 7, 5, 3, 1 }; // initializer list
00078     std::array<int, 5> my_array{9, 7, 5, 3, 1}; // list initialization
00079     my_array[0] = 10; // standard accessing
00080     my_array.at(1) = 8; // other possibility
00081     std::cout << "size of my_array: " << my_array.size() << std::endl;
00085     // dynamic arrays without the need of dynamically allocating memory
00086 }
```

```

00087     //std::vector<int> vec_array;
00088     //std::vector<int> vec_array = { 9, 7, 5, 3, 1 }; // use initializer list to initialize array
(Before C++11)
00089     std::vector<int> vec_array { 9, 7, 5, 3, 1 }; // use uniform initialization to initialize array
00090     vec_array[0] = 10; // standard accessing
00091     vec_array.at(1) = 8; // other possibility
00092     std::cout << "size of vec_array: " << vec_array.size() << std::endl;
00093     // resize
00094     vec_array.resize(10);
00095     std::cout << "size of vec_array (after resize): " << vec_array.size() << std::endl;
00118     return 0;
00119 }

```


## 15.61 README.md File Reference

## 15.62 src/Main.cpp File Reference

```
#include <iostream>
```

```
#include <string>
```

Include dependency graph for Main.cpp:



## Functions

- int [main](#) ()

### 15.62.1 Function Documentation

#### 15.62.1.1 main()

```
int main ( )
```

Definition at line 4 of file [Main.cpp](#).

```

00004     {
00005
00006         printf("Hello World!\n");
00007
00008         return 0;
00009     }

```

## 15.63 Main.cpp

```

00001 #include <iostream>
00002 #include <string>
00003
00004 int main() {
00005
00006     printf("Hello World!\n");
00007
00008     return 0;


```

```
00009 }  
00010
```

## 15.64 test/tester.cpp File Reference

```
#include <iostream>
```

Include dependency graph for tester.cpp:



### Functions

- int `main` ()

#### 15.64.1 Function Documentation

##### 15.64.1.1 main()

```
int main ( )
```

Definition at line 3 of file `tester.cpp`.

```
00003     {  
00004  
00005     std::cout << "This is a tester file" << std::endl;  
00006     return 0;  
00007  
00008 }
```

## 15.65 tester.cpp

```
00001 #include <iostream>  
00002  
00003 int main() {  
00004  
00005     std::cout << "This is a tester file" << std::endl;  
00006     return 0;  
00007  
00008 }  
00009
```