Writing Code Together

When you come in, line up from the front of the room to the back of the room in order of your pet's name - A in the front of the room, Z in the back. (If you have no pet, use "No" as its name.)

If you are in AP CS, do the same in a different line.

If you are in Game & App Dev, be together.

If you are the three Machine Learning students, be together.

Question of the day (and roll).

In your groups, write and debug code

Create a menu system that must run at least one time and stays in the loop until the user chooses to exit. You must have a minimum of 4 numbered menu items. The last item on the menu must be EXIT or QUIT.

Example menu:

1. Copy (C)

2. Cut (T)

3. Paste (V)

4. eXit / Quit

You must be able to take input as either the number or a single letter without throwing an error. Make sure to show the user what that one letter is. (In the example, the single letters are in parentheses or capitalized.) When you get the input, you will branch off and signal to the users that they are in whatever choice they made. The case of the input letter must not matter for choosing the option (t and T must give the same result). Later, we will go to a function to do what was chosen.

10 minutes to plan, rest of the time to code. (Hint: This could work for the ASCII art problem.)

Machine Learning Trio: 10 minutes to plan. No talking after that. 1 repo - pull requests, issues, etc.

Extensions:

- Make it so that the input takes only one character without needing to press <ENTER>.
- Place the menu in the middle of the screen (external console/terminal). (Hint: Console.SetCursorPosition(x,y); is your friend.)
- Change the color of your text and/or the background of the menu.

In your groups, write and debug code

Part 2:

Continue the menu system, but instead of having just an output when the user chooses an option, write the code in such a way that a function/method is called instead. Your function must do what the menu describes. (You might want it to output some ASCII art.) At least one of your functions needs to have a loop that continues until the user presses a key (perhaps an ASCII animation). To do this, you will need to use a loop in your function/method. This loop will need to check to see if a key is pressed and then exit that loop. You will need to use the following code (plus other code) somewhere in your loop:

```
if(Console.KeyAvailable) {}
```