

File: client/src/components/ui/drawer.tsx

Type: tsx | Size: 3021 bytes

```
"use client"

import * as React from "react"
import { Drawer as DrawerPrimitive } from "vaul"

import { cn } from "@lib/utils"

const Drawer = ({
  shouldScaleBackground = true,
  ...props
}: React.ComponentProps<typeof DrawerPrimitive.Root>) => (
  <DrawerPrimitive.Root
    shouldScaleBackground={shouldScaleBackground}
    {...props}
  />
)
Drawer.displayName = "Drawer"

const DrawerTrigger = DrawerPrimitive.Trigger

const DrawerPortal = DrawerPrimitive.Portal

const DrawerClose = DrawerPrimitive.Close

const DrawerOverlay = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Overlay
    ref={ref}
    className={cn("fixed inset-0 z-50 bg-black/80", className)}
    {...props}
  />
))
DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName

const DrawerContent = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DrawerPortal>
    <DrawerOverlay />
    <DrawerPrimitive.Content
      ref={ref}
      className={cn(
        "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-background",
        className
      )}
      {...props}
    >
      <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
      {children}
    </DrawerPrimitive.Content>
  </DrawerPortal>
))
DrawerContent.displayName = "DrawerContent"

const DrawerHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)}
    {...props}
  />
)
DrawerHeader.displayName = "DrawerHeader"

const DrawerFooter = ({
  className,
```

```

    ...props
  }: React.HTMLAttributes<HTMLDivElement>) => (
    <div
      className={cn("mt-auto flex flex-col gap-2 p-4", className)}
      {...props}
    />
  )
  DrawerFooter.displayName = "DrawerFooter"

  const DrawerTitle = React.forwardRef<
    React.ElementRef<typeof DrawerPrimitive.Title>,
    React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
  >(({ className, ...props }, ref) => (
    <DrawerPrimitive.Title
      ref={ref}
      className={cn(
        "text-lg font-semibold leading-none tracking-tight",
        className
      )}
      {...props}
    />
  ))
  DrawerTitle.displayName = DrawerPrimitive.Title.displayName

  const DrawerDescription = React.forwardRef<
    React.ElementRef<typeof DrawerPrimitive.Description>,
    React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
  >(({ className, ...props }, ref) => (
    <DrawerPrimitive.Description
      ref={ref}
      className={cn("text-sm text-muted-foreground", className)}
      {...props}
    />
  ))
  DrawerDescription.displayName = DrawerPrimitive.Description.displayName

  export {
    Drawer,
    DrawerPortal,
    DrawerOverlay,
    DrawerTrigger,
    DrawerClose,
    DrawerContent,
    DrawerHeader,
    DrawerFooter,
    DrawerTitle,
    DrawerDescription,
  }

```