

File: client/src/components/ui/alert-dialog.tsx

Type: tsx | Size: 4420 bytes

```
import * as React from "react"
import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog"

import { cn } from "@lib/utils"
import { buttonVariants } from "@components/ui/button"

const AlertDialog = AlertDialogPrimitive.Root

const AlertDialogTrigger = AlertDialogPrimitive.Trigger

const AlertDialogPortal = AlertDialogPrimitive.Portal

const AlertDialogOverlay = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[stat...
      className
    )}
    {...props}
    ref={ref}
  />
))
AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName

const AlertDialogContent = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
>(({ className, ...props }, ref) => (
  <AlertDialogPortal>
    <AlertDialogOverlay />
    <AlertDialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 bord...
        className
      )}
      {...props}
    />
  </AlertDialogPortal>
))
AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName

const AlertDialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-2 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
AlertDialogHeader.displayName = "AlertDialogHeader"

const AlertDialogFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
```

```

)
AlertDialogFooter.displayName = "AlertDialogFooter"

const AlertDialogTitle = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold", className)}
    {...props}
  />
))
AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName

const AlertDialogDescription = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
AlertDialogDescription.displayName =
  AlertDialogPrimitive.Description.displayName

const AlertDialogAction = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Action>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Action
    ref={ref}
    className={cn(buttonVariants(), className)}
    {...props}
  />
))
AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName

const AlertDialogCancel = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Cancel>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Cancel
    ref={ref}
    className={cn(
      buttonVariants({ variant: "outline" }),
      "mt-2 sm:mt-0",
      className
    )}
    {...props}
  />
))
AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName

export {
  AlertDialog,
  AlertDialogPortal,
  AlertDialogOverlay,
  AlertDialogTrigger,
  AlertDialogContent,
  AlertDialogHeader,
  AlertDialogFooter,
  AlertDialogTitle,
  AlertDialogDescription,
  AlertDialogAction,
  AlertDialogCancel,
}

```