

File: client/src/components/ui/toast.tsx

Type: tsx | Size: 4845 bytes

```
import * as React from "react"
import * as ToastPrimitives from "@radix-ui/react-toast"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@lib/utils"

const ToastProvider = ToastPrimitives.Provider

const ToastViewport = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Viewport>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Viewport
    ref={ref}
    className={cn(
      "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:...",
      className
    )}
    {...props}
  />
))
ToastViewport.displayName = ToastPrimitives.Viewport.displayName

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden round...",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive:
          "destructive group border-destructive bg-destructive text-destructive-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Toast = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &
  VariantProps<typeof toastVariants>
>(({ className, variant, ...props }, ref) => {
  return (
    <ToastPrimitives.Root
      ref={ref}
      className={cn(toastVariants({ variant }), className)}
      {...props}
    />
  )
})
Toast.displayName = ToastPrimitives.Root.displayName

const ToastAction = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Action>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Action
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm font...",
      className
    )}
    {...props}
  />
))
ToastAction.displayName = ToastPrimitives.Action.displayName
```

```

const ToastClose = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Close>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Close
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity hover:text-foregr...
      className
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </ToastPrimitives.Close>
))
ToastClose.displayName = ToastPrimitives.Close.displayName

const ToastTitle = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Title>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Title
    ref={ref}
    className={cn("text-sm font-semibold", className)}
    {...props}
  />
))
ToastTitle.displayName = ToastPrimitives.Title.displayName

const ToastDescription = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Description>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Description
    ref={ref}
    className={cn("text-sm opacity-90", className)}
    {...props}
  />
))
ToastDescription.displayName = ToastPrimitives.Description.displayName

type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>

type ToastActionElement = React.ReactElement<typeof ToastAction>

export {
  type ToastProps,
  type ToastActionElement,
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
}

```