

File: client/src/components/ui/dialog.tsx

Type: tsx | Size: 3848 bytes

```
"use client"

import * as React from "react"
import * as DialogPrimitive from "@radix-ui/react-dialog"
import { X } from "lucide-react"

import { cn } from "@lib/utils"

const Dialog = DialogPrimitive.Root

const DialogTrigger = DialogPrimitive.Trigger

const DialogPortal = DialogPrimitive.Portal

const DialogClose = DialogPrimitive.Close

const DialogOverlay = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Overlay
    ref={ref}
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state...
      className
    )}
    {...props}
  />
))
DialogOverlay.displayName = DialogPrimitive.Overlay.displayName

const DialogContent = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DialogPortal>
    <DialogOverlay />
    <DialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 bord...
        className
      )}
      {...props}
    >
      {children}
      <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background tr...
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </DialogPrimitive.Close>
    </DialogPrimitive.Content>
  </DialogPortal>
))
DialogContent.displayName = DialogPrimitive.Content.displayName

const DialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-1.5 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
DialogHeader.displayName = "DialogHeader"

const DialogFooter = ({
```

```

    className,
    ...props
  }: React.HTMLAttributes<HTMLDivElement>) => (
    <div
      className={cn(
        "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
        className
      )}
      {...props}
    />
  )
DialogFooter.displayName = "DialogFooter"

const DialogTitle = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
DialogTitle.displayName = DialogPrimitive.Title.displayName

const DialogDescription = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
DialogDescription.displayName = DialogPrimitive.Description.displayName

export {
  Dialog,
  DialogPortal,
  DialogOverlay,
  DialogClose,
  DialogTrigger,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
}

```