

File: client/src/components/ui/menubar.tsx

Type: tsx | Size: 8605 bytes

```
"use client"

import * as React from "react"
import * as MenubarPrimitive from "@radix-ui/react-menubar"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@lib/utils"

function MenubarMenu({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Menu>) {
  return <MenubarPrimitive.Menu {...props} />
}

function MenubarGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Group>) {
  return <MenubarPrimitive.Group {...props} />
}

function MenubarPortal({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Portal>) {
  return <MenubarPrimitive.Portal {...props} />
}

function MenubarRadioGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.RadioGroup>) {
  return <MenubarPrimitive.RadioGroup {...props} />
}

function MenubarSub({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Sub>) {
  return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props} />
}

const Menubar = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Root
    ref={ref}
    className={cn(
      "flex h-10 items-center space-x-1 rounded-md border bg-background p-1",
      className
    )}
    {...props}
  />
))
Menubar.displayName = MenubarPrimitive.Root.displayName

const MenubarTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-3 py-1.5 text-sm font-medium outline-none fo...",
      className
    )}
    {...props}
  />
))
MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName

const MenubarSubTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
```

```

    React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
      inset?: boolean
    }
  >(({ className, inset, children, ...props }, ref) => (
    <MenubarPrimitive.SubTrigger
      ref={ref}
      className={cn(
        "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accen...
        inset && "pl-8",
        className
      )}
      {...props}
    >
      {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </MenubarPrimitive.SubTrigger>
  ))
  MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName

const MenubarSubContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground data-[state=...
      className
    )}
    {...props}
  >
  </>
  ))
  MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName

const MenubarContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
>(
  (
    { className, align = "start", alignOffset = -4, sideOffset = 8, ...props },
    ref
  ) => (
    <MenubarPrimitive.Portal>
      <MenubarPrimitive.Content
        ref={ref}
        align={align}
        alignOffset={alignOffset}
        sideOffset={sideOffset}
        className={cn(
          "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-...
          className
        )}
        {...props}
      >
    </MenubarPrimitive.Portal>
  )
)
  MenubarContent.displayName = MenubarPrimitive.Content.displayName

const MenubarItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus...
      inset && "pl-8",
      className
    )}
    {...props}
  >

```

```

    />
  ))
  MenubarItem.displayName = MenubarPrimitive.Item.displayName

const MenubarCheckboxItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <MenubarPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none ..."
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.CheckboxItem>
))
MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName

const MenubarRadioItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <MenubarPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none ..."
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Circle className="h-2 w-2 fill-current" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.RadioItem>
))
MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName

const MenubarLabel = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
    )}
    {...props}
  />
))
MenubarLabel.displayName = MenubarPrimitive.Label.displayName

const MenubarSeparator = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Separator
    ref={ref}

```

```

        className={cn("-mx-1 my-1 h-px bg-muted", className)}
        {...props}
      />
    ))
    MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName

const MenubarShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
MenubarShortcut.displayName = "MenubarShortcut"

export {
  Menubar,
  MenubarMenu,
  MenubarTrigger,
  MenubarContent,
  MenubarItem,
  MenubarSeparator,
  MenubarLabel,
  MenubarCheckboxItem,
  MenubarRadioGroup,
  MenubarRadioItem,
  MenubarPortal,
  MenubarSubContent,
  MenubarSubTrigger,
  MenubarGroup,
  MenubarSub,
  MenubarShortcut,
}

```