



deeplearning.ai

Setting up  
your goal

---

When to change  
dev/test sets and  
metrics

# Cat dataset examples

Metric + Dev : Prefer A  
You/users : Prefer B.

→ Metric: classification error

Algorithm A: 3% error → Pornographic

✓ Algorithm B: 5% error

Error:  $\frac{1}{\sum_i w^{(i)}} \times m_{dev}$

$$\sum_{i=1}^{m_{dev}} \frac{w^{(i)}}{\{y_{pred}^{(i)} + y^{(i)}\}}$$

predval value (0/1)

$$w^{(i)} = \begin{cases} 1 & \text{if } x^{(i)} \text{ is non-porn} \\ 10 & \text{if } x^{(i)} \text{ is porn} \end{cases}$$

# Orthogonalization for cat pictures: anti-porn

- 1. So far we've only discussed how to define a metric to evaluate classifiers. ← Place target 
- 2. Worry separately about how to do well on this metric. 

Am (shot at target)

$$\rightarrow J = \frac{1}{\sum w^{(i)}} \sum_{i=1}^m w^{(i)} \ell(\hat{y}^{(i)}, y^{(i)})$$



# Another example

Algorithm A: 3% error

✓ Algorithm B: 5% error ↙

→ Dev/test ↘



→ User images ↗



If doing well on your metric + dev/test set does not correspond to doing well on your application, change your metric and/or dev/test set.