PRD: Add to phone wallet from the approval screen

Author: @Michaela · Status: Draft · Target: High-Fidelity Prototype · Nov 11, 2026

1. The big picture

Vision. Every approved Riverty cardholder can pay with the card at the till within a minute of being approved, without typing a card number.

Press release (internal, fictional)

Riverty Card now goes into your phone wallet in one tap, right after approval. Lena, 32, uses pay later on most online orders but taps her bank card in shops by habit. In the friends-and-family test, 143 of 431 activated cards never reached a phone wallet (T-102), so at the till her Riverty card was not an option and she fell back to debit (N-03, N-06).

Now the approval screen offers "Add to wallet" as the main action. One tap, one confirmation, and the card is ready to tap in any shop. If she is not ready, she skips and her card still works online. If something fails, she sees what went wrong and can try again.

Success metrics

	Metric	Baseline (fact, data pack)	Target
Primary	Activated cards added to phone wallet	66.8% (288 of 431; 143 not added, T-102)	You set it. Placeholder: 80% (assumption, not evidence-based)
Guardrail	Month-1 retention of activated cards	64-69% across cohorts; must not fall below 64%	At or above 64%

Program anchor, watched but not claimed: in-store decline rate, 8.7% in Month 4 (206 attempts), 6.4% at best in Month 3. This feature should add in-store attempts, so the rate may rise unless B1 (decline reason) ships first or together. Employees are 59% of activations (N-10), so real-customer baselines are likely worse. Baselines are fictional practice data, not Riverty research.

2. The details

User stories

US-1: add in one tap. As Lena, a heavy pay later user, I want to add my new card to my phone wallet straight from the approval screen, so that I can tap it at the till instead of reaching for my debit card.

- Acceptance: the "Add to wallet" button is visible without scrolling on a 375 x 667 px viewport.
- Acceptance: from approval screen to success screen takes 3 taps or fewer.

US-2: skip without penalty. As Lena, who may not want the wallet step right now, I want to skip it and still use my card, so that approval never feels blocked.

- Acceptance: "Skip for now" reaches the card home in 1 tap.
- Acceptance: skipping leaves approval and activation status unchanged.

US-3: understand a failure. As Lena, who went back to debit after an unexplained decline (N-06), I want to see what went wrong when adding fails and how to retry, so that I do not give up on the card.

- Acceptance: every failure shows one plain-language reason and a Retry button.
- Acceptance: after 3 failed retries the screen offers "Add later from the card screen" and does not loop.

Screens to build (exactly 3)

#	Screen	Job	UI elements
1	Entry point: Approved	Make the wallet step the obvious next action	Approved confirmation headline; card visual showing last 4 digits only (fictional "4821"); primary button "Add to wallet"; secondary text button "Skip for now"; one line: "Tap to pay in shops. Online orders work without it."

#	Screen	Job	UI elements
2	Feature core: Adding to wallet	Show progress, handle failure	Progress state (spinner + "Adding your card", max 3 seconds in the prototype); failure state with reason line, "Try again" button, "Add later" link; step counter hidden (it is not a sequence)
3	Success: Card ready	Confirm and point to the next action	Check mark and "Your card is in your wallet"; card visual with wallet badge; one line "Hold your phone to the reader to pay"; button "Go to my card"

A small scenario switch (success, timeout, device unsupported, already added) sits outside the 3 screens as a reviewer tool, not as product UI.

Functional requirements

1. **FR-1** The approval screen shows "Add to wallet" as the primary button, visible without scrolling at 375 x 667 px.
2. **FR-2** The path from screen 1 to screen 3 takes 3 taps or fewer on success.
3. **FR-3** "Skip for now" reaches the card home in 1 tap, with approval and activation status unchanged. The step never blocks approval.
4. **FR-4** Every failure shows one reason from a fixed list of 3 (connection lost, wallet app declined the request, device not supported) plus a Retry button. No other reason text exists.
5. **FR-5** After 3 failed retries the screen shows "Add later" and stops offering Retry.
6. **FR-6** If the card is already in the wallet or the device is unsupported, the button is hidden and replaced by a one-line explanation.
7. **FR-7** Six events are written to an in-memory list: shown, tapped, started, succeeded, failed (with reason code), abandoned. A debug panel can display them.
8. **FR-8** Only the last 4 digits of the card appear anywhere in the UI or event list.

Smart behaviors

Situation	Outcome
Add succeeds	Go to screen 3; log "succeeded"
Add fails, fewer than 3 retries used	Show reason + "Try again"; log "failed" with reason code
Add fails the third time	Replace "Try again" with "Add later"; log "failed"
User taps "Skip for now"	Go to card home; log "abandoned" at screen 1
User leaves during progress	Treat as abandoned; card stays usable online
Card already in wallet	Hide button, show "Your card is already in your wallet"
Device cannot support the wallet	Hide button, show "This phone can't hold the card in a wallet. Your card works online."
Progress takes longer than 3 seconds	Switch to the connection-lost failure state

Technical constraints (what not to build)

- No external APIs and no real Apple Pay or Google Pay SDK. Provisioning is simulated with a timer.
- No login, accounts or backend. All data is hardcoded and fictional.
- One HTML file, plain JavaScript, no frameworks, no libraries.
- State lives in memory only and resets on reload.
- No real card data. The card number is fictional and only "4821" is ever shown.
- Open for engineering (not for the prototype): whether the issuing processor supports in-app provisioning, whether the token can be created before activation, and whether the wallet providers need approval. All three are unverified.

3. The logistics

Features out (Won't have, now)

- Forcing the wallet step before activation.

- Decline reasons and retry hints (B1) and the unified balance view (B3). Separate features.
- Wallets other than Apple Pay and Google Pay.
- Physical card, cashback and partner offers (all on the cut list).
- Any change to pricing, credit policy or terms. That triggers the approval cycle (N-11, months).
- Changes to the identity check (T-106) or the card issuing and token stack.
- Explaining credit score effects (T-107). No approved help content exists.

Edge cases

Unhappy path	Expected handling
Add fails and user leaves	Log "abandoned"; card stays usable online; no repeated prompt in this flow
Phone has no supported wallet	Hide the button; explain that the card works online
Card already in wallet (second device, earlier attempt)	Hide the button; show the already-added line
Connection drops mid-add	Connection-lost failure state with Retry; never show success
User taps the button twice	Ignore the second tap; one attempt at a time
Wallet reports success but state check disagrees	Treat as failed and show the generic retry reason

Safety and hallucination guard. The prototype must never show "in your wallet" unless the simulated provisioning returned success. It uses only the 3 fixed failure reasons and never invents a cause. It makes no claim about credit score, interest or fees. It shows only the last 4 digits. All strings are hardcoded and none are generated at run time.

Decision log

#	Decision	Why
D-1	The wallet step is skippable, not forced.	Approved to activated is already 73.5%, and month-1 retention must stay at or above 64%. Online purchases do not need the wallet. Cost: some people will skip and stay unreachable at the till.
D-2	Failure copy covers 3 fixed reasons only. Decline reasons at payment (B1) stay out.	Keeps this feature small and shippable. Cost: B2 sends more people into shops, where declines still show no reason. Sequence B1 first or together. This is open.

Evals

None of these have a baseline in the data pack. Targets are my proposals (assumptions). Set your own before testing.

#	Type	Target (proposed)	How to check
E-1	Task success	90% or more of testers reach screen 3 in 3 taps or fewer, unaided	5 or more internal testers, success scenario
E-2	Time on task	Median 20 seconds or less from screen 1 to screen 3	Stopwatch or event timestamps
E-3	Safety triggers	0 states that show success after a failure, 0 card digits beyond the last 4, and 4 of 4 scenarios show a reason plus a way forward on failure	Run every scenario in the switch and read the event list

Caution: internal testers are not Lena. Employees flatter results (N-10), so treat E-1 and E-2 as a usability check, not as evidence of the live wallet add rate.