
spinmate

AI AGENT FOR SPINTRONICS SIMULATION · VERSION 2.0

Spintronics simulation, by conversation.

Describe a setup in plain language or provide a parameter file. SpinMate checks it with the solver's own parser, runs two-sublattice macrospin simulations and explains the result from the actual magnetization dynamics.




Michael Lianeris · github.com/Michaellianeris/Spinmate-AI-Agent · MIT license

Outline


01	Version 2.0	What changed: any agent through MCP, a core package, validation, engines
02	Architecture	How the clients, the MCP server, the core and the engines fit together
03	Models and value	Five personas over Claude, OpenAI and Gemini; runs, sweeps, figures, reports on real runs
04	Trusted physics	The validation suite and the engines: macrospin and mumax3
05	Numbers and setup	Speed, tests, tools, the codebase, and how to run it

What’s new in Version 2.0

Version 1.0 (today)



Version 2.0 (proposal)



Any agent

An MCP server: Claude Code, Claude Desktop and the web app use the same tools

spinmate-core

The engine as a package with no LLM inside, and its own command line


Validated physics

9 analytic cases on every change; 4 solver issues found and fixed

Engines

macrospin built in, mumax3 as a plug-in, one interface

Architecture



Clients

The web app, Claude Code, Claude Desktop, any MCP agent

spinmate-mcp

19 tools, resources and prompts, with a physics subagent

spinmate-core

Run queue, engines (macrospin, mumax3), validation, catalog, /data

Use it from any agent

Claude Code

```
claude mcp add --transport http \
  spinmate http://localhost:8421/mcp
```

Without Docker

```
python -m spinmate_mcp          # stdio
python -m spinmate_mcp --http   # :8422
```

Claude Desktop: the same server over stdio, in claude_desktop_config.json. The repository brings a physics subagent and skill for Claude Code.

19 tools
Validate, run, sweep, wait, get the plot, compare, figure, report, SQL on the catalog

Resources
spinmate:// parameters, physics guide and scales, validation, runs, examples

Prompts
design_experiment, find_threshold, interpret_run

Same safety
Large requests return needs_confirmation; the agent asks you first

Five personas, one router



Hermes

Quick and economical

Claude Haiku, GPT nano / mini, Gemini Flash-Lite



Dionysus

Balanced, the default

Claude Sonnet, GPT-5.x, Gemini Flash



Zeus

Deep, most capable

Claude Opus, OpenAI o-series, Gemini Pro



Apollo

Specialised and new

Claude Fable / Mythos, new models



Athena

The guide


How to use the app; built-in answers offline

ON AUTO, EVERY REQUEST IS SCORED OVER THE PERSONA'S MODELS

$$\text{score} = \text{capability} + \text{bonus} - \lambda(\text{persona}, \text{request}) \times \log_{10}(\text{price} / \text{cheapest}) - \text{shortfall}$$

The strongest model wins unless a cheaper one is clearly enough. Every answer shows the model, the reason and the cost in €, at the daily ECB rate.

A tour of the home page



LEFT BAR

1. New conversation (Ctrl+K)
2. Conversation history
3. Runs panel and catalog (Ctrl+/)
4. Default parameters
5. Run setup, no AI needed
6. Physics validation
7. Connect to Claude (MCP)
8. Model gods, tools guide
9. Settings: language, theme, API keys

MESSAGE BOX

10. Ask, attach a .txt, or the sweep form
11. Voice input
12. Persona: the model level
13. Fast or Deep; tokens and € per provider

START HERE

14. Find a skill: ready questions
15. Athena: how-to, guide and slides

What SpinMate gives you

BY HAND

1. Edit the parameter file
2. Run the solver and wait
3. Write a plotting script
4. Read the curves for switches and settling
5. Collect parameters and figures into a write-up

WITH SPINMATE

1. One sentence, or the same .txt file
2. Every value checked by the solver’s parser
3. Run card with the sphere, curves and metrics
4. Answer written from the computed metrics
5. IEEE figure and PDF report on request

Same solver, same physics: the agent removes the steps around it, not the model.


One question, one run



Behind one question

1. The router picks a model for the chosen persona and request.
2. The model calls validate_parameters, then start_simulation.
3. The run queue starts the solver; the card shows live progress.
4. wait_for_run returns the metrics, and the answer is written from them.

Sweeps, thresholds and continued runs




“Sweep A0 from −0.25e-12 to +0.25e-12 in 11 steps, 0.5 ns each. Where does the final order change?”


RESULT

The order changes between A0 = −0.05e-12 and 0: AFM below, FM from 0 upwards.

- Runs go in parallel; click a point to open that run.
- Threshold search: bracketing sweeps narrow the interval.
- Continue run keeps the clock, so AC fields and the FeRh cycle do not restart.

Figures and reports, ready to share




spinmate

SIMULATION REPORT

Exchange sign and final order

2026-10-16 12:37 · Michael · runs r0001, r0002

Method

Two-sublattice macrospin model of the original SpinMate code: the coupled Landau-Lifshitz-Gilbert equations of $\mathbf{m}_1$ and $\mathbf{m}_2$ are integrated with Heun's method. Each sublattice feels the inter-sublattice exchange field $4A_0 / (\mu_0 M_s^2 l^2)$ along the other sublattice and the uniaxial anisotropy field $2K_u / (\mu_0 M_s^2)$ along $\mathbf{u}_{ani}$ (both in units of M_s), and the applied fields, spin-orbit torques and thermal field set in its parameter file. Order is read from $\mathbf{m}_1 \cdot \mathbf{m}_2$ (AFM below -0.9, FM above $+0.9$); a switch is a reversal of the Néel vector $\mathbf{n} = (\mathbf{m}_1 - \mathbf{m}_2) / 2$ with n_z crossing from below -0.5 to above $+0.5$ or back.

Results

Run	Label	Order	$\mathbf{m}_1 \cdot \mathbf{m}_2$ (end)	n_z switches	First switch (ps)	Settled (ps)	$f(m_{1z})$ (GHz)	Duration (ns)	Runtime (s)
r0001	FM → AFM, A0 = -0.248e-12	FM → AFM	-1	0	–	–	–	0.0499	1.32
r0002	AFM → FM, A0 = +0.248e-12	AFM → FM	1	8	3.7	–	–	0.0499	1.34

Parameters shared by all runs (differing from the defaults)

Parameter	Value
n1	0.25, 0, 0.968
t	5e-11

Parameters that differ between runs

Parameter	r0001	r0002
A0	-2.48e-13	2.48e-13
n2	0.35, 0, 0.937	-0.35, 0, -0.937

Discussion

Figures

IEEE, Nature and science styles, as PDF, SVG and PNG.


Reports

Method, results, parameters and figures, with LaTeX math and the SpinMate header.

Export

Print to PDF, or download the HTML or a Markdown and figures zip.

Every run in one catalog



One row per run

Postgres in Docker, SQLite in the Windows app: parameters, summary and the links between runs.


Questions across runs

The model writes one read-only SELECT; the result comes back as a table with Export CSV.

Runs panel

Search by id, label, #tag or parameter; filter, star, compare, plot or report.

Validated physics



Measured AFM/FM boundary (12 points) on $|Ku| = 2|A0|/l^2$, within 2–6 %

Case	Expected	Measured
$|m_1| = |m_2| = 1$	0	2e-16
Same input, same trajectory	0	0
Energy at α = 0	conserved	drift 1.6e-6
Kittel mode	5.62 GHz	5.61 GHz
AFM resonance	67.3 GHz	67.3 GHz
Time-step convergence	h = 1e-13 s	0.03 %
Gilbert damping α·ω	0.3525 /ns	0.3524 /ns
AFM/FM boundary	$2|A0|/l^2$	at ±10 %
Thermal field σ	Temp_Ampl	within 3 %

4 solver issues fixed: anisotropy counted twice, Ku(t) amplitude, RK4 weights, thermal noise. Runs at T = 0 stay bit-identical.

python -m spinmate_core.validation · runs on every pull request that touches the solver

Engines as plug-ins

BUILT IN · DEFAULT

macrospin

- Two coupled LLG equations, sublattices m_1 and m_2
- Exchange, anisotropy, field, SOT, temperature, drives
- Sweeps, continuation, combination of runs
- Runs on any CPU in seconds

PLUG-IN · OPTIONAL

mumax3

- GPU micromagnetics of a ferromagnet on a grid
- SpinMate lines become an .mx3 script, or bring your own
- Run card shows the average ⟨m⟩(t)
- Needs an NVIDIA GPU and MUMAX3_BIN

```
[project.entry-points."spinmate.engines"]
mumax3 = "spinmate_mumax3:Mumax3Engine"
```

One interface: parameter_schema, validate, run_command, outputs. mumax3 (GPL v3) runs as a separate program, so SpinMate stays MIT.

Cite mumax3: Vansteenkiste et al., AIP Advances 4, 107133 (2014)

SpinMate in numbers


1.3 s
to simulate 50 ps (500 steps), run r0001

51 s
for an 11-run A0 sweep, 0.5 ns each

89
automated tests, all passing

16
eval cases through the real agent and solver

Codebase by part · 13,314 lines



- **37 %** web UI
- **24 %** core, MCP and plug-ins
- **18 %** agent and web server
- **13 %** tests and evals
- **5 %** solver, validated
- **4 %** desktop app and guide

The 19 tools by job



- **5** inputs, validation, engines
- **5** runs
- **3** sweeps
- **2** continue and combine
- **4** compare, figure, report, SQL

Measured on the runs in this deck; lines of .py, .html and .js in the repository

Runs on your machine

Local by default

Listens on 127.0.0.1 only. Docker on Linux, macOS and WSL, or a Windows app.

Your keys

In .env or the browser tab, never committed. Calls bill your own account; TOKEN_BUDGET sets a cap.

Your data

Runs, figures, reports and accounts stay in /data. Only the optional welcome email leaves; MAIL_RELAY=off turns it off.

Guard rails

Read-only SQL with a timeout; runs start only through the solver’s parser; big requests ask first, over MCP too.

Get started

Docker

```
cp .env.example .env
docker compose up --build
```

Add an Anthropic, OpenAI or Gemini key to .env, then open localhost:8421.

Windows app

Download SpinMate-windows.zip from Releases, unzip and run SpinMate.exe. No Docker or Python needed; the catalog is SQLite.

First start

Athena asks your name and, optionally, your email for the PDF guide. No key yet? Run setup runs a preset directly.

From Claude Code `claude mcp add --transport http spinmate http://localhost:8421/mcp`

spinmate **github.com/Michaellianeris/Spinmate-AI-Agent**

Free and open source under the MIT license · the user guide is web/spinmate-guide.pdf