

ALCANTARA®

ALCANTARA® Thin

Cod. 5010

Application

Apparel Accessories

Main Characteristics

COMPOSITION	ALCANTARA®	Polyester Polyurethane	70 ± 3 % 30 ± 3 %
THICKNESS			0.40 ± 0.05 mm
UNIT WEIGHT		UNI EN 29073-1	115 - 145 g/m2
WIDTH			≥ 142 cm
DIMENSIONAL STABILITY	Water 40°C	UNI EN ISO 25077 + 6330	≤ 3 %
BREAKING LOAD	Lengthwise Crosswise	UNI EN 29073-3	≥ 60 N ≥ 40 N
TEAR STRENGTH	Lengthwise Crosswise	EN ISO 13937-2	≥ 2.5 N ≥ 1.5 N

Color Fastness (*)

TO LIGHT	Xenotest Beta - 36h	UNI EN ISO 105 B02	≥ 5.5 blue scale (1-8)
TO DOMESTIC WASHING	Tone change Staining	UNI EN ISO 105 C06	≥ 4 grey scale (1-5) ≥ 3 grey scale (1-5)
TO DRY CLEANING	Tone change Staining	AATCC 132	≥ 4 grey scale (1-5) ≥ 3 grey scale (1-5)
TO RUBBING	Dry Wet	UNI EN ISO 105 X12	≥ 4 grey scale (1-5) ≥ 3 grey scale (1-5)
TO PERSPIRATION	Acid Basic	UNI EN ISO 105 E04	≥ 4.5 grey scale (1-5) ≥ 4.5 grey scale (1-5)

General Washing



(*) Slight shade variations from one production batch to another one are possible on these products
In case of items manufactured using different materials, always verify the compatibility of the same

