

Variable	Unit	Description	Value Range
SpO ₂	%	Peripheral oxygen saturation	95–100%
HR	bpm	Heart rate from pulse oximeter	60–100 bpm
PI	%	Perfusion index	0.2–20%
RR	breaths/min	Respiratory rate	12–20 breaths/min
EtCO ₂	mmHg	End-tidal carbon dioxide	35–45 mmHg
FiO ₂	%	Fraction of inspired oxygen	21–100%
PRV	ms	Pulse rate variability	20–200 ms
BP	mmHg	Blood pressure (systolic diastolic mean)	90/60–120/80 mmHg
Skin Temperature	°C	Peripheral temperature	33–38 °C
Motion/Activity index	-	Sensor artifact correction	
PVI	%	Pleth Variability Index	10–20%
Hb level	g/dL	Hemoglobin concentration	12–18 g/dL
SV	mL/beat	Stroke volume	60–100 mL/beat
CO	L/min	Cardiac output	4–8 L/min
Blood Flow Index	-	Optical/near-infrared blood flow measurement	Relative units
PPG waveform features	-	Photoplethysmography signal parameters	
Signal Quality Index	-	Reliability indicator of readings	0–100
Respiratory effort	-	Chest impedance or belt-derived effort	
O ₂ extraction ratio	-	Calculated oxygen extraction metric	0.2–0.3
SNR	dB	Signal-to-noise ratio from sensor	20–40 dB