



Player & UI

YOU'LL SHIP

An intro screen, a main menu and an in-game HUD.

- 4.1 Build a studio-grade intro screen
- 4.2 ScreenGui, Frames and TextLabels
- 4.3 Scaling for desktop, mobile and console
- 4.4 Animation with TweenService
- 4.5 Main menu and HUD

UI is the first thing players judge. A clean intro, a readable HUD and a menu that works on a phone make a game feel trustworthy before anyone has played a single round. In this module you'll build all three for Coin Rush.

4.1 Build a studio-grade intro screen

This is the free preview lesson, in short. (The full step-by-step version with explanations is in [free-lesson-intro-screen.md](#).)

Put a **LocalScript** named `IntroSplash` in **ReplicatedFirst**, which is the first thing that runs when a player joins:

```
local ReplicatedFirst = game:GetService("ReplicatedFirst")
local Players = game:GetService("Players")
local TweenService = game:GetService("TweenService")

ReplicatedFirst:RemoveDefaultLoadingScreen()

local playerGui = Players.LocalPlayer:WaitForChild("PlayerGui")

local gui = Instance.new("ScreenGui")
gui.IgnoreGuiInset = true
gui.DisplayOrder = 1000
gui.ResetOnSpawn = false

local bg = Instance.new("Frame")
bg.Size = UDim2.fromScale(1, 1)
bg.BackgroundColor3 = Color3.new(0, 0, 0)
bg.BorderSizePixel = 0
bg.Parent = gui

local logo = Instance.new("ImageLabel")
logo.Image = "rbxassetid://YOUR_ASSET_ID"
logo.BackgroundTransparency = 1
logo.AnchorPoint = Vector2.new(0.5, 0.5)
logo.Position = UDim2.fromScale(0.5, 0.5)
logo.Size = UDim2.fromScale(0.4, 0.4)
logo.ImageTransparency = 1
logo.Parent = bg
Instance.new("UIAspectRatioConstraint", logo).AspectRatio = 1
local scale = Instance.new("UIScale", logo)
scale.Scale = 0.9
```

```

gui.Parent = playerGui

TweenService:Create(scale, TweenInfo.new(0.25, Enum.EasingStyle.Back), { Scale = 1
}):Play()
local fadeIn = TweenService:Create(logo, TweenInfo.new(0.25), { ImageTransparency = 0 })
fadeIn:Play()
fadeIn.Completed:Wait()
task.wait(1.75)

local out = TweenInfo.new(0.4)
TweenService:Create(logo, out, { ImageTransparency = 1 }):Play()
local bgOut = TweenService:Create(bg, out, { BackgroundTransparency = 1 })
bgOut:Play()
bgOut.Completed:Wait()
gui:Destroy()

```



ScreenGui, Frames and TextLabels

All 2D interface lives inside a **ScreenGui**. You design UI in **StarterGui**; when a player spawns, Roblox copies it into their **PlayerGui**.

The building blocks:

Class	Use
Frame	A rectangle, used as a panel or container.
TextLabel	Text that players read.
TextButton / ImageButton	Things players click or tap.
ImageLabel	Pictures and icons.
UICorner	Rounded corners.
UIStroke	Outlines, for text or frames.
UIListLayout / UIGridLayout	Automatic arrangement of children.
UIPadding	Inner spacing.

Build the HUD layout in StarterGui:

```

StarterGui
├─ HUD (ScreenGui)
│   ├─ CoinPanel (Frame, top-left)
│   │   ├─ UICorner
│   │   ├─ Icon (ImageLabel)
│   │   └─ CoinText (TextLabel) "0"
│   └─ TimerPanel (Frame, top-center)
│       ├─ UICorner
│       └─ TimerText (TextLabel) "Intermission"

```

Text tips: use a bold, readable font (`FontFace` → Gotham/Montserrat/Fredoka One style), turn on `TextScaled` with a `UITextSizeConstraint` (MaxTextSize ~36), and add a `UIStroke` so text stays readable on bright backgrounds.

Scaling for desktop, mobile and console

More than half of Roblox players are on phones. UI that looks perfect on your monitor can be unusable on a phone.

Rule 1: use Scale, not Offset. A `UDim2` has four numbers: `(xScale, xOffset, yScale, yOffset)`. Scale is a fraction of the screen; Offset is pixels.

```

UDim2.new(0.2, 0, 0.08, 0)    -- 20% of width, 8% of height: works everywhere
UDim2.new(0, 300, 0, 60)      -- 300x60 px: huge on phones, tiny on 4K

```

Rule 2: lock shapes with `UIAspectRatioConstraint`. A coin icon should stay round on every screen.

Rule 3: position with `AnchorPoint`. `AnchorPoint = (0.5, 0)` plus `Position = (0.5, 0, 0.02, 0)` keeps the timer centered at the top on any screen.

Rule 4: respect the safe area. Phones have notches and Roblox has its top-bar buttons. Keep important UI a little away from the edges, or check `ScreenGui.ScreenInsets`.

Test it: in the **Test** tab open the **Device emulator** and switch between phone, tablet and console sizes. Fix anything that overlaps or gets too small.

Animation with TweenService

`TweenService` smoothly animates any property from its current value to a target.

```

local TweenService = game:GetService("TweenService")

local info = TweenInfo.new(
    0.3, -- duration (seconds)
    Enum.EasingStyle.Quad, -- shape of the motion
    Enum.EasingDirection.Out -- slow down at the end
)

local tween = TweenService:Create(frame, info, {
    Position = UDim2.fromScale(0.5, 0.5),
    BackgroundTransparency = 0,
})
tween:Play()

```

Juice for the coin counter. Make it "pop" whenever the number changes:

```

local function pop(label: TextLabel)
    local uiScale = label:FindFirstChildOfClass("UIScale") or Instance.new("UIScale",
label)
    uiScale.Scale = 1.25
    TweenService:Create(uiScale, TweenInfo.new(0.25, Enum.EasingStyle.Back), { Scale = 1
}):Play()
end

```

Easing styles change the feeling: **Quad** is calm, **Back** overshoots playfully, **Bounce** is cartoony, **Linear** feels mechanical. Keep UI animations short (0.15–0.4 s). Slow UI feels laggy.

4.5

Main menu and HUD

Main menu. A full-screen frame with the game title, a big **PLAY** button, and a **SHOP** button (wired up in Module 7). Put a LocalScript in the menu ScreenGui:

```

local TweenService = game:GetService("TweenService")

local menu = script.Parent.WaitForChild("Menu")
local playButton = menu.WaitForChild("PlayButton")

playButton.Activated:Connect(function()
    local tween = TweenService:Create(menu, TweenInfo.new(0.3), { Position =
UDim2.fromScale(0, -1) })
    tween:Play()
    tween.Completed:Wait()
    menu.Visible = false
end)

```

Use `Activated` instead of `MouseButton1Click`. It works for mouse, touch and gamepad.

HUD coin counter. This LocalScript in `HUD` shows the player's coins. The `leaderstats` it reads are created in Module 6; until then it simply shows 0.

```

local Players = game:GetService("Players")
local TweenService = game:GetService("TweenService")

local player = Players.LocalPlayer
local coinText = script.Parent.WaitForChild("CoinPanel"):WaitForChild("CoinText")

local function pop()
    local s = coinText:FindFirstChildOfClass("UIScale") or Instance.new("UIScale",
coinText)
    s.Scale = 1.25
    TweenService:Create(s, TweenInfo.new(0.25, Enum.EasingStyle.Back), { Scale = 1
}):Play()
end

local leaderstats = player.WaitForChild("leaderstats")
local coins = leaderstats.WaitForChild("Coins")

coinText.Text = tostring(coins.Value)
coins.Changed:Connect(function(value)
    coinText.Text = tostring(value)
    pop()
end)

```

Round timer. In Module 7 the server will store the round state in attributes on `ReplicatedStorage`. The HUD just listens:

```

local ReplicatedStorage = game:GetService("ReplicatedStorage")
local timerText = script.Parent:WaitForChild("TimerPanel"):WaitForChild("TimerText")

local function refresh()
    local status = ReplicatedStorage:GetAttribute("RoundStatus") or "Waiting"
    local timeLeft = ReplicatedStorage:GetAttribute("TimeLeft") or 0
    timerText.Text = if timeLeft > 0 then `{status} · {timeLeft}s` else status
end

ReplicatedStorage:GetAttributeChangedSignal("RoundStatus"):Connect(refresh)
ReplicatedStorage:GetAttributeChangedSignal("TimeLeft"):Connect(refresh)
refresh()

```

TIP The backtick string `{status} · {timeLeft}s` is Luau string interpolation, a clean way to build text from values.

TRY IT

1. Add a subtle idle animation to the PLAY button (scale 1 → 1.05 and back, repeating). Hint: `TweenInfo.new(0.8, Enum.EasingStyle.Sine, Enum.EasingDirection.InOut, -1, true)`.
2. Test the menu and HUD in the device emulator at phone size.

Module recap

- ☐ Intro screen runs once on join
- ☐ HUD with coin counter and round timer, built with Scale and AnchorPoint
- ☐ Main menu with PLAY that animates away
- ☐ Everything checked in the device emulator