Mutual Exclusion

Intermediate Summary

IPC

 Disabling Interrupts Not recommended for multi-user systems.

 Lock Variables Problem remains the same.

 Strict Alternation Violation of condition 3. Busy waiting.

 Peterson Algorithm Busy waiting.

 TSL instruction Solves the problem through atomic operation. Should be used without busy waiting.

In essence, what the last three solutions do is this: A process checks whether the entry to its critical region is allowed. If it is not, the process just sits in a tight loop waiting until it is.

Unexpected side effects, such as priority inversion problem.

Computer Architecture WS 06/07

Dr.-Ing. Stefan Freinatis



Priority Inversion Problem

IPC

Consider a computer with two processes

Process *H* with high priority Process L with low priority

The scheduling rules are such that **H** is run whenever it is in ready state.

At a certain moment, with **L** in its critical region, **H** becomes ready and is scheduled. **H** now begins busy waiting, but since **L** is never scheduled while **H** is running, **L** never has the chance to leave its critical region. H loops forever. This is sometimes referred to as the priority inversion problem.

Solution: blocking a process instead of wasting CPU time.



IPC

sleep()

A system call that causes the caller to block, that is, the process voluntarily goes from the running state into the waiting state. The scheduler switches over to another process.

wakeup (process)

A system call that causes the process process to awake from its sleep () and to continue execution. If the process process is not asleep at that moment, the wakeup signal is lost.

Note: these two calls are fictitious representatives of real system calls whose names and parameters depend on the particular operating system.

Computer Architecture WS 06/07

Dr.-Ing. Stefan Freinatis



Producer – Consumer Problem

IPC

Shared buffer with limited size


The buffer allows for a maximum of N entries (it is bounded). The problem is also known as bounded buffer problem.

Producer puts information into buffer

When the buffer is full, the producer must wait until at least one item has been consumed

Consumer removes information from buffer

When the buffer is empty the consumer must wait until at least one new item has been entered.



```
Producer – Consumer Implementation Example
int count = 0;
                                 This implementation suffers from race conditions
void producer() {
                                                 constantly producing
  while (TRUE) {
   int item = produce item();
                                                 produce item
   if (count == N) sleep();
                                                 sleep when buffer is full
   insert item(item);
                                                 enter item to buffer
   count++;
                                                 adjust item counter
   if (count == 1) wakeup(consumer);
                                           when the buffer was empty beforehand
}
                                           (and thus now has 1 item), wakeup any
                                           consumer(s) that may be waiting
void consumer() {
  while (TRUE) {
                                                 constantly consuming
     if (count == 0) \downarrow sleep();
                                                 sleep when buffer is empty
     item = remove_item();
                                                 remove one item
     count--;
                                                 adjust item counter
    if (count == N-1) wakeup(producer);
    consume item(item);
                                          when the buffer was full beforehand
                                           (and thus now has N-1 items), wakeup
  }
```

Producer - Consumer Problem

A race condition may occur in this case:

const int N = IUU;

Mutual Exclusion

The buffer is empty and the consumer has just read **count** to see if it is 0. At that instant (see A in listing) the scheduler decides to switch over to the producer.

The producer inserts an item in the buffer, increments **count** and notices that **count** is now 1. Reasoning that **count** was just 0 and thus the consumer must be sleeping, the producer calls **wakeup()** to wake the consumer up.

However, the consumer was not yet asleep, it was just taken away the CPU shortly before it could enter **sleep()**. The wakeup signal is lost.

When the consumer is rescheduled and resumes at (A), it will go to sleep. Sooner or later the producer has filled up the buffer and goes asleep as well.

Both processes will sleep forever.

producer(s) that may be waiting.

Producer – Consumer Problem

Mutual Exclusion

Reasons for race condition

- The variable count is unconstrained Any process has access any time.
- Evaluating count and going asleep is a non-atomic operation The prerequisite(s) that lead to sleep() may have changed when sleep() is reached.

Workaround:

- Add a wakeup waiting bit When the bit is set, sleep() will reset that bit and the process stays awake.
- Each process must have a wakeup bit assigned Although this is possible, the principal problem is not solved.

What is needed is something that does testing a variable and going to sleep – dependent on that variable – in a single non-interruptible manner.

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Semaphores

Mutual Exclusion

- Introduced by Dijkstra (1965)
- Counting the number of wakeups An integer variable counts the number of wakeups for future use.
- Two operations: down and up

down is a generalization of sleep. up is a generalization of wakeup. Both operations are carried out in a single, indivisible operation (usually in kernel). Once a semaphore operation is started, no other process can access the semaphore.

```
down(int* sem) {
 if (*sem < 1) sleep();
 *sem--;
```

principle of down-operation

```
up(int* sem) {
 *sem++;
if (*sem == 1) wakeup a process
```

principle of up-operation



Semaphores

Mutual Exclusion

Up and down are system calls

in order to make sure that the operating system briefly disables all interrupts while carrying out the few machine instructions implementing up and down.

· Semaphores should be lock-protected

This is recommended at least in multi-processor systems to prevent another CPU from simultaneously accessing a semaphore. TSL instruction helps out.

Producer – Consumer problem using semaphores (next page)

```
Definition of variables:

a semaphore is an integer typedef int semaphore;

counting empty slots semaphore empty = N;

counting full slots semaphore full = 0;

mutual exclusion on buffer access semaphore mutex = 1;
```

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis


DUISBURG

```
Producer – Consumer Implementation Example
void producer() {
                                  This implementation does not suffer from race conditions
  while (TRUE) {
   int item = produce item();
                                     possibly sleep, decrement empty counter
   down (&empty);
   down (&mutex);
                                     possibly sleep, claim mutex (set it to 0) thereafter
   insert item(item);
   up(&mutex);
                                     release mutex, wake up other process
   up(&full);
                                     increment full counter, possibly wake up other ...
}
void consumer() {
  while(TRUE) {
     down(&full);
                                     possibly sleep, decrement full counter
     down (&mutex);
                                     possibly sleep, claim mutex (set it to 0) thereafter
     item = remove item();
     up(&mutex);
                                     release mutex, wake up other process
     up(&empty);
                                     increment empty counter, possibly wake up other ..
     consume item(item);
   }
```

Semaphores


Assume N = 5. Initial condition: empty = 5, full = 0.

Mutual Exclusion



Scenario: producer is working, no consumer present

Initial condition: empty = 0, full = 5.



Scenario: consumer is working, no producer present


Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Semaphores

Assume N = 5. Initial condition: empty = 1, full = 4.

Mutual Exclusion




Scenario: Consumer waking up producer

Semaphores

Assume N = 5. Initial condition: empty = 4, full = 1.

Mutual Exclusion




Scenario: Producer waking up consumer

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Semaphores

3



If processes overlap, then temporary it may be that empty + full \neq N Note that consumer and producer may almost concurrently change the same semaphore legally.

23 up

up


Mutex

Mutual Exclusion

Simplified semaphore when counting is not needed.

Two states

Locked or unlocked. Used for managing mutual exclusion (hence the name).



Pseudo assembler listing implementing mutex lock() and mutex unlock().

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Monitors

Mutual Exclusion

- High level synchronization primitive at programming language level. Direct support by some programming languages.
- A collection of procedures, variables and data structures grouped together in a module
 - A monitor has multiple entry points
 - Only one process can be in the monitor at a time
 - Enforces mutual exclusion less chances for programming errors
- Monitor implementation
 - Compiler handles implementation
 - Library functions using semaphores



Monitors

Mutual Exclusion monitor example; Variables not accessible from outside the integer i; monitor's own methods (capsulation). condition c: procedure producer() Functions (methods) publicly accessible to all processes, however only one process at a time may call a monitor function. end: procedure consumer() If the buffer is full, the producer must wait. If the buffer is empty the consumer must wait. end: end monitor; A monitor in Pidgin Pascal, from [Ta01 p.115]

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Monitors

Mutual Exclusion

How can a process wait inside a monitor?

Cannot put to sleep because no other process can enter the monitor meanwhile.

Use a condition variable!

A condition variable supports two operations.

- wait(): suspend this process until it is signaled. The suspended process is not considered inside the monitor any more. Another process is allowed to enter the monitor.
- signal(): wake up one process waiting on the condition variable. No effect if nobody is waiting. The signaling process automatically leaves the monitor (Hoare monitor).
- Condition variables usable only inside a monitor.



Monitors

monitor ProducerConsumer

integer count;

begin

end:

begin

end: count := 0;end monitor:

condition full, empty;

procedure insert(item: integer);

insert_item(item);

count := count + 1;

count := count - 1;

function remove: integer;

if *count* = *N* **then wait**(*full*);

if count = 1 then signal(empty)

if count = 0 then wait(empty); remove = remove item;

if count = N - 1 then signal(full)

```
Mutual Exclusion
procedure producer;
begin
     while true do
     begin
           item = produce_item;
           ProducerConsumer.insert(item)
     end
end:
procedure consumer;
begin
     while true do
     begin
           item = ProducerConsumer.remove;
           consume_item(item)
     end
end:
```

Producer-Consumer problem with monitors, from [Ta01 p.117]

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis




IPC

Barriers

Group synchronization

Intended for groups of processes rather than for two processes.

- Processes wait at a barrier for the others according to the all-or-none principle
- After all have arrived, all can proceed



Processes approaching barrier


Waiting for C to arrive

All processes continuing

Figure from [Ta01 p.124]



Barriers



An array (e.g. an image) is updated frequently by some process 0 (producer). Many processes are working in parallel on certain array elements (consumers). All consumers must wait until the array has been updated and can then start working again on the updated input.

Computer Architecture WS 06/07

Dr.-Ing. Stefan Freinatis



IPC

Intermediate Summary (II)

Semaphores

Counting variable, used in non-interruptible manner. Down may put the caller to sleep, up may wake up another process.

Mutexes

Simplified semaphore with two states. Used for mutual exclusion.

Monitors

High level construct for achieving mutual exclusion at programming language level.


Barriers

Used for synchronizing a group of processes.

These mechanisms all serve for process synchronization. For data exchange among processes something else is needed: Messages.



- Kernel supported mechanism for data exchange
 Eliminates the need for ,self-made' (user-programmed) communication via shared
 resources such as shared files or shared memory.
- Two basic operations: send(): send data
 provided by the kernel (system calls)
 receive(): receive data



Computer Architecture

WS 06/07

Dr.-Ing. Stefan Freinatis



Direct Communication

Messages

- Both processes must exist

 As the name *direct* implies, you cannot send a message to a future process.
- · Processes must name each other explicitly
 - send(P, message): send data to process P
 - receive(Q, message): receive data from process Q

Symmetry in addressing. Both processes need to know each other by some identifier. This is no problem if both were **fork()**ed off the same parent beforehand, but is a problem when they are ,strangers' to each other.

- Communication link properties
 - One process pair has exactly one link
 - The link may be unidirectional or bidirectional



Indirect Communication

Messages

Messages are send / received from mailboxes

The mailbox must exist, not necessarily the receiving process yet.

- Each mailbox has a unique identifier
- Processes communicate when they access the same mailbox

Primitives

- send(A, message): send message to mailbox A
- receive(A, message): receive message from mailbox A

Communication link properties

- Link is established when processes share a mailbox
- A link may be associated with many processes (broadcast)
- Unidirectional or bidirectional communication

Computer Architecture WS 06/07


Dr.-Ing. Stefan Freinatis



Synchronous Communication

Messages

- Also called blocking send / receive
- Sender waits for receiver to receive the data The send() system call blocks until receiver has received the message.



Receiver waits for sender to send data

The receive() system call blocks until a message is arriving.




Asynchronous Communication

Messages

Also called non-blocking send / receive

Sender drops message and passes on

The send() system call returns to the caller when the kernel has the message.



Multiple buffers (for each pair) needed

Receiver peeks for messages

The receive() system does not block, but rather returns some error code telling whether there is a message or not. Receiver must do polling to check for messages.

Computer Architecture WS 06/07

Dr.-Ing. Stefan Freinatis



Messages

IPC

Send by copy

The message is copied to kernel buffer at send time. At receive time the message is copied to the receiver. Copying takes time.

Send by reference

A reference (a memory address or a handle) is copied to the receiver which uses the reference to access the data. The data usually resides in a kernel buffer (is copied there beforehand). Fast read access.

Fixed sized messages

The kernel buffers are of fixed size – as are the messages. Straightforward system level implementation. Big messages must be constructed from many small messages which makes user level programming somewhat more difficult.

Variable sized messages

Sender and receiver must communicate about the message size. Best use of kernel buffer space, however, buffers must not grow indefinitely.



UNIX IPC Mechanisms

IPC

Pipes

Simple(st) communication link between two processes. Applies *first-in first-out* principle. Works like an invisible file, but is no file. Operations: read(), write().

FIFOs

Also called *named* pipe. Works like a file. May exist in modern Unices just in the kernel (and not in the file system). There can be more than one writer or reader on a FIFO. Operations: open(), close(), read(), write().

Messages

Allow for message transfer. Messages can have types. A process may read all messages or only those of a particular type. Message communication works according to the *first-in first-out* principle.

Operations: msgget(), msgsnd(), msgrcv(), msgctl().

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



UNIX IPC Mechanisms

IPC

Shared memory

A selectable part of the address space of process P_1 is mapped into the address space of another process P_2 (or others). The processes have simultaneous access. Operations: shmget(), shmat(), shmdt(), shmctl().

Semaphores

Creation and manipulation of sets of semaphores. Operations: semget(), semop(), semctl().

For an introduction into the UNIX IPC mechanisms (with examples) see

Stefan Freinatis: *Interprozeßkommunikation unter Unix - eine Einführung*, Technischer Bericht, Fachgebiet Datenverarbeitung, Universität Duisburg, 1994. http://www.fb9dv.uni-duisburg.de/vs/members/fr/ipc.pdf



```
const int FIXSIZE=80
void main() {
   int fd[2];
                                     // file descriptors for pipe
   pipe(fd);
                                     // create pipe
   int result = fork();
                                     // duplicate process
                                     // start child's code
   if (result == 0) {
     printf("This is the child, my pid is: %d\n", getpid());
                                     // we do not need writing
     close(fd[1]);
                                     // a buffer
     char buf[256];
     read(fd[0], buf, FIXSIZE)
                                     // wait for message from parent
     printf("Child: received message was: %s\n", buf);
     exit(0);
                                     // good bye
                                     // end child, start parent
   }
   close(fd[0]);
                                     // we do not need reading
   printf("This is the parent, my pid is: %d\n", getpid());
   write(fd[1], "Hallo!", FIXSIZE); // write message to child
}
```

Classical IPC Problems

The dining philosophers

An artificial synchronization problem posed and solved by Edsger Dijkstra 1965.

Five philosophers sitting at a table

The problem can be generalized to more than five philosophers, of course.

- · Each either eats or thinks
- · Five forks available
- Eating needs 2 forks
 Slippery spaghetti, one needs two forks!
- Pick one fork at a time
 Either first the right fork and then the left one, or vice versa.




Figure from [Ta01 p.125]

IPC

Dining philosophers

Classical IPC problems

The life of these philosophers consists of alternate periods of eating and thinking. When a philosopher becomes hungry, she tries to acquire her left and right fork, one at a time, in either order. If successful in acquiring two forks, she eats for a while, then puts down the forks and continues to think.

Text from [Ta01 p.125]

Can you write a program that

- makes the philosophers eating and thinking (thus creation of 5 threads or processes, one for each philosopher),
- allows maximum utilization (parallelism), that is, two philosophers may eat at a time (no simple solution with just one philosopher eating at a time),
- is not centrally controlled by somebody instructing the philosophers,
- and that never gets stuck?

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



Dining philosophers

}

Classical IPC problems

```
const int N=5;
void philosopher(int i) {
                                 // N philosophers in parallel
   while (TRUE) {
                                 // for the whole life
     think();
     take fork(i);
                                 // take left fork
     take fork((i+1)%N);
                                 // take right fork
     eat();
     put fork(i);
                                 // put left fork
     put fork((i+1)%N);
                                 // put right fork
```

A *non*solution to the dining philosophers problem

If all philosophers take their left fork simultaneously, none will be able to take the right fork. All philosophers get stuck. Deadlock situation.



Classical IPC Problems

The Readers and Writers Problem

An artificial shared database access problem by Courtois et. al. 1971

Database system

such as an airline reservation system.

 Many competing processes wish to read and write Many reading processes is not the problem, but if one process wants to write, no other process may have access - not even readers.

How to program the readers and writers?

- Writer waits until all readers are gone Not good. Usually there are always readers present. Indefinite wait.
- Writer blocks new readers A solution. Writer waits until old readers are gone and meanwhile blocks new readers

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis



IPC

Classical IPC Problems

The sleeping barber problem

An artificial queuing situation problem



IPC

barber sleeps when no customers are present

customer chairs




Figure from [Ta01 p.130]

IPC

The barber shop has one barber, one barber chair, and *n* chairs for customers, if any, to sit on. If there are no customers present, the barber sits down in the barber chair and falls asleep. When a customer arrives, he has to wake up the sleeping barber. If additional customers arrive while the barber is cutting a customer's hair, they either sit down (if there are empty chairs) or leave the shop (if all chairs are full). Text from [Ta01 p.129]

How to program the barber and the customers without getting into race conditions?

```
const int CHAIRS=5;
                           // number of chairs
typdef int semaphore;
semaphore customers = 0;
                          // number of customers waiting
                          // number of barbers waiting
semaphore barbers = 0;
semaphore mutex = 1;
                           // for mutual exclusion
int waiting = 0;
```

Computer Architecture WS 06/07 Dr.-Ing. Stefan Freinatis

```
void barber() {
                                 // barber process
   while (TRUE) {
                                 // for the whole life
                                                                    IPC
     down(&customers);
                                 // sleep if no customers
     down (&mutex);
                                // acquire access to 'waiting'
     waiting--;
     up(&barbers);
                                 // one barber ready to cut
     up(&mutex);
                                 // release 'waiting'
                                 // cut hair (non critical)
     cut hair();
   }
}
         A solution to the sleeping barber problem [Ta01 p.131]
void customer() {
                                 // customer process
  down (&mutex);
                                 // enter critical region
  if (waiting < CHAIRS) {
                                // when seats available
   waiting++;
                                 // one more waiting
                                 // tell barber if first customer
    up(&customers);
   up(&mutex);
                                // release 'waiting'
                                // sleep if no barber available
    down(&barbers);
                                // get serviced
    get haircut();
  } else up(&mutex);
                                 // shop is full, leave
```

