

Annual Review

Michalis Panayides

2022-06-21

Motivation

Patients forced to wait for 24 hours in ambulances, data shows

Ambulance crews forced to wait outside A&Es for 24 hours, according to chiefs

Rebecca Thomas Health Correspondent • Tuesday 17 May 2022 08:26 • Comments



(AFP/Getty)

'Appalling' waits for ambulances in England leaving lives at risk

Exclusive: Royal College of Emergency Medicine president says NHS is breaking its agreement to treat sickest in a timely way
The staff, this is heart-breaking - senior doctor's view on crisis
I feel we let down long waits for ambulances on the south-west



Ambulance handover delays highest since start of winter
© iStockphoto.com




NHS 'on its knees' as ambulance response times for life-threatening calls rise to record high

Average response time to deal with Category 1 cases – such as cardiac arrest – is now nine minutes and 20 seconds, with rises across all categories.



© The Independent. All rights reserved. This content may not be published, reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system.



Queues - Custom network of queues





Parameters:

- ▶ λ_1 : Arrival rate of type 1 individuals
- ▶ λ_2 : Arrival rate of type 2 individuals
- ▶ μ : Service rate
- ▶ C : Number of servers
- ▶ T : Threshold



Markov Chain - Custom network





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$





Markov Chain - Custom network - $N = 4, M = 2$



Markov Chain - Custom network - $N = 4, M = 2$



Markov Chain - Custom network - $N = 4, M = 2$



Game - Motivation




Game - Players, Strategies and Objectives




$$p_A, p_B \in [0, 1]$$
$$p_A + p_B = 1$$

$\min B$



$$T_A \in [1, N_A]$$

$$P(W^{(A)} < t) > 0.95$$




$$T_B \in [1, N_B]$$


$$P(W^{(B)} < t) > 0.95$$

Game - Formulation





Blocking time



Proportion of individuals within target



Game - Results



Reinforcement Learning - Server's behaviour



1



2



2




3

Utility


Idle time + Lost inds

Reinforcement Learning - Server's behaviour when flooding

Utilities of all servers over all iterations



Weighted mean rates of all servers over all iterations



Thesis structure

1. Introduction
2. Literature review
3. Queueing model
4. Game theoretic model
5. Methodology
6. EMS/ED application
7. Agent based extension
8. Results
9. Conclusion

Timeline

- ▶ Final revision for paper publication
- ▶ Simulated Annealing version of reinforcement learning algorithm
- ▶ Get some more results
- ▶ Thesis write-up