

Abstract interpretation with bounded numeric intervals

Second assignment of the Software Verification
course, A.Y. 2022/2023

Christian Micheletti
November 5, 2023



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

- 1 The Language
 - Arithmetic Expressions
 - Boolean Expressions
- 2 Abstract Interpreter
 - Abstract States
 - Abstract Semantics of Statements
- 3 Implementation
 - The Interval Domain
- 4 Introduction
- 5 First section

The language is a variation of the While language seen in class. It differs on:

- it admits some syntactic sugar (it's not minimal);
- its semantic functions are modified to allow divergence and state changes in both arithmetic and boolean expressions.

$$\begin{aligned} AExp ::= & n \mid x \mid -e \mid (e) \\ & \mid e_1 + e_2 \mid e_1 - e_2 \mid e_1 * e_2 \mid e_1 / e_2 \\ & \mid x++ \mid ++x \mid x-- \mid --x \end{aligned}$$

$$\mathcal{A} : AExp \rightarrow State \hookrightarrow \mathbb{Z} \times State$$

$$\mathcal{A}[[n]]\varphi = (n_{\mathbb{Z}}, \varphi)$$

$$\mathcal{A}[[x]]\varphi = (\varphi(x), \varphi)$$

$$\mathcal{A}[[e]]\varphi = \mathcal{A}[[e]]\varphi$$

$$\mathcal{A}[-e]\varphi = \begin{cases} (-a, \varphi') & \mathcal{A}[[e]]\varphi = (a, \varphi') \\ \uparrow & (\mathcal{A}[[e]]\varphi) \uparrow \end{cases}$$

$\mathcal{A} : AExp \rightarrow State \hookrightarrow \mathbb{Z} \times State$

$$\mathcal{A}[\![e_1/e_2]\!] \varphi = \begin{cases} (a_1 \div a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ & \wedge a_2 \neq 0 \\ \uparrow & \text{otherwise} \end{cases}$$
$$\mathcal{A}[\![e_1 \text{ op } e_2]\!] \varphi = \begin{cases} (a_1 \text{ op } a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ \uparrow & \text{otherwise} \end{cases}$$

$\mathcal{A} : AExp \rightarrow State \hookrightarrow \mathbb{Z} \times State$

$$\mathcal{A}[\![x++]\!] \varphi = (\varphi(x), \varphi[x \mapsto x + 1])$$

$$\begin{aligned} \mathcal{A}[\![++x]\!] \varphi = & \text{let } \varphi' = \varphi[x \mapsto x + 1] \\ & \text{in } (\varphi'(x), \varphi') \end{aligned}$$

$$\mathcal{A}[\![x--]\!] \varphi = (\varphi(x), \varphi[x \mapsto x - 1])$$

$$\begin{aligned} \mathcal{A}[\![--x]\!] \varphi = & \text{let } \varphi' = \varphi[x \mapsto x - 1] \\ & \text{in } (\varphi'(x), \varphi') \end{aligned}$$

$$\begin{aligned} BExp ::= & \text{true} \mid \text{false} \mid (b) \mid b_1 \text{ and } b_2 \mid b_1 \text{ or } b_2 \\ & \mid e_1 = e_2 \mid e_1 \neq e_2 \mid e_1 < e_2 \mid e_1 \geq e_2 \end{aligned}$$

$\mathcal{B} : BExp \rightarrow State \hookrightarrow \mathbb{T} \times State$

$$\mathcal{B}[\text{true}]\varphi = (\mathbf{tt}, \varphi)$$

$$\mathcal{B}[\text{false}]\varphi = (\mathbf{ff}, \varphi)$$

$$\mathcal{B}[(b)]\varphi = \mathcal{B}[b]\varphi$$

Operators between booleans short circuits results:

$$\mathcal{B} : BExp \rightarrow State \hookrightarrow \mathbb{T} \times State$$

$$\mathcal{B}[[b_1 \text{ and } b_2]]\varphi = \begin{cases} (\mathbf{ff}, \varphi') & \mathcal{B}[[b_1]]\varphi = (\mathbf{ff}, \varphi') \\ \mathcal{B}[[b_2]]\varphi' & \mathcal{B}[[b_1]]\varphi = (\mathbf{tt}, \varphi') \\ \uparrow & \text{otherwise} \end{cases}$$

$$\mathcal{B}[[b_1 \text{ or } b_2]]\varphi = \begin{cases} (\mathbf{tt}, \varphi') & \mathcal{B}[[b_1]]\varphi = (\mathbf{tt}, \varphi') \\ \mathcal{B}[[b_2]]\varphi' & \mathcal{B}[[b_1]]\varphi = (\mathbf{ff}, \varphi') \\ \uparrow & \text{otherwise} \end{cases}$$

Comparison operations propagate updates in the state:

$$\mathcal{B} : BExp \rightarrow State \hookrightarrow \mathbb{T} \times State$$

$$\mathcal{B}[\![e_1 = e_2]\!] \varphi = \begin{cases} (a_1 = a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ \uparrow & \text{otherwise} \end{cases}$$

$$\mathcal{B}[\![e_1 < e_2]\!] \varphi = \begin{cases} (a_1 < a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ \uparrow & \text{otherwise} \end{cases}$$

$\mathcal{B} : BExp \rightarrow State \hookrightarrow \mathbb{T} \times State$

$$\mathcal{B}[\![e_1 \neq e_2]\!] \varphi = \begin{cases} (a_1 \neq a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ \uparrow & \text{otherwise} \end{cases}$$

$$\mathcal{B}[\![e_1 \geq e_2]\!] \varphi = \begin{cases} (a_1 \geq a_2, \varphi'') & \mathcal{A}[\![e_1]\!] \varphi = (a_1, \varphi') \\ & \wedge \mathcal{A}[\![e_2]\!] \varphi' = (a_2, \varphi'') \\ \uparrow & \text{otherwise} \end{cases}$$

Negation is expressed by syntactic sugar:

$$\text{not true} \stackrel{\text{def}}{=} \text{false}$$

$$\text{not false} \stackrel{\text{def}}{=} \text{true}$$

$$\text{not } (b_1 \text{ and } b_2) \stackrel{\text{def}}{=} \text{not } b_1 \text{ or not } b_2$$

$$\text{not } (b_1 \text{ or } b_2) \stackrel{\text{def}}{=} \text{not } b_1 \text{ and not } b_2$$

$$\text{not } e_1 = e_2 \stackrel{\text{def}}{=} e_1 \neq e_2$$

$$\text{not } e_1 < e_2 \stackrel{\text{def}}{=} e_1 \geq e_2$$

$$\text{not } e_1 \neq e_2 \stackrel{\text{def}}{=} e_1 = e_2$$

$$\text{not } e_1 \geq e_2 \stackrel{\text{def}}{=} e_1 < e_2$$

Also other arithmetic comparisons are expressed with syntactic sugar:

$$e_1 > e_2 \stackrel{\text{def}}{=} e_2 < e_1$$
$$e_1 <= e_2 \stackrel{\text{def}}{=} e_2 >= e_1$$

While ::= $x := e$ | skip | $\{S\}$ | $S_1 ; S_2$
| if b then S_1 else S_2 | while b do S

$\mathcal{S}_{ds} : \text{While} \rightarrow \text{State} \hookrightarrow \text{State}$

$$\mathcal{S}_{ds}[[x := e]]\varphi = \begin{cases} \varphi'[x \mapsto a] & \mathcal{A}[[e]]\varphi = (a, \varphi') \\ \uparrow & \text{otherwise} \end{cases}$$

$$\mathcal{S}_{ds}[[\text{skip}]]\varphi = \varphi$$

$$\mathcal{S}_{ds}[[\{S\}]]\varphi = \mathcal{S}_{ds}[[S]]\varphi$$

$\mathcal{S}_{ds} : \text{While} \rightarrow \text{State} \hookrightarrow \text{State}$

$$\mathcal{S}_{ds} \llbracket S_1 ; S_2 \rrbracket \varphi = (\mathcal{S}_{ds} \llbracket S_2 \rrbracket \circ \mathcal{S}_{ds} \llbracket S_1 \rrbracket) \varphi$$

$$\mathcal{S}_{ds} \llbracket \text{if } b \text{ then } S_1 \text{ else } S_2 \rrbracket \varphi = \text{cond}(\mathcal{B} \llbracket b \rrbracket, \mathcal{S}_{ds} \llbracket S_1 \rrbracket, \mathcal{S}_{ds} \llbracket S_2 \rrbracket)$$

$$\mathcal{S}_{ds} \llbracket \text{while } b \text{ do } S \rrbracket \varphi = \text{FIX}(\lambda g. \text{cond}(\mathcal{B} \llbracket b \rrbracket, g \circ \mathcal{S}_{ds} \llbracket S \rrbracket, \text{id}))$$

Where

$$\text{cond}(\text{pred}, g_1, g_2) = \begin{cases} g_1(\varphi') & \text{pred}(\varphi) = (\mathbf{tt}, \varphi') \\ g_2(\varphi') & \text{pred}(\varphi) = (\mathbf{ff}, \varphi') \\ \uparrow & \text{otherwise} \end{cases}$$

We define for any abstract domain A , which is a complete lattice as well, the abstract state type $\mathbb{S}_A = \text{Map}(\text{Var}, A)$.

Assumption

The absence of a variable in the abstract state is interpreted as \top_A . This is due to the fact that we assume that all referenced variables in the program are initialized.

Moreover, $\perp_{\mathbb{S}_A}$ represents an abnormal termination (no update operation can be performed over this state):

$$s(x) = \begin{cases} a & (x, a) \in s \\ \top_A & \text{otherwise} \end{cases}$$
$$s[x \mapsto a] = \begin{cases} \perp_{\mathbb{S}_A} & s = \perp_{\mathbb{S}_A} \\ \{(k, v) \mid (k, v) \in s, k \neq x\} & a \neq \top_A, s \neq \perp_{\mathbb{S}_A} \\ \{(k, v) \mid (k, v) \in s, k \neq x\} & \text{otherwise} \end{cases}$$

\mathbb{S}_A is partially ordered

$$s_1 \leq s_2 \iff s_1(x) \leq s_2(x) \quad \forall x \in \text{Var}$$

\mathbb{S}_A is a complete lattice

$$\perp_{\mathbb{S}_A} = \{(x, \perp_A) \mid x \in \text{Var}\}$$

$$\top_{\mathbb{S}_A} = \emptyset$$

$$s_1 \vee_{\mathbb{S}_A} s_2 = \{(var, a_1 \vee_A a_2) \mid (var, a_1) \in s_1, (var, a_2) \in s_2\}$$

$$s_1 \wedge_{\mathbb{S}_A} s_2 = \{(var, a_1 \wedge_A a_2) \mid (var, a_1) \in s_1, (var, a_2) \in s_2\} \\ \cup \{e \mid e \in s_1, e \notin s_2\} \cup \{e \mid e \notin s_1, e \in s_2\}$$

The abstract semantic functions are:

- $\mathcal{A}^\sharp : AExp \rightarrow \mathbb{S}_A \rightarrow A \times \mathbb{S}_A$:
 - the first element of the tuple approximates the result returned by arithmetic expression;
 - the second element approximates the state after the transition induced by the expression;
- $\mathcal{B}^\sharp : BExp \rightarrow \mathbb{S}_A \rightarrow (\mathbb{S}_A \times \mathbb{S}_A)$:
 - the first element of the tuple approximates the states where the boolean expression would evaluate **tt**;
 - the second element approximates the states where the negation of the boolean expression would evaluate **tt**.
- $\mathcal{D}^\sharp : While \rightarrow \mathbb{S}_A \rightarrow \mathbb{S}_A$.

$\mathcal{D}^\# : While \rightarrow \mathbb{S}_A \rightarrow \mathbb{S}_A$

$$\mathcal{D}^\# \llbracket x := e \rrbracket s^\# \stackrel{\text{def}}{=} \begin{cases} s'^\# [x \mapsto a] & (a, s'^\#) = \mathcal{A}^\# \llbracket e \rrbracket s^\# \\ & \wedge a \neq \perp_A \\ \perp_{\mathbb{S}_A} & \text{otherwise} \end{cases}$$

The Interval Domain (1)



$$I_{m,n} \subset \wp(\mathbb{Z}) \text{ with } m, n \in \mathbb{Z} \cup -\infty, \infty$$

$$\begin{aligned} I_{m,n} = & \{\mathbb{Z}, \emptyset\} \cup \{\{z\} \mid z \in \mathbb{Z}\} \\ & \cup \{\{x \mid w \leq x \leq z\} \mid x, w, z \in \mathbb{Z} \text{ s.t. } m \leq w \leq z \leq n\} \\ & \cup \{\{x \mid x \leq z\} \mid x, z \in \mathbb{Z} \text{ s.t. } m \leq z \leq n\} \\ & \cup \{\{x \mid x \geq z\} \mid x, z \in \mathbb{Z} \text{ s.t. } m \leq z \leq n\} \end{aligned}$$

The Interval Domain (2)



$I_{m,n}$ is partially ordered

$$i_1 \leq i_2 \iff i_1 \subseteq i_2$$

$I_{m,n}$ is a complete lattice

$$\perp_{I_{m,n}} = \emptyset$$

$$\top_{I_{m,n}} = \mathbb{Z}$$

$$\vee_{I_{m,n}} = \cup$$

$$\wedge_{I_{m,n}} = \cap$$

Etiam eu interdum ligula

Nunc mi eros, vulputate in ornare a, viverra eget quam

- Morbi **vitae lacus** porta neque tincidunt sodales
- Proin tincidunt, **neque** at tincidunt mollis
- Ut **lacinia sem a nibh** consequat porttitor

Normal block

Fusce luctus venenatis felis quis semper

Alert block

$$E = (x_1 \vee \neg x_2 \vee \neg x_3) \wedge (x_1 \vee x_2 \vee x_4)$$

Example block

Proin tincidunt, neque at tincidunt mollis