Scaling LLM Test-Time Compute Optimally can be More Effective than Scaling Model Parameters

Allocating inference compute under a fixed budget

Zhenbang Lyu

Heidelberg University
Institute of Computer Science

Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar
2024, arXiv:2408.03314v1

Can Language Models Benefit from More Thinking?

Humans often think for longer about difficult problems to reach better answers and improve their decisions.

Extra thought gives us time to reconsider an initial answer and work through the reasoning more carefully.

Can language models also improve their answers by using more computation at test time?

The paper studies how a trained model can use an additional inference budget on a challenging question.

How Do We Work through a Math Problem?

Suppose we want a better chance of finding the correct answer to a math problem.

- **Ask several people to solve it independently.** Collect their complete solutions, then compare the answers.
- **Build on an existing attempt.** Read someone else's working and use it to develop an improved solution.
- **Ask for feedback before we finished the question.** Show someone our unfinished reasoning before deciding how to continue.

A model can also try independently, revise earlier work, or use feedback during generation.

Two Directions for Using Extra Computation

Baseline Generate N independent solutions, then select an answer with a verifier: **best-of-N**.


The paper improves on this baseline in two directions.

- **Change what the model generates.** Give it earlier answers and ask for a revised solution. **Revisions** change its **proposal distribution**.
- **Change how feedback guides generation.** Score partial solutions and choose which paths to develop. This is **verifier-guided search**.

We first follow the verifier-guided search route from intermediate steps to a final answer.

PRM-Guided Search from Steps to an Answer

Score partial solutions and stop low-scoring branches before they become complete answers.




Repeat until completion or the expansion limit. Three decisions remain:

1. Who scores the reasoning?
2. How do we select the final answer?
3. Which candidates should the search retain and expand?

Who Can Score the Reasoning?

Train a **process reward model (PRM)** to predict the chance of finishing correctly from a given prefix.



Illustrative training rollouts. Dashed paths are possible futures.

During search, the trained PRM **scores new prefixes directly**.

How Do We Select the Final Answer?

Use the PRM's **last-step score** for each complete solution, then sum scores for matching final answers.


Example candidate	Final answer	Last-step score
Y_1	$x = 2$	0.60
Y_2	$x = 2$	0.55
Y_3	$x = 3$	0.90

$$\text{score}(x = 2) = 1.15, \qquad \text{score}(x = 3) = 0.90$$

Weighted best-of-N selects $x = 2$.

Standard best-of-N would pick the single highest-scoring candidate. Majority voting counts answers without weights.

Which Candidates Should We Develop?




Best-of-N Generate independent complete solutions, then select.
Beam search Score prefixes, keep the top candidates, then expand.
Lookahead Temporarily continue k steps before scoring a prefix.

Lookahead spends additional compute on its temporary continuations.

Beam Search Helps Most at Low Budgets

PaLM 2-S* on MATH: 12,000 training questions and 500 test questions.




Beam search is strongest at low budgets, but its advantage shrinks as compute increases.

At matched cost, extra lookahead usually gives less benefit.

Difficulty Changes Which Search Strategy Wins

Each difficulty bin has four budgets, left to right: **4, 16, 64, 256**.



Read the top of each color. The bars overlap.

Example, bin 2: beam wins at budget 4.
Best-of-N wins at 256.

Easy questions (bins 1–2)

Beam search can win at small budgets, then stall or decline. Best-of-N catches up.

Medium difficulty (bins 3–4)


Beam search consistently beats best-of-N at the same budget.

Hardest questions (bin 5)

All three methods make little progress.

Choose the search setting using both difficulty and budget.

Less Compute Can Reach Similar Accuracy



The compute used to estimate difficulty is not included.

Choosing the search setting by difficulty can reach similar accuracy with less compute.


Oracle at 16 generations: almost the same accuracy as PRM best-of-N weighted at 64.

Predicted at 16 generations: also close to the same 64-generation baseline.


Revising Answers and Selecting the Output

A fine-tuned revision model uses earlier answer to write a new answer.

1 Generate Each call sees the question and up to four most recent answers.





2 Select Use ORM weighted selection within each chain, then across chains.



A later revision can undo a correct answer, so select from the saved history.

Revision Quality and Final Answer Accuracy





Four chains per question.

Average correctness at the same round.

No voting or ORM selection.

Most improvement happens in early rounds.

Sequential: N answers in one chain.


Parallel: N independent answers.


Majority or ORM-weighted voting.

Sequential is slightly better with either selector.

The Best Mix Depends on Difficulty and Budget

Both figures: ORM weighted selection within each chain, then across chains.






Left: each line fixes the total budget.


At high budgets, a mix can beat both extremes.

Right: 128 answers, grouped by difficulty.

Easy questions favor longer chains; harder ones often need more starts.



Adaptive Revisions Use the Generation Budget More Efficiently



The reported saving excludes difficulty-estimation cost.

Adaptive revisions keep improving after parallel sampling begins to plateau.

64 candidates can beat parallel best-of-N with 256 candidates.

Both oracle and predicted difficulty improve the allocation.

Pretraining and Inference at Equal Total FLOPs

Extra inference improves the small model. How does it compare with training a larger model?

Hold training tokens fixed and increase parameters by a factor M.

$$X \approx 6PD_{\text{pretrain}}, \qquad Y \approx 2PD_{\text{inference}}$$

P is the parameter count. $D_{\text{inference}}$ is the total inference token workload.

$$\underbrace{X + aY}_{\text{small model, extra inference}} = \underbrace{M(X + Y)}_{\text{large model, greedy decoding}}$$

The larger model costs more both to train and to run. The small model can spend its training savings on inference.

Using R to Compare Total Compute

R is the inference-to-pretraining token ratio used in the cost comparison:

$$R = \frac{D_{\text{inference}}}{D_{\text{pretrain}}}.$$


From $X + aY = M(X + Y)$, the small model's inference multiplier is

$$\begin{aligned} a &= M + (M-1)\frac{X}{Y} \\ &= M + (M-1)\frac{6PD_{\text{pretrain}}}{2PD_{\text{inference}}} \\ &= M + 3(M-1)\frac{D_{\text{pretrain}}}{D_{\text{inference}}} = M + \frac{3(M-1)}{R}. \end{aligned}$$

R determines which value of a matches the larger model's total cost.

The accuracy curve measures capability. This equation identifies the equal-cost comparison point.

Extra Inference Can Beat a Larger Model in Some Settings



- Extra inference often wins on easy or medium questions, especially when expected inference use is low.
- A larger model is often better on very hard questions or when expected inference use is high.

The comparison depends on both difficulty and the expected inference workload.

Conclusions

- **PRM search.** Beam search works better on harder questions and at low budgets. Best-of-N often wins on easier questions or at high budgets.
- **Revisions.** Easy questions favor longer chains. Harder questions often need a mix of sequential revisions and independent starts.
- **Allocation by difficulty and budget.** Search nearly matches best-of-N with **16 vs. 64** generations. Revisions can beat it with **64 vs. 256**.
- **Training versus inference.** At equal total FLOPs, extra inference can beat a model with $\sim$**14**$\times$ **more parameters**. Very hard questions or a high inference workload often favor pretraining.

Generation budgets exclude difficulty-estimation compute.

Thank you

Questions and Discussion

Backup: Constructing Revision Training Data

Build a training pair

- Sample 64 independent answers to one question.
- Choose a correct answer as the target.
- Add 0–4 related incorrect answers as context.
- Prefer close pairs using character edit distance.

An illustrative pair

Question: solve $2x + 3 = 7$.

Incorrect reference

$$2x = 4, \qquad x = 4$$

Correct target

$$2x = 4, \qquad x = 2$$

The target keeps the valid setup and fixes the final calculation.


Fine-tune on **question + incorrect references** as input, with the **correct solution** as the target.

Backup: Why the Last Revision Can Be Wrong

Training history Incorrect references, followed by a correct target.

Inference history Generated references can already be correct.

A possible revision chain, illustrated on $2x + 3 = 7$:



About 38% of correct answers became incorrect under the authors' naive revision approach.

Selecting from the history gives the system a chance to recover an earlier correct answer.

Backup: A Complete Beam-Search Example

Suppose each round maintains $N = 6$ candidates and each retained prefix gets $M = 2$ continuations.

1. Generate 6 possible first steps and score their prefixes with the PRM.
2. Keep the top $N/M = 3$ prefixes.
3. Extend each twice, giving $3 \times 2 = 6$ candidates for the next round.
4. Repeat scoring and expansion until completion or 40 rounds.
5. Apply weighted best-of-N to the final candidates and return one answer.

The base model proposes, the PRM scores, search allocates effort, and final selection chooses the output.

Backup: Difficulty Estimation and Policy Selection

Test this idea with **PaLM 2-S* (Codey)** on **MATH**: 12,000 training questions and 500 test questions.

1. Estimate difficulty from 2,048 independent samples per question.
2. Sort questions into five equal-frequency bins, from easy to hard.
3. For each bin and budget, select a setting on one fold and evaluate on the other. Swap folds and average.

Oracle bins Rank by actual correctness rate.
Predicted bins Rank by the verifier's mean final-answer score.

Reported budgets exclude difficulty-estimation cost.