



K Means Clustering Project

For this project we will attempt to use KMeans Clustering to cluster Universities into two groups, Private and Public.

It is **very important to note**, we actually have the labels for this data set, but we will **NOT** use them for the KMeans clustering algorithm, since that is an unsupervised learning algorithm.

When using the Kmeans algorithm under normal circumstances, it is because you don't have labels. In this case we will use the labels to try to get an idea of how well the algorithm performed, but you won't usually do this for Kmeans, so the classification report and confusion matrix at the end of this project, don't truly make sense in a real world setting!.

The Data

We will use a data frame with 777 observations on the following 18 variables.

- Private A factor with levels No and Yes indicating private or public university
- Apps Number of applications received
- Accept Number of applications accepted
- Enroll Number of new students enrolled
- Top10perc Pct. new students from top 10% of H.S. class
- Top25perc Pct. new students from top 25% of H.S. class
- F.Undergrad Number of fulltime undergraduates
- P.Undergrad Number of parttime undergraduates
- Outstate Out-of-state tuition
- Room.Board Room and board costs
- Books Estimated book costs
- Personal Estimated personal spending
- PhD Pct. of faculty with Ph.D.'s
- Terminal Pct. of faculty with terminal degree
- S.F.Ratio Student/faculty ratio
- perc.alumni Pct. alumni who donate
- Expend Instructional expenditure per student
- Grad.Rate Graduation rate

Import Libraries

Import the libraries you usually use for data analysis.

```
In [2]: import pandas as pd
import numpy as np
```

```
In [4]: import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
```

Get the Data

Read in the College_Data file using read_csv. Figure out how to set the first column as the index.

```
In [6]: df = pd.read_csv('College_Data', index_col=0)
```

Check the head of the data

```
In [7]: df.head()
```

Out[7]:	Private	Apps	Accept	Enroll	Top10perc	Top25perc	F.Undergrad	P.Undergrad	Outstate	Room.Board	Books	Personal	PhD	1
Abilene Christian University	Yes	1660	1232	721	23	52	2885	537	7440	3300	450	2200	70	
Adelphi University	Yes	2186	1924	512	16	29	2683	1227	12280	6450	750	1500	29	
Adrian College	Yes	1428	1097	336	22	50	1036	99	11250	3750	400	1165	53	
Agnes Scott College	Yes	417	349	137	60	89	510	63	12960	5450	450	875	92	
Alaska Pacific University	Yes	193	146	55	16	44	249	869	7560	4120	800	1500	76	

Check the info() and describe() methods on the data.

```
In [8]: df.info()

<class 'pandas.core.frame.DataFrame'>
Index: 777 entries, Abilene Christian University to York College of Pennsylvania
Data columns (total 18 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Private                777 non-null    object
1   Apps                   777 non-null    int64
2   Accept                 777 non-null    int64
3   Enroll                 777 non-null    int64
4   Top10perc              777 non-null    int64
5   Top25perc              777 non-null    int64
6   F.Undergrad            777 non-null    int64
7   P.Undergrad            777 non-null    int64
8   Outstate               777 non-null    int64
9   Room.Board             777 non-null    int64
10  Books                  777 non-null    int64
11  Personal               777 non-null    int64
12  PhD                    777 non-null    int64
13  Terminal               777 non-null    int64
14  S.F.Ratio              777 non-null    float64
15  perc.alumni            777 non-null    int64
16  Expend                 777 non-null    int64
17  Grad.Rate              777 non-null    int64
dtypes: float64(1), int64(16), object(1)
memory usage: 115.3+ KB
```

```
In [9]: df.describe()

Out[9]:
```

	Apps	Accept	Enroll	Top10perc	Top25perc	F.Undergrad	P.Undergrad	Outstate	Room.Board	Books
count	777.000000	777.000000	777.000000	777.000000	777.000000	777.000000	777.000000	777.000000	777.000000	777.000000
mean	3001.638353	2018.804376	779.972973	27.558559	55.796654	3699.907336	855.298584	10440.669241	4357.526384	549.380953
std	3870.201484	2451.113971	929.176190	17.640364	19.804778	4850.420531	1522.431887	4023.016484	1096.696416	165.105361
min	81.000000	72.000000	35.000000	1.000000	9.000000	139.000000	1.000000	2340.000000	1780.000000	96.000000
25%	776.000000	604.000000	242.000000	15.000000	41.000000	992.000000	95.000000	7320.000000	3597.000000	470.000000
50%	1558.000000	1110.000000	434.000000	23.000000	54.000000	1707.000000	353.000000	9990.000000	4200.000000	500.000000
75%	3624.000000	2424.000000	902.000000	35.000000	69.000000	4005.000000	967.000000	12925.000000	5050.000000	600.000000
max	48094.000000	26330.000000	6392.000000	96.000000	100.000000	31643.000000	21836.000000	21700.000000	8124.000000	2340.000000

EDA


It's time to create some data visualizations!

Create a scatterplot of Grad.Rate versus Room.Board where the points are colored by the Private column.

```
In [13]: sns.lmplot(x='Room.Board',y='Grad.Rate',data=df,hue='Private',fit_reg=False,
                palette='coolwarm',size=6,aspect=1)

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\regression.py:581: UserWarning: The `size` parameter has been renamed to `height`; please update your code.
  warnings.warn(msg, UserWarning)

Out[13]: <seaborn.axisgrid.FacetGrid at 0x288e10293a0>
```




Create a scatterplot of F.Undergrad versus Outstate where the points are colored by the Private column.

```
In [15]: sns.lmplot(x='Outstate',y='F.Undergrad',data=df,hue='Private',fit_reg=False,
                  size=6,aspect=1)
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\regression.py:581: UserWarning: The `size` parameter has been renamed to `height`; please update your code.
warnings.warn(msg, UserWarning)


```
Out[15]: <seaborn.axisgrid.FacetGrid at 0x288e1536cd0>
```



Create a stacked histogram showing Out of State Tuition based on the Private column. Try doing this using `sns.FacetGrid`. If that is too tricky, see if you can do it just by using two instances of `pandas.plot(kind='hist')`.

```
In [17]: g = sns.FacetGrid(df, hue='Private', palette='coolwarm', size=6, aspect=2)
g = g.map(plt.hist, 'Outstate', bins=20, alpha=0.7)
```


C:\ProgramData\Anaconda3\lib\site-packages\seaborn\axisgrid.py:337: UserWarning: The `size` parameter has been renamed to `height`; please update your code.
warnings.warn(msg, UserWarning)



Create a similar histogram for the Grad.Rate column.

```
In [18]: g = sns.FacetGrid(df,hue='Private',palette='coolwarm',size=6,aspect=2)
g = g.map(plt.hist,'Grad.Rate',bins=20,alpha=0.7)
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\axisgrid.py:337: UserWarning: The `size` parameter has been renamed to `height`; please update your code.
warnings.warn(msg, UserWarning)



Notice how there seems to be a private school with a graduation rate of higher than 100%.What is the name of that school?

```
In [19]: df[df['Grad.Rate']>100]
```

#The name is Cazenovia College

```
Out[19]:
```

	Private	Apps	Accept	Enroll	Top10perc	Top25perc	F.Undergrad	P.Undergrad	Outstate	Room.Board	Books	Personal	PhD
Cazenovia College	Yes	3847	3433	527	9	35	1010	12	9384	4840	600	500	22

Set that school's graduation rate to 100 so it makes sense. You may get a warning not an error) when doing this operation, so use dataframe operations or just re-do the histogram visualization to make sure it actually went through.

```
In [20]: # To do this operation we do;
df['Grad.Rate']['Cazenovia College'] = 100
```

```
C:\Users\17737\AppData\Local\Temp\ipykernel_27700\1003957697.py:2: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame
```

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy

```
df['Grad.Rate']['Cazenovia College'] = 100
```

```
In [21]: #Let's see if we fixed it
```


```
df[df['Grad.Rate']>100]
```

```
Out[21]: Private  Apps  Accept  Enroll  Top10perc  Top25perc  F.Undergrad  P.Undergrad  Outstate  Room.Board  Books  Personal  PhD  Terminal
```

```
In [22]: g = sns.FacetGrid(df,hue='Private',palette='coolwarm',size=6,aspect=2)
g = g.map(plt.hist,'Grad.Rate',bins=20,alpha=0.7)
```

```
#Everything is all good
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\axisgrid.py:337: UserWarning: The `size` parameter has been
renamed to `height`; please update your code.
warnings.warn(msg, UserWarning)
```



K Means Cluster Creation

Now it is time to create the Cluster labels!

Import KMeans from SciKit Learn.

```
In [24]: from sklearn.cluster import KMeans
```

Create an instance of a K Means model with 2 clusters.

```
In [25]: kmeans = KMeans(n_clusters=2)
```

Fit the model to all the data except for the Private label.

```
In [27]: kmeans.fit(df.drop('Private',axis=1))
```

```
Out[27]: KMeans(n_clusters=2)
```

What are the cluster center vectors?

```
In [28]: kmeans.cluster_centers_
```

```
Out[28]: array([[1.03631389e+04, 6.55089815e+03, 2.56972222e+03, 4.14907407e+01,
7.02037037e+01, 1.30619352e+04, 2.46486111e+03, 1.07191759e+04,
4.64347222e+03, 5.95212963e+02, 1.71420370e+03, 8.63981481e+01,
9.13333333e+01, 1.40277778e+01, 2.00740741e+01, 1.41705000e+04,
6.75925926e+01],
[1.81323468e+03, 1.28716592e+03, 4.91044843e+02, 2.53094170e+01,
5.34708520e+01, 2.18854858e+03, 5.95458894e+02, 1.03957085e+04,
4.31136472e+03, 5.41982063e+02, 1.28033632e+03, 7.04424514e+01,
7.78251121e+01, 1.40997010e+01, 2.31748879e+01, 8.93204634e+03,
6.50926756e+01]])
```

Evaluation

There is no perfect way to evaluate clustering if you don't have the labels, however since this is just an exercise, we do have the labels, so we take advantage of this to evaluate our clusters, keep in mind, you usually won't have this luxury in the real world.

Create a new column for df called 'Cluster', which is a 1 for a Private school, and a 0 for a public school.

```
In [30]: #Creation of the function below
```

```
def converter(private):
    if private == 'Yes':
        return 1
    else:
        return 0
```

```
In [31]: df['Cluster'] = df['Private'].apply(converter)
```

```
In [33]: #Now our Cluster column is well aligned with our Private column
```

```
df.head()
```

```
Out[33]:
```

	Private	Apps	Accept	Enroll	Top10perc	Top25perc	F.Undergrad	P.Undergrad	Outstate	Room.Board	Books	Personal	PhD	1
Abilene Christian University	Yes	1660	1232	721	23	52	2885	537	7440	3300	450	2200	70	
Adelphi University	Yes	2186	1924	512	16	29	2683	1227	12280	6450	750	1500	29	
Adrian College	Yes	1428	1097	336	22	50	1036	99	11250	3750	400	1165	53	
Agnes Scott College	Yes	417	349	137	60	89	510	63	12960	5450	450	875	92	
Alaska Pacific University	Yes	193	146	55	16	44	249	869	7560	4120	800	1500	76	

Create a confusion matrix and classification report to see how well the Kmeans clustering worked without being given any labels.

```
In [35]: from sklearn.metrics import confusion_matrix, classification_report
```

```
In [37]: print(confusion_matrix(df['Cluster'], kmeans.labels_))
print('\n')
print(classification_report(df['Cluster'], kmeans.labels_))
```

```
[[ 74 138]
 [ 34 531]]
```

	precision	recall	f1-score	support
0	0.69	0.35	0.46	212
1	0.79	0.94	0.86	565
accuracy			0.78	777
macro avg	0.74	0.64	0.66	777
weighted avg	0.76	0.78	0.75	777

Not so bad considering the algorithm is purely using the features to cluster the universities into 2 distinct groups! Hopefully you can begin to see how K Means is useful for clustering un-labeled data!

Great Job!