Principal Component Analysis

In [1]:
```
import matplotlib.pyplot as plt
import pandas as pd
import numpy as np
import seaborn as sns
%matplotlib inline
```

In [2]:
```
from sklearn.datasets import load_breast_cancer
```

In [3]:
```
cancer = load_breast_cancer()
```

In [4]:
```
type(cancer)
```

Out[4]:
```
sklearn.utils.Bunch
```

In [5]:
```
cancer.keys()
```

Out[5]:
```
dict_keys(['data', 'target', 'frame', 'target_names', 'DESCR', 'feature_names', 'filename', 'data_module'])
```

In [6]:
```
print(cancer['DESCR'])
```

```
.. _breast_cancer_dataset:

Breast cancer wisconsin (diagnostic) dataset
--------------------------------------------

**Data Set Characteristics:**

    :Number of Instances: 569

    :Number of Attributes: 30 numeric, predictive attributes and the class

    :Attribute Information:
        - radius (mean of distances from center to points on the perimeter)
        - texture (standard deviation of gray-scale values)
        - perimeter
        - area
        - smoothness (local variation in radius lengths)
        - compactness (perimeter^2 / area - 1.0)
        - concavity (severity of concave portions of the contour)
        - concave points (number of concave portions of the contour)
        - symmetry
        - fractal dimension ("coastline approximation" - 1)

        The mean, standard error, and "worst" or largest (mean of the three
        worst/largest values) of these features were computed for each image,
        resulting in 30 features.  For instance, field 0 is Mean Radius, field
        10 is Radius SE, field 20 is Worst Radius.

        - class:
                - WDBC-Malignant
                - WDBC-Benign

    :Summary Statistics:

    ===================================== ====== ======
                                           Min    Max
    ===================================== ====== ======
    radius (mean):                        6.981  28.11
    texture (mean):                       9.71   39.28
    perimeter (mean):                     43.79  188.5
    area (mean):                          143.5  2501.0
    smoothness (mean):                    0.053  0.163
    compactness (mean):                   0.019  0.345
    concavity (mean):                     0.0    0.427
    concave points (mean):                0.0    0.201
    symmetry (mean):                      0.106  0.304
    fractal dimension (mean):             0.05   0.097
    radius (standard error):              0.112  2.873
    texture (standard error):             0.36   4.885
    perimeter (standard error):           0.757  21.98
    area (standard error):                6.802  542.2
    smoothness (standard error):          0.002  0.031
    compactness (standard error):         0.002  0.135
    concavity (standard error):           0.0    0.396
    concave points (standard error):      0.0    0.053
    symmetry (standard error):            0.008  0.079
    fractal dimension (standard error):   0.001  0.03
    radius (worst):                       7.93   36.04
    texture (worst):                      12.02  49.54
    perimeter (worst):                    50.41  251.2
```

```
    area (worst):                         185.2  4254.0
    smoothness (worst):                   0.071  0.223
    compactness (worst):                  0.027  1.058
    concavity (worst):                    0.0    1.252
    concave points (worst):               0.0    0.291
    symmetry (worst):                     0.156  0.664
    fractal dimension (worst):            0.055  0.208
    ===================================== ====== ======

    :Missing Attribute Values: None

    :Class Distribution: 212 - Malignant, 357 - Benign

    :Creator:  Dr. William H. Wolberg, W. Nick Street, Olvi L. Mangasarian

    :Donor: Nick Street

    :Date: November, 1995

This is a copy of UCI ML Breast Cancer Wisconsin (Diagnostic) datasets.
https://goo.gl/U2Uwz2

Features are computed from a digitized image of a fine needle
aspirate (FNA) of a breast mass.  They describe
characteristics of the cell nuclei present in the image.

Separating plane described above was obtained using
Multisurface Method-Tree (MSM-T) [K. P. Bennett, "Decision Tree
Construction Via Linear Programming." Proceedings of the 4th
Midwest Artificial Intelligence and Cognitive Science Society,
pp. 97-101, 1992], a classification method which uses linear
programming to construct a decision tree.  Relevant features
were selected using an exhaustive search in the space of 1-4
features and 1-3 separating planes.

The actual linear program used to obtain the separating plane
in the 3-dimensional space is that described in:
[K. P. Bennett and O. L. Mangasarian: "Robust Linear
Programming Discrimination of Two Linearly Inseparable Sets",
Optimization Methods and Software 1, 1992, 23-34].

This database is also available through the UW CS ftp server:

ftp ftp.cs.wisc.edu
cd math-prog/cpo-dataset/machine-learn/WDBC/

.. topic:: References

   - W.N. Street, W.H. Wolberg and O.L. Mangasarian. Nuclear feature extraction
     for breast tumor diagnosis. IS&T/SPIE 1993 International Symposium on
     Electronic Imaging: Science and Technology, volume 1905, pages 861-870,
     San Jose, CA, 1993.
   - O.L. Mangasarian, W.N. Street and W.H. Wolberg. Breast cancer diagnosis and
     prognosis via linear programming. Operations Research, 43(4), pages 570-577,
     July-August 1995.
   - W.H. Wolberg, W.N. Street, and O.L. Mangasarian. Machine learning techniques
     to diagnose breast cancer from fine-needle aspirates. Cancer Letters 77 (1994)
     163-171.
```

In [8]:
```
df = pd.DataFrame(cancer['data'],columns=cancer['feature_names'])
```

In [10]:
```
#So it is hard to visualize a high dimensional data especially here where we have
# 30 numeric variables (attributes) hence our data has 30 dimensions.

#So let's use PCA to find the main 2 components and transform it into 2D
```

In [12]:
```
from sklearn.preprocessing import StandardScaler
```

In [13]:
```
scaler = StandardScaler()
```

In [14]:
```
scaler.fit(df)
```

Out[14]:
```
StandardScaler()
```

In [15]:
```
scaled_data = scaler.transform(df)
```

In [16]:
```
#PCA
from sklearn.decomposition import PCA
```

In [17]:
```
pca = PCA(n_components=2)
```

In [18]:
```
pca.fit(scaled_data)
```

Out[18]:
```
PCA(n_components=2)
```

In [19]:
```
x_pca = pca.transform(scaled_data)
```

In [20]:
```
scaled_data.shape
```

Out[20]:
```
(569, 30)
```

In [21]:
```
x_pca.shape
```

Out[21]:
```
(569, 2)
```

In [24]:
```
plt.figure(figsize=(8,6))
plt.scatter(x_pca[:,0],x_pca[:,1],c=cancer['target'])
plt.xlabel('First Principal Component')
plt.ylabel('Second Principal Component')
```

Out[24]:
```
Text(0, 0.5, 'Second Principal Component')
```



In [25]:
```
pca.components_
```

Out[25]:
```
array([[ 0.21890244,  0.10372458,  0.22753729,  0.22099499,  0.14258969,
         0.23928535,  0.25840048,  0.26085376,  0.13816696,  0.06436335,
         0.20597878,  0.01742803,  0.21132592,  0.20286964,  0.01453145,
         0.17039345,  0.15358979,  0.1834174 ,  0.04249842,  0.10256832,
         0.22799663,  0.10446933,  0.23663968,  0.22487053,  0.12795256,
         0.21009588,  0.22876753,  0.25088597,  0.12290456,  0.13178394],
       [-0.23385713, -0.05970609, -0.21518136, -0.23107671,  0.18611302,
         0.15189161,  0.06016536, -0.0347675 ,  0.19034877,  0.36657547,
        -0.10555215,  0.08997968, -0.08945723, -0.15229263,  0.20443045,
         0.2327159 ,  0.19720728,  0.13032156,  0.183848  ,  0.28009203,
        -0.21986638, -0.0454673 , -0.19987843, -0.21935186,  0.17230435,
         0.14359317,  0.09796411, -0.00825724,  0.14188335,  0.27533947]])
```

In [27]:
```
df_comp = pd.DataFrame(pca.components_,columns=cancer['feature_names'])
```

In [29]:
```
plt.figure(figsize=(12,6))
sns.heatmap(df_comp,cmap='plasma')
```

Out[29]:
```
<AxesSubplot:>
```



In [ ]:

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js