



# Support Vector Machines Project

Welcome to your Support Vector Machine Project! Just follow along with the notebook and instructions below. We will be analyzing the famous iris data set!

## The Data

For this series of lectures, we will be using the famous [Iris flower data set](#).

The Iris flower data set or Fisher's Iris data set is a multivariate data set introduced by Sir Ronald Fisher in the 1936 as an example of discriminant analysis.

The data set consists of 50 samples from each of three species of Iris (Iris setosa, Iris virginica and Iris versicolor), so 150 total samples. Four features were measured from each sample: the length and the width of the sepals and petals, in centimeters.

Here's a picture of the three different Iris types:

```
In [1]: # The Iris Setosa
from IPython.display import Image
url = 'http://upload.wikimedia.org/wikipedia/commons/5/56/Kosaciec_szczecinkowaty_Iris_setosa.jpg'
Image(url,width=300, height=300)
```

Out[1]:



```
In [18]: # The Iris Versicolor
from IPython.display import Image
url = 'http://upload.wikimedia.org/wikipedia/commons/4/41/Iris_versicolor_3.jpg'
Image(url,width=300, height=300)
```

Out[18]:



```
In [19]: # The Iris Virginica
from IPython.display import Image
url = 'http://upload.wikimedia.org/wikipedia/commons/9/9f/Iris_virginica.jpg'
Image(url,width=300, height=300)
```

Out[19]:



The iris dataset contains measurements for 150 iris flowers from three different species.

The three classes in the Iris dataset:

```
Iris-setosa (n=50)
Iris-versicolor (n=50)
Iris-virginica (n=50)
```

The four features of the Iris dataset:

```
sepal length in cm
sepal width in cm
petal length in cm
petal width in cm
```

## Get the data

Use seaborn to get the iris data by using: `iris = sns.load_dataset('iris')`

```
In [4]: import seaborn as sns
```

```
In [6]: iris = sns.load_dataset('iris')
```

Let's visualize the data and get you started!

## Exploratory Data Analysis

Time to put your data viz skills to the test! Try to recreate the following plots, make sure to import the libraries you'll need!


Import some libraries you think you'll need.

```
In [8]: import pandas as pd
import numpy as np
%matplotlib inline
```

Create a pairplot of the data set. Which flower species seems to be the most separable?

```
In [11]: sns.pairplot(iris,hue='species',palette='Dark2') #So the setosa class is highly seperable
```

```
Out[11]: <seaborn.axisgrid.PairGrid at 0x25cf6ae4400>
```



Create a kde plot of sepal\_length versus sepal width for setosa species of flower.

```
In [13]: #Let's separate the data frame first.
setosa = iris[iris['species']=='setosa']


#Now all it's good so let's move on to the plot
sns.kdeplot(setosa['sepal_width'],setosa['sepal_length'],cmap='plasma',shade=True,shade_lowest=False)
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\\_decorators.py:36: FutureWarning: Pass the following variable as a keyword arg: y. From version 0.12, the only valid positional argument will be `data`, and passing other arguments without an explicit keyword will result in an error or misinterpretation.

warnings.warn(C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:1718: UserWarning: `shade\_lowest` is now deprecated in favor of `thresh`. Setting `thresh=0.05`, but please update your code.

warnings.warn(msg, UserWarning)

```
Out[13]: <AxesSubplot:xlabel='sepal_width', ylabel='sepal_length'>
```



## Train Test Split

Split your data into a training set and a testing set.

```
In [23]: from sklearn.model_selection import train_test_split
```

```
In [24]: X = iris.drop('species',axis=1)
y = iris['species']

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=42)
```

## Train a Model

Now its time to train a Support Vector Machine Classifier.

Call the SVC() model from sklearn and fit the model to the training data.

```
In [25]: from sklearn.svm import SVC
```

```
In [26]: svc_model = SVC()
```

```
In [27]: svc_model.fit(X_train,y_train)
```

```
Out[27]: SVC()
```

## Model Evaluation

Now get predictions from the model and create a confusion matrix and a classification report.

```
In [28]: predictions = svc_model.predict(X_test)
```

```
In [29]: from sklearn.metrics import classification_report,confusion_matrix
```

```
In [30]: print(confusion_matrix(y_test,predictions)) # Seems that the model is already perfect
```

```
#There are no mislabeled data points
#Still let's check with the Grid Search component(especially because the question asks me)

[[19  0  0]
 [ 0 13  0]
 [ 0  0 13]]
```

```
In [31]: print(classification_report(y_test,predictions))
```

	precision	recall	f1-score	support
setosa	1.00	1.00	1.00	19
versicolor	1.00	1.00	1.00	13
virginica	1.00	1.00	1.00	13
accuracy			1.00	45
macro avg	1.00	1.00	1.00	45
weighted avg	1.00	1.00	1.00	45

Wow! You should have noticed that your model was pretty good! Let's see if we can tune the parameters to try to get even better (unlikely, and you probably would be satisfied with these results in real life because the data set is quite small, but I just want you to practice using GridSearch.

## Gridsearch Practice

**Import GridsearchCV from SciKit Learn.**

```
In [34]: from sklearn.model_selection import GridSearchCV
```

**Create a dictionary called param\_grid and fill out some parameters for C and gamma.**

```
In [35]: param_grid = {'C':[0.1,1,10,100], 'gamma':[1,0.1,0.01,0.001]}
```

**Create a GridSearchCV object and fit it to the training data.**

```
In [36]: grid = GridSearchCV(SVC(),param_grid,verbose=2)
grid.fit(X_train,y_train)
```

```

Fitting 5 folds for each of 16 candidates, totalling 80 fits
[CV] END .....C=0.1, gamma=1; total time= 0.0s
[CV] END .....C=0.1, gamma=1; total time= 0.0s
[CV] END .....C=0.1, gamma=1; total time= 0.0s
[CV] END .....C=0.1, gamma=1; total time= 0.0s
[CV] END .....C=0.1, gamma=1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.1; total time= 0.0s
[CV] END .....C=0.1, gamma=0.01; total time= 0.0s
[CV] END .....C=0.1, gamma=0.01; total time= 0.0s
[CV] END .....C=0.1, gamma=0.01; total time= 0.0s
[CV] END .....C=0.1, gamma=0.01; total time= 0.0s
[CV] END .....C=0.1, gamma=0.01; total time= 0.0s
[CV] END .....C=0.1, gamma=0.001; total time= 0.0s
[CV] END .....C=0.1, gamma=0.001; total time= 0.0s
[CV] END .....C=0.1, gamma=0.001; total time= 0.0s
[CV] END .....C=0.1, gamma=0.001; total time= 0.0s
[CV] END .....C=0.1, gamma=0.001; total time= 0.0s
[CV] END .....C=1, gamma=1; total time= 0.0s
[CV] END .....C=1, gamma=1; total time= 0.0s
[CV] END .....C=1, gamma=1; total time= 0.0s
[CV] END .....C=1, gamma=1; total time= 0.0s
[CV] END .....C=1, gamma=1; total time= 0.0s
[CV] END .....C=1, gamma=0.1; total time= 0.0s
[CV] END .....C=1, gamma=0.1; total time= 0.0s
[CV] END .....C=1, gamma=0.1; total time= 0.0s
[CV] END .....C=1, gamma=0.1; total time= 0.0s
[CV] END .....C=1, gamma=0.1; total time= 0.0s
[CV] END .....C=1, gamma=0.01; total time= 0.0s
[CV] END .....C=1, gamma=0.01; total time= 0.0s
[CV] END .....C=1, gamma=0.01; total time= 0.0s
[CV] END .....C=1, gamma=0.01; total time= 0.0s
[CV] END .....C=1, gamma=0.01; total time= 0.0s
[CV] END .....C=1, gamma=0.001; total time= 0.0s
[CV] END .....C=1, gamma=0.001; total time= 0.0s
[CV] END .....C=1, gamma=0.001; total time= 0.0s
[CV] END .....C=1, gamma=0.001; total time= 0.0s
[CV] END .....C=10, gamma=1; total time= 0.0s
[CV] END .....C=10, gamma=1; total time= 0.0s
[CV] END .....C=10, gamma=1; total time= 0.0s
[CV] END .....C=10, gamma=1; total time= 0.0s
[CV] END .....C=10, gamma=1; total time= 0.0s
[CV] END .....C=10, gamma=0.1; total time= 0.0s
[CV] END .....C=10, gamma=0.1; total time= 0.0s
[CV] END .....C=10, gamma=0.1; total time= 0.0s
[CV] END .....C=10, gamma=0.1; total time= 0.0s
[CV] END .....C=10, gamma=0.1; total time= 0.0s
[CV] END .....C=10, gamma=0.01; total time= 0.0s
[CV] END .....C=10, gamma=0.01; total time= 0.0s
[CV] END .....C=10, gamma=0.01; total time= 0.0s
[CV] END .....C=10, gamma=0.01; total time= 0.0s
[CV] END .....C=10, gamma=0.01; total time= 0.0s
[CV] END .....C=10, gamma=0.001; total time= 0.0s
[CV] END .....C=10, gamma=0.001; total time= 0.0s
[CV] END .....C=10, gamma=0.001; total time= 0.0s
[CV] END .....C=10, gamma=0.001; total time= 0.0s
[CV] END .....C=100, gamma=1; total time= 0.0s
[CV] END .....C=100, gamma=1; total time= 0.0s
[CV] END .....C=100, gamma=1; total time= 0.0s
[CV] END .....C=100, gamma=1; total time= 0.0s
[CV] END .....C=100, gamma=1; total time= 0.0s
[CV] END .....C=100, gamma=0.1; total time= 0.0s
[CV] END .....C=100, gamma=0.1; total time= 0.0s
[CV] END .....C=100, gamma=0.1; total time= 0.0s
[CV] END .....C=100, gamma=0.1; total time= 0.0s
[CV] END .....C=100, gamma=0.1; total time= 0.0s
[CV] END .....C=100, gamma=0.01; total time= 0.0s
[CV] END .....C=100, gamma=0.01; total time= 0.0s
[CV] END .....C=100, gamma=0.01; total time= 0.0s
[CV] END .....C=100, gamma=0.01; total time= 0.0s
[CV] END .....C=100, gamma=0.01; total time= 0.0s
[CV] END .....C=100, gamma=0.001; total time= 0.0s
[CV] END .....C=100, gamma=0.001; total time= 0.0s
[CV] END .....C=100, gamma=0.001; total time= 0.0s
[CV] END .....C=100, gamma=0.001; total time= 0.0s
[CV] END .....C=100, gamma=0.001; total time= 0.0s

```

```

Out[36]: GridSearchCV(estimator=SVC(),
                      param_grid={'C': [0.1, 1, 10, 100],
                                  'gamma': [1, 0.1, 0.01, 0.001]},
                      verbose=2)

```

Now take that grid model and create some predictions using the test set and create classification reports and confusion matrices for them. Were you able to improve?

```
In [37]: grid_predictions= grid.predict(X_test)

In [38]: print(confusion_matrix(y_test,grid_predictions))

[[19  0  0]
 [ 0 13  0]
 [ 0  0 13]]

In [40]: print(classification_report(y_test,grid_predictions))
```

	precision	recall	f1-score	support
setosa	1.00	1.00	1.00	19
versicolor	1.00	1.00	1.00	13
virginica	1.00	1.00	1.00	13
accuracy			1.00	45
macro avg	1.00	1.00	1.00	45
weighted avg	1.00	1.00	1.00	45

You should have done about the same or exactly the same, this makes sense, there is basically just one point that is too noisy to grab, which makes sense, we don't want to have an overfit model that would be able to grab that.

Great Job!