

UNIVERSITÀ DEGLI STUDI DI NAPOLI FEDERICO II  
WEB TECHNOLOGIES — LECTURE 03


# CSS: CASCADING STYLE SHEETS

Luigi Libero Lucio Starace, PhD

[luigiliberolucio.starace@unina.it](mailto:luigiliberolucio.starace@unina.it)

<https://luistar.github.io>

<https://www.docenti.unina.it/luigiliberolucio.starace>



## PREVIOUSLY, ON WEB TECHNOLOGIES

- We have learned how to write HTML documents
- HTML is concerned with **structure** and **semantics** of documents
- HTML is saying nothing at all on the **appearance** of documents
- An **<em>** element specifies that its content should be emphasized
- It's not saying **how** the emphasizing part should be done
  - Emphasis might be conveyed using *italics*, **different colors** or **backgrounds**.

## CSS: CASCADING STYLE SHEETS

- A **rule-based, declarative** language for specifying how documents should be presented to users.
- A **stylesheet** is a set of **Rules**, each defined as follows
- The **selector** specifies which HTML elems are affected by the rule
- Rules contain a set of **declarations**, in the form of **property-value pairs**, which specify the style to apply

```
selector {  
  property: value;  
  property: value;  
}
```

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

3

## CSS: FIRST EXAMPLE

```
<h1>Hello CSS</h1>  
<p>  
  Our <em>first</em> page  
  with <em>style</em>!  
</p>
```

```
h1 {  
  color: red;  
  font-size: 50px;  
}  
  
em {  
  color: blue;  
}
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

4

## DEFAULT USER AGENT STYLES

- But the first web pages we developed have some styling!
  - Headings are bigger and shown with a bold face...
  - `<p>` starts on new lines, `<em>` are displayed in italic, `<strong>` in bold, `<a>` are underlined and blue, `<ul>` have bullets, and so on...
- That's because browsers apply their own, basic styles to every page!
- They are often referred to as **user agent styles**
- These defaults are roughly the same across different browsers, but some **differences** exist (and we'll get back to that!)

## INCLUDING STYLESHEETS IN WEB PAGES

Styling can be included in HTML documents in different ways

- Using `<link>` elements in the `<head>` of the document
  - The `rel="stylesheet"` attribute specifies the relation between the current document and the linked document
  - The `href="style.css"` attrib. specifies the URL of the stylesheet to load
  - Same mechanism as `<img>`: browser will make an additional HTTP request to fetch the stylesheet before rendering the page

```
<head>
  <meta charset="UTF-8">
  <title>CSS</title>
  <link rel="stylesheet" href="style.css">
</head>
```

## INCLUDING STYLESHEETS IN WEB PAGES

- CSS rules can also be defined in `<style>` elements in the `<head>`
- It is generally preferable to use external stylesheets and `<link>`
  - Can you think of some reasons why?

```
<head>
  <meta charset="UTF-8">
  <title>CSS</title>
  <style>
    h1 {
      color: red;
      font-size: 50px;
    }
  </style>
</head>
```

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

7

## STYLING HTML ELEMENTS

- HTML elements can also be styled inline, using the `style` attribute
- The value of the style attribute is a sequence of declarations, separated by «;»
- These styling declarations apply **only to the specific element** bearing the attribute

```
<em style="color: fuchsia; font-weight: bold;">inline style</em>
```

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

8

## CSS: INLINE STYLES

```
<h1>Hello CSS</h1>
<p>
  Our <em style="color:fuchsia;font-weight: bold;">first</em>
  page with <em>style</em>!
</p>
```

```
h1 {
  color: red;
  font-size: 50px;
}

em {
  color: blue;
}
```



## SELECTORS

## SELECTORS

- Selectors are a **key** part of CSS
- They specify to which elements a CSS rule applies
- CSS selectors are not only used for styling!
  - When using JavaScript to make web pages dynamic, they can be used to select which elements to interact with
  - When doing automated web testing, they can be used to determine which elements the test needs to interact with
  - When doing scraping/crawling, they can be used to select the elements that contain the information we want to extract

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

11


## SIMPLE CSS SELECTORS

There exist **five** kinds of simple selectors:

- **Universal** selector (a.k.a **wildcard**). Matches any element.

```
* {  
  color: hotpink;  
}
```

```
<p>Here's a list:</p>  
<ul>  
  <li>Ann</li>  
  <li>Bob</li>  
  <li><a href="/car/">Carl</a></li>  
  <li>Dave</li>  
</ul>  
<a href="/">Back to homepage</a>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


12

## SIMPLE CSS SELECTORS

- **Type** selector. Matches all element of a given type (i.e., tag name)
- The selector is simply the name of the tag to match

```
a {  
  background: yellow;  
}
```

```
<p>Here's a list:</p>  
<ul>  
  <li>Ann</li>  
  <li>Bob</li>  
  <li><a href="/car/">Carl</a></li>  
  <li>Dave</li>  
</ul>  
<a href="/">Back to homepage</a>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


13

## SIMPLE CSS SELECTORS

- **Id** selector. Matches the element with the given **id** attribute.
- Selector has the form **#ElementId**

```
#msg {  
  background: cyan;  
}
```

```
<form>  
  <label for="msg">Message: </label>  
  <input id="msg" type="text" name="msg"><br>  
  <label for="num">Number: </label>  
  <input id="num" type="number" name="num">  
</form>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


14

## SIMPLE CSS SELECTORS

- **Class selector.** Matches the element with the given **class** attribute.
- Selector has the form **.classname**

```
.primary {  
  background: blue;  
  color: white;  
}
```

```
<button>Reset form</button>  
<button class="primary btn">Continue</button>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


15

## SIMPLE CSS SELECTORS

- **Attribute selector.** Matches the element with a certain attribute.
- Selector has the form **[attribute]** or **[attribute='value']**

```
[for]{ /*all elems with a for attribute*/  
  background: yellow;  
}  
[type='number']{ /*all elems with type=number*/  
  background: cyan;  
}
```

```
<form>  
  <label for="msg">Message: </label>  
  <input id="msg" type="text" name="msg"><br>  
  <label for="num">Number: </label>  
  <input id="num" type="number" name="num">  
</form>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

16



## SIMPLE CSS SELECTORS

- Additional operators (\*=, ^=, \$=) allow **partial matching** with attribute values

```
[href*='programming'] { /*contains 'programming'*/  
  text-decoration: overline;  
}  
[href^='https'] { /*start with 'https'*/  
  color: red;  
}  
[href$='.it/'] { /*ends with '.it/'*/  
  color: green;  
}
```

```
<a href="http://bookofprogramming.com/">Link 1</a>  
<a href="https://programming.net/">Link 2</a>  
<a href="http://webtechnologies.it/">Link 3</a>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

17

## COMPLEX CSS SELECTORS: COMPOUNDS

- It is possible to combine selectors to get fine-grained control
- This is done by concatenating selectors
- Basically select the **intersection** of the involved selectors

```
a[target='_blank'] {  
  color: red;  
}  
a.my-class {  
  color: green;  
}  
a[href*='programming'].my-class {  
  background: yellow;  
}
```

```
<a href="http://bookofprogramming.com/" target="_blank">Link 1</a>  
<a class="my-class" href="https://programming.net/">Link 2</a>  
<em class="my-class">Hello</em>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

18

## COMPLEX CSS SELECTORS: COMBINATORS

- Combinators are used to select elements based on their position in the document (remember that HTML documents can be seen as **trees**!)
- Syntax is: selector1 **combinator** selector2
- Four different combinators exist in CSS:
  - Descendant selector (space)
  - Child selector (>)
  - Adjacent sibling selector (+)
  - General sibling selector (~)

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


19

## COMBINATORS: DESCENDANT SELECTOR

- Syntax: selectorA selectorB
- Semantics: match all elements that match selectorB and are contained within (i.e., are a descendant of) an element matching selectorA

```
<section>
  <p>
    A student asked Fu-Tzu about the nature of
    the cycle of Data and Control. Fu-Tzu replied:
    <em>Think of a compiler, compiling itself.</em>
  </p>
</section>
<em>-- Fragment of the Book of Programming</em>
```

```
section em {
  color: teal;
}
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


20

## COMBINATORS: CHILD SELECTOR

- Syntax: `selectorA > selectorB`
- Semantics: match all elements that match `selectorB` and are a **directly** contained within (i.e., are a direct child of) an element matching `selectorA`

```
main > em {  
  color: teal;  
  font-variant: small-caps;  
}
```

```
<main>  
  CSS <em>selectors</em>:  
  <p>We <em>like</em> 'em.</p>  
</main>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


21

## COMBINATORS: ADJACENT SIBLINGS

- Syntax: `selectorA + selectorB`
- Semantics: match all elements that match `selectorB` and are a **next adjacent siblings** of an element matching `selectorA`

```
.master + li {  
  color: red;  
}
```

```
<ul>  
  <li>Tsu-li</li>  
  <li class="master">Fu-Tzu</li>  
  <li>Tsu-ssu</li>  
  <li class="disciple">Li-Win</li>  
</ul>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS



22

## COMBINATORS: GENERAL SIBLINGS

- Syntax: `selectorA ~ selectorB`
- Semantics: match all elements that match `selectorB` and are a **subsequent siblings** of an element matching `selectorA`

```
.master ~ li.disciple {  
  color:red;  
}
```

```
<ul>  
  <li>Tsu-li</li>  
  <li class="master">Fu-Tzu</li>  
  <li>Tsu-ssu</li>  
  <li class="disciple">Li-Win</li>  
</ul>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

23

## CSS SELECTORS: PSEUDO – CLASSES

HTML elements can be in different **states**, for example because of **user interactions** or because of their relation with other elements.

Pseudo-classes selectors start with « : », and allow to style elements based on their **state**:

- **Interactive states** (resulting from user interaction)
- **Historic states** (used to «remember» which links were visited)
- **Form states** (specific of interaction with forms)
- States deriving from **relations with other elements**

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

24


## PSEUDO – CLASSES: INTERACTIVE STATES

- **:hover** selects the elements on which a pointing device (i.e.: mouse) is placed over
- **:active** matches the state in which an element is actively being interacted with (e.g.: button is being pressed)
- **:focus** matches the state in which an element (e.g.: a link or an input field) has focus (i.e.: is currently selected) in the web page

## PSEUDO – CLASSES: INTERACTIVE STATES

```
<p>Learning <em>HTML</em> and <em>CSS</em>.</p>  
Message: <input type="text"><br><br>  
<button>Keep me pressed</button>
```

```
em:hover {  
  background: yellow;  
}  
input[type='text']:focus{  
  background: cyan;  
}  
button:active{  
  background: blue;  
  color: white;  
}
```




## PSEUDO—CLASSES: HISTORIC STATES

- **:link** selects links that have not been visited yet
- **:visited** selects links that have already been visited

```
:link{  
  color: red;  
}  
:visited{  
  color: darkred;  
}
```

```
<a href="./js/">New link</a>  
<a href="./css/">Visited link</a>
```



Historic states are **not supported** in the *Live Preview* browser within Visual Studio Code! Open the page in Firefox to check them out.


Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

27

## PSEUDO—CLASSES: FORM STATES

```
<div>  
  <label for="mail">Message:</label><input id="mail" type="email">  
  <button disabled>Cancel</button><button>Subscribe</button>  
</div>  
<input type="checkbox"> Checkbox<br><br>  
<em>What a nice form!</em>
```

```
:disabled {  
  border: 2px dashed red;  
}  
:invalid {  
  color: red;  
}  
:checked ~ em {  
  color: deeppink; font-weight: bold;  
}
```



Technically, there can be email address without a dot. For example, user@localhost or user@com are valid addresses!

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

28

## PSEUDO – CLASSES: POSITION RELATIONS

- **:first-child** and **:last-child** select the first (last) child among a set of siblings.
- **:only-child** can be used to select elements that have no siblings.
- **:first-of-type** and **:last-of-type** can be used to select elements that are the first (last) child among a set of sibling, considering only elements of the same type.
- **:nth-child(n)** and **:nth-of-type(n)** can be used to select elements that are in the n-th position among their siblings.
  - Indexing in CSS starts at 1!

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

```
em:last-child {  
  color: red;  
}
```

Ann **Bob** **Carl**  
Ann Bob **Car**

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

31

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

```
em:last-of-type {  
  color: red;  
}
```

Ann **Bob** **Carl**  
Ann **Bob** **Car**

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

32



## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

```
em:first-child {  
  color: red;  
}
```

**Ann** Bob Carl  
Ann Bob **Car**

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

```
em:first-of-type {  
  color: red;  
}
```

**Ann** Bob Carl  
Ann **Bob** Car

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>  
  <em>Ann</em> <strong>Bob</strong> <em>Carl</em>  
</p>  
<p>  
  <strong>Ann</strong> <em>Bob</em> <strong>Carl</strong>  
</p>
```

Ann **Bob** Carl  
Ann Bob **Car**

```
em:nth-child(2) {  
  color: red;  
}
```

Ann **Bob** Carl  
Ann **Bob** Car

## PSEUDO – CLASSES: POSITION RELATIONS

```
<p>Lectures:</p>  
<ol>  
  <li>Introduction</li>  
  <li>HTML</li>  
  <li>CSS (basics)</li>  
  <li>CSS (frameworks + Sass)</li>  
  <li>JavaScript</li>  
</ol>
```

```
li:nth-child(even){  
  color: red;  
}  
li:nth-child(odd){  
  color: blue;  
}
```



## PSEUDO – ELEMENTS

Pseudo-elements can be used to target specific parts of the content of a given HTML element, without adding extra HTML markup


The syntax of pseudo-element selectors is **selector::pseudo-element**

- **selector** is a CSS selector for the target element
- **pseudo-element** is one of the supported pseudo-element selectors:
  - **::first-letter**: targets the first letter of the content of a **block-level** element
  - **::first-line**: targets the first line of the content of a **block-level** element
  - **::selection**: targets the content that is currently selected by the user
  - **::before**: creates an element that is the **first child** of the selected element
  - **::after**: creates an element that is the **last child** of the selected element

## PSEUDO – ELEMENTS: EXAMPLES

```
<p>A student had been sitting motionless behind his computer for hours, frowning darkly. He was trying to write a beautiful solution to a difficult problem, but could not find the right approach.</p>  
<p>Fu-Tzu hit him on the back of his head and shouted 'Type something!' The student started writing an ugly solution. After he had finished, he suddenly understood the beautiful solution.</p>
```

```
p::first-letter {  
  font-weight:bold;  
}  
p::first-line{  
  color: red;  
}  
p:last-child::selection {  
  background: red;  
  color: white;  
}
```



Pseudo-classes X ...

← → ↺ http://127.0.0.1:3000/03-CSS/pseudo.html ☰

A student had been sitting motionless behind his computer for hours, frowning darkly. He was trying to write a beautiful solution to a difficult problem, but could not find the right approach.

Fu-Tzu hit him on the back of his head and shouted 'Type something!' The student started writing an ugly solution. After he had finished, he suddenly understood the beautiful solution.

## PSEUDO–ELEMENTS: EXAMPLES

```
<p class="narrator">A hermit spent ten years writing the perfect program. He  
proudly announced: </p>  
<p class="hermit">'My program can compute the motion of the stars on a 286-  
computer running MS DOS'.</p>  
<p class="narrator">Fu-Tzu responded:</p>  
<p class="fu-tzu">'Nobody owns a 286-computer or uses MS DOS anymore.'</p>
```

```
.narrator::before {  
  content: "Narrator » "; font-weight: bold;  
}  
.narrator::after {  
  content: " «"; font-weight: bold;  
}  
.hermit::before {  
  content: " 🧙 "; font-size: 24px;  
}  
.fu-tzu::before {  
  content: " 🧙 "; font-size: 24px;  
}
```

Pseudo-elements ×

← → ↺ http://127.0.0.1:3000/03-CSS/ps€

**Narrator** » A hermit spent ten years writing the perfect program. He proudly announced: «

🧙 : 'My program can compute the motion of the stars on a 286-computer running MS DOS'.

**Narrator** » Fu-Tzu responded: «

🧙 : 'Nobody owns a 286-computer or uses MS DOS anymore.'

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

39

## THE CASCADE

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

40

## THE CASCADE IN CASCADING STYLE SHEETS

- Sometimes, two or more rules might apply to the same element
- These rules might be **conflicting**, i.e., assign different values to the same property (e.g.: color)
- **The cascade** is the algorithm used to **resolve** such **conflicts**
  - **Input:** a set of conflicting properties that apply to a given element
  - **Output:** a single, cascaded, property to actually apply
- The cascade considers **4 key aspects, in order:**
  1. **Origin and Importance**
  2. **Layers**
  3. **Specificity**
  4. **Position and order of appearance** of the rule

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

41

## THE CASCADE: ORIGIN

- The CSS we write (a.k.a. **authored CSS**) is not the only one being applied to a web page
- We've already mentioned that **user agent styles** exist
  - The stylesheets that are included by browsers by default
- Other styles (a.k.a. **local user styles**) might be added by specific browser extensions or from the operating system level
  - For example, for accessibility purposes
  - Visually-impaired persons might want to use high-contrast color schemes, with larger fonts, etc.

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

42

## THE CASCADE: IMPORTANCE


- The **!important** rule can be used to add more importance to a property inside a CSS rule
- **!important** is simply added at the end of the property declaration

```
h1 {  
  color: red !important;  
}
```

- Importance plays a significant role in the cascade

## THE CASCADE: ORIGIN – IMPORTANCE


From the least specific origin to the most specific one



## THE CASCADE: LAYERS

Within each origin/importance bucket, there can be multiple cascade **layers**

- Within authored styles:
  - Custom layers can be defined using [@layer](#) rule (we won't see that)
    - The custom layers that are declared later have higher priority
  - All other CSS (in `<style>` or imported with `<link>`) belongs to an unnamed layer
  - Inline styles belong to a separate layer and have the highest priority



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

45

## THE CASCADE: SPECIFICITY

When two conflicting rules:

- Belong to the same origin-importance bucket, and
- Belong to the same layer

**Specificity** is considered.

- The idea is that the **most specific** selector should win

```
.primary {  
  color: blue;  
}
```

**VS**

```
h1 {  
  color: red;  
}
```

```
<h1 class="primary">Cascading!</h1>
```

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

46

# THE CASCADE: SPECIFICITY

CSS defines how to calculate the specificity of a selector:

- Ignore the universal selector
- Count the number of id selectors (=A)
- Count the number of class, attribute and pseudo-classes selectors (=B)
- Count the number of type and pseudo-element selectors (=C)

The specificity is a numeric triple **(A, B, C)** computed as above

# THE CASCADE: SPECIFICITY EXAMPLES

- A: Number of id selectors
- B: Number of class, attribute and pseudo-classes selectors
- C: Number of type and pseudo-element selectors

Selector	Specificity (A, B, C)
#id	(1, 0, 0)
em.master[target]	(0, 2, 1)
#navbar ul li a.nav-link[href*='/']	(1, 2, 3)
article.item section p::first-letter	(0, 1, 4)
a:hover	(0, 1, 1)
*	(0, 0, 0)



# THE CASCADE: COMPARING SPECIFICITIES

Comparisons are made by considering the three components in order:

- the specificity with a larger **A** is more specific;
- if the two **A** are tied, then the specificity with a larger **B** wins;
- if the two **B** are also tied, then the specificity with a larger **C** wins;
- if all the values are tied, the two specificities are **equal**.

# THE CASCADE: SPECIFICITY

VS

Selector #1	Specif. #1	Selector #2	Specif. #2	Winner
a[target]	(0, 1, 1)	.list a	(0, 1, 1)	Draw
#msg	(1, 0, 0)	input[type].inp	(0, 2, 1)	#1
#nav > #brd a.lk	(2, 1, 1)	em.foo.bar.light	(0, 3, 1)	#1
[id='nav'] a	(0, 1, 1)	#nav a	(1, 0, 1)	#2

## THE CASCADE: POSITION AND APPEARENCE

When two properties:

- Belong to the same origin/importance bucket
- Belong to the same layer
- Have the same specificity

The **last rule** to appear has the highest priority

```
h1 {  
  color: red;  
}  
h1 {  
  color: blue;  
}
```




Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

51

## THE CASCADE: POSITION AND APPEARENCE


- This rule applies within the same stylesheet, and on the order in which stylesheets appear



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS


52

THE CASCADE: OVERVIEW



THE CASCADE: ORIGIN – IMPORTANCE


From the least specific origin to the most specific one



## THE CASCADE: LAYERS

Within each origin/importance bucket, there can be multiple cascade **layers**

- Within authored styles:
  - Custom layers can be defined using @layer rule (we won't see that)
    - The custom layers that are declared later have higher priority
  - All other CSS (in **<style>** or imported with **<link>**) belongs to a unnamed layer
  - Inline styles belong to a separate layer and have the highest priority



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

55

## THE CASCADE: SPECIFICITY

CSS defines how to calculate the specificity of a selector:

- Ignore the universal selector
- Count the number of id selectors (=A)
- Count the number of class, attribute and pseudo-classes selectors (=B)
- Count the number of type and pseudo-element selectors (=C)

The specificity is a numeric triple (**A, B, C**) computed as above

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

56

## THE CASCADE: POSITION AND APPEARANCE

When two properties:

- Belong to the same origin/importance bucket
- Belong to the same layer
- Have the same specificity

The **last** rule to appear has the highest priority

```
h1 {  
  color: red;  
}  
h1 {  
  color: blue;  
}
```

Cascading!

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

57

## THE CASCADE IN BROWSER DEV TOOLS

User agent styles are **hidden** in Dev Tools by default. If you want to see them, press F1 in Dev Tools and change the settings.

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

58

# INHERITANCE



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

59

## INHERITANCE IN CSS

- Some CSS properties can be inherited from ancestor elements, if no specific value is set
- Inheritable properties include **color**, **font-size**, **font-family**, **font-weight**, **font-style**

```
p {  
  font-family: sans-serif;  
  color: red;  
  font-style: normal;  
}
```


```
<p>  
  Hello <em>Inheritance</em>  
</p>
```



Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

60

## INHERITANCE IN CSS



Inherited properties have the lowest specificity of all styling methods

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

61

## ASSIGNMENT #2

Today's lecture comes with **Assignment #2**! In this assignment, you will:

- Do some practice with basic CSS
- Write some tricky CSS rules
- Test your knowledge of the Cascade algorithm

**Note:** the live HTTP server we setup in **Exercise 1** of **Assignment #1** will be handy for this assignment! Unless you are already familiar with HTTP servers and already know what you're doing, make sure you completed at least **Exercise 1** in **Assignment #1** before doing **Assignment #2**!

Luigi Libero Lucio Starace, Ph.D. - University of Naples Federico II - Web Technologies Course - Lecture 03 - CSS

62

## REFERENCES

- **Learn CSS**

web.dev

<https://web.dev/learn/css/>

Sections: 1, 3 to 6, 14, 15

- **Introducing the CSS Cascade**

MDN web docs

<https://developer.mozilla.org/en-US/docs/Web/CSS/Cascade>

- **Flukeout: A game-based approach to learning CSS selectors**

<https://flukeout.github.io/>

