System Timing

Paolo Bernardi

System timing

- A system can require
  - To wait for a delay time
  - To perform operations at regular time
- These functionalities are supported by peripheral cores called timers
- Timers main function is therefore to give the programmer opportunities to synchronize the system, based on counting.

User view of timers

- They are configurable module that implement a kind of counting mode
- Usually, when a count procedure reaches its end, the system needs to react
  - Typically an interrupt handler is entered at this point
  - Along timer count, the CPU can enter a reduced power mode.

Working principle

- Timers are supplied with a (dedicated) clock signal
- Timers ability is to count based the clock
- Timers include registers to be programmed with a number of clock cycles to count



Counting modes and timing computation

- A timer may be designed following different philosophies
  - Decreasing count – interrupt when count reaches 0
  - Increasing count – interrupt when a match value is reached
- Whatever the counting mode is the following formula can be used to compute the number of clock cycles to count

count = time [s] * frequency [1/s]

Timing computation examples

- To obtain a time setup of
  - 10 seconds
  - with a 25MHz frequency

→ count = 10 [s] * $25*10^6$ [1/s]

→ count = $25*10^7$

→ count = 0x0EE6B280

- To obtain a time setup of
  - 10 milliseconds
  - With a frequency of 100MHz

→ count = $10*10^{-3}$ [s] * $100*10^6$ [1/s]

→ count = 10^6

→ count = 0x000F4240

Timer count limits

- If a timing request is large, the count value could not fit in the timer register
- Hardware and software features can be used to address this issue
  - HW – Cascade of counters
  - HW – Prescalers
  - SW – Handler software count of HW events.

Timers in the LPC1768

- It is quite normal that a System-on-Chip includes several timers

- Standard Timers – to be programmed by the user to implement delays and regular intervals
- Operating System Timers – to be used by system management software
- Extra Timers – providing the system with specific functionalities
  - Repetitive Interrupt Timer
  - PWM.

Standard Timers

- The Timer/Counter is designed to count cycles of the peripheral clock (PCLK) or an externally-supplied clock, and can optionally generate interrupts or perform other actions at specified timer values, based on four match registers.
- It also includes four capture inputs to trap the timer value when an input signal transitions, optionally generating an interrupt.



Fig 117. Timer block diagram

Match registers

- Four 32-bit match registers allows:
  - Continuous operation with optional interrupt generation on match
  - Stop timer on match with optional interrupt generation
  - Reset timer on match with optional interrupt generation



Fig 117. Timer block diagram

Capture Signals

- A transition on a capture pin can be configured to load one of the Capture Registers
- with the value in the Timer Counter and optionally generate an interrupt.



Fig 117. Timer block diagram

External Match Output

- When a match register (MR3:0) equals the timer counter (TC) this output can either toggle, go low, go high, or do nothing.



Fig 117. Timer block diagram

Main registers
(basic timer usage)

Table 426. TIMER/COUNTER0-3 register map

Generic Name	Description	Access	Reset Value[1]	TIMERn Register/ Name & Address
IR	Interrupt Register. The IR can be written to clear interrupts. The IR can be read to identify which of eight possible interrupt sources are pending.	R/W	0	T0IR - 0x4000 4000 T1IR - 0x4000 8000 T2IR - 0x4009 0000 T3IR - 0x4009 4000
TCR	Timer Control Register. The TCR is used to control the Timer Counter functions. The Timer Counter can be disabled or reset through the TCR.	R/W	0	T0TCR - 0x4000 4004 T1TCR - 0x4000 8004 T2TCR - 0x4009 0004 T3TCR - 0x4009 4004
TC	Timer Counter. The 32-bit TC is incremented every PR+1 cycles of PCLK. The TC is controlled through the TCR.	R/W	0	T0TC - 0x4000 4008 T1TC - 0x4000 8008 T2TC - 0x4009 0008 T3TC - 0x4009 4008
MCR	Match Control Register. The MCR is used to control if an interrupt is generated and if the TC is reset when a Match occurs.	R/W	0	T0MCR - 0x4000 4014 T1MCR - 0x4000 8014 T2MCR - 0x4009 0014 T3MCR - 0x4009 4014
MR0	Match Register 0. MR0 can be enabled through the MCR to reset the TC, stop both the TC and PC, and/or generate an interrupt every time MR0 matches the TC.	R/W	0	T0MR0 - 0x4000 4018 T1MR0 - 0x4000 8018 T2MR0 - 0x4009 0018



Fig 117. Timer block diagram

Match Registers

- The Match register values are continuously compared to the Timer Counter value
- When the two values are equal, actions can be triggered automatically
- The action possibilities are
  - to generate an interrupt
  - reset the Timer Counter
  - stop the timer
- Actions are controlled by the settings in the Match Control Register.

Match Control Register

- The Match Control Register is used to control what operations are performed when one of the Match Registers matches the Timer Counter

Table 430. Match Control Register (T[0/1/2/3]MCR - addresses 0x4000 4014, 0x4000 8014, 0x4009 0014, 0x4009 4014) bit description

Bit	Symbol	Value	Description	Reset Value
0	MR0I	1	Interrupt on MR0: an interrupt is generated when MR0 matches the value in the TC.	0
		0	This interrupt is disabled	
1	MR0R	1	Reset on MR0: the TC will be reset if MR0 matches it.	0
		0	Feature disabled.	
2	MR0S	1	Stop on MR0: the TC and PC will be stopped and TCR[0] will be set to 0 if MR0 matches the TC.	0
		0	Feature disabled.	

Timer Control Register

- The Timer Control Register (TCR) is used to control the operation of the Timer/Counter
  - Counter Enable = 1 → Timer/Counter activated
  - Counter Reset = 1 → Timer/Counter fixed to reset value

Table 428. Timer Control Register (TCR, TIMERn: TnTCR - addresses 0x4000 4004, 0x4000 8004, 0x4009 0004, 0x4009 4004) bit description

Bit	Symbol	Description	Reset Value
0	Counter Enable	When one, the Timer Counter and Prescale Counter are enabled for counting. When zero, the counters are disabled.	0
1	Counter Reset	When one, the Timer Counter and the Prescale Counter are synchronously reset on the next positive edge of PCLK. The counters remain reset until TCR[1] is returned to zero.	0
31:2	-	Reserved, user software should not write ones to reserved bits. The value read from a reserved bit is not defined.	NA

Interrupt Register

- The Interrupt Register consists of 4 bits for the match interrupts and 4 bits for the capture interrupts.
  - If an interrupt is generated then the corresponding bit in the IR will be high.
  - Otherwise, the bit will be low.
- Writing a logic one to the corresponding IR bit will reset the interrupt
- Writing a zero has no effect.

Table 427. Interrupt Register (T[0/1/2/3]IR - addresses 0x4000 4000, 0x4000 8000, 0x4009 0000, 0x4009 4000) bit description

Bit	Symbol	Description	Reset Value
0	MR0 Interrupt	Interrupt flag for match channel 0.	0
1	MR1 Interrupt	Interrupt flag for match channel 1.	0
2	MR2 Interrupt	Interrupt flag for match channel 2.	0
3	MR3 Interrupt	Interrupt flag for match channel 3.	0
4	CR0 Interrupt	Interrupt flag for capture channel 0 event.	0
5	CR1 Interrupt	Interrupt flag for capture channel 1 event.	0
31:6	-	Reserved	-

Timer library

- lib_timer.c
  - init_timer(timer_num, timerInterval)
  - enable_timer(timer_num);
  - disable_timer(timer_num);
  - reset_timer(timer_num);
- IRQ_timer.c
  - TIMER0_IRQHandler();
  - TIMER1_IRQHandler();



Delay setup example

- Setup a 10 seconds delay with 25MHz supply frequency
- Raise and interrupt, reset and stop TC

```
24 int main (void) {
25
26   SystemInit();                          /* System
27   LED_init();                            /* LED In
28   BUTTON_init();                         /*
29   init_timer(0,0x0EE6B280);              /* TIMER0
30   enable_timer(0);
31
32   LPC_SC->PCON |= 0x1;                   /* power-
33   LPC_SC->PCON &= 0xFFFFFFFD;
34
35   while (1) {                            /* Loop f
36     __ASM("wfi");
37   }
```

See slide 6 about 0x0EE6B280

init_timer function

- MCR setup occurs in init_timer through a configuration wizard.

```
23  *---------------------------------
24  int main (void) {
25
26    SystemInit();
27    LED_init();
28    BUTTON_init();
29    init_timer(0,0x0EE6B280);
30    enable_timer(0);
31
32    LPC_SC->PCON |= 0x1;
33    LPC_SC->PCON &= 0xFFFFFFFD;
34
35    while (1) {
36      __ASM("wfi");
37    }
38
39  }
40
```



lib_timer.c

- Text editor and configuration wizard

```
91  //*** <<< Use Configuration Wizard in Context Menu >>> ***
92  // <h> timer0 MCR
93  //   <e.0> MR0I
94  //   <i> 1 Interrupt on MR0: an interrupt is generated when MR0
95  //   <i> 0 This interrupt is disabled
96  //   </e>
97  //   <e.1> MR0R
98  //   <i> 1 Reset on MR0: the TC will be reset if MR0 matches it.
99  //   <i> 0 Feature disabled.
100 //   </e>
101 //   <e.2> MR0S
102 //   <i> 1 Stop on MR0: the TC and PC will be stopped and TCR[0]
103 //   <i> 0 Feature disabled.
135 //   <i> 0 Feature disabled.
136 //   </e>
137 //   <e.11> MR3S
138 //   <i> 1 Stop on MR3: the TC and PC will be stopped and TCR[3]
139 //   <i> 0 Feature disabled.
140 //   </e>
141   LPC_TIM0->MCR = 7;
142 // </h>
143 //*** <<< end of configuration section >>>    ***
```



Enable_timer function

- The timer is made running.

```
24 int main (void) {
25
26   SystemInit();
27   LED_init();
28   BUTTON_init();
29   init_timer(0,0x0EE6B280);
30   enable_timer(0);
31
32   LPC_SC->PCON |= 0x1;
33   LPC_SC->PCON &= 0xFFFFFFFD;
34
35   while (1) {
36     __ASM("wfi");
37   }
38 }
```



Timing check

- Measure time between breakpoints.

```
13 /*****************************************************************
14 ** Function name:    Timer0_IRQHandler
15 **
16 ** Descriptions:     Timer/Counter 0 interrupt handler
17 **
18 ** parameters:       None
19 ** Returned value:    None
20 **
21 *****************************************************************/
22
23 void TIMER0_IRQHandler (void)
24 {
25
26   LPC_TIM0->IR = 1;      /* clear interrupt flag */
27   return;
28 }
```

```
21 /*------------------------------
22    Main Program
23  *------------------------------*/
24 int main (void) {
25
26   SystemInit();                    /* System Init
27   LED_init();                      /* LED Initial
28   BUTTON_init();                   /* BUTTON Init
29   init_timer(0,0x0EE6B280);        /* TIMER0 Init
30   enable_timer(0);
31
32   LPC_SC->PCON |= 0x1;             /* power-down
33   LPC_SC->PCON &= 0xFFFFFFFD;
```


IRQ_timer.c
lib_timer.c
sample.c
startup_LPC17xx.s
* Note(s):
*
* This software is supplied "AS IS" without warranties of an
* Copyright (c) 2017 Politecnico di Torino. All rights reser
#include <stdio.h>
#include "LPC17xx.H" /* LPC17xx definition
#include "led/led.h"
#include "button_EXINT/button.h"
#include "timer/timer.h"
/* Led external variables from funct_led */
extern unsigned char led_value; /* defined in funct_l
Main Program
int main (void) {
SystemInit(); /* System Initializat
LED_init(); /* LED Initialization
BUTTON_init(); /* BUTTON Initializat
init_timer(0,0x0EE6B280); /* TIMER0 Initializat
enable_timer(0);
LPC_SC->PCON |= 0x1; /* power-down mode
LPC_SC->PCON &= 0xFFFFFFFD;
while (1) { /* Loop forever
__ASM("wfi");
}
}
Timer 0
Prescaler
PR: 0x00000000
PC: 0x00000000
Timer
TCR: 0x00000000
Enable
TC: 0x00000000
Reset
Interrupt Register
IR: 0x00000000
Match Channels
MCR: 0x00000007
EMR: 0x00000000
MR0: 0x0EE6B280
MR1: 0x00000000
MR2: 0x00000000
MR3: 0x00000000
Interrupt on MR0
Interrupt on MR1
Interrupt on MR2
Interrupt on MR3
Reset on MR0
Reset on MR1
Reset on MR2
Reset on MR3
Stop on MR0
Stop on MR1
Stop on MR2
Stop on MR3
EMC0: Nothing
EMC1: Nothing
EMC2: Nothing
EMC3: Nothing
External Match 0
External Match 1
External Match 2
External Match 3
MR0 Interrupt
MR1 Interrupt
MR2 Interrupt
MR3 Interrupt
Capture Channels
CCR: 0x00000000
CR0: 0x00000000
CR1: 0x00000000
Rising Edge 0
Rising Edge 1
Falling Edge 0
Falling Edge 1
Interrupt on Event 0
Interrupt on Event 1
CAP0.0
CAP0.1
CR0 Interrupt
CR1 Interrupt
Count Control
CTCR: 0x00000000
Mode: Timer
Counter Input: CAP0.0
Simulation
t1: 0.00003513 sec
L:30 C:1
CAP NUM SCRL OVR R/W


IRQ_timer.c
lib_timer.c
sample.c
startup_LPC17xx.s
/***
**--------------File Info---
** File name: IRQ_timer.c
** Last modified Date: 2014-09-25
** Last Version: V1.00
** Descriptions: functions to manage T0 and T1 interru
** Correlated files: timer.h
**--
***/
#include "lpc17xx.h"
#include "timer.h"
/***
** Function name: Timer0_IRQHandler
**
** Descriptions: Timer/Counter 0 interrupt handler
**
** parameters: None
** Returned value: None
**
***/
void TIMER0_IRQHandler (void)
{
LPC_TIM0->IR = 1; /* clear interrupt flag */
return;
}
/***
** Function na
**
** Descriptions: pt handler
**
** parameters: None
** Returned value: None
Timer 0
Prescaler
PR: 0x00000000
PC: 0x00000000
Timer
TCR: 0x00000000
Enable
TC: 0x00000000
Reset
Interrupt Register
IR: 0x00000001
Match Channels
MCR: 0x00000007
EMR: 0x00000000
MR0: 0x0EE6B280
MR1: 0x00000000
Interrupt on MR0
Reset on MR0
Stop on MR0
Stop on MR1
Stop on MR2
Stop on MR3
EMC0: Nothing
EMC1: Nothing
EMC2: Nothing
EMC3: Nothing
External Match 0
External Match 1
External Match 2
External Match 3
MR0 Interrupt
MR1 Interrupt
MR2 Interrupt
MR3 Interrupt
Capture Channels
CCR: 0x00000000
CR0: 0x00000000
CR1: 0x00000000
Rising Edge 0
Rising Edge 1
Falling Edge 0
Falling Edge 1
Interrupt on Event 0
Interrupt on Event 1
CAP0.0
CAP0.1
CR0 Interrupt
CR1 Interrupt
Count Control
CTCR: 0x00000000
Mode: Timer
Counter Input: CAP0.0
Interrupt register
Clear Interrupt flag
Simulation
t1: 10.00003533 sec
L:26 C:1
CAP NUM SCRL OVR R/W

Exercise 1

- Setup regular interval time interruption

Exercise 2

- Figure out the maximum delay that can be obtained when using 12.5 MHz
- Try to overcome this limitation using
  - HW resources available in the peripheral
  - SW methods.