| /nffgs       | Retrieve the set of all nffgs or create a set of new nffgs          |
|--------------|---|
| /nffg        | Used to create a new nffg   |
| /nffg/{id}   | Retrieve an nffg given its name                                     |
| /policies    | Retrieve the set of all policies or create a set of new policies    |
| /policy/{id} | Retrieve the information of a single policy                         |
| /policy      | Used to create a single new policy or to verify a not stored policy |
|              | *the way this operations are implemented are described below        |
|              |   |

#### CREATE NFFG WITH NAME

| POST                             | /nffg  |
|----------------------------------|--|
| Content-Type                     | application/xml  |
| Accept                           | application/xml  |
| Body                             | xsd type: Nffg   |
| Response                         | 201 – Created - application /xml   |
|                                  | type: xsd:XNffg  |
|                                  | Return the same entity we send to the service with a modification:       |
|                                  | the last update time is now set to the server actual time.               |
|                                  | 403 Forbidden – Resource already existing - Nffg already existing        |
|                                  | (I don't used error 409 - Conflict because it is suggested to use it for |
|                                  | PUT requests)  |
|                                  | 500 - Internal Server Error – all problems concerning contacting neo4j   |
| In case of service not available | 404 - Problems, service not available – e.g. wrong url, WS not started   |

## GET all available Nffgs

| GET                    | /nffgs  |
|------------------------|---|
| Accept                 | Application/xml   |
| Response               | 200 application/xml   |
|                        | Body type: xsd:Nffgs  |
|                        |   |
|                        |   |
| In case of service not | 404 - Problems, service not available – wrong url ,WS not started |
| available              |   |
|                        | Typically no other errors can occur as no queries are executed,   |
|                        | neither to Neo4J service  |

## Get NFFG by name

| GET          | /nffg/{name}         |
|--------------|----------------------|
| Content-Type | Application/xml      |
|              |                      |
| Response     | 200 application/xml  |
|              | Body type: xsd:XNffg |

|                                  | 404 Not Found – If the nffg with the requested name is not available  |
|----------------------------------|---|
|                                  | in the system   |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started   |
|                                  |   |
|                                  | Note: an error 404 is automatically sent back if the name of the  |
|                                  | requested Nffg does not respect the regular expression on the name ( as explained in the intro.pdf of assignment 1) |
|                                  | as explained in the intro-par of assignment 1)  |

#### DELETE NFFG by name – remove related policies

| DELETE                           | /nffg/{name}?delpolicy=y  |
|----------------------------------|---|
|                                  | Or  |
|                                  | /nffg/{name}  |
|                                  | Considering as default delpolicy=y                                      |
| Response                         | 200 application/xml   |
|                                  | Returns the information about the deleted Nffg.                         |
|                                  | Deletes all the policies relaying on this NFFG.                         |
|                                  |   |
|                                  | 404 – The Nffg you want to delete is not available. Impossible to       |
|                                  | remove it   |
|                                  | 500 – Internal Server Error – Occurs if you try to delete the Nffg from |
|                                  | NEO4J and NEO4J is not reachable.                                       |
|                                  |   |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started       |

#### DELETE NFFG by name – Do not remove related policies

| DELETE                 | /nffg/{name}?delpolicy=n   |
|------------------------|--|
| Response               | 200 application/xml  |
|                        | Returns the information about the deleted Nffg. Possible only if all   |
|                        | policies relative to the nffg have already removed.  |
|                        | 404 – NotFound The Nffg you want to delete is not available.   |
|                        | Impossible to remove it  |
|                        | 403 – Forbidden The policies referring to the nffg are still available.  |
|                        | Remove all related policies and try again  |
|                        | 500 – Internal Server Error – Occurs if you try to delete the Nffg from  |
|                        | NEO4J and NEO4J is not reachable.  |
| In case of service not | 404 - Problems, service not available – wrong URL, WS not started  |
| available              | The state of the s |

Note: if delpolicy assumes values different from y/n an error:

405 – Method Not Allowed is returned. Please provide the query parameter: delpolicy=y or delpolicy=n. Alternatively do not specify the parameter delpolicy (default actions y is assumed)

#### CREATE a new Policy overwriting a previously existing one

| POST                   | /policy?overwrite=y  |
|------------------------|--|
| Content-Type           | application/xml  |
| Accept                 | application/xml  |
| Body                   | xsd:XPolicy  |
| Response               | 201 – Created - – application/xml Policy created, returns the            |
|                        | information of the created policy  |
|                        | 404 – NotFound – The Policy refers to a Nffg that is not existing.       |
|                        | 500 – Internal Server Error – in case NEO4J is not available or retrieve |
|                        | some errors.   |
| In case of service not | 404 - Problems, service not available – wrong URL, WS not started        |
| available              |  |
|                        |  |

#### CREATE a new Policy without overwriting a previously existing one

| POST                             | /policy?overwrite=n  |
|----------------------------------|--|
| Content-Type                     | application/xml  |
| Accept                           | application/xml  |
| Body                             | xsd:XPolicy  |
| Response                         |  |
|                                  | 201 – Created - application/xml Policy created, returns the              |
|                                  | information of the created policy  |
|                                  | 404 – NotFound – The Policy refers to a Nffg that is not existing.       |
|                                  | 403 – Forbidden. The policy can't be created because another policy      |
|                                  | with the same name is present.   |
|                                  | 500 – Internal Server Error – in case NEO4J is not available or retrieve |
|                                  | some errors.   |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started        |
|                                  |  |

If overwrite assumes values different from y or n an error:

Error 403 – Forbidden is returned. Please provide the query parameter: overwrite=y or overwrite=n. Alternatively do not specify the parameter overwrite (default actions y is assumed).

#### NB IS IT A PROBLEM TO HAVE THE SAME STATUS CODE FOR DIFFERENT PROBLEMS?!

#### **GET all policies**

| GET                              | /policies  |
|----------------------------------|--|
| Content-Type                     | application/xml  |
|                                  |  |
| Response                         | 200 application/xml xsd:XPolicies Contains the set of all policies stored in the service with verification results |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started  |

# CREATE a set of policies

| POST                             | /policies  |
|----------------------------------|--|
| Query Parameter                  | ?overwrite=y   |
|                                  | ?overwrite=n   |
| Content-Type                     | application/xml  |
| Accept                           | Application/xml  |
| Response                         | 200 application/xml  |
|                                  | xsd:XPolicies  |
|                                  | Contains the set of all policies just created                            |
|                                  | 404 – NotFound – At least one policy refers to a Nffg that is not        |
|                                  | existing.  |
|                                  | *403 – Forbidden. The set of policies can't be created because at        |
|                                  | least one policy witis present.  |
|                                  | *Only if ?overwrite=n is specifieid                                      |
|                                  | **403 – Forbidden – The parameter overwrite assumes a not allowed        |
|                                  | value (only y/n or no parameter are allowed)                             |
|                                  | 500 – Internal Server Error – in case NEO4J is not available or retrieve |
|                                  | some errors.   |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started        |
|                                  |  |

## GET Policy given its name

| GET                              | /policy/{name}  |
|----------------------------------|---|
| Content-Type                     | application/xml   |
| Response                         | 200 application/xml xsd:XPolicy   |
|                                  | Contains all the information of the given Policy  |
|                                  | 200 / Body: xsd type: Policy  |
|                                  | 404 – NotFound – In case the policy with the requested name is not stored in the database |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started                         |

### DELETE Policy given its name

| DELETE       | /policy/{name}  |
|--------------|---|
| Content-Type | application/xml   |
| Body         |   |
| Response     | 200 application/xml   |
|              | xsd:XPolicy   |
|              | Contains the information of the deleted policy.                     |
|              | 404 – NotFound – The policy you want to delete is not stored in the |
|              | database  |

| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started |
|----------------------------------|---|
|                                  |   |

#### **DELETE** all stored policies

| DELETE                           | /policies   |
|----------------------------------|---|
|                                  |   |
|                                  |   |
| Response                         | 204 - No content  |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started |

#### **UPDATE** a Policy

| PUT                    | /policy/{name}  |
|------------------------|---|
| Content-Type           | application/xml   |
| Accept                 | application/xml   |
|                        | xsd:XPolicy   |
| Response               | 200 application/xml   |
|                        | xsd:XPolicy   |
|                        | Contains the information of the updated policy                    |
|                        | 403 – Forbidden – The Nffg the policy refers to does not exist.   |
|                        | 404 – NotFound – The policy you want to update does not exists.   |
| In case of service not | 404 - Problems, service not available – wrong URL, WS not started |
| available              |   |

NOTE: The policy name cannot be modified; it identifies in a unique way the policy itself! All the others parameters, including the nffg the policy refers to, can be modified.

#### VERIFICATION OF A POLICY ALREADY STORED IN THE SERVER

| POST                             | /policy/{name}  |
|----------------------------------|---|
| Content-Type                     | application/xml   |
| Response                         | 200 application/xml   |
|                                  | xsd:XPolicy   |
|                                  | Contains the information of the verified policy, including all    |
|                                  | verification informations   |
|                                  | 404 – NotFound – The policy you want to verify does not exists.   |
|                                  | 500 – InternalServerError – Problems while contacting Neo4j       |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started |

NOTE: to verify more than one policy, it is required to exploit multiple requests to the system.

| POST                             | /policy/verify   |
|----------------------------------|--|
| Accept                           | Application/xml  |
|                                  | xsd:XPolicy  |
|                                  | Contains the information of the policy to be verified without storing it |
|                                  | in the system  |
| Content-Type                     | application/xml  |
| Response                         | 200 application/xml  |
|                                  | xsd:XPolicy  |
|                                  | Contains the information of the verified policy, including all           |
|                                  | verification informations  |
|                                  | 404 – NotFound – The nffg or the nodes the policy requires to be         |
|                                  | verified are not stored in the system, impossible to satisfy the request |
|                                  | 500 – InternalServerError – Problems while contacting Neo4j              |
| In case of service not available | 404 - Problems, service not available – wrong URL, WS not started        |

NOTE: to verify more than one policy, it is required to exploit multiple requests to the system.