



LocalGPT documentation

Version 2.3.6

Complete Kawaii handbook: 24 conceptual/reference pages and 853 API namespace/type pages with summaries, declarations and member signatures.



Contents

1. LocalGPT documentation [index.html](#)
2. Chat and AI Council [guide/chat-and-council.html](#)
3. Documentation inside LocalGPT [guide/documentation.html](#)
4. Embedded planning, GameDirector, and creative runtimes [guide/embedded-and-games.html](#)
5. Getting started [guide/getting-started.html](#)
6. User guide [guide/index.html](#)
7. Projects and workspaces [guide/projects-and-workspaces.html](#)
8. AI Host control plane [architecture/ai-host.html](#)
9. Chat and Council runtime [architecture/council-runtime.html](#)
10. Frontend, DevExpress, and themes [architecture/frontend-and-themes.html](#)
11. Architecture [architecture/index.html](#)
12. Organic 1-Wire and security [architecture/onewire-security.html](#)
13. Projects, workspaces, and persistence [architecture/project-data.html](#)
14. System overview [architecture/system-overview.html](#)
15. Build and validation [engineering/build-validation.html](#)
16. Engineering guidance [engineering/index.html](#)
17. Maintenance status [engineering/maintenance-status.html](#)
18. Release and documentation pipeline [engineering/release-and-docs.html](#)
19. Capability map [reference/capability-map.html](#)
20. Design evolution and provenance [reference/design-evolution.html](#)
21. Documentation migration map [reference/documentation-migration.html](#)
22. Reference [reference/index.html](#)
23. LocalGPT API reference [api/index.html](#)
24. LocalGPT documentation [LocalGPT-2.3.6.print.html](#)

API appendix: 853 generated pages, searchable in this PDF and fully linked in the HTML site.

LocalGPT documentation

Version 2.3.6

LocalGPT is a local-first AI workbench for direct chat, configurable AI Councils, project maintenance, persistent knowledge, provider-qualified model routing, embedded planning, game runtimes, and guarded local execution.

This site is the maintained product and architecture documentation. It deliberately separates stable design from historical experiments, so you can understand *what LocalGPT is now* without walking through every learning step that shaped it. 🐾

Choose a path

🌸 Use LocalGPT

Start with the application concepts, common workflows, and the boundaries around actions that can change files, run tools, or operate hardware.

[Open the user guide](#)

🧠 Understand the architecture

Follow the modular-monolith boundaries from Blazor UI through services, provider adapters, persistence, the AI Host control plane, Council orchestration, and 1-Wire transports.

[Explore the architecture](#)

🔧 Build and maintain it

Read the compilation truth, diagnostics policy, documentation pipeline, release checks, and the rules that keep generated work reviewable.

[Open engineering guidance](#)

📖 Look up details

Use the capability map, design evolution notes, documentation migration map, or the complete XML-generated API reference.

[Browse reference material](#)

Architecture at a glance

```
flowchart LR
    U[Human user] --> UI[Blazor + DevExpress UI]
    UI --> APP[Application services]
    APP --> COUNCIL[Chat and Council runtime]
    APP --> PROJECTS[Projects, workspaces and knowledge]
    APP --> HOST[Provider-qualified AI Host control plane]
    APP --> WIRE[Organic 1-Wire boundary]
    COUNCIL --> PROVIDERS[Ollama / OpenAI-compatible / cloud providers]
    PROJECTS --> DB[(SQLite + EF Core)]
    HOST --> PROVIDERS
    WIRE --> PEERS[Approved peers, publishers and devices]
```

The human request remains the authority. Model output, uploaded content, repository text, remote peers, and generated artifacts are data—not permission.

Complete documentation set

The conceptual pages are built together with compiler-generated XML documentation for public types and members. The same themed HTML site is shipped inside LocalGPT and published to GitHub Pages.

The packaged PDF is a readable portrait handbook: it contains every maintained guide, architecture, engineering, and reference chapter plus a complete linked inventory of all generated API pages. Detailed API members remain in the searchable HTML site, GitHub Pages, and the in-app viewer so the PDF stays compact and useful.

🐾 [Download the Kawaii handbook](#)

Chat and AI Council

Direct chat

The Chat page is the primary conversation surface. One provider-qualified model answers ordinary requests while configuration remains collapsible so the transcript keeps the available viewport.

A chat session owns its selected provider route, protocol profile, formatter, bounded context, and feedback state. Protocol-specific control tokens are normalized by the matching profile instead of being scattered through the UI.

Supported protocol families include Harmony-style channels, DeepSeek/R1 thinking markers, Gemma turn markers, Apple/OpenELM-style roles, and generic think-tag formats. The formatter boundary keeps these families isolated.

Council teams

A Council team turns one request into an explicit workflow. Each member has a role, provider-qualified model route, optional runtime class, and bounded task. The team configuration is durable; the active run state is not replaced by whichever model speaks last.

Typical roles include:

- coordinator or leader;
- implementation specialist;
- architecture or safety reviewer;
- verifier;
- domain specialist;
- world actor for GameDirector sessions;
- human participant when invited.

The Council spooler and preflight services prepare work, validate routes, and track steps. A model can propose a result, but deterministic application rules still decide whether a step is complete, failed, recoverable, or waiting for a human.

Provider-qualified routing

The visible address follows this shape:

```
Provider – model @ endpoint
```

A bare model name is accepted only when it resolves to one provider route. Ambiguous or stale selections fail clearly instead of falling back to an arbitrary endpoint.

Mixed-provider Councils can combine Ollama, LM Studio or another OpenAI-compatible endpoint, OpenAI, and Azure OpenAI. The correct client is created immediately before each call. Provider-specific settings—such as Ollama GPU options—stay with the provider that understands them.

Benchmark Council

A bounded benchmark measures one or more selected routes using deterministic tasks and explicit limits for context, output, count, and timeout. Other selected models can review the recommendation; when no independent reviewer is available, a bounded self-review may be used.

Recommendations are never applied automatically. The user chooses whether to save or apply a preset. Applying a preset changes future LocalGPT routing; it does not rewrite provider-global server configuration.

Result integrity

A step that produces thinking but no substantive final answer receives at most one bounded final-only recovery request. If the result is still empty, the step is failed rather than counted as success.

Peer verification is advisory. A failed verifier can be recorded as a warning while a valid result remains available, but the UI must not relabel unrelated notices as successful verification.

Human participation

A human can join a running Council, answer a question, approve a proposed boundary, or provide a correction. Human participation does not turn every human message into unrestricted authority; the application still binds decisions to the current request, action, target, and approval scope.

DX functions and change reviews

DX functions expose bounded application capabilities through typed parameters and explicit handlers. Generated changes can be stored as review records with proposed files, findings, execution status, and human decisions. The function catalog describes what can be requested; it does not bypass the service that owns the real operation.

Note

Documentation inside LocalGPT

One documentation tree

The conceptual documentation and compiler-generated API reference are built into one DocFX site. That exact static tree is:

- copied into `wwwroot/help-docs` for the running application;
- packaged inside release ZIPs;
- extracted by the GitHub Pages workflow;
- used to generate the versioned PDF or packaged handbook.

GitHub Pages does not rebuild LocalGPT or require DevExpress packages. It publishes the already reviewed documentation shipped in a release.

Important routes

- `/help-docs/index.html` — documentation home in the local application.
- `/help-docs/api/index.html` — generated API reference.
- `/api/documentation/status` — build mode, counts, PDF state, and theme hashes.
- `/api/documentation/comments` — bounded XML-comment search.
- `/api/documentation/pdf` — current versioned PDF.

On GitHub Pages, the equivalent root is `/LocalGPT/`.

Theme selector

The navigation theme menu supports **Light**, **Dark**, and **Auto**. The selected value is written to:

- DocFX's theme local-storage key for compatibility;
- LocalGPT's `localgpt-docs-theme` local-storage key;
- the first-party `localgpt-docs-theme` cookie.

The cookie uses `Path=/`, `SameSite=Lax`, and a one-year lifetime. HTTPS pages add the `Secure` attribute. A tiny bootstrap script applies the stored value in the document head before the body is painted, reducing light/dark flicker.

The GitHub Pages origin and the local application origin have separate browser storage. A selection persists on each host, but browsers correctly do not share it across those origins.

Kawaii shell

The Kawaii layer is deliberately separate from DocFX's generated content. It provides the gradient shell, paw/cat branding, cards, subtle motion, cursor trail on fine pointers, and light/dark palettes. Reduced-motion and coarse-pointer users keep normal cursor and animation behavior.

PDF

The owner-side documentation build can assemble a complete PDF from generated conceptual and API HTML pages. It requires meaningful source-page and API-page counts and rejects a tiny fallback shell. Website-only motion and navigation are removed in print styles.

A prebuilt source package may include a curated handbook: all maintained conceptual chapters are printed in full, followed by a linked inventory of every generated API page. The full API reference remains available in HTML, and the regular LocalGPT build can regenerate the complete HTML-backed PDF when .NET, DocFX, and a supported browser are present.

Publishing verification

The Pages extractor verifies:

- `index.html` and `api/index.html`;
- current Kawaii CSS and JavaScript markers;
- `documentation-status.json` (including UTF-8 BOM compatibility);
- project-relative assets;
- a nonzero API count;
- the versioned PDF when available.

The Node deprecation messages emitted by GitHub's own actions are warnings; deployment success is determined by artifact upload and the Pages deployment result.

Embedded planning, GameDirector, and creative runtimes

Embedded firmware planning

LocalGPT can turn a board description, pin layout, sensor/actuator roles, transport requirements, and policy constraints into a reviewable firmware plan.

The planner is transport-neutral. GPIO, ADC, PWM, I²C, SPI, UART, CAN, RS-485, physical 1-Wire, and LocalGPT logical telemetry are capabilities—not assumptions.

A plan can include:

- board and pin assignments;
- electrical or protocol findings;
- firmware module layout;
- telemetry contract;
- generated source artifacts;
- compiler and flashing prerequisites.

Planning, compilation, serial access, flashing, and actuator control are distinct operations. The later stages require the matching workspace and approval checks.

Organic 1-Wire

LocalGPT's "organic 1-Wire" is an application protocol for approved peers, publishers, add-ons, and devices. It is not limited to the Dallas/Maxim physical bus. Transport adapters can use TCP, HTTP/JSON, or a gateway while the application contract keeps identity, replay protection, approval, and capability routing explicit.

GameDirector

GameDirector is the authoritative game engine. Player controllers, creature Councils, and reactive map objects submit proposals; they do not mutate world state directly.

The deterministic resolver validates legality, turn order, movement, and state transitions. A configured model can enrich narration or predict consequences without owning the authoritative frame.

Runtime classes describe sessions, maps, players, directors, creatures, objects, and frames. Council roles can be assigned to world actors while the actual transition remains inside GameDirector.

ASCII play surface

The Chat ASCII console presents a stable 80×25 authoritative frame with responsive Fit, Width, and Native modes. It can be mounted or closed without deleting the underlying session. Fullscreen exit occurs before the component is removed so the normal conversation layout is restored correctly.

Minecraft Mod AI Builder

The Minecraft builder applies the same project principles: source knowledge is versioned, generated artifacts are reviewable, dependencies are explicit, and a generated mod/datapack is not presented as tested until the correct toolchain has actually built or validated it.

Historical source comparisons and early game presets are retained as internal notes, while this page describes the maintained runtime contract.

Getting started

Application shape

LocalGPT is one local application with several cooperating surfaces:

- **Chat** for ordinary provider-backed conversation.
- **AI Council** for role-based multi-model work.
- **Projects** and **Project Maintenance** for durable requirements, revisions, artifacts, workspaces, and toolchains.
- **SQLite Database** for inspected local data and persistent configuration.
- **DX Functions & 1-Wire** for bounded callable functions and peer/device operations.
- **Embedded workbench**, **Minecraft Mod Builder**, **Test Lab**, and other focused tools.
- **Help** for the generated DocFX site and API reference.

The desktop wrapper and web host expose the same backend application. The wrapper is a host, not a second architecture.

Configure a model provider

Provider identity is more than a model name. LocalGPT addresses a model using:

```
provider kind + provider name + endpoint + provider-native model name
```

This prevents an Ollama model and an LM Studio/OpenAI-compatible model with the same visible name from being merged accidentally.

A practical first setup is:

1. Configure or discover one local provider.
2. Test its endpoint.
3. Select one discovered model for Chat.
4. Send a harmless request before enabling Council or tool workflows.
5. Add credentials only to the exact endpoint that requires them.

Credentials are not copied to fallback endpoints and are not displayed in documentation or diagnostics.

Understand local data

LocalGPT stores durable application state in SQLite through EF Core. Depending on the enabled features, this includes projects, revisions, requirements, Council configuration, reviewed knowledge, runtime policies, presets, collaboration requests, and bounded operational records.

The database is not an authority source by itself. A stored row can describe a prior approval or preference, but it cannot manufacture a new approval for a consequential action.

Read-only work versus execution

LocalGPT separates four stages:

1. **Inspect** — read bounded files, metadata, provider catalogs, logs, or project state.
2. **Plan** — create a reviewable proposal, command plan, firmware plan, or change set.
3. **Approve** — collect the required user decision for the exact target and scope.
4. **Execute** — perform the bounded operation and record a sanitized result.

A failure at any stage remains visible. The application should report the missing dependency, source, permission, compiler, provider, or capability rather than claiming success.

Theme and documentation preference

The documentation theme selector supports **Light**, **Dark**, and **Auto**. The selection is stored in both browser storage and a first-party cookie named `localgpt-docs-theme`, so it persists when revisiting the GitHub Pages site or the documentation hosted by the local application. The two hosts keep their own preference because browsers isolate storage by origin.

Next step

Continue with [Chat and AI Council](#), or jump to [Projects and workspaces](#) when your goal is code, documents, firmware, or another maintained artifact.

User guide

Welcome to the practical side of LocalGPT. The interface is playful; the operational boundaries are not. A tiny bit kawaii, a lot of explicit control. 🌸

Start here

1. [Getting started](#) — application shape, providers, storage, and approval boundaries.
2. [Chat and AI Council](#) — direct conversations, teams, roles, provider-qualified models, benchmarks, and human participation.
3. [Projects and workspaces](#) — durable projects, revisions, tracked files, toolchains, and permission assessment.
4. [Embedded planning and games](#) — firmware plans, logical telemetry, GameDirector, ASCII play surfaces, and Minecraft generation.
5. [Documentation inside LocalGPT](#) — HTML, API reference, PDF, GitHub Pages, search, and theme persistence.

What LocalGPT does not do silently

LocalGPT does not treat an AI answer as authorization. Consequential actions—writes, builds, native commands, serial access, flashing, actuator control, or protected peer operations—must cross an explicit application policy and, where required, a fresh user approval.

The application may prepare plans, drafts, diffs, firmware layouts, Council proposals, and capability reports without pretending those artifacts have already been executed.

Tip

Begin with one provider and one project. Add Council members, runtime classes, and toolchains after the basic route works. Cute complexity is still complexity.

Projects and workspaces

Durable project model

A LocalGPT project is language-neutral. It can describe a .NET solution, firmware workspace, game content, documentation set, or another technical/creative structure.

The durable model separates:

- project identity and purpose;
- versions and revisions;
- requirements and requirement links;
- named artifacts;
- topics and reviewed knowledge;
- tracked files and file-pattern rules;
- workspace roots and environment profiles;
- compiler installations and build evidence.

A filesystem path helps locate a checkout; it is not the identity of the project. Stable database identifiers survive moves and alternate workspaces.

Revisions and tracked files

A revision records ancestry, status, structure metadata, and build evidence. A tracked file uses a normalized relative path and stable identity. Hashes provide evidence that the file being reviewed is the file that was assessed; they do not grant permission to overwrite it.

The typical flow is:

1. register or select a project;
2. resolve an allowed workspace root;
3. scan expected files using maintained patterns;
4. create or select a revision;
5. inspect and propose changes;
6. save a review record;
7. approve the exact revision for testing;
8. run bounded verification through the configured toolchain.

Workspace permission assessment

A workspace contains rules for allowed paths, expected structure, compiler profiles, and environment variables. Findings are grouped as:

- **Approved** — the required operation is inside the allowed boundary;
- **Warning** — the operation may proceed only after visible review;
- **Danger** — the operation is blocked until the boundary is corrected.

Compiler execution requires a fresh assessment with proven access and no unresolved danger finding. A prior successful build does not automatically approve a later command against changed files or another path.

Toolchains

Compiler installations are records, not guessed commands. A toolchain can describe executable path, version, environment, supported project types, and validation state. Native execution goes through the command runner and approval policy rather than direct `cmd.exe` composition.

Collaboration and knowledge

Projects can link reviewed Council knowledge to topics and versions. Knowledge entries keep provenance, review state, archival state, and optional expiration. Automatic context should use only entries that remain current and explicitly eligible.

Artifacts

Generated source, documents, firmware, reports, and other outputs belong to reviewable artifact workspaces. Saving an artifact is separate from compiling, flashing, publishing, or replacing a project file.

Continue with [Project and data architecture](#) for the service and persistence boundaries.

AI Host control plane

The AI Host control plane is a first-class part of LocalGPT's architecture. It defines how providers, model catalogs, runners, downloads, settings, logs, chat, and API-compatible routes fit behind explicit .NET service boundaries.

Purpose

The AI Host boundary gives LocalGPT a provider-neutral way to discover, configure, run, and observe compatible model runtimes while keeping native inference engines replaceable.

It separates four concerns:

1. **Control plane** — model catalog, running-model state, settings, downloads, health, logs, and request validation.
2. **Provider adapter** — Ollama, OpenAI-compatible, OpenAI, Azure OpenAI, or another bounded route.
3. **Native/model runtime** — the process or library that owns inference, model loading, and hardware use.
4. **LocalGPT orchestration** — Chat/Council selection, benchmarks, presets, policy, and UI.

LocalGPT should not pretend that rebuilding a high-performance inference engine in managed code is a small UI task. A .NET host can provide a strong control plane, provider-compatible API, native runner boundary, and plugin model while delegating optimized inference to a suitable runtime.

Provider-qualified identity

A model route contains:

- provider kind;
- configured provider name;
- endpoint;
- provider-native model name;
- optional credentials held by the configured provider;
- capabilities and provider-specific options.

The route is the identity. Model-name strings alone are insufficient.

Core services

A practical .NET architecture uses contracts similar to:

Service	Responsibility
IProviderModelRuntimeService	Discover and invoke provider-qualified routes
IChatClientFactory	Create the correct client for a route immediately before use
IOllamaProcessService	Inspect or control a bounded local Ollama process when explicitly configured
IAiConnectivityProbe	Test provider health without starting unrelated processes
IModelPresetService	Store LocalGPT routing presets
IProviderModelBenchmarkService	Run bounded benchmark tasks and recommendations
INativeCommandRunner	Execute approved native commands without shell-string composition

A host-specific adapter owns route translation, streaming payloads, error normalization, and capability discovery. The Council layer consumes the common route model rather than branching on provider details in Razor components.

API families

A compatible control plane commonly needs route families for:

- health and version;
- model catalog and model details;
- installed/running models;
- chat/generate/embedding requests;
- streaming responses and cancellation;
- pull/download progress;
- load/unload/keep-alive;
- runtime settings and resource limits;
- logs and diagnostics.

Compatibility must be explicit. A route should not be advertised until its request, response, streaming, cancellation, and error behavior are implemented and tested.

Native runner boundary

The managed application owns configuration and policy; a native runner owns the executable process. The boundary should provide:

- executable and argument arrays rather than shell command strings;
- working-directory and environment allowlists;
- cancellation and timeout;
- bounded stdout/stderr capture;
- process identity and exit code;
- no automatic elevation;
- no execution of uploaded binaries.

Plugins or runners should be registered from reviewed application configuration, not discovered and executed from arbitrary archives.

Model lifecycle

Model acquisition is a separate workflow from model use. A safe lifecycle includes:

1. user selects a provider and model source;
2. LocalGPT shows size, destination, compatibility, and checksum/signature information when available;
3. the user approves the download;
4. progress is recorded without leaking credentials;
5. the adapter verifies the result;
6. the model enters the catalog;
7. load/unload remains explicit and observable.

A benchmark may recommend context/output bounds or an Ollama GPU profile. It does not pull a model or rewrite provider-global settings automatically.

Blazor and DevExpress surfaces

A useful host UI can include:

- provider dashboard and health cards;
- model catalog and installed-model grid;
- active model/process view;
- chat playground;
- benchmark panel;
- download queue;
- settings and diagnostics;
- API compatibility status.

DevExpress grids, forms, dialogs, tabs, and charts should be used where they add concrete behavior. Bootstrap owns the responsive shell. Pages call application services; they do not become provider adapters.

Multi-model operation

LocalGPT may run several compatible routes at once when hardware, provider behavior, and policy allow it. Resource planning should remain visible: model size, estimated memory, context, output bounds, concurrency, and provider limits are inputs to the plan.

The architecture must degrade honestly. If a requested model cannot be loaded beside another one, the host reports the constraint and offers a reviewable unload/retry plan instead of silently replacing the active model.

Acceptance target

A LocalGPT AI Host milestone is complete only when:

- provider-qualified routes remain distinct;
- health/discovery and invocation use the same configured endpoint;
- streaming and cancellation work;
- native execution is bounded;
- credentials stay scoped;
- model lifecycle actions are explicit;
- the UI shows real state;
- benchmark recommendations require user application;
- compatibility claims are backed by tests.

Chat and Council runtime

Session boundary

A chat session combines a selected provider route, protocol profile, formatter, prompt configuration, function catalog, and bounded context. These dependencies are resolved through services and remain stable for the response stream.

Protocol profiles are stateless. They detect provider/model families and normalize only their own control markers. The response formatter owns presentation of thinking, final content, tools, code, and structured sections.

Council orchestration

A Council request is decomposed into explicit workflow steps. The runtime owns:

- team and member configuration;
- provider-qualified route resolution;
- preflight and readiness checks;
- role/task prompts;
- step ordering and cancellation;
- human questions and decisions;
- final-result composition;
- durable summaries and artifacts where appropriate.

The spooler represents queued/running work. Runtime classes describe reusable behavior or game actors, but they do not bypass the workflow service.

Deterministic completion

Models are probabilistic; step completion is not. The application evaluates whether a response contains substantive final content, whether required outputs exist, and whether a bounded recovery is allowed.

A verifier can add confidence or a warning. It cannot retroactively make an invalid primary result valid. Conversely, a failed verifier should not erase a valid result when the workflow contract treats verification as advisory.

Human collaboration

Human participation is modeled as a request and decision flow with an exact question, boundary, status, and optional reuse scope. It supports:

- answering a Council question;
- choosing among alternatives;
- reviewing a proposed change;
- approving a bounded operation;
- contributing domain knowledge.

A human decision is bound to its context. It is not a global bypass token.

DX functions

DX functions expose typed application operations to chat and Council workflows. The catalog describes parameters and capabilities. The handler/service still owns validation, policy, and execution.

Functions should return structured outcomes that distinguish:

- success;
- user decision required;
- capability missing;
- validation failure;
- execution failure;
- partial/reviewable output.

Change reviews

Generated changes are stored as reviewable records rather than immediately applied. A review can include proposed files, diffs or replacement content, architecture findings, build instructions, execution evidence, and user decisions.

The workflow can approve a revision for testing without marking it released or deployed.

Knowledge

Council knowledge is persistent but curated. Automatic context uses reviewed, active, non-expired entries whose provenance is acceptable. Source-backed knowledge is refreshed when its source hash changes. Raw uploads and model answers do not become trusted knowledge automatically.

GameDirector reuse

GameDirector uses the same Council machinery for role-assigned world actors while retaining a deterministic authoritative resolver. This is an example of the intended architecture: generative proposals inside a strict application-owned state machine.

Frontend, DevExpress, and themes

UI ownership

Bootstrap v5 owns responsive layout, spacing, breakpoints, and the application shell. DevExpress components provide behavior-rich grids, editors, dialogs, charts, tabs, menus, and chat surfaces where their features are actually needed.

Razor components present state and call services. They do not own provider protocols, command execution, database initialization, or file policy.

Component contract

Maintained components use explicit injected dependencies for logging, notification, and bounded activity reporting. Long operations support cancellation and show progress. Dialogs have one internal scroll owner and remain usable at ordinary browser zoom.

A failure boundary prevents one component exception from taking down the full circuit when a recoverable user-facing result is possible.

Design patterns

- persistent navigation shell;
- responsive card/grid layouts;
- collapsible advanced configuration;
- reusable provider-model panel;
- status chips with text, not color alone;
- confirmation dialogs that name the exact target;
- bounded tables with search/filter;
- empty states that explain the next action;
- no fake controls or decorative buttons without behavior.

DevExpress assets

DevExpress packages and runtime assets remain governed by their own license. Generated license material, proprietary distribution assets, or credentials must not be committed accidentally. Build and publish scripts use the configured package source and fail clearly when licensed dependencies are unavailable.

Theme Fusion in the application

The application theme system keeps two selections:

1. **Base Theme** — shell/background, Bootstrap metadata, syntax highlighting, and native LocalGPT surfaces.
2. **Style Layer** — optional blend/override for DevExpress and other component surfaces.

Selections are persistent and applied through a service/JavaScript boundary. A theme failure falls back to a readable base rather than leaving the UI half-styled.

Runtime theme ownership

ThemeService is scoped and keeps independent Base Theme and Style Layer selections. MenuIsland owns the interactive render mode; nested switcher components inherit that circuit. Startup registers the active component theme through `DxResourceManager.RegisterTheme`, while runtime component-theme changes await `IThemeChangeService.SetTheme(...)`. Base-only changes do not inject a competing DevExpress stylesheet.

The browser boundary persists validated names, sets `data-bs-theme` and LocalGPT theme metadata, and optionally updates syntax highlighting. A failed change restores the prior readable state. The maintained catalog still supports classic themes such as **Blazing Berry** alongside newer palettes.

Documentation theme

The DocFX site uses a separate Kawaii shell around generated content. It supports light, dark, and auto modes through the standard DocFX selector, with LocalGPT persistence layered on top.

The theme script:

- applies preference before paint;
- stores it in local storage and a first-party cookie;
- observes DocFX changes without replacing its dropdown;
- keeps the dropdown above decorative layers;
- respects reduced-motion and coarse-pointer preferences;
- decorates the brand with a real paw/cat SVG and favicon.

JavaScript boundary

JavaScript is used for browser-only behavior: theme metadata, focus/layout helpers, fullscreen, file download, documentation decoration, and DevExpress interop. Each entry point is registered and diagnostically traceable. Missing functions fail with a useful message rather than a silent `undefined` call.

Testing

Frontend validation combines static checks, component tests where available, browser automation for important routes, and manual visual review at responsive sizes. A screenshot alone is not a behavioral test, but it is useful evidence for layout regressions.

Architecture

LocalGPT is a modular monolith: one deployable local application with explicit service boundaries, provider adapters, persistence, Blazor UI, and optional host wrappers.

Read in this order

1. [System overview](#)
2. [AI Host control plane](#)
3. [Chat and Council runtime](#)
4. [Projects, workspaces, and persistence](#)
5. [Organic 1-Wire and security](#)
6. [Frontend, DevExpress, and themes](#)

Dependency direction

```
flowchart TD
    UI[Components and controllers] --> SVC[Application services]
    SVC --> CONTRACTS[Interfaces and business contracts]
    SVC --> ADAPTERS[Provider / transport / tool adapters]
    ADAPTERS --> EXT[External runtimes and devices]
    SVC --> DATA[EF Core persistence]
    DATA --> DB[(SQLite)]
```

Components coordinate user interaction. Services own operations. Adapters own protocol details. Persistence owns durable state. Static helpers may format or parse immutable data, but application-owned mutable state belongs to scoped, singleton, or hosted services with explicit lifetimes.

Important

Architecture documents describe boundaries; they do not authorize execution. The current user interaction remains the authority source.

Organic 1-Wire and security

Protocol meaning

LocalGPT's organic 1-Wire is a transport-neutral application protocol for cooperation between LocalGPT, PublisherStudio-style peers, approved add-ons, and device gateways. It may travel over TCP, HTTP/JSON, or another bounded transport. It is not the physical Dallas/Maxim 1-Wire protocol, though a gateway may bridge to physical hardware.

Identity

Each application creates its own local identity material at runtime. Private keys, shared secrets, certificates, MFA seeds, and trusted-peer databases are not committed to source or embedded in releases.

Identity creation, regeneration, deletion, and peer trust are visible user operations. Read-only program directories fall back to the user's application-data location.

Connection flow

A safe peer flow is:

1. discover a peer without auto-trusting it;
2. user selects the peer;
3. exchange and display identity information;
4. user confirms the intended relationship;
5. establish the protected session;
6. advertise bounded capabilities;
7. submit work through the spooler;
8. require fresh approval for protected operations.

A sender-supplied `UserConfirmed=true` flag is data, not proof of local approval.

Envelope and replay protection

Protected messages use an envelope with stable identifiers, timestamps/nonces, target capability, payload, and authentication material. The receiver validates identity, freshness, replay policy, capability, and local approval before dispatch.

Replay records are durable where needed and bounded by retention policy. Invalid envelopes fail without exposing secrets or executing partial work.

Capability routing

The capability catalog maps protocol operations to application services. It prevents transport handlers from reflecting arbitrary public methods or constructing unreviewed commands.

Capabilities may include reviewed text exchange, screen capture requests, website/document content, embedded wiring proposals, OCR, or plugin work results. Each capability has its own parameters and approval behavior.

Work spooler

Incoming work enters a queue with peer identity, capability, payload summary, status, and decision state. A hosted processor executes only work that has passed validation and approval.

Security invariants

- no trust on discovery alone;
- no credential reuse across unrelated endpoints;
- no arbitrary reflection execution;
- no uploaded executable execution;
- no automatic filesystem write outside approved workspace;
- no actuator/flash/native command without the matching approval;
- no secret content in logs or documentation;
- no model response treated as authority.

The protocol remains useful because the boundaries are explicit, not because every peer is assumed friendly. 🐾

Projects, workspaces, and persistence

Database-first project model

LocalGPT stores the project model in SQLite through EF Core. The database describes the user's technical intent independently of a particular checkout path or language.

Core records include projects, versions, revisions, requirements, requirement links, artifacts, topics, knowledge links, tracked files, workspace roots, compiler installations, build verifications, and Council review records.

Identity and paths

Stable identifiers belong to database records. Paths are mutable location data. A project can have several workspace roots or move to another machine without changing its conceptual identity.

Tracked files use normalized relative paths and hashes. This supports exact-source review and prevents a report about one file version from being mistaken for evidence about another.

Workspace service boundary

The workspace resolver maps a project/revision to an approved root and validates:

- path containment;
- expected structure;
- read/write requirements;
- file-pattern policy;
- environment variables;
- compiler/tool availability;
- danger findings.

The project service does not execute compilers. The artifact service does not silently replace tracked files. The command runner does not decide project policy.

Compiler inventory

Compiler installations are explicit records with path, version, supported workload, and validation state. Discovery can propose installations; the user selects what the project may use.

Build verification stores the command plan, revision, timing, exit status, bounded output, and artifact evidence. A successful historical record is not a standing approval for future execution.

EF Core initialization

Database initialization supports both clean installs and older development databases that may contain application tables before migration history was complete.

The bootstrap sequence must:

1. open the configured database safely;
2. inspect migration history and existing schema;
3. distinguish an empty database from a legacy schema;
4. apply or baseline migrations in the maintained order;
5. preserve user data;
6. initialize seed/catalog data idempotently;
7. expose readiness to dependent services.

Logging tables are handled carefully so diagnostic logging does not recurse into an unready database.

Migration snapshots

EF migration snapshots and generated migrations are architecture artifacts. They must remain ordered, compilable, and consistent with the context model. Manual fixes should not create duplicate identities or silently drop columns.

Knowledge and runtime policy

Seed services initialize known catalogs and policy definitions. Mutable values are stored in the database or owning service, not in global static collections. User changes remain distinct from shipped defaults.

Durable entity contract

The database-first model keeps the important records explicit:

- LocalGptProject owns revisions, requirements, artifacts, topics, and versions.
- LocalGptProjectRevision stores ancestry, status, structure metadata, and build evidence without touching Git or files by itself.
- LocalGptProjectRequirementLink maps a requirement to a stable function, service, controller, business object, table, configuration, variable, regex, prompt, knowledge entry, or generated-code target.
- ProjectDocumentImport stores bounded normalized text with source, hash, and safety metadata.

Before a Council step calls a function, it identifies the project/revision, maps the task to approved requirements, states missing evidence, and chooses the smallest relevant function set. **Function availability is not a reason to call it.**

Migration compatibility sequence

Older owner databases can contain application tables before EF migration history was complete. Compatibility handling therefore performs SQLite health checks, schema inspection, stale-lock handling, and a **SQLite online backup** before adopting history or migrating a compatible logging table. A history row is inserted only when the migration's **complete signature** is present. **Refuse partially applied ambiguous schemas** and report the missing markers plus the backup path instead of guessing.

The database logger uses a separate readiness gate so queued startup diagnostics cannot write through EF while migrations and deterministic seed stages are still running.

Snapshot ordering contract

LocalGptMemoryDbContextModelSnapshot is executable model-building code. Keep **properties first**, configure **relationships** only after both entity property blocks exist, and add collection navigations after the matching relationships. An early navigation-only call can accidentally create a shared Dictionary<string, object> entity under the CLR type name.

Run build/Assert-EfSnapshotArchitecture.ps1 after editing the context, an EF entity, a migration, or the snapshot. Static ordering checks protect against the known regression; they do not replace a real migration smoke test.

Data safety

Database rows, imported JSON, and localization catalogs are untrusted inputs. Services validate shape and bounds before using them to construct paths, commands, routes, or UI markup.

System overview

Architectural goal

LocalGPT keeps an “old-school .NET, updated” shape: one inspectable application rather than a mesh of accidental services. The architecture favors explicit classes, typed contracts, dependency injection, EF Core, controller/service boundaries, and deterministic validation around AI-generated work.

Main layers

Layer	Responsibility
Blazor and DevExpress UI	Present state, collect decisions, coordinate user-visible workflows
Controllers/endpoints	Validate HTTP input and delegate to application services
Application services	Own use cases, orchestration, policy checks, and result composition
Council and provider services	Resolve model routes, protocols, formatters, teams, steps, and recovery
Project and artifact services	Own durable project structure, workspaces, revisions, and review records
Persistence services	EF Core contexts, migrations, seed data, and database health
Native/tool adapters	Compilers, commands, provider processes, browsers, serial and file operations
1-Wire services	Identity, discovery, capability routing, replay protection, and approved peer work

Service lifetimes

- **Singleton** services hold process-wide catalogs, bounded registries, or hosted coordination state that is safe to share.
- **Scoped** services own request/circuit work and database contexts.
- **Transient** services are used for small stateless operations.
- **Hosted services** handle background queues or discovery with cancellation and bounded recovery.

Mutable application state must not be hidden in static fields. Framework-required static syntax and pure immutable helpers are exceptions, not a pattern for runtime ownership.

Request authority and untrusted data

Repository files, database rows, logs, model output, uploads, generated source, remote peer messages, and tool descriptions are untrusted data. They may inform a plan; they cannot authorize one.

The authority chain is:

1. the current user requests an outcome;
2. LocalGPT resolves the exact operation and target;
3. policy determines whether read-only work is sufficient or approval is required;
4. the user approves the bounded action when needed;
5. the owning service executes and records a sanitized result.

Component safety

Maintained components use logging, user notification, and bounded component-activity services. Technical failures are logged without embedding prompts, full uploads, generated source, credentials, or secrets. User-facing messages remain sanitized and actionable.

The application can keep a small in-process operational briefing—current screen, active operation, and recent status—without turning it into durable conversational memory or authority.

Streaming

Streaming provider responses are normalized through the selected protocol profile and formatter. Cancellation, disposal, and partial-result behavior belong to the session/service layer, not arbitrary component event handlers.

Generation contracts

Generated code or artifacts must include:

- a declared target and purpose;
- bounded files and dependencies;
- missing-source/capability reporting;
- reviewable output;
- a validation plan;
- no claim of successful build or execution without real evidence.

An archetype is a generation contract, not a template dump. It can define expected projects, services, routes, pages, tests, and acceptance criteria while still allowing the implementation to fit the current repository.

Diagnostics

Diagnostics are layered:

- structured application logs;
- bounded user notifications;
- component activity summaries;
- build/static validation scripts;
- documentation status metadata;
- explicit debug artifact inspection.

A regex scan or delimiter counter is not compilation. A successful static scan is useful evidence, not proof that the complete application builds.

Build and validation

Build truth

A successful LocalGPT build is the primary compilation truth. Delimiter counts, regex scans, JSON/XML parsing, IDE inspection, or screenshots cannot replace it.

The repository pins its SDK through `global.json` and provides validation scripts for architecture and policy. When .NET is unavailable, those scripts can still provide partial evidence, but the result must be labeled uncompiled.

Validation sequence

A normal maintenance pass should run, as applicable:

1. source formatting and encoding checks;
2. JSON/YAML/XML parsing;
3. C# syntax parsing through the pinned SDK/Roslyn route;
4. architecture assertions;
5. dependency and publish-configuration checks;
6. localization and JavaScript diagnostics checks;
7. database migration/snapshot checks;
8. application build/tests;
9. documentation build and artifact verification;
10. focused browser smoke tests.

Generated C#

Generated source must preserve namespaces, nullable context, project references, service lifetimes, and existing framework patterns. It must not report compilation success until the target project has actually compiled.

Warnings are triaged by category. Suppression is not the default response to a warning introduced by generated code.

Static and runtime ownership

Application-owned mutable catalogs, regex lists, runtime values, and policy state are not static. Framework bootstrap and pure immutable helpers remain valid static boundaries.

Runtime-value services own mutable definitions and current values. Persistence services own durable policy. Components consume services rather than constructing global state.

Logging integrity

Logs contain technical context needed for diagnosis but avoid prompts, full model responses, uploads, generated file contents, credentials, secrets, and unbounded exception data.

The database logger exposes readiness so startup failures do not recurse. User notifications are sanitized; detailed traces remain in the configured logger.

JavaScript diagnostics

Maintained JavaScript functions used through interop are registered and validated. Build checks detect missing function names and known unsafe patterns. Browser tests cover theme selection, documentation dropdown behavior, fullscreen/close flows, and critical navigation.

Frontend checks

Important checks include:

- interactive render-mode ownership;
- no nested incompatible render boundaries;
- responsive dialogs and scroll ownership;
- keyboard focus and visible labels;
- clickable menus above decorative layers;
- reduced-motion behavior;
- light/dark contrast;
- no fake or dead controls.

Documentation checks

The documentation build verifies conceptual pages, generated API YAML/HTML, versioned PDF, Kawaii CSS/JS markers, icon assets, status JSON, and nonzero source/API counts.

Engineering guidance

This section collects the rules that keep LocalGPT maintainable after the architecture has become interesting enough to bite back.

- [Build and validation](#)
- [Release and documentation pipeline](#)
- [Maintenance status](#)

Working principle

Use the strongest available evidence and label weaker evidence honestly:

```
real build/test > parser/static validation > focused inspection > assumption
```

A capability gap should report the requested outcome, missing dependency or source, evidence inspected, safe next step, and whether owner-side tooling or approval is required.

Open work

Current owner-side verification tasks live on the [maintenance status](#) page. Historical task lists and pass manifests remain under docs/internal-notes and are excluded from the reader site.

Maintenance status

This is the small, honest maintenance corner of the documentation. 🐾 It keeps owner-only validation and unfinished integration work visible without mixing temporary pass notes into the architecture chapters.

A task is complete only after implementation, compatibility review, validation, and user-visible verification. Drafted code or a successful static scan is useful evidence, but not the finish line.

Build and runtime gates

- Compile the root LocalGPT project and run startup against a backed-up owner database using the exact release candidate.
- Complete a licensed Windows/DevExpress Release build and the supported package matrix.
- Run real-package DevExpress and SQLite integration tests.
- Test supervised routes, collaboration refresh, and Chat autosave during rapid navigation, reconnect, and disposal.
- Review singleton registrations for thread safety; move circuit- or user-mutable state to scoped services where required.

Persistence and recovery gates

- Verify compatibility-backup creation, migration-history adoption, pending migrations, and initial catalog seeding.
- Inspect and record `__EFMigrationsHistory` after a successful owner run.
- Run migration and recovery smoke tests for empty, logging-only, untracked-current, partial, locked, and corrupt SQLite databases.

UI and theme gates

- Test runtime theme initialization, Light/Dark/Auto switching, rollback, reconnect, and disposal in the app and in the shipped DocFX site.
- Confirm the documentation theme preference persists independently on the local application origin and the GitHub Pages origin.
- Decide whether Highlight.js theme stylesheets should be vendored for completely offline switching.
- Complete rich SQLite custom mask, format, and null-text editing.
- Add a catalog-assisted requirement-link picker with validation.

Remaining integration work

- Continue converting legacy logger helpers to injected logging and bounded service activity at high-level boundaries.
- Complete repository-pull UI integration through safe text ingestion.

Carry-forward rule

Every unresolved item moves into the next current changelog, issue, or release-planning source. Historical pass manifests and superseded task lists remain available under `docs/internal-notes`, excluded from DocFX, so the public documentation stays focused without losing the trail that led here.

Release and documentation pipeline

Release discipline

Releases use a clean, reviewable lane. The version must be greater than prior public releases, repository state must be understood, and required build/validation steps must finish before assets are published.

The release package matrix includes desktop/WebView and backend packages for supported Windows, Linux, macOS, and architecture targets. Setup packages remain separate from portable packages.

Documentation build

The build restores the repository-local DocFX tool, extracts metadata from LocalGPT.dll and LocalGPT.xml, builds conceptual and API pages, installs the Kawaii assets, produces the versioned PDF, writes documentation-status.json, and copies the complete tree into wwwroot/help-docs.

The build script injects:

- the localgpt-kawaii-docs HTML class;
- cache-busted Kawaii CSS/JS links;
- an early theme bootstrap;
- paw/cat favicon and brand assets.

GitHub Pages

The Pages workflow resolves a release tag, downloads release ZIPs, inspects each ZIP safely, and scores complete documentation candidates. It validates theme markers, hashes, index/API pages, status metadata, relative assets, and page counts before uploading one Pages artifact.

Windows ZIP backslashes and UTF-8 BOMs are accepted. Setup archives that do not contain the full site are ignored.

Node warnings

GitHub's official Pages and artifact actions may emit Node or dependency deprecation warnings. These warnings do not mean the static site runs Node. The deployed site is HTML, CSS, browser JavaScript, and assets. The workflow result and Pages deployment status determine success.

PDF

The preferred PDF route assembles the generated HTML pages and prints them with an installed Edge/Chrome/Chromium browser. A secondary DocFX PDF route may require Node. Both routes must produce a real, sufficiently sized document; a one-page fallback shell is rejected.

Stop conditions

Stop and report clearly when:

- the working tree or version is unsuitable;
- required licensed dependencies are unavailable;
- compilation or validation fails;
- the API graph is empty;
- the PDF is incomplete;
- release assets do not contain the complete docs tree;
- publishing credentials/permissions are unavailable.

Capability map

Area	Maintained capability	Important boundary
Chat	Provider-qualified single-model sessions	Protocol/formatter isolation
AI Council	Teams, roles, runtime classes, workflows, human participation	Deterministic step state and bounded recovery
Providers	Ollama, OpenAI-compatible, OpenAI, Azure OpenAI routes	Endpoint-qualified identity and scoped credentials
Benchmarking	Bounded tasks, peer/self review, presets	Recommendations require user application
Projects	Versions, revisions, requirements, artifacts, topics	Database identity is separate from paths
Workspaces	Root resolution, policies, toolchains, build evidence	Fresh assessment before execution
Knowledge	Reviewed persistent entries and source refresh	Raw uploads/model output are not trusted automatically
DX functions	Typed callable application operations	Handler/service owns policy and execution
1-Wire	Peer discovery, identity, capabilities, work spooler	Discovery is not trust; remote flags are not approval
Embedded	Board/pin/transport plans and artifacts	Plan, compile, flash, and actuate are separate
GameDirector	Deterministic sessions with generative proposals	Models do not directly mutate state
Minecraft	Reviewable mod/datapack generation	Toolchain evidence required for build claims
Documentation	Conceptual docs, XML API, PDF, Pages	Publishes shipped static tree

Capability-gap contract

When LocalGPT cannot complete a requested task, it should report:

- the requested outcome;
- the missing dependency, source, API, framework knowledge, permission, or runtime capability;
- what evidence was inspected;
- what can still be produced safely;
- the next reviewable step;
- whether owner-side tooling, licensed dependencies, or human approval is required.

A gap report is not permission to self-expand or execute arbitrary installers.

Design evolution and provenance

LocalGPT was created and is maintained by Michael Fleischer (Michi0403). It is an independent, local-first engineering project rather than a commercial hosted service.

AI systems have contributed suggestions, code drafts, reviews, and capability reports throughout development. The maintainer remains responsible for architecture decisions, integration, testing, releases, and the user-visible product.

From experiments to maintained boundaries

Several current subsystems began as focused experiments:

- multi-role AI Councils became explicit team/workflow/runtime-class services;
- provider experiments became endpoint-qualified routes and a reusable provider-model panel;
- AI Host research became a provider-neutral .NET control-plane architecture;
- game prompts became GameDirector plus deterministic frames and actor roles;
- firmware ideas became transport-neutral plans and approval-separated tool stages;
- peer communication sketches became the organic 1-Wire identity/capability/spooler boundary;
- build-pass notes became repository validation policies;
- DocFX experiments became one shipped site for the app, PDF, and GitHub Pages.

The public documentation now describes those maintained results. Local paths, uploaded archive names, transient pass manifests, and version-specific repair narratives are retained only in docs/internal-notes for archaeology.

Project stance

LocalGPT is built for real use, study, and continued experimentation. Public availability does not imply enterprise support or a promise to preserve every historical UI shape. The project values:

- local control and inspectability;
- explicit human authority;
- practical provider neutrality;
- durable architecture over demo-only behavior;
- honest capability reporting;
- playful interfaces that do not weaken operational boundaries.

Attribution versus authority

Project provenance is important and remains visible. It is not an authentication mechanism and does not grant a person, document, model, database row, or remote peer standing authority inside another user's active session.

Documentation migration map

The rework replaced a flat list of research notes, build-pass records, and feature patches with a curated product documentation structure.

No source information was discarded. Exact former pages are retained under docs/internal-notes/legacy-source, excluded from DocFX, and mapped below to the maintained page that now owns their durable content.

Former public page	Maintained destination	Preservation
AI_HOST_CONTROL_PLANE_ARCHITECTURE.md	architecture/ai-host.md	Original retained in internal-notes/legacy-source/top-level/AI_HOST_CONTROL_PLANE_ARCHITECTURE.md
AI_HOST_DOTNET_BLAZOR_REBUILD_GUIDE.md	architecture/ai-host.md	Original retained in internal-notes/legacy-source/top-level/AI_HOST_DOTNET_BLAZOR_REBUILD_GUIDE.md
AI_HOST_DOTNET_EXPERIMENT.md	architecture/ai-host.md	Original retained in internal-notes/legacy-source/top-level/AI_HOST_DOTNET_EXPERIMENT.md
ARCHITECTURE.md	architecture/system-overview.md	Original retained in internal-notes/legacy-source/top-level/ARCHITECTURE.md
ARCHITECTURE_FOR_AI.md	architecture/system-overview.md	Original retained in internal-notes/legacy-source/top-level/ARCHITECTURE_FOR_AI.md
ASCII_RUNTIME_GAME_PRESETS.md	guide/embedded-and-games.md	Original retained in internal-notes/legacy-source/top-level/ASCII_RUNTIME_GAME_PRESETS.md
BLAZOR_BOOTSTRAP_DEVEXPRESS_DESIGN.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/BLAZOR_BOOTSTRAP_DEVEXPRESS_DESIGN.md
BLAZOR_DEVEXPRESS_AI_GENERATION.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/BLAZOR_DEVEXPRESS_AI_GENERATION.md
CAPABILITY_GAP_CONTRACT.md	reference/capability-map.md	Original retained in internal-notes/legacy-source/top-level/CAPABILITY_GAP_CONTRACT.md
CHAT_PROTOCOLS_AND_SESSION_CONTEXT.md	architecture/council-runtime.md	Original retained in internal-notes/legacy-source/top-level/CHAT_PROTOCOLS_AND_SESSION_CONTEXT.md
COMPILER_VALIDATION_AND_GENERATION_RULES.md	engineering/build-validation.md	Original retained in internal-notes/legacy-source/top-level/COMPILER_VALIDATION_AND_GENERATION_RULES.md
COMPONENT_SAFETY_AND_SHORT_TERM_MEMORY.md	architecture/system-overview.md	Original retained in internal-notes/legacy-source/top-level/COMPONENT_SAFETY_AND_SHORT_TERM_MEMORY.md
DATABASE_FIRST_PROJECT_ARCHITECTURE.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/DATABASE_FIRST_PROJECT_ARCHITECTURE.md
DATABASE_MIGRATION_BOOTSTRAP.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/DATABASE_MIGRATION_BOOTSTRAP.md
DEVEXPRESS_ASSETS.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/DEVEXPRESS_ASSETS.md
DOTNET_AI_HOST_ARCHITECTURE_PATTERNS.md	architecture/ai-host.md	Original retained in internal-notes/legacy-source/top-level/DOTNET_AI_HOST_ARCHITECTURE_PATTERNS.md
DXAI_FUNCTIONS_AND_CHANGE_REVIEWS.md	architecture/council-runtime.md	Original retained in internal-notes/legacy-source/top-level/DXAI_FUNCTIONS_AND_CHANGE_REVIEWS.md
EF_DEVEXPRESS_BUSINESS_OBJECTS.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/EF_DEVEXPRESS_BUSINESS_OBJECTS.md
EF_MIGRATION_SNAPSHOT_ARCHITECTURE.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/EF_MIGRATION_SNAPSHOT_ARCHITECTURE.md
FRONTEND_DESIGN_PATTERN_LIBRARY.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/FRONTEND_DESIGN_PATTERN_LIBRARY.md
FRONTEND_TEST_AUTOMATION.md	engineering/build-validation.md	Original retained in internal-notes/legacy-source/top-level/FRONTEND_TEST_AUTOMATION.md
GENERATION_ARCHETYPE_CONTRACTS.md	architecture/system-overview.md	Original retained in internal-notes/legacy-source/top-level/GENERATION_ARCHETYPE_CONTRACTS.md
HUMAN_AI_COLLABORATION.md	architecture/council-runtime.md	Original retained in internal-notes/legacy-source/top-level/HUMAN_AI_COLLABORATION.md
JAVASCRIPT_RUNTIME_DIAGNOSTICS.md	engineering/build-validation.md	Original retained in internal-notes/legacy-source/top-level/JAVASCRIPT_RUNTIME_DIAGNOSTICS.md
LOCALGPT_CAPABILITY_SNAPSHOT.md	reference/capability-map.md	Original retained in internal-notes/legacy-source/top-level/LOCALGPT_CAPABILITY_SNAPSHOT.md
LOCALGPT_DEVELOPER_DIARY.md	reference/design-evolution.md	Original retained in internal-notes/legacy-source/top-level/LOCALGPT_DEVELOPER_DIARY.md

Former public page	Maintained destination	Preservation
LOCALGPT_WORKFLOW_MEMORY.md	reference/design-evolution.md	Original retained in internal-notes/legacy-source/top-level/LOCALGPT_WORKFLOW_MEMORY.md
LOGGING_INTEGRITY.md	engineering/build-validation.md	Original retained in internal-notes/legacy-source/top-level/LOGGING_INTEGRITY.md
MICROSOFT_DOTNET_SAMPLE_CURRICULUM.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/MICROSOFT_DOTNET_SAMPLE_CURRICULUM.md
MINECRAFT_MOD_AI_BUILDER.md	guide/embedded-and-games.md	Original retained in internal-notes/legacy-source/top-level/MINECRAFT_MOD_AI_BUILDER.md
MINECRAFT_SOURCE_KNOWLEDGE.md	guide/embedded-and-games.md	Original retained in internal-notes/legacy-source/top-level/MINECRAFT_SOURCE_KNOWLEDGE.md
ONEWIRE_RUNTIME_SECURITY_HTTP_JSON.md	architecture/onewire-security.md	Original retained in internal-notes/legacy-source/top-level/ONEWIRE_RUNTIME_SECURITY_HTTP_JSON.md
OPEN_TASKS.md	engineering/maintenance-status.md	Original retained in internal-notes/legacy-source/top-level/OPEN_TASKS.md
OPEN_WIRINGS_2.0.3.md	reference/design-evolution.md	Original retained in internal-notes/legacy-source/top-level/OPEN_WIRINGS_2.0.3.md
ORGANIC_AI_COUNCIL_BLUEPRINT-v1.6.md	architecture/onewire-security.md	Original retained in internal-notes/legacy-source/top-level/ORGANIC_AI_COUNCIL_BLUEPRINT-v1.6.md
ORGANIC_AI_COUNCIL_BLUEPRINT_2_1.md	architecture/onewire-security.md	Original retained in internal-notes/legacy-source/top-level/ORGANIC_AI_COUNCIL_BLUEPRINT_2_1.md
PROJECT-MAINTENANCE-WORKSPACES-TOOLCHAINS.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/PROJECT-MAINTENANCE-WORKSPACES-TOOLCHAINS.md
PROJECT_COLLABORATION.md	architecture/project-data.md	Original retained in internal-notes/legacy-source/top-level/PROJECT_COLLABORATION.md
PROJECT_IDENTITY.md	reference/design-evolution.md	Original retained in internal-notes/legacy-source/top-level/PROJECT_IDENTITY.md
PROJECT_STANCE.md	reference/design-evolution.md	Original retained in internal-notes/legacy-source/top-level/PROJECT_STANCE.md
README_IMAGE_PLAN.md	internal-notes/legacy-source/top-level/README_IMAGE_PLAN.md	Original retained in internal-notes/legacy-source/top-level/README_IMAGE_PLAN.md
RELEASE_PROCESS.md	engineering/release-and-docs.md	Original retained in internal-notes/legacy-source/top-level/RELEASE_PROCESS.md
SAFE_REWORK_MANIFEST.md	reference/documentation-migration.md	Original retained in internal-notes/legacy-source/top-level/SAFE_REWORK_MANIFEST.md
SAFE_STATIC_RUNTIME_AND_DIAGNOSTICS_POLICY.md	engineering/build-validation.md	Original retained in internal-notes/legacy-source/top-level/SAFE_STATIC_RUNTIME_AND_DIAGNOSTICS_POLICY.md
THEME_RUNTIME_ARCHITECTURE.md	architecture/frontend-and-themes.md	Original retained in internal-notes/legacy-source/top-level/THEME_RUNTIME_ARCHITECTURE.md
index.md (former generated landing source)	index.md (curated landing page)	Original retained in internal-notes/legacy-source/top-level/index.md

Public release articles

The former release-specific articles under docs/articles are preserved under internal-notes/legacy-source/articles. Stable feature behavior was folded into the user guide and architecture pages; patch-version narration is no longer mixed into the timeless documentation.

Former article	Maintained destination	Preservation
articles/chat-and-council.md	guide/chat-and-council.md and architecture/council-runtime.md	Original retained in internal-notes/legacy-source/articles/chat-and-council.md
articles/embedded-firmware.md	guide/embedded-and-games.md	Original retained in internal-notes/legacy-source/articles/embedded-firmware.md
articles/workspaces.md	guide/projects-and-workspaces.md and architecture/project-data.md	Original retained in internal-notes/legacy-source/articles/workspaces.md
articles/security.md	architecture/onewire-security.md and architecture/system-overview.md	Original retained in internal-notes/legacy-source/articles/security.md
articles/game-director.md	guide/embedded-and-games.md and architecture/council-runtime.md	Original retained in internal-notes/legacy-source/articles/game-director.md
articles/documentation.md	guide/documentation.md and engineering/release-and-docs.md	Original retained in internal-notes/legacy-source/articles/documentation.md

Former article	Maintained destination	Preservation
articles/provider-qualified-council-benchmarking.md	guide/chat-and-council.md and reference/capability-map.md	Original retained in internal-notes/legacy-source/articles/provider-qualified-council-benchmarking.md
articles/build-policy-council-recovery.md	engineering/build-validation.md and architecture/council-runtime.md	Original retained in internal-notes/legacy-source/articles/build-policy-council-recovery.md
articles/removable-chat-ascii-console.md	guide/embedded-and-games.md	Original retained in internal-notes/legacy-source/articles/removable-chat-ascii-console.md

Why this structure is safer

- Readers see current behavior first.
- Architecture is grouped by boundary rather than by the order it was learned.
- Important AI Host and Council material remains prominent.
- Local archive paths and source-acquisition notes are not presented as product design.
- Repository archaeology remains possible when a maintainer needs the original context.

Reference

- [Capability map](#)
- [Design evolution and provenance](#)
- [Documentation migration map](#)
- [Complete API reference](#)

This section preserves context without turning temporary experiments into current architecture.

LocalGPT API reference

This reference is generated from LocalGPT.dll and its side-by-side LocalGPT.xml compiler documentation for version 2.3.6.

The namespace, type, and member pages below are generated by DocFX and are included in the complete versioned PDF.

Use the grouped API navigation to browse namespaces, types, properties, methods, events, and the other generated member sections.

LocalGPT documentation

Version 2.3.6

LocalGPT is a local-first AI workbench for direct chat, configurable AI Councils, project maintenance, persistent knowledge, provider-qualified model routing, embedded planning, game runtimes, and guarded local execution.

This site is the maintained product and architecture documentation. It deliberately separates stable design from historical experiments, so you can understand *what LocalGPT is now* without walking through every learning step that shaped it. 🐾

Choose a path

🌸 Use LocalGPT

Start with the application concepts, common workflows, and the boundaries around actions that can change files, run tools, or operate hardware.

[Open the user guide](#)

🧠 Understand the architecture

Follow the modular-monolith boundaries from Blazor UI through services, provider adapters, persistence, the AI Host control plane, Council orchestration, and 1-Wire transports.

[Explore the architecture](#)

🔧 Build and maintain it

Read the compilation truth, diagnostics policy, documentation pipeline, release checks, and the rules that keep generated work reviewable.

[Open engineering guidance](#)

📖 Look up details

Use the capability map, design evolution notes, documentation migration map, or the complete XML-generated API reference.

[Browse reference material](#)

Architecture at a glance

```

flowchart LR
    U[Human user] --> UI[Blazor + DevExpress UI]
    UI --> APP[Application services]
    APP --> COUNCIL[Chat and Council runtime]
    APP --> PROJECTS[Projects, workspaces and knowledge]
    APP --> HOST[Provider-qualified AI Host control plane]
    APP --> WIRE[Organic 1-Wire boundary]
    COUNCIL --> PROVIDERS[Ollama / OpenAI-compatible / cloud providers]
    PROJECTS --> DB[(SQLite + EF Core)]
    HOST --> PROVIDERS
    WIRE --> PEERS[Approved peers, publishers and devices]
```

The human request remains the authority. Model output, uploaded content, repository text, remote peers, and generated artifacts are data—not permission.

Complete documentation set

The conceptual pages are built together with compiler-generated XML documentation for public types and members. The same themed HTML site is shipped inside LocalGPT and published to GitHub Pages.

The packaged PDF is a readable portrait handbook: it contains every maintained guide, architecture, engineering, and reference chapter plus a complete linked inventory of all generated API pages. Detailed API members remain in the searchable HTML site, GitHub Pages, and the in-app viewer so the PDF stays compact and useful.

🐾 [Download the Kawaii handbook](#)

Complete API reference

All 853 reviewed generated API pages follow. The owner build regenerates them from the current compiled assembly and XML comments.

Class AdaptiveOllamaBenchmarkModelResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object AdaptiveOllamaBenchmarkModelResult

```
public sealed class AdaptiveOllamaBenchmarkModelResult
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkModelResult()

```
public AdaptiveOllamaBenchmarkModelResult()
```

🐾 Properties 8

BestProfile

```
public string BestProfile { get; set; }
```

BestScore

```
public double BestScore { get; set; }
```

Error

```
public string Error { get; set; }
```

InstalledSizeBytes

```
public long? InstalledSizeBytes { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

ParameterSize

```
public string ParameterSize { get; set; }
```

Profiles

```
public List<AdaptiveOllamaBenchmarkProfileResult> Profiles { get; set; }
```

StoppedBecauseImprovementWasBelowThreshold

```
public bool StoppedBecauseImprovementWasBelowThreshold { get; set; }
```

Class AdaptiveOllamaBenchmarkOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AdaptiveOllamaBenchmarkOptions

```
public sealed class AdaptiveOllamaBenchmarkOptions
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkOptions()

```
public AdaptiveOllamaBenchmarkOptions()
```

🐾 Properties 13

Endpoint

```
public string Endpoint { get; set; }
```

ImprovementThresholdPercent

```
public double ImprovementThresholdPercent { get; set; }
```

IncludePeerAuthoredTask

```
public bool IncludePeerAuthoredTask { get; set; }
```

MakeDefault

```
public bool MakeDefault { get; set; }
```

MaxModels

```
public int MaxModels { get; set; }
```

MaxProfilesPerModel

```
public int MaxProfilesPerModel { get; set; }
```

MaxSecondsPerCall

```
public int MaxSecondsPerCall { get; set; }
```

MaxTasks

```
public int MaxTasks { get; set; }
```

MaximumContextTokens

```
public int MaximumContextTokens { get; set; }
```

MaximumOutputTokens

```
public int MaximumOutputTokens { get; set; }
```

ModelNames

```
public List<string> ModelNames { get; set; }
```

PersistPreset

```
public bool PersistPreset { get; set; }
```

PresetName

```
public string PresetName { get; set; }
```

Class AdaptiveOllamaBenchmarkProfileResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AdaptiveOllamaBenchmarkProfileResult

```
public sealed class AdaptiveOllamaBenchmarkProfileResult
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkProfileResult()

```
public AdaptiveOllamaBenchmarkProfileResult()
```

🐾 Properties 10

AverageQualityScore

```
public double AverageQualityScore { get; set; }
```

AverageTokensPerSecond

```
public double AverageTokensPerSecond { get; set; }
```

AverageTotalMilliseconds

```
public double AverageTotalMilliseconds { get; set; }
```

ContextTokens

```
public int ContextTokens { get; set; }
```

NumBatch

```
public int NumBatch { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

OutputTokens

```
public int OutputTokens { get; set; }
```

ProfileName

```
public string ProfileName { get; set; }
```

Score

```
public double Score { get; set; }
```

Tasks

```
public List<AdaptiveOllamaBenchmarkTaskResult> Tasks { get; set; }
```

Class AdaptiveOllamaBenchmarkReport

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AdaptiveOllamaBenchmarkReport

```
public sealed class AdaptiveOllamaBenchmarkReport
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkReport()

```
public AdaptiveOllamaBenchmarkReport()
```

🐾 Properties 13

BestModel

```
public string BestModel { get; set; }
```

BestProfile

```
public string BestProfile { get; set; }
```

BestScore

```
public double BestScore { get; set; }
```

CompletedAtUtc

```
public DateTimeOffset CompletedAtUtc { get; set; }
```

Endpoint

```
public string Endpoint { get; set; }
```

HardwareSummary

```
public string HardwareSummary { get; set; }
```

Models

```
public List<AdaptiveOllamaBenchmarkModelResult> Models { get; set; }
```

PeerAuthoredTask

```
public string PeerAuthoredTask { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

SavedPresetId

```
public Guid? SavedPresetId { get; set; }
```

SavedPresetName

```
public string SavedPresetName { get; set; }
```

StartedAtUtc

```
public DateTimeOffset StartedAtUtc { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class AdaptiveOllamaBenchmarkTask

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object AdaptiveOllamaBenchmarkTask

```
public sealed class AdaptiveOllamaBenchmarkTask
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkTask()

```
public AdaptiveOllamaBenchmarkTask()
```

🐾 Properties 4

ExpectJson

```
public bool ExpectJson { get; set; }
```

ExpectedTokens

```
public List<string> ExpectedTokens { get; set; }
```

Name

```
public string Name { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

Class AdaptiveOllamaBenchmarkTaskResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object AdaptiveOllamaBenchmarkTaskResult

```
public sealed class AdaptiveOllamaBenchmarkTaskResult
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkTaskResult()

```
public AdaptiveOllamaBenchmarkTaskResult()
```

🐾 Properties 8

Error

```
public string Error { get; set; }
```

EvaluatedTokens

```
public int EvaluatedTokens { get; set; }
```

QualityScore

```
public double QualityScore { get; set; }
```

ResponsePreview

```
public string ResponsePreview { get; set; }
```

Succeeded

```
public bool Succeeded { get; set; }
```

TaskName

```
public string TaskName { get; set; }
```

TokensPerSecond

```
public double TokensPerSecond { get; set; }
```

TotalMilliseconds

```
public long TotalMilliseconds { get; set; }
```

Class AdaptiveOllamaTuningProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AdaptiveOllamaTuningProfile

```
public sealed class AdaptiveOllamaTuningProfile
```

🌟 Constructors 1

AdaptiveOllamaTuningProfile()

```
public AdaptiveOllamaTuningProfile()
```

🐾 Properties 5

ContextTokens

```
public int ContextTokens { get; set; }
```

Name

```
public string Name { get; set; }
```

NumBatch

```
public int NumBatch { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

OutputTokens

```
public int OutputTokens { get; set; }
```

Class AddLocalGptProjectTopicRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AddLocalGptProjectTopicRequest

```
public sealed class AddLocalGptProjectTopicRequest
```

🌟 Constructors 1

AddLocalGptProjectTopicRequest()

```
public AddLocalGptProjectTopicRequest()
```

🐾 Properties 4

Description

```
public string Description { get; set; }
```

Name

```
public string Name { get; set; }
```

Status

```
public string Status { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class AddLocalGptProjectVersionRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AddLocalGptProjectVersionRequest

```
public sealed class AddLocalGptProjectVersionRequest
```

🌟 Constructors 1

AddLocalGptProjectVersionRequest()

```
public AddLocalGptProjectVersionRequest()
```

🐾 Properties 5

IsCurrent

```
public bool IsCurrent { get; set; }
```

Notes

```
public string Notes { get; set; }
```

PathSnapshot

```
public string PathSnapshot { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Version

```
public string Version { get; set; }
```


Class AICoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AICoreOptions

```
public class AICoreOptions
```

🌟 Constructors 1

AICoreOptions()

```
public AICoreOptions()
```

🔑 Fields 1

AICore

```
public const string AICore = "AICore"
```

🐾 Properties 5

ChatGPTLocalCore

```
public ChatGPTLocalCoreOptions ChatGPTLocalCore { get; set; }
```

OllamaCore

```
public OllamaCoreOptions OllamaCore { get; set; }
```

OllamaCores

```
public List<OllamaCoreOptions> OllamaCores { get; set; }
```

OpenAICore

```
public OpenAICompatOptions OpenAICore { get; set; }
```

OpenAIServiceCore

```
public OpenAIServiceCoreOptions OpenAIServiceCore { get; set; }
```

Class AmbientLocalGptContextSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AmbientLocalGptContextSnapshot

Implements IEquatable < AmbientLocalGptContextSnapshot >

```
public sealed record AmbientLocalGptContextSnapshot : IEquatable<AmbientLocalGptContextSnapshot>
```

🌟 Constructors 1

AmbientLocalGptContextSnapshot(string, string, string, string, Guid?, Guid?, int, string, Guid?, string)

```
public AmbientLocalGptContextSnapshot(string CorrelationId, string ActorKind, string ActorDisplayName, string AuthorityKind = "", Guid? HumanProfileId = null, Guid? CouncilRunId = null, int CouncilRound = 0, string Phase = "", Guid? ApprovalRequestId = null, string Source = "")
```

🐾 Properties 11

ActorDisplayName

```
public string ActorDisplayName { get; init; }
```

ActorKind

```
public string ActorKind { get; init; }
```

ApprovalRequestId

```
public Guid? ApprovalRequestId { get; init; }
```

AuthorityKind

```
public string AuthorityKind { get; init; }
```

CorrelationId

```
public string CorrelationId { get; init; }
```

CouncilRound

```
public int CouncilRound { get; init; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; init; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; init; }
```

HumanProfileId

```
public Guid? HumanProfileId { get; init; }
```

Phase

```
public string Phase { get; init; }
```

Source

```
public string Source { get; init; }
```

⚙️ Methods 7

Deconstruct(out string, out string, out string, out string, out Guid?, out Guid?, out int, out string, out Guid?, out string)

```
public void Deconstruct(out string CorrelationId, out string ActorKind, out string ActorDisplayName, out string AuthorityKind, out Guid? HumanProfileId, out Guid? CouncilRunId, out int CouncilRound, out string Phase, out Guid? ApprovalRequestId, out string Source)
```

Equals(AmbientLocalGptContextSnapshot?)

```
public bool Equals(AmbientLocalGptContextSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

HasHumanApproval(LocalGptVocabularySnapshot)

```
public bool HasHumanApproval(LocalGptVocabularySnapshot vocabulary)
```

IsTrustedHumanInteraction(LocalGptVocabularySnapshot)

```
public bool IsTrustedHumanInteraction(LocalGptVocabularySnapshot vocabulary)
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(AmbientLocalGptContextSnapshot?, AmbientLocalGptContextSnapshot?)

```
public static bool operator ==(AmbientLocalGptContextSnapshot? left, AmbientLocalGptContextSnapshot? right)
```

operator !=(AmbientLocalGptContextSnapshot?, AmbientLocalGptContextSnapshot?)

```
public static bool operator !=(AmbientLocalGptContextSnapshot? left, AmbientLocalGptContextSnapshot? right)
```

Class AnalyzedUploadFile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object AnalyzedUploadFile

Implements IEquatable < AnalyzedUploadFile >

```
public sealed record AnalyzedUploadFile : IEquatable<AnalyzedUploadFile>
```

🌟 Constructors 1

AnalyzedUploadFile(ChatUploadWorkspaceFileSummary, string)

```
public AnalyzedUploadFile(ChatUploadWorkspaceFileSummary Summary, string Excerpt)
```

🐾 Properties 2

Excerpt

```
public string Excerpt { get; init; }
```

Summary

```
public ChatUploadWorkspaceFileSummary Summary { get; init; }
```

⚙️ Methods 5

Deconstruct(out ChatUploadWorkspaceFileSummary, out string)

```
public void Deconstruct(out ChatUploadWorkspaceFileSummary Summary, out string Excerpt)
```

Equals(AnalyzedUploadFile?)

```
public bool Equals(AnalyzedUploadFile? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(AnalyzedUploadFile?, AnalyzedUploadFile?)

```
public static bool operator ==(AnalyzedUploadFile? left, AnalyzedUploadFile? right)
```

operator !=(AnalyzedUploadFile?, AnalyzedUploadFile?)

```
public static bool operator !=(AnalyzedUploadFile? left, AnalyzedUploadFile? right)
```

Class ApplicationLogEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ApplicationLogEntry

```
public class ApplicationLogEntry
```

🌟 Constructors 1

ApplicationLogEntry()

```
public ApplicationLogEntry()
```

🐾 Properties 12

Category

```
public string Category { get; set; }
```

EventId

```
public int EventId { get; set; }
```

EventName

```
public string? EventName { get; set; }
```

Exception

```
public string? Exception { get; set; }
```

Id

```
[Key] public long Id { get; set; }
```

Level

```
public string Level { get; set; }
```

LogLevelValue

```
public int LogLevelValue { get; set; }
```

MachineName

```
public string MachineName { get; set; }
```

Message

```
public string Message { get; set; }
```

ProcessId

```
public int ProcessId { get; set; }
```

ThreadId

```
public int ThreadId { get; set; }
```

TimestampUtc

```
public DateTime TimestampUtc { get; set; }
```

Class ApplicationLogSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ApplicationLogSummary

Implements IEquatable < ApplicationLogSummary >

```
public sealed record ApplicationLogSummary : IEquatable<ApplicationLogSummary>
```

🌟 Constructors 1

ApplicationLogSummary(long, DateTime, string, int, string, int, string?, string, string?)

```
public ApplicationLogSummary(long Id, DateTime TimestampUtc, string Level, int LogLevelValue, string Category, int EventId, string? EventName, string Message, string? Exception)
```

🐾 Properties 9

Category

```
public string Category { get; init; }
```

EventId

```
public int EventId { get; init; }
```

EventName

```
public string? EventName { get; init; }
```

Exception

```
public string? Exception { get; init; }
```

Id

```
public long Id { get; init; }
```

Level

```
public string Level { get; init; }
```

LogLevelValue

```
public int LogLevelValue { get; init; }
```

Message

```
public string Message { get; init; }
```

TimestampUtc

```
public DateTime TimestampUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out long, out DateTime, out string, out int, out string, out int, out string?, out string, out string?)

```
public void Deconstruct(out long Id, out DateTime TimestampUtc, out string Level, out int LogLevelValue, out string Category, out int EventId, out string? EventName, out string Message, out string? Exception)
```

Equals(ApplicationLogSummary?)

```
public bool Equals(ApplicationLogSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(ApplicationLogSummary?, ApplicationLogSummary?)

```
public static bool operator ==(ApplicationLogSummary? left, ApplicationLogSummary? right)
```

operator !=(ApplicationLogSummary?, ApplicationLogSummary?)

```
public static bool operator !=(ApplicationLogSummary? left, ApplicationLogSummary? right)
```

api/LocalGPT.BusinessObjects.ApproveRevisionReadyForTestRequest.html

Class ApproveRevisionReadyForTestRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ApproveRevisionReadyForTestRequest

```
public sealed class ApproveRevisionReadyForTestRequest
```

🌟 Constructors 1

ApproveRevisionReadyForTestRequest()

```
public ApproveRevisionReadyForTestRequest()
```

🐾 Properties 4

CreateLosslessSnapshot

```
public bool CreateLosslessSnapshot { get; set; }
```

RequireTests

```
public bool RequireTests { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

VerificationId

```
public Guid VerificationId { get; set; }
```

Class ArtifactBuildExecutionResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactBuildExecutionResult

Implements IEquatable < ArtifactBuildExecutionResult >

```
public sealed record ArtifactBuildExecutionResult : IEquatable<ArtifactBuildExecutionResult>
```

🌟 Constructors 1

ArtifactBuildExecutionResult(string, int?, string, string, TimeSpan)

```
public ArtifactBuildExecutionResult(string Status, int? ExitCode, string StandardOutput, string StandardError, TimeSpan Duration)
```

🐾 Properties 7

Duration

```
public TimeSpan Duration { get; init; }
```

ExitCode

```
public int? ExitCode { get; init; }
```

StandardError

```
public string StandardError { get; init; }
```

StandardOutput

```
public string StandardOutput { get; init; }
```

Status

```
public string Status { get; init; }
```

Succeeded

```
public bool Succeeded { get; }
```

TimedOut

```
public bool TimedOut { get; }
```

⚙️ Methods 5

Deconstruct(out string, out int?, out string, out string, out TimeSpan)

```
public void Deconstruct(out string Status, out int? ExitCode, out string StandardOutput, out string StandardError, out TimeSpan Duration)
```

Equals(ArtifactBuildExecutionResult?)

```
public bool Equals(ArtifactBuildExecutionResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(ArtifactBuildExecutionResult?, ArtifactBuildExecutionResult?)

```
public static bool operator ==(ArtifactBuildExecutionResult? left, ArtifactBuildExecutionResult? right)
```

operator !=(ArtifactBuildExecutionResult?, ArtifactBuildExecutionResult?)

```
public static bool operator !=(ArtifactBuildExecutionResult? left, ArtifactBuildExecutionResult? right)
```


Class ArtifactBuildOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactBuildOptions

```
public sealed class ArtifactBuildOptions
```

🌟 Constructors 1

ArtifactBuildOptions()

```
public ArtifactBuildOptions()
```

🔗 Fields 1

SectionName

```
public const string SectionName = "ArtifactBuilds"
```

🐾 Properties 2

Enabled

```
public bool Enabled { get; set; }
```

MaxDurationSeconds

```
public int MaxDurationSeconds { get; set; }
```

Class ArtifactContractReport

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactContractReport

Implements IEquatable < ArtifactContractReport >

```
public sealed record ArtifactContractReport : IEquatable<ArtifactContractReport>
```

🌟 Constructors 1

ArtifactContractReport(string, string, IReadOnlyList<string>, IReadOnlyList<string>, string)

```
public ArtifactContractReport(string QualityStatus, string ContractStatus, IReadOnlyList<string> ContractChecks, IReadOnlyList<string> MissingRequirements, string Summary)
```

🐾 Properties 5

ContractChecks

```
public IReadOnlyList<string> ContractChecks { get; init; }
```

ContractStatus

```
public string ContractStatus { get; init; }
```

MissingRequirements

```
public IReadOnlyList<string> MissingRequirements { get; init; }
```

QualityStatus

```
public string QualityStatus { get; init; }
```

Summary

```
public string Summary { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out IReadOnlyList<string>, out IReadOnlyList<string>, out string)

```
public void Deconstruct(out string QualityStatus, out string ContractStatus, out IReadOnlyList<string> ContractChecks, out IReadOnlyList<string> MissingRequirements, out string Summary)
```

Equals(ArtifactContractReport?)

```
public bool Equals(ArtifactContractReport? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactContractReport?, ArtifactContractReport?)

```
public static bool operator ==(ArtifactContractReport? left, ArtifactContractReport? right)
```

operator !=(ArtifactContractReport?, ArtifactContractReport?)

```
public static bool operator !=(ArtifactContractReport? left, ArtifactContractReport? right)
```

Class ArtifactWorkspaceFileResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceFileResponse

Implements IEquatable < ArtifactWorkspaceFileResponse >

```
public sealed record ArtifactWorkspaceFileResponse : IEquatable<ArtifactWorkspaceFileResponse>
```

🌟 Constructors 1

ArtifactWorkspaceFileResponse(string, string, string, string, long, DateTime, string)

```
public ArtifactWorkspaceFileResponse(string WorkspaceName, string RootPath, string RelativePath, string FullPath, long Length, DateTime LastWriteTimeUtc, string Content)
```

🐾 Properties 7

Content

```
public string Content { get; init; }
```

FullPath

```
public string FullPath { get; init; }
```

LastWriteTimeUtc

```
public DateTime LastWriteTimeUtc { get; init; }
```

Length

```
public long Length { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out long, out DateTime, out string)

```
public void Deconstruct(out string WorkspaceName, out string RootPath, out string RelativePath, out string FullPath, out long Length, out DateTime LastWriteTimeUtc, out string Content)
```

Equals(ArtifactWorkspaceFileResponse?)

```
public bool Equals(ArtifactWorkspaceFileResponse? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceFileResponse?, ArtifactWorkspaceFileResponse?)

```
public static bool operator ==(ArtifactWorkspaceFileResponse? left, ArtifactWorkspaceFileResponse? right)
```

operator !=(ArtifactWorkspaceFileResponse?, ArtifactWorkspaceFileResponse?)

```
public static bool operator !=(ArtifactWorkspaceFileResponse? left, ArtifactWorkspaceFileResponse? right)
```

Class ArtifactWorkspaceFileSaveRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceFileSaveRequest

Implements IEquatable < ArtifactWorkspaceFileSaveRequest >

```
public sealed record ArtifactWorkspaceFileSaveRequest : IEquatable<ArtifactWorkspaceFileSaveRequest>
```

🌟 Constructors 1

ArtifactWorkspaceFileSaveRequest(string, string?)

```
public ArtifactWorkspaceFileSaveRequest(string RelativePath, string? Content)
```

🐾 Properties 2

Content

```
public string? Content { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string?)

```
public void Deconstruct(out string RelativePath, out string? Content)
```

Equals(ArtifactWorkspaceFileSaveRequest?)

```
public bool Equals(ArtifactWorkspaceFileSaveRequest? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceFileSaveRequest?, ArtifactWorkspaceFileSaveRequest?)

```
public static bool operator ==(ArtifactWorkspaceFileSaveRequest? left, ArtifactWorkspaceFileSaveRequest? right)
```

operator !=(ArtifactWorkspaceFileSaveRequest?, ArtifactWorkspaceFileSaveRequest?)

```
public static bool operator !=(ArtifactWorkspaceFileSaveRequest? left, ArtifactWorkspaceFileSaveRequest? right)
```

Class ArtifactWorkspaceFilesResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceFilesResponse

Implements IEquatable < ArtifactWorkspaceFilesResponse >

```
public sealed record ArtifactWorkspaceFilesResponse : IEquatable<ArtifactWorkspaceFilesResponse>
```

🌟 Constructors 1

ArtifactWorkspaceFilesResponse(string, string, List<ArtifactWorkspaceFileSummary>)

```
public ArtifactWorkspaceFilesResponse(string WorkspaceName, string RootPath, List<ArtifactWorkspaceFileSummary> Files)
```

🐾 Properties 3

Files

```
public List<ArtifactWorkspaceFileSummary> Files { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out List<ArtifactWorkspaceFileSummary>)

```
public void Deconstruct(out string WorkspaceName, out string RootPath, out List<ArtifactWorkspaceFileSummary> Files)
```

Equals(ArtifactWorkspaceFilesResponse?)

```
public bool Equals(ArtifactWorkspaceFilesResponse? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceFilesResponse?, ArtifactWorkspaceFilesResponse?)

```
public static bool operator ==(ArtifactWorkspaceFilesResponse? left, ArtifactWorkspaceFilesResponse? right)
```

operator !=(ArtifactWorkspaceFilesResponse?, ArtifactWorkspaceFilesResponse?)

```
public static bool operator !=(ArtifactWorkspaceFilesResponse? left, ArtifactWorkspaceFilesResponse? right)
```

Class ArtifactWorkspaceFileSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceFileSummary

Implements IEquatable < ArtifactWorkspaceFileSummary >

```
public sealed record ArtifactWorkspaceFileSummary : IEquatable<ArtifactWorkspaceFileSummary>
```

🌟 Constructors 1

ArtifactWorkspaceFileSummary(string, long, DateTime)

```
public ArtifactWorkspaceFileSummary(string RelativePath, long Length, DateTime LastWriteTimeUtc)
```

🐾 Properties 3

LastWriteTimeUtc

```
public DateTime LastWriteTimeUtc { get; init; }
```

Length

```
public long Length { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out long, out DateTime)

```
public void Deconstruct(out string RelativePath, out long Length, out DateTime LastWriteTimeUtc)
```

Equals(ArtifactWorkspaceFileSummary?)

```
public bool Equals(ArtifactWorkspaceFileSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceFileSummary?, ArtifactWorkspaceFileSummary?)

```
public static bool operator ==(ArtifactWorkspaceFileSummary? left, ArtifactWorkspaceFileSummary? right)
```

operator !=(ArtifactWorkspaceFileSummary?, ArtifactWorkspaceFileSummary?)

```
public static bool operator !=(ArtifactWorkspaceFileSummary? left, ArtifactWorkspaceFileSummary? right)
```

Class ArtifactWorkspaceListResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceListResponse

Implements IEquatable < ArtifactWorkspaceListResponse >

```
public sealed record ArtifactWorkspaceListResponse : IEquatable<ArtifactWorkspaceListResponse>
```

🌟 Constructors 1

ArtifactWorkspaceListResponse(string, string, int, ArtifactWorkspaceSummary?, List<ArtifactWorkspaceSummary>)

```
public ArtifactWorkspaceListResponse(string BaseUrl, string ArtifactRoot, int Count, ArtifactWorkspaceSummary? LatestWorkspace,
List<ArtifactWorkspaceSummary> Workspaces)
```

🐾 Properties 5

ArtifactRoot

```
public string ArtifactRoot { get; init; }
```

BaseUrl

```
public string BaseUrl { get; init; }
```

Count

```
public int Count { get; init; }
```

LatestWorkspace

```
public ArtifactWorkspaceSummary? LatestWorkspace { get; init; }
```

Workspaces

```
public List<ArtifactWorkspaceSummary> Workspaces { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out int, out ArtifactWorkspaceSummary?, out List<ArtifactWorkspaceSummary>)

```
public void Deconstruct(out string BaseUrl, out string ArtifactRoot, out int Count, out ArtifactWorkspaceSummary? LatestWorkspace, out
List<ArtifactWorkspaceSummary> Workspaces)
```

Equals(ArtifactWorkspaceListResponse?)

```
public bool Equals(ArtifactWorkspaceListResponse? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceListResponse?, ArtifactWorkspaceListResponse?)

```
public static bool operator ==(ArtifactWorkspaceListResponse? left, ArtifactWorkspaceListResponse? right)
```

operator !=(ArtifactWorkspaceListResponse?, ArtifactWorkspaceListResponse?)

```
public static bool operator !=(ArtifactWorkspaceListResponse? left, ArtifactWorkspaceListResponse? right)
```

Class ArtifactWorkspaceSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ArtifactWorkspaceSummary

Implements IEquatable < ArtifactWorkspaceSummary >

```
public sealed record ArtifactWorkspaceSummary : IEquatable<ArtifactWorkspaceSummary>
```

✨ Constructors 1

ArtifactWorkspaceSummary(string, string, DateTime, int, int, int, List<string>)

```
public ArtifactWorkspaceSummary(string WorkspaceName, string RootPath, DateTime LastWriteTimeUtc, int SourceFileCount, int RazorFileCount, int CSharpFileCount, List<string> ZipNames)
```

🐾 Properties 7

CSharpFileCount

```
public int CSharpFileCount { get; init; }
```

LastWriteTimeUtc

```
public DateTime LastWriteTimeUtc { get; init; }
```

RazorFileCount

```
public int RazorFileCount { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

SourceFileCount

```
public int SourceFileCount { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

ZipNames

```
public List<string> ZipNames { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out DateTime, out int, out int, out int, out List<string>)

```
public void Deconstruct(out string WorkspaceName, out string RootPath, out DateTime LastWriteTimeUtc, out int SourceFileCount, out int RazorFileCount, out int CSharpFileCount, out List<string> ZipNames)
```

Equals(ArtifactWorkspaceSummary?)

```
public bool Equals(ArtifactWorkspaceSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ArtifactWorkspaceSummary?, ArtifactWorkspaceSummary?)

```
public static bool operator ==(ArtifactWorkspaceSummary? left, ArtifactWorkspaceSummary? right)
```

operator !=(ArtifactWorkspaceSummary?, ArtifactWorkspaceSummary?)

```
public static bool operator !=(ArtifactWorkspaceSummary? left, ArtifactWorkspaceSummary? right)
```


Class BenchmarkTaskDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object BenchmarkTaskDefinition

Implements IEquatable < BenchmarkTaskDefinition >

```
public sealed record BenchmarkTaskDefinition : IEquatable<BenchmarkTaskDefinition>
```

🌟 Constructors 1

BenchmarkTaskDefinition(string, string, string, string, string, int, IReadOnlyList<string>, IReadOnlyList<string>, IReadOnlyList<string>)

```
public BenchmarkTaskDefinition(string Id, string Name, string Prompt, string ManualExpectedOutput, string LocalGptFinalAnswer, int LocalGptBuildabilityScore, IReadOnlyList<string> RequiredArtifactEntries, IReadOnlyList<string> ArchitectureEvidence, IReadOnlyList<string> WrongTemplateGuards)
```

🐾 Properties 9

ArchitectureEvidence

```
public IReadOnlyList<string> ArchitectureEvidence { get; init; }
```

Id

```
public string Id { get; init; }
```

LocalGptBuildabilityScore

```
public int LocalGptBuildabilityScore { get; init; }
```

LocalGptFinalAnswer

```
public string LocalGptFinalAnswer { get; init; }
```

ManualExpectedOutput

```
public string ManualExpectedOutput { get; init; }
```

Name

```
public string Name { get; init; }
```

Prompt

```
public string Prompt { get; init; }
```

RequiredArtifactEntries

```
public IReadOnlyList<string> RequiredArtifactEntries { get; init; }
```

WrongTemplateGuards

```
public IReadOnlyList<string> WrongTemplateGuards { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out int, out IReadOnlyList<string>, out IReadOnlyList<string>, out IReadOnlyList<string>)

```
public void Deconstruct(out string Id, out string Name, out string Prompt, out string ManualExpectedOutput, out string LocalGptFinalAnswer, out int LocalGptBuildabilityScore, out IReadOnlyList<string> RequiredArtifactEntries, out IReadOnlyList<string> ArchitectureEvidence, out IReadOnlyList<string> WrongTemplateGuards)
```

Equals(BenchmarkTaskDefinition?)

```
public bool Equals(BenchmarkTaskDefinition? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚙ Operators 2

operator ==(BenchmarkTaskDefinition?, BenchmarkTaskDefinition?)

```
public static bool operator ==(BenchmarkTaskDefinition? left, BenchmarkTaskDefinition? right)
```

operator !=(BenchmarkTaskDefinition?, BenchmarkTaskDefinition?)

```
public static bool operator !=(BenchmarkTaskDefinition? left, BenchmarkTaskDefinition? right)
```

api/LocalGPT.BusinessObjects.BuildDebugFileSummary.html

Class BuildDebugFileSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object BuildDebugFileSummary

```
public sealed class BuildDebugFileSummary
```

🌟 Constructors 1

BuildDebugFileSummary()

```
public BuildDebugFileSummary()
```

🐾 Properties 7

CopiedPath

```
public string? CopiedPath { get; set; }
```

Extension

```
public string Extension { get; set; }
```

LastWriteUtc

```
public DateTime LastWriteUtc { get; set; }
```

Length

```
public long Length { get; set; }
```

Name

```
public string Name { get; set; }
```

SourceArea

```
public string SourceArea { get; set; }
```

SourcePath

```
public string SourcePath { get; set; }
```

Class BuildDebugInventory

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object BuildDebugInventory

```
public sealed class BuildDebugInventory
```

🌟 Constructors 1

BuildDebugInventory()

```
public BuildDebugInventory()
```

🐾 Properties 6

ArtifactRoot

```
public string ArtifactRoot { get; set; }
```

CapturedAtUtc

```
public DateTime CapturedAtUtc { get; set; }
```

CopiedFiles

```
public bool CopiedFiles { get; set; }
```

Files

```
public List<BuildDebugFileSummary> Files { get; set; }
```

Succeeded

```
public bool Succeeded { get; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class CatalogEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CatalogEntry

Implements IEquatable < CatalogEntry >

```
public sealed record CatalogEntry : IEquatable<CatalogEntry>
```

✨ Constructors 1

CatalogEntry(string, string?, string?, string?, string?, string)

```
public CatalogEntry(string MinecraftVersion, string? FabricApiVersion, string? NeoForgeVersion, string? PaperApiVersion, string? JavaVersion, string Notes)
```

🐾 Properties 6

FabricApiVersion

```
public string? FabricApiVersion { get; init; }
```

JavaVersion

```
public string? JavaVersion { get; init; }
```

MinecraftVersion

```
public string MinecraftVersion { get; init; }
```

NeoForgeVersion

```
public string? NeoForgeVersion { get; init; }
```

Notes

```
public string Notes { get; init; }
```

PaperApiVersion

```
public string? PaperApiVersion { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string?, out string?, out string?, out string?, out string)

```
public void Deconstruct(out string MinecraftVersion, out string? FabricApiVersion, out string? NeoForgeVersion, out string? PaperApiVersion, out string? JavaVersion, out string Notes)
```

Equals(CatalogEntry?)

```
public bool Equals(CatalogEntry? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(CatalogEntry?, CatalogEntry?)

```
public static bool operator ==(CatalogEntry? left, CatalogEntry? right)
```

operator !=(CatalogEntry?, CatalogEntry?)

```
public static bool operator !=(CatalogEntry? left, CatalogEntry? right)
```

Class ChatFeedbackTarget

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Identifies an assistant message that can receive user feedback in Chat.

Inheritance object ChatFeedbackTarget

Implements IEquatable < ChatFeedbackTarget >

```
public sealed record ChatFeedbackTarget : IEquatable<ChatFeedbackTarget>
```

🌟 Constructors 1

ChatFeedbackTarget(int, string)

Identifies an assistant message that can receive user feedback in Chat.

```
public ChatFeedbackTarget(int SortOrder, string Label)
```

🐾 Properties 2

Label

```
public string Label { get; init; }
```

SortOrder

```
public int SortOrder { get; init; }
```

⚙️ Methods 5

Deconstruct(out int, out string)

```
public void Deconstruct(out int SortOrder, out string Label)
```

Equals(ChatFeedbackTarget?)

```
public bool Equals(ChatFeedbackTarget? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatFeedbackTarget?, ChatFeedbackTarget?)

```
public static bool operator ==(ChatFeedbackTarget? left, ChatFeedbackTarget? right)
```

operator !=(ChatFeedbackTarget?, ChatFeedbackTarget?)

```
public static bool operator !=(ChatFeedbackTarget? left, ChatFeedbackTarget? right)
```

Class ChatGPTLocalCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatGPTLocalCoreOptions

```
public class ChatGPTLocalCoreOptions
```

🌟 Constructors 1

ChatGPTLocalCoreOptions()

```
public ChatGPTLocalCoreOptions()
```

🔴 Fields 1

ChatGPTLocalCore

```
public const string ChatGPTLocalCore = "ChatGPTLocalCore"
```

🐾 Properties 9

ApiKey

```
public string ApiKey { get; set; }
```

AutoStartServer

```
public bool AutoStartServer { get; set; }
```

Endpoint

```
public string Endpoint { get; set; }
```

HealthTimeoutSeconds

```
public int HealthTimeoutSeconds { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

PythonEnvironment

```
public string? PythonEnvironment { get; set; }
```

StartCommand

```
public string? StartCommand { get; set; }
```

StartScript

```
public string? StartScript { get; set; }
```

WorkingDir

```
public string? WorkingDir { get; set; }
```

Class ChatMemoryConversation

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryConversation

```
public class ChatMemoryConversation
```

🌟 Constructors 1

ChatMemoryConversation()

```
public ChatMemoryConversation()
```

🐾 Properties 9

ApplicationVersion

```
public string ApplicationVersion { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Id

```
public Guid Id { get; set; }
```

Messages

```
public ICollection<ChatMemoryMessage> Messages { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; set; }
```

ProviderName

```
public string ProviderName { get; set; }
```

Title

```
public string Title { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class ChatMemoryConversationListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryConversationListParameters

```
public sealed class ChatMemoryConversationListParameters
```

🌟 Constructors 1

ChatMemoryConversationListParameters()

```
public ChatMemoryConversationListParameters()
```

🐾 Properties 1

Take

```
public int Take { get; set; }
```

Class ChatMemoryConversationSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryConversationSnapshot

Implements IEquatable < ChatMemoryConversationSnapshot >

```
public sealed record ChatMemoryConversationSnapshot : IEquatable<ChatMemoryConversationSnapshot>
```

✨ Constructors 1

ChatMemoryConversationSnapshot(Guid, string, string, DateTime, DateTime, List<BlazorChatMessage>)

```
public ChatMemoryConversationSnapshot(Guid Id, string Title, string ProviderName, DateTime CreatedAtUtc, DateTime UpdatedAtUtc, List<BlazorChatMessage> Messages)
```

🐾 Properties 9

ApplicationVersion

```
public string ApplicationVersion { get; init; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; init; }
```

Id

```
public Guid Id { get; init; }
```

Messages

```
public List<BlazorChatMessage> Messages { get; init; }
```

ProjectId

```
public Guid? ProjectId { get; init; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; init; }
```

ProviderName

```
public string ProviderName { get; init; }
```

Title

```
public string Title { get; init; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out string, out string, out DateTime, out DateTime, out List<BlazorChatMessage>)

```
public void Deconstruct(out Guid Id, out string Title, out string ProviderName, out DateTime CreatedAtUtc, out DateTime UpdatedAtUtc, out List<BlazorChatMessage> Messages)
```

Equals(ChatMemoryConversationSnapshot?)

```
public bool Equals(ChatMemoryConversationSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```


÷ Operators 2

operator ==(ChatMemoryConversationSnapshot?, ChatMemoryConversationSnapshot?)

```
public static bool operator ==(ChatMemoryConversationSnapshot? left, ChatMemoryConversationSnapshot? right)
```

operator !=(ChatMemoryConversationSnapshot?, ChatMemoryConversationSnapshot?)

```
public static bool operator !=(ChatMemoryConversationSnapshot? left, ChatMemoryConversationSnapshot? right)
```

Class ChatMemoryConversationSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryConversationSummary

Implements IEquatable < ChatMemoryConversationSummary >

```
public sealed record ChatMemoryConversationSummary : IEquatable<ChatMemoryConversationSummary>
```

✨ Constructors 1

ChatMemoryConversationSummary(Guid, string, string, DateTime, DateTime, int)

```
public ChatMemoryConversationSummary(Guid Id, string Title, string ProviderName, DateTime CreatedAtUtc, DateTime UpdatedAtUtc, int MessageCount)
```

🐾 Properties 10

ApplicationVersion

```
public string ApplicationVersion { get; init; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; init; }
```

DisplayName

```
public string DisplayName { get; }
```

Id

```
public Guid Id { get; init; }
```

MessageCount

```
public int MessageCount { get; init; }
```

ProjectId

```
public Guid? ProjectId { get; init; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; init; }
```

ProviderName

```
public string ProviderName { get; init; }
```

Title

```
public string Title { get; init; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out string, out string, out DateTime, out DateTime, out int)

```
public void Deconstruct(out Guid Id, out string Title, out string ProviderName, out DateTime CreatedAtUtc, out DateTime UpdatedAtUtc, out int MessageCount)
```

Equals(ChatMemoryConversationSummary?)

```
public bool Equals(ChatMemoryConversationSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(ChatMemoryConversationSummary?, ChatMemoryConversationSummary?)

```
public static bool operator ==(ChatMemoryConversationSummary? left, ChatMemoryConversationSummary? right)
```

operator !=(ChatMemoryConversationSummary?, ChatMemoryConversationSummary?)

```
public static bool operator !=(ChatMemoryConversationSummary? left, ChatMemoryConversationSummary? right)
```

api/LocalGPT.BusinessObjects.ChatMemoryMessage.html

Class ChatMemoryMessage

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryMessage

```
public class ChatMemoryMessage
```

🌟 Constructors 1

ChatMemoryMessage()

```
public ChatMemoryMessage()
```

🐾 Properties 11

Content

```
public string Content { get; set; }
```

Conversation

```
public ChatMemoryConversation Conversation { get; set; }
```

ConversationId

```
public Guid ConversationId { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

FeedbackComment

```
public string FeedbackComment { get; set; }
```

FeedbackUpdatedAtUtc

```
public DateTime? FeedbackUpdatedAtUtc { get; set; }
```

Id

```
public long Id { get; set; }
```

IsPositiveFeedback

```
public bool? IsPositiveFeedback { get; set; }
```

Role

```
public string Role { get; set; }
```

SortOrder

```
public int SortOrder { get; set; }
```

Thinking

```
public string? Thinking { get; set; }
```

Class ChatMemoryThought

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMemoryThought

Implements IEquatable < ChatMemoryThought >

```
public sealed record ChatMemoryThought : IEquatable<ChatMemoryThought>
```

🌟 Constructors 1

ChatMemoryThought(Guid, string, DateTime, string)

```
public ChatMemoryThought(Guid ConversationId, string ConversationTitle, DateTime CreatedAtUtc, string Thinking)
```

🐾 Properties 4

ConversationId

```
public Guid ConversationId { get; init; }
```

ConversationTitle

```
public string ConversationTitle { get; init; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; init; }
```

Thinking

```
public string Thinking { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out string, out DateTime, out string)

```
public void Deconstruct(out Guid ConversationId, out string ConversationTitle, out DateTime CreatedAtUtc, out string Thinking)
```

Equals(ChatMemoryThought?)

```
public bool Equals(ChatMemoryThought? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatMemoryThought?, ChatMemoryThought?)

```
public static bool operator ==(ChatMemoryThought? left, ChatMemoryThought? right)
```

operator !=(ChatMemoryThought?, ChatMemoryThought?)

```
public static bool operator !=(ChatMemoryThought? left, ChatMemoryThought? right)
```

Class ChatMessageFeedbackSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatMessageFeedbackSnapshot

Implements IEquatable < ChatMessageFeedbackSnapshot >

```
public sealed record ChatMessageFeedbackSnapshot : IEquatable<ChatMessageFeedbackSnapshot>
```

🌟 Constructors 1

ChatMessageFeedbackSnapshot(long, Guid, int, string, string, bool?, string, DateTime?)

```
public ChatMessageFeedbackSnapshot(long MessageId, Guid ConversationId, int SortOrder, string Role, string Preview, bool? IsPositive, string Comment, DateTime? UpdatedAtUtc)
```

🐾 Properties 8

Comment

```
public string Comment { get; init; }
```

ConversationId

```
public Guid ConversationId { get; init; }
```

IsPositive

```
public bool? IsPositive { get; init; }
```

MessageId

```
public long MessageId { get; init; }
```

Preview

```
public string Preview { get; init; }
```

Role

```
public string Role { get; init; }
```

SortOrder

```
public int SortOrder { get; init; }
```

UpdatedAtUtc

```
public DateTime? UpdatedAtUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out long, out Guid, out int, out string, out string, out bool?, out string, out DateTime?)

```
public void Deconstruct(out long MessageId, out Guid ConversationId, out int SortOrder, out string Role, out string Preview, out bool? IsPositive, out string Comment, out DateTime? UpdatedAtUtc)
```

Equals(ChatMessageFeedbackSnapshot?)

```
public bool Equals(ChatMessageFeedbackSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatMessageFeedbackSnapshot?, ChatMessageFeedbackSnapshot?)

```
public static bool operator ==(ChatMessageFeedbackSnapshot? left, ChatMessageFeedbackSnapshot? right)
```

operator !=(ChatMessageFeedbackSnapshot?, ChatMessageFeedbackSnapshot?)

```
public static bool operator !=(ChatMessageFeedbackSnapshot? left, ChatMessageFeedbackSnapshot? right)
```

Enum ChatResponseProtocol

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Identifies the wire/text convention emitted by a model. Each non-auto protocol has its own DI profile so control tokens from one model family are never applied to another family's response stream.

```
public enum ChatResponseProtocol
```

Fields 1

Class ChatSessionContextSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatSessionContextSnapshot

Implements IEquatable < ChatSessionContextSnapshot >

```
public sealed record ChatSessionContextSnapshot : IEquatable<ChatSessionContextSnapshot>
```

Constructors 1

ChatSessionContextSnapshot(Guid?, Guid?, Guid?, string)

```
public ChatSessionContextSnapshot(Guid? ConversationId, Guid? ProjectId, Guid? ProjectVersionId, string ApplicationVersion)
```

Properties 4

ApplicationVersion

```
public string ApplicationVersion { get; init; }
```

ConversationId

```
public Guid? ConversationId { get; init; }
```

ProjectId

```
public Guid? ProjectId { get; init; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; init; }
```

Methods 5

Deconstruct(out Guid?, out Guid?, out Guid?, out string)

```
public void Deconstruct(out Guid? ConversationId, out Guid? ProjectId, out Guid? ProjectVersionId, out string ApplicationVersion)
```

Equals(ChatSessionContextSnapshot?)

```
public bool Equals(ChatSessionContextSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(ChatSessionContextSnapshot?, ChatSessionContextSnapshot?)

```
public static bool operator ==(ChatSessionContextSnapshot? left, ChatSessionContextSnapshot? right)
```

operator !=(ChatSessionContextSnapshot?, ChatSessionContextSnapshot?)

```
public static bool operator !=(ChatSessionContextSnapshot? left, ChatSessionContextSnapshot? right)
```

Class ChatUploadWorkspaceFileReadResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceFileReadResult

Implements IEquatable < ChatUploadWorkspaceFileReadResult >

```
public sealed record ChatUploadWorkspaceFileReadResult : IEquatable<ChatUploadWorkspaceFileReadResult>
```

🌟 Constructors 1

ChatUploadWorkspaceFileReadResult(string, string, string, string, long, string)

```
public ChatUploadWorkspaceFileReadResult(string WorkspaceName, string RelativePath, string FullPath, string Kind, long Length, string Content)
```

🐾 Properties 6

Content

```
public string Content { get; init; }
```

FullPath

```
public string FullPath { get; init; }
```

Kind

```
public string Kind { get; init; }
```

Length

```
public long Length { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out long, out string)

```
public void Deconstruct(out string WorkspaceName, out string RelativePath, out string FullPath, out string Kind, out long Length, out string Content)
```

Equals(ChatUploadWorkspaceFileReadResult?)

```
public bool Equals(ChatUploadWorkspaceFileReadResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(ChatUploadWorkspaceFileReadResult?, ChatUploadWorkspaceFileReadResult?)

```
public static bool operator ==(ChatUploadWorkspaceFileReadResult? left, ChatUploadWorkspaceFileReadResult? right)
```

operator !=(ChatUploadWorkspaceFileReadResult?, ChatUploadWorkspaceFileReadResult?)

```
public static bool operator !=(ChatUploadWorkspaceFileReadResult? left, ChatUploadWorkspaceFileReadResult? right)
```


Class ChatUploadWorkspaceFileSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceFileSummary

Implements IEquatable < ChatUploadWorkspaceFileSummary >

```
public sealed record ChatUploadWorkspaceFileSummary : IEquatable<ChatUploadWorkspaceFileSummary>
```

🌟 Constructors 1

ChatUploadWorkspaceFileSummary(string, string, long, DateTime, bool, string)

```
public ChatUploadWorkspaceFileSummary(string RelativePath, string Kind, long Length, DateTime LastWriteTimeUtc, bool IncludedInPrompt, string Note)
```

🐾 Properties 6

IncludedInPrompt

```
public bool IncludedInPrompt { get; init; }
```

Kind

```
public string Kind { get; init; }
```

LastWriteTimeUtc

```
public DateTime LastWriteTimeUtc { get; init; }
```

Length

```
public long Length { get; init; }
```

Note

```
public string Note { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out long, out DateTime, out bool, out string)

```
public void Deconstruct(out string RelativePath, out string Kind, out long Length, out DateTime LastWriteTimeUtc, out bool IncludedInPrompt, out string Note)
```

Equals(ChatUploadWorkspaceFileSummary?)

```
public bool Equals(ChatUploadWorkspaceFileSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatUploadWorkspaceFileSummary?, ChatUploadWorkspaceFileSummary?)

```
public static bool operator ==(ChatUploadWorkspaceFileSummary? left, ChatUploadWorkspaceFileSummary? right)
```

operator !=(ChatUploadWorkspaceFileSummary?, ChatUploadWorkspaceFileSummary?)

```
public static bool operator !=(ChatUploadWorkspaceFileSummary? left, ChatUploadWorkspaceFileSummary? right)
```

Class ChatUploadWorkspaceInputFile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceInputFile

Implements IEquatable < ChatUploadWorkspaceInputFile >

```
public sealed record ChatUploadWorkspaceInputFile : IEquatable<ChatUploadWorkspaceInputFile>
```

🌟 Constructors 1

ChatUploadWorkspaceInputFile(string, string, long, ReadOnlyMemory<byte>)

```
public ChatUploadWorkspaceInputFile(string Name, string ContentType, long SizeBytes, ReadOnlyMemory<byte> Data)
```

🐾 Properties 4

ContentType

```
public string ContentType { get; init; }
```

Data

```
public ReadOnlyMemory<byte> Data { get; init; }
```

Name

```
public string Name { get; init; }
```

SizeBytes

```
public long SizeBytes { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out long, out ReadOnlyMemory<byte>)

```
public void Deconstruct(out string Name, out string ContentType, out long SizeBytes, out ReadOnlyMemory<byte> Data)
```

Equals(ChatUploadWorkspaceInputFile?)

```
public bool Equals(ChatUploadWorkspaceInputFile? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatUploadWorkspaceInputFile?, ChatUploadWorkspaceInputFile?)

```
public static bool operator ==(ChatUploadWorkspaceInputFile? left, ChatUploadWorkspaceInputFile? right)
```

operator !=(ChatUploadWorkspaceInputFile?, ChatUploadWorkspaceInputFile?)

```
public static bool operator !=(ChatUploadWorkspaceInputFile? left, ChatUploadWorkspaceInputFile? right)
```

Class ChatUploadWorkspaceResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceResult

Implements IEquatable < ChatUploadWorkspaceResult >

```
public sealed record ChatUploadWorkspaceResult : IEquatable<ChatUploadWorkspaceResult>
```

🌟 Constructors 1

ChatUploadWorkspaceResult(string, string, string, string, DateTimeOffset, IReadOnlyList<ChatUploadWorkspaceFileSummary>, IReadOnlyList<string>, string)

```
public ChatUploadWorkspaceResult(string WorkspaceName, string RootPath, string ManifestPath, string ContextPath, DateTimeOffset CreatedAtUtc,
IReadOnlyList<ChatUploadWorkspaceFileSummary> Files, IReadOnlyList<string> Warnings, string ContextMarkdown)
```

🐾 Properties 10

CharacterCount

```
public int CharacterCount { get; }
```

ContextMarkdown

```
public string ContextMarkdown { get; init; }
```

ContextPath

```
public string ContextPath { get; init; }
```

CreatedAtUtc

```
public DateTimeOffset CreatedAtUtc { get; init; }
```

FileCount

```
public int FileCount { get; }
```

Files

```
public IReadOnlyList<ChatUploadWorkspaceFileSummary> Files { get; init; }
```

ManifestPath

```
public string ManifestPath { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

Warnings

```
public IReadOnlyList<string> Warnings { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out DateTimeOffset, out IReadOnlyList<ChatUploadWorkspaceFileSummary>, out IReadOnlyList<string>, out string)

```
public void Deconstruct(out string WorkspaceName, out string RootPath, out string ManifestPath, out string ContextPath, out DateTimeOffset CreatedAtUtc,
out IReadOnlyList<ChatUploadWorkspaceFileSummary> Files, out IReadOnlyList<string> Warnings, out string ContextMarkdown)
```

Equals(ChatUploadWorkspaceResult?)

```
public bool Equals(ChatUploadWorkspaceResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(ChatUploadWorkspaceResult?, ChatUploadWorkspaceResult?)

```
public static bool operator ==(ChatUploadWorkspaceResult? left, ChatUploadWorkspaceResult? right)
```

operator !=(ChatUploadWorkspaceResult?, ChatUploadWorkspaceResult?)

```
public static bool operator !=(ChatUploadWorkspaceResult? left, ChatUploadWorkspaceResult? right)
```

Class ChatUploadWorkspaceSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceSummary

Implements IEquatable < ChatUploadWorkspaceSummary >

```
public sealed record ChatUploadWorkspaceSummary : IEquatable<ChatUploadWorkspaceSummary>
```

🌟 Constructors 1

ChatUploadWorkspaceSummary(string, string, DateTimeOffset, DateTime, int, long, string)

```
public ChatUploadWorkspaceSummary(string WorkspaceName, string RootPath, DateTimeOffset CreatedAtUtc, DateTime LastWriteTimeUtc, int FileCount, long TotalBytes, string ContextPath)
```

🐾 Properties 7

ContextPath

```
public string ContextPath { get; init; }
```

CreatedAtUtc

```
public DateTimeOffset CreatedAtUtc { get; init; }
```

FileCount

```
public int FileCount { get; init; }
```

LastWriteTimeUtc

```
public DateTime LastWriteTimeUtc { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

TotalBytes

```
public long TotalBytes { get; init; }
```

WorkspaceName

```
public string WorkspaceName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out DateTimeOffset, out DateTime, out int, out long, out string)

```
public void Deconstruct(out string WorkspaceName, out string RootPath, out DateTimeOffset CreatedAtUtc, out DateTime LastWriteTimeUtc, out int FileCount, out long TotalBytes, out string ContextPath)
```

Equals(ChatUploadWorkspaceSummary?)

```
public bool Equals(ChatUploadWorkspaceSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ChatUploadWorkspaceSummary?, ChatUploadWorkspaceSummary?)

```
public static bool operator ==(ChatUploadWorkspaceSummary? left, ChatUploadWorkspaceSummary? right)
```

operator !=(ChatUploadWorkspaceSummary?, ChatUploadWorkspaceSummary?)

```
public static bool operator !=(ChatUploadWorkspaceSummary? left, ChatUploadWorkspaceSummary? right)
```

Class CodeDomTypeSpec

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeDomTypeSpec

```
public sealed class CodeDomTypeSpec
```

🌟 Constructors 1

CodeDomTypeSpec()

```
public CodeDomTypeSpec()
```

🐾 Properties 6

MethodName

```
public string MethodName { get; set; }
```

MethodResult

```
public string MethodResult { get; set; }
```

Namespace

```
public string Namespace { get; set; }
```

RelativePath

```
public string RelativePath { get; set; }
```

Summary

```
public string Summary { get; set; }
```

TypeName

```
public string TypeName { get; set; }
```

Class CodeGenerationChangeReview

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationChangeReview

```
public sealed class CodeGenerationChangeReview
```

🌟 Constructors 1

CodeGenerationChangeReview()

```
public CodeGenerationChangeReview()
```

🐾 Properties 23

ApprovalConsumed

```
public bool ApprovalConsumed { get; set; }
```

BuildStatus

```
public string BuildStatus { get; set; }
```

ChangeSummary

```
public string ChangeSummary { get; set; }
```

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; set; }
```

CouncilSummary

```
public string CouncilSummary { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CurrentProjectState

```
public string CurrentProjectState { get; set; }
```

DecidedAtUtc

```
public DateTime? DecidedAtUtc { get; set; }
```

DecisionNote

```
public string DecisionNote { get; set; }
```

Goal

```
public string Goal { get; set; }
```

Id

```
public Guid Id { get; set; }
```

PayloadJson

```
public string PayloadJson { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectRevisionId

```
public Guid? ProjectRevisionId { get; set; }
```

ProjectTopicId

```
public Guid? ProjectTopicId { get; set; }
```

ReviewHash

```
public string ReviewHash { get; set; }
```

SafetySummary

```
public string SafetySummary { get; set; }
```

Status

```
public string Status { get; set; }
```

Title

```
public string Title { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

WorkspaceName

```
public string WorkspaceName { get; set; }
```

ZipFileName

```
public string ZipFileName { get; set; }
```


Class CodeGenerationExecutionResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationExecutionResult

```
public sealed class CodeGenerationExecutionResult
```

🌟 Constructors 1

CodeGenerationExecutionResult()

```
public CodeGenerationExecutionResult()
```

🐾 Properties 10

BuildStatus

```
public string BuildStatus { get; set; }
```

DownloadUrl

```
public string DownloadUrl { get; set; }
```

ReviewHash

```
public string ReviewHash { get; set; }
```

ReviewId

```
public Guid ReviewId { get; set; }
```

Status

```
public string Status { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

WorkspaceName

```
public string WorkspaceName { get; set; }
```

WorkspacePath

```
public string WorkspacePath { get; set; }
```

WrittenFiles

```
public List<string> WrittenFiles { get; set; }
```

ZipFileName

```
public string ZipFileName { get; set; }
```

Class CodeGenerationFileReview

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CodeGenerationFileReview

```
public sealed class CodeGenerationFileReview
```

🌟 Constructors 1

CodeGenerationFileReview()

```
public CodeGenerationFileReview()
```

🐾 Properties 4

CharacterCount

```
public int CharacterCount { get; set; }
```

ContentHash

```
public string ContentHash { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

RelativePath

```
public string RelativePath { get; set; }
```

Class CodeGenerationFileSpec

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CodeGenerationFileSpec

```
public sealed class CodeGenerationFileSpec
```

🌟 Constructors 1

CodeGenerationFileSpec()

```
public CodeGenerationFileSpec()
```

🐾 Properties 3

Content

```
public string Content { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

RelativePath

```
public string RelativePath { get; set; }
```

Class CodeGenerationOutputKinds

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CodeGenerationOutputKinds

```
public sealed class CodeGenerationOutputKinds
```

Fields 7

CSharpScript

```
public const string CSharpScript = "CSharpScript"
```

ClassLibrary

```
public const string ClassLibrary = "ClassLibrary"
```

ConsoleApplication

```
public const string ConsoleApplication = "ConsoleApplication"
```

JavaScriptModule

```
public const string JavaScriptModule = "JavaScriptModule"
```

LocalGptAddon

```
public const string LocalGptAddon = "LocalGptAddon"
```

Solution

```
public const string Solution = "Solution"
```

SourceFiles

```
public const string SourceFiles = "SourceFiles"
```

Class CodeGenerationOutputSpec

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationOutputSpec

```
public sealed class CodeGenerationOutputSpec
```

🌟 Constructors 1

CodeGenerationOutputSpec()

```
public CodeGenerationOutputSpec()
```

🐾 Properties 6

Description

```
public string Description { get; set; }
```

Kind

```
public string Kind { get; set; }
```

Name

```
public string Name { get; set; }
```

RelativeDirectory

```
public string RelativeDirectory { get; set; }
```

RootNamespace

```
public string RootNamespace { get; set; }
```

TargetFramework

```
public string TargetFramework { get; set; }
```

Class CodeGenerationReviewExecuteParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewExecuteParameters

```
public sealed class CodeGenerationReviewExecuteParameters
```

🌟 Constructors 1

CodeGenerationReviewExecuteParameters()

```
public CodeGenerationReviewExecuteParameters()
```

🐾 Properties 2

Request

```
public ExecuteCodeGenerationReviewRequest Request { get; set; }
```

ReviewId

```
public Guid ReviewId { get; set; }
```

Class CodeGenerationReviewGetParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewGetParameters

```
public sealed class CodeGenerationReviewGetParameters
```

🌟 Constructors 1

CodeGenerationReviewGetParameters()

```
public CodeGenerationReviewGetParameters()
```

🐾 Properties 1

ReviewId

```
public Guid ReviewId { get; set; }
```

Class CodeGenerationReviewListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewListParameters

```
public sealed class CodeGenerationReviewListParameters
```

🌟 Constructors 1

CodeGenerationReviewListParameters()

```
public CodeGenerationReviewListParameters()
```

🐾 Properties 2

ProjectId

```
public Guid? ProjectId { get; set; }
```

Take

```
public int Take { get; set; }
```

Class CodeGenerationReviewPayload

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewPayload

```
public sealed class CodeGenerationReviewPayload
```

🌟 Constructors 1

CodeGenerationReviewPayload()

```
public CodeGenerationReviewPayload()
```

🐾 Properties 3

CodeDomTypes

```
public List<CodeDomTypeSpec> CodeDomTypes { get; set; }
```

Files

```
public List<CodeGenerationFileSpec> Files { get; set; }
```

Outputs

```
public List<CodeGenerationOutputSpec> Outputs { get; set; }
```

Class CodeGenerationReviewRejectParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewRejectParameters

```
public sealed class CodeGenerationReviewRejectParameters
```

🌟 Constructors 1

CodeGenerationReviewRejectParameters()

```
public CodeGenerationReviewRejectParameters()
```

🐾 Properties 2

Request

```
public RejectCodeGenerationReviewRequest Request { get; set; }
```

ReviewId

```
public Guid ReviewId { get; set; }
```

Class CodeGenerationReviewSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewSnapshot

```
public sealed class CodeGenerationReviewSnapshot
```

🌟 Constructors 1

CodeGenerationReviewSnapshot()

```
public CodeGenerationReviewSnapshot()
```

🐾 Properties 25

ApprovalConsumed

```
public bool ApprovalConsumed { get; set; }
```

BuildStatus

```
public string BuildStatus { get; set; }
```

ChangeSummary

```
public string ChangeSummary { get; set; }
```

CodeDomTypes

```
public List<CodeDomTypeSpec> CodeDomTypes { get; set; }
```

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; set; }
```

CouncilSummary

```
public string CouncilSummary { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CurrentProjectState

```
public string CurrentProjectState { get; set; }
```

DecidedAtUtc

```
public DateTime? DecidedAtUtc { get; set; }
```

DecisionNote

```
public string DecisionNote { get; set; }
```

Files

```
public List<CodeGenerationFileReview> Files { get; set; }
```

Goal

```
public string Goal { get; set; }
```

Id

```
public Guid Id { get; set; }
```

Outputs

```
public List<CodeGenerationOutputSpec> Outputs { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectRevisionId

```
public Guid? ProjectRevisionId { get; set; }
```

ProjectTopicId

```
public Guid? ProjectTopicId { get; set; }
```

ReviewHash

```
public string ReviewHash { get; set; }
```

SafetySummary

```
public string SafetySummary { get; set; }
```

Status

```
public string Status { get; set; }
```

Title

```
public string Title { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

WorkspaceName

```
public string WorkspaceName { get; set; }
```

ZipFileName

```
public string ZipFileName { get; set; }
```

api/LocalGPT.BusinessObjects.CodeGenerationReviewStatuses.html

Class CodeGenerationReviewStatuses

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CodeGenerationReviewStatuses

```
public sealed class CodeGenerationReviewStatuses
```

Fields 7

AwaitingUserDecision

```
public const string AwaitingUserDecision = "AwaitingUserDecision"
```

BuildFailed

```
public const string BuildFailed = "BuildFailed"
```

BuildPassed

```
public const string BuildPassed = "BuildPassed"
```

Failed

```
public const string Failed = "Failed"
```

Generated

```
public const string Generated = "Generated"
```

Generating

```
public const string Generating = "Generating"
```

Rejected

```
public const string Rejected = "Rejected"
```


Class CommandExecutionResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CommandExecutionResult

```
public class CommandExecutionResult
```

🌟 Constructors 1

CommandExecutionResult()

```
public CommandExecutionResult()
```

🐾 Properties 15

Arguments

```
public string Arguments { get; set; }
```

CommandProfile

```
public string CommandProfile { get; set; }
```

CompletedAtUtc

```
public DateTime CompletedAtUtc { get; set; }
```

Duration

```
public TimeSpan Duration { get; set; }
```

ExitCode

```
public int ExitCode { get; set; }
```

FileName

```
public string FileName { get; set; }
```

PolicyDecision

```
public string PolicyDecision { get; set; }
```

PolicyReason

```
public string PolicyReason { get; set; }
```

StandardError

```
public string StandardError { get; set; }
```

StandardOutput

```
public string StandardOutput { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

StderrPath

```
public string StderrPath { get; set; }
```

StdoutPath

```
public string StdoutPath { get; set; }
```

Succeeded

```
public bool Succeeded { get; }
```

WorkingDirectory

```
public string WorkingDirectory { get; set; }
```

Class CommandPolicyDecision

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CommandPolicyDecision

Implements IEquatable < CommandPolicyDecision >

```
public sealed record CommandPolicyDecision : IEquatable<CommandPolicyDecision>
```

🌟 Constructors 1

CommandPolicyDecision(bool, string, string, string)

```
public CommandPolicyDecision(bool Allowed, string Decision, string Reason, string Profile)
```

🐾 Properties 4

Allowed

```
public bool Allowed { get; init; }
```

Decision

```
public string Decision { get; init; }
```

Profile

```
public string Profile { get; init; }
```

Reason

```
public string Reason { get; init; }
```

⚙️ Methods 5

Deconstruct(out bool, out string, out string, out string)

```
public void Deconstruct(out bool Allowed, out string Decision, out string Reason, out string Profile)
```

Equals(CommandPolicyDecision?)

```
public bool Equals(CommandPolicyDecision? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(CommandPolicyDecision?, CommandPolicyDecision?)

```
public static bool operator ==(CommandPolicyDecision? left, CommandPolicyDecision? right)
```

operator !=(CommandPolicyDecision?, CommandPolicyDecision?)

```
public static bool operator !=(CommandPolicyDecision? left, CommandPolicyDecision? right)
```

Class ComponentActivitySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ComponentActivitySnapshot

Implements IEquatable < ComponentActivitySnapshot >

```
public sealed record ComponentActivitySnapshot : IEquatable<ComponentActivitySnapshot>
```

🌟 Constructors 1

ComponentActivitySnapshot(DateTimeOffset, string, string, string, string, string?)

```
public ComponentActivitySnapshot(DateTimeOffset TimestampUtc, string Component, string Operation, string Status, string Summary, string? Route)
```

🐾 Properties 6

Component

```
public string Component { get; init; }
```

Operation

```
public string Operation { get; init; }
```

Route

```
public string? Route { get; init; }
```

Status

```
public string Status { get; init; }
```

Summary

```
public string Summary { get; init; }
```

TimestampUtc

```
public DateTimeOffset TimestampUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out DateTimeOffset, out string, out string, out string, out string, out string?)

```
public void Deconstruct(out DateTimeOffset TimestampUtc, out string Component, out string Operation, out string Status, out string Summary, out string? Route)
```

Equals(ComponentActivitySnapshot?)

```
public bool Equals(ComponentActivitySnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ComponentActivitySnapshot?, ComponentActivitySnapshot?)

```
public static bool operator ==(ComponentActivitySnapshot? left, ComponentActivitySnapshot? right)
```

operator !=(ComponentActivitySnapshot?, ComponentActivitySnapshot?)

```
public static bool operator !=(ComponentActivitySnapshot? left, ComponentActivitySnapshot? right)
```

Class ConfigurationRoot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ConfigurationRoot

```
public class ConfigurationRoot
```

🌟 Constructors 1

ConfigurationRoot()

```
public ConfigurationRoot()
```

🔴 Fields 1

Configuration

```
public const string Configuration = "Configuration"
```

🐾 Properties 4

AICore

```
public AICoreOptions? AICore { get; set; }
```

ConnectionStringsCore

```
public ConnectionStringsCoreOptions? ConnectionStringsCore { get; set; }
```

LoggingCore

```
public LoggingCoreOptions? LoggingCore { get; set; }
```

PythonCore

```
public PythonCoreOptions? PythonCore { get; set; }
```

Class ConnectionStringsCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ConnectionStringsCoreOptions

```
public class ConnectionStringsCoreOptions
```

🌟 Constructors 1

ConnectionStringsCoreOptions()

```
public ConnectionStringsCoreOptions()
```

🔴 Fields 1

ConnectionStringsCore

```
public const string ConnectionStringsCore = "ConnectionStringsCore"
```

🐾 Properties 3

ConnectionString

```
public string? ConnectionString { get; set; }
```

DefaultConnection

```
public string? DefaultConnection { get; set; }
```

EasyTestConnectionString

```
public string? EasyTestConnectionString { get; set; }
```

Class CouncilArtifact

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilArtifact

```
public sealed class CouncilArtifact
```

🌟 Constructors 1

CouncilArtifact()

```
public CouncilArtifact()
```

🐾 Properties 9

ContractChecks

```
public List<string> ContractChecks { get; set; }
```

ContractStatus

```
public string ContractStatus { get; set; }
```

DownloadUrl

```
public string DownloadUrl { get; set; }
```

FilePath

```
public string FilePath { get; set; }
```

Kind

```
public string Kind { get; set; }
```

MissingRequirements

```
public List<string> MissingRequirements { get; set; }
```

Name

```
public string Name { get; set; }
```

QualityStatus

```
public string QualityStatus { get; set; }
```

Summary

```
public string Summary { get; set; }
```

Class CouncilCodeGenerationPlanResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilCodeGenerationPlanResult

```
public sealed class CouncilCodeGenerationPlanResult
```

🌟 Constructors 1

CouncilCodeGenerationPlanResult()

```
public CouncilCodeGenerationPlanResult()
```

🐾 Properties 4

Found

```
public bool Found { get; set; }
```

Payload

```
public CodeGenerationReviewPayload Payload { get; set; }
```

SourceFormat

```
public string SourceFormat { get; set; }
```

Warning

```
public string Warning { get; set; }
```

Class CouncilDxFunctionCallRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilDxFunctionCallRequest

```
public sealed class CouncilDxFunctionCallRequest
```

🌟 Constructors 1

CouncilDxFunctionCallRequest()

```
public CouncilDxFunctionCallRequest()
```

🐾 Properties 3

FunctionName

```
public string FunctionName { get; set; }
```

Parameters

```
public JsonElement Parameters { get; set; }
```

Reason

```
public string Reason { get; set; }
```

Class CouncilDxFunctionPolicy

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CouncilDxFunctionPolicy

```
public sealed class CouncilDxFunctionPolicy
```

🌟 Constructors 1

CouncilDxFunctionPolicy()

```
public CouncilDxFunctionPolicy()
```

🐾 Properties 4

MaximumCallsPerStep

```
public int MaximumCallsPerStep { get; set; }
```

MaximumParameterCharacters

```
public int MaximumParameterCharacters { get; set; }
```

MaximumResultCharacters

```
public int MaximumResultCharacters { get; set; }
```

PromptInstruction

```
public string PromptInstruction { get; set; }
```

Enum CouncilGameActorKind

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Identifies the runtime actor that proposed an action.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilGameActorKind
```

Fields 1

Class CouncilGameActorRuntimeDescriptor

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes one factory-created actor instance and its Council assignment slot.

Inheritance object CouncilGameActorRuntimeDescriptor

```
public sealed class CouncilGameActorRuntimeDescriptor
```

Constructors 1

CouncilGameActorRuntimeDescriptor()

```
public CouncilGameActorRuntimeDescriptor()
```

Properties 7

ActorKind

```
public CouncilGameActorKind ActorKind { get; set; }
```

Archetype

```
public string Archetype { get; set; }
```

CouncilAssignmentGroup

```
public string CouncilAssignmentGroup { get; set; }
```

CouncilAssignmentSlot

```
public string CouncilAssignmentSlot { get; set; }
```

CouncilRole

```
public string CouncilRole { get; set; }
```

InstanceKey

```
public string InstanceKey { get; set; }
```

RuntimeClassKey

```
public string RuntimeClassKey { get; set; }
```


Enum CouncilGameControlMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilGameControlMode
```

Fields 1

Class CouncilGameControlRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilGameControlRequest

```
public sealed class CouncilGameControlRequest
```

Constructors 1

CouncilGameControlRequest()

```
public CouncilGameControlRequest()
```

Properties 11

Action

```
public string Action { get; set; }
```

ActorKind

```
public CouncilGameActorKind ActorKind { get; set; }
```

ActorName

```
public string ActorName { get; set; }
```

AimX

```
public int? AimX { get; set; }
```

AimY

```
public int? AimY { get; set; }
```

AxisX

```
public double? AxisX { get; set; }
```

AxisY

```
public double? AxisY { get; set; }
```

ExpectedTurn

```
public long? ExpectedTurn { get; set; }
```

RuntimeClassKey

```
public string RuntimeClassKey { get; set; }
```

SessionId

```
public Guid SessionId { get; set; }
```

Source

```
public string Source { get; set; }
```

Class CouncilGameDirectorContext

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Provides the immutable input used by the authoritative GameDirector for one proposed action.
Inheritance object CouncilGameDirectorContext

```
public sealed class CouncilGameDirectorContext
```

🌟 Constructors 1

CouncilGameDirectorContext()

```
public CouncilGameDirectorContext()
```

🐾 Properties 5

DirectorMode

```
public CouncilGameDirectorMode DirectorMode { get; init; }
```

DirectorModelName

```
public string DirectorModelName { get; init; }
```

NormalizedAction

```
public required string NormalizedAction { get; init; }
```

Proposal

```
public required CouncilGameControlRequest Proposal { get; init; }
```

Session

```
public required CouncilGameSessionSnapshot Session { get; init; }
```

Class CouncilGameDirectorDecision

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Records the GameDirector decision that authorizes or rejects one state transition.
Inheritance object CouncilGameDirectorDecision

```
public sealed class CouncilGameDirectorDecision
```

🌟 Constructors 1

CouncilGameDirectorDecision()

```
public CouncilGameDirectorDecision()
```

🐾 Properties 11

Approved

```
public bool Approved { get; set; }
```

DecidedAtUtc

```
public DateTime DecidedAtUtc { get; set; }
```

DecisionId

```
public Guid DecisionId { get; set; }
```

DirectorMode

```
public CouncilGameDirectorMode DirectorMode { get; set; }
```

DirectorModelName

```
public string DirectorModelName { get; set; }
```

DirectorName

```
public string DirectorName { get; set; }
```

ExpectedTurn

```
public long ExpectedTurn { get; set; }
```

NormalizedAction

```
public string NormalizedAction { get; set; }
```

Predictions

```
public IReadOnlyList<CouncilGameSubdirectorPrediction> Predictions { get; set; }
```

Reason

```
public string Reason { get; set; }
```

SessionId

```
public Guid SessionId { get; set; }
```

Enum CouncilGameDirectorMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Chooses how a game action is reviewed before the authoritative session state changes.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilGameDirectorMode
```

Fields 1

Class CouncilGameSessionRecord

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Persistent envelope for an authoritative GameDirector runtime session.

Inheritance object CouncilGameSessionRecord

```
[DocumentationUpdated("2.1.23")] public sealed class CouncilGameSessionRecord
```

Constructors 1

CouncilGameSessionRecord()

```
public CouncilGameSessionRecord()
```

Properties 9

ConversationId

Gets or sets an optional linked chat-memory conversation identifier.

```
public Guid? ConversationId { get; set; }
```

CreatedAtUtc

Gets or sets the UTC creation timestamp.

```
public DateTime CreatedAtUtc { get; set; }
```

GameKey

Gets or sets the game/runtime key.

```
[MaxLength(160)] public string GameKey { get; set; }
```

Id

Gets or sets the stable database identifier.

```
public Guid Id { get; set; }
```

SessionKey

Gets or sets the stable runtime session key.

```
[MaxLength(160)] public string SessionKey { get; set; }
```

SnapshotJson

Gets or sets the latest authoritative runtime snapshot JSON.

```
public string SnapshotJson { get; set; }
```

Status

Gets or sets the authoritative runtime status.

```
[MaxLength(80)] public string Status { get; set; }
```

TeamKey

Gets or sets the responsible Council team key.

```
[MaxLength(160)] public string TeamKey { get; set; }
```

UpdatedAtUtc

Gets or sets the UTC update timestamp.

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilGameSessionSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilGameSessionSnapshot

```
public sealed class CouncilGameSessionSnapshot
```

🌟 Constructors 1

CouncilGameSessionSnapshot()

```
public CouncilGameSessionSnapshot()
```

🐾 Properties 36

Ammo

```
public int Ammo { get; set; }
```

AutoplayDelayMilliseconds

```
public int AutoplayDelayMilliseconds { get; set; }
```

AutoplayEnabled

```
public bool AutoplayEnabled { get; set; }
```

ControlMode

```
public CouncilGameControlMode ControlMode { get; set; }
```

ConversationId

```
public Guid? ConversationId { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CreatureDirectorCount

```
public int CreatureDirectorCount { get; set; }
```

CurrentTurnOwner

```
public string CurrentTurnOwner { get; set; }
```

DirectorMode

```
public CouncilGameDirectorMode DirectorMode { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

FacingDegrees

```
public double FacingDegrees { get; set; }
```

FrameCaption

```
public string FrameCaption { get; set; }
```

FrameHeight

```
public int FrameHeight { get; set; }
```

FrameRenderer

```
public string FrameRenderer { get; set; }
```

FrameText

```
public string FrameText { get; set; }
```

FrameWidth

```
public int FrameWidth { get; set; }
```

GameDirectorModelName

```
public string GameDirectorModelName { get; set; }
```

GameDirectorName

```
public string GameDirectorName { get; set; }
```

GameKey

```
public string GameKey { get; set; }
```

Health

```
public int Health { get; set; }
```

HumanInputRequired

```
public bool HumanInputRequired { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InputBindings

```
public IReadOnlyList<RuntimeInputBindingDefinition> InputBindings { get; set; }
```

InputReason

```
public string InputReason { get; set; }
```

IsDucking

```
public bool IsDucking { get; set; }
```

LastAction

```
public string LastAction { get; set; }
```

LastActionBy

```
public string LastActionBy { get; set; }
```

LastDirectorDecision

```
public string LastDirectorDecision { get; set; }
```

LastDirectorPredictions

```
public IReadOnlyList<CouncilGameSubdirectorPrediction> LastDirectorPredictions { get; set; }
```

LegalActions

```
public IReadOnlyList<string> LegalActions { get; set; }
```

PlayerX

```
public int PlayerX { get; set; }
```

PlayerY

```
public int PlayerY { get; set; }
```

Status

```
public string Status { get; set; }
```

TeamKey

```
public string TeamKey { get; set; }
```

Turn

```
public long Turn { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilGameSessionState

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Internal authoritative state for one in-chat Council game session. It is deliberately data-only so the session service owns orchestration, rendering and synchronization policy.

Inheritance object CouncilGameSessionState

```
public sealed class CouncilGameSessionState
```

✨ Constructors 1

CouncilGameSessionState()

```
public CouncilGameSessionState()
```

🐾 Properties 42

Ammo

```
public int Ammo { get; set; }
```

AutoplayDelayMilliseconds

```
public int AutoplayDelayMilliseconds { get; set; }
```

AutoplayEnabled

```
public bool AutoplayEnabled { get; set; }
```

ControlMode

```
public CouncilGameControlMode ControlMode { get; set; }
```

ConversationId

```
public Guid? ConversationId { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CreatureDirectorCount

```
public int CreatureDirectorCount { get; set; }
```

CurrentTurnOwner

```
public string CurrentTurnOwner { get; set; }
```

DirectorMode

```
public CouncilGameDirectorMode DirectorMode { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

FacingRadians

```
public double FacingRadians { get; set; }
```

FrameCaption

```
public string FrameCaption { get; set; }
```

FrameHeight

```
public int FrameHeight { get; set; }
```

FrameOwner

```
public string FrameOwner { get; set; }
```

FrameOwnerTurn

```
public long FrameOwnerTurn { get; set; }
```

FrameRenderer

```
public string FrameRenderer { get; set; }
```

FrameText

```
public string FrameText { get; set; }
```

FrameWidth

```
public int FrameWidth { get; set; }
```

GameDirectorModelName

```
public string GameDirectorModelName { get; set; }
```

GameDirectorName

```
public string GameDirectorName { get; set; }
```

GameKey

```
public string GameKey { get; set; }
```

Health

```
public int Health { get; set; }
```

HumanInputRequired

```
public bool HumanInputRequired { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InputBindings

```
public List<RuntimeInputBindingDefinition> InputBindings { get; set; }
```

InputReason

```
public string InputReason { get; set; }
```

IsDucking

```
public bool IsDucking { get; set; }
```

LastAction

```
public string LastAction { get; set; }
```

LastActionBy

```
public string LastActionBy { get; set; }
```

LastDirectorDecision

```
public string LastDirectorDecision { get; set; }
```

LastDirectorPredictions

```
public List<CouncilGameSubdirectorPrediction> LastDirectorPredictions { get; set; }
```

LegalActions

```
public List<string> LegalActions { get; set; }
```

MuzzleFlash

```
public int MuzzleFlash { get; set; }
```

PlayerX

```
public int PlayerX { get; set; }
```

PlayerY

```
public int PlayerY { get; set; }
```


Status

```
public string Status { get; set; }
```

StoryLine

```
public string StoryLine { get; set; }
```

SyncRoot

```
public object SyncRoot { get; }
```

TeamKey

```
public string TeamKey { get; set; }
```

Turn

```
public long Turn { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

UsePulse

```
public int UsePulse { get; set; }
```

api/LocalGPT.BusinessObjects.CouncilGameSubdirectorPrediction.html

Class CouncilGameSubdirectorPrediction

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Represents one bounded prediction from a creature or reactive-object subdirector.

Inheritance object CouncilGameSubdirectorPrediction

```
public sealed class CouncilGameSubdirectorPrediction
```

🌟 Constructors 1

CouncilGameSubdirectorPrediction()

```
public CouncilGameSubdirectorPrediction()
```

🐾 Properties 6

ActorInstances

```
public IReadOnlyList<CouncilGameActorRuntimeDescriptor> ActorInstances { get; set; }
```

ActorKind

```
public CouncilGameActorKind ActorKind { get; set; }
```

ConfidencePercent

```
public int ConfidencePercent { get; set; }
```

DirectorKey

```
public string DirectorKey { get; set; }
```

Prediction

```
public string Prediction { get; set; }
```

RuntimeClassKey

```
public string RuntimeClassKey { get; set; }
```

Class CouncilHardwareRoadPlan

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Immutable execution limits selected for one model on one CPU/GPU road.

Inheritance object CouncilHardwareRoadPlan

Implements IEquatable < CouncilHardwareRoadPlan >

```
public sealed record CouncilHardwareRoadPlan : IEquatable<CouncilHardwareRoadPlan>
```

🌟 Constructors 1

CouncilHardwareRoadPlan(string, OneWireHardwareKind, int, string, string, int, int, int, int?, int)

Immutable execution limits selected for one model on one CPU/GPU road.

```
public CouncilHardwareRoadPlan(string ModelName, OneWireHardwareKind HardwareKind, int HardwareIndex, string HardwareName, string LaneKey, int EffectiveLoadPercent, int EffectiveMaxOutputTokens, int EffectiveMaxContextTokens, int? OllamaNumGpu, int MaxConcurrentModelsOnLane)
```

🐾 Properties 10

EffectiveLoadPercent

```
public int EffectiveLoadPercent { get; init; }
```

EffectiveMaxContextTokens

```
public int EffectiveMaxContextTokens { get; init; }
```

EffectiveMaxOutputTokens

```
public int EffectiveMaxOutputTokens { get; init; }
```

HardwareIndex

```
public int HardwareIndex { get; init; }
```

HardwareKind

```
public OneWireHardwareKind HardwareKind { get; init; }
```

HardwareName

```
public string HardwareName { get; init; }
```

LaneKey

```
public string LaneKey { get; init; }
```

MaxConcurrentModelsOnLane

```
public int MaxConcurrentModelsOnLane { get; init; }
```

ModelName

```
public string ModelName { get; init; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out OneWireHardwareKind, out int, out string, out string, out int, out int, out int, out int?, out int)

```
public void Deconstruct(out string ModelName, out OneWireHardwareKind HardwareKind, out int HardwareIndex, out string HardwareName, out string LaneKey, out int EffectiveLoadPercent, out int EffectiveMaxOutputTokens, out int EffectiveMaxContextTokens, out int? OllamaNumGpu, out int MaxConcurrentModelsOnLane)
```

Equals(CouncilHardwareRoadPlan?)

```
public bool Equals(CouncilHardwareRoadPlan? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(CouncilHardwareRoadPlan?, CouncilHardwareRoadPlan?)

```
public static bool operator ==(CouncilHardwareRoadPlan? left, CouncilHardwareRoadPlan? right)
```

operator !=(CouncilHardwareRoadPlan?, CouncilHardwareRoadPlan?)

```
public static bool operator !=(CouncilHardwareRoadPlan? left, CouncilHardwareRoadPlan? right)
```

Class CouncilKnowledgeEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilKnowledgeEntry

```
public class CouncilKnowledgeEntry
```

🌟 Constructors 1

CouncilKnowledgeEntry()

```
public CouncilKnowledgeEntry()
```

🐾 Properties 24

Confidence

```
public int Confidence { get; set; }
```

Content

```
[Required] [Column(TypeName = "TEXT")] public string Content { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

ExpiresAtUtc

```
public DateTime? ExpiresAtUtc { get; set; }
```

HelpfulSources

```
public string HelpfulSources { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsArchived

```
public bool IsArchived { get; set; }
```

IsPinned

```
public bool IsPinned { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

LastUsedAtUtc

```
public DateTime? LastUsedAtUtc { get; set; }
```

LastVerifiedAtUtc

```
public DateTime? LastVerifiedAtUtc { get; set; }
```

ReviewStatus

```
public string ReviewStatus { get; set; }
```

Scope

```
public string Scope { get; set; }
```

Source

```
public string Source { get; set; }
```

SourceDateUtc

```
public DateTime? SourceDateUtc { get; set; }
```

SourceHash

```
public string SourceHash { get; set; }
```

StalenessDetectedAtUtc

```
public DateTime? StalenessDetectedAtUtc { get; set; }
```

StalenessDetectedBy

```
public string StalenessDetectedBy { get; set; }
```

StalenessReason

```
public string StalenessReason { get; set; }
```

SupersededByKnowledgeId

```
public Guid? SupersededByKnowledgeId { get; set; }
```

Tags

```
public string Tags { get; set; }
```

Topic

```
public string Topic { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

VerificationStatus

```
public string VerificationStatus { get; set; }
```

api/LocalGPT.BusinessObjects.CouncilKnowledgeListParameters.html

Class CouncilKnowledgeListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilKnowledgeListParameters

```
public sealed class CouncilKnowledgeListParameters
```

🌟 Constructors 1

CouncilKnowledgeListParameters()

```
public CouncilKnowledgeListParameters()
```

🐾 Properties 2

IncludeArchived

```
public bool IncludeArchived { get; set; }
```

Take

```
public int Take { get; set; }
```

Class CouncilKnowledgeUserRating

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilKnowledgeUserRating

```
public sealed class CouncilKnowledgeUserRating
```

🌟 Constructors 1

CouncilKnowledgeUserRating()

```
public CouncilKnowledgeUserRating()
```

🐾 Properties 10

AccuracyStatus

```
[MaxLength(80)] public string AccuracyStatus { get; set; }
```

ApprovedForCouncilUse

```
public bool ApprovedForCouncilUse { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Id

```
public Guid Id { get; set; }
```

KnowledgeEntry

```
public CouncilKnowledgeEntry? KnowledgeEntry { get; set; }
```

KnowledgeEntryId

```
public Guid KnowledgeEntryId { get; set; }
```

Notes

```
[MaxLength(4000)] public string Notes { get; set; }
```

RatedBy

```
[MaxLength(120)] public string RatedBy { get; set; }
```

Rating

```
public int Rating { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilLiveSessionSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilLiveSessionSnapshot

Implements IEquatable < CouncilLiveSessionSnapshot >

```
public sealed record CouncilLiveSessionSnapshot : IEquatable<CouncilLiveSessionSnapshot>
```

🌟 Constructors 1

CouncilLiveSessionSnapshot(Guid, bool, DateTime, DateTime, IReadOnlyList<string>, string, IReadOnlyList<string>, string)

```
public CouncilLiveSessionSnapshot(Guid RunId, bool IsRunning, DateTime StartedAtUtc, DateTime UpdatedAtUtc, IReadOnlyList<string> CouncilMembers, string UserMessage, IReadOnlyList<string> AdditionalUserMessages, string Transcript)
```

🐾 Properties 8

AdditionalUserMessages

```
public IReadOnlyList<string> AdditionalUserMessages { get; init; }
```

CouncilMembers

```
public IReadOnlyList<string> CouncilMembers { get; init; }
```

IsRunning

```
public bool IsRunning { get; init; }
```

RunId

```
public Guid RunId { get; init; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; init; }
```

Transcript

```
public string Transcript { get; init; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; init; }
```

UserMessage

```
public string UserMessage { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out bool, out DateTime, out DateTime, out IReadOnlyList<string>, out string, out IReadOnlyList<string>, out string)

```
public void Deconstruct(out Guid RunId, out bool IsRunning, out DateTime StartedAtUtc, out DateTime UpdatedAtUtc, out IReadOnlyList<string> CouncilMembers, out string UserMessage, out IReadOnlyList<string> AdditionalUserMessages, out string Transcript)
```

Equals(CouncilLiveSessionSnapshot?)

```
public bool Equals(CouncilLiveSessionSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(CouncilLiveSessionSnapshot?, CouncilLiveSessionSnapshot?)

```
public static bool operator ==(CouncilLiveSessionSnapshot? left, CouncilLiveSessionSnapshot? right)
```

operator !=(CouncilLiveSessionSnapshot?, CouncilLiveSessionSnapshot?)

```
public static bool operator !=(CouncilLiveSessionSnapshot? left, CouncilLiveSessionSnapshot? right)
```

api/LocalGPT.BusinessObjects.CouncilLiveSessionSummary.html

Class CouncilLiveSessionSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilLiveSessionSummary

Implements IEquatable < CouncilLiveSessionSummary >

```
public sealed record CouncilLiveSessionSummary : IEquatable<CouncilLiveSessionSummary>
```

🌟 Constructors 1

CouncilLiveSessionSummary(Guid, bool, DateTime, DateTime, IReadOnlyList<string>)

```
public CouncilLiveSessionSummary(Guid RunId, bool IsRunning, DateTime StartedAtUtc, DateTime UpdatedAtUtc, IReadOnlyList<string> CouncilMembers)
```

🐾 Properties 5

CouncilMembers

```
public IReadOnlyList<string> CouncilMembers { get; init; }
```

IsRunning

```
public bool IsRunning { get; init; }
```

RunId

```
public Guid RunId { get; init; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; init; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out bool, out DateTime, out DateTime, out IReadOnlyList<string>)

```
public void Deconstruct(out Guid RunId, out bool IsRunning, out DateTime StartedAtUtc, out DateTime UpdatedAtUtc, out IReadOnlyList<string> CouncilMembers)
```

Equals(CouncilLiveSessionSummary?)

```
public bool Equals(CouncilLiveSessionSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(CouncilLiveSessionSummary?, CouncilLiveSessionSummary?)

```
public static bool operator ==(CouncilLiveSessionSummary? left, CouncilLiveSessionSummary? right)
```

operator !=(CouncilLiveSessionSummary?, CouncilLiveSessionSummary?)

```
public static bool operator !=(CouncilLiveSessionSummary? left, CouncilLiveSessionSummary? right)
```


Class CouncilMemberOrganicSkillLink

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilMemberOrganicSkillLink

```
public sealed class CouncilMemberOrganicSkillLink
```

🌟 Constructors 1

CouncilMemberOrganicSkillLink()

```
public CouncilMemberOrganicSkillLink()
```

🐾 Properties 12

ControllerMethodsJson

```
[Column(TypeName = "TEXT")] public string ControllerMethodsJson { get; set; }
```

DxFunctionsJson

```
[Column(TypeName = "TEXT")] public string DxFunctionsJson { get; set; }
```

Evidence

```
[MaxLength(4000)] public string Evidence { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsSelfRevealed

```
public bool IsSelfRevealed { get; set; }
```

MemberKey

```
[Required] [MaxLength(240)] public string MemberKey { get; set; }
```

OrganicCapabilitiesJson

```
[Column(TypeName = "TEXT")] public string OrganicCapabilitiesJson { get; set; }
```

Proficiency

```
public int Proficiency { get; set; }
```

Skill

```
public OrganicSkillDefinition? Skill { get; set; }
```

SkillId

```
public Guid SkillId { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilMemberReadiness

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Readiness facts for one council member and its selected hardware road.
Inheritance object CouncilMemberReadiness

```
public sealed class CouncilMemberReadiness
```

🌟 Constructors 1

CouncilMemberReadiness()

```
public CouncilMemberReadiness()
```

🐾 Properties 12

AssignedDxFunctions

```
public List<string> AssignedDxFunctions { get; set; }
```

AssignedOrganicSkills

```
public List<string> AssignedOrganicSkills { get; set; }
```

EffectiveLoadPercent

```
public int EffectiveLoadPercent { get; set; }
```

EffectiveMaxContextTokens

```
public int EffectiveMaxContextTokens { get; set; }
```

EffectiveMaxOutputTokens

```
public int EffectiveMaxOutputTokens { get; set; }
```

HardwareIndex

```
public int HardwareIndex { get; set; }
```

HardwareKind

```
public OneWireHardwareKind HardwareKind { get; set; }
```

HardwareName

```
public string HardwareName { get; set; }
```

LaneKey

```
public string LaneKey { get; set; }
```

MissingCapabilities

```
public List<string> MissingCapabilities { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

Class CouncilModelPreset

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilModelPreset

```
public sealed class CouncilModelPreset
```

🌟 Constructors 1

CouncilModelPreset()

```
public CouncilModelPreset()
```

🐾 Properties 18

AllowParallelHardwareRoads

```
public bool AllowParallelHardwareRoads { get; set; }
```

CreateProjectPerRun

```
public bool CreateProjectPerRun { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Description

```
[MaxLength(1000)] public string Description { get; set; }
```

GenerateArtifacts

```
public bool GenerateArtifacts { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IncludeMemory

```
public bool IncludeMemory { get; set; }
```

IsArchived

```
public bool IsArchived { get; set; }
```

IsDefault

```
public bool IsDefault { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

MaxContextTokens

```
public int MaxContextTokens { get; set; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; set; }
```

MaxParallelModels

```
public int MaxParallelModels { get; set; }
```

ModelNamesJson

```
[Required] [Column(TypeName = "TEXT")] public string ModelNamesJson { get; set; }
```

ModelRoutesJson

```
[Required] [Column(TypeName = "TEXT")] public string ModelRoutesJson { get; set; }
```

Name

```
[Required] [MaxLength(160)] public string Name { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilPreflightReport

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Database, function, skill, project and hardware readiness report created before every council run.

Inheritance object CouncilPreflightReport

```
public sealed class CouncilPreflightReport
```

✨ Constructors 1

CouncilPreflightReport()

```
public CouncilPreflightReport()
```

🐾 Properties 20

CapabilityTeachings

Bounded connected 1-Wire capability contracts taught to every Council member before substantive work.

```
public List<string> CapabilityTeachings { get; set; }
```

CheckedAtUtc

```
public DateTime CheckedAtUtc { get; set; }
```

DxFunctionCount

```
public int DxFunctionCount { get; set; }
```

FunctionNames

```
public List<string> FunctionNames { get; set; }
```

IntroductionPromptTemplate

```
public string IntroductionPromptTemplate { get; set; }
```

KnowledgeEntryCount

```
public int KnowledgeEntryCount { get; set; }
```

Members

```
public List<CouncilMemberReadiness> Members { get; set; }
```

MissingRequirements

```
public List<string> MissingRequirements { get; set; }
```

OfflineSkillKeys

```
public List<string> OfflineSkillKeys { get; set; }
```

OnlineSkillKeys

```
public List<string> OnlineSkillKeys { get; set; }
```

OrganicSkillCount

```
public int OrganicSkillCount { get; set; }
```

ProjectCount

```
public int ProjectCount { get; set; }
```

ProjectNames

```
public List<string> ProjectNames { get; set; }
```

PromptContext

```
public string PromptContext { get; set; }
```

RegexNames

```
public List<string> RegexNames { get; set; }
```

RegexPatternCount

```
public int RegexPatternCount { get; set; }
```

SkillKeys

```
public List<string> SkillKeys { get; set; }
```

TeamKey

```
public string TeamKey { get; set; }
```

TeamName

```
public string TeamName { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class CouncilPreparationConfiguration

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CouncilPreparationConfiguration
Implements IEquatable < CouncilPreparationConfiguration >

```
public sealed record CouncilPreparationConfiguration : IEquatable<CouncilPreparationConfiguration>
```

🌟 Constructors 1

CouncilPreparationConfiguration(IReadOnlyList<string>, IReadOnlyList<OneWireCouncilModelRoute>, int, int, int, int?, bool, int, int, bool, bool, string)

```
public CouncilPreparationConfiguration(IReadOnlyList<string> ModelNames, IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes, int ResourceLoadPercent, int MaxOutputTokens, int MaxContextTokens, int? OllamaNumGpu, bool AllowParallelHardwareRoads, int MaxParallelModels, int CritiqueRounds, bool IncludeMemory, bool CreateProjectPerRun, string CouncilTeamKey)
```

🐾 Properties 12

AllowParallelHardwareRoads

```
public bool AllowParallelHardwareRoads { get; init; }
```

CouncilTeamKey

```
public string CouncilTeamKey { get; init; }
```

CreateProjectPerRun

```
public bool CreateProjectPerRun { get; init; }
```

CritiqueRounds

```
public int CritiqueRounds { get; init; }
```

IncludeMemory

```
public bool IncludeMemory { get; init; }
```

MaxContextTokens

```
public int MaxContextTokens { get; init; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; init; }
```

MaxParallelModels

```
public int MaxParallelModels { get; init; }
```

ModelNames

```
public IReadOnlyList<string> ModelNames { get; init; }
```

ModelRoutes

```
public IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes { get; init; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; init; }
```

ResourceLoadPercent

```
public int ResourceLoadPercent { get; init; }
```

⚙️ Methods 5

Deconstruct(out IReadOnlyList<string>, out IReadOnlyList<OneWireCouncilModelRoute>, out int, out int, out int, out int?, out bool, out int, out int, out bool, out bool, out string)

```
public void Deconstruct(out IReadOnlyList<string> ModelNames, out IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes, out int ResourceLoadPercent, out int MaxOutputTokens, out int MaxContextTokens, out int? OllamaNumGpu, out bool AllowParallelHardwareRoads, out int MaxParallelModels, out int CritiqueRounds, out bool IncludeMemory, out bool CreateProjectPerRun, out string CouncilTeamKey)
```

Equals(CouncilPreparationConfiguration?)

```
public bool Equals(CouncilPreparationConfiguration? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(CouncilPreparationConfiguration?, CouncilPreparationConfiguration?)

```
public static bool operator ==(CouncilPreparationConfiguration? left, CouncilPreparationConfiguration? right)
```

operator !=(CouncilPreparationConfiguration?, CouncilPreparationConfiguration?)

```
public static bool operator !=(CouncilPreparationConfiguration? left, CouncilPreparationConfiguration? right)
```


Class CouncilPromptStarterConfiguration

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Persistent configuration for one visible chat prompt that can start an AI Council run.

Inheritance object CouncilPromptStarterConfiguration

```
[DocumentationUpdated("2.1.23")] public sealed class CouncilPromptStarterConfiguration
```

🌟 Constructors 1

CouncilPromptStarterConfiguration()

```
public CouncilPromptStarterConfiguration()
```

🐾 Properties 11

CreatedAtUtc

Gets or sets the UTC creation timestamp.

```
public DateTime CreatedAtUtc { get; set; }
```

Id

Gets or sets the stable database identifier.

```
public Guid Id { get; set; }
```

IsBuiltIn

Gets or sets whether the row originated from a maintained LocalGPT seed.

```
public bool IsBuiltIn { get; set; }
```

IsEnabled

Gets or sets whether the starter is available to the UI.

```
public bool IsEnabled { get; set; }
```

Key

Gets or sets the unique machine-readable starter key.

```
[MaxLength(160)] public string Key { get; set; }
```

PromptMessage

Gets or sets the full prompt submitted to the selected chat or Council.

```
public string PromptMessage { get; set; }
```

StartsCouncilDirectly

Gets or sets whether choosing this card starts an AI Council run rather than a normal chat prompt.

```
public bool StartsCouncilDirectly { get; set; }
```

Summary

Gets or sets the short description shown on the prompt card.

```
[MaxLength(1000)] public string Summary { get; set; }
```

TeamKeysJson

Gets or sets a JSON array of compatible Council team keys.

```
public string TeamKeysJson { get; set; }
```

Title

Gets or sets the user-visible starter title.

```
[MaxLength(240)] public string Title { get; set; }
```

UpdatedAtUtc

Gets or sets the UTC update timestamp.

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilQuickStart

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes a direct route into a seeded LocalGPT team and model-preset combination.

Inheritance object CouncilQuickStart

Implements IEquatable < CouncilQuickStart >

```
[DocumentationUpdated("2.1.22")] public sealed record CouncilQuickStart : IEquatable<CouncilQuickStart>
```

🌟 Constructors 1

CouncilQuickStart(string, string, string, string, string, string, string)

Describes a direct route into a seeded LocalGPT team and model-preset combination.

```
public CouncilQuickStart(string Key, string DisplayName, string Description, string CouncilTeamKey, string ModelPresetName, string StarterPromptKey, string Route)
```

🐾 Properties 7

CouncilTeamKey

Seeded council-team key selected by the route.

```
public string CouncilTeamKey { get; init; }
```

Description

Explanation of the intended round and resource profile.

```
public string Description { get; init; }
```

DisplayName

Human-readable quick-start label.

```
public string DisplayName { get; init; }
```

Key

Stable quick-start key.

```
public string Key { get; init; }
```

ModelPresetName

Seeded model-preset name selected by the route.

```
public string ModelPresetName { get; init; }
```

Route

Application-relative Chat route containing the requested team, preset and starter prompt.

```
public string Route { get; init; }
```

StarterPromptKey

Stable prompt key submitted by the direct Council starter.

```
public string StarterPromptKey { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out string)

```
public void Deconstruct(out string Key, out string DisplayName, out string Description, out string CouncilTeamKey, out string ModelPresetName, out string StarterPromptKey, out string Route)
```

Equals(CouncilQuickStart?)

```
public bool Equals(CouncilQuickStart? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(CouncilQuickStart?, CouncilQuickStart?)

```
public static bool operator ==(CouncilQuickStart? left, CouncilQuickStart? right)
```

operator !=(CouncilQuickStart?, CouncilQuickStart?)

```
public static bool operator !=(CouncilQuickStart? left, CouncilQuickStart? right)
```

api/LocalGPT.BusinessObjects.CouncilRoleAiSelectionMode.html

Enum CouncilRoleAiSelectionMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines how LocalGPT assigns AI participants to a Council role.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilRoleAiSelectionMode
```

🔍 Fields 1

api/LocalGPT.BusinessObjects.CouncilRoleBoundaryMode.html

Enum CouncilRoleBoundaryMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines how strictly a Council role must remain inside its assigned responsibility.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilRoleBoundaryMode
```

🔍 Fields 1

api/LocalGPT.BusinessObjects.CouncilRoleLanguageMode.html

Enum CouncilRoleLanguageMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines the language policy applied to a Council role.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilRoleLanguageMode
```

🔍 Fields 1

api/LocalGPT.BusinessObjects.CouncilRolePerformanceMode.html

Enum CouncilRolePerformanceMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines whether a role behaves as a task specialist or an improvisation player.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum CouncilRolePerformanceMode
```

🔍 Fields 1

api/LocalGPT.BusinessObjects.CouncilRunConfigurationSnapshot.html

Class CouncilRunConfigurationSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilRunConfigurationSnapshot

Implements IEquatable < CouncilRunConfigurationSnapshot >

```
public sealed record CouncilRunConfigurationSnapshot : IEquatable<CouncilRunConfigurationSnapshot>
```

🌟 Constructors 1

CouncilRunConfigurationSnapshot(Guid, long, IReadOnlyList<string>, IReadOnlyList<OneWireCouncilModelRoute>, int, int, int, int?, bool, int, string, bool, bool)

```
public CouncilRunConfigurationSnapshot(Guid RunId, long Revision, IReadOnlyList<string> Participants, IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes, int ResourceLoadPercent, int RequestedMaxOutputTokens, int RequestedMaxContextTokens, int? FallbackOllamaNumGpu, bool AllowParallelHardwareRoads, int CurrentRound, string CurrentPhase, bool IsRoundSkipRequested, bool IsRunning)
```

🐾 Properties 13

AllowParallelHardwareRoads

```
public bool AllowParallelHardwareRoads { get; init; }
```

CurrentPhase

```
public string CurrentPhase { get; init; }
```

CurrentRound

```
public int CurrentRound { get; init; }
```

FallbackOllamaNumGpu

```
public int? FallbackOllamaNumGpu { get; init; }
```

IsRoundSkipRequested

```
public bool IsRoundSkipRequested { get; init; }
```

IsRunning

```
public bool IsRunning { get; init; }
```

ModelRoutes

```
public IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes { get; init; }
```

Participants

```
public IReadOnlyList<string> Participants { get; init; }
```

RequestedMaxContextTokens

```
public int RequestedMaxContextTokens { get; init; }
```

RequestedMaxOutputTokens

```
public int RequestedMaxOutputTokens { get; init; }
```

ResourceLoadPercent

```
public int ResourceLoadPercent { get; init; }
```

Revision

```
public long Revision { get; init; }
```

RunId

```
public Guid RunId { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out long, out IReadOnlyList<string>, out IReadOnlyList<OneWireCouncilModelRoute>, out int, out int, out int, out int?, out bool, out int, out string, out bool, out bool)

```
public void Deconstruct(out Guid RunId, out long Revision, out IReadOnlyList<string> Participants, out IReadOnlyList<OneWireCouncilModelRoute> ModelRoutes, out int ResourceLoadPercent, out int RequestedMaxOutputTokens, out int RequestedMaxContextTokens, out int? FallbackOllamaNumGpu, out bool AllowParallelHardwareRoads, out int CurrentRound, out string CurrentPhase, out bool IsRoundSkipRequested, out bool IsRunning)
```

Equals(CouncilRunConfigurationSnapshot?)

```
public bool Equals(CouncilRunConfigurationSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(CouncilRunConfigurationSnapshot?, CouncilRunConfigurationSnapshot?)

```
public static bool operator ==(CouncilRunConfigurationSnapshot? left, CouncilRunConfigurationSnapshot? right)
```

operator !=(CouncilRunConfigurationSnapshot?, CouncilRunConfigurationSnapshot?)

```
public static bool operator !=(CouncilRunConfigurationSnapshot? left, CouncilRunConfigurationSnapshot? right)
```

Class CouncilRuntimeClassConfiguration

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilRuntimeClassConfiguration

```
public sealed class CouncilRuntimeClassConfiguration
```

🌟 Constructors 1

CouncilRuntimeClassConfiguration()

```
public CouncilRuntimeClassConfiguration()
```

🐾 Properties 16

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

FieldsJson

```
public string FieldsJson { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InputBindingsJson

```
public string InputBindingsJson { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsSystemSeed

```
public bool IsSystemSeed { get; set; }
```

IsUserModified

```
public bool IsUserModified { get; set; }
```

Key

```
public string Key { get; set; }
```

Kind

```
public string Kind { get; set; }
```

Namespace

```
public string Namespace { get; set; }
```

RecommendedDxFunctionsJson

```
public string RecommendedDxFunctionsJson { get; set; }
```

SeedVersion

```
public int SeedVersion { get; set; }
```

SourceReferencesJson

```
public string SourceReferencesJson { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class CouncilRuntimeClassDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilRuntimeClassDefinition

```
public sealed class CouncilRuntimeClassDefinition
```

🌟 Constructors 1

CouncilRuntimeClassDefinition()

```
public CouncilRuntimeClassDefinition()
```

🐾 Properties 14

Aliases

```
public List<string> Aliases { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

Fields

```
public List<RuntimeClassFieldDefinition> Fields { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InputBindings

```
public List<RuntimeInputBindingDefinition> InputBindings { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsSystemSeed

```
public bool IsSystemSeed { get; set; }
```

IsUserModified

```
public bool IsUserModified { get; set; }
```

Key

```
public string Key { get; set; }
```

Kind

```
public RuntimeClassKind Kind { get; set; }
```

Namespace

```
public string Namespace { get; set; }
```

RecommendedDxFunctions

```
public List<string> RecommendedDxFunctions { get; set; }
```

SourceReferences

```
public List<string> SourceReferences { get; set; }
```

Class CouncilSpoolerSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilSpoolerSnapshot

```
public sealed class CouncilSpoolerSnapshot
```

🌟 Constructors 1

CouncilSpoolerSnapshot()

```
public CouncilSpoolerSnapshot()
```

🐾 Properties 13

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

CouncilTeamKey

```
public string CouncilTeamKey { get; set; }
```

CurrentRound

```
public int CurrentRound { get; set; }
```

FinalAnswer

```
public string FinalAnswer { get; set; }
```

ModelNames

```
public List<string> ModelNames { get; set; }
```

Phase

```
public string Phase { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

Status

```
public string Status { get; set; }
```

Steps

```
public List<MultiModelCouncilStep> Steps { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```


Class CouncilTeamConfiguration

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Represents the persisted SQLite row for one Council team configuration.
Inheritance object CouncilTeamConfiguration

```
[DocumentationUpdated("2.1.20")] public sealed class CouncilTeamConfiguration
```

🌟 Constructors 1

CouncilTeamConfiguration()

```
public CouncilTeamConfiguration()
```

🐾 Properties 17

ArchitectureContractsJson

Gets or sets serialized architecture contracts.

```
public string ArchitectureContractsJson { get; set; }
```

CreatedAtUtc

Gets or sets the UTC creation time.

```
public DateTime CreatedAtUtc { get; set; }
```

DisplayName

Gets or sets the team display name.

```
public string DisplayName { get; set; }
```

ExpertPreparationPromptTemplate

Gets or sets the expert-preparation prompt.

```
public string ExpertPreparationPromptTemplate { get; set; }
```

Id

Gets or sets the row identifier.

```
public Guid Id { get; set; }
```

IsEnabled

Gets or sets whether the team can be selected.

```
public bool IsEnabled { get; set; }
```

IsSystemSeed

Gets or sets whether the row is maintained seed data.

```
public bool IsSystemSeed { get; set; }
```

IsUserModified

Gets or sets whether a user changed the row.

```
public bool IsUserModified { get; set; }
```

Key

Gets or sets the stable team key.

```
public string Key { get; set; }
```

LeaderSynthesisPromptTemplate

Gets or sets the leader-synthesis prompt.

```
public string LeaderSynthesisPromptTemplate { get; set; }
```

MainRoundInstructionTemplate

Gets or sets the common main-round instruction.

```
public string MainRoundInstructionTemplate { get; set; }
```

PreferredCapabilitiesJson

Gets or sets serialized preferred capabilities.

```
public string PreferredCapabilitiesJson { get; set; }
```

Purpose

Gets or sets the team purpose.

```
public string Purpose { get; set; }
```

RolesJson

Gets or sets serialized role definitions.

```
public string RolesJson { get; set; }
```

SeedVersion

Gets or sets the maintained seed schema version.

```
public int SeedVersion { get; set; }
```

UpdatedAtUtc

Gets or sets the UTC update time.

```
public DateTime UpdatedAtUtc { get; set; }
```

WorkflowStepsJson

Gets or sets serialized workflow steps.

```
public string WorkflowStepsJson { get; set; }
```

api/LocalGPT.BusinessObjects.CouncilUserPoll.html

Class CouncilUserPoll

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CouncilUserPoll

```
public sealed class CouncilUserPoll
```

🌟 Constructors 1

CouncilUserPoll()

```
public CouncilUserPoll()
```

🐾 Properties 3

Options

```
public List<CouncilUserPollOption> Options { get; set; }
```

Question

```
public string Question { get; set; }
```

Reason

```
public string Reason { get; set; }
```

Class CouncilUserPollOption

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object CouncilUserPollOption

```
public sealed class CouncilUserPollOption
```

🌟 Constructors 1

CouncilUserPollOption()

```
public CouncilUserPollOption()
```

🐾 Properties 2

FollowUpPrompt

```
public string FollowUpPrompt { get; set; }
```

Label

```
public string Label { get; set; }
```

Class CouncilWorkflowStepDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines one ordered Council round and its execution, loop, function and ASCII-frame policies.

Inheritance object CouncilWorkflowStepDefinition

```
[DocumentationUpdated("2.1.20")] public sealed class CouncilWorkflowStepDefinition
```

✨ Constructors 1

CouncilWorkflowStepDefinition()

```
public CouncilWorkflowStepDefinition()
```

🐾 Properties 22

AsciiFrameHeight

Gets or sets the requested ASCII frame height.

```
public int AsciiFrameHeight { get; set; }
```

AsciiFrameWidth

Gets or sets the requested ASCII frame width.

```
public int AsciiFrameWidth { get; set; }
```

AssignedModelName

Gets or sets the explicit model used by assigned-model execution.

```
public string AssignedModelName { get; set; }
```

CanUseOrganicFunctions

Gets or sets whether registered organic/DX functions may be requested.

```
public bool CanUseOrganicFunctions { get; set; }
```

DisplayName

Gets or sets the visible step name.

```
public string DisplayName { get; set; }
```

ExecutionMode

Gets or sets the supported execution-mode name.

```
public string ExecutionMode { get; set; }
```

IncludePriorTranscript

Gets or sets whether prior step output is included in the prompt.

```
public bool IncludePriorTranscript { get; set; }
```

IsEnabled

Gets or sets whether the step is active.

```
public bool IsEnabled { get; set; }
```

Key

Gets or sets the stable step key.

```
public string Key { get; set; }
```

LoopCompletionMarker

Gets or sets the transcript marker that completes the loop.

```
public string LoopCompletionMarker { get; set; }
```

LoopGroup

Gets or sets the loop-group key shared by consecutive steps.

```
public string LoopGroup { get; set; }
```

MaximumLoopIterations

Gets or sets the maximum loop iterations.

```
public int MaximumLoopIterations { get; set; }
```

Phase

Gets or sets the workflow phase label.

```
public string Phase { get; set; }
```

ProducesAsciiFrame

Gets or sets whether the step owns a complete ASCII frame.

```
public bool ProducesAsciiFrame { get; set; }
```

ProducesFinalAnswer

Gets or sets whether the step produces the visible final answer.

```
public bool ProducesFinalAnswer { get; set; }
```

PromptTemplate

Gets or sets the literal prompt template.

```
public string PromptTemplate { get; set; }
```

RepeatCount

Gets or sets how many times the step is expanded outside a loop group.

```
public int RepeatCount { get; set; }
```

RequiresHumanCheckpoint

Gets or sets whether the step pauses for a human checkpoint.

```
public bool RequiresHumanCheckpoint { get; set; }
```

Role

Gets or sets the role assigned to the step.

```
public string Role { get; set; }
```

SortOrder

Gets or sets the primary ordering value.

```
public int SortOrder { get; set; }
```

UseBuiltInBehavior

Gets or sets whether the built-in orchestration behavior is used.

```
public bool UseBuiltInBehavior { get; set; }
```

WorldStepScale

Gets or sets the logical world-step scale represented by one frame.

```
public int WorldStepScale { get; set; }
```

Class CreateCodeGenerationReviewRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CreateCodeGenerationReviewRequest

```
public sealed class CreateCodeGenerationReviewRequest
```

✨ Constructors 1

CreateCodeGenerationReviewRequest()

```
public CreateCodeGenerationReviewRequest()
```

🐾 Properties 13

ChangeSummary

```
public string ChangeSummary { get; set; }
```

CodeDomTypes

```
public List<CodeDomTypeSpec> CodeDomTypes { get; set; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; set; }
```

CouncilSummary

```
public string CouncilSummary { get; set; }
```

CurrentProjectState

```
public string CurrentProjectState { get; set; }
```

Files

```
public List<CodeGenerationFileSpec> Files { get; set; }
```

Goal

```
public string Goal { get; set; }
```

Outputs

```
public List<CodeGenerationOutputSpec> Outputs { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectRevisionId

```
public Guid? ProjectRevisionId { get; set; }
```

ProjectTopicId

```
public Guid? ProjectTopicId { get; set; }
```

SafetySummary

```
public string SafetySummary { get; set; }
```

Title

```
public string Title { get; set; }
```

Class CustomVersion

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object CustomVersion

Implements ICustomVersion

```
public class CustomVersion : ICustomVersion
```

✨ Constructors 1

CustomVersion(string)

```
public CustomVersion(string version)
```

🐾 Properties 1

Version

```
public string Version { get; set; }
```

Class DatabaseLoggerCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DatabaseLoggerCoreOptions

```
public class DatabaseLoggerCoreOptions
```

✨ Constructors 1

DatabaseLoggerCoreOptions()

```
public DatabaseLoggerCoreOptions()
```

🌀 Fields 1

DatabaseLoggerCore

```
public const string DatabaseLoggerCore = "DatabaseLoggerCore"
```

🐾 Properties 5

BatchSize

```
[JsonInclude] public int BatchSize { get; set; }
```

CoreLogLevel

```
[JsonInclude] public CoreLogLevel CoreLogLevel { get; set; }
```

FlushIntervalSeconds

```
[JsonInclude] public int FlushIntervalSeconds { get; set; }
```

MaxQueueLength

```
[JsonInclude] public int MaxQueueLength { get; set; }
```

RetentionDays

```
[JsonInclude] public int RetentionDays { get; set; }
```

Class DatapackReferenceComparison

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DatapackReferenceComparison

Implements IEquatable < DatapackReferenceComparison >

```
public sealed record DatapackReferenceComparison : IEquatable<DatapackReferenceComparison>
```

✨ Constructors 1

DatapackReferenceComparison(string, string, bool, int, int, int, int, int, int, bool, bool, bool, bool, bool, bool, bool, int, int, string[], string[], string)

```
public DatapackReferenceComparison(string GeneratedZipPath, string ReferenceZipPath, bool ReferenceExists, int GeneratedFileCount, int
GeneratedFunctionFileCount, int GeneratedPlaceholderCount, int ReferenceFileCount, int ReferenceFunctionFileCount, int ReferencePlaceholderCount, bool
GeneratedHasRootPackMcmeta, bool ReferenceHasRootPackMcmeta, bool ReferenceHasNestedPackMcmeta, bool GeneratedHasLoadTag, bool GeneratedHasTickTag, bool
ReferenceHasLoadTag, bool ReferenceHasTickTag, int CriticalFileCount, int PreservedCriticalFileCount, string[] PreservedCriticalFiles, string[]
ReferencePlaceholderSamples, string Summary)
```

🐾 Properties 21

CriticalFileCount

```
public int CriticalFileCount { get; init; }
```

GeneratedFileCount

```
public int GeneratedFileCount { get; init; }
```

GeneratedFunctionFileCount

```
public int GeneratedFunctionFileCount { get; init; }
```

GeneratedHasLoadTag

```
public bool GeneratedHasLoadTag { get; init; }
```

GeneratedHasRootPackMcmeta

```
public bool GeneratedHasRootPackMcmeta { get; init; }
```

GeneratedHasTickTag

```
public bool GeneratedHasTickTag { get; init; }
```

GeneratedPlaceholderCount

```
public int GeneratedPlaceholderCount { get; init; }
```

GeneratedZipPath

```
public string GeneratedZipPath { get; init; }
```

PreservedCriticalFileCount

```
public int PreservedCriticalFileCount { get; init; }
```

PreservedCriticalFiles

```
public string[] PreservedCriticalFiles { get; init; }
```

ReferenceExists

```
public bool ReferenceExists { get; init; }
```

ReferenceFileCount

```
public int ReferenceFileCount { get; init; }
```

ReferenceFunctionFileCount

```
public int ReferenceFunctionFileCount { get; init; }
```

ReferenceHasLoadTag

```
public bool ReferenceHasLoadTag { get; init; }
```

ReferenceHasNestedPackMcmeta

```
public bool ReferenceHasNestedPackMcmeta { get; init; }
```


ReferenceHasRootPackMcmeta

```
public bool ReferenceHasRootPackMcmeta { get; init; }
```

ReferenceHasTickTag

```
public bool ReferenceHasTickTag { get; init; }
```

ReferencePlaceholderCount

```
public int ReferencePlaceholderCount { get; init; }
```

ReferencePlaceholderSamples

```
public string[] ReferencePlaceholderSamples { get; init; }
```

ReferenceZipPath

```
public string ReferenceZipPath { get; init; }
```

Summary

```
public string Summary { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out bool, out int, out int, out int, out int, out int, out int, out bool, out bool, out bool, out bool, out bool, out bool, out int, out int, out string[], out string[], out string)

```
public void Deconstruct(out string GeneratedZipPath, out string ReferenceZipPath, out bool ReferenceExists, out int GeneratedFileCount, out int GeneratedFunctionFileCount, out int GeneratedPlaceholderCount, out int ReferenceFileCount, out int ReferenceFunctionFileCount, out int ReferencePlaceholderCount, out bool GeneratedHasRootPackMcmeta, out bool ReferenceHasRootPackMcmeta, out bool ReferenceHasNestedPackMcmeta, out bool GeneratedHasLoadTag, out bool GeneratedHasTickTag, out bool ReferenceHasLoadTag, out bool ReferenceHasTickTag, out int CriticalFileCount, out int PreservedCriticalFileCount, out string[] PreservedCriticalFiles, out string[] ReferencePlaceholderSamples, out string Summary)
```

Equals(DatapackReferenceComparison?)

```
public bool Equals(DatapackReferenceComparison? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(DatapackReferenceComparison?, DatapackReferenceComparison?)

```
public static bool operator ==(DatapackReferenceComparison? left, DatapackReferenceComparison? right)
```

operator !=(DatapackReferenceComparison?, DatapackReferenceComparison?)

```
public static bool operator !=(DatapackReferenceComparison? left, DatapackReferenceComparison? right)
```

Class DebugArtifactInspectionResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DebugArtifactInspectionResult

```
public sealed class DebugArtifactInspectionResult
```

🌟 Constructors 1

DebugArtifactInspectionResult()

```
public DebugArtifactInspectionResult()
```

🐾 Properties 8

Documents

```
public List<string> Documents { get; set; }
```

FileName

```
public string FileName { get; set; }
```

Format

```
public string Format { get; set; }
```

FullPath

```
public string FullPath { get; set; }
```

LastWriteUtc

```
public DateTime LastWriteUtc { get; set; }
```

Metadata

```
public List<string> Metadata { get; set; }
```

SizeBytes

```
public long SizeBytes { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class DeferredDxAiExecutionOutcome

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DeferredDxAiExecutionOutcome

Implements IEquatable < DeferredDxAiExecutionOutcome >

```
public sealed record DeferredDxAiExecutionOutcome : IEquatable<DeferredDxAiExecutionOutcome>
```

🌟 Constructors 1

DeferredDxAiExecutionOutcome(Guid, Guid, string, string, string, string)

```
public DeferredDxAiExecutionOutcome(Guid DeferredInvocationId, Guid ApprovalRequestId, string FunctionName, string Status, string ResultStatus, string ResultSummary)
```

🐾 Properties 6

ApprovalRequestId

```
public Guid ApprovalRequestId { get; init; }
```

DeferredInvocationId

```
public Guid DeferredInvocationId { get; init; }
```

FunctionName

```
public string FunctionName { get; init; }
```

ResultStatus

```
public string ResultStatus { get; init; }
```

ResultSummary

```
public string ResultSummary { get; init; }
```

Status

```
public string Status { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out Guid, out string, out string, out string, out string)

```
public void Deconstruct(out Guid DeferredInvocationId, out Guid ApprovalRequestId, out string FunctionName, out string Status, out string ResultStatus, out string ResultSummary)
```

Equals(DeferredDxAiExecutionOutcome?)

```
public bool Equals(DeferredDxAiExecutionOutcome? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(DeferredDxAiExecutionOutcome?, DeferredDxAiExecutionOutcome?)

```
public static bool operator ==(DeferredDxAiExecutionOutcome? left, DeferredDxAiExecutionOutcome? right)
```

operator !=(DeferredDxAiExecutionOutcome?, DeferredDxAiExecutionOutcome?)

```
public static bool operator !=(DeferredDxAiExecutionOutcome? left, DeferredDxAiExecutionOutcome? right)
```

Class DeferredDxAiInvocation

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DeferredDxAiInvocation

```
public sealed class DeferredDxAiInvocation
```

🌟 Constructors 1

DeferredDxAiInvocation()

```
public DeferredDxAiInvocation()
```

🐾 Properties 21

ApplicationVersion

```
public string ApplicationVersion { get; set; }
```

ApprovalRequestId

```
public Guid ApprovalRequestId { get; set; }
```

AttemptCount

```
public int AttemptCount { get; set; }
```

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

ConfirmationSummaryHash

```
public string ConfirmationSummaryHash { get; set; }
```

ConversationId

```
public Guid? ConversationId { get; set; }
```

CorrelationId

```
public string CorrelationId { get; set; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

FunctionName

```
public string FunctionName { get; set; }
```

Id

```
public Guid Id { get; set; }
```

LastAttemptAtUtc

```
public DateTime? LastAttemptAtUtc { get; set; }
```

OperationId

```
public Guid OperationId { get; set; }
```

ParametersJson

```
public string ParametersJson { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; set; }
```

RequestedBy

```
public string RequestedBy { get; set; }
```

ResultStatus

```
public string ResultStatus { get; set; }
```

ResultSummary

```
public string ResultSummary { get; set; }
```

Status

```
public string Status { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

api/LocalGPT.BusinessObjects.DiscoverProjectCompilersRequest.html

Class DiscoverProjectCompilersRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Describes one approval-gated compiler and runtime discovery request.
Inheritance object DiscoverProjectCompilersRequest

```
[DocumentationUpdated("2.1.23")] public sealed class DiscoverProjectCompilersRequest
```

🌟 Constructors 1

DiscoverProjectCompilersRequest()

```
public DiscoverProjectCompilersRequest()
```

🐾 Properties 4

CustomSearchRoots

Gets or sets additional absolute directories that LocalGPT may inspect.

```
public List<string> CustomSearchRoots { get; set; }
```

CustomSearchRootsText

Gets or sets optional newline-delimited search roots for UI and HTTP clients.

```
public string CustomSearchRootsText { get; set; }
```

SaveDiscovered

Gets or sets whether detected executable profiles are persisted in the project database.

```
public bool SaveDiscovered { get; set; }
```

UserConfirmed

Gets or sets whether the user explicitly approved bounded local path discovery and persistence.

```
public bool UserConfirmed { get; set; }
```

Class DocumentationBuildRecord

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Persistent evidence for one documentation build or fallback generation.
Inheritance object DocumentationBuildRecord

```
[DocumentationUpdated("2.1.23")] public sealed class DocumentationBuildRecord
```

🌟 Constructors 1

DocumentationBuildRecord()

```
public DocumentationBuildRecord()
```

🐾 Properties 10

DocumentationMode

Gets or sets the HTML generation mode, such as DocFX or static fallback.

```
[MaxLength(120)] public string DocumentationMode { get; set; }
```

GeneratedAtUtc

Gets or sets the UTC generation timestamp.

```
public DateTime GeneratedAtUtc { get; set; }
```

HtmlAvailable

Gets or sets whether an HTML index was published.

```
public bool HtmlAvailable { get; set; }
```

Id

Gets or sets the stable database identifier.

```
public Guid Id { get; set; }
```

OutputRoot

Gets or sets the published documentation root.

```
[MaxLength(2048)] public string OutputRoot { get; set; }
```

PdfAvailable

Gets or sets whether a versioned PDF was published.

```
public bool PdfAvailable { get; set; }
```

PdfMode

Gets or sets the PDF generation mode, such as DocFX or minimal fallback.

```
[MaxLength(120)] public string PdfMode { get; set; }
```

ToolSource

Gets or sets the source tool selection used for this build.

```
[MaxLength(240)] public string ToolSource { get; set; }
```

Version

Gets or sets the LocalGPT version documented by this build.

```
[MaxLength(80)] public string Version { get; set; }
```

Warning

Gets or sets a bounded warning or fallback explanation.

```
[MaxLength(4000)] public string Warning { get; set; }
```

Class DocumentationUpdatedAttribute

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Marks a documented type with the LocalGPT version in which its maintained XML documentation was last reviewed.

Inheritance object Attribute DocumentationUpdatedAttribute

```
[AttributeUsage(AttributeTargets.Class|AttributeTargets.Struct|AttributeTargets.Enum|AttributeTargets.Interface|AttributeTargets.Delegate, Inherited = true, AllowMultiple = false)] public sealed class DocumentationUpdatedAttribute : Attribute
```

🌟 Constructors 1

DocumentationUpdatedAttribute(string)

Creates documentation-version metadata for a maintained public contract.

```
public DocumentationUpdatedAttribute(string version)
```

🐾 Properties 1

Version

Gets the LocalGPT version that last reviewed the annotated contract documentation.

```
public string Version { get; }
```

Class DxaichatFunctionInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxaichatFunctionInfo

Implements IEquatable < DxaichatFunctionInfo >

```
public sealed record DxaichatFunctionInfo : IEquatable<DxaichatFunctionInfo>
```

🌟 Constructors 1

DxaichatFunctionInfo(string, string, string, string, string, string, bool, bool, bool, bool, bool, string, string, bool, bool, bool)

```
public DxaichatFunctionInfo(string Name, string Method, string Route, string Purpose, string Parameters, string SafetyNotes, bool IsReadOnly = true, bool AvailableToAi = true, bool RequiresHumanConfirmation = false, bool SupportsDirectInvocation = false, bool SupportsAutomaticInvocation = false, string Source = "ControllerRoute", string ParameterSchemaJson = "{\n\"type\":\n\"object\", \"properties\":{}}", bool IsCoordinationOnly = false, bool SupportsDeferredApprovalRequest = false, bool ApprovalRequiredBeforeCompletion = false)
```

🐾 Properties 16

ApprovalRequiredBeforeCompletion

```
public bool ApprovalRequiredBeforeCompletion { get; init; }
```

AvailableToAi

```
public bool AvailableToAi { get; init; }
```

IsCoordinationOnly

```
public bool IsCoordinationOnly { get; init; }
```

IsReadOnly

```
public bool IsReadOnly { get; init; }
```

Method

```
public string Method { get; init; }
```

Name

```
public string Name { get; init; }
```

ParameterSchemaJson

```
public string ParameterSchemaJson { get; init; }
```

Parameters

```
public string Parameters { get; init; }
```

Purpose

```
public string Purpose { get; init; }
```

RequiresHumanConfirmation

```
public bool RequiresHumanConfirmation { get; init; }
```

Route

```
public string Route { get; init; }
```

SafetyNotes

```
public string SafetyNotes { get; init; }
```

Source

```
public string Source { get; init; }
```

SupportsAutomaticInvocation

```
public bool SupportsAutomaticInvocation { get; init; }
```

SupportsDeferredApprovalRequest

```
public bool SupportsDeferredApprovalRequest { get; init; }
```


SupportsDirectInvocation

```
public bool SupportsDirectInvocation { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out string, out bool, out bool, out bool, out bool, out bool, out string, out string, out bool, out bool, out bool)

```
public void Deconstruct(out string Name, out string Method, out string Route, out string Purpose, out string Parameters, out string SafetyNotes, out bool IsReadOnly, out bool AvailableToAi, out bool RequiresHumanConfirmation, out bool SupportsDirectInvocation, out bool SupportsAutomaticInvocation, out string Source, out string ParameterSchemaJson, out bool IsCoordinationOnly, out bool SupportsDeferredApprovalRequest, out bool ApprovalRequiredBeforeCompletion)
```

Equals(DxaichatFunctionInfo?)

```
public bool Equals(DxaichatFunctionInfo? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(DxaichatFunctionInfo?, DxaichatFunctionInfo?)

```
public static bool operator ==(DxaichatFunctionInfo? left, DxaichatFunctionInfo? right)
```

operator !=(DxaichatFunctionInfo?, DxaichatFunctionInfo?)

```
public static bool operator !=(DxaichatFunctionInfo? left, DxaichatFunctionInfo? right)
```

api/LocalGPT.BusinessObjects.DxaichatSmokeRequest.html

Class DxaichatSmokeRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxaichatSmokeRequest

```
public sealed class DxaichatSmokeRequest
```

🌟 Constructors 1

DxaichatSmokeRequest()

```
public DxaichatSmokeRequest()
```

🐾 Properties 5

IncludeDiagnosticSystemPrompt

```
public bool IncludeDiagnosticSystemPrompt { get; set; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

SaveToMemory

```
public bool SaveToMemory { get; set; }
```

Title

```
public string? Title { get; set; }
```

Class DxAiFunctionCatalogEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Database-backed, user-editable policy and discovery record for a DX function or public application service method. Descriptor metadata is refreshed from the running application while user policy fields are preserved.

Inheritance object DxAiFunctionCatalogEntry

```
public sealed class DxAiFunctionCatalogEntry
```

🌟 Constructors 1

DxAiFunctionCatalogEntry()

```
public DxAiFunctionCatalogEntry()
```

🐾 Properties 27

AllowRemoteInvocation

```
public bool AllowRemoteInvocation { get; set; }
```

AllowedPeerIdsJson

```
public string AllowedPeerIdsJson { get; set; }
```

CatalogKey

```
public string CatalogKey { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

DescriptorHash

```
public string DescriptorHash { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

ExposeToAiChat

```
public bool ExposeToAiChat { get; set; }
```

ExposeToOneWire

```
public bool ExposeToOneWire { get; set; }
```

FunctionName

```
public string FunctionName { get; set; }
```

ImplementationTypeName

```
public string ImplementationTypeName { get; set; }
```

InteractionEditor

```
public OneWireInteractionEditor InteractionEditor { get; set; }
```

IsAvailable

```
public bool IsAvailable { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsReadOnly

```
public bool IsReadOnly { get; set; }
```

IsSystemSeed

```
public bool IsSystemSeed { get; set; }
```

Kind

```
public string Kind { get; set; }
```

Method

```
public string Method { get; set; }
```

ParameterSchemaJson

```
public string ParameterSchemaJson { get; set; }
```

ParameterTypeNamesJson

```
public string ParameterTypeNamesJson { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

RequiresFrontendConfirmation

```
public bool RequiresFrontendConfirmation { get; set; }
```

Route

```
public string Route { get; set; }
```

ServiceContractTypeName

```
public string ServiceContractTypeName { get; set; }
```

ServiceMethodName

```
public string ServiceMethodName { get; set; }
```

Source

```
public string Source { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

UpdatedBy

```
public string UpdatedBy { get; set; }
```

Methods 2

AllowsPeer(string)

```
public bool AllowsPeer(string peerId)
```

GetAllowedPeerIds()

```
public IReadOnlyList<string> GetAllowedPeerIds()
```

Class DxAiFunctionCatalogSaveRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxAiFunctionCatalogSaveRequest

```
public sealed class DxAiFunctionCatalogSaveRequest
```

🌟 Constructors 1

DxAiFunctionCatalogSaveRequest()

```
public DxAiFunctionCatalogSaveRequest()
```

🐾 Properties 9

AllowRemoteInvocation

```
public bool AllowRemoteInvocation { get; set; }
```

AllowedPeerIdsJson

```
public string AllowedPeerIdsJson { get; set; }
```

CatalogKey

```
public string CatalogKey { get; set; }
```

ExposeToAiChat

```
public bool ExposeToAiChat { get; set; }
```

ExposeToOneWire

```
public bool ExposeToOneWire { get; set; }
```

InteractionEditor

```
public OneWireInteractionEditor InteractionEditor { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

RequiresFrontendConfirmation

```
public bool RequiresFrontendConfirmation { get; set; }
```

UpdatedBy

```
public string UpdatedBy { get; set; }
```

Class DxAiFunctionInvocationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxAiFunctionInvocationRequest

```
public sealed class DxAiFunctionInvocationRequest
```

🌟 Constructors 1

DxAiFunctionInvocationRequest()

```
public DxAiFunctionInvocationRequest()
```

🐾 Properties 10

ApplicationVersion

```
public string ApplicationVersion { get; set; }
```

AutomaticInvocation

```
public bool AutomaticInvocation { get; set; }
```

ConfirmationSummaryHash

```
public string? ConfirmationSummaryHash { get; set; }
```

ConversationId

```
public Guid? ConversationId { get; set; }
```

OperationId

```
public Guid? OperationId { get; set; }
```

Parameters

```
public JsonElement Parameters { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; set; }
```

RequestedBy

```
public string RequestedBy { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class DxAiFunctionInvocationResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxAiFunctionInvocationResult

```
public sealed class DxAiFunctionInvocationResult
```

🌟 Constructors 1

DxAiFunctionInvocationResult()

```
public DxAiFunctionInvocationResult()
```

🐾 Properties 6

Error

```
public string? Error { get; set; }
```

FunctionName

```
public string FunctionName { get; set; }
```

OperationId

```
public Guid OperationId { get; set; }
```

Status

```
public string Status { get; set; }
```

Succeeded

```
public bool Succeeded { get; set; }
```

Value

```
public object? Value { get; set; }
```

Class DxAiFunctionParameterBinding<T>

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object DxAiFunctionParameterBinding<T>

```
public sealed class DxAiFunctionParameterBinding<T> where T : new()
```

🌟 Constructors 1

DxAiFunctionParameterBinding()

```
public DxAiFunctionParameterBinding()
```

🐾 Properties 3

Error

```
public string Error { get; init; }
```

Succeeded

```
public bool Succeeded { get; init; }
```

Value

```
public T Value { get; init; }
```

Namespace LocalGPT.BusinessObjects.EFCore

Classes

Class LocalGptMemoryDbContext

Namespace LocalGPT . BusinessObjects . EFCore Assembly LocalGPT.dll

Inheritance object DbContext LocalGptMemoryDbContext

Implements [IInfrastructure](#) < [IServiceProvider](#) > [IDbContextDependencies](#) [IDbSetCache](#) [IDbContextPoolable](#) [IResettableService](#) [IDisposable](#) [IAsyncDisposable](#)

```
public class LocalGptMemoryDbContext : DbContext, IInfrastructure<IServiceProvider>, IDbContextDependencies, IDbSetCache, IDbContextPoolable, IResettableService, IDisposable, IAsyncDisposable
```

🌟 Constructors 1

LocalGptMemoryDbContext(DbContextOptions<LocalGptMemoryDbContext>)

```
public LocalGptMemoryDbContext(DbContextOptions<LocalGptMemoryDbContext> options)
```

🐾 Properties 39

ApplicationLogs

```
public DbSet<ApplicationLogEntry> ApplicationLogs { get; }
```

CodeGenerationChangeReviews

```
public DbSet<CodeGenerationChangeReview> CodeGenerationChangeReviews { get; }
```

Conversations

```
public DbSet<ChatMemoryConversation> Conversations { get; }
```

CouncilGameSessionRecords

```
public DbSet<CouncilGameSessionRecord> CouncilGameSessionRecords { get; }
```

CouncilKnowledgeEntries

```
public DbSet<CouncilKnowledgeEntry> CouncilKnowledgeEntries { get; }
```

CouncilKnowledgeUserRatings

```
public DbSet<CouncilKnowledgeUserRating> CouncilKnowledgeUserRatings { get; }
```

CouncilMemberOrganicSkillLinks

```
public DbSet<CouncilMemberOrganicSkillLink> CouncilMemberOrganicSkillLinks { get; }
```

CouncilModelPresets

```
public DbSet<CouncilModelPreset> CouncilModelPresets { get; }
```

CouncilPromptStarterConfigurations

```
public DbSet<CouncilPromptStarterConfiguration> CouncilPromptStarterConfigurations { get; }
```

CouncilRuntimeClassConfigurations

```
public DbSet<CouncilRuntimeClassConfiguration> CouncilRuntimeClassConfigurations { get; }
```

CouncilTeamConfigurations

```
public DbSet<CouncilTeamConfiguration> CouncilTeamConfigurations { get; }
```

DeferredDxAiInvocations

```
public DbSet<DeferredDxAiInvocation> DeferredDxAiInvocations { get; }
```

DocumentationBuildRecords

```
public DbSet<DocumentationBuildRecord> DocumentationBuildRecords { get; }
```

EmbeddedFirmwarePlanRecords

```
public DbSet<EmbeddedFirmwarePlanRecord> EmbeddedFirmwarePlanRecords { get; }
```

HumanCollaborationRequests

```
public DbSet<HumanCollaborationRequest> HumanCollaborationRequests { get; }
```

HumanCouncilContributions

```
public DbSet<HumanCouncilContribution> HumanCouncilContributions { get; }
```

HumanCouncilParticipantProfiles

```
public DbSet<HumanCouncilParticipantProfile> HumanCouncilParticipantProfiles { get; }
```

LocalGptProjectArtifacts

```
public DbSet<LocalGptProjectArtifact> LocalGptProjectArtifacts { get; }
```

LocalGptProjectRequirementLinks

```
public DbSet<LocalGptProjectRequirementLink> LocalGptProjectRequirementLinks { get; }
```

LocalGptProjectRequirements

```
public DbSet<LocalGptProjectRequirement> LocalGptProjectRequirements { get; }
```

LocalGptProjectRevisions

```
public DbSet<LocalGptProjectRevision> LocalGptProjectRevisions { get; }
```

LocalGptProjectTopicKnowledgeLinks

```
public DbSet<LocalGptProjectTopicKnowledgeLink> LocalGptProjectTopicKnowledgeLinks { get; }
```

LocalGptProjectTopics

```
public DbSet<LocalGptProjectTopic> LocalGptProjectTopics { get; }
```

LocalGptProjectTrackedFiles

```
public DbSet<LocalGptProjectTrackedFile> LocalGptProjectTrackedFiles { get; }
```

LocalGptProjectVersions

```
public DbSet<LocalGptProjectVersion> LocalGptProjectVersions { get; }
```

LocalGptProjects

```
public DbSet<LocalGptProject> LocalGptProjects { get; }
```

LocalizationCatalogRegistrations

```
public DbSet<LocalizationCatalogRegistration> LocalizationCatalogRegistrations { get; }
```

Messages

```
public DbSet<ChatMemoryMessage> Messages { get; }
```

NativeCommandLogs

```
public DbSet<NativeCommandLogEntry> NativeCommandLogs { get; }
```

OrganicSkills

```
public DbSet<OrganicSkillDefinition> OrganicSkills { get; }
```

ProjectBuildVerifications

```
public DbSet<ProjectBuildVerification> ProjectBuildVerifications { get; }
```

ProjectCompilerInstallations

```
public DbSet<ProjectCompilerInstallation> ProjectCompilerInstallations { get; }
```

ProjectDocumentImports

```
public DbSet<ProjectDocumentImport> ProjectDocumentImports { get; }
```


ProjectOrganicSkillLinks

```
public DbSet<ProjectOrganicSkillLink> ProjectOrganicSkillLinks { get; }
```

ProjectWorkspaceRoots

```
public DbSet<ProjectWorkspaceRoot> ProjectWorkspaceRoots { get; }
```

Prompts

```
public DbSet<PromptConfig> Prompts { get; set; }
```

RegexPatterns

```
public DbSet<RegexPattern> RegexPatterns { get; set; }
```

SqliteEditorFieldOverrides

```
public DbSet<SqliteEditorFieldOverride> SqliteEditorFieldOverrides { get; }
```

SystemVariables

```
public DbSet<SystemVariable> SystemVariables { get; set; }
```

⚙️ Methods 1

OnModelCreating(ModelBuilder)

```
protected override void OnModelCreating(ModelBuilder modelBuilder)
```

Class EmailLoggerCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmailLoggerCoreOptions

```
public class EmailLoggerCoreOptions
```

🌟 Constructors 1

EmailLoggerCoreOptions()

```
public EmailLoggerCoreOptions()
```

🔴 Fields 1

EmailLoggerCore

```
public const string EmailLoggerCore = "EmailLoggerCore"
```

🐾 Properties 10

BccRecipients

```
[JsonInclude] public IEnumerable<string> BccRecipients { get; set; }
```

CcRecipients

```
[JsonInclude] public IEnumerable<string> CcRecipients { get; set; }
```

CoreLogLevel

```
[JsonInclude] public CoreLogLevel CoreLogLevel { get; set; }
```

EmailRecipients

```
[JsonInclude] public IEnumerable<string> EmailRecipients { get; set; }
```

EnableSsl

```
[JsonInclude] public bool EnableSsl { get; set; }
```

Password

```
[JsonInclude] public string? Password { get; set; }
```

SenderEmail

```
[JsonInclude] public string? SenderEmail { get; set; }
```

SmtpPort

```
[JsonInclude] public int SmtpPort { get; set; }
```

SmtpServer

```
[JsonInclude] public string? SmtpServer { get; set; }
```

Username

```
[JsonInclude] public string? Username { get; set; }
```

Class EmbeddedBoardCatalog

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedBoardCatalog

```
public sealed class EmbeddedBoardCatalog
```

🌟 Constructors 1

EmbeddedBoardCatalog()

```
public EmbeddedBoardCatalog()
```

🐾 Properties 3

Boards

```
public List<EmbeddedBoardProfile> Boards { get; set; }
```

Protocols

```
public List<EmbeddedProtocolDescriptor> Protocols { get; set; }
```

PublisherWorkbench

```
public EmbeddedPublisherWorkbenchContract PublisherWorkbench { get; set; }
```

Class EmbeddedBoardPinProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedBoardPinProfile

```
public sealed class EmbeddedBoardPinProfile
```

🌟 Constructors 1

EmbeddedBoardPinProfile()

```
public EmbeddedBoardPinProfile()
```

🐾 Properties 13

CanvasX

```
public double CanvasX { get; set; }
```

CanvasY

```
public double CanvasY { get; set; }
```

Capabilities

```
public List<string> Capabilities { get; set; }
```

Gpio

```
public int? Gpio { get; set; }
```

IsBootStrap

```
public bool IsBootStrap { get; set; }
```

IsGroundPin

```
public bool IsGroundPin { get; set; }
```

IsInputOnly

```
public bool IsInputOnly { get; set; }
```

IsPowerPin

```
public bool IsPowerPin { get; set; }
```

IsReserved

```
public bool IsReserved { get; set; }
```

Label

```
public string Label { get; set; }
```

PinKey

```
public string PinKey { get; set; }
```

Voltage

```
public double? Voltage { get; set; }
```

Warning

```
public string Warning { get; set; }
```

Class EmbeddedBoardProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedBoardProfile

```
public sealed class EmbeddedBoardProfile
```

🌟 Constructors 1

EmbeddedBoardProfile()

```
public EmbeddedBoardProfile()
```

🐾 Properties 11

DisplayName

```
public string DisplayName { get; set; }
```

DocumentationSource

```
public string DocumentationSource { get; set; }
```

Family

```
public string Family { get; set; }
```

Framework

```
public string Framework { get; set; }
```

Key

```
public string Key { get; set; }
```

LogicVoltage

```
public double LogicVoltage { get; set; }
```

Notes

```
public List<string> Notes { get; set; }
```

Pins

```
public List<EmbeddedBoardPinProfile> Pins { get; set; }
```

PlatformIoBoard

```
public string PlatformIoBoard { get; set; }
```

Status

```
public string Status { get; set; }
```

SupportedProtocols

```
public List<string> SupportedProtocols { get; set; }
```

Class EmbeddedFirmwareArtifactResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedFirmwareArtifactResult

```
public sealed class EmbeddedFirmwareArtifactResult
```

🌟 Constructors 1

EmbeddedFirmwareArtifactResult()

```
public EmbeddedFirmwareArtifactResult()
```

🐾 Properties 4

ArtifactDirectory

```
public string ArtifactDirectory { get; set; }
```

Files

```
public List<string> Files { get; set; }
```

PlanId

```
public Guid PlanId { get; set; }
```

ZipPath

```
public string ZipPath { get; set; }
```

Class EmbeddedFirmwarePlan

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedFirmwarePlan

```
public sealed class EmbeddedFirmwarePlan
```

✨ Constructors 1

EmbeddedFirmwarePlan()

```
public EmbeddedFirmwarePlan()
```

🐾 Properties 23

ArduinoSketch

```
public string ArduinoSketch { get; set; }
```

BaudRate

```
public int BaudRate { get; set; }
```

BoardFamily

```
public string BoardFamily { get; set; }
```

BoardName

```
public string BoardName { get; set; }
```

BoardProfileKey

```
public string BoardProfileKey { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

DeviceName

```
public string DeviceName { get; set; }
```

Findings

```
public List<EmbeddedPlanFinding> Findings { get; set; }
```

Framework

```
public string Framework { get; set; }
```

LearningRoundAdvice

```
public string LearningRoundAdvice { get; set; }
```

OneWireContract

```
public EmbeddedOneWireContract OneWireContract { get; set; }
```

OverallStatus

```
public string OverallStatus { get; set; }
```

PinAssignments

```
public List<EmbeddedPinAssignment> PinAssignments { get; set; }
```

PlanId

```
public Guid PlanId { get; set; }
```

PlatformIoConfiguration

```
public string PlatformIoConfiguration { get; set; }
```

ProtocolBindings

```
public List<EmbeddedProtocolBinding> ProtocolBindings { get; set; }
```

TelemetryIntervalMilliseconds

```
public int TelemetryIntervalMilliseconds { get; set; }
```

TelemetryTransport

```
public string TelemetryTransport { get; set; }
```

TransportContracts

```
public List<EmbeddedTransportContract> TransportContracts { get; set; }
```

WiringDraft

```
public EmbeddedWiringDraft? WiringDraft { get; set; }
```

WiringMarkdown

```
public string WiringMarkdown { get; set; }
```

WiringSteps

```
public List<string> WiringSteps { get; set; }
```

WiringValidation

```
public EmbeddedWiringValidationResult? WiringValidation { get; set; }
```


Class EmbeddedFirmwarePlanRecord

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Persistent envelope for an embedded firmware plan and its generated artifacts.

Inheritance object EmbeddedFirmwarePlanRecord

```
[DocumentationUpdated("2.1.23")] public sealed class EmbeddedFirmwarePlanRecord
```

🌟 Constructors 1

EmbeddedFirmwarePlanRecord()

```
public EmbeddedFirmwarePlanRecord()
```

🐾 Properties 9

BoardProfileKey

Gets or sets the selected board profile key.

```
[MaxLength(160)] public string BoardProfileKey { get; set; }
```

CreatedAtUtc

Gets or sets the UTC creation timestamp.

```
public DateTime CreatedAtUtc { get; set; }
```

DeviceName

Gets or sets the target device name.

```
[MaxLength(240)] public string DeviceName { get; set; }
```

Id

Gets or sets the stable database identifier.

```
public Guid Id { get; set; }
```

PlanJson

Gets or sets the complete versioned plan JSON.

```
public string PlanJson { get; set; }
```

PlanKey

Gets or sets the stable planning identifier.

```
[MaxLength(160)] public string PlanKey { get; set; }
```

ProjectId

Gets or sets an optional LocalGPT project identifier.

```
public Guid? ProjectId { get; set; }
```

Status

Gets or sets the planning or approval status.

```
[MaxLength(80)] public string Status { get; set; }
```

UpdatedAtUtc

Gets or sets the UTC update timestamp.

```
public DateTime UpdatedAtUtc { get; set; }
```

Class EmbeddedFirmwarePlanRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedFirmwarePlanRequest

```
public sealed class EmbeddedFirmwarePlanRequest
```

🌟 Constructors 1

EmbeddedFirmwarePlanRequest()

```
public EmbeddedFirmwarePlanRequest()
```

🐾 Properties 13

AdditionalRequirements

```
[MaxLength(8000)] public string AdditionalRequirements { get; set; }
```

BaudRate

```
public int BaudRate { get; set; }
```

BoardFamily

```
[MaxLength(120)] public string BoardFamily { get; set; }
```

BoardName

```
[MaxLength(160)] public string BoardName { get; set; }
```

BoardProfileKey

```
[MaxLength(160)] public string BoardProfileKey { get; set; }
```

DeviceName

```
[MaxLength(120)] public string DeviceName { get; set; }
```

Framework

```
[MaxLength(80)] public string Framework { get; set; }
```

Pins

```
public List<EmbeddedPinRequirement> Pins { get; set; }
```

ProtocolBindings

```
public List<EmbeddedProtocolBinding> ProtocolBindings { get; set; }
```

Sensors

```
public List<EmbeddedSensorRequirement> Sensors { get; set; }
```

TelemetryIntervalMilliseconds

```
public int TelemetryIntervalMilliseconds { get; set; }
```

TelemetryTransport

```
[MaxLength(120)] public string TelemetryTransport { get; set; }
```

WiringDraft

```
public EmbeddedWiringDraft? WiringDraft { get; set; }
```

Class EmbeddedOneWireContract

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedOneWireContract

```
public sealed class EmbeddedOneWireContract
```

🌟 Constructors 1

EmbeddedOneWireContract()

```
public EmbeddedOneWireContract()
```

🐾 Properties 7

CapabilityKey

```
public string CapabilityKey { get; set; }
```

Controller

```
public string Controller { get; set; }
```

Direction

```
public string Direction { get; set; }
```

ExampleEnvelopeJson

```
public string ExampleEnvelopeJson { get; set; }
```

Method

```
public string Method { get; set; }
```

ProtocolVersion

```
public string ProtocolVersion { get; set; }
```

TransportBoundary

```
public string TransportBoundary { get; set; }
```

Class EmbeddedPinAssignment

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedPinAssignment

```
public sealed class EmbeddedPinAssignment
```

🌟 Constructors 1

EmbeddedPinAssignment()

```
public EmbeddedPinAssignment()
```

🐾 Properties 12

BusKey

```
public string BusKey { get; set; }
```

Function

```
public string Function { get; set; }
```

Gpio

```
public int Gpio { get; set; }
```

Metric

```
public string Metric { get; set; }
```

Mode

```
public string Mode { get; set; }
```

Notes

```
public string Notes { get; set; }
```

PinKey

```
public string PinKey { get; set; }
```

ProtocolKey

```
public string ProtocolKey { get; set; }
```

SensorKey

```
public string SensorKey { get; set; }
```

Status

```
public string Status { get; set; }
```

SupplyVoltage

```
public double SupplyVoltage { get; set; }
```

Unit

```
public string Unit { get; set; }
```

Class EmbeddedPinRequirement

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedPinRequirement

```
public sealed class EmbeddedPinRequirement
```

🌟 Constructors 1

EmbeddedPinRequirement()

```
public EmbeddedPinRequirement()
```

🐾 Properties 11

BusKey

```
[MaxLength(120)] public string BusKey { get; set; }
```

Function

```
[MaxLength(120)] public string Function { get; set; }
```

Gpio

```
public int Gpio { get; set; }
```

Metric

```
[MaxLength(80)] public string Metric { get; set; }
```

Mode

```
[MaxLength(80)] public string Mode { get; set; }
```

Notes

```
[MaxLength(1000)] public string Notes { get; set; }
```

PinKey

```
[MaxLength(80)] public string PinKey { get; set; }
```

ProtocolKey

```
[MaxLength(120)] public string ProtocolKey { get; set; }
```

SensorKey

```
[MaxLength(120)] public string SensorKey { get; set; }
```

SupplyVoltage

```
public double SupplyVoltage { get; set; }
```

Unit

```
[MaxLength(80)] public string Unit { get; set; }
```

Class EmbeddedPlanFinding

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedPlanFinding

Implements IEquatable < EmbeddedPlanFinding >

```
public sealed record EmbeddedPlanFinding : IEquatable<EmbeddedPlanFinding>
```

🌟 Constructors 1

EmbeddedPlanFinding(string, string, string, int?, string)

```
public EmbeddedPlanFinding(string Severity, string Code, string Message, int? Gpio = null, string PinKey = "")
```

🐾 Properties 5

Code

```
public string Code { get; init; }
```

Gpio

```
public int? Gpio { get; init; }
```

Message

```
public string Message { get; init; }
```

PinKey

```
public string PinKey { get; init; }
```

Severity

```
public string Severity { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out int?, out string)

```
public void Deconstruct(out string Severity, out string Code, out string Message, out int? Gpio, out string PinKey)
```

Equals(EmbeddedPlanFinding?)

```
public bool Equals(EmbeddedPlanFinding? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(EmbeddedPlanFinding?, EmbeddedPlanFinding?)

```
public static bool operator ==(EmbeddedPlanFinding? left, EmbeddedPlanFinding? right)
```

operator !=(EmbeddedPlanFinding?, EmbeddedPlanFinding?)

```
public static bool operator !=(EmbeddedPlanFinding? left, EmbeddedPlanFinding? right)
```

Class EmbeddedProtocolBinding

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedProtocolBinding

```
public sealed class EmbeddedProtocolBinding
```

🌟 Constructors 1

EmbeddedProtocolBinding()

```
public EmbeddedProtocolBinding()
```

🐾 Properties 9

CapabilityKey

```
[MaxLength(200)] public string CapabilityKey { get; set; }
```

Direction

```
[MaxLength(120)] public string Direction { get; set; }
```

Key

```
[MaxLength(120)] public string Key { get; set; }
```

PinKeys

```
public List<string> PinKeys { get; set; }
```

ProtocolKey

```
[MaxLength(120)] public string ProtocolKey { get; set; }
```

Role

```
[MaxLength(120)] public string Role { get; set; }
```

SettingsJson

```
public string SettingsJson { get; set; }
```

TargetController

```
[MaxLength(160)] public string TargetController { get; set; }
```

TargetMethod

```
[MaxLength(160)] public string TargetMethod { get; set; }
```

Class EmbeddedProtocolDescriptor

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedProtocolDescriptor

```
public sealed class EmbeddedProtocolDescriptor
```

🌟 Constructors 1

EmbeddedProtocolDescriptor()

```
public EmbeddedProtocolDescriptor()
```

🐾 Properties 10

DisplayName

```
public string DisplayName { get; set; }
```

Key

```
public string Key { get; set; }
```

Layer

```
public string Layer { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

RequiredRoles

```
public List<string> RequiredRoles { get; set; }
```

RequiresExternalHardware

```
public bool RequiresExternalHardware { get; set; }
```

RequiresGateway

```
public bool RequiresGateway { get; set; }
```

SafetyNote

```
public string SafetyNote { get; set; }
```

SupportedByGeneratedSketch

```
public bool SupportedByGeneratedSketch { get; set; }
```

SupportsSharedBus

```
public bool SupportsSharedBus { get; set; }
```


Class EmbeddedProtocolKeys

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedProtocolKeys

```
public sealed class EmbeddedProtocolKeys
```

Fields 15

AnalogAdc

```
public const string AnalogAdc = "gpio.analog"
```

Can

```
public const string Can = "bus.can"
```

Custom

```
public const string Custom = "custom"
```

DigitalGpio

```
public const string DigitalGpio = "gpio.digital"
```

HttpJson

```
public const string HttpJson = "transport.http-json"
```

I2c

```
public const string I2c = "bus.i2c"
```

LocalGptOneWire

```
public const string LocalGptOneWire = "localgpt.onewire-envelope"
```

Mqtt

```
public const string Mqtt = "transport.mqtt"
```

OrganicPeer

```
public const string OrganicPeer = "localgpt.organic-peer"
```

PhysicalOneWire

```
public const string PhysicalOneWire = "bus.onewire.physical"
```

Pwm

```
public const string Pwm = "gpio.pwm"
```

Rs485

```
public const string Rs485 = "bus.rs485"
```

SerialJsonLines

```
public const string SerialJsonLines = "transport.serial-json-lines"
```

Spi

```
public const string Spi = "bus.spi"
```

Uart

```
public const string Uart = "bus.uart"
```

Class EmbeddedPublisherWorkbenchContract

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedPublisherWorkbenchContract

```
public sealed class EmbeddedPublisherWorkbenchContract
```

🌟 Constructors 1

EmbeddedPublisherWorkbenchContract()

```
public EmbeddedPublisherWorkbenchContract()
```

🐾 Properties 7

AnimationContract

```
public string AnimationContract { get; set; }
```

CanvasContract

```
public string CanvasContract { get; set; }
```

CapabilityKey

```
public string CapabilityKey { get; set; }
```

Controller

```
public string Controller { get; set; }
```

Method

```
public string Method { get; set; }
```

Route

```
public string Route { get; set; }
```

SupportedOperations

```
public List<string> SupportedOperations { get; set; }
```

Class EmbeddedSensorRequirement

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedSensorRequirement

```
public sealed class EmbeddedSensorRequirement
```

🌟 Constructors 1

EmbeddedSensorRequirement()

```
public EmbeddedSensorRequirement()
```

🐾 Properties 12

BusKey

```
[MaxLength(120)] public string BusKey { get; set; }
```

DriverKey

```
[MaxLength(120)] public string DriverKey { get; set; }
```

Interface

```
[MaxLength(120)] public string Interface { get; set; }
```

Key

```
[MaxLength(120)] public string Key { get; set; }
```

Metric

```
[MaxLength(80)] public string Metric { get; set; }
```

Notes

```
[MaxLength(1000)] public string Notes { get; set; }
```

PreferredGpio

```
public int? PreferredGpio { get; set; }
```

PreferredPinKey

```
[MaxLength(80)] public string PreferredPinKey { get; set; }
```

ProtocolKey

```
[MaxLength(120)] public string ProtocolKey { get; set; }
```

SensorType

```
[MaxLength(160)] public string SensorType { get; set; }
```

SupplyVoltage

```
public double SupplyVoltage { get; set; }
```

Unit

```
[MaxLength(80)] public string Unit { get; set; }
```

Class EmbeddedTelemetryBridgeRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetryBridgeRequest

```
public sealed class EmbeddedTelemetryBridgeRequest
```

🌟 Constructors 1

EmbeddedTelemetryBridgeRequest()

```
public EmbeddedTelemetryBridgeRequest()
```

🐾 Properties 8

BoardProfileKey

```
public string BoardProfileKey { get; set; }
```

DeviceId

```
public string DeviceId { get; set; }
```

DeviceTimestampMilliseconds

```
public long DeviceTimestampMilliseconds { get; set; }
```

MetadataJson

```
public string MetadataJson { get; set; }
```

Readings

```
public List<EmbeddedTelemetryReading> Readings { get; set; }
```

Sequence

```
public long Sequence { get; set; }
```

TargetPeerId

```
public string TargetPeerId { get; set; }
```

TransportKey

```
public string TransportKey { get; set; }
```

Class EmbeddedTelemetryBridgeResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetryBridgeResult

```
public sealed class EmbeddedTelemetryBridgeResult
```

🌟 Constructors 1

EmbeddedTelemetryBridgeResult()

```
public EmbeddedTelemetryBridgeResult()
```

🐾 Properties 5

EdgeEnvelopeJson

```
public string EdgeEnvelopeJson { get; set; }
```

Findings

```
public List<EmbeddedPlanFinding> Findings { get; set; }
```

OneWireEnvelope

```
public OneWireEnvelope? OneWireEnvelope { get; set; }
```

Status

```
public string Status { get; set; }
```

Succeeded

```
public bool Succeeded { get; set; }
```

Class EmbeddedTelemetryIngressResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EmbeddedTelemetryIngressResult

```
public sealed class EmbeddedTelemetryIngressResult
```

🌟 Constructors 1

EmbeddedTelemetryIngressResult()

```
public EmbeddedTelemetryIngressResult()
```

🐾 Properties 7

Accepted

```
public bool Accepted { get; set; }
```

DeviceId

```
public string DeviceId { get; set; }
```

Findings

```
public List<EmbeddedPlanFinding> Findings { get; set; }
```

ReadingCount

```
public int ReadingCount { get; set; }
```

ReceivedAtUtc

```
public DateTime ReceivedAtUtc { get; set; }
```

Sequence

```
public long Sequence { get; set; }
```

Status

```
public string Status { get; set; }
```

Class EmbeddedTelemetryReading

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetryReading

```
public sealed class EmbeddedTelemetryReading
```

🌟 Constructors 1

EmbeddedTelemetryReading()

```
public EmbeddedTelemetryReading()
```

🐾 Properties 7

Gpio

```
public int? Gpio { get; set; }
```

Metric

```
public string Metric { get; set; }
```

PinKey

```
public string PinKey { get; set; }
```

Quality

```
public string Quality { get; set; }
```

SensorKey

```
public string SensorKey { get; set; }
```

Unit

```
public string Unit { get; set; }
```

Value

```
public double Value { get; set; }
```

Class EmbeddedTelemetrySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetrySnapshot

```
public sealed class EmbeddedTelemetrySnapshot
```

🌟 Constructors 1

EmbeddedTelemetrySnapshot()

```
public EmbeddedTelemetrySnapshot()
```

🐾 Properties 6

BoardProfileKey

```
public string BoardProfileKey { get; set; }
```

DeviceId

```
public string DeviceId { get; set; }
```

Readings

```
public List<EmbeddedTelemetryReading> Readings { get; set; }
```

ReceivedAtUtc

```
public DateTime ReceivedAtUtc { get; set; }
```

Sequence

```
public long Sequence { get; set; }
```

TransportKey

```
public string TransportKey { get; set; }
```


Class EmbeddedTransportContract

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedTransportContract

```
public sealed class EmbeddedTransportContract
```

✨ Constructors 1

EmbeddedTransportContract()

```
public EmbeddedTransportContract()
```

🐾 Properties 10

Boundary

```
public string Boundary { get; set; }
```

CapabilityKey

```
public string CapabilityKey { get; set; }
```

Controller

```
public string Controller { get; set; }
```

Direction

```
public string Direction { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

ExampleEnvelopeJson

```
public string ExampleEnvelopeJson { get; set; }
```

Method

```
public string Method { get; set; }
```

ProtocolKey

```
public string ProtocolKey { get; set; }
```

RequiresGateway

```
public bool RequiresGateway { get; set; }
```

RequiresOneWireSecurity

```
public bool RequiresOneWireSecurity { get; set; }
```

Class EmbeddedWiringConnection

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringConnection

```
public sealed class EmbeddedWiringConnection
```

✨ Constructors 1

EmbeddedWiringConnection()

```
public EmbeddedWiringConnection()
```

🐾 Properties 12

Animated

```
public bool Animated { get; set; }
```

AnimationKey

```
public string AnimationKey { get; set; }
```

BusKey

```
public string BusKey { get; set; }
```

Direction

```
public string Direction { get; set; }
```

Id

```
public string Id { get; set; }
```

PropertiesJson

```
public string PropertiesJson { get; set; }
```

ProtocolKey

```
public string ProtocolKey { get; set; }
```

SignalName

```
public string SignalName { get; set; }
```

SourceNodeId

```
public string SourceNodeId { get; set; }
```

StyleKey

```
public string StyleKey { get; set; }
```

TargetNodeId

```
public string TargetNodeId { get; set; }
```

Voltage

```
public double Voltage { get; set; }
```

Class EmbeddedWiringDraft

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringDraft

```
public sealed class EmbeddedWiringDraft
```

🌟 Constructors 1

EmbeddedWiringDraft()

```
public EmbeddedWiringDraft()
```

🐾 Properties 9

BoardProfileKey

```
public string BoardProfileKey { get; set; }
```

CanvasHeight

```
public double CanvasHeight { get; set; }
```

CanvasWidth

```
public double CanvasWidth { get; set; }
```

Connections

```
public List<EmbeddedWiringConnection> Connections { get; set; }
```

CoordinateSystem

```
public string CoordinateSystem { get; set; }
```

Id

```
public Guid Id { get; set; }
```

MetadataJson

```
public string MetadataJson { get; set; }
```

Name

```
public string Name { get; set; }
```

Nodes

```
public List<EmbeddedWiringNode> Nodes { get; set; }
```

Class EmbeddedWiringDraftCreateRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringDraftCreateRequest

```
public sealed class EmbeddedWiringDraftCreateRequest
```

🌟 Constructors 1

EmbeddedWiringDraftCreateRequest()

```
public EmbeddedWiringDraftCreateRequest()
```

🐾 Properties 2

BoardProfileKey

```
public string BoardProfileKey { get; set; }
```

Name

```
public string Name { get; set; }
```

Class EmbeddedWiringNode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringNode

```
public sealed class EmbeddedWiringNode
```

🌟 Constructors 1

EmbeddedWiringNode()

```
public EmbeddedWiringNode()
```

🐾 Properties 16

Direction

```
public string Direction { get; set; }
```

ElectricalRole

```
public string ElectricalRole { get; set; }
```

Height

```
public double Height { get; set; }
```

Id

```
public string Id { get; set; }
```

Kind

```
public string Kind { get; set; }
```

Label

```
public string Label { get; set; }
```

OpenScadPartKey

```
public string OpenScadPartKey { get; set; }
```

PartKey

```
public string PartKey { get; set; }
```

PinKey

```
public string PinKey { get; set; }
```

PropertiesJson

```
public string PropertiesJson { get; set; }
```

ProtocolKey

```
public string ProtocolKey { get; set; }
```

StyleKey

```
public string StyleKey { get; set; }
```

Voltage

```
public double Voltage { get; set; }
```

Width

```
public double Width { get; set; }
```

X

```
public double X { get; set; }
```

Y

```
public double Y { get; set; }
```

Class EmbeddedWiringValidationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringValidationRequest

```
public sealed class EmbeddedWiringValidationRequest
```

🌟 Constructors 1

EmbeddedWiringValidationRequest()

```
public EmbeddedWiringValidationRequest()
```

🐾 Properties 3

Draft

```
public EmbeddedWiringDraft Draft { get; set; }
```

RequireBoardPinProfileMatch

```
public bool RequireBoardPinProfileMatch { get; set; }
```

RequireGroundPath

```
public bool RequireGroundPath { get; set; }
```

Class EmbeddedWiringValidationResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EmbeddedWiringValidationResult

```
public sealed class EmbeddedWiringValidationResult
```

🌟 Constructors 1

EmbeddedWiringValidationResult()

```
public EmbeddedWiringValidationResult()
```

🐾 Properties 6

CouncilReviewPrompt

```
public string CouncilReviewPrompt { get; set; }
```

DraftId

```
public Guid DraftId { get; set; }
```

Findings

```
public List<EmbeddedPlanFinding> Findings { get; set; }
```

SharedBuses

```
public List<string> SharedBuses { get; set; }
```

Status

```
public string Status { get; set; }
```

UsedProtocols

```
public List<string> UsedProtocols { get; set; }
```

Class EngineeringBenchmarkBuildCheck

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EngineeringBenchmarkBuildCheck

```
public sealed class EngineeringBenchmarkBuildCheck
```

🌟 Constructors 1

EngineeringBenchmarkBuildCheck()

```
public EngineeringBenchmarkBuildCheck()
```

🐾 Properties 8

ArtifactName

```
public string ArtifactName { get; set; }
```

Duration

```
public TimeSpan? Duration { get; set; }
```

ErrorPreview

```
public string ErrorPreview { get; set; }
```

ExitCode

```
public int? ExitCode { get; set; }
```

ExtractedRoot

```
public string ExtractedRoot { get; set; }
```

OutputPreview

```
public string OutputPreview { get; set; }
```

SolutionPath

```
public string SolutionPath { get; set; }
```

Status

```
public string Status { get; set; }
```

Class EngineeringBenchmarkLaneResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EngineeringBenchmarkLaneResult

```
public sealed class EngineeringBenchmarkLaneResult
```

🌟 Constructors 1

EngineeringBenchmarkLaneResult()

```
public EngineeringBenchmarkLaneResult()
```

🐾 Properties 17

Artifacts

```
public List<CouncilArtifact> Artifacts { get; set; }
```

BuildChecks

```
public List<EngineeringBenchmarkBuildCheck> BuildChecks { get; set; }
```

BuildabilityScore

```
public int BuildabilityScore { get; set; }
```

DownloadableArtifactScore

```
public int DownloadableArtifactScore { get; set; }
```

Duration

```
public TimeSpan? Duration { get; set; }
```

Evidence

```
public List<string> Evidence { get; set; }
```

Lane

```
public string Lane { get; set; }
```

MissingFiles

```
public List<string> MissingFiles { get; set; }
```

MissingFilesScore

```
public int MissingFilesScore { get; set; }
```

Notes

```
public string Notes { get; set; }
```

RepairPromptCount

```
public int RepairPromptCount { get; set; }
```

RepairPromptsScore

```
public int RepairPromptsScore { get; set; }
```

Status

```
public string Status { get; set; }
```

TimeToUsableOutputScore

```
public int TimeToUsableOutputScore { get; set; }
```

TotalScore

```
public int TotalScore { get; set; }
```

ValidArchitectureScore

```
public int ValidArchitectureScore { get; set; }
```

WrongPackagesTemplatesScore

```
public int WrongPackagesTemplatesScore { get; set; }
```

api/LocalGPT.BusinessObjects.EngineeringBenchmarkRequest.html

Class EngineeringBenchmarkRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EngineeringBenchmarkRequest

```
public sealed class EngineeringBenchmarkRequest
```

🌟 Constructors 1

EngineeringBenchmarkRequest()

```
public EngineeringBenchmarkRequest()
```

🐾 Properties 8

ImportLearnBaseFirst

```
public bool ImportLearnBaseFirst { get; set; }
```

LearnBaseRootPath

```
public string LearnBaseRootPath { get; set; }
```

MaxBuildArtifacts

```
public int MaxBuildArtifacts { get; set; }
```

RunLocalGptArtifacts

```
public bool RunLocalGptArtifacts { get; set; }
```

SaveToKnowledge

```
public bool SaveToKnowledge { get; set; }
```

TaskSet

```
public string TaskSet { get; set; }
```

UserConfirmedArtifactActions

```
public bool UserConfirmedArtifactActions { get; set; }
```

ValidateBuildableArtifacts

```
public bool ValidateBuildableArtifacts { get; set; }
```


Class EngineeringBenchmarkResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object EngineeringBenchmarkResult

```
public sealed class EngineeringBenchmarkResult
```

🌟 Constructors 1

EngineeringBenchmarkResult()

```
public EngineeringBenchmarkResult()
```

🐾 Properties 8

CompletedAtUtc

```
public DateTime CompletedAtUtc { get; set; }
```

KnowledgeEntryId

```
public Guid? KnowledgeEntryId { get; set; }
```

LearnBaseImport

```
public LearnBaseImportResult? LearnBaseImport { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

TaskSet

```
public string TaskSet { get; set; }
```

Tasks

```
public List<EngineeringBenchmarkTaskResult> Tasks { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class EngineeringBenchmarkTaskResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object EngineeringBenchmarkTaskResult

```
public sealed class EngineeringBenchmarkTaskResult
```

🌟 Constructors 1

EngineeringBenchmarkTaskResult()

```
public EngineeringBenchmarkTaskResult()
```

🐾 Properties 4

Lanes

```
public List<EngineeringBenchmarkLaneResult> Lanes { get; set; }
```

Name

```
public string Name { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

TaskId

```
public string TaskId { get; set; }
```

Enum CoreLogLevel

Namespace LocalGPT . BusinessObjects . Enums Assembly LocalGPT.dll

```
public enum CoreLogLevel
```

🎯 Fields 1

Namespace LocalGPT.BusinessObjects.Enums

Enums

Class ExecuteCodeGenerationReviewRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ExecuteCodeGenerationReviewRequest

```
public sealed class ExecuteCodeGenerationReviewRequest
```

🌟 Constructors 1

ExecuteCodeGenerationReviewRequest()

```
public ExecuteCodeGenerationReviewRequest()
```

🐾 Properties 5

BuildAfterGeneration

```
public bool BuildAfterGeneration { get; set; }
```

DecisionNote

```
public string DecisionNote { get; set; }
```

ExpectedReviewHash

```
public string ExpectedReviewHash { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

UserConfirmedBuild

```
public bool UserConfirmedBuild { get; set; }
```

api/LocalGPT.BusinessObjects.FileLoggerCoreOptions.html

Class FileLoggerCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object FileLoggerCoreOptions

```
public class FileLoggerCoreOptions
```

 Constructors 1

FileLoggerCoreOptions()

```
public FileLoggerCoreOptions()
```

 Fields 1

FileLoggerCore

```
public const string FileLoggerCore = "FileLoggerCore"
```

 Properties 2

CoreLogLevel

```
[JsonInclude] public CoreLogLevel CoreLogLevel { get; set; }
```

FilePath

```
[JsonInclude] public string? FilePath { get; set; }
```

 Methods 1

CloneOptions(FileLoggerCoreOptions)

```
public FileLoggerCoreOptions CloneOptions(FileLoggerCoreOptions options)
```

Class FirstRunOnboardingStatus

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Represents the bounded first-run setup state shown by LocalGPT before the user starts normal work.

Inheritance object FirstRunOnboardingStatus

```
[DocumentationUpdated("2.1.20")] public sealed class FirstRunOnboardingStatus
```

🌟 Constructors 1

FirstRunOnboardingStatus()

```
public FirstRunOnboardingStatus()
```

🐾 Properties 13

ChatRoute

Gets the LocalGPT Chat route.

```
public string ChatRoute { get; }
```

CouncilTeamKeys

Gets or sets the currently available seeded or user-owned council team keys.

```
public List<string> CouncilTeamKeys { get; set; }
```

CouncilTeamsRoute

Gets the LocalGPT council-team editor route.

```
public string CouncilTeamsRoute { get; }
```

DocumentationRoute

Gets the LocalGPT generated-documentation route.

```
public string DocumentationRoute { get; }
```

InstalledModels

Gets or sets the distinct locally discovered model names.

```
public List<string> InstalledModels { get; set; }
```

InstallerProfiles

Gets or sets installer profiles that remain user-triggered and reviewable.

```
public List<OnboardingInstallerProfile> InstallerProfiles { get; set; }
```

InstallerRoute

Gets the LocalGPT installer route.

```
public string InstallerRoute { get; }
```

IsCompleted

Gets or sets whether the user has dismissed the first-run guide.

```
public bool IsCompleted { get; set; }
```

LocalAiReachable

Gets or sets whether at least one supported local AI endpoint answered the bounded discovery probe.

```
public bool LocalAiReachable { get; set; }
```

ModelPresetNames

Gets or sets the currently available model-preset names.

```
public List<string> ModelPresetNames { get; set; }
```

QuickStarts

Gets or sets direct Chat quick starts for common council workloads.

```
public List<CouncilQuickStart> QuickStarts { get; set; }
```

Version

Gets or sets the LocalGPT version that produced the status.

```
public string Version { get; set; }
```

Warnings

Gets or sets warnings collected while optional connectivity discovery ran.

```
public List<string> Warnings { get; set; }
```

api/LocalGPT.BusinessObjects.GeneratedArchetypePage.html

Class GeneratedArchetypePage

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object GeneratedArchetypePage

Implements IEquatable < GeneratedArchetypePage >

```
public sealed record GeneratedArchetypePage : IEquatable<GeneratedArchetypePage>
```

🌟 Constructors 1

GeneratedArchetypePage(string, string)

```
public GeneratedArchetypePage(string FileName, string Source)
```

🐾 Properties 2

FileName

```
public string FileName { get; init; }
```

Source

```
public string Source { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string)

```
public void Deconstruct(out string FileName, out string Source)
```

Equals(GeneratedArchetypePage?)

```
public bool Equals(GeneratedArchetypePage? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(GeneratedArchetypePage?, GeneratedArchetypePage?)

```
public static bool operator ==(GeneratedArchetypePage? left, GeneratedArchetypePage? right)
```

operator !=(GeneratedArchetypePage?, GeneratedArchetypePage?)

```
public static bool operator !=(GeneratedArchetypePage? left, GeneratedArchetypePage? right)
```

Class GeneratedPromiseModule

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object GeneratedPromiseModule

Implements IEquatable < GeneratedPromiseModule >

```
public sealed record GeneratedPromiseModule : IEquatable<GeneratedPromiseModule>
```

🌟 Constructors 1

GeneratedPromiseModule(string, string, string, string, IReadOnlyList<string>)

```
public GeneratedPromiseModule(string FileName, string Route, string Title, string Summary, IReadOnlyList<string> Areas)
```

🐾 Properties 5

Areas

```
public IReadOnlyList<string> Areas { get; init; }
```

FileName

```
public string FileName { get; init; }
```

Route

```
public string Route { get; init; }
```

Summary

```
public string Summary { get; init; }
```

Title

```
public string Title { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out IReadOnlyList<string>)

```
public void Deconstruct(out string FileName, out string Route, out string Title, out string Summary, out IReadOnlyList<string> Areas)
```

Equals(GeneratedPromiseModule?)

```
public bool Equals(GeneratedPromiseModule? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(GeneratedPromiseModule?, GeneratedPromiseModule?)

```
public static bool operator ==(GeneratedPromiseModule? left, GeneratedPromiseModule? right)
```

operator !=(GeneratedPromiseModule?, GeneratedPromiseModule?)

```
public static bool operator !=(GeneratedPromiseModule? left, GeneratedPromiseModule? right)
```

Enum GeneratedSolutionArchetype

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum GeneratedSolutionArchetype
```

Fields 1

Class GroundedProcessReviewRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object GroundedProcessReviewRequest

```
public sealed class GroundedProcessReviewRequest
```

Constructors 1

GroundedProcessReviewRequest()

```
public GroundedProcessReviewRequest()
```

Properties 3

Facts

```
public List<string> Facts { get; set; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; set; }
```

Question

```
public string? Question { get; set; }
```

Namespace LocalGPT.BusinessObjects

Namespaces

Classes

Enums

Identifies an assistant message that can receive user feedback in Chat.

Describes one factory-created actor instance and its Council assignment slot.

Provides the immutable input used by the authoritative GameDirector for one proposed action.

Records the GameDirector decision that authorizes or rejects one state transition.

Persistent envelope for an authoritative GameDirector runtime session.

Internal authoritative state for one in-chat Council game session. It is deliberately data-only so the session service owns orchestration, rendering and synchronization policy.

Represents one bounded prediction from a creature or reactive-object subdirector.

Immutable execution limits selected for one model on one CPU/GPU road.

Readiness facts for one council member and its selected hardware road.

Database, function, skill, project and hardware readiness report created before every council run.

Persistent configuration for one visible chat prompt that can start an AI Council run.

Describes a direct route into a seeded LocalGPT team and model-preset combination.

Represents the persisted SQLite row for one Council team configuration.

Defines one ordered Council round and its execution, loop, function and ASCII-frame policies.

Describes one approval-gated compiler and runtime discovery request.

Persistent evidence for one documentation build or fallback generation.

Marks a documented type with the LocalGPT version in which its maintained XML documentation was last reviewed.

Database-backed, user-editable policy and discovery record for a DX function or public application service method. Descriptor metadata is refreshed from the running application while user policy fields are preserved.

Persistent envelope for an embedded firmware plan and its generated artifacts.

Represents the bounded first-run setup state shown by LocalGPT before the user starts normal work.

Mutable draft state for one human-collaboration response editor. Kept in the business-object domain so Razor components contain behavior and rendering only.

Immutable runtime settings for the local SQLite store.

Represents one compiler-generated XML documentation member after localization adaptation and version enrichment.

Describes the generated LocalGPT documentation artifacts available to the running application.

Describes a built-in or user-supplied LocalGPT localization catalog.

Reports the durable result of importing a localization catalog.

Persistent registration for a built-in or user-imported localization JSON catalog.

Reports the result of validating a user-provided localization JSON catalog.

Describes one installer profile that can prepare models or repository knowledge for a LocalGPT workstation.

Local runtime state for a protocol work item. Transfer contracts live in LocalGPT.WireProtocolVersion.

Offline, source-controlled description of an organic add-on. The manifest makes an add-on's controller surface discoverable while its process is offline; invocation still requires a live, trusted 1-Wire peer and the existing user-controlled catalog policy.

Defines one role and its AI, human, language, runtime-class and pairing policies.

Defines one editable LocalGPT Council team, its roles, workflow and architecture contracts.

Stores project and revision metadata used to route organic Council capabilities.

Describes one reusable Chat prompt and its optional Council-team ownership.

Provider-qualified model identity. No credential is stored in this object; credentials are resolved from the matching configured provider at execution time.

Current dependency-injected function and organic-skill directory persisted for AI context.

Carries a reviewed Council team change and its persistence flags.

Approval-gated request for creating or updating one persistent feature record.

Extends project organic context with the confirmation required for persistence.

Mutable aggregate for one service-operation diagnostics batch. The object is data only; batching and logging behavior remain owned by the diagnostics proxy.

One successful selection in the order-sensitive Theme Fusion route. The route is intentionally preserved because repeated theme swaps can create a visual result that is not described by the final Base Theme and Style Layer alone.

Identifies the wire/text convention emitted by a model. Each non-auto protocol has its own DI profile so control tokens from one model family are never applied to another family's response stream.

Identifies the runtime actor that proposed an action.

Chooses how a game action is reviewed before the authoritative session state changes.

Defines how LocalGPT assigns AI participants to a Council role.

Defines how strictly a Council role must remain inside its assigned responsibility.

Defines the language policy applied to a Council role.

Defines whether a role behaves as a task specialist or an improvisation player.

Class HumanApprovalGateResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanApprovalGateResult

Implements IEquatable < HumanApprovalGateResult >

```
public sealed record HumanApprovalGateResult : IEquatable<HumanApprovalGateResult>
```

🌟 Constructors 1

HumanApprovalGateResult(bool, bool, Guid?, string, string, string, string, string)

```
public HumanApprovalGateResult(bool IsAuthorized, bool IsDeclined, Guid? RequestId, string Status, string Message, string DecisionReason = "", string CorrelationId = "", string UserResponse = "")
```

🐾 Properties 8

CorrelationId

```
public string CorrelationId { get; init; }
```

DecisionReason

```
public string DecisionReason { get; init; }
```

IsAuthorized

```
public bool IsAuthorized { get; init; }
```

IsDeclined

```
public bool IsDeclined { get; init; }
```

Message

```
public string Message { get; init; }
```

RequestId

```
public Guid? RequestId { get; init; }
```

Status

```
public string Status { get; init; }
```

UserResponse

```
public string UserResponse { get; init; }
```

⚙️ Methods 5

Deconstruct(out bool, out bool, out Guid?, out string, out string, out string, out string, out string)

```
public void Deconstruct(out bool IsAuthorized, out bool IsDeclined, out Guid? RequestId, out string Status, out string Message, out string DecisionReason, out string CorrelationId, out string UserResponse)
```

Equals(HumanApprovalGateResult?)

```
public bool Equals(HumanApprovalGateResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(HumanApprovalGateResult?, HumanApprovalGateResult?)

```
public static bool operator ==(HumanApprovalGateResult? left, HumanApprovalGateResult? right)
```

operator !=(HumanApprovalGateResult?, HumanApprovalGateResult?)

```
public static bool operator !=(HumanApprovalGateResult? left, HumanApprovalGateResult? right)
```

Class HumanApprovalRequestSpec

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanApprovalRequestSpec

Implements IEquatable < HumanApprovalRequestSpec >

```
public sealed record HumanApprovalRequestSpec : IEquatable<HumanApprovalRequestSpec>
```

🌟 Constructors 1

HumanApprovalRequestSpec(string, string, string, string, string, string, string, string, Guid?, int, bool, bool, string, string, string, string, bool, string, string, string, string, int, string)

```
public HumanApprovalRequestSpec(string CorrelationId, string OperationKey, string Title, string Description, string RiskLevel, string Source, string RequestedBy, string RequestedRole, Guid? CouncilRunId = null, int EarliestCouncilRound = 0, bool RequiredBeforeCompletion = false, bool IsSensitive = true, string RequestKind = "", string SuggestedResponsesText = "", string ResponsePrompt = "", string PrefillText = "", bool AllowFreeText = true, string ParameterFingerprint = "", string QuestionScope = "Member", string GateMode = "None", string TargetMembersText = "", int RequestedCouncilRound = 0, string RequestedCouncilPhase = "")
```

🐾 Properties 23

AllowFreeText

```
public bool AllowFreeText { get; init; }
```

CorrelationId

```
public string CorrelationId { get; init; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; init; }
```

Description

```
public string Description { get; init; }
```

EarliestCouncilRound

```
public int EarliestCouncilRound { get; init; }
```

GateMode

```
public string GateMode { get; init; }
```

IsSensitive

```
public bool IsSensitive { get; init; }
```

OperationKey

```
public string OperationKey { get; init; }
```

ParameterFingerprint

```
public string ParameterFingerprint { get; init; }
```

PrefillText

```
public string PrefillText { get; init; }
```

QuestionScope

```
public string QuestionScope { get; init; }
```

RequestKind

```
public string RequestKind { get; init; }
```

RequestedBy

```
public string RequestedBy { get; init; }
```

RequestedCouncilPhase

```
public string RequestedCouncilPhase { get; init; }
```

RequestedCouncilRound

```
public int RequestedCouncilRound { get; init; }
```

RequestedRole

```
public string RequestedRole { get; init; }
```

RequiredBeforeCompletion

```
public bool RequiredBeforeCompletion { get; init; }
```

ResponsePrompt

```
public string ResponsePrompt { get; init; }
```

RiskLevel

```
public string RiskLevel { get; init; }
```

Source

```
public string Source { get; init; }
```

SuggestedResponsesText

```
public string SuggestedResponsesText { get; init; }
```

TargetMembersText

```
public string TargetMembersText { get; init; }
```

Title

```
public string Title { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out string, out string, out string, out Guid?, out int, out bool, out bool, out string, out string, out string, out string, out bool, out string, out string, out string, out string, out int, out string)

```
public void Deconstruct(out string CorrelationId, out string OperationKey, out string Title, out string Description, out string RiskLevel, out string Source, out string RequestedBy, out string RequestedRole, out Guid? CouncilRunId, out int EarliestCouncilRound, out bool RequiredBeforeCompletion, out bool IsSensitive, out string RequestKind, out string SuggestedResponsesText, out string ResponsePrompt, out string PrefillText, out bool AllowFreeText, out string ParameterFingerprint, out string QuestionScope, out string GateMode, out string TargetMembersText, out int RequestedCouncilRound, out string RequestedCouncilPhase)
```

Equals(HumanApprovalRequestSpec?)

```
public bool Equals(HumanApprovalRequestSpec? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(HumanApprovalRequestSpec?, HumanApprovalRequestSpec?)

```
public static bool operator ==(HumanApprovalRequestSpec? left, HumanApprovalRequestSpec? right)
```

operator !=(HumanApprovalRequestSpec?, HumanApprovalRequestSpec?)

```
public static bool operator !=(HumanApprovalRequestSpec? left, HumanApprovalRequestSpec? right)
```

Enum HumanApprovalReuseScope

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum HumanApprovalReuseScope
```

Fields 1

Enum HumanCollaborationBoundary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum HumanCollaborationBoundary
```

Fields 1

Class HumanCollaborationGateStatus

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCollaborationGateStatus

Implements IEquatable < HumanCollaborationGateStatus >

```
public sealed record HumanCollaborationGateStatus : IEquatable<HumanCollaborationGateStatus>
```

Constructors 1

HumanCollaborationGateStatus(bool, HumanCollaborationBoundary, int, string, IReadOnlyList<HumanCollaborationRequest>)

```
public HumanCollaborationGateStatus(bool IsBlocked, HumanCollaborationBoundary Boundary, int UpcomingRound, string UpcomingPhase,
IReadOnlyList<HumanCollaborationRequest> BlockingRequests)
```

Properties 5

BlockingRequests

```
public IReadOnlyList<HumanCollaborationRequest> BlockingRequests { get; init; }
```

Boundary

```
public HumanCollaborationBoundary Boundary { get; init; }
```

IsBlocked

```
public bool IsBlocked { get; init; }
```

UpcomingPhase

```
public string UpcomingPhase { get; init; }
```

UpcomingRound

```
public int UpcomingRound { get; init; }
```

Methods 5

Deconstruct(out bool, out HumanCollaborationBoundary, out int, out string, out IReadOnlyList<HumanCollaborationRequest>)

```
public void Deconstruct(out bool IsBlocked, out HumanCollaborationBoundary Boundary, out int UpcomingRound, out string UpcomingPhase, out
IReadOnlyList<HumanCollaborationRequest> BlockingRequests)
```

Equals(HumanCollaborationGateStatus?)

```
public bool Equals(HumanCollaborationGateStatus? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(HumanCollaborationGateStatus?, HumanCollaborationGateStatus?)

```
public static bool operator ==(HumanCollaborationGateStatus? left, HumanCollaborationGateStatus? right)
```

operator !=(HumanCollaborationGateStatus?, HumanCollaborationGateStatus?)

```
public static bool operator !=(HumanCollaborationGateStatus? left, HumanCollaborationGateStatus? right)
```

Class HumanCollaborationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCollaborationRequest

```
public sealed class HumanCollaborationRequest
```

🌟 Constructors 1

HumanCollaborationRequest()

```
public HumanCollaborationRequest()
```

🐾 Properties 39

AllowFreeText

```
public bool AllowFreeText { get; set; }
```

ApprovalReuseScope

```
public HumanApprovalReuseScope ApprovalReuseScope { get; set; }
```

ApprovalSessionId

```
public Guid? ApprovalSessionId { get; set; }
```

ConsumeApproval

```
public bool ConsumeApproval { get; set; }
```

ConsumedAtUtc

```
public DateTime? ConsumedAtUtc { get; set; }
```

CorrelationId

```
public string CorrelationId { get; set; }
```

CouncilRunId

```
public Guid? CouncilRunId { get; set; }
```

DecidedAtUtc

```
public DateTime? DecidedAtUtc { get; set; }
```

DecisionBy

```
public string DecisionBy { get; set; }
```

DecisionByProfileId

```
public Guid? DecisionByProfileId { get; set; }
```

DecisionReason

```
public string DecisionReason { get; set; }
```

DecisionVersion

```
public int DecisionVersion { get; set; }
```

Description

```
public string Description { get; set; }
```

EarliestCouncilRound

```
public int EarliestCouncilRound { get; set; }
```

GateMode

```
public string GateMode { get; set; }
```

Id

```
public Guid Id { get; set; }
```


IsSensitive

```
public bool IsSensitive { get; set; }
```

OperationKey

```
public string OperationKey { get; set; }
```

ParameterFingerprint

```
public string ParameterFingerprint { get; set; }
```

PrefillText

```
public string PrefillText { get; set; }
```

QuestionScope

```
public string QuestionScope { get; set; }
```

RequestKind

```
public string RequestKind { get; set; }
```

RequestedAtUtc

```
public DateTime RequestedAtUtc { get; set; }
```

RequestedBy

```
public string RequestedBy { get; set; }
```

RequestedCouncilPhase

```
public string RequestedCouncilPhase { get; set; }
```

RequestedCouncilRound

```
public int RequestedCouncilRound { get; set; }
```

RequestedRole

```
public string RequestedRole { get; set; }
```

RequiredBeforeCompletion

```
public bool RequiredBeforeCompletion { get; set; }
```

ResponsePrompt

```
public string ResponsePrompt { get; set; }
```

RiskLevel

```
public string RiskLevel { get; set; }
```

Source

```
public string Source { get; set; }
```

Status

```
public string Status { get; set; }
```

SuggestedResponses

```
[NotMapped] public IReadOnlyList<string> SuggestedResponses { get; }
```

SuggestedResponsesText

```
public string SuggestedResponsesText { get; set; }
```

TargetMembersDisplay

```
[NotMapped] public string TargetMembersDisplay { get; }
```

TargetMembersText

```
public string TargetMembersText { get; set; }
```

Title

```
public string Title { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

UserResponse

```
public string UserResponse { get; set; }
```

api/LocalGPT.BusinessObjects.HumanCollaborationRequestEditor.html

Class HumanCollaborationRequestEditor

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Mutable draft state for one human-collaboration response editor. Kept in the business-object domain so Razor components contain behavior and rendering only.
Inheritance object HumanCollaborationRequestEditor

```
public sealed class HumanCollaborationRequestEditor
```

🌟 Constructors 1

HumanCollaborationRequestEditor(string, string, HumanApprovalReuseScope, bool)
Mutable draft state for one human-collaboration response editor. Kept in the business-object domain so Razor components contain behavior and rendering only.

```
public HumanCollaborationRequestEditor(string response, string reason, HumanApprovalReuseScope reuseScope = HumanApprovalReuseScope.ExactRequestOnce, bool consumeApproval = true)
```

🐾 Properties 4

ConsumeApproval

```
public bool ConsumeApproval { get; set; }
```

Reason

```
public string Reason { get; set; }
```

Response

```
public string Response { get; set; }
```

ReuseScope

```
public HumanApprovalReuseScope ReuseScope { get; set; }
```

Class HumanCollaborationRequestParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCollaborationRequestParameters

```
public sealed class HumanCollaborationRequestParameters
```

🌟 Constructors 1

HumanCollaborationRequestParameters()

```
public HumanCollaborationRequestParameters()
```

🐾 Properties 12

AllowFreeText

```
public bool AllowFreeText { get; set; }
```

Description

```
public string Description { get; set; }
```

Gate

```
public string Gate { get; set; }
```

Kind

```
public string Kind { get; set; }
```

PrefillText

```
public string PrefillText { get; set; }
```

QuestionScope

```
public string QuestionScope { get; set; }
```

RequestedRole

```
public string RequestedRole { get; set; }
```

RequiredBeforeCompletion

```
public bool RequiredBeforeCompletion { get; set; }
```

ResponsePrompt

```
public string ResponsePrompt { get; set; }
```

SuggestedResponses

```
public string[]? SuggestedResponses { get; set; }
```

TargetMembers

```
public string[]? TargetMembers { get; set; }
```

Title

```
public string Title { get; set; }
```

Class HumanCollaborationSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCollaborationSnapshot

Implements IEquatable < HumanCollaborationSnapshot >

```
public sealed record HumanCollaborationSnapshot : IEquatable<HumanCollaborationSnapshot>
```

🌟 Constructors 1

HumanCollaborationSnapshot(HumanCouncilParticipantProfile, IReadOnlyList<HumanCollaborationRequest>, IReadOnlyList<HumanCouncilRunSnapshot>, IReadOnlyList<HumanCouncilContribution>)

```
public HumanCollaborationSnapshot(HumanCouncilParticipantProfile Profile, IReadOnlyList<HumanCollaborationRequest> Requests,
IReadOnlyList<HumanCouncilRunSnapshot> ActiveRuns, IReadOnlyList<HumanCouncilContribution> Contributions)
```

🐾 Properties 4

ActiveRuns

```
public IReadOnlyList<HumanCouncilRunSnapshot> ActiveRuns { get; init; }
```

Contributions

```
public IReadOnlyList<HumanCouncilContribution> Contributions { get; init; }
```

Profile

```
public HumanCouncilParticipantProfile Profile { get; init; }
```

Requests

```
public IReadOnlyList<HumanCollaborationRequest> Requests { get; init; }
```

⚙️ Methods 5

Deconstruct(out HumanCouncilParticipantProfile, out IReadOnlyList<HumanCollaborationRequest>, out IReadOnlyList<HumanCouncilRunSnapshot>, out IReadOnlyList<HumanCouncilContribution>)

```
public void Deconstruct(out HumanCouncilParticipantProfile Profile, out IReadOnlyList<HumanCollaborationRequest> Requests, out
IReadOnlyList<HumanCouncilRunSnapshot> ActiveRuns, out IReadOnlyList<HumanCouncilContribution> Contributions)
```

Equals(HumanCollaborationSnapshot?)

```
public bool Equals(HumanCollaborationSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(HumanCollaborationSnapshot?, HumanCollaborationSnapshot?)

```
public static bool operator ==(HumanCollaborationSnapshot? left, HumanCollaborationSnapshot? right)
```

operator !=(HumanCollaborationSnapshot?, HumanCollaborationSnapshot?)

```
public static bool operator !=(HumanCollaborationSnapshot? left, HumanCollaborationSnapshot? right)
```

Class HumanCouncilContribution

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCouncilContribution

```
public sealed class HumanCouncilContribution
```

✨ Constructors 1

HumanCouncilContribution()

```
public HumanCouncilContribution()
```

🐾 Properties 13

Content

```
public string Content { get; set; }
```

CouncilRunId

```
public Guid CouncilRunId { get; set; }
```

EarliestCouncilRound

```
public int EarliestCouncilRound { get; set; }
```

EvaluatedAfterRound

```
public int EvaluatedAfterRound { get; set; }
```

EvaluatedAtUtc

```
public DateTime? EvaluatedAtUtc { get; set; }
```

Evaluation

```
public string Evaluation { get; set; }
```

EvaluationVerdict

```
public string EvaluationVerdict { get; set; }
```

HumanDisplayName

```
public string HumanDisplayName { get; set; }
```

HumanRole

```
public string HumanRole { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InjectedAtUtc

```
public DateTime? InjectedAtUtc { get; set; }
```

Status

```
public string Status { get; set; }
```

SubmittedAtUtc

```
public DateTime SubmittedAtUtc { get; set; }
```

Class HumanCouncilParticipantProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCouncilParticipantProfile

```
public sealed class HumanCouncilParticipantProfile
```

🌟 Constructors 1

HumanCouncilParticipantProfile()

```
public HumanCouncilParticipantProfile()
```

🐾 Properties 9

DisplayName

```
public string DisplayName { get; set; }
```

Expertise

```
public string Expertise { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

ProfileVersion

```
public int ProfileVersion { get; set; }
```

RoleName

```
public string RoleName { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

UpdatedBy

```
public string UpdatedBy { get; set; }
```

WorkingStyle

```
public string WorkingStyle { get; set; }
```

Class HumanCouncilRunSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanCouncilRunSnapshot

Implements IEquatable < HumanCouncilRunSnapshot >

```
public sealed record HumanCouncilRunSnapshot : IEquatable<HumanCouncilRunSnapshot>
```

🌟 Constructors 1

HumanCouncilRunSnapshot(Guid, DateTime, int, string, IReadOnlyList<string>, bool)

```
public HumanCouncilRunSnapshot(Guid RunId, DateTime StartedAtUtc, int CurrentRound, string Phase, IReadOnlyList<string> CouncilMembers, bool IsWaitingForFinalHumanInput)
```

🐾 Properties 6

CouncilMembers

```
public IReadOnlyList<string> CouncilMembers { get; init; }
```

CurrentRound

```
public int CurrentRound { get; init; }
```

IsWaitingForFinalHumanInput

```
public bool IsWaitingForFinalHumanInput { get; init; }
```

Phase

```
public string Phase { get; init; }
```

RunId

```
public Guid RunId { get; init; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out DateTime, out int, out string, out IReadOnlyList<string>, out bool)

```
public void Deconstruct(out Guid RunId, out DateTime StartedAtUtc, out int CurrentRound, out string Phase, out IReadOnlyList<string> CouncilMembers, out bool IsWaitingForFinalHumanInput)
```

Equals(HumanCouncilRunSnapshot?)

```
public bool Equals(HumanCouncilRunSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(HumanCouncilRunSnapshot?, HumanCouncilRunSnapshot?)

```
public static bool operator ==(HumanCouncilRunSnapshot? left, HumanCouncilRunSnapshot? right)
```

operator !=(HumanCouncilRunSnapshot?, HumanCouncilRunSnapshot?)

```
public static bool operator !=(HumanCouncilRunSnapshot? left, HumanCouncilRunSnapshot? right)
```

Class HumanDecisionSubmission

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object HumanDecisionSubmission

Implements IEquatable < HumanDecisionSubmission >

```
public sealed record HumanDecisionSubmission : IEquatable<HumanDecisionSubmission>
```

🌟 Constructors 1

HumanDecisionSubmission(bool?, string, string, HumanApprovalReuseScope, bool)

```
public HumanDecisionSubmission(bool? Approved, string Response, string Reason, HumanApprovalReuseScope ReuseScope = HumanApprovalReuseScope.ExactRequestOnce, bool ConsumeApproval = true)
```

🐾 Properties 5

Approved

```
public bool? Approved { get; init; }
```

ConsumeApproval

```
public bool ConsumeApproval { get; init; }
```

Reason

```
public string Reason { get; init; }
```

Response

```
public string Response { get; init; }
```

ReuseScope

```
public HumanApprovalReuseScope ReuseScope { get; init; }
```

⚙️ Methods 5

Deconstruct(out bool?, out string, out string, out HumanApprovalReuseScope, out bool)

```
public void Deconstruct(out bool? Approved, out string Response, out string Reason, out HumanApprovalReuseScope ReuseScope, out bool ConsumeApproval)
```

Equals(HumanDecisionSubmission?)

```
public bool Equals(HumanDecisionSubmission? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(HumanDecisionSubmission?, HumanDecisionSubmission?)

```
public static bool operator ==(HumanDecisionSubmission? left, HumanDecisionSubmission? right)
```

operator !=(HumanDecisionSubmission?, HumanDecisionSubmission?)

```
public static bool operator !=(HumanDecisionSubmission? left, HumanDecisionSubmission? right)
```


Enum HumanParticipationMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines how a human participant may join a Council role.

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum HumanParticipationMode
```

🔗 Fields 1

Class InspectDebugArtifactParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object InspectDebugArtifactParameters

```
public sealed class InspectDebugArtifactParameters
```

🌟 Constructors 1

InspectDebugArtifactParameters()

```
public InspectDebugArtifactParameters()
```

🐾 Properties 1

FilePath

```
public string FilePath { get; set; }
```

Class LearnBaseImportRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearnBaseImportRequest

```
public sealed class LearnBaseImportRequest
```

🌟 Constructors 1

LearnBaseImportRequest()

```
public LearnBaseImportRequest()
```

🐾 Properties 11

AdditionalFileExtensions

```
public string AdditionalFileExtensions { get; set; }
```

FileExcludeRegex

```
public string FileExcludeRegex { get; set; }
```

FileExtensions

```
public List<string> FileExtensions { get; set; }
```

FileIncludeRegex

```
public string FileIncludeRegex { get; set; }
```

ImportKnownDocumentationCorpora

```
public bool ImportKnownDocumentationCorpora { get; set; }
```

ImportLearningSourceManifests

```
public bool ImportLearningSourceManifests { get; set; }
```

ImportProjectArchitecture

```
public bool ImportProjectArchitecture { get; set; }
```

MaxProjects

```
public int MaxProjects { get; set; }
```

MaximumFileBytes

```
public int MaximumFileBytes { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

SaveToKnowledge

```
public bool SaveToKnowledge { get; set; }
```

Class LearnBaseImportResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object LearnBaseImportResult

```
public sealed class LearnBaseImportResult
```

🌟 Constructors 1

LearnBaseImportResult()

```
public LearnBaseImportResult()
```

🐾 Properties 8

DuplicatePolicy

```
public string DuplicatePolicy { get; set; }
```

FilePolicy

```
public string FilePolicy { get; set; }
```

ImportMode

```
public string ImportMode { get; set; }
```

ProjectCount

```
public int ProjectCount { get; set; }
```

Projects

```
public List<LearnBaseProjectSummary> Projects { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

SavedKnowledgeCount

```
public int SavedKnowledgeCount { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class LearnBasePreset

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearnBasePreset

Implements IEquatable < LearnBasePreset >

```
public sealed record LearnBasePreset : IEquatable<LearnBasePreset>
```

🌟 Constructors 1

LearnBasePreset(string, string, string, int)

```
public LearnBasePreset(string Label, string RootPath, string Description, int RecommendedMaxProjects)
```

🐾 Properties 4

Description

```
public string Description { get; init; }
```

Label

```
public string Label { get; init; }
```

RecommendedMaxProjects

```
public int RecommendedMaxProjects { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out int)

```
public void Deconstruct(out string Label, out string RootPath, out string Description, out int RecommendedMaxProjects)
```

Equals(LearnBasePreset?)

```
public bool Equals(LearnBasePreset? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LearnBasePreset?, LearnBasePreset?)

```
public static bool operator ==(LearnBasePreset? left, LearnBasePreset? right)
```

operator !=(LearnBasePreset?, LearnBasePreset?)

```
public static bool operator !=(LearnBasePreset? left, LearnBasePreset? right)
```

Class LearnBaseProjectSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearnBaseProjectSummary

```
public sealed class LearnBaseProjectSummary
```

🌟 Constructors 1

LearnBaseProjectSummary()

```
public LearnBaseProjectSummary()
```

🐾 Properties 10

Architecture

```
public string Architecture { get; set; }
```

BinaryFileCount

```
public int BinaryFileCount { get; set; }
```

ImportantFiles

```
public string ImportantFiles { get; set; }
```

KnowledgeEntryId

```
public Guid? KnowledgeEntryId { get; set; }
```

Name

```
public string Name { get; set; }
```

PackageReferences

```
public string PackageReferences { get; set; }
```

ProtocolsAndComponents

```
public string ProtocolsAndComponents { get; set; }
```

SourceFileCount

```
public int SourceFileCount { get; set; }
```

SourcePath

```
public string SourcePath { get; set; }
```

TargetFrameworks

```
public string TargetFrameworks { get; set; }
```

Class LearnBaseScanProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearnBaseScanProfile

Implements IEquatable < LearnBaseScanProfile >

```
public sealed record LearnBaseScanProfile : IEquatable<LearnBaseScanProfile>
```

🌟 Constructors 1

LearnBaseScanProfile(string, int, string)

```
public LearnBaseScanProfile(string Label, int MaxProjects, string Description)
```

🐾 Properties 3

Description

```
public string Description { get; init; }
```

Label

```
public string Label { get; init; }
```

MaxProjects

```
public int MaxProjects { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out int, out string)

```
public void Deconstruct(out string Label, out int MaxProjects, out string Description)
```

Equals(LearnBaseScanProfile?)

```
public bool Equals(LearnBaseScanProfile? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LearnBaseScanProfile?, LearnBaseScanProfile?)

```
public static bool operator ==(LearnBaseScanProfile? left, LearnBaseScanProfile? right)
```

operator !=(LearnBaseScanProfile?, LearnBaseScanProfile?)

```
public static bool operator !=(LearnBaseScanProfile? left, LearnBaseScanProfile? right)
```

Class LearningFactInput

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearningFactInput

```
public sealed class LearningFactInput
```

🌟 Constructors 1

LearningFactInput()

```
public LearningFactInput()
```

🐾 Properties 6

Confidence

```
public int Confidence { get; set; }
```

Content

```
public string Content { get; set; }
```

HelpfulSources

```
public string HelpfulSources { get; set; }
```

Scope

```
public string Scope { get; set; }
```

Tags

```
public string Tags { get; set; }
```

Topic

```
public string Topic { get; set; }
```

Class LearningMaintenanceRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearningMaintenanceRequest

```
public sealed class LearningMaintenanceRequest
```

🌟 Constructors 1

LearningMaintenanceRequest()

```
public LearningMaintenanceRequest()
```

🐾 Properties 2

Facts

```
public List<LearningFactInput> Facts { get; set; }
```

RegexPatterns

```
public List<LearningRegexInput> RegexPatterns { get; set; }
```

Class LearningMaintenanceResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearningMaintenanceResult

Implements IEquatable < LearningMaintenanceResult >

```
public sealed record LearningMaintenanceResult : IEquatable<LearningMaintenanceResult>
```

🌟 Constructors 1

LearningMaintenanceResult(int, int, IReadOnlyList<Guid>, IReadOnlyList<string>)

```
public LearningMaintenanceResult(int FactsStored, int RegexPatternsStored, IReadOnlyList<Guid> KnowledgeEntryIds, IReadOnlyList<string> RegexNames)
```

🐾 Properties 4

FactsStored

```
public int FactsStored { get; init; }
```

KnowledgeEntryIds

```
public IReadOnlyList<Guid> KnowledgeEntryIds { get; init; }
```

RegexNames

```
public IReadOnlyList<string> RegexNames { get; init; }
```

RegexPatternsStored

```
public int RegexPatternsStored { get; init; }
```

⚙️ Methods 5

Deconstruct(out int, out int, out IReadOnlyList<Guid>, out IReadOnlyList<string>)

```
public void Deconstruct(out int FactsStored, out int RegexPatternsStored, out IReadOnlyList<Guid> KnowledgeEntryIds, out IReadOnlyList<string> RegexNames)
```

Equals(LearningMaintenanceResult?)

```
public bool Equals(LearningMaintenanceResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LearningMaintenanceResult?, LearningMaintenanceResult?)

```
public static bool operator ==(LearningMaintenanceResult? left, LearningMaintenanceResult? right)
```

operator !=(LearningMaintenanceResult?, LearningMaintenanceResult?)

```
public static bool operator !=(LearningMaintenanceResult? left, LearningMaintenanceResult? right)
```


Class LearningRegexInput

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearningRegexInput

```
public sealed class LearningRegexInput
```

🌟 Constructors 1

LearningRegexInput()

```
public LearningRegexInput()
```

🐾 Properties 3

Flags

```
public string Flags { get; set; }
```

Name

```
public string Name { get; set; }
```

Pattern

```
public string Pattern { get; set; }
```

Class LearningRoundSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LearningRoundSnapshot

```
public sealed class LearningRoundSnapshot
```

🌟 Constructors 1

LearningRoundSnapshot()

```
public LearningRoundSnapshot()
```

🐾 Properties 11

ConversationCount

```
public int ConversationCount { get; set; }
```

GeneratedAtUtc

```
public DateTime GeneratedAtUtc { get; set; }
```

KnowledgeCount

```
public int KnowledgeCount { get; set; }
```

LogCount

```
public int LogCount { get; set; }
```

MessageCount

```
public int MessageCount { get; set; }
```

RecentConversations

```
public IReadOnlyList<object> RecentConversations { get; set; }
```

RecentKnowledge

```
public IReadOnlyList<object> RecentKnowledge { get; set; }
```

RecentLogs

```
public IReadOnlyList<object> RecentLogs { get; set; }
```

RecentMessages

```
public IReadOnlyList<object> RecentMessages { get; set; }
```

RegexCount

```
public int RegexCount { get; set; }
```

RegexPatterns

```
public IReadOnlyList<object> RegexPatterns { get; set; }
```

Class LinkProjectOrganicSkillRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LinkProjectOrganicSkillRequest

```
public sealed class LinkProjectOrganicSkillRequest
```

✨ Constructors 1

LinkProjectOrganicSkillRequest()

```
public LinkProjectOrganicSkillRequest()
```

🐾 Properties 6

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsRequired

```
public bool IsRequired { get; set; }
```

Notes

```
public string Notes { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

SkillId

```
public Guid SkillId { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class LinkProjectTopicKnowledgeRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LinkProjectTopicKnowledgeRequest

```
public sealed class LinkProjectTopicKnowledgeRequest
```

✨ Constructors 1

LinkProjectTopicKnowledgeRequest()

```
public LinkProjectTopicKnowledgeRequest()
```

🐾 Properties 3

KnowledgeEntryId

```
public Guid KnowledgeEntryId { get; set; }
```

LinkReason

```
public string LinkReason { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class LocalAiHostDiscoveryResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalAiHostDiscoveryResult

```
public sealed class LocalAiHostDiscoveryResult
```

🌟 Constructors 1

LocalAiHostDiscoveryResult()

```
public LocalAiHostDiscoveryResult()
```

🐾 Properties 5

Endpoint

```
public string Endpoint { get; set; }
```

IsReachable

```
public bool IsReachable { get; set; }
```

Models

```
public List<LocalAiModelInfo> Models { get; set; }
```

Provider

```
public string Provider { get; set; }
```

Status

```
public string Status { get; set; }
```

Class LocalAiModelInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalAiModelInfo

```
public sealed class LocalAiModelInfo
```

🌟 Constructors 1

LocalAiModelInfo()

```
public LocalAiModelInfo()
```

🐾 Properties 3

Details

```
public string? Details { get; set; }
```

IsLoaded

```
public bool IsLoaded { get; set; }
```

Name

```
public string Name { get; set; }
```

Class LocalGptDatabaseOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Immutable runtime settings for the local SQLite store.

Inheritance object LocalGptDatabaseOptions

Implements IEquatable < LocalGptDatabaseOptions >

```
public sealed record LocalGptDatabaseOptions : IEquatable<LocalGptDatabaseOptions>
```

🌟 Constructors 1

LocalGptDatabaseOptions(string, int)

Immutable runtime settings for the local SQLite store.

```
public LocalGptDatabaseOptions(string DatabasePath, int ProbeCommandTimeoutSeconds = 5)
```

🔴 Fields 1

SectionName

```
public const string SectionName = "LocalGptDatabase"
```

🐾 Properties 2

DatabasePath

```
public string DatabasePath { get; init; }
```

ProbeCommandTimeoutSeconds

```
public int ProbeCommandTimeoutSeconds { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out int)

```
public void Deconstruct(out string DatabasePath, out int ProbeCommandTimeoutSeconds)
```

Equals(LocalGptDatabaseOptions?)

```
public bool Equals(LocalGptDatabaseOptions? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptDatabaseOptions?, LocalGptDatabaseOptions?)

```
public static bool operator ==(LocalGptDatabaseOptions? left, LocalGptDatabaseOptions? right)
```

operator !=(LocalGptDatabaseOptions?, LocalGptDatabaseOptions?)

```
public static bool operator !=(LocalGptDatabaseOptions? left, LocalGptDatabaseOptions? right)
```

Class LocalGptDocumentationComment

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Represents one compiler-generated XML documentation member after localization adaptation and version enrichment.
Inheritance object LocalGptDocumentationComment

```
[DocumentationUpdated("2.1.20")] public sealed class LocalGptDocumentationComment
```

🌟 Constructors 1

LocalGptDocumentationComment()

```
public LocalGptDocumentationComment()
```

🐾 Properties 8

Culture
Gets or sets the requested UI culture used by the documentation translation adapter.

```
public string Culture { get; set; }
```

CurrentVersion
Gets or sets the current LocalGPT application version.

```
public string CurrentVersion { get; set; }
```

DisplayName
Gets or sets a readable member name derived from the stable identifier.

```
public string DisplayName { get; set; }
```

IsCurrent
Gets or sets whether the comment review version matches the running application version.

```
public bool IsCurrent { get; set; }
```

LastUpdatedVersion
Gets or sets the LocalGPT version in which the declaring contract documentation was last reviewed.

```
public string LastUpdatedVersion { get; set; }
```

MemberId
Gets or sets the stable XML documentation member identifier.

```
public string MemberId { get; set; }
```

Remarks
Gets or sets localized extended guidance, falling back to the maintained XML remarks.

```
public string Remarks { get; set; }
```

Summary
Gets or sets the localized summary text, falling back to the maintained XML comment.

```
public string Summary { get; set; }
```

Class LocalGptDocumentationStatus

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes the generated LocalGPT documentation artifacts available to the running application.

Inheritance object LocalGptDocumentationStatus

```
[DocumentationUpdated("2.1.20")] public sealed class LocalGptDocumentationStatus
```

✨ Constructors 1

LocalGptDocumentationStatus()

```
public LocalGptDocumentationStatus()
```

🐾 Properties 11

CommentCount

Gets or sets the number of XML-comment members currently available through the documentation API.

```
public int CommentCount { get; set; }
```

CommentsUrl

Gets or sets the application-relative URL of the searchable XML-comment catalog.

```
public string CommentsUrl { get; set; }
```

GeneratedAtUtc

Gets or sets the UTC build time recorded by the generated documentation manifest.

```
public DateTime? GeneratedAtUtc { get; set; }
```

HtmlAvailable

Gets or sets whether the generated DocFX HTML entry page exists.

```
public bool HtmlAvailable { get; set; }
```

HtmlUrl

Gets or sets the application-relative URL of the generated HTML documentation.

```
public string HtmlUrl { get; set; }
```

InspectedAtUtc

Gets or sets the UTC time at which the documentation status was inspected.

```
public DateTime InspectedAtUtc { get; set; }
```

PdfAvailable

Gets or sets whether the versioned PDF artifact exists.

```
public bool PdfAvailable { get; set; }
```

PdfFileName

Gets or sets the versioned PDF file name.

```
public string PdfFileName { get; set; }
```

PdfUrl

Gets or sets the application-relative URL of the generated PDF documentation.

```
public string PdfUrl { get; set; }
```

Version

Gets or sets the LocalGPT application version represented by the documentation.

```
public string Version { get; set; }
```

XmlCommentsAvailable

Gets or sets whether the compiler-generated XML comment catalog exists.

```
public bool XmlCommentsAvailable { get; set; }
```

Class LocalGptProject

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProject

```
public sealed class LocalGptProject
```

🌟 Constructors 1

LocalGptProject()

```
public LocalGptProject()
```

🐾 Properties 23

Artifacts

```
public ICollection<LocalGptProjectArtifact> Artifacts { get; set; }
```

BuildVerifications

```
public ICollection<ProjectBuildVerification> BuildVerifications { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CurrentVersion

```
public string CurrentVersion { get; set; }
```

FileExcludePattern

```
public string FileExcludePattern { get; set; }
```

FileIncludePattern

```
public string FileIncludePattern { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsArchived

```
public bool IsArchived { get; set; }
```

Name

```
[Required] public string Name { get; set; }
```

ProjectType

```
public string ProjectType { get; set; }
```

Purpose

```
[Column(TypeName = "TEXT")] public string Purpose { get; set; }
```

RecommendGit

```
public bool RecommendGit { get; set; }
```

Requirements

```
public ICollection<LocalGptProjectRequirement> Requirements { get; set; }
```

Revisions

```
public ICollection<LocalGptProjectRevision> Revisions { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

SolutionPath

```
public string SolutionPath { get; set; }
```


SolutionSearchPattern

```
public string SolutionSearchPattern { get; set; }
```

Status

```
public string Status { get; set; }
```

Topics

```
public ICollection<LocalGptProjectTopic> Topics { get; set; }
```

TrackedFiles

```
public ICollection<LocalGptProjectTrackedFile> TrackedFiles { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Versions

```
public ICollection<LocalGptProjectVersion> Versions { get; set; }
```

WorkspaceRoots

```
public ICollection<ProjectWorkspaceRoot> WorkspaceRoots { get; set; }
```

Class LocalGptProjectArtifact

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectArtifact

```
public sealed class LocalGptProjectArtifact
```

🌟 Constructors 1

LocalGptProjectArtifact()

```
public LocalGptProjectArtifact()
```

🐾 Properties 18

ArtifactKind

```
[Required] [MaxLength(80)] public string ArtifactKind { get; set; }
```

CouncilReviewStatus

```
[MaxLength(80)] public string CouncilReviewStatus { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

DataType

```
[MaxLength(120)] public string DataType { get; set; }
```

Description

```
[MaxLength(2000)] public string Description { get; set; }
```

Flags

```
[MaxLength(160)] public string Flags { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsSensitive

```
public bool IsSensitive { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

Name

```
[Required] [MaxLength(240)] public string Name { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Requirement

```
public LocalGptProjectRequirement? Requirement { get; set; }
```

RequirementId

```
public Guid? RequirementId { get; set; }
```

Revision

```
public LocalGptProjectRevision? Revision { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Value

```
[Column(TypeName = "TEXT")] public string Value { get; set; }
```

api/LocalGPT.BusinessObjects.LocalGptProjectDetails.html

Class LocalGptProjectDetails

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectDetails

```
public sealed class LocalGptProjectDetails
```

🌟 Constructors 1

LocalGptProjectDetails()

```
public LocalGptProjectDetails()
```

🐾 Properties 9

Artifacts

```
public IReadOnlyList<LocalGptProjectArtifact> Artifacts { get; init; }
```

BuildVerifications

```
public IReadOnlyList<ProjectBuildVerification> BuildVerifications { get; init; }
```

Project

```
public required LocalGptProject Project { get; init; }
```

Requirements

```
public IReadOnlyList<LocalGptProjectRequirement> Requirements { get; init; }
```

Revisions

```
public IReadOnlyList<LocalGptProjectRevision> Revisions { get; init; }
```

Topics

```
public IReadOnlyList<LocalGptProjectTopic> Topics { get; init; }
```

TrackedFiles

```
public IReadOnlyList<LocalGptProjectTrackedFile> TrackedFiles { get; init; }
```

Versions

```
public IReadOnlyList<LocalGptProjectVersion> Versions { get; init; }
```

WorkspaceRoots

```
public IReadOnlyList<ProjectWorkspaceRoot> WorkspaceRoots { get; init; }
```

Class LocalGptProjectGetParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectGetParameters

```
public sealed class LocalGptProjectGetParameters
```

🌟 Constructors 1

LocalGptProjectGetParameters()

```
public LocalGptProjectGetParameters()
```

🐾 Properties 1

ProjectId

```
public Guid ProjectId { get; set; }
```

Class LocalGptProjectListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectListParameters

```
public sealed class LocalGptProjectListParameters
```

🌟 Constructors 1

LocalGptProjectListParameters()

```
public LocalGptProjectListParameters()
```

🐾 Properties 1

IncludeArchived

```
public bool IncludeArchived { get; set; }
```

Class LocalGptProjectRequirement

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectRequirement

```
public sealed class LocalGptProjectRequirement
```

🌟 Constructors 1

LocalGptProjectRequirement()

```
public LocalGptProjectRequirement()
```

🐾 Properties 17

CouncilRating

```
public int CouncilRating { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Description

```
[Column(TableName = "TEXT")] public string Description { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

Links

```
public ICollection<LocalGptProjectRequirementLink> Links { get; set; }
```

Name

```
[Required] [MaxLength(240)] public string Name { get; set; }
```

Priority

```
[MaxLength(40)] public string Priority { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

RequiredCapability

```
[MaxLength(240)] public string RequiredCapability { get; set; }
```

RequirementType

```
[MaxLength(80)] public string RequirementType { get; set; }
```

Revision

```
public LocalGptProjectRevision? Revision { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

SourceKind

```
[MaxLength(160)] public string SourceKind { get; set; }
```

Status

```
[MaxLength(80)] public string Status { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

api/LocalGPT.BusinessObjects.LocalGptProjectRequirementLink.html

Class LocalGptProjectRequirementLink

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectRequirementLink

```
public sealed class LocalGptProjectRequirementLink
```

🌟 Constructors 1

LocalGptProjectRequirementLink()

```
public LocalGptProjectRequirementLink()
```

🐾 Properties 11

CouncilReviewStatus

```
[MaxLength(80)] public string CouncilReviewStatus { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

LinkPurpose

```
[MaxLength(1000)] public string LinkPurpose { get; set; }
```

LinkedAtUtc

```
public DateTime LinkedAtUtc { get; set; }
```

Requirement

```
public LocalGptProjectRequirement? Requirement { get; set; }
```

RequirementId

```
public Guid RequirementId { get; set; }
```

TargetId

```
[MaxLength(160)] public string TargetId { get; set; }
```

TargetKind

```
[Required] [MaxLength(80)] public string TargetKind { get; set; }
```

TargetName

```
[Required] [MaxLength(240)] public string TargetName { get; set; }
```

TargetTable

```
[MaxLength(160)] public string TargetTable { get; set; }
```

Class LocalGptProjectRevision

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectRevision

```
public sealed class LocalGptProjectRevision
```

🌟 Constructors 1

LocalGptProjectRevision()

```
public LocalGptProjectRevision()
```

🐾 Properties 25

ApprovedForTestingAtUtc

```
public DateTime? ApprovedForTestingAtUtc { get; set; }
```

BranchName

```
[Required] [MaxLength(160)] public string BranchName { get; set; }
```

BuildVerifications

```
public ICollection<ProjectBuildVerification> BuildVerifications { get; set; }
```

ChildRevisions

```
public ICollection<LocalGptProjectRevision> ChildRevisions { get; set; }
```

CompileVerified

```
public bool CompileVerified { get; set; }
```

CouncilVerified

```
public bool CouncilVerified { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

CreatedBy

```
[MaxLength(120)] public string CreatedBy { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsCurrent

```
public bool IsCurrent { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

ParentRevision

```
public LocalGptProjectRevision? ParentRevision { get; set; }
```

ParentRevisionId

```
public Guid? ParentRevisionId { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

ProjectStructureJson

```
[Column(TypeName = "TEXT")] public string ProjectStructureJson { get; set; }
```

ReadyForTesting

```
public bool ReadyForTesting { get; set; }
```

RevisionName

```
[Required] [MaxLength(160)] public string RevisionName { get; set; }
```

SnapshotArchivePath

```
[MaxLength(2048)] public string SnapshotArchivePath { get; set; }
```

SolutionPath

```
[MaxLength(2048)] public string SolutionPath { get; set; }
```

SourceRootPath

```
[MaxLength(2048)] public string SourceRootPath { get; set; }
```

SourceSnapshotHash

```
[MaxLength(128)] public string SourceSnapshotHash { get; set; }
```

Summary

```
[Column(TypeName = "TEXT")] public string Summary { get; set; }
```

TrackedFiles

```
public ICollection<LocalGptProjectTrackedFile> TrackedFiles { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```


Class LocalGptProjectSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectSummary

Implements IEquatable < LocalGptProjectSummary >

```
public sealed record LocalGptProjectSummary : IEquatable<LocalGptProjectSummary>
```

🌟 Constructors 1

LocalGptProjectSummary(Guid, string, string, string, string, string, bool, bool, int, int, DateTime)

```
public LocalGptProjectSummary(Guid Id, string Name, string Purpose, string RootPath, string CurrentVersion, string Status, bool RecommendGit, bool IsArchived, int TopicCount, int VersionCount, DateTime UpdatedAtUtc)
```

🐾 Properties 12

CurrentVersion

```
public string CurrentVersion { get; init; }
```

DisplayName

```
public string DisplayName { get; }
```

Id

```
public Guid Id { get; init; }
```

IsArchived

```
public bool IsArchived { get; init; }
```

Name

```
public string Name { get; init; }
```

Purpose

```
public string Purpose { get; init; }
```

RecommendGit

```
public bool RecommendGit { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

Status

```
public string Status { get; init; }
```

TopicCount

```
public int TopicCount { get; init; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; init; }
```

VersionCount

```
public int VersionCount { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out string, out string, out string, out string, out string, out bool, out bool, out int, out int, out DateTime)

```
public void Deconstruct(out Guid Id, out string Name, out string Purpose, out string RootPath, out string CurrentVersion, out string Status, out bool RecommendGit, out bool IsArchived, out int TopicCount, out int VersionCount, out DateTime UpdatedAtUtc)
```

Equals(LocalGptProjectSummary?)

```
public bool Equals(LocalGptProjectSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(LocalGptProjectSummary?, LocalGptProjectSummary?)

```
public static bool operator ==(LocalGptProjectSummary? left, LocalGptProjectSummary? right)
```

operator !=(LocalGptProjectSummary?, LocalGptProjectSummary?)

```
public static bool operator !=(LocalGptProjectSummary? left, LocalGptProjectSummary? right)
```

api/LocalGPT.BusinessObjects.LocalGptProjectTopic.html

Class LocalGptProjectTopic

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectTopic

```
public sealed class LocalGptProjectTopic
```

🌟 Constructors 1

LocalGptProjectTopic()

```
public LocalGptProjectTopic()
```

🐾 Properties 10

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Description

```
[Column(TypeName = "TEXT")] public string Description { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

KnowledgeLinks

```
public ICollection<LocalGptProjectTopicKnowledgeLink> KnowledgeLinks { get; set; }
```

Name

```
[Required] public string Name { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Status

```
public string Status { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class LocalGptProjectTopicKnowledgeLink

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectTopicKnowledgeLink

```
public sealed class LocalGptProjectTopicKnowledgeLink
```

🌟 Constructors 1

LocalGptProjectTopicKnowledgeLink()

```
public LocalGptProjectTopicKnowledgeLink()
```

🐾 Properties 7

KnowledgeEntry

```
public CouncilKnowledgeEntry? KnowledgeEntry { get; set; }
```

KnowledgeEntryId

```
public Guid KnowledgeEntryId { get; set; }
```

LinkReason

```
public string LinkReason { get; set; }
```

LinkedAtUtc

```
public DateTime LinkedAtUtc { get; set; }
```

LinkedByHuman

```
public bool LinkedByHuman { get; set; }
```

ProjectTopic

```
public LocalGptProjectTopic? ProjectTopic { get; set; }
```

ProjectTopicId

```
public Guid ProjectTopicId { get; set; }
```

Class LocalGptProjectTrackedFile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectTrackedFile

```
public sealed class LocalGptProjectTrackedFile
```

🌟 Constructors 1

LocalGptProjectTrackedFile()

```
public LocalGptProjectTrackedFile()
```

🐾 Properties 25

AbsolutePath

```
[Required] [MaxLength(2048)] public string AbsolutePath { get; set; }
```

ContentFormatRegex

```
[Column(TypeName = "TEXT")] public string ContentFormatRegex { get; set; }
```

ContentHash

```
[Required] [MaxLength(128)] public string ContentHash { get; set; }
```

ContentType

```
[MaxLength(120)] public string ContentType { get; set; }
```

EncodingName

```
[MaxLength(80)] public string EncodingName { get; set; }
```

Exists

```
public bool Exists { get; set; }
```

Extension

```
[MaxLength(40)] public string Extension { get; set; }
```

FileName

```
[Required] [MaxLength(260)] public string FileName { get; set; }
```

FileRole

```
[MaxLength(120)] public string FileRole { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsGenerated

```
public bool IsGenerated { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

LastSeenAtUtc

```
public DateTime LastSeenAtUtc { get; set; }
```

LastWriteTimeUtc

```
public DateTime? LastWriteTimeUtc { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectFilePath

```
[MaxLength(2048)] public string ProjectFilePath { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

ProjectRelativePath

```
[Required] [MaxLength(2048)] public string ProjectRelativePath { get; set; }
```

Revision

```
public LocalGptProjectRevision? Revision { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

SizeBytes

```
public long SizeBytes { get; set; }
```

SolutionPath

```
[MaxLength(2048)] public string SolutionPath { get; set; }
```

StableFileKey

```
[Required] [MaxLength(128)] public string StableFileKey { get; set; }
```

StructureRegex

```
[Column(TypeName = "TEXT")] public string StructureRegex { get; set; }
```

WorkspaceRelativePath

```
[MaxLength(2048)] public string WorkspaceRelativePath { get; set; }
```

Class LocalGptProjectVersion

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptProjectVersion

```
public sealed class LocalGptProjectVersion
```

🌟 Constructors 1

LocalGptProjectVersion()

```
public LocalGptProjectVersion()
```

🐾 Properties 9

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsCurrent

```
public bool IsCurrent { get; set; }
```

IsUserConfirmed

```
public bool IsUserConfirmed { get; set; }
```

Notes

```
[Column(TypeName = "TEXT")] public string Notes { get; set; }
```

PathSnapshot

```
public string PathSnapshot { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Version

```
[Required] public string Version { get; set; }
```

Enum LocalGptRuntimeCollection

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum LocalGptRuntimeCollection
```

Fields 1

Class LocalGptRuntimeCollectionSeed

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimeCollectionSeed

Implements IEquatable < LocalGptRuntimeCollectionSeed >

```
public sealed record LocalGptRuntimeCollectionSeed : IEquatable<LocalGptRuntimeCollectionSeed>
```

Constructors 1

LocalGptRuntimeCollectionSeed(LocalGptRuntimeCollection, string, IReadOnlyList<string>)

```
public LocalGptRuntimeCollectionSeed(LocalGptRuntimeCollection Key, string Name, IReadOnlyList<string> Values)
```

Properties 3

Key

```
public LocalGptRuntimeCollection Key { get; init; }
```

Name

```
public string Name { get; init; }
```

Values

```
public IReadOnlyList<string> Values { get; init; }
```

Methods 5

Deconstruct(out LocalGptRuntimeCollection, out string, out IReadOnlyList<string>)

```
public void Deconstruct(out LocalGptRuntimeCollection Key, out string Name, out IReadOnlyList<string> Values)
```

Equals(LocalGptRuntimeCollectionSeed?)

```
public bool Equals(LocalGptRuntimeCollectionSeed? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(LocalGptRuntimeCollectionSeed?, LocalGptRuntimeCollectionSeed?)

```
public static bool operator ==(LocalGptRuntimeCollectionSeed? left, LocalGptRuntimeCollectionSeed? right)
```

operator !=(LocalGptRuntimeCollectionSeed?, LocalGptRuntimeCollectionSeed?)

```
public static bool operator !=(LocalGptRuntimeCollectionSeed? left, LocalGptRuntimeCollectionSeed? right)
```

Enum LocalGptRuntimePattern

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum LocalGptRuntimePattern
```

Fields 1

Class LocalGptRuntimePolicyDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicyDefinition

Implements IEquatable < LocalGptRuntimePolicyDefinition >

```
public sealed record LocalGptRuntimePolicyDefinition : IEquatable<LocalGptRuntimePolicyDefinition>
```

Constructors 1

LocalGptRuntimePolicyDefinition()

```
public LocalGptRuntimePolicyDefinition()
```

Properties 3

Collections

```
public IReadOnlyDictionary<LocalGptRuntimeCollection, IReadOnlyList<string>> Collections { get; init; }
```

RegexPatterns

```
public IReadOnlyDictionary<LocalGptRuntimePattern, LocalGptRuntimeRegexDefinition> RegexPatterns { get; init; }
```

Values

```
public IReadOnlyDictionary<LocalGptRuntimeValue, string> Values { get; init; }
```

Methods 4

Equals(LocalGptRuntimePolicyDefinition?)

```
public bool Equals(LocalGptRuntimePolicyDefinition? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(LocalGptRuntimePolicyDefinition?, LocalGptRuntimePolicyDefinition?)

```
public static bool operator ==(LocalGptRuntimePolicyDefinition? left, LocalGptRuntimePolicyDefinition? right)
```

operator !=(LocalGptRuntimePolicyDefinition?, LocalGptRuntimePolicyDefinition?)

```
public static bool operator !=(LocalGptRuntimePolicyDefinition? left, LocalGptRuntimePolicyDefinition? right)
```


Class LocalGptRuntimePolicySeedModel

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicySeedModel

Implements IEquatable < LocalGptRuntimePolicySeedModel >

```
public sealed record LocalGptRuntimePolicySeedModel : IEquatable<LocalGptRuntimePolicySeedModel>
```

🌟 Constructors 1

LocalGptRuntimePolicySeedModel()

```
public LocalGptRuntimePolicySeedModel()
```

🐾 Properties 5

Collections

```
public IReadOnlyList<LocalGptRuntimeCollectionSeed> Collections { get; init; }
```

LocalGptCoreProjectId

```
public Guid LocalGptCoreProjectId { get; }
```

RegexPatterns

```
public IReadOnlyList<LocalGptRuntimeRegexSeed> RegexPatterns { get; init; }
```

SystemVariables

```
public IReadOnlyList<LocalGptRuntimeSystemVariableSeed> SystemVariables { get; }
```

Values

```
public IReadOnlyList<LocalGptRuntimeSystemVariableSeed> Values { get; init; }
```

⚙️ Methods 4

Equals(LocalGptRuntimePolicySeedModel?)

```
public bool Equals(LocalGptRuntimePolicySeedModel? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptRuntimePolicySeedModel?, LocalGptRuntimePolicySeedModel?)

```
public static bool operator ==(LocalGptRuntimePolicySeedModel? left, LocalGptRuntimePolicySeedModel? right)
```

operator !=(LocalGptRuntimePolicySeedModel?, LocalGptRuntimePolicySeedModel?)

```
public static bool operator !=(LocalGptRuntimePolicySeedModel? left, LocalGptRuntimePolicySeedModel? right)
```

Class LocalGptRuntimePolicySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicySnapshot

Implements IEquatable < LocalGptRuntimePolicySnapshot >

```
public sealed record LocalGptRuntimePolicySnapshot : IEquatable<LocalGptRuntimePolicySnapshot>
```

🌟 Constructors 1

LocalGptRuntimePolicySnapshot()

```
public LocalGptRuntimePolicySnapshot()
```

🐾 Properties 3

Collections

```
public IReadOnlyDictionary<string, IReadOnlyList<string>> Collections { get; init; }
```

RegexPatterns

```
public IReadOnlyDictionary<string, string> RegexPatterns { get; init; }
```

Values

```
public IReadOnlyDictionary<string, string> Values { get; init; }
```

⚙️ Methods 4

Equals(LocalGptRuntimePolicySnapshot?)

```
public bool Equals(LocalGptRuntimePolicySnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptRuntimePolicySnapshot?, LocalGptRuntimePolicySnapshot?)

```
public static bool operator ==(LocalGptRuntimePolicySnapshot? left, LocalGptRuntimePolicySnapshot? right)
```

operator !=(LocalGptRuntimePolicySnapshot?, LocalGptRuntimePolicySnapshot?)

```
public static bool operator !=(LocalGptRuntimePolicySnapshot? left, LocalGptRuntimePolicySnapshot? right)
```

Class LocalGptRuntimeRegexDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimeRegexDefinition

Implements IEquatable < LocalGptRuntimeRegexDefinition >

```
public sealed record LocalGptRuntimeRegexDefinition : IEquatable<LocalGptRuntimeRegexDefinition>
```

🌟 Constructors 1

LocalGptRuntimeRegexDefinition()

```
public LocalGptRuntimeRegexDefinition()
```

🐾 Properties 5

Flags

```
public string Flags { get; init; }
```

Key

```
public LocalGptRuntimePattern Key { get; init; }
```

Name

```
public string Name { get; init; }
```

Pattern

```
public string Pattern { get; init; }
```

UpdatedOn

```
public DateTime UpdatedOn { get; init; }
```

⚙️ Methods 4

Equals(LocalGptRuntimeRegexDefinition?)

```
public bool Equals(LocalGptRuntimeRegexDefinition? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptRuntimeRegexDefinition?, LocalGptRuntimeRegexDefinition?)

```
public static bool operator ==(LocalGptRuntimeRegexDefinition? left, LocalGptRuntimeRegexDefinition? right)
```

operator !=(LocalGptRuntimeRegexDefinition?, LocalGptRuntimeRegexDefinition?)

```
public static bool operator !=(LocalGptRuntimeRegexDefinition? left, LocalGptRuntimeRegexDefinition? right)
```

Class LocalGptRuntimeRegexSeed

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimeRegexSeed

Implements IEquatable < LocalGptRuntimeRegexSeed >

```
public sealed record LocalGptRuntimeRegexSeed : IEquatable<LocalGptRuntimeRegexSeed>
```

🌟 Constructors 1

LocalGptRuntimeRegexSeed(LocalGptRuntimePattern, string, string, string)

```
public LocalGptRuntimeRegexSeed(LocalGptRuntimePattern Key, string Name, string Pattern, string Flags)
```

🐾 Properties 4

Flags

```
public string Flags { get; init; }
```

Key

```
public LocalGptRuntimePattern Key { get; init; }
```

Name

```
public string Name { get; init; }
```

Pattern

```
public string Pattern { get; init; }
```

⚙️ Methods 5

Deconstruct(out LocalGptRuntimePattern, out string, out string, out string)

```
public void Deconstruct(out LocalGptRuntimePattern Key, out string Name, out string Pattern, out string Flags)
```

Equals(LocalGptRuntimeRegexSeed?)

```
public bool Equals(LocalGptRuntimeRegexSeed? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptRuntimeRegexSeed?, LocalGptRuntimeRegexSeed?)

```
public static bool operator ==(LocalGptRuntimeRegexSeed? left, LocalGptRuntimeRegexSeed? right)
```

operator !=(LocalGptRuntimeRegexSeed?, LocalGptRuntimeRegexSeed?)

```
public static bool operator !=(LocalGptRuntimeRegexSeed? left, LocalGptRuntimeRegexSeed? right)
```

Class LocalGptRuntimeSystemVariableSeed

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptRuntimeSystemVariableSeed

Implements IEquatable < LocalGptRuntimeSystemVariableSeed >

```
public sealed record LocalGptRuntimeSystemVariableSeed : IEquatable<LocalGptRuntimeSystemVariableSeed>
```

🌟 Constructors 1

LocalGptRuntimeSystemVariableSeed(LocalGptRuntimeValue, string, string, string)

```
public LocalGptRuntimeSystemVariableSeed(LocalGptRuntimeValue Key, string Name, string Value, string DataType)
```

🐾 Properties 4

DataType

```
public string DataType { get; init; }
```

Key

```
public LocalGptRuntimeValue Key { get; init; }
```

Name

```
public string Name { get; init; }
```

Value

```
public string Value { get; init; }
```

⚙️ Methods 5

Deconstruct(out LocalGptRuntimeValue, out string, out string, out string)

```
public void Deconstruct(out LocalGptRuntimeValue Key, out string Name, out string Value, out string DataType)
```

Equals(LocalGptRuntimeSystemVariableSeed?)

```
public bool Equals(LocalGptRuntimeSystemVariableSeed? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalGptRuntimeSystemVariableSeed?, LocalGptRuntimeSystemVariableSeed?)

```
public static bool operator ==(LocalGptRuntimeSystemVariableSeed? left, LocalGptRuntimeSystemVariableSeed? right)
```

operator !=(LocalGptRuntimeSystemVariableSeed?, LocalGptRuntimeSystemVariableSeed?)

```
public static bool operator !=(LocalGptRuntimeSystemVariableSeed? left, LocalGptRuntimeSystemVariableSeed? right)
```

Enum LocalGptRuntimeValue

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum LocalGptRuntimeValue
```

Fields 1

Class LocalGptVocabularySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalGptVocabularySnapshot

```
public sealed class LocalGptVocabularySnapshot
```

Constructors 1

LocalGptVocabularySnapshot()

```
public LocalGptVocabularySnapshot()
```

Properties 36

ActorAiModel

```
public string ActorAiModel { get; set; }
```

ActorApiClient

```
public string ActorApiClient { get; set; }
```

ActorCouncil

```
public string ActorCouncil { get; set; }
```

ActorHuman

```
public string ActorHuman { get; set; }
```

ActorSystem

```
public string ActorSystem { get; set; }
```

AuthorityHumanApproval

```
public string AuthorityHumanApproval { get; set; }
```

AuthorityHumanInteraction

```
public string AuthorityHumanInteraction { get; set; }
```

AuthorityNone

```
public string AuthorityNone { get; set; }
```

CatalogDxFunction

```
public string CatalogDxFunction { get; set; }
```

CatalogPublicServiceMethod

```
public string CatalogPublicServiceMethod { get; set; }
```

ContributionEvaluated

```
public string ContributionEvaluated { get; set; }
```

ContributionInjected

```
public string ContributionInjected { get; set; }
```

ContributionQueued

```
public string ContributionQueued { get; set; }
```

CouncilSpoolerCompleted

```
public string CouncilSpoolerCompleted { get; set; }
```

CouncilSpoolerFailed

```
public string CouncilSpoolerFailed { get; set; }
```

CouncilSpoolerRunning

```
public string CouncilSpoolerRunning { get; set; }
```

DeferredCompleted

```
public string DeferredCompleted { get; set; }
```

DeferredCompletedElsewhere

```
public string DeferredCompletedElsewhere { get; set; }
```

DeferredDeclined

```
public string DeferredDeclined { get; set; }
```

DeferredExecuting

```
public string DeferredExecuting { get; set; }
```

DeferredFailed

```
public string DeferredFailed { get; set; }
```

DeferredPendingApproval

```
public string DeferredPendingApproval { get; set; }
```

HumanRequestApproval

```
public string HumanRequestApproval { get; set; }
```

HumanRequestFeedback

```
public string HumanRequestFeedback { get; set; }
```

HumanRequestGuidance

```
public string HumanRequestGuidance { get; set; }
```

HumanStatusAnswered

```
public string HumanStatusAnswered { get; set; }
```

HumanStatusApproved

```
public string HumanStatusApproved { get; set; }
```

HumanStatusConsumed

```
public string HumanStatusConsumed { get; set; }
```

HumanStatusDeclined

```
public string HumanStatusDeclined { get; set; }
```

HumanStatusExpired

```
public string HumanStatusExpired { get; set; }
```

HumanStatusPending

```
public string HumanStatusPending { get; set; }
```

VerdictMixed

```
public string VerdictMixed { get; set; }
```

VerdictNeedsCorrection

```
public string VerdictNeedsCorrection { get; set; }
```

VerdictNotReviewed

```
public string VerdictNotReviewed { get; set; }
```

VerdictPending

```
public string VerdictPending { get; set; }
```

VerdictSupported

```
public string VerdictSupported { get; set; }
```


Class LocalizationCatalogDescriptor

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes a built-in or user-supplied LocalGPT localization catalog.

Inheritance object LocalizationCatalogDescriptor

Implements IEquatable < LocalizationCatalogDescriptor >

```
[DocumentationUpdated("2.1.21")] public sealed record LocalizationCatalogDescriptor : IEquatable<LocalizationCatalogDescriptor>
```

🌟 Constructors 1

LocalizationCatalogDescriptor(string, bool, bool, int, string)

Describes a built-in or user-supplied LocalGPT localization catalog.

```
public LocalizationCatalogDescriptor(string Culture, bool IsBuiltIn, bool HasUserOverride, int StringCount, string DisplayName)
```

🐾 Properties 5

Culture

Normalized .NET culture name represented by the catalog.

```
public string Culture { get; init; }
```

DisplayName

Culture display name resolved by the local .NET runtime.

```
public string DisplayName { get; init; }
```

HasUserOverride

Indicates whether a persistent user catalog augments or overrides the built-in catalog.

```
public bool HasUserOverride { get; init; }
```

IsBuiltIn

Indicates whether LocalGPT ships a catalog for the culture.

```
public bool IsBuiltIn { get; init; }
```

StringCount

Number of effective localized strings after fallback and overrides are merged.

```
public int StringCount { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out bool, out bool, out int, out string)

```
public void Deconstruct(out string Culture, out bool IsBuiltIn, out bool HasUserOverride, out int StringCount, out string DisplayName)
```

Equals(LocalizationCatalogDescriptor?)

```
public bool Equals(LocalizationCatalogDescriptor? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(LocalizationCatalogDescriptor?, LocalizationCatalogDescriptor?)

```
public static bool operator ==(LocalizationCatalogDescriptor? left, LocalizationCatalogDescriptor? right)
```

operator !=(LocalizationCatalogDescriptor?, LocalizationCatalogDescriptor?)

```
public static bool operator !=(LocalizationCatalogDescriptor? left, LocalizationCatalogDescriptor? right)
```

Class LocalizationCatalogImportResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Reports the durable result of importing a localization catalog.

Inheritance object LocalizationCatalogImportResult

Implements IEquatable < LocalizationCatalogImportResult >

```
[DocumentationUpdated("2.1.21")] public sealed record LocalizationCatalogImportResult : IEquatable<LocalizationCatalogImportResult>
```

🌟 Constructors 1

LocalizationCatalogImportResult(string, int, int)

Reports the durable result of importing a localization catalog.

```
public LocalizationCatalogImportResult(string Culture, int StringCount, int MissingBaselineKeyCount)
```

🦋 Properties 3

Culture

Normalized culture name written by the import.

```
public string Culture { get; init; }
```

MissingBaselineKeyCount

Number of English baseline keys supplied through fallback.

```
public int MissingBaselineKeyCount { get; init; }
```

StringCount

Number of submitted strings.

```
public int StringCount { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out int, out int)

```
public void Deconstruct(out string Culture, out int StringCount, out int MissingBaselineKeyCount)
```

Equals(LocalizationCatalogImportResult?)

```
public bool Equals(LocalizationCatalogImportResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(LocalizationCatalogImportResult?, LocalizationCatalogImportResult?)

```
public static bool operator ==(LocalizationCatalogImportResult? left, LocalizationCatalogImportResult? right)
```

operator !=(LocalizationCatalogImportResult?, LocalizationCatalogImportResult?)

```
public static bool operator !=(LocalizationCatalogImportResult? left, LocalizationCatalogImportResult? right)
```

Class LocalizationCatalogRegistration

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Persistent registration for a built-in or user-imported localization JSON catalog.

Inheritance object LocalizationCatalogRegistration

```
[DocumentationUpdated("2.1.23")] public sealed class LocalizationCatalogRegistration
```

🌟 Constructors 1

LocalizationCatalogRegistration()

```
public LocalizationCatalogRegistration()
```

🐾 Properties 10

CatalogPath

Gets or sets the bounded catalog path.

```
[MaxLength(2048)] public string CatalogPath { get; set; }
```

CreatedAtUtc

Gets or sets the UTC creation timestamp.

```
public DateTime CreatedAtUtc { get; set; }
```

CultureName

Gets or sets the normalized .NET culture name.

```
[MaxLength(40)] public string CultureName { get; set; }
```

DisplayName

Gets or sets the localized display name.

```
[MaxLength(240)] public string DisplayName { get; set; }
```

Id

Gets or sets the stable database identifier.

```
public Guid Id { get; set; }
```

IsEnabled

Gets or sets whether this catalog is offered by the language selector.

```
public bool IsEnabled { get; set; }
```

IsUserOverride

Gets or sets whether the catalog was imported by a user.

```
public bool IsUserOverride { get; set; }
```

MissingBaselineKeyCount

Gets or sets the number of English baseline keys not supplied by this catalog.

```
public int MissingBaselineKeyCount { get; set; }
```

StringCount

Gets or sets the number of parsed string entries.

```
public int StringCount { get; set; }
```

UpdatedAtUtc

Gets or sets the UTC update timestamp.

```
public DateTime UpdatedAtUtc { get; set; }
```

Class LocalizationCatalogValidationResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Reports the result of validating a user-provided localization JSON catalog.
Inheritance object LocalizationCatalogValidationResult

```
[DocumentationUpdated("2.1.21")] public sealed class LocalizationCatalogValidationResult
```

🌟 Constructors 1

LocalizationCatalogValidationResult()

```
public LocalizationCatalogValidationResult()
```

🐾 Properties 6

Culture
Gets or sets the normalized culture name.

```
public string Culture { get; set; }
```

Errors
Gets or sets validation errors that prevent import.

```
public List<string> Errors { get; set; }
```

IsValid
Gets or sets whether the culture name and JSON dictionary are valid.

```
public bool IsValid { get; set; }
```

MissingBaselineKeyCount
Gets or sets the number of English baseline keys absent from the submitted catalog.

```
public int MissingBaselineKeyCount { get; set; }
```

StringCount
Gets or sets the number of non-empty localization keys in the submitted catalog.

```
public int StringCount { get; set; }
```

Warnings
Gets or sets validation warnings that do not prevent import.

```
public List<string> Warnings { get; set; }
```

Class LocalVisionOcrRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalVisionOcrRequest

```
public sealed class LocalVisionOcrRequest
```

🌟 Constructors 1

LocalVisionOcrRequest()

```
public LocalVisionOcrRequest()
```

🐾 Properties 4

ImageUrl

```
public string ImageDataUrl { get; set; }
```

MaximumOutputTokens

```
public int MaximumOutputTokens { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

Class LocalVisionOcrResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LocalVisionOcrResult

```
public sealed class LocalVisionOcrResult
```

🌟 Constructors 1

LocalVisionOcrResult()

```
public LocalVisionOcrResult()
```

🐾 Properties 5

MediaType

```
public string MediaType { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

NeedsHumanReview

```
public bool NeedsHumanReview { get; set; }
```

ProviderUri

```
public string ProviderUri { get; set; }
```

Text

```
public string Text { get; set; }
```

Class LoggingCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object LoggingCoreOptions

```
public class LoggingCoreOptions
```

🌟 Constructors 1

LoggingCoreOptions()

```
public LoggingCoreOptions()
```

🔴 Fields 1

LoggingCore

```
public const string LoggingCore = "LoggingCore"
```

🐾 Properties 4

CoreLogLevel

```
public CoreLogLevel CoreLogLevel { get; set; }
```

DatabaseCore

```
public DatabaseLoggerCoreOptions? DatabaseCore { get; set; }
```

EmailCore

```
public EmailLoggerCoreOptions? EmailCore { get; set; }
```

FileCore

```
public FileLoggerCoreOptions? FileCore { get; set; }
```

Class MinecraftDatapackArtifactIdentity

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MinecraftDatapackArtifactIdentity

Implements IEquatable < MinecraftDatapackArtifactIdentity >

```
public sealed record MinecraftDatapackArtifactIdentity : IEquatable<MinecraftDatapackArtifactIdentity>
```

🌟 Constructors 1

MinecraftDatapackArtifactIdentity(string, string, string, string)

```
public MinecraftDatapackArtifactIdentity(string ProjectName, string ModId, string PackageName, string DisplayName)
```

🐾 Properties 4

DisplayName

```
public string DisplayName { get; init; }
```

ModId

```
public string ModId { get; init; }
```

PackageName

```
public string PackageName { get; init; }
```

ProjectName

```
public string ProjectName { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string)

```
public void Deconstruct(out string ProjectName, out string ModId, out string PackageName, out string DisplayName)
```

Equals(MinecraftDatapackArtifactIdentity?)

```
public bool Equals(MinecraftDatapackArtifactIdentity? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(MinecraftDatapackArtifactIdentity?, MinecraftDatapackArtifactIdentity?)

```
public static bool operator ==(MinecraftDatapackArtifactIdentity? left, MinecraftDatapackArtifactIdentity? right)
```

operator !=(MinecraftDatapackArtifactIdentity?, MinecraftDatapackArtifactIdentity?)

```
public static bool operator !=(MinecraftDatapackArtifactIdentity? left, MinecraftDatapackArtifactIdentity? right)
```

Class MinecraftDatapackVersionInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MinecraftDatapackVersionInfo

Implements IEquatable < MinecraftDatapackVersionInfo >

```
public sealed record MinecraftDatapackVersionInfo : IEquatable<MinecraftDatapackVersionInfo>
```

✨ Constructors 1

MinecraftDatapackVersionInfo(string, string, string, string, bool, bool, string, string)

```
public MinecraftDatapackVersionInfo(string RequestedVersion, string MatchedVersion, string PackFormat, string FunctionRegistryFolder, bool IsExactMatch, bool NeedsVerification, string Notes, string Source)
```

🐾 Properties 8

FunctionRegistryFolder

```
public string FunctionRegistryFolder { get; init; }
```

IsExactMatch

```
public bool IsExactMatch { get; init; }
```

MatchedVersion

```
public string MatchedVersion { get; init; }
```

NeedsVerification

```
public bool NeedsVerification { get; init; }
```

Notes

```
public string Notes { get; init; }
```

PackFormat

```
public string PackFormat { get; init; }
```

RequestedVersion

```
public string RequestedVersion { get; init; }
```

Source

```
public string Source { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out bool, out bool, out string, out string)

```
public void Deconstruct(out string RequestedVersion, out string MatchedVersion, out string PackFormat, out string FunctionRegistryFolder, out bool IsExactMatch, out bool NeedsVerification, out string Notes, out string Source)
```

Equals(MinecraftDatapackVersionInfo?)

```
public bool Equals(MinecraftDatapackVersionInfo? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(MinecraftDatapackVersionInfo?, MinecraftDatapackVersionInfo?)

```
public static bool operator ==(MinecraftDatapackVersionInfo? left, MinecraftDatapackVersionInfo? right)
```


operator !=(MinecraftDatapackVersionInfo?, MinecraftDatapackVersionInfo?)

```
public static bool operator !=(MinecraftDatapackVersionInfo? left, MinecraftDatapackVersionInfo? right)
```

Class MinecraftDependencyVersionInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MinecraftDependencyVersionInfo

Implements IEquatable < MinecraftDependencyVersionInfo >

```
public sealed record MinecraftDependencyVersionInfo : IEquatable<MinecraftDependencyVersionInfo>
```

🌟 Constructors 1

MinecraftDependencyVersionInfo(string, string, string, string, string, string?, string?, string?, string?, string?, bool, bool, string, string)

```
public MinecraftDependencyVersionInfo(string Loader, string RequestedMinecraftVersion, string MatchedMinecraftVersion, string JavaVersion, string
GradleVersion, string? FabricLoaderVersion, string? FabricApiVersion, string? NeoForgeVersion, string? PaperApiVersion, string? DatapackPackFormat, bool
IsExactMatch, bool NeedsVerification, string Notes, string Source)
```

🐾 Properties 14

DatapackPackFormat

```
public string? DatapackPackFormat { get; init; }
```

FabricApiVersion

```
public string? FabricApiVersion { get; init; }
```

FabricLoaderVersion

```
public string? FabricLoaderVersion { get; init; }
```

GradleVersion

```
public string GradleVersion { get; init; }
```

IsExactMatch

```
public bool IsExactMatch { get; init; }
```

JavaVersion

```
public string JavaVersion { get; init; }
```

Loader

```
public string Loader { get; init; }
```

MatchedMinecraftVersion

```
public string MatchedMinecraftVersion { get; init; }
```

NeedsVerification

```
public bool NeedsVerification { get; init; }
```

NeoForgeVersion

```
public string? NeoForgeVersion { get; init; }
```

Notes

```
public string Notes { get; init; }
```

PaperApiVersion

```
public string? PaperApiVersion { get; init; }
```

RequestedMinecraftVersion

```
public string RequestedMinecraftVersion { get; init; }
```

Source

```
public string Source { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out string?, out string?, out string?, out string?, out string?, out bool, out bool, out string, out string)

```
public void Deconstruct(out string Loader, out string RequestedMinecraftVersion, out string MatchedMinecraftVersion, out string JavaVersion, out string GradleVersion, out string? FabricLoaderVersion, out string? FabricApiVersion, out string? NeoForgeVersion, out string? PaperApiVersion, out string? DatapackPackFormat, out bool IsExactMatch, out bool NeedsVerification, out string Notes, out string Source)
```

Equals(MinecraftDependencyVersionInfo?)

```
public bool Equals(MinecraftDependencyVersionInfo? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(MinecraftDependencyVersionInfo?, MinecraftDependencyVersionInfo?)

```
public static bool operator ==(MinecraftDependencyVersionInfo? left, MinecraftDependencyVersionInfo? right)
```

operator !=(MinecraftDependencyVersionInfo?, MinecraftDependencyVersionInfo?)

```
public static bool operator !=(MinecraftDependencyVersionInfo? left, MinecraftDependencyVersionInfo? right)
```

Class MinecraftModBuildRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MinecraftModBuildRequest

```
public class MinecraftModBuildRequest
```

🌟 Constructors 1

MinecraftModBuildRequest()

```
public MinecraftModBuildRequest()
```

🐾 Properties 10

Description

```
public string Description { get; set; }
```

GradleVersion

```
public string GradleVersion { get; set; }
```

Ide

```
public string Ide { get; set; }
```

IncludeLivingCitiesStarter

```
public bool IncludeLivingCitiesStarter { get; set; }
```

JavaVersion

```
public string JavaVersion { get; set; }
```

Loader

```
public string Loader { get; set; }
```

MinecraftVersion

```
public string MinecraftVersion { get; set; }
```

ModId

```
public string ModId { get; set; }
```

PackageName

```
public string PackageName { get; set; }
```

ProjectName

```
public string ProjectName { get; set; }
```

Class MinecraftModWorkspace

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MinecraftModWorkspace

```
public class MinecraftModWorkspace
```

🌟 Constructors 1

MinecraftModWorkspace()

```
public MinecraftModWorkspace()
```

🐾 Properties 9

BuildCommand

```
public string BuildCommand { get; set; }
```

BuildFilePath

```
public string BuildFilePath { get; set; }
```

CreatedAt

```
public DateTimeOffset CreatedAt { get; set; }
```

EclipseImportHint

```
public string EclipseImportHint { get; set; }
```

MainClassPath

```
public string MainClassPath { get; set; }
```

MetadataPath

```
public string MetadataPath { get; set; }
```

ProjectName

```
public string ProjectName { get; set; }
```

ReadmePath

```
public string ReadmePath { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

Namespace LocalGPT.BusinessObjects.Models

Classes

Class PromptConfigDto

Namespace LocalGPT . BusinessObjects . Models Assembly LocalGPT.dll

Inheritance object PromptConfigDto

Implements IEquatable < PromptConfigDto >

```
public record PromptConfigDto : IEquatable<PromptConfigDto>
```

🌟 Constructors 2

PromptConfigDto(PromptConfigDto)

```
protected PromptConfigDto(PromptConfigDto original)
```

PromptConfigDto(string, string?, string)

```
public PromptConfigDto(string Key, string? Language, string Text)
```

🐾 Properties 4

EqualityContract

```
protected virtual Type EqualityContract { get; }
```

Key

```
public string Key { get; init; }
```

Language

```
public string? Language { get; init; }
```

Text

```
public string Text { get; init; }
```

⚙️ Methods 6

Deconstruct(out string, out string?, out string)

```
public void Deconstruct(out string Key, out string? Language, out string Text)
```

Equals(PromptConfigDto?)

```
public virtual bool Equals(PromptConfigDto? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

PrintMembers(StringBuilder)

```
protected virtual bool PrintMembers(StringBuilder builder)
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(PromptConfigDto?, PromptConfigDto?)

```
public static bool operator ==(PromptConfigDto? left, PromptConfigDto? right)
```

operator !=(PromptConfigDto?, PromptConfigDto?)

```
public static bool operator !=(PromptConfigDto? left, PromptConfigDto? right)
```

api/LocalGPT.BusinessObjects.Models.RegexPatternDto.html

Class RegexPatternDto

Namespace LocalGPT . BusinessObjects . Models Assembly LocalGPT.dll

Inheritance object RegexPatternDto

Implements IEquatable < RegexPatternDto >

```
public record RegexPatternDto : IEquatable<RegexPatternDto>
```

🌟 Constructors 2

RegexPatternDto(RegexPatternDto)

```
protected RegexPatternDto(RegexPatternDto original)
```

RegexPatternDto(string, string, string?)

```
public RegexPatternDto(string Name, string Pattern, string? Flags)
```

🔗 Properties 4

EqualityContract

```
protected virtual Type EqualityContract { get; }
```

Flags

```
public string? Flags { get; init; }
```

Name

```
public string Name { get; init; }
```

Pattern

```
public string Pattern { get; init; }
```

⚙️ Methods 6

Deconstruct(out string, out string, out string?)

```
public void Deconstruct(out string Name, out string Pattern, out string? Flags)
```

Equals(RegexPatternDto?)

```
public virtual bool Equals(RegexPatternDto? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

PrintMembers(StringBuilder)

```
protected virtual bool PrintMembers(StringBuilder builder)
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(RegexPatternDto?, RegexPatternDto?)

```
public static bool operator ==(RegexPatternDto? left, RegexPatternDto? right)
```

operator !=(RegexPatternDto?, RegexPatternDto?)

```
public static bool operator !=(RegexPatternDto? left, RegexPatternDto? right)
```

Class MsLoggingOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MsLoggingOptions

```
public class MsLoggingOptions
```

🌟 Constructors 1

MsLoggingOptions()

```
public MsLoggingOptions()
```

🐾 Properties 1

LogLevel

```
public Dictionary<string, string>? LogLevel { get; set; }
```


Class MultiModelCouncilModelCandidate

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MultiModelCouncilModelCandidate

Implements IEquatable < MultiModelCouncilModelCandidate >

```
public sealed record MultiModelCouncilModelCandidate : IEquatable<MultiModelCouncilModelCandidate>
```

🌟 Constructors 1

MultiModelCouncilModelCandidate(string, string, string, bool, bool, bool, string?, string, bool, bool)

```
public MultiModelCouncilModelCandidate(string ModelName, string Provider, string Endpoint, bool IsInstalled, bool IsConfigured, bool IsLoaded, string? Details, string ProviderKind = "ollama", bool IsLocal = true, bool SupportsBenchmark = true)
```

🐾 Properties 12

Details

```
public string? Details { get; init; }
```

DisplayName

```
public string DisplayName { get; }
```

Endpoint

```
public string Endpoint { get; init; }
```

IsConfigured

```
public bool IsConfigured { get; init; }
```

IsInstalled

```
public bool IsInstalled { get; init; }
```

IsLoaded

```
public bool IsLoaded { get; init; }
```

IsLocal

```
public bool IsLocal { get; init; }
```

ModelName

```
public string ModelName { get; init; }
```

Provider

```
public string Provider { get; init; }
```

ProviderKind

```
public string ProviderKind { get; init; }
```

SelectionKey

```
public string SelectionKey { get; }
```

SupportsBenchmark

```
public bool SupportsBenchmark { get; init; }
```

⚙️ Methods 6

Deconstruct(out string, out string, out string, out bool, out bool, out bool, out string?, out string, out bool, out bool)

```
public void Deconstruct(out string ModelName, out string Provider, out string Endpoint, out bool IsInstalled, out bool IsConfigured, out bool IsLoaded, out string? Details, out string ProviderKind, out bool IsLocal, out bool SupportsBenchmark)
```

Equals(MultiModelCouncilModelCandidate?)

```
public bool Equals(MultiModelCouncilModelCandidate? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToReference()

```
public ProviderModelReference ToReference()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(MultiModelCouncilModelCandidate?, MultiModelCouncilModelCandidate?)

```
public static bool operator ==(MultiModelCouncilModelCandidate? left, MultiModelCouncilModelCandidate? right)
```

operator !=(MultiModelCouncilModelCandidate?, MultiModelCouncilModelCandidate?)

```
public static bool operator !=(MultiModelCouncilModelCandidate? left, MultiModelCouncilModelCandidate? right)
```

Class MultiModelCouncilRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MultiModelCouncilRequest

```
public sealed class MultiModelCouncilRequest
```

🌟 Constructors 1

MultiModelCouncilRequest()

```
public MultiModelCouncilRequest()
```

🐾 Properties 36

AllowParallelHardwareRoads

```
public bool AllowParallelHardwareRoads { get; set; }
```

BaseUri

```
public string? BaseUri { get; set; }
```

ContinueConversationId

```
public Guid? ContinueConversationId { get; set; }
```

CouncilLeaderModelName

```
public string CouncilLeaderModelName { get; set; }
```

CouncilTeamKey

```
public string CouncilTeamKey { get; set; }
```

CreateProjectForRun

```
public bool CreateProjectForRun { get; set; }
```

ExternalProjectContextJson

```
public string ExternalProjectContextJson { get; set; }
```

GenerateImplementationArtifact

```
public bool GenerateImplementationArtifact { get; set; }
```

IncludeMemory

```
public bool IncludeMemory { get; set; }
```

MaxContextTokens

```
public int MaxContextTokens { get; set; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; set; }
```

MaxParallelModels

```
public int MaxParallelModels { get; set; }
```

MaxRounds

```
public int MaxRounds { get; set; }
```

ModelNames

```
public List<string> ModelNames { get; set; }
```

ModelRoutes

```
public List<OneWireCouncilModelRoute> ModelRoutes { get; set; }
```

ModelSelections

Provider-qualified model identities for this run. Bare ModelNames remain supported for legacy presets.

```
public List<ProviderModelReference> ModelSelections { get; set; }
```

ModelTimeoutSeconds

```
public int ModelTimeoutSeconds { get; set; }
```

OllamaKeepAlive

```
public string? OllamaKeepAlive { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

OneWireCorrelationId

```
public string OneWireCorrelationId { get; set; }
```

ProgressMessage

```
[JsonIgnore] public Action<string>? ProgressMessage { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectRevisionId

```
public Guid? ProjectRevisionId { get; set; }
```

ProjectTopicId

```
public Guid? ProjectTopicId { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

RequestedOrganicCapabilities

```
public List<string> RequestedOrganicCapabilities { get; set; }
```

ResourceLoadPercent

0..100 session position between each model route's independent minimum and maximum.

```
public int ResourceLoadPercent { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

SaveToMemory

```
public bool SaveToMemory { get; set; }
```

StepCompleted

```
[JsonIgnore] public Action<MultiModelCouncilStep>? StepCompleted { get; set; }
```

StreamUpdate

```
[JsonIgnore] public Action<string>? StreamUpdate { get; set; }
```

Title

```
public string? Title { get; set; }
```

UseChangeReviewWorkflow

```
public bool UseChangeReviewWorkflow { get; set; }
```

UseOrganicCouncilWorkflow

```
public bool UseOrganicCouncilWorkflow { get; set; }
```

UserConfirmedArtifactBuild

```
public bool UserConfirmedArtifactBuild { get; set; }
```

UserConfirmedProjectLink

```
public bool UserConfirmedProjectLink { get; set; }
```

Class MultiModelCouncilResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MultiModelCouncilResult

```
public sealed class MultiModelCouncilResult
```

🌟 Constructors 1

MultiModelCouncilResult()

```
public MultiModelCouncilResult()
```

🐾 Properties 23

Artifacts

```
public List<CouncilArtifact> Artifacts { get; set; }
```

ChangeReview

```
public CodeGenerationReviewSnapshot? ChangeReview { get; set; }
```

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

ContinuedFromConversationId

```
public Guid? ContinuedFromConversationId { get; set; }
```

ContinuedFromTitle

```
public string? ContinuedFromTitle { get; set; }
```

CouncilTeamKey

```
public string CouncilTeamKey { get; set; }
```

FinalAnswer

```
public string FinalAnswer { get; set; }
```

KnowledgeEntryId

```
public Guid? KnowledgeEntryId { get; set; }
```

LogPath

```
public string? LogPath { get; set; }
```

MemoryConversationId

```
public Guid? MemoryConversationId { get; set; }
```

ModelNames

```
public List<string> ModelNames { get; set; }
```

ModelSelections

```
public List<ProviderModelReference> ModelSelections { get; set; }
```

OneWireCorrelationId

```
public string OneWireCorrelationId { get; set; }
```

PreflightSummary

```
public string PreflightSummary { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectRevisionId

```
public Guid? ProjectRevisionId { get; set; }
```

ProjectTopicId

```
public Guid? ProjectTopicId { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

Steps

```
public List<MultiModelCouncilStep> Steps { get; set; }
```

UserPoll

```
public CouncilUserPoll? UserPoll { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class MultiModelCouncilStep

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object MultiModelCouncilStep

```
public sealed class MultiModelCouncilStep
```

🌟 Constructors 1

MultiModelCouncilStep()

```
public MultiModelCouncilStep()
```

🐾 Properties 24

BrainPart

```
[JsonIgnore] public string BrainPart { get; }
```

CompletedAtUtc

```
public DateTime CompletedAtUtc { get; set; }
```

Content

```
public string Content { get; set; }
```

CouncilMembers

```
public List<string> CouncilMembers { get; set; }
```

DurationSeconds

```
public double DurationSeconds { get; set; }
```

EffectiveLoadPercent

```
public int EffectiveLoadPercent { get; set; }
```

EffectiveMaxContextTokens

```
public int EffectiveMaxContextTokens { get; set; }
```

EffectiveMaxOutputTokens

```
public int EffectiveMaxOutputTokens { get; set; }
```

Error

```
public string? Error { get; set; }
```

HardwareIndex

```
public int HardwareIndex { get; set; }
```

HardwareKind

```
public OneWireHardwareKind HardwareKind { get; set; }
```

HardwareLane

```
public string HardwareLane { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

Moment

```
[JsonIgnore] public string Moment { get; }
```

Phase

```
public string Phase { get; set; }
```

ProviderEndpoint

```
public string ProviderEndpoint { get; set; }
```

ProviderModelName

```
public string ProviderModelName { get; set; }
```

ProviderName

```
public string ProviderName { get; set; }
```

Role

```
public string Role { get; set; }
```

Round

```
public int Round { get; set; }
```

SortOrder

```
public int SortOrder { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

Thinking

```
public string? Thinking { get; set; }
```

VisibleContent

```
public string VisibleContent { get; set; }
```


Class NativeCommandLogEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object NativeCommandLogEntry

```
public class NativeCommandLogEntry
```

🌟 Constructors 1

NativeCommandLogEntry()

```
public NativeCommandLogEntry()
```

🐾 Properties 15

Arguments

```
public string Arguments { get; set; }
```

CommandProfile

```
public string CommandProfile { get; set; }
```

CompletedAtUtc

```
public DateTime CompletedAtUtc { get; set; }
```

DurationMilliseconds

```
public double DurationMilliseconds { get; set; }
```

Executable

```
public string Executable { get; set; }
```

ExitCode

```
public int ExitCode { get; set; }
```

FeatureName

```
public string FeatureName { get; set; }
```

Id

```
public long Id { get; set; }
```

PolicyDecision

```
public string PolicyDecision { get; set; }
```

PolicyReason

```
public string PolicyReason { get; set; }
```

RequestedBy

```
public string RequestedBy { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

StderrPath

```
public string StderrPath { get; set; }
```

StdoutPath

```
public string StdoutPath { get; set; }
```

WorkingDirectory

```
public string WorkingDirectory { get; set; }
```

Class NativeCommandOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object NativeCommandOptions

```
public sealed class NativeCommandOptions
```

🌟 Constructors 1

NativeCommandOptions()

```
public NativeCommandOptions()
```

🔴 Fields 1

SectionName

```
public const string SectionName = "NativeCommands"
```

🐾 Properties 3

AllowPowerShellWorkspaceScripts

```
public bool AllowPowerShellWorkspaceScripts { get; set; }
```

Enabled

```
public bool Enabled { get; set; }
```

MaxDurationSeconds

```
public int MaxDurationSeconds { get; set; }
```

Class OllamaBenchmarkGenerateRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaBenchmarkGenerateRequest

```
public sealed class OllamaBenchmarkGenerateRequest
```

🌟 Constructors 1

OllamaBenchmarkGenerateRequest()

```
public OllamaBenchmarkGenerateRequest()
```

🐾 Properties 5

KeepAlive

```
[JsonPropertyName("keep_alive")] public string KeepAlive { get; set; }
```

Model

```
[JsonPropertyName("model")] public string Model { get; set; }
```

Options

```
[JsonPropertyName("options")] public Dictionary<string, object?> Options { get; set; }
```

Prompt

```
[JsonPropertyName("prompt")] public string Prompt { get; set; }
```

Stream

```
[JsonPropertyName("stream")] public bool Stream { get; set; }
```

Class OllamaBenchmarkGenerateResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaBenchmarkGenerateResponse

```
public sealed class OllamaBenchmarkGenerateResponse
```

🌟 Constructors 1

OllamaBenchmarkGenerateResponse()

```
public OllamaBenchmarkGenerateResponse()
```

🐾 Properties 8

Done

```
[JsonPropertyName("done")] public bool Done { get; set; }
```

EvaluationCount

```
[JsonPropertyName("eval_count")] public int EvaluationCount { get; set; }
```

EvaluationDurationNanoseconds

```
[JsonPropertyName("eval_duration")] public long EvaluationDurationNanoseconds { get; set; }
```

LoadDurationNanoseconds

```
[JsonPropertyName("load_duration")] public long LoadDurationNanoseconds { get; set; }
```

PromptEvaluationCount

```
[JsonPropertyName("prompt_eval_count")] public int PromptEvaluationCount { get; set; }
```

PromptEvaluationDurationNanoseconds

```
[JsonPropertyName("prompt_eval_duration")] public long PromptEvaluationDurationNanoseconds { get; set; }
```

Response

```
[JsonPropertyName("response")] public string Response { get; set; }
```

TotalDurationNanoseconds

```
[JsonPropertyName("total_duration")] public long TotalDurationNanoseconds { get; set; }
```

Class OllamaBenchmarkModelDetails

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaBenchmarkModelDetails

```
public sealed class OllamaBenchmarkModelDetails
```

🌟 Constructors 1

OllamaBenchmarkModelDetails()

```
public OllamaBenchmarkModelDetails()
```

🐾 Properties 2

ParameterSize

```
[JsonPropertyName("parameter_size")] public string ParameterSize { get; set; }
```

QuantizationLevel

```
[JsonPropertyName("quantization_level")] public string QuantizationLevel { get; set; }
```

Class OllamaBenchmarkModelInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaBenchmarkModelInfo

```
public sealed class OllamaBenchmarkModelInfo
```

🌟 Constructors 1

OllamaBenchmarkModelInfo()

```
public OllamaBenchmarkModelInfo()
```

🐾 Properties 4

Details

```
[JsonPropertyName("details")] public OllamaBenchmarkModelDetails Details { get; set; }
```

Model

```
[JsonPropertyName("model")] public string Model { get; set; }
```

Name

```
[JsonPropertyName("name")] public string Name { get; set; }
```

Size

```
[JsonPropertyName("size")] public long Size { get; set; }
```

Class OllamaBenchmarkTagsResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaBenchmarkTagsResponse

```
public sealed class OllamaBenchmarkTagsResponse
```

🌟 Constructors 1

OllamaBenchmarkTagsResponse()

```
public OllamaBenchmarkTagsResponse()
```

🐾 Properties 1

Models

```
[JsonPropertyName("models")] public List<OllamaBenchmarkModelInfo> Models { get; set; }
```

Class OllamaChatMessage

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaChatMessage

```
public sealed class OllamaChatMessage
```

🌟 Constructors 1

OllamaChatMessage()

```
public OllamaChatMessage()
```

🐾 Properties 6

Content

```
public string Content { get; set; }
```

Images

```
[JsonPropertyName("images")] public List<string>? Images { get; set; }
```

Role

```
public string Role { get; set; }
```

Thinking

```
public string? Thinking { get; set; }
```

ToolCalls

```
[JsonPropertyName("tool_calls")] public List<OllamaToolCall>? ToolCalls { get; set; }
```

ToolName

```
[JsonPropertyName("tool_name")] public string? ToolName { get; set; }
```

Class OllamaChatRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaChatRequest

```
public sealed class OllamaChatRequest
```

🌟 Constructors 1

OllamaChatRequest()

```
public OllamaChatRequest()
```

🐾 Properties 6

KeepAlive

```
public string KeepAlive { get; set; }
```

Messages

```
public List<OllamaChatMessage> Messages { get; set; }
```

Model

```
public string Model { get; set; }
```

Options

```
public OllamaRequestOptions? Options { get; set; }
```

Stream

```
public bool Stream { get; set; }
```

Tools

```
public List<OllamaToolDefinition>? Tools { get; set; }
```

Class OllamaChatResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaChatResponse

```
public sealed class OllamaChatResponse
```

🌟 Constructors 1

OllamaChatResponse()

```
public OllamaChatResponse()
```

🐾 Properties 1

Message

```
public OllamaChatMessage? Message { get; set; }
```

Class OllamaCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaCoreOptions

```
public class OllamaCoreOptions
```

🌟 Constructors 1

OllamaCoreOptions()

```
public OllamaCoreOptions()
```

🔴 Fields 1

OllamaCore

```
public const string OllamaCore = "OllamaCore"
```

🐾 Properties 3

ModelName

```
public string ModelName { get; set; }
```

ResponseProtocol

```
public ChatResponseProtocol ResponseProtocol { get; set; }
```

Uri

```
public string Uri { get; set; }
```

Class OllamaModelDetails

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaModelDetails

```
public sealed class OllamaModelDetails
```

🌟 Constructors 1

OllamaModelDetails()

```
public OllamaModelDetails()
```

🐾 Properties 3

Family

```
public string? Family { get; set; }
```

ParameterSize

```
[JsonPropertyName("parameter_size")] public string? ParameterSize { get; set; }
```

QuantizationLevel

```
[JsonPropertyName("quantization_level")] public string? QuantizationLevel { get; set; }
```

Class OllamaModelEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object OllamaModelEntry

```
public sealed class OllamaModelEntry
```

🌟 Constructors 1

OllamaModelEntry()

```
public OllamaModelEntry()
```

🐾 Properties 3

Details

```
public OllamaModelDetails? Details { get; set; }
```

Model

```
public string? Model { get; set; }
```

Name

```
public string? Name { get; set; }
```

Class OllamaModelResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object OllamaModelResponse

```
public sealed class OllamaModelResponse
```

🌟 Constructors 1

OllamaModelResponse()

```
public OllamaModelResponse()
```

🐾 Properties 3

Details

```
public OllamaModelDetails? Details { get; set; }
```

Model

```
public string Model { get; set; }
```

Name

```
public string Name { get; set; }
```


Class OllamaProcessInfo

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaProcessInfo

Implements IEquatable < OllamaProcessInfo >

```
public sealed record OllamaProcessInfo : IEquatable<OllamaProcessInfo>
```

🌟 Constructors 1

OllamaProcessInfo(int, string, string?)

```
public OllamaProcessInfo(int ProcessId, string ProcessName, string? ExecutablePath)
```

🐾 Properties 3

ExecutablePath

```
public string? ExecutablePath { get; init; }
```

ProcessId

```
public int ProcessId { get; init; }
```

ProcessName

```
public string ProcessName { get; init; }
```

⚙️ Methods 5

Deconstruct(out int, out string, out string?)

```
public void Deconstruct(out int ProcessId, out string ProcessName, out string? ExecutablePath)
```

Equals(OllamaProcessInfo?)

```
public bool Equals(OllamaProcessInfo? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(OllamaProcessInfo?, OllamaProcessInfo?)

```
public static bool operator ==(OllamaProcessInfo? left, OllamaProcessInfo? right)
```

operator !=(OllamaProcessInfo?, OllamaProcessInfo?)

```
public static bool operator !=(OllamaProcessInfo? left, OllamaProcessInfo? right)
```

Class OllamaProcessStatus

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaProcessStatus

Implements IEquatable < OllamaProcessStatus >

```
public sealed record OllamaProcessStatus : IEquatable<OllamaProcessStatus>
```

🌟 Constructors 1

OllamaProcessStatus(bool, bool, string?, IReadOnlyList<OllamaProcessInfo>, string, string)

```
public OllamaProcessStatus(bool IsInstalled, bool IsRunning, string? ExecutablePath, IReadOnlyList<OllamaProcessInfo> Processes, string ProcessSummary, string Message)
```

🐾 Properties 6

ExecutablePath

```
public string? ExecutablePath { get; init; }
```

IsInstalled

```
public bool IsInstalled { get; init; }
```

IsRunning

```
public bool IsRunning { get; init; }
```

Message

```
public string Message { get; init; }
```

ProcessSummary

```
public string ProcessSummary { get; init; }
```

Processes

```
public IReadOnlyList<OllamaProcessInfo> Processes { get; init; }
```

⚙️ Methods 5

Deconstruct(out bool, out bool, out string?, out IReadOnlyList<OllamaProcessInfo>, out string, out string)

```
public void Deconstruct(out bool IsInstalled, out bool IsRunning, out string? ExecutablePath, out IReadOnlyList<OllamaProcessInfo> Processes, out string ProcessSummary, out string Message)
```

Equals(OllamaProcessStatus?)

```
public bool Equals(OllamaProcessStatus? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(OllamaProcessStatus?, OllamaProcessStatus?)

```
public static bool operator ==(OllamaProcessStatus? left, OllamaProcessStatus? right)
```

operator !=(OllamaProcessStatus?, OllamaProcessStatus?)

```
public static bool operator !=(OllamaProcessStatus? left, OllamaProcessStatus? right)
```

Class OllamaRequestOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaRequestOptions

```
public sealed class OllamaRequestOptions
```

🌟 Constructors 1

OllamaRequestOptions()

```
public OllamaRequestOptions()
```

🐾 Properties 4

NumCtx

```
[JsonPropertyName("num_ctx")] public int? NumCtx { get; set; }
```

NumGpu

```
[JsonPropertyName("num_gpu")] public int? NumGpu { get; set; }
```

NumPredict

```
[JsonPropertyName("num_predict")] public int NumPredict { get; set; }
```

Temperature

```
[JsonPropertyName("temperature")] public double? Temperature { get; set; }
```

Class OllamaTagsResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaTagsResponse

```
public sealed class OllamaTagsResponse
```

🌟 Constructors 1

OllamaTagsResponse()

```
public OllamaTagsResponse()
```

🐾 Properties 1

Models

```
public List<OllamaModelEntry> Models { get; set; }
```

Class OllamaToolCall

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaToolCall

```
public sealed class OllamaToolCall
```

🌟 Constructors 1

OllamaToolCall()

```
public OllamaToolCall()
```

🐾 Properties 1

Function

```
public OllamaToolFunctionCall Function { get; set; }
```

Class OllamaToolDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaToolDefinition

```
public sealed class OllamaToolDefinition
```

🌟 Constructors 1

OllamaToolDefinition()

```
public OllamaToolDefinition()
```

🐾 Properties 2

Function

```
public OllamaToolFunctionDefinition Function { get; set; }
```

Type

```
public string Type { get; set; }
```

Class OllamaToolFunctionCall

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaToolFunctionCall

```
public sealed class OllamaToolFunctionCall
```

🌟 Constructors 1

OllamaToolFunctionCall()

```
public OllamaToolFunctionCall()
```

🐾 Properties 2

Arguments

```
public JsonElement Arguments { get; set; }
```

Name

```
public string Name { get; set; }
```

Class OllamaToolFunctionDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaToolFunctionDefinition

```
public sealed class OllamaToolFunctionDefinition
```

🌟 Constructors 1

OllamaToolFunctionDefinition()

```
public OllamaToolFunctionDefinition()
```

🐾 Properties 3

Description

```
public string Description { get; set; }
```

Name

```
public string Name { get; set; }
```

Parameters

```
public JsonElement Parameters { get; set; }
```

Class OllamaUnloadRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OllamaUnloadRequest

```
public sealed class OllamaUnloadRequest
```

🌟 Constructors 1

OllamaUnloadRequest()

```
public OllamaUnloadRequest()
```

🐾 Properties 4

KeepAlive

```
[JsonPropertyName("keep_alive")] public string KeepAlive { get; set; }
```

Model

```
public string Model { get; set; }
```

Prompt

```
public string Prompt { get; set; }
```

Stream

```
public bool Stream { get; set; }
```

Class OnboardingInstallerProfile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes one installer profile that can prepare models or repository knowledge for a LocalGPT workstation.

Inheritance object OnboardingInstallerProfile

Implements IEquatable < OnboardingInstallerProfile >

```
[DocumentationUpdated("2.1.20")] public sealed record OnboardingInstallerProfile : IEquatable<OnboardingInstallerProfile>
```

🌟 Constructors 1

OnboardingInstallerProfile(string, string, string, string, IReadOnlyList<string>, IReadOnlyList<string>)

Describes one installer profile that can prepare models or repository knowledge for a LocalGPT workstation.

```
public OnboardingInstallerProfile(string Key, string DisplayName, string Purpose, string Command, IReadOnlyList<string> Models, IReadOnlyList<string> Repositories)
```

🐾 Properties 8

Command

Reviewable installer command that the user can run explicitly.

```
public string Command { get; init; }
```

DisplayName

Human-readable profile name.

```
public string DisplayName { get; init; }
```

Key

Stable profile key used by UI and API clients.

```
public string Key { get; init; }
```

ModelSummary

Gets the comma-separated recommended model labels for display.

```
public string ModelSummary { get; }
```

Models

Recommended Ollama model tags for the profile.

```
public IReadOnlyList<string> Models { get; init; }
```

Purpose

Short explanation of the profile's intended workload.

```
public string Purpose { get; init; }
```

Repositories

Recommended GitHub repositories for the profile's learning base.

```
public IReadOnlyList<string> Repositories { get; init; }
```

RepositorySummary

Gets the comma-separated recommended repository labels for display.

```
public string RepositorySummary { get; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out IReadOnlyList<string>, out IReadOnlyList<string>)

```
public void Deconstruct(out string Key, out string DisplayName, out string Purpose, out string Command, out IReadOnlyList<string> Models, out IReadOnlyList<string> Repositories)
```

Equals(OnboardingInstallerProfile?)

```
public bool Equals(OnboardingInstallerProfile? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(OnboardingInstallerProfile?, OnboardingInstallerProfile?)

```
public static bool operator ==(OnboardingInstallerProfile? left, OnboardingInstallerProfile? right)
```

operator !=(OnboardingInstallerProfile?, OnboardingInstallerProfile?)

```
public static bool operator !=(OnboardingInstallerProfile? left, OnboardingInstallerProfile? right)
```

api/LocalGPT.BusinessObjects.OneWireDispatchContext.html

Class OneWireDispatchContext

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OneWireDispatchContext

```
public sealed class OneWireDispatchContext
```

🌟 Constructors 1

OneWireDispatchContext()

```
public OneWireDispatchContext()
```

🐾 Properties 5

AuthenticatedPeerId

```
public string AuthenticatedPeerId { get; init; }
```

ConnectionId

```
public Guid ConnectionId { get; init; }
```

IsInternal

```
public bool IsInternal { get; init; }
```

IsLoopback

```
public bool IsLoopback { get; init; }
```

Transport

```
public string Transport { get; init; }
```

Class OneWireOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OneWireOptions

```
public sealed class OneWireOptions
```

🌟 Constructors 1

OneWireOptions()

```
public OneWireOptions()
```

🔴 Fields 1

SectionName

```
public const string SectionName = "OneWire"
```

🐾 Properties 10

BroadcastAddress

```
public string BroadcastAddress { get; set; }
```

BroadcastIntervalSeconds

```
public int BroadcastIntervalSeconds { get; set; }
```

DiscoveryPort

```
public int DiscoveryPort { get; set; }
```

EnableDiscovery

```
public bool EnableDiscovery { get; set; }
```

EnableLanTransport

```
public bool EnableLanTransport { get; set; }
```

Enabled

```
public bool Enabled { get; set; }
```

ListenAddress

```
public string ListenAddress { get; set; }
```

MaximumMessageBytes

```
public int MaximumMessageBytes { get; set; }
```

PeerExpirySeconds

```
public int PeerExpirySeconds { get; set; }
```

ServicePort

```
public int ServicePort { get; set; }
```


Class OneWirePendingCouncilRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OneWirePendingCouncilRequest

```
public sealed class OneWirePendingCouncilRequest
```

🌟 Constructors 1

OneWirePendingCouncilRequest()

```
public OneWirePendingCouncilRequest()
```

🐾 Properties 4

ApprovalRequestId

```
public Guid? ApprovalRequestId { get; set; }
```

Envelope

```
public OneWireEnvelope Envelope { get; set; }
```

LastCheckedUtc

```
public DateTimeOffset LastCheckedUtc { get; set; }
```

QueuedUtc

```
public DateTimeOffset QueuedUtc { get; set; }
```

Class OneWireReplayPolicySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OneWireReplayPolicySnapshot

```
public sealed class OneWireReplayPolicySnapshot
```

🌟 Constructors 1

OneWireReplayPolicySnapshot()

```
public OneWireReplayPolicySnapshot()
```

🐾 Properties 4

AllowedFutureSkew

```
public TimeSpan AllowedFutureSkew { get; init; }
```

CleanupInterval

```
public int CleanupInterval { get; init; }
```

MaximumTrackedMessages

```
public int MaximumTrackedMessages { get; init; }
```

Retention

```
public TimeSpan Retention { get; init; }
```

Class OneWireWorkItem

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Local runtime state for a protocol work item. Transfer contracts live in LocalGPT.WireProtocolVersion.

Inheritance object OneWireWorkItem

```
public sealed class OneWireWorkItem
```

✨ Constructors 1

OneWireWorkItem()

```
public OneWireWorkItem()
```

🐾 Properties 13

CapabilityKey

```
public string CapabilityKey { get; set; }
```

CorrelationId

```
public Guid CorrelationId { get; set; }
```

CreatedUtc

```
public DateTimeOffset CreatedUtc { get; set; }
```

Error

```
public string Error { get; set; }
```

ExecutionMode

```
public OneWireExecutionMode ExecutionMode { get; set; }
```

Id

```
public Guid Id { get; set; }
```

NotBeforeUtc

```
public DateTimeOffset? NotBeforeUtc { get; set; }
```

Request

```
public OneWireEnvelope Request { get; set; }
```

RequestType

```
public OneWireMessageType RequestType { get; set; }
```

ResultJson

```
public string ResultJson { get; set; }
```

SourcePeerId

```
public string SourcePeerId { get; set; }
```

Status

```
public OneWireWorkStatus Status { get; set; }
```

UpdatedUtc

```
public DateTimeOffset UpdatedUtc { get; set; }
```

Class OpenAICompatOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OpenAICompatOptions

```
public class OpenAICompatOptions
```

🌟 Constructors 1

OpenAICompatOptions()

```
public OpenAICompatOptions()
```

🔴 Fields 1

OpenAICore

```
public const string OpenAICore = "OpenAICore"
```

🐾 Properties 3

ApiKey

```
public string ApiKey { get; set; }
```

Endpoint

```
public string Endpoint { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

Class OpenAIModelEntry

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OpenAIModelEntry

```
public sealed class OpenAIModelEntry
```

🌟 Constructors 1

OpenAIModelEntry()

```
public OpenAIModelEntry()
```

🐾 Properties 1

Id

```
public string Id { get; set; }
```

Class OpenAIModelsResponse

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OpenAIModelsResponse

```
public sealed class OpenAIModelsResponse
```

🌟 Constructors 1

OpenAIModelsResponse()

```
public OpenAIModelsResponse()
```

🐾 Properties 1

Data

```
public List<OpenAIModelEntry> Data { get; set; }
```

Class OpenAIServiceCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OpenAIServiceCoreOptions

```
public class OpenAIServiceCoreOptions
```

🌟 Constructors 1

OpenAIServiceCoreOptions()

```
public OpenAIServiceCoreOptions()
```

🌀 Fields 1

OpenAIServiceCore

```
public const string OpenAIServiceCore = "OpenAIServiceCore"
```

🐾 Properties 3

DeploymentName

```
public string DeploymentName { get; set; }
```

Endpoint

```
public string Endpoint { get; set; }
```

Key

```
public string Key { get; set; }
```

Class OrganicAddonControllerMethodManifest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OrganicAddonControllerMethodManifest

```
public sealed class OrganicAddonControllerMethodManifest
```

🌟 Constructors 1

OrganicAddonControllerMethodManifest()

```
public OrganicAddonControllerMethodManifest()
```

🐾 Properties 6

Controller

```
public string Controller { get; set; }
```

HttpMethod

```
public string HttpMethod { get; set; }
```

IsReadOnly

```
public bool IsReadOnly { get; set; }
```

MethodName

```
public string MethodName { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

Route

```
public string Route { get; set; }
```

Class OrganicAddonManifest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Offline, source-controlled description of an organic add-on. The manifest makes an add-on's controller surface discoverable while its process is offline; invocation still requires a live, trusted 1-Wire peer and the existing user-controlled catalog policy.

Inheritance object OrganicAddonManifest

```
public sealed class OrganicAddonManifest
```

🌟 Constructors 1

OrganicAddonManifest()

```
public OrganicAddonManifest()
```

🐾 Properties 8

CapabilityKeys

```
public List<string> CapabilityKeys { get; set; }
```

ControllerMethods

```
public List<OrganicAddonControllerMethodManifest> ControllerMethods { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

Key

```
public string Key { get; set; }
```

Organs

```
public List<string> Organs { get; set; }
```

SourcePeerId

```
public string SourcePeerId { get; set; }
```

UiActivationKeys

```
public List<string> UiActivationKeys { get; set; }
```

Class OrganicCouncilRoleDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines one role and its AI, human, language, runtime-class and pairing policies.

Inheritance object OrganicCouncilRoleDefinition

```
[DocumentationUpdated("2.1.20")] public sealed class OrganicCouncilRoleDefinition
```

✨ Constructors 1

OrganicCouncilRoleDefinition()

```
public OrganicCouncilRoleDefinition()
```

🐾 Properties 14

AISelectionMode

Gets or sets how AI participants are selected for the role.

```
public CouncilRoleAiSelectionMode AiSelectionMode { get; set; }
```

BoundaryMode

Gets or sets the role-boundary strictness.

```
public CouncilRoleBoundaryMode BoundaryMode { get; set; }
```

DistinctAiAssignmentGroup

Gets or sets the assignment group that requires distinct model identities.

```
public string DistinctAiAssignmentGroup { get; set; }
```

Expertise

Gets or sets the expertise expected from participants assigned to the role.

```
public string Expertise { get; set; }
```

HumanParticipationMode

Gets or sets the human participation policy.

```
public HumanParticipationMode HumanParticipationMode { get; set; }
```

LanguageMode

Gets or sets the role language policy.

```
public CouncilRoleLanguageMode LanguageMode { get; set; }
```

MatchAiParticipantCountToRole

Gets or sets another role whose participant count this role mirrors.

```
public string MatchAiParticipantCountToRole { get; set; }
```

MaximumAiParticipants

Gets or sets the maximum AI participant count.

```
public int MaximumAiParticipants { get; set; }
```

MinimumAiParticipants

Gets or sets the minimum AI participant count.

```
public int MinimumAiParticipants { get; set; }
```

PairedRole

Gets or sets the role paired one-to-one with this role.

```
public string PairedRole { get; set; }
```

PerformanceMode

Gets or sets the task-specialist or improvisation behavior.

```
public CouncilRolePerformanceMode PerformanceMode { get; set; }
```

Responsibility

Gets or sets the responsibility and ownership boundary of the role.

```
public string Responsibility { get; set; }
```

Role

Gets or sets the unique role name within the team.

```
public string Role { get; set; }
```

RuntimeClassKeys

Gets or sets runtime-class keys exposed to participants in this role.

```
public List<string> RuntimeClassKeys { get; set; }
```


Class OrganicCouncilTeamDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Defines one editable LocalGPT Council team, its roles, workflow and architecture contracts.

Inheritance object OrganicCouncilTeamDefinition

```
[DocumentationUpdated("2.1.20")] public sealed class OrganicCouncilTeamDefinition
```

✨ Constructors 1

OrganicCouncilTeamDefinition()

```
public OrganicCouncilTeamDefinition()
```

🐾 Properties 13

ArchitectureContracts

Gets or sets architecture and safety contracts that every round must preserve.

```
public List<string> ArchitectureContracts { get; set; }
```

DisplayName

Gets or sets the human-readable team name.

```
public string DisplayName { get; set; }
```

ExpertPreparationPromptTemplate

Gets or sets the expert-preparation prompt used by the built-in workflow.

```
public string ExpertPreparationPromptTemplate { get; set; }
```

IsEnabled

Gets or sets whether the team may be selected for new runs.

```
public bool IsEnabled { get; set; }
```

IsSystemSeed

Gets or sets whether the row originated from maintained seed data.

```
public bool IsSystemSeed { get; set; }
```

IsUserModified

Gets or sets whether a user edited the seed-owned row.

```
public bool IsUserModified { get; set; }
```

Key

Gets or sets the stable lowercase team key.

```
public string Key { get; set; }
```

LeaderSynthesisPromptTemplate

Gets or sets the leader-synthesis prompt used by the built-in workflow.

```
public string LeaderSynthesisPromptTemplate { get; set; }
```

MainRoundInstructionTemplate

Gets or sets the common main-round instruction.

```
public string MainRoundInstructionTemplate { get; set; }
```

PreferredCapabilities

Gets or sets preferred registered DXFunction and organic capability keys.

```
public List<string> PreferredCapabilities { get; set; }
```

Purpose

Gets or sets the bounded purpose of the team.

```
public string Purpose { get; set; }
```

Roles

Gets or sets the role definitions used by the team.

```
public List<OrganicCouncilRoleDefinition> Roles { get; set; }
```

WorkflowSteps

Gets or sets the literal ordered Council workflow.

```
public List<CouncilWorkflowStepDefinition> WorkflowSteps { get; set; }
```

Class OrganicSkillDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object OrganicSkillDefinition

```
public sealed class OrganicSkillDefinition
```

🌟 Constructors 1

OrganicSkillDefinition()

```
public OrganicSkillDefinition()
```

🐾 Properties 15

CapabilityKeysJson

```
[Column(TypeName = "TEXT")] public string CapabilityKeysJson { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

Description

```
[MaxLength(2000)] public string Description { get; set; }
```

DisplayName

```
[Required] [MaxLength(240)] public string DisplayName { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsOnline

```
public bool IsOnline { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

Key

```
[Required] [MaxLength(200)] public string Key { get; set; }
```

MemberLinks

```
public ICollection<CouncilMemberOrganicSkillLink> MemberLinks { get; set; }
```

OrgansJson

```
[Column(TypeName = "TEXT")] public string OrgansJson { get; set; }
```

ProjectLinks

```
public ICollection<ProjectOrganicSkillLink> ProjectLinks { get; set; }
```

SourcePeerId

```
[MaxLength(240)] public string SourcePeerId { get; set; }
```

UiActivationKeysJson

```
[Column(TypeName = "TEXT")] public string UiActivationKeysJson { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class ProjectArchitectureGetParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectArchitectureGetParameters

```
public sealed class ProjectArchitectureGetParameters
```

🌟 Constructors 1

ProjectArchitectureGetParameters()

```
public ProjectArchitectureGetParameters()
```

🐾 Properties 1

ProjectId

```
public Guid ProjectId { get; set; }
```

Class ProjectArtifactSaveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectArtifactSaveParameters

```
public sealed class ProjectArtifactSaveParameters
```

🌟 Constructors 1

ProjectArtifactSaveParameters()

```
public ProjectArtifactSaveParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public SaveProjectArtifactRequest Request { get; set; }
```

Class ProjectBuildVerification

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectBuildVerification

```
public sealed class ProjectBuildVerification
```

🌟 Constructors 1

ProjectBuildVerification()

```
public ProjectBuildVerification()
```

🐾 Properties 29

Arguments

```
[Column(TypeName = "TEXT")] public string Arguments { get; set; }
```

BuildSucceeded

```
public bool BuildSucceeded { get; set; }
```

CompilerInstallation

```
public ProjectCompilerInstallation? CompilerInstallation { get; set; }
```

CompilerInstallationId

```
public Guid? CompilerInstallationId { get; set; }
```

CompletedAtUtc

```
public DateTime? CompletedAtUtc { get; set; }
```

Configuration

```
[MaxLength(80)] public string Configuration { get; set; }
```

CouncilReviewSucceeded

```
public bool CouncilReviewSucceeded { get; set; }
```

CouncilReviewSummary

```
[Column(TypeName = "TEXT")] public string CouncilReviewSummary { get; set; }
```

EvidenceManifestPath

```
[MaxLength(2048)] public string EvidenceManifestPath { get; set; }
```

ExecutablePath

```
[Required] [MaxLength(2048)] public string ExecutablePath { get; set; }
```

ExitCode

```
public int? ExitCode { get; set; }
```

Id

```
public Guid Id { get; set; }
```

OutputHash

```
[MaxLength(128)] public string OutputHash { get; set; }
```

OutputLogPath

```
[MaxLength(2048)] public string OutputLogPath { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Revision

```
public LocalGptProjectRevision? Revision { get; set; }
```

RevisionId

```
public Guid RevisionId { get; set; }
```

RuntimeIdentifier

```
[MaxLength(80)] public string RuntimeIdentifier { get; set; }
```

SnapshotArchivePath

```
[MaxLength(2048)] public string SnapshotArchivePath { get; set; }
```

SourceChangedDuringVerification

```
public bool SourceChangedDuringVerification { get; set; }
```

SourceSnapshotHash

```
[MaxLength(128)] public string SourceSnapshotHash { get; set; }
```

StartedAtUtc

```
public DateTime StartedAtUtc { get; set; }
```

Summary

```
[Column(TypeName = "TEXT")] public string Summary { get; set; }
```

TargetFramework

```
[MaxLength(160)] public string TargetFramework { get; set; }
```

TestsExecuted

```
public bool TestsExecuted { get; set; }
```

TestsSucceeded

```
public bool TestsSucceeded { get; set; }
```

UserApprovedReadyForTest

```
public bool UserApprovedReadyForTest { get; set; }
```

WorkingDirectory

```
[Required] [MaxLength(2048)] public string WorkingDirectory { get; set; }
```

Class ProjectCompilerInstallation

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectCompilerInstallation

```
public sealed class ProjectCompilerInstallation
```

🌟 Constructors 1

ProjectCompilerInstallation()

```
public ProjectCompilerInstallation()
```

🐾 Properties 17

Architecture

```
[MaxLength(80)] public string Architecture { get; set; }
```

CompilerHomePath

```
[MaxLength(2048)] public string CompilerHomePath { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

DiscoverySource

```
[MaxLength(80)] public string DiscoverySource { get; set; }
```

EnvironmentVariablesJson

```
[Column(TypeName = "TEXT")] public string EnvironmentVariablesJson { get; set; }
```

ExecutablePath

```
[Required] [MaxLength(2048)] public string ExecutablePath { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsDefaultForLanguage

```
public bool IsDefaultForLanguage { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

Language

```
[Required] [MaxLength(80)] public string Language { get; set; }
```

LastValidatedAtUtc

```
public DateTime? LastValidatedAtUtc { get; set; }
```

LastValidationMessage

```
[MaxLength(4000)] public string LastValidationMessage { get; set; }
```

LastValidationSucceeded

```
public bool LastValidationSucceeded { get; set; }
```

Name

```
[Required] [MaxLength(200)] public string Name { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

ValidationArguments

```
[MaxLength(500)] public string ValidationArguments { get; set; }
```

Version

```
[MaxLength(160)] public string Version { get; set; }
```

api/LocalGPT.BusinessObjects.ProjectCouncilBuildReviewRecordParameters.html

Class ProjectCouncilBuildReviewRecordParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectCouncilBuildReviewRecordParameters

```
public sealed class ProjectCouncilBuildReviewRecordParameters
```

🌟 Constructors 1

ProjectCouncilBuildReviewRecordParameters()

```
public ProjectCouncilBuildReviewRecordParameters()
```

🐾 Properties 2

Request

```
public RecordCouncilBuildReviewRequest Request { get; set; }
```

VerificationId

```
public Guid VerificationId { get; set; }
```


Class ProjectDocumentImport

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectDocumentImport

```
public sealed class ProjectDocumentImport
```

🌟 Constructors 1

ProjectDocumentImport()

```
public ProjectDocumentImport()
```

🐾 Properties 15

ContentHash

```
[Required] [MaxLength(128)] public string ContentHash { get; set; }
```

ContentType

```
[MaxLength(120)] public string ContentType { get; set; }
```

EncodingName

```
[MaxLength(80)] public string EncodingName { get; set; }
```

ExtractedText

```
[Column(TypeName = "TEXT")] public string ExtractedText { get; set; }
```

Id

```
public Guid Id { get; set; }
```

ImportedAtUtc

```
public DateTime ImportedAtUtc { get; set; }
```

IsUserApproved

```
public bool IsUserApproved { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Revision

```
public LocalGptProjectRevision? Revision { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

SafetyNotes

```
[MaxLength(2000)] public string SafetyNotes { get; set; }
```

SourceName

```
[Required] [MaxLength(260)] public string SourceName { get; set; }
```

SourceUri

```
[MaxLength(2048)] public string SourceUri { get; set; }
```

Status

```
[MaxLength(80)] public string Status { get; set; }
```

Class ProjectFilePatternsSaveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectFilePatternsSaveParameters

```
public sealed class ProjectFilePatternsSaveParameters
```

🌟 Constructors 1

ProjectFilePatternsSaveParameters()

```
public ProjectFilePatternsSaveParameters()
```

🐾 Properties 2

Request

```
public SaveTrackedFilePatternRequest Request { get; set; }
```

TrackedFileId

```
public Guid TrackedFileId { get; set; }
```

Class ProjectFilesScanParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectFilesScanParameters

```
public sealed class ProjectFilesScanParameters
```

🌟 Constructors 1

ProjectFilesScanParameters()

```
public ProjectFilesScanParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public ScanProjectFilesRequest Request { get; set; }
```

Class ProjectMaintenanceGetParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectMaintenanceGetParameters

```
public sealed class ProjectMaintenanceGetParameters
```

🌟 Constructors 1

ProjectMaintenanceGetParameters()

```
public ProjectMaintenanceGetParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

Class ProjectOrganicContext

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Stores project and revision metadata used to route organic Council capabilities.

Inheritance object ProjectOrganicContext

```
[DocumentationUpdated("2.1.20")] public class ProjectOrganicContext
```

✨ Constructors 1

ProjectOrganicContext()

```
public ProjectOrganicContext()
```

🐾 Properties 14

BuildSuccessful

Gets or sets the latest known build result.

```
public bool? BuildSuccessful { get; set; }
```

Compilers

Gets or sets known compiler or tool names.

```
public List<string> Compilers { get; set; }
```

DebugPaths

Gets or sets approved debug and diagnostic paths.

```
public List<string> DebugPaths { get; set; }
```

ExternalOrganPlugins

Gets or sets external organic plugin identifiers.

```
public List<string> ExternalOrganPlugins { get; set; }
```

FileRegexPatterns

Gets or sets file-level regex patterns.

```
public List<string> FileRegexPatterns { get; set; }
```

HasInstaller

Gets or sets whether an installer is known to exist.

```
public bool? HasInstaller { get; set; }
```

InstallerPath

Gets or sets the recorded installer path.

```
public string InstallerPath { get; set; }
```

KnowledgeReferences

Gets or sets knowledge references relevant to the project.

```
public List<string> KnowledgeReferences { get; set; }
```

LastCouncilActivityUtc

Gets or sets the most recent Council activity time.

```
public DateTimeOffset? LastCouncilActivityUtc { get; set; }
```

ProjectId

Gets or sets the owning project identifier.

```
public Guid ProjectId { get; set; }
```

ProjectRegexPatterns

Gets or sets project-level regex patterns.

```
public List<string> ProjectRegexPatterns { get; set; }
```

RequiredOrganicCapabilities

Gets or sets required organic capability keys.

```
public List<string> RequiredOrganicCapabilities { get; set; }
```

RevisionId

Gets or sets the optional project revision identifier.

```
public Guid? RevisionId { get; set; }
```

SystemCommands

Gets or sets bounded system-command descriptions.

```
public List<string> SystemCommands { get; set; }
```

api/LocalGPT.BusinessObjects.ProjectOrganicSkillLink.html

Class ProjectOrganicSkillLink

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectOrganicSkillLink

```
public sealed class ProjectOrganicSkillLink
```

🌟 Constructors 1

ProjectOrganicSkillLink()

```
public ProjectOrganicSkillLink()
```

🐾 Properties 9

Id

```
public Guid Id { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsRequired

```
public bool IsRequired { get; set; }
```

Notes

```
[MaxLength(2000)] public string Notes { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

Skill

```
public OrganicSkillDefinition? Skill { get; set; }
```

SkillId

```
public Guid SkillId { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class ProjectRequirementSaveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectRequirementSaveParameters

```
public sealed class ProjectRequirementSaveParameters
```

🌟 Constructors 1

ProjectRequirementSaveParameters()

```
public ProjectRequirementSaveParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public SaveProjectRequirementRequest Request { get; set; }
```

Class ProjectRevisionApproveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectRevisionApproveParameters

```
public sealed class ProjectRevisionApproveParameters
```

🌟 Constructors 1

ProjectRevisionApproveParameters()

```
public ProjectRevisionApproveParameters()
```

🐾 Properties 3

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public ApproveRevisionReadyForTestRequest Request { get; set; }
```

RevisionId

```
public Guid RevisionId { get; set; }
```

Class ProjectRevisionBuildVerifyParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectRevisionBuildVerifyParameters

```
public sealed class ProjectRevisionBuildVerifyParameters
```

🌟 Constructors 1

ProjectRevisionBuildVerifyParameters()

```
public ProjectRevisionBuildVerifyParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public RunProjectBuildVerificationRequest Request { get; set; }
```

Class ProjectRevisionSaveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectRevisionSaveParameters

```
public sealed class ProjectRevisionSaveParameters
```

🌟 Constructors 1

ProjectRevisionSaveParameters()

```
public ProjectRevisionSaveParameters()
```

🐾 Properties 2

ProjectId

```
public Guid ProjectId { get; set; }
```

Request

```
public SaveProjectRevisionRequest Request { get; set; }
```

Class ProjectRevisionWorkspaceRegisterParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectRevisionWorkspaceRegisterParameters

```
public sealed class ProjectRevisionWorkspaceRegisterParameters
```

🌟 Constructors 1

ProjectRevisionWorkspaceRegisterParameters()

```
public ProjectRevisionWorkspaceRegisterParameters()
```

🐾 Properties 4

ProjectId

```
public Guid ProjectId { get; set; }
```

RevisionId

```
public Guid RevisionId { get; set; }
```

SolutionPath

```
public string SolutionPath { get; set; }
```

SourceRootPath

```
public string SourceRootPath { get; set; }
```

Class ProjectScanResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectScanResult

Implements IEquatable < ProjectScanResult >

```
public sealed record ProjectScanResult : IEquatable<ProjectScanResult>
```

🌟 Constructors 1

ProjectScanResult(Guid, Guid?, string, string, int, int, int, IReadOnlyList<string>)

```
public ProjectScanResult(Guid ProjectId, Guid? RevisionId, string ProjectRootPath, string SolutionPath, int FilesSeen, int FilesStored, int FilesSkipped, IReadOnlyList<string> Warnings)
```

🐾 Properties 8

FilesSeen

```
public int FilesSeen { get; init; }
```

FilesSkipped

```
public int FilesSkipped { get; init; }
```

FilesStored

```
public int FilesStored { get; init; }
```

ProjectId

```
public Guid ProjectId { get; init; }
```

ProjectRootPath

```
public string ProjectRootPath { get; init; }
```

RevisionId

```
public Guid? RevisionId { get; init; }
```

SolutionPath

```
public string SolutionPath { get; init; }
```

Warnings

```
public IReadOnlyList<string> Warnings { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out Guid?, out string, out string, out int, out int, out int, out IReadOnlyList<string>)

```
public void Deconstruct(out Guid ProjectId, out Guid? RevisionId, out string ProjectRootPath, out string SolutionPath, out int FilesSeen, out int FilesStored, out int FilesSkipped, out IReadOnlyList<string> Warnings)
```

Equals(ProjectScanResult?)

```
public bool Equals(ProjectScanResult? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ProjectScanResult?, ProjectScanResult?)

```
public static bool operator ==(ProjectScanResult? left, ProjectScanResult? right)
```


operator !=(ProjectScanResult?, ProjectScanResult?)

```
public static bool operator !=(ProjectScanResult? left, ProjectScanResult? right)
```

api/LocalGPT.BusinessObjects.ProjectTextDocumentImportParameters.html

Class ProjectTextDocumentImportParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectTextDocumentImportParameters

```
public sealed class ProjectTextDocumentImportParameters
```

🌟 Constructors 1

ProjectTextDocumentImportParameters()

```
public ProjectTextDocumentImportParameters()
```

🐾 Properties 3

FilePath

```
public string FilePath { get; set; }
```

ProjectId

```
public Guid ProjectId { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

api/LocalGPT.BusinessObjects.ProjectWorkspaceEnvironmentAssessParameters.html

Class ProjectWorkspaceEnvironmentAssessParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectWorkspaceEnvironmentAssessParameters

```
public sealed class ProjectWorkspaceEnvironmentAssessParameters
```

🌟 Constructors 1

ProjectWorkspaceEnvironmentAssessParameters()

```
public ProjectWorkspaceEnvironmentAssessParameters()
```

🐾 Properties 1

WorkspaceRootId

```
public Guid WorkspaceRootId { get; set; }
```

api/LocalGPT.BusinessObjects.ProjectWorkspaceEnvironmentSaveParameters.html

Class ProjectWorkspaceEnvironmentSaveParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectWorkspaceEnvironmentSaveParameters

```
public sealed class ProjectWorkspaceEnvironmentSaveParameters
```

🌟 Constructors 1

ProjectWorkspaceEnvironmentSaveParameters()

```
public ProjectWorkspaceEnvironmentSaveParameters()
```

🐾 Properties 1

Request

```
public SaveProjectWorkspaceRootRequest Request { get; set; }
```

Class ProjectWorkspaceResolution

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectWorkspaceResolution

Implements IEquatable < ProjectWorkspaceResolution >

```
public sealed record ProjectWorkspaceResolution : IEquatable<ProjectWorkspaceResolution>
```

🌟 Constructors 1

ProjectWorkspaceResolution(Guid?, string, string, string, bool)

```
public ProjectWorkspaceResolution(Guid? WorkspaceRootId, string RootPath, string ScopeKind, string MatchReason, bool Exists)
```

🐾 Properties 5

Exists

```
public bool Exists { get; init; }
```

MatchReason

```
public string MatchReason { get; init; }
```

RootPath

```
public string RootPath { get; init; }
```

ScopeKind

```
public string ScopeKind { get; init; }
```

WorkspaceRootId

```
public Guid? WorkspaceRootId { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid?, out string, out string, out string, out bool)

```
public void Deconstruct(out Guid? WorkspaceRootId, out string RootPath, out string ScopeKind, out string MatchReason, out bool Exists)
```

Equals(ProjectWorkspaceResolution?)

```
public bool Equals(ProjectWorkspaceResolution? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ProjectWorkspaceResolution?, ProjectWorkspaceResolution?)

```
public static bool operator ==(ProjectWorkspaceResolution? left, ProjectWorkspaceResolution? right)
```

operator !=(ProjectWorkspaceResolution?, ProjectWorkspaceResolution?)

```
public static bool operator !=(ProjectWorkspaceResolution? left, ProjectWorkspaceResolution? right)
```

Class ProjectWorkspaceRoot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProjectWorkspaceRoot

```
public sealed class ProjectWorkspaceRoot
```

🌟 Constructors 1

ProjectWorkspaceRoot()

```
public ProjectWorkspaceRoot()
```

🐾 Properties 28

AccessPolicyJson

```
[Column(TypeName = "TEXT")] public string AccessPolicyJson { get; set; }
```

BuildArguments

```
[Column(TypeName = "TEXT")] public string BuildArguments { get; set; }
```

CreatedAtUtc

```
public DateTime CreatedAtUtc { get; set; }
```

DefaultSubdirectoriesJson

```
[Column(TypeName = "TEXT")] public string DefaultSubdirectoriesJson { get; set; }
```

EnvironmentKind

```
[MaxLength(80)] public string EnvironmentKind { get; set; }
```

EnvironmentRootPath

```
[MaxLength(2048)] public string EnvironmentRootPath { get; set; }
```

EnvironmentVariablesJson

```
[Column(TypeName = "TEXT")] public string EnvironmentVariablesJson { get; set; }
```

ExpectedStructureRegex

```
[Column(TypeName = "TEXT")] public string ExpectedStructureRegex { get; set; }
```

Id

```
public Guid Id { get; set; }
```

IsDefault

```
public bool IsDefault { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

LastPermissionCheckedAtUtc

```
public DateTime? LastPermissionCheckedAtUtc { get; set; }
```

LastPermissionReadAccess

```
public bool LastPermissionReadAccess { get; set; }
```

LastPermissionStatus

```
[MaxLength(80)] public string LastPermissionStatus { get; set; }
```

LastPermissionSummary

```
[MaxLength(4000)] public string LastPermissionSummary { get; set; }
```

LastPermissionWriteAccess

```
public bool LastPermissionWriteAccess { get; set; }
```

LastResolutionStatus

```
[MaxLength(80)] public string LastResolutionStatus { get; set; }
```

LastResolvedAtUtc

```
public DateTime? LastResolvedAtUtc { get; set; }
```

Name

```
[Required] [MaxLength(200)] public string Name { get; set; }
```

PreferredCompilerInstallationId

```
public Guid? PreferredCompilerInstallationId { get; set; }
```

Priority

```
public int Priority { get; set; }
```

Project

```
public LocalGptProject? Project { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectTypePattern

```
[MaxLength(240)] public string ProjectTypePattern { get; set; }
```

RootPath

```
[Required] [MaxLength(2048)] public string RootPath { get; set; }
```

ScopeKind

```
[Required] [MaxLength(40)] public string ScopeKind { get; set; }
```

SolutionPattern

```
[MaxLength(1000)] public string SolutionPattern { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class PromptConfig

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object PromptConfig

```
public class PromptConfig
```

🌟 Constructors 1

PromptConfig()

```
public PromptConfig()
```

🐾 Properties 5

Id

```
[Key] public int Id { get; set; }
```

Key

```
[Required] [MaxLength(128)] public string Key { get; set; }
```

Language

```
[MaxLength(10)] public string? Language { get; set; }
```

LastUpdated

```
public DateTime LastUpdated { get; set; }
```

Text

```
[Required] [Column(TypeName = "TEXT")] public string Text { get; set; }
```

Class PromptSuggestion

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Describes one reusable Chat prompt and its optional Council-team ownership.

Inheritance object PromptSuggestion

```
[DocumentationUpdated("2.1.22")] public sealed class PromptSuggestion
```

🌟 Constructors 1

PromptSuggestion(string, string, string, string?, IEnumerable<string>?, bool)

Creates one prompt suggestion.

```
public PromptSuggestion(string title, string text, string promptMessage, string? key = null, IEnumerable<string>? teamKeys = null, bool startsCouncilDirectly = false)
```

🐾 Properties 6

Key

Gets the stable prompt key used by direct Council starter routes.

```
public string Key { get; }
```

PromptMessage

Gets or sets the full text submitted to the selected chat or Council session.

```
[Column(TypeName = "TEXT")] public string PromptMessage { get; set; }
```

StartsCouncilDirectly

Gets whether the prompt is intended to create a fresh AI Council run rather than a normal single-model reply.

```
public bool StartsCouncilDirectly { get; }
```

TeamKeys

Gets the Council-team keys for which this prompt is recommended.

```
public IReadOnlyList<string> TeamKeys { get; }
```

Text

Gets or sets the compact prompt description.

```
[Column(TypeName = "TEXT")] public string Text { get; set; }
```

Title

Gets or sets the visible prompt title.

```
public string Title { get; set; }
```

⚙️ Methods 1

IsAvailableForTeam(string?)

Returns whether this prompt is generic or assigned to the requested Council team.

```
public bool IsAvailableForTeam(string? teamKey)
```

Class ProviderModelBenchmarkAppliedEvent

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkAppliedEvent

Implements IEquatable < ProviderModelBenchmarkAppliedEvent >

```
public sealed record ProviderModelBenchmarkAppliedEvent : IEquatable<ProviderModelBenchmarkAppliedEvent>
```

🌟 Constructors 1

ProviderModelBenchmarkAppliedEvent(ProviderModelReference, OneWireCouncilModelRoute, CouncilModelPreset)

```
public ProviderModelBenchmarkAppliedEvent(ProviderModelReference Model, OneWireCouncilModelRoute Route, CouncilModelPreset Preset)
```

🐾 Properties 3

Model

```
public ProviderModelReference Model { get; init; }
```

Preset

```
public CouncilModelPreset Preset { get; init; }
```

Route

```
public OneWireCouncilModelRoute Route { get; init; }
```

⚙️ Methods 5

Deconstruct(out ProviderModelReference, out OneWireCouncilModelRoute, out CouncilModelPreset)

```
public void Deconstruct(out ProviderModelReference Model, out OneWireCouncilModelRoute Route, out CouncilModelPreset Preset)
```

Equals(ProviderModelBenchmarkAppliedEvent?)

```
public bool Equals(ProviderModelBenchmarkAppliedEvent? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ProviderModelBenchmarkAppliedEvent?, ProviderModelBenchmarkAppliedEvent?)

```
public static bool operator ==(ProviderModelBenchmarkAppliedEvent? left, ProviderModelBenchmarkAppliedEvent? right)
```

operator !=(ProviderModelBenchmarkAppliedEvent?, ProviderModelBenchmarkAppliedEvent?)

```
public static bool operator !=(ProviderModelBenchmarkAppliedEvent? left, ProviderModelBenchmarkAppliedEvent? right)
```

Class ProviderModelBenchmarkBatchAppliedEvent

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkBatchAppliedEvent

Implements IEquatable < ProviderModelBenchmarkBatchAppliedEvent >

```
public sealed record ProviderModelBenchmarkBatchAppliedEvent : IEquatable<ProviderModelBenchmarkBatchAppliedEvent>
```

🌟 Constructors 1

ProviderModelBenchmarkBatchAppliedEvent(IReadOnlyList<ProviderModelReference>, IReadOnlyList<OneWireCouncilModelRoute>, CouncilModelPreset)

```
public ProviderModelBenchmarkBatchAppliedEvent(IReadOnlyList<ProviderModelReference> Models, IReadOnlyList<OneWireCouncilModelRoute> Routes, CouncilModelPreset Preset)
```

🐾 Properties 3

Models

```
public IReadOnlyList<ProviderModelReference> Models { get; init; }
```

Preset

```
public CouncilModelPreset Preset { get; init; }
```

Routes

```
public IReadOnlyList<OneWireCouncilModelRoute> Routes { get; init; }
```

⚙️ Methods 5

Deconstruct(out IReadOnlyList<ProviderModelReference>, out IReadOnlyList<OneWireCouncilModelRoute>, out CouncilModelPreset)

```
public void Deconstruct(out IReadOnlyList<ProviderModelReference> Models, out IReadOnlyList<OneWireCouncilModelRoute> Routes, out CouncilModelPreset Preset)
```

Equals(ProviderModelBenchmarkBatchAppliedEvent?)

```
public bool Equals(ProviderModelBenchmarkBatchAppliedEvent? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(ProviderModelBenchmarkBatchAppliedEvent?, ProviderModelBenchmarkBatchAppliedEvent?)

```
public static bool operator ==(ProviderModelBenchmarkBatchAppliedEvent? left, ProviderModelBenchmarkBatchAppliedEvent? right)
```

operator !=(ProviderModelBenchmarkBatchAppliedEvent?, ProviderModelBenchmarkBatchAppliedEvent?)

```
public static bool operator !=(ProviderModelBenchmarkBatchAppliedEvent? left, ProviderModelBenchmarkBatchAppliedEvent? right)
```


Class ProviderModelBenchmarkProfileResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkProfileResult

```
public sealed class ProviderModelBenchmarkProfileResult
```

🌟 Constructors 1

ProviderModelBenchmarkProfileResult()

```
public ProviderModelBenchmarkProfileResult()
```

🐾 Properties 9

AverageQualityScore

```
public double AverageQualityScore { get; set; }
```

AverageTokensPerSecond

```
public double AverageTokensPerSecond { get; set; }
```

AverageTotalMilliseconds

```
public double AverageTotalMilliseconds { get; set; }
```

ContextTokens

```
public int ContextTokens { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

OutputTokens

```
public int OutputTokens { get; set; }
```

ProfileName

```
public string ProfileName { get; set; }
```

Score

```
public double Score { get; set; }
```

Tasks

```
public List<ProviderModelBenchmarkTaskResult> Tasks { get; set; }
```

Class ProviderModelBenchmarkRecommendation

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object ProviderModelBenchmarkRecommendation

```
public sealed class ProviderModelBenchmarkRecommendation
```

🌟 Constructors 1

ProviderModelBenchmarkRecommendation()

```
public ProviderModelBenchmarkRecommendation()
```

🐾 Properties 7

ContextTokens

```
public int ContextTokens { get; set; }
```

CouncilScore

```
public double CouncilScore { get; set; }
```

EmpiricalScore

```
public double EmpiricalScore { get; set; }
```

OllamaNumGpu

```
public int? OllamaNumGpu { get; set; }
```

OutputTokens

```
public int OutputTokens { get; set; }
```

ProfileName

```
public string ProfileName { get; set; }
```

Rationale

```
public string Rationale { get; set; }
```

Class ProviderModelBenchmarkReport

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkReport

```
public sealed class ProviderModelBenchmarkReport
```

🌟 Constructors 1

ProviderModelBenchmarkReport()

```
public ProviderModelBenchmarkReport()
```

🐾 Properties 8

AppliedPresetId

```
public Guid? AppliedPresetId { get; set; }
```

AppliedPresetName

```
public string AppliedPresetName { get; set; }
```

CompletedAtUtc

```
public DateTimeOffset CompletedAtUtc { get; set; }
```

CouncilMembers

```
public List<string> CouncilMembers { get; set; }
```

RunId

```
public Guid RunId { get; set; }
```

StartedAtUtc

```
public DateTimeOffset StartedAtUtc { get; set; }
```

Targets

```
public List<ProviderModelBenchmarkTargetResult> Targets { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class ProviderModelBenchmarkRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkRequest

```
public sealed class ProviderModelBenchmarkRequest
```

🌟 Constructors 1

ProviderModelBenchmarkRequest()

```
public ProviderModelBenchmarkRequest()
```

🐾 Properties 10

CouncilReviewers

```
public List<ProviderModelReference> CouncilReviewers { get; set; }
```

ImprovementThresholdPercent

```
public double ImprovementThresholdPercent { get; set; }
```

IncludeCouncilReview

```
public bool IncludeCouncilReview { get; set; }
```

MaxCouncilReviewers

```
public int MaxCouncilReviewers { get; set; }
```

MaxProfilesPerModel

```
public int MaxProfilesPerModel { get; set; }
```

MaxSecondsPerCall

```
public int MaxSecondsPerCall { get; set; }
```

MaxTasks

```
public int MaxTasks { get; set; }
```

MaximumContextTokens

```
public int MaximumContextTokens { get; set; }
```

MaximumOutputTokens

```
public int MaximumOutputTokens { get; set; }
```

Targets

```
public List<ProviderModelReference> Targets { get; set; }
```

Class ProviderModelBenchmarkTargetResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelBenchmarkTargetResult

```
public sealed class ProviderModelBenchmarkTargetResult
```

🌟 Constructors 1

ProviderModelBenchmarkTargetResult()

```
public ProviderModelBenchmarkTargetResult()
```

🐾 Properties 6

CouncilReviews

```
public List<ProviderModelCouncilReview> CouncilReviews { get; set; }
```

Error

```
public string Error { get; set; }
```

Model

```
public ProviderModelReference Model { get; set; }
```

Profiles

```
public List<ProviderModelBenchmarkProfileResult> Profiles { get; set; }
```

Recommendation

```
public ProviderModelBenchmarkRecommendation Recommendation { get; set; }
```

StoppedBecauseImprovementWasBelowThreshold

```
public bool StoppedBecauseImprovementWasBelowThreshold { get; set; }
```

Class ProviderModelBenchmarkTaskResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object ProviderModelBenchmarkTaskResult

```
public sealed class ProviderModelBenchmarkTaskResult
```

🌟 Constructors 1

ProviderModelBenchmarkTaskResult()

```
public ProviderModelBenchmarkTaskResult()
```

🐾 Properties 7

Error

```
public string Error { get; set; }
```

QualityScore

```
public double QualityScore { get; set; }
```

ResponsePreview

```
public string ResponsePreview { get; set; }
```

Succeeded

```
public bool Succeeded { get; set; }
```

TaskName

```
public string TaskName { get; set; }
```

TokensPerSecond

```
public double TokensPerSecond { get; set; }
```

TotalMilliseconds

```
public long TotalMilliseconds { get; set; }
```

Class ProviderModelCouncilReview

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ProviderModelCouncilReview

```
public sealed class ProviderModelCouncilReview
```

🌟 Constructors 1

ProviderModelCouncilReview()

```
public ProviderModelCouncilReview()
```

🐾 Properties 7

Error

```
public string Error { get; set; }
```

QualityScore

```
public double QualityScore { get; set; }
```

Rationale

```
public string Rationale { get; set; }
```

RecommendedContextTokens

```
public int RecommendedContextTokens { get; set; }
```

RecommendedOutputTokens

```
public int RecommendedOutputTokens { get; set; }
```

ReliabilityScore

```
public double ReliabilityScore { get; set; }
```

Reviewer

```
public ProviderModelReference Reviewer { get; set; }
```

Class ProviderModelReference

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Provider-qualified model identity. No credential is stored in this object; credentials are resolved from the matching configured provider at execution time.

Inheritance object ProviderModelReference

```
public sealed class ProviderModelReference
```

🌟 Constructors 1

ProviderModelReference()

```
public ProviderModelReference()
```

🐾 Properties 14

Details

```
public string Details { get; set; }
```

DisplayName

```
public string DisplayName { get; }
```

Endpoint

```
public string Endpoint { get; set; }
```

EndpointLabel

```
public string EndpointLabel { get; }
```

IsConfigured

```
public bool IsConfigured { get; set; }
```

IsLoaded

```
public bool IsLoaded { get; set; }
```

IsLocal

```
public bool IsLocal { get; set; }
```

IsReachable

```
public bool IsReachable { get; set; }
```

ModelName

```
public string ModelName { get; set; }
```

ProviderKind

```
public string ProviderKind { get; set; }
```

ProviderName

```
public string ProviderName { get; set; }
```

SelectionKey

```
public string SelectionKey { get; }
```

StableId

```
public string StableId { get; }
```

SupportsBenchmark

```
public bool SupportsBenchmark { get; set; }
```


Class PublicServiceMethodInvocationParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object PublicServiceMethodInvocationParameters

```
public sealed class PublicServiceMethodInvocationParameters
```

✨ Constructors 1

PublicServiceMethodInvocationParameters()

```
public PublicServiceMethodInvocationParameters()
```

🐾 Properties 2

CatalogKey

```
public string CatalogKey { get; set; }
```

Parameters

```
public JsonElement Parameters { get; set; }
```

Class PublicServiceMethodInvocationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object PublicServiceMethodInvocationRequest

```
public sealed class PublicServiceMethodInvocationRequest
```

✨ Constructors 1

PublicServiceMethodInvocationRequest()

```
public PublicServiceMethodInvocationRequest()
```

🐾 Properties 3

CatalogKey

```
public string CatalogKey { get; set; }
```

Parameters

```
public JsonElement Parameters { get; set; }
```

RequestedBy

```
public string RequestedBy { get; set; }
```

Class PythonCoreOptions

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object PythonCoreOptions

```
public class PythonCoreOptions
```

🌟 Constructors 1

PythonCoreOptions()

```
public PythonCoreOptions()
```

🔴 Fields 1

PythonCore

```
public const string PythonCore = "PythonCore"
```

🐾 Properties 1

PythonRuntime

```
public string? PythonRuntime { get; set; }
```

Class RecentApplicationLogListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RecentApplicationLogListParameters

```
public sealed class RecentApplicationLogListParameters
```

🌟 Constructors 1

RecentApplicationLogListParameters()

```
public RecentApplicationLogListParameters()
```

🐾 Properties 2

MinimumLevel

```
public string MinimumLevel { get; set; }
```

Take

```
public int Take { get; set; }
```

Class RecordCouncilBuildReviewRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RecordCouncilBuildReviewRequest

```
public sealed class RecordCouncilBuildReviewRequest
```

🌟 Constructors 1

RecordCouncilBuildReviewRequest()

```
public RecordCouncilBuildReviewRequest()
```

🐾 Properties 3

CompileErrorsAbsent

```
public bool CompileErrorsAbsent { get; set; }
```

Summary

```
public string Summary { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class RegexPattern

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RegexPattern

```
public class RegexPattern
```

🌟 Constructors 1

RegexPattern()

```
public RegexPattern()
```

🐾 Properties 6

CreatedOn

```
public DateTime CreatedOn { get; set; }
```

Flags

```
[MaxLength(32)] public string? Flags { get; set; }
```

Id

```
[Key] public int Id { get; set; }
```

Name

```
[Required] [MaxLength(128)] public string Name { get; set; }
```

Pattern

```
[Required] public string Pattern { get; set; }
```

UpdatedOn

```
public DateTime UpdatedOn { get; set; }
```

Class RegexPatternListParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RegexPatternListParameters

```
public sealed class RegexPatternListParameters
```

🌟 Constructors 1

RegexPatternListParameters()

```
public RegexPatternListParameters()
```

🐾 Properties 2

Prefix

```
public string Prefix { get; set; }
```

Take

```
public int Take { get; set; }
```

Class RegisterRevisionWorkspaceRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RegisterRevisionWorkspaceRequest

```
public sealed class RegisterRevisionWorkspaceRequest
```

🌟 Constructors 1

RegisterRevisionWorkspaceRequest()

```
public RegisterRevisionWorkspaceRequest()
```

🐾 Properties 3

SolutionPath

```
public string SolutionPath { get; set; }
```

SourceRootPath

```
public string SourceRootPath { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class RejectCodeGenerationReviewRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RejectCodeGenerationReviewRequest

```
public sealed class RejectCodeGenerationReviewRequest
```

🌟 Constructors 1

RejectCodeGenerationReviewRequest()

```
public RejectCodeGenerationReviewRequest()
```

🐾 Properties 3

DecisionNote

```
public string DecisionNote { get; set; }
```

ExpectedReviewHash

```
public string ExpectedReviewHash { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class RemoteKnowledgeImportFile

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RemoteKnowledgeImportFile

```
public sealed class RemoteKnowledgeImportFile
```

🌟 Constructors 1

RemoteKnowledgeImportFile()

```
public RemoteKnowledgeImportFile()
```

🐾 Properties 6

Imported

```
public bool Imported { get; set; }
```

Length

```
public long Length { get; set; }
```

MatchesFilePolicy

```
public bool MatchesFilePolicy { get; set; }
```

RelativePath

```
public string RelativePath { get; set; }
```

SourceUrl

```
public string SourceUrl { get; set; }
```

Status

```
public string Status { get; set; }
```

Class RemoteKnowledgeImportRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RemoteKnowledgeImportRequest

```
public sealed class RemoteKnowledgeImportRequest
```

✨ Constructors 1

RemoteKnowledgeImportRequest()

```
public RemoteKnowledgeImportRequest()
```

🐾 Properties 11

Branch

```
public string Branch { get; set; }
```

FileIncludeRegex

```
public string FileIncludeRegex { get; set; }
```

MaxFiles

```
public int MaxFiles { get; set; }
```

MaxLinkedPages

```
public int MaxLinkedPages { get; set; }
```

PreviewOnly

```
public bool PreviewOnly { get; set; }
```

RoleKeys

```
public List<string> RoleKeys { get; set; }
```

SaveToKnowledge

```
public bool SaveToKnowledge { get; set; }
```

SourceKind

```
public string SourceKind { get; set; }
```

SourceUrl

```
public string SourceUrl { get; set; }
```

Topics

```
public List<string> Topics { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class RemoteKnowledgeImportResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RemoteKnowledgeImportResult

```
public sealed class RemoteKnowledgeImportResult
```

🌟 Constructors 1

RemoteKnowledgeImportResult()

```
public RemoteKnowledgeImportResult()
```

🐾 Properties 11

AppliedTags

```
public List<string> AppliedTags { get; set; }
```

CacheRoot

```
public string CacheRoot { get; set; }
```

DownloadedFileCount

```
public int DownloadedFileCount { get; set; }
```

Files

```
public List<RemoteKnowledgeImportFile> Files { get; set; }
```

ImportedKnowledgeCount

```
public int ImportedKnowledgeCount { get; set; }
```

LearnBaseResult

```
public LearnBaseImportResult? LearnBaseResult { get; set; }
```

MatchedFileCount

```
public int MatchedFileCount { get; set; }
```

ResolvedRevision

```
public string ResolvedRevision { get; set; }
```

SourceKind

```
public string SourceKind { get; set; }
```

SourceUrl

```
public string SourceUrl { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class ReportCouncilMemberSkillRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ReportCouncilMemberSkillRequest

```
public sealed class ReportCouncilMemberSkillRequest
```

🌟 Constructors 1

ReportCouncilMemberSkillRequest()

```
public ReportCouncilMemberSkillRequest()
```

🐾 Properties 10

ControllerMethods

```
public List<string> ControllerMethods { get; set; }
```

DxFunctions

```
public List<string> DxFunctions { get; set; }
```

Evidence

```
public string Evidence { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsSelfRevealed

```
public bool IsSelfRevealed { get; set; }
```

MemberKey

```
public string MemberKey { get; set; }
```

OrganicCapabilities

```
public List<string> OrganicCapabilities { get; set; }
```

Proficiency

```
public int Proficiency { get; set; }
```

SkillId

```
public Guid SkillId { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```


Class RunProjectBuildVerificationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RunProjectBuildVerificationRequest

```
public sealed class RunProjectBuildVerificationRequest
```

🌟 Constructors 1

RunProjectBuildVerificationRequest()

```
public RunProjectBuildVerificationRequest()
```

🐾 Properties 7

Arguments

```
public string Arguments { get; set; }
```

CompilerInstallationId

```
public Guid CompilerInstallationId { get; set; }
```

Configuration

```
public string Configuration { get; set; }
```

RevisionId

```
public Guid RevisionId { get; set; }
```

TestArguments

```
public string TestArguments { get; set; }
```

TimeoutSeconds

```
public int TimeoutSeconds { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class RuntimeCapabilityDirectorySnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Current dependency-injected function and organic-skill directory persisted for AI context.
Inheritance object RuntimeCapabilityDirectorySnapshot

```
public sealed class RuntimeCapabilityDirectorySnapshot
```

🌟 Constructors 1

RuntimeCapabilityDirectorySnapshot()

```
public RuntimeCapabilityDirectorySnapshot()
```

🐾 Properties 5

CatalogEntries

```
public IReadOnlyList<DxAiFunctionCatalogEntry> CatalogEntries { get; set; }
```

Functions

```
public IReadOnlyList<DxaichatFunctionInfo> Functions { get; set; }
```

Skills

```
public IReadOnlyList<OneWireSkillDescriptor> Skills { get; set; }
```

SynchronizedAtUtc

```
public DateTime SynchronizedAtUtc { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class RuntimeClassFieldDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RuntimeClassFieldDefinition

```
public sealed class RuntimeClassFieldDefinition
```

🌟 Constructors 1

RuntimeClassFieldDefinition()

```
public RuntimeClassFieldDefinition()
```

🐾 Properties 13

AiAssignable

```
public bool AiAssignable { get; set; }
```

AllowedValuesJson

```
public string AllowedValuesJson { get; set; }
```

BlocksNextRoundUntilHumanInput

```
public bool BlocksNextRoundUntilHumanInput { get; set; }
```

DataType

```
public string DataType { get; set; }
```

DefaultValue

```
public string DefaultValue { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

GamepadButton

```
public string GamepadButton { get; set; }
```

HumanAssignable

```
public bool HumanAssignable { get; set; }
```

InputMode

```
public RuntimeFieldInputMode InputMode { get; set; }
```

IsRequired

```
public bool IsRequired { get; set; }
```

KeyboardKey

```
public string KeyboardKey { get; set; }
```

Name

```
public string Name { get; set; }
```

Enum RuntimeClassKind

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum RuntimeClassKind
```

Fields 1

Enum RuntimeFieldInputMode

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
[JsonConverter(typeof(JsonStringEnumConverter))] public enum RuntimeFieldInputMode
```

Fields 1

Class RuntimeInputBindingDefinition

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object RuntimeInputBindingDefinition

```
public sealed class RuntimeInputBindingDefinition
```

Constructors 1

RuntimeInputBindingDefinition()

```
public RuntimeInputBindingDefinition()
```

Properties 5

Action

```
public string Action { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

GamepadButton

```
public string GamepadButton { get; set; }
```

KeyboardKey

```
public string KeyboardKey { get; set; }
```

Class SaveCouncilRuntimeClassRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveCouncilRuntimeClassRequest

```
public sealed class SaveCouncilRuntimeClassRequest
```

🌟 Constructors 1

SaveCouncilRuntimeClassRequest()

```
public SaveCouncilRuntimeClassRequest()
```

🐾 Properties 2

Definition

```
public CouncilRuntimeClassDefinition Definition { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class SaveCouncilTeamConfigurationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Carries a reviewed Council team change and its persistence flags.

Inheritance object SaveCouncilTeamConfigurationRequest

```
[DocumentationUpdated("2.1.20")] public sealed class SaveCouncilTeamConfigurationRequest
```

🌟 Constructors 1

SaveCouncilTeamConfigurationRequest()

```
public SaveCouncilTeamConfigurationRequest()
```

🐾 Properties 3

IsEnabled

Gets or sets whether the saved team remains enabled.

```
public bool IsEnabled { get; set; }
```

Team

Gets or sets the team definition to save.

```
public OrganicCouncilTeamDefinition Team { get; set; }
```

UserConfirmed

Gets or sets whether the current user confirmed the exact change.

```
public bool UserConfirmed { get; set; }
```

Class SaveFeatureRecordRequest<TRecord>

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Approval-gated request for creating or updating one persistent feature record.

Inheritance object SaveFeatureRecordRequest<TRecord>

```
[DocumentationUpdated("2.1.23")] public sealed class SaveFeatureRecordRequest<TRecord>
```

✨ Constructors 1

SaveFeatureRecordRequest()

```
public SaveFeatureRecordRequest()
```

🐾 Properties 2

Record

Gets or sets the record to create or update.

```
public TRecord Record { get; set; }
```

UserConfirmed

Gets or sets whether the user explicitly approved this write.

```
public bool UserConfirmed { get; set; }
```

Class SaveLocalGptProjectRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveLocalGptProjectRequest

```
public sealed class SaveLocalGptProjectRequest
```

🌟 Constructors 1

SaveLocalGptProjectRequest()

```
public SaveLocalGptProjectRequest()
```

🐾 Properties 14

CurrentVersion

```
public string CurrentVersion { get; set; }
```

FileExcludePattern

```
public string FileExcludePattern { get; set; }
```

FileIncludePattern

```
public string FileIncludePattern { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

IsArchived

```
public bool IsArchived { get; set; }
```

Name

```
public string Name { get; set; }
```

ProjectType

```
public string ProjectType { get; set; }
```

Purpose

```
public string Purpose { get; set; }
```

RecommendGit

```
public bool RecommendGit { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

SolutionPath

```
public string SolutionPath { get; set; }
```

SolutionSearchPattern

```
public string SolutionSearchPattern { get; set; }
```

Status

```
public string Status { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class SaveOrganicSkillRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveOrganicSkillRequest

```
public sealed class SaveOrganicSkillRequest
```

🌟 Constructors 1

SaveOrganicSkillRequest()

```
public SaveOrganicSkillRequest()
```

🐾 Properties 11

CapabilityKeys

```
public List<string> CapabilityKeys { get; set; }
```

Description

```
public string Description { get; set; }
```

DisplayName

```
public string DisplayName { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

IsOnline

```
public bool IsOnline { get; set; }
```

Key

```
public string Key { get; set; }
```

Organs

```
public List<string> Organs { get; set; }
```

SourcePeerId

```
public string SourcePeerId { get; set; }
```

UiActivationKeys

```
public List<string> UiActivationKeys { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```


Class SaveProjectArtifactRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectArtifactRequest

```
public sealed class SaveProjectArtifactRequest
```

🌟 Constructors 1

SaveProjectArtifactRequest()

```
public SaveProjectArtifactRequest()
```

🐾 Properties 11

ArtifactKind

```
public string ArtifactKind { get; set; }
```

DataType

```
public string DataType { get; set; }
```

Description

```
public string Description { get; set; }
```

Flags

```
public string Flags { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

IsSensitive

```
public bool IsSensitive { get; set; }
```

Name

```
public string Name { get; set; }
```

RequirementId

```
public Guid? RequirementId { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Value

```
public string Value { get; set; }
```

Class SaveProjectCompilerInstallationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectCompilerInstallationRequest

```
public sealed class SaveProjectCompilerInstallationRequest
```

🌟 Constructors 1

SaveProjectCompilerInstallationRequest()

```
public SaveProjectCompilerInstallationRequest()
```

🐾 Properties 13

Architecture

```
public string Architecture { get; set; }
```

CompilerHomePath

```
public string CompilerHomePath { get; set; }
```

DiscoverySource

```
public string DiscoverySource { get; set; }
```

EnvironmentVariablesJson

```
public string EnvironmentVariablesJson { get; set; }
```

ExecutablePath

```
public string ExecutablePath { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

IsDefaultForLanguage

```
public bool IsDefaultForLanguage { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

Language

```
public string Language { get; set; }
```

Name

```
public string Name { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

ValidationArguments

```
public string ValidationArguments { get; set; }
```

Version

```
public string Version { get; set; }
```

Class SaveProjectOrganicContextRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Extends project organic context with the confirmation required for persistence.

Inheritance object ProjectOrganicContext SaveProjectOrganicContextRequest

```
[DocumentationUpdated("2.1.20")] public sealed class SaveProjectOrganicContextRequest : ProjectOrganicContext
```

🌟 Constructors 1

SaveProjectOrganicContextRequest()

```
public SaveProjectOrganicContextRequest()
```

🐾 Properties 1

UserConfirmed

Gets or sets whether the current user confirmed the exact change.

```
public bool UserConfirmed { get; set; }
```

Class SaveProjectRequirementLinkRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectRequirementLinkRequest

```
public sealed class SaveProjectRequirementLinkRequest
```

🌟 Constructors 1

SaveProjectRequirementLinkRequest()

```
public SaveProjectRequirementLinkRequest()
```

🐾 Properties 7

LinkPurpose

```
public string LinkPurpose { get; set; }
```

RequirementId

```
public Guid RequirementId { get; set; }
```

TargetId

```
public string TargetId { get; set; }
```

TargetKind

```
public string TargetKind { get; set; }
```

TargetName

```
public string TargetName { get; set; }
```

TargetTable

```
public string TargetTable { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class SaveProjectRequirementRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectRequirementRequest

```
public sealed class SaveProjectRequirementRequest
```

🌟 Constructors 1

SaveProjectRequirementRequest()

```
public SaveProjectRequirementRequest()
```

🐾 Properties 10

CouncilRating

```
public int CouncilRating { get; set; }
```

Description

```
public string Description { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

Name

```
public string Name { get; set; }
```

Priority

```
public string Priority { get; set; }
```

RequiredCapability

```
public string RequiredCapability { get; set; }
```

RequirementType

```
public string RequirementType { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

Status

```
public string Status { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class SaveProjectRevisionRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectRevisionRequest

```
public sealed class SaveProjectRevisionRequest
```

🌟 Constructors 1

SaveProjectRevisionRequest()

```
public SaveProjectRevisionRequest()
```

🐾 Properties 7

BranchName

```
public string BranchName { get; set; }
```

IsCurrent

```
public bool IsCurrent { get; set; }
```

ParentRevisionId

```
public Guid? ParentRevisionId { get; set; }
```

ProjectStructureJson

```
public string ProjectStructureJson { get; set; }
```

RevisionName

```
public string RevisionName { get; set; }
```

Summary

```
public string Summary { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class SaveProjectWorkspaceRootRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveProjectWorkspaceRootRequest

```
public sealed class SaveProjectWorkspaceRootRequest
```

🌟 Constructors 1

SaveProjectWorkspaceRootRequest()

```
public SaveProjectWorkspaceRootRequest()
```

🐾 Properties 19

AccessPolicyJson

```
public string AccessPolicyJson { get; set; }
```

BuildArguments

```
public string BuildArguments { get; set; }
```

DefaultSubdirectoriesJson

```
public string DefaultSubdirectoriesJson { get; set; }
```

EnvironmentKind

```
public string EnvironmentKind { get; set; }
```

EnvironmentRootPath

```
public string EnvironmentRootPath { get; set; }
```

EnvironmentVariablesJson

```
public string EnvironmentVariablesJson { get; set; }
```

ExpectedStructureRegex

```
public string ExpectedStructureRegex { get; set; }
```

Id

```
public Guid? Id { get; set; }
```

IsDefault

```
public bool IsDefault { get; set; }
```

IsEnabled

```
public bool IsEnabled { get; set; }
```

Name

```
public string Name { get; set; }
```

PreferredCompilerInstallationId

```
public Guid? PreferredCompilerInstallationId { get; set; }
```

Priority

```
public int Priority { get; set; }
```

ProjectId

```
public Guid? ProjectId { get; set; }
```

ProjectTypePattern

```
public string ProjectTypePattern { get; set; }
```

RootPath

```
public string RootPath { get; set; }
```

ScopeKind

```
public string ScopeKind { get; set; }
```

SolutionPattern

```
public string SolutionPattern { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

api/LocalGPT.BusinessObjects.SaveTrackedFilePatternRequest.html

Class SaveTrackedFilePatternRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SaveTrackedFilePatternRequest

```
public sealed class SaveTrackedFilePatternRequest
```

🌟 Constructors 1

SaveTrackedFilePatternRequest()

```
public SaveTrackedFilePatternRequest()
```

🐾 Properties 4

ContentFormatRegex

```
public string ContentFormatRegex { get; set; }
```

FileRole

```
public string FileRole { get; set; }
```

StructureRegex

```
public string StructureRegex { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class ScanProjectFilesRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ScanProjectFilesRequest

```
public sealed class ScanProjectFilesRequest
```

🌟 Constructors 1

ScanProjectFilesRequest()

```
public ScanProjectFilesRequest()
```

🐾 Properties 5

MaximumFileBytes

```
public long MaximumFileBytes { get; set; }
```

MaximumFiles

```
public int MaximumFiles { get; set; }
```

MaximumTextFileBytes

```
public long MaximumTextFileBytes { get; set; }
```

RevisionId

```
public Guid? RevisionId { get; set; }
```

UserConfirmed

```
public bool UserConfirmed { get; set; }
```

Class ServiceOperationBatch

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Mutable aggregate for one service-operation diagnostics batch. The object is data only; batching and logging behavior remain owned by the diagnostics proxy.

Inheritance object ServiceOperationBatch

```
public sealed class ServiceOperationBatch
```

🌟 Constructors 1

ServiceOperationBatch()

```
public ServiceOperationBatch()
```

🐾 Properties 5

Count

```
public long Count { get; set; }
```

MaximumElapsedMilliseconds

```
public long MaximumElapsedMilliseconds { get; set; }
```

StartedAtUtc

```
public DateTimeOffset StartedAtUtc { get; set; }
```

SyncRoot

```
public object SyncRoot { get; }
```

TotalElapsedMilliseconds

```
public long TotalElapsedMilliseconds { get; set; }
```


Class ServiceOperationBatchSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ServiceOperationBatchSnapshot

Implements IEquatable < ServiceOperationBatchSnapshot >

```
public sealed record ServiceOperationBatchSnapshot : IEquatable<ServiceOperationBatchSnapshot>
```

🌟 Constructors 1

ServiceOperationBatchSnapshot(long, long, long, DateTimeOffset, DateTimeOffset)

```
public ServiceOperationBatchSnapshot(long Count, long TotalElapsedMilliseconds, long MaximumElapsedMilliseconds, DateTimeOffset StartedAtUtc, DateTimeOffset EndedAtUtc)
```

🐾 Properties 5

Count

```
public long Count { get; init; }
```

EndedAtUtc

```
public DateTimeOffset EndedAtUtc { get; init; }
```

MaximumElapsedMilliseconds

```
public long MaximumElapsedMilliseconds { get; init; }
```

StartedAtUtc

```
public DateTimeOffset StartedAtUtc { get; init; }
```

TotalElapsedMilliseconds

```
public long TotalElapsedMilliseconds { get; init; }
```

⚙️ Methods 5

Deconstruct(out long, out long, out long, out DateTimeOffset, out DateTimeOffset)

```
public void Deconstruct(out long Count, out long TotalElapsedMilliseconds, out long MaximumElapsedMilliseconds, out DateTimeOffset StartedAtUtc, out DateTimeOffset EndedAtUtc)
```

Equals(ServiceOperationBatchSnapshot?)

```
public bool Equals(ServiceOperationBatchSnapshot? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(ServiceOperationBatchSnapshot?, ServiceOperationBatchSnapshot?)

```
public static bool operator ==(ServiceOperationBatchSnapshot? left, ServiceOperationBatchSnapshot? right)
```

operator !=(ServiceOperationBatchSnapshot?, ServiceOperationBatchSnapshot?)

```
public static bool operator !=(ServiceOperationBatchSnapshot? left, ServiceOperationBatchSnapshot? right)
```

Class SetCouncilGameControlModeRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SetCouncilGameControlModeRequest

```
public sealed class SetCouncilGameControlModeRequest
```

🌟 Constructors 1

SetCouncilGameControlModeRequest()

```
public SetCouncilGameControlModeRequest()
```

🐾 Properties 4

AutoplayDelayMilliseconds

```
public int AutoplayDelayMilliseconds { get; set; }
```

AutoplayEnabled

```
public bool AutoplayEnabled { get; set; }
```

ControlMode

```
public CouncilGameControlMode ControlMode { get; set; }
```

SessionId

```
public Guid SessionId { get; set; }
```

Class SetCouncilGameInputGateRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SetCouncilGameInputGateRequest

```
public sealed class SetCouncilGameInputGateRequest
```

🌟 Constructors 1

SetCouncilGameInputGateRequest()

```
public SetCouncilGameInputGateRequest()
```

🐾 Properties 4

HumanInputRequired

```
public bool HumanInputRequired { get; set; }
```

LegalActions

```
public IReadOnlyList<string> LegalActions { get; set; }
```

Reason

```
public string Reason { get; set; }
```

SessionId

```
public Guid SessionId { get; set; }
```

Class SqliteCellUpdate

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteCellUpdate

```
public sealed class SqliteCellUpdate
```

🌟 Constructors 1

SqliteCellUpdate()

```
public SqliteCellUpdate()
```

🐾 Properties 2

ColumnName

```
public string ColumnName { get; set; }
```

Value

```
public string? Value { get; set; }
```

Class SqliteColumnSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteColumnSummary

Implements IEquatable < SqliteColumnSummary >

```
public sealed record SqliteColumnSummary : IEquatable<SqliteColumnSummary>
```

🌟 Constructors 1

SqliteColumnSummary(string, string, bool, bool, string?)

```
public SqliteColumnSummary(string Name, string Type, bool IsNotNull, bool IsPrimaryKey, string? DefaultValue)
```

🐾 Properties 5

DefaultValue

```
public string? DefaultValue { get; init; }
```

IsNotNull

```
public bool IsNotNull { get; init; }
```

IsPrimaryKey

```
public bool IsPrimaryKey { get; init; }
```

Name

```
public string Name { get; init; }
```

Type

```
public string Type { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out bool, out bool, out string?)

```
public void Deconstruct(out string Name, out string Type, out bool IsNotNull, out bool IsPrimaryKey, out string? DefaultValue)
```

Equals(SqliteColumnSummary?)

```
public bool Equals(SqliteColumnSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(SqliteColumnSummary?, SqliteColumnSummary?)

```
public static bool operator ==(SqliteColumnSummary? left, SqliteColumnSummary? right)
```

operator !=(SqliteColumnSummary?, SqliteColumnSummary?)

```
public static bool operator !=(SqliteColumnSummary? left, SqliteColumnSummary? right)
```

Class SQLiteEditorFieldOverride

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SQLiteEditorFieldOverride

```
public sealed class SQLiteEditorFieldOverride
```

🌟 Constructors 1

SQLiteEditorFieldOverride()

```
public SQLiteEditorFieldOverride()
```

🐾 Properties 10

ColumnName

```
[Required] [MaxLength(160)] public string ColumnName { get; set; }
```

EditorKind

```
[Required] [MaxLength(40)] public string EditorKind { get; set; }
```

FormatString

```
[MaxLength(160)] public string FormatString { get; set; }
```

Id

```
public Guid Id { get; set; }
```

InputMask

```
[MaxLength(240)] public string InputMask { get; set; }
```

IsSensitive

```
public bool IsSensitive { get; set; }
```

NullText

```
[MaxLength(120)] public string NullText { get; set; }
```

RequireHumanApproval

```
public bool RequireHumanApproval { get; set; }
```

TableName

```
[Required] [MaxLength(160)] public string TableName { get; set; }
```

UpdatedAtUtc

```
public DateTime UpdatedAtUtc { get; set; }
```

Class SqliteRowDeleteParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteRowDeleteParameters

```
public sealed class SqliteRowDeleteParameters
```

✨ Constructors 1

SqliteRowDeleteParameters()

```
public SqliteRowDeleteParameters()
```

🐾 Properties 2

RowId

```
public long RowId { get; set; }
```

TableName

```
public string TableName { get; set; }
```

Class SqliteRowSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteRowSnapshot

```
public sealed class SqliteRowSnapshot
```

✨ Constructors 1

SqliteRowSnapshot()

```
public SqliteRowSnapshot()
```

🐾 Properties 3

DisplayName

```
public string DisplayName { get; }
```

RowId

```
public long RowId { get; set; }
```

Values

```
public Dictionary<string, string?> Values { get; set; }
```

Class SqliteRowUpsertParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteRowUpsertParameters

```
public sealed class SqliteRowUpsertParameters
```

🌟 Constructors 1

SqliteRowUpsertParameters()

```
public SqliteRowUpsertParameters()
```

🐾 Properties 3

RowId

```
public long? RowId { get; set; }
```

TableName

```
public string TableName { get; set; }
```

Values

```
public Dictionary<string, string?> Values { get; set; }
```

Class SqliteTableReadParameters

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteTableReadParameters

```
public sealed class SqliteTableReadParameters
```

🌟 Constructors 1

SqliteTableReadParameters()

```
public SqliteTableReadParameters()
```

🐾 Properties 2

TableName

```
public string TableName { get; set; }
```

Take

```
public int Take { get; set; }
```

Class SQLiteTableSnapshot

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object SQLiteTableSnapshot

```
public sealed class SQLiteTableSnapshot
```

🌟 Constructors 1

SQLiteTableSnapshot()

```
public SQLiteTableSnapshot()
```

🐾 Properties 4

Columns

```
public List<SQLiteColumnSummary> Columns { get; set; }
```

DatabasePath

```
public string DatabasePath { get; set; }
```

Rows

```
public List<SQLiteRowSnapshot> Rows { get; set; }
```

TableName

```
public string TableName { get; set; }
```


Class SqliteTableSummary

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SqliteTableSummary

Implements IEquatable < SqliteTableSummary >

```
public sealed record SqliteTableSummary : IEquatable<SqliteTableSummary>
```

🌟 Constructors 1

SqliteTableSummary(string, int, long, bool)

```
public SqliteTableSummary(string Name, int ColumnCount, long RowCount, bool HasPrimaryKey)
```

🐾 Properties 4

ColumnCount

```
public int ColumnCount { get; init; }
```

HasPrimaryKey

```
public bool HasPrimaryKey { get; init; }
```

Name

```
public string Name { get; init; }
```

RowCount

```
public long RowCount { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out int, out long, out bool)

```
public void Deconstruct(out string Name, out int ColumnCount, out long RowCount, out bool HasPrimaryKey)
```

Equals(SqliteTableSummary?)

```
public bool Equals(SqliteTableSummary? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(SqliteTableSummary?, SqliteTableSummary?)

```
public static bool operator ==(SqliteTableSummary? left, SqliteTableSummary? right)
```

operator !=(SqliteTableSummary?, SqliteTableSummary?)

```
public static bool operator !=(SqliteTableSummary? left, SqliteTableSummary? right)
```

Class StartCouncilGameRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object StartCouncilGameRequest

```
public sealed class StartCouncilGameRequest
```

🌟 Constructors 1

StartCouncilGameRequest()

```
public StartCouncilGameRequest()
```

🐾 Properties 10

AutoplayDelayMilliseconds

```
public int AutoplayDelayMilliseconds { get; set; }
```

AutoplayEnabled

```
public bool AutoplayEnabled { get; set; }
```

ControlMode

```
public CouncilGameControlMode ControlMode { get; set; }
```

ConversationId

```
public Guid? ConversationId { get; set; }
```

CreatureDirectorCount

```
public int CreatureDirectorCount { get; set; }
```

DirectorMode

```
public CouncilGameDirectorMode DirectorMode { get; set; }
```

GameDirectorModelName

```
public string GameDirectorModelName { get; set; }
```

GameKey

```
public string GameKey { get; set; }
```

StartedBy

```
public string StartedBy { get; set; }
```

TeamKey

```
public string TeamKey { get; set; }
```

Class StructuredJsonCandidate

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object StructuredJsonCandidate

Implements IEquatable < StructuredJsonCandidate >

```
public sealed record StructuredJsonCandidate : IEquatable<StructuredJsonCandidate>
```

🌟 Constructors 1

StructuredJsonCandidate(int, int, string)

```
public StructuredJsonCandidate(int Start, int Length, string Json)
```

🐾 Properties 3

Json

```
public string Json { get; init; }
```

Length

```
public int Length { get; init; }
```

Start

```
public int Start { get; init; }
```

⚙️ Methods 5

Deconstruct(out int, out int, out string)

```
public void Deconstruct(out int Start, out int Length, out string Json)
```

Equals(StructuredJsonCandidate?)

```
public bool Equals(StructuredJsonCandidate? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(StructuredJsonCandidate?, StructuredJsonCandidate?)

```
public static bool operator ==(StructuredJsonCandidate? left, StructuredJsonCandidate? right)
```

operator !=(StructuredJsonCandidate?, StructuredJsonCandidate?)

```
public static bool operator !=(StructuredJsonCandidate? left, StructuredJsonCandidate? right)
```

Class StructuredJsonDocument

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object StructuredJsonDocument

```
public sealed class StructuredJsonDocument
```

🌟 Constructors 1

StructuredJsonDocument()

```
public StructuredJsonDocument()
```

🐾 Properties 6

Index

```
public int Index { get; set; }
```

Length

```
public int Length { get; set; }
```

Markdown

```
public string Markdown { get; set; }
```

NormalizedJson

```
public string NormalizedJson { get; set; }
```

RootKind

```
public string RootKind { get; set; }
```

StartIndex

```
public int StartIndex { get; set; }
```

Class StructuredJsonTranslationRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object StructuredJsonTranslationRequest

```
public sealed class StructuredJsonTranslationRequest
```

🌟 Constructors 1

StructuredJsonTranslationRequest()

```
public StructuredJsonTranslationRequest()
```

🐾 Properties 3

IncludeRawJson

```
public bool IncludeRawJson { get; set; }
```

MaximumDocuments

```
public int MaximumDocuments { get; set; }
```

Text

```
public string Text { get; set; }
```

Class StructuredJsonTranslationResult

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object StructuredJsonTranslationResult

```
public sealed class StructuredJsonTranslationResult
```

🌟 Constructors 1

StructuredJsonTranslationResult()

```
public StructuredJsonTranslationResult()
```

🐾 Properties 5

Documents

```
public List<StructuredJsonDocument> Documents { get; set; }
```

Status

```
public string Status { get; set; }
```

Succeeded

```
public bool Succeeded { get; set; }
```

TranslatedText

```
public string TranslatedText { get; set; }
```

Warnings

```
public List<string> Warnings { get; set; }
```

Class SubmitCouncilGameFrameRequest

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object SubmitCouncilGameFrameRequest

```
public sealed class SubmitCouncilGameFrameRequest
```

🌟 Constructors 1

SubmitCouncilGameFrameRequest()

```
public SubmitCouncilGameFrameRequest()
```

🐾 Properties 5

Caption

```
public string Caption { get; set; }
```

FrameText

```
public string FrameText { get; set; }
```

RendererName

```
public string RendererName { get; set; }
```

SessionId

```
public Guid SessionId { get; set; }
```

Turn

```
public long Turn { get; set; }
```

Class SystemVariable

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll
Inheritance object SystemVariable

```
public class SystemVariable
```

🌟 Constructors 1

SystemVariable()

```
public SystemVariable()
```

🐾 Properties 5

DataType

```
[MaxLength(32)] public string? DataType { get; set; }
```

Id

```
[Key] public int Id { get; set; }
```

LastUpdated

```
public DateTime LastUpdated { get; set; }
```

Name

```
[Required] [MaxLength(128)] public string Name { get; set; }
```

ValueString

```
[Required] public string ValueString { get; set; }
```

Class TestLabDownloadLink

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object TestLabDownloadLink

Implements IEquatable < TestLabDownloadLink >

```
public sealed record TestLabDownloadLink : IEquatable<TestLabDownloadLink>
```

🌟 Constructors 1

TestLabDownloadLink(string, string)

```
public TestLabDownloadLink(string Label, string AbsoluteUrl)
```

🐾 Properties 2

AbsoluteUrl

```
public string AbsoluteUrl { get; init; }
```

Label

```
public string Label { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string)

```
public void Deconstruct(out string Label, out string AbsoluteUrl)
```

Equals(TestLabDownloadLink?)

```
public bool Equals(TestLabDownloadLink? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(TestLabDownloadLink?, TestLabDownloadLink?)

```
public static bool operator ==(TestLabDownloadLink? left, TestLabDownloadLink? right)
```

operator !=(TestLabDownloadLink?, TestLabDownloadLink?)

```
public static bool operator !=(TestLabDownloadLink? left, TestLabDownloadLink? right)
```

Class TestLabRoute

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object TestLabRoute

Implements IEquatable < TestLabRoute >

```
public sealed record TestLabRoute : IEquatable<TestLabRoute>
```

🌟 Constructors 1

TestLabRoute(string, string, ButtonRenderStyle)

```
public TestLabRoute(string Label, string Path, ButtonRenderStyle Style)
```

🐾 Properties 3

Label

```
public string Label { get; init; }
```

Path

```
public string Path { get; init; }
```

Style

```
public ButtonRenderStyle Style { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out ButtonRenderStyle)

```
public void Deconstruct(out string Label, out string Path, out ButtonRenderStyle Style)
```

Equals(TestLabRoute?)

```
public bool Equals(TestLabRoute? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(TestLabRoute?, TestLabRoute?)

```
public static bool operator ==(TestLabRoute? left, TestLabRoute? right)
```

operator !=(TestLabRoute?, TestLabRoute?)

```
public static bool operator !=(TestLabRoute? left, TestLabRoute? right)
```


Class Theme

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object Theme

```
public sealed class Theme
```

🌟 Constructors 1

Theme(string, ITheme, bool, string?, string?, string?)

```
public Theme(string name, ITheme devExpressTheme, bool isBootstrapNative, string? title = null, string? bootstrapThemeMode = null, string? themePath = null)
```

🐾 Properties 7

BootstrapThemeMode

```
public string BootstrapThemeMode { get; }
```

DevExpressTheme

```
public ITheme DevExpressTheme { get; }
```

IconCssClass

```
public string IconCssClass { get; }
```

IsBootstrapNative

```
public bool IsBootstrapNative { get; }
```

Name

```
public string Name { get; }
```

ThemePath

```
public string ThemePath { get; }
```

Title

```
public string Title { get; }
```

⚙️ Methods 1

GetCssClass(bool)

```
public string GetCssClass(bool isActive)
```

Enum ThemeApplicationTarget

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

```
public enum ThemeApplicationTarget
```

Fields 1

Class ThemeFusionStep

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

One successful selection in the order-sensitive Theme Fusion route. The route is intentionally preserved because repeated theme swaps can create a visual result that is not described by the final Base Theme and Style Layer alone.

Inheritance object ThemeFusionStep

```
public sealed class ThemeFusionStep
```

Constructors 1

ThemeFusionStep(int, ThemeApplicationTarget, string)

```
public ThemeFusionStep(int sequence, ThemeApplicationTarget target, string themeName)
```

Properties 3

Sequence

```
public int Sequence { get; }
```

Target

```
public ThemeApplicationTarget Target { get; }
```

ThemeName

```
public string ThemeName { get; }
```

Class ThemeSet

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object ThemeSet

```
public sealed class ThemeSet
```

Constructors 1

ThemeSet(string, params Theme[])

```
public ThemeSet(string title, params Theme[] themes)
```

Properties 2

Themes

```
public Theme[] Themes { get; }
```

Title

```
public string Title { get; }
```

Class WorkspaceAccessPolicyRule

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object WorkspaceAccessPolicyRule

```
public sealed class WorkspaceAccessPolicyRule
```

🌟 Constructors 1

WorkspaceAccessPolicyRule()

```
public WorkspaceAccessPolicyRule()
```

🐾 Properties 7

CouncilMaintained

```
public bool CouncilMaintained { get; set; }
```

ExpectedEntryKind

```
public string ExpectedEntryKind { get; set; }
```

Name

```
public string Name { get; set; }
```

RelativePathRegex

```
public string RelativePathRegex { get; set; }
```

Required

```
public bool Required { get; set; }
```

RequiredAccess

```
public string RequiredAccess { get; set; }
```

Severity

```
public string Severity { get; set; }
```

Class WorkspaceContext

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object WorkspaceContext

Implements IEquatable < WorkspaceContext >

```
public sealed record WorkspaceContext : IEquatable<WorkspaceContext>
```

🌟 Constructors 1

WorkspaceContext(string, string, string, string, string, string, string, string, string, string, string, string)

```
public WorkspaceContext(string ProjectName, string ModId, string PackageName, string MainClassName, string ProjectRoot, string JavaRoot, string ResourceRoot, string AssetsRoot, string BuildFilePath, string MainClassPath, string MetadataPath, string ReadmePath)
```

🐾 Properties 12

AssetsRoot

```
public string AssetsRoot { get; init; }
```

BuildFilePath

```
public string BuildFilePath { get; init; }
```

JavaRoot

```
public string JavaRoot { get; init; }
```

MainClassName

```
public string MainClassName { get; init; }
```

MainClassPath

```
public string MainClassPath { get; init; }
```

MetadataPath

```
public string MetadataPath { get; init; }
```

ModId

```
public string ModId { get; init; }
```

PackageName

```
public string PackageName { get; init; }
```

ProjectName

```
public string ProjectName { get; init; }
```

ProjectRoot

```
public string ProjectRoot { get; init; }
```

ReadmePath

```
public string ReadmePath { get; init; }
```

ResourceRoot

```
public string ResourceRoot { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out string, out string, out string, out string, out string, out string, out string)

```
public void Deconstruct(out string ProjectName, out string ModId, out string PackageName, out string MainClassName, out string ProjectRoot, out string JavaRoot, out string ResourceRoot, out string AssetsRoot, out string BuildFilePath, out string MainClassPath, out string MetadataPath, out string ReadmePath)
```

Equals(WorkspaceContext?)

```
public bool Equals(WorkspaceContext? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(WorkspaceContext?, WorkspaceContext?)

```
public static bool operator ==(WorkspaceContext? left, WorkspaceContext? right)
```

operator !=(WorkspaceContext?, WorkspaceContext?)

```
public static bool operator !=(WorkspaceContext? left, WorkspaceContext? right)
```

api/LocalGPT.BusinessObjects.WorkspaceLayout.html

Class WorkspaceLayout

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object WorkspaceLayout

```
public sealed class WorkspaceLayout
```

🌟 Constructors 1

WorkspaceLayout(WorkspaceContext)

```
public WorkspaceLayout(WorkspaceContext context)
```

🐾 Properties 1

Context

```
public WorkspaceContext Context { get; }
```

⚙️ Methods 1

ToResult(string, string)

```
public MinecraftModWorkspace ToResult(string buildCommand = "powershell.exe -NoProfile -ExecutionPolicy Bypass -File .\\build-local.ps1", string eclipseImportHint = "File > Import > Gradle > Existing Gradle Project")
```

Class WorkspacePermissionAssessment

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object WorkspacePermissionAssessment

Implements IEquatable < WorkspacePermissionAssessment >

```
public sealed record WorkspacePermissionAssessment : IEquatable<WorkspacePermissionAssessment>
```

🌟 Constructors 1

WorkspacePermissionAssessment(Guid, string, DateTime, bool, bool, bool, string, Guid?, IReadOnlyList<string>, IReadOnlyList<WorkspacePermissionFinding>)

```
public WorkspacePermissionAssessment(Guid WorkspaceRootId, string Status, DateTime CheckedAtUtc, bool RootExists, bool ReadAccess, bool WriteAccess, string EnvironmentRootPath, Guid? PreferredCompilerInstallationId, IReadOnlyList<string> ExpectedSubdirectories, IReadOnlyList<WorkspacePermissionFinding> Findings)
```

🐾 Properties 10

CheckedAtUtc

```
public DateTime CheckedAtUtc { get; init; }
```

EnvironmentRootPath

```
public string EnvironmentRootPath { get; init; }
```

ExpectedSubdirectories

```
public IReadOnlyList<string> ExpectedSubdirectories { get; init; }
```

Findings

```
public IReadOnlyList<WorkspacePermissionFinding> Findings { get; init; }
```

PreferredCompilerInstallationId

```
public Guid? PreferredCompilerInstallationId { get; init; }
```

ReadAccess

```
public bool ReadAccess { get; init; }
```

RootExists

```
public bool RootExists { get; init; }
```

Status

```
public string Status { get; init; }
```

WorkspaceRootId

```
public Guid WorkspaceRootId { get; init; }
```

WriteAccess

```
public bool WriteAccess { get; init; }
```

⚙️ Methods 5

Deconstruct(out Guid, out string, out DateTime, out bool, out bool, out bool, out string, out Guid?, out IReadOnlyList<string>, out IReadOnlyList<WorkspacePermissionFinding>)

```
public void Deconstruct(out Guid WorkspaceRootId, out string Status, out DateTime CheckedAtUtc, out bool RootExists, out bool ReadAccess, out bool WriteAccess, out string EnvironmentRootPath, out Guid? PreferredCompilerInstallationId, out IReadOnlyList<string> ExpectedSubdirectories, out IReadOnlyList<WorkspacePermissionFinding> Findings)
```

Equals WorkspacePermissionAssessment?

```
public bool Equals WorkspacePermissionAssessment? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

Operators 2

operator ==(WorkspacePermissionAssessment?, WorkspacePermissionAssessment?)

```
public static bool operator ==(WorkspacePermissionAssessment? left, WorkspacePermissionAssessment? right)
```

operator !=(WorkspacePermissionAssessment?, WorkspacePermissionAssessment?)

```
public static bool operator !=(WorkspacePermissionAssessment? left, WorkspacePermissionAssessment? right)
```

Class WorkspacePermissionFinding

Namespace LocalGPT . BusinessObjects Assembly LocalGPT.dll

Inheritance object WorkspacePermissionFinding

Implements IEquatable < WorkspacePermissionFinding >

```
public sealed record WorkspacePermissionFinding : IEquatable<WorkspacePermissionFinding>
```

🌟 Constructors 1

WorkspacePermissionFinding(string, string, string, string)

```
public WorkspacePermissionFinding(string Severity, string Code, string Message, string RelativePath = "")
```

🐾 Properties 4

Code

```
public string Code { get; init; }
```

Message

```
public string Message { get; init; }
```

RelativePath

```
public string RelativePath { get; init; }
```

Severity

```
public string Severity { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string)

```
public void Deconstruct(out string Severity, out string Code, out string Message, out string RelativePath)
```

Equals(WorkspacePermissionFinding?)

```
public bool Equals(WorkspacePermissionFinding? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

⚡ Operators 2

operator ==(WorkspacePermissionFinding?, WorkspacePermissionFinding?)

```
public static bool operator ==(WorkspacePermissionFinding? left, WorkspacePermissionFinding? right)
```

operator !=(WorkspacePermissionFinding?, WorkspacePermissionFinding?)

```
public static bool operator !=(WorkspacePermissionFinding? left, WorkspacePermissionFinding? right)
```


Class _Imports

Namespace LocalGPT . Components Assembly LocalGPT.dll

Inheritance object _Imports

```
public class _Imports
```

🌟 Constructors 1

_Imports()

```
public _Imports()
```

⚙️ Methods 1

Execute()

```
protected void Execute()
```

Class App

Namespace LocalGPT . Components Assembly LocalGPT.dll

Inheritance object ComponentBase App

Implements IComponent IHandleEvent IHandleAfterRender

```
public class App : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

App()

```
public App()
```

⚙️ Methods 1

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Namespace LocalGPT.Components

Namespaces

Classes

Class InteractiveStartupMarker

Namespace LocalGPT . Components Assembly LocalGPT.dll

Inheritance object ComponentBase InteractiveStartupMarker

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class InteractiveStartupMarker : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

InteractiveStartupMarker()

```
public InteractiveStartupMarker()
```

⚙️ Methods 4

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

ReportJavaScriptErrorAsync(string, string, string)

```
[JSInvokable] public Task ReportJavaScriptErrorAsync(string context, string message, string stack)
```

Class CouncilSpoolerPanel

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase CouncilSpoolerPanel

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class CouncilSpoolerPanel : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

CouncilSpoolerPanel()

```
public CouncilSpoolerPanel()
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnInitialized()

```
protected override void OnInitialized()
```

Class Drawer

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase LayoutComponentBase Drawer

Implements IComponent IHandleEvent IHandleAfterRender

```
public class Drawer : LayoutComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Drawer()

```
public Drawer()
```

🐾 Properties 7

CssClass

```
[Parameter] public string CssClass { get; set; }
```

DrawerBody

```
[Parameter] public RenderFragment? DrawerBody { get; set; }
```

DrawerFooter

```
[Parameter] public RenderFragment? DrawerFooter { get; set; }
```

DrawerHeader

```
[Parameter] public RenderFragment? DrawerHeader { get; set; }
```

DrawerTarget

```
[Parameter] public RenderFragment? DrawerTarget { get; set; }
```

ToggledSidebar

```
[SupplyParameterFromQuery(Name = "toggledSidebar")] public bool ToggledSidebar { get; set; }
```

Width

```
[Parameter] public string Width { get; set; }
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

OnParametersSet()

```
protected override void OnParametersSet()
```

Namespace LocalGPT.Components.Layout

Classes

Bridges LocalGPT's independently selectable shell and DevExpress component themes to the browser. Browser persistence is owned by the JavaScript module; DevExpress remains the owner of component theme resources.

Class HumanCollaborationInbox

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase HumanCollaborationInbox

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class HumanCollaborationInbox : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

HumanCollaborationInbox()

```
public HumanCollaborationInbox()
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class MainLayout

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase LayoutComponentBase MainLayout

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class MainLayout : LayoutComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

MainLayout()

```
public MainLayout()
```

🔗 Properties 1

ToggledSidebar

```
[SupplyParameterFromQuery(Name = "toggledSidebar")] public bool ToggledSidebar { get; set; }
```

⚙️ Methods 4

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnInitialized()

```
protected override void OnInitialized()
```

OnParametersSet()

```
protected override void OnParametersSet()
```

Class MenuIsland

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase MenuIsland

Implements IComponent IHandleEvent IHandleAfterRender

```
public class MenuIsland : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

MenuIsland()

```
public MenuIsland()
```

⚙️ Methods 1

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Class NavMenu

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase NavMenu

Implements IComponent IHandleEvent IHandleAfterRender

```
public class NavMenu : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

NavMenu()

```
public NavMenu()
```

⚙️ Methods 1

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Class SafeErrorBoundary

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase SafeErrorBoundary

Implements IComponent IHandleEvent IHandleAfterRender

```
public class SafeErrorBoundary : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

SafeErrorBoundary()

```
public SafeErrorBoundary()
```

🐾 Properties 3

Area

```
[Parameter] public string Area { get; set; }
```

ChildContent

```
[Parameter] [EditorRequired] public RenderFragment? ChildContent { get; set; }
```

ToastName

```
[Parameter] public string ToastName { get; set; }
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Recover()

```
public void Recover()
```

Class ThemeJsChangeDispatcher

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Bridges LocalGPT's independently selectable shell and DevExpress component themes to the browser. Browser persistence is owned by the JavaScript module; DevExpress remains the owner of component theme resources.

Inheritance object ComponentBase ThemeJsChangeDispatcher

Implements IComponent IHandleEvent IHandleAfterRender IThemeChangeRequestDispatcher IAsyncDisposable IDisposable

```
public sealed class ThemeJsChangeDispatcher : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IThemeChangeRequestDispatcher,
    IAsyncDisposable, IDisposable
```

🌟 Constructors 1

ThemeJsChangeDispatcher()

```
public ThemeJsChangeDispatcher()
```

🐾 Properties 2

InitialComponentThemeName

```
[Parameter] public required string InitialComponentThemeName { get; set; }
```

InitialShellThemeName

```
[Parameter] public required string InitialShellThemeName { get; set; }
```

⚙️ Methods 4

DisposeAsync()

```
public ValueTask DisposeAsync()
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

RequestThemeChangeAsync(Theme, ThemeApplicationTarget)

```
public Task RequestThemeChangeAsync(Theme theme, ThemeApplicationTarget target)
```

ResetFusionRouteAsync()

```
public Task ResetFusionRouteAsync()
```

Class ThemeSwitcher

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase ThemeSwitcher

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class ThemeSwitcher : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

ThemeSwitcher()

```
public ThemeSwitcher()
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnInitialized()

```
protected override void OnInitialized()
```

Class ThemeSwitcherContainer

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase ThemeSwitcherContainer

Implements IComponent IHandleEvent IHandleAfterRender IDisposable IThemeLoadNotifier

```
public class ThemeSwitcherContainer : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable, IThemeLoadNotifier
```

🌟 Constructors 1

ThemeSwitcherContainer()

```
public ThemeSwitcherContainer()
```

🐾 Properties 6

ComponentThemeName

```
[Parameter] public string? ComponentThemeName { get; set; }
```

ComponentThemeNameChanged

```
[Parameter] public EventCallback<string> ComponentThemeNameChanged { get; set; }
```

ShellThemeName

```
[Parameter] public string? ShellThemeName { get; set; }
```

ShellThemeNameChanged

```
[Parameter] public EventCallback<string> ShellThemeNameChanged { get; set; }
```

Shown

```
[Parameter] public bool Shown { get; set; }
```

ShownChanged

```
[Parameter] public EventCallback<bool> ShownChanged { get; set; }
```

⚙️ Methods 4

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

NotifyThemeLoadedAsync(Theme, ThemeApplicationTarget)

```
public Task NotifyThemeLoadedAsync(Theme theme, ThemeApplicationTarget target)
```

OnAfterRender(bool)

```
protected override void OnAfterRender(bool firstRender)
```

OnInitialized()

```
protected override void OnInitialized()
```


Class ThemeSwitcherItem

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase ThemeSwitcherItem

Implements IComponent IHandleEvent IHandleAfterRender

```
public class ThemeSwitcherItem : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

ThemeSwitcherItem()

```
public ThemeSwitcherItem()
```

🐾 Properties 3

Click

```
[Parameter] public EventCallback<Theme> Click { get; set; }
```

IsActive

```
[Parameter] public bool IsActive { get; set; }
```

Theme

```
[Parameter] public Theme? Theme { get; set; }
```

⚙️ Methods 1

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Class ToastWrapper

Namespace LocalGPT . Components . Layout Assembly LocalGPT.dll

Inheritance object ComponentBase ToastWrapper

Implements IComponent IHandleEvent IHandleAfterRender

```
public class ToastWrapper : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

ToastWrapper()

```
public ToastWrapper()
```

🐾 Properties 9

AnimationType

```
[Parameter] public ToastAnimationType AnimationType { get; set; }
```

DisplayTime

```
[Parameter] public TimeSpan DisplayTime { get; set; }
```

HorizontalAlignment

```
[Parameter] public HorizontalAlignment HorizontalAlignment { get; set; }
```

Name

```
[Parameter] public string Name { get; set; }
```

ShowCloseButton

```
[Parameter] public bool ShowCloseButton { get; set; }
```

ShowIcon

```
[Parameter] public bool ShowIcon { get; set; }
```

SizeMode

```
[Parameter] public SizeMode? SizeMode { get; set; }
```

ThemeMode

```
[Parameter] public ToastThemeMode ThemeMode { get; set; }
```

VerticalAlignment

```
[Parameter] public VerticalEdge VerticalAlignment { get; set; }
```

⚙️ Methods 1

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Class Chat

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Chat

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
[Route("/chat")] public class Chat : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

Chat()

```
public Chat()
```

🐾 Properties 6

AutoStartCouncilStarter

```
[Parameter] [SupplyParameterFromQuery(Name = "autoStartCouncil")] public bool AutoStartCouncilStarter { get; set; }
```

RequestedCouncilStarterKey

```
[Parameter] [SupplyParameterFromQuery(Name = "starter")] public string? RequestedCouncilStarterKey { get; set; }
```

RequestedCouncilTeamKey

```
[Parameter] [SupplyParameterFromQuery(Name = "team")] public string? RequestedCouncilTeamKey { get; set; }
```

RequestedModelPresetName

```
[Parameter] [SupplyParameterFromQuery(Name = "preset")] public string? RequestedModelPresetName { get; set; }
```

RequestedRejoinCouncilRunId

```
[Parameter] [SupplyParameterFromQuery(Name = "rejoinCouncilRunId")] public Guid? RequestedRejoinCouncilRunId { get; set; }
```

StartNewCouncilChat

```
[Parameter] [SupplyParameterFromQuery(Name = "newCouncil")] public bool StartNewCouncilChat { get; set; }
```

⚙️ Methods 6

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

QueueLiveCouncilUserMessageAsync(string)

```
[JSInvokable] public Task<bool> QueueLiveCouncilUserMessageAsync(string content)
```

StopActiveCouncilRunAsync()

```
[JSInvokable] public Task<bool> StopActiveCouncilRunAsync()
```

Class CouncilTeams

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase CouncilTeams

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/council-teams")] public class CouncilTeams : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

CouncilTeams()

```
public CouncilTeams()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class Database

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Database

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/database")] public class Database : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Database()

```
public Database()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class DxFunctionCatalog

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase DxFunctionCatalog

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/dx-functions")] public class DxFunctionCatalog : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

DxFunctionCatalog()

```
public DxFunctionCatalog()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class Error

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Error

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/Error")] public class Error : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Error()

```
public Error()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitialized()

```
protected override void OnInitialized()
```

Class Help

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Help

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/help")] public class Help : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Help()

```
public Help()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitialized()

```
protected override void OnInitialized()
```

Namespace LocalGPT.Components.Pages

Classes

Class Index

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Index

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/")] public class Index : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Index()

```
public Index()
```

🐾 Properties 1

ToggledSidebar

```
[SupplyParameterFromQuery(Name = "toggledSidebar")] public bool ToggledSidebar { get; set; }
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

Loads the first-run guide and bounded loopback model-discovery state before rendering the page.

```
protected override Task OnInitializedAsync()
```

Class Install

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Install

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/install")] public class Install : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Install()

```
public Install()
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

OnInitialized()

```
protected override void OnInitialized()
```

Class MinecraftModBuilder

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase MinecraftModBuilder

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/minecraft-mod-builder")] public class MinecraftModBuilder : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

MinecraftModBuilder()

```
public MinecraftModBuilder()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class ModelCouncil

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase ModelCouncil

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/model-council")] public class ModelCouncil : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

ModelCouncil()

```
public ModelCouncil()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class OneWireSecurity

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase OneWireSecurity

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
[Route("/onewire-security")] public class OneWireSecurity : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

OneWireSecurity()

```
public OneWireSecurity()
```

⚙️ Methods 4

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

OnInitialized()

```
protected override void OnInitialized()
```


Class ProjectMaintenance

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase ProjectMaintenance

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/project-maintenance")] public class ProjectMaintenance : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

ProjectMaintenance()

```
public ProjectMaintenance()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class Projects

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase Projects

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/projects")] public class Projects : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

Projects()

```
public Projects()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class TestLab

Namespace LocalGPT . Components . Pages Assembly LocalGPT.dll

Inheritance object ComponentBase TestLab

Implements IComponent IHandleEvent IHandleAfterRender

```
[Route("/test-lab")] public class TestLab : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

TestLab()

```
public TestLab()
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

Class Routes

Namespace LocalGPT . Components Assembly LocalGPT.dll

Inheritance object ComponentBase Routes

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class Routes : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

Routes()

```
public Routes()
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnInitialized()

```
protected override void OnInitialized()
```

Class ChatGameConsole

Namespace LocalGPT . Components . Shared Assembly LocalGPT.dll

Inheritance object ComponentBase ChatGameConsole

Implements IComponent IHandleEvent IHandleAfterRender IAsyncDisposable

```
public class ChatGameConsole : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IAsyncDisposable
```

🌟 Constructors 1

ChatGameConsole()

```
public ChatGameConsole()
```

🐾 Properties 3

CloseRequested

```
[Parameter] public EventCallback CloseRequested { get; set; }
```

ConversationId

```
[Parameter] public Guid? ConversationId { get; set; }
```

SuggestedTeamKey

```
[Parameter] public string SuggestedTeamKey { get; set; }
```

⚙️ Methods 6

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

DisposeAsync()

```
public ValueTask DisposeAsync()
```

OnAfterRenderAsync(bool)

```
protected override Task OnAfterRenderAsync(bool firstRender)
```

OnInitializedAsync()

```
protected override Task OnInitializedAsync()
```

OnParametersSetAsync()

```
protected override Task OnParametersSetAsync()
```

SubmitControlFromJs(string)

```
[JSInvokable] public Task SubmitControlFromJs(string action)
```

Class CouncilHardwareRoadEditor

Namespace LocalGPT . Components . Shared Assembly LocalGPT.dll

Inheritance object ComponentBase CouncilHardwareRoadEditor

Implements IComponent IHandleEvent IHandleAfterRender

```
public class CouncilHardwareRoadEditor : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender
```

🌟 Constructors 1

CouncilHardwareRoadEditor()

```
public CouncilHardwareRoadEditor()
```

🐾 Properties 4

Changed

```
[Parameter] public EventCallback Changed { get; set; }
```

ModelNames

```
[Parameter] public IReadOnlyCollection<string> ModelNames { get; set; }
```

ResourceLoadPercent

```
[Parameter] public int ResourceLoadPercent { get; set; }
```

Routes

```
[Parameter] [EditorRequired] public List<OneWireCouncilModelRoute> Routes { get; set; }
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

OnParametersSet()

```
protected override void OnParametersSet()
```

Namespace LocalGPT.Components.Shared

Classes

Class ProviderModelBenchmarkCouncilPanel

Namespace LocalGPT . Components . Shared Assembly LocalGPT.dll

Inheritance object ComponentBase ProviderModelBenchmarkCouncilPanel

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class ProviderModelBenchmarkCouncilPanel : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

ProviderModelBenchmarkCouncilPanel()

```
public ProviderModelBenchmarkCouncilPanel()
```

🐾 Properties 2

BenchmarkApplied

```
[Parameter] public EventCallback<ProviderModelBenchmarkBatchAppliedEvent> BenchmarkApplied { get; set; }
```

Models

```
[Parameter] public IReadOnlyList<ProviderModelReference> Models { get; set; }
```

⚙️ Methods 3

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

OnParametersSet()

```
protected override void OnParametersSet()
```

Class ProviderModelPanel

Namespace LocalGPT . Components . Shared Assembly LocalGPT.dll

Inheritance object ComponentBase ProviderModelPanel

Implements IComponent IHandleEvent IHandleAfterRender IDisposable

```
public class ProviderModelPanel : ComponentBase, IComponent, IHandleEvent, IHandleAfterRender, IDisposable
```

🌟 Constructors 1

ProviderModelPanel()

```
public ProviderModelPanel()
```

🐾 Properties 9

Activated

```
[Parameter] public EventCallback<ProviderModelReference> Activated { get; set; }
```

BenchmarkApplied

```
[Parameter] public EventCallback<ProviderModelBenchmarkAppliedEvent> BenchmarkApplied { get; set; }
```

CouncilModels

```
[Parameter] public IReadOnlyList<ProviderModelReference> CouncilModels { get; set; }
```

Model

```
[Parameter] [EditorRequired] public ProviderModelReference Model { get; set; }
```

Selected

```
[Parameter] public bool Selected { get; set; }
```

SelectedChanged

```
[Parameter] public EventCallback<bool> SelectedChanged { get; set; }
```

ShowSelection

```
[Parameter] public bool ShowSelection { get; set; }
```

ShowUseAction

```
[Parameter] public bool ShowUseAction { get; set; }
```

UseActionText

```
[Parameter] public string UseActionText { get; set; }
```

⚙️ Methods 2

BuildRenderTree(RenderTreeBuilder)

```
protected override void BuildRenderTree(RenderTreeBuilder __builder)
```

Dispose()

```
public void Dispose()
```

Class ChatController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase ChatController

```
public class ChatController : ControllerBase
```

🌟 Constructors 1

ChatController(IRegexPatternService, ILogger<ChatController>)

```
public ChatController(IRegexPatternService regexSvc, ILogger<ChatController> logger)
```

⚙️ Methods 1

GetHelpMessage()

```
[HttpGet("help-message")] public Task<IActionResult> GetHelpMessage()
```

Class CodeGenerationController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase CodeGenerationController

```
[ApiController] [Route("api/code-generation/reviews")] public sealed class CodeGenerationController : ControllerBase
```

🌟 Constructors 1

CodeGenerationController(ICodeGenerationWorkflowService, ILogger<CodeGenerationController>)

```
public CodeGenerationController(ICodeGenerationWorkflowService workflow, ILogger<CodeGenerationController> logger)
```

⚙️ Methods 5

CreateReview(CreateCodeGenerationReviewRequest, bool, CancellationTokens)

```
[HttpPost] [HumanApprovalRequired("code-generation.review.create", "Store exact code-generation review", "Persist the submitted reviewed change plan so the human can inspect its files, outputs, hashes, and safety summary before execution.", "Medium", "Code review coordinator", false)] public Task<IResult> CreateReview(CreateCodeGenerationReviewRequest request, bool userConfirmed, CancellationTokens cancellationTokens)
```

ExecuteReview(Guid, ExecuteCodeGenerationReviewRequest, CancellationTokens)

```
[HttpPost("{reviewId:guid}/execute")] [HumanApprovalRequired("code-generation.review.execute", "Execute exact code-generation review", "Generate the exact hash-bound reviewed files and, when requested by this same input, run the bounded build inside the isolated artifact workspace.", "High", "Code-generation security reviewer", true)] public Task<IResult> ExecuteReview(Guid reviewId, ExecuteCodeGenerationReviewRequest request, CancellationTokens cancellationTokens)
```

GetReview(Guid, CancellationTokens)

```
[HttpGet("{reviewId:guid}")] public Task<IResult> GetReview(Guid reviewId, CancellationTokens cancellationTokens)
```

ListReviews(Guid?, int, CancellationTokens)

```
[HttpGet] public Task<IResult> ListReviews(Guid? projectId, int take = 20, CancellationTokens cancellationTokens = default)
```

RejectReview(Guid, RejectCodeGenerationReviewRequest, CancellationTokens)

```
[HttpPost("{reviewId:guid}/reject")] public Task<IResult> RejectReview(Guid reviewId, RejectCodeGenerationReviewRequest request, CancellationTokens cancellationTokens)
```

Class CompleteFirstRunOnboardingRequest

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Carries the explicit confirmation required to dismiss first-run onboarding.

Inheritance object CompleteFirstRunOnboardingRequest

```
[DocumentationUpdated("2.1.20")] public sealed class CompleteFirstRunOnboardingRequest
```

🌟 Constructors 1

CompleteFirstRunOnboardingRequest()

```
public CompleteFirstRunOnboardingRequest()
```

🐾 Properties 1

UserConfirmed

Gets or sets whether the current user explicitly confirmed completion.

```
public bool UserConfirmed { get; set; }
```

Class CouncilGameController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase CouncilGameController

```
[ApiController] [Route("api/council/games")] public sealed class CouncilGameController : ControllerBase
```

🌟 Constructors 1

CouncilGameController(ICouncilGameSessionService, ILogger<CouncilGameController>)

```
public CouncilGameController(ICouncilGameSessionService games, ILogger<CouncilGameController> logger)
```

⚙️ Methods 8

Control(CouncilGameControlRequest, CancellationToken)

```
[HttpPost("control")] public Task<ActionResult<CouncilGameSessionSnapshot>> Control(CouncilGameControlRequest request, CancellationTokencancellationToken)
```

ControlMode(SetCouncilGameControlModeRequest, CancellationToken)

```
[HttpPost("control-mode")] public Task<ActionResult<CouncilGameSessionSnapshot>> ControlMode(SetCouncilGameControlModeRequest request, CancellationTokencancellationToken)
```

Frame(SubmitCouncilGameFrameRequest, CancellationToken)

```
[HttpPost("frame")] public Task<ActionResult<CouncilGameSessionSnapshot>> Frame(SubmitCouncilGameFrameRequest request, CancellationTokencancellationToken)
```

Get(Guid, CancellationToken)

```
[HttpGet("{sessionId:guid}")] public Task<ActionResult<CouncilGameSessionSnapshot>> Get(Guid sessionId, CancellationTokencancellationToken)
```

InputGate(SetCouncilGameInputGateRequest, CancellationToken)

```
[HttpPost("input-gate")] public Task<ActionResult<CouncilGameSessionSnapshot>> InputGate(SetCouncilGameInputGateRequest request, CancellationTokencancellationToken)
```

List(bool, CancellationToken)

```
[HttpGet] public Task<ActionResult<IReadOnlyList<CouncilGameSessionSnapshot>>> List(bool includeCompleted, CancellationTokencancellationToken)
```

PreviewControl(CouncilGameControlRequest, CancellationToken)

```
[HttpPost("control/preview")] public Task<ActionResult<CouncilGameDirectorDecision>> PreviewControl(CouncilGameControlRequest request, CancellationTokencancellationToken)
```

Start(StartCouncilGameRequest, CancellationToken)

```
[HttpPost("start")] public Task<ActionResult<CouncilGameSessionSnapshot>> Start(StartCouncilGameRequest request, CancellationTokencancellationToken)
```


Class CouncilRuntimeClassesController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase CouncilRuntimeClassesController

```
[ApiController] [Route("api/council/runtime-classes")] public sealed class CouncilRuntimeClassesController : ControllerBase
```

🌟 Constructors 1

CouncilRuntimeClassesController(ICouncilRuntimeClassService, ILogger<CouncilRuntimeClassesController>)

```
public CouncilRuntimeClassesController(ICouncilRuntimeClassService runtimeClasses, ILogger<CouncilRuntimeClassesController> logger)
```

⚙️ Methods 3

Get(string, CancellationToken)

```
[HttpGet("{key}")] public Task<ActionResult<CouncilRuntimeClassDefinition>> Get(string key, CancellationToken cancellationToken)
```

GetAll(bool, CancellationToken)

```
[HttpGet] public Task<ActionResult<IReadOnlyList<CouncilRuntimeClassDefinition>>> GetAll(bool includeDisabled, CancellationToken cancellationToken)
```

Save(SaveCouncilRuntimeClassRequest, CancellationToken)

```
[HttpPost] [HumanApprovalRequired("council.runtime-class.save", "Save Council runtime class", "Persist the reviewed runtime class fields, input ownership, keyboard/gamepad bindings, source references and recommended DXFunctions.", "High", "Runtime class reviewer", false)] public Task<ActionResult<CouncilRuntimeClassDefinition>> Save(SaveCouncilRuntimeClassRequest request, CancellationToken cancellationToken)
```

Class DatabaseKnowledgeController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase DatabaseKnowledgeController

```
[ApiController] [Route("__diag/knowledge/{controller}")] public class DatabaseKnowledgeController : ControllerBase
```

🌟 Constructors 1

DatabaseKnowledgeController(LocalGptMemoryDbContext, ILogger<DatabaseKnowledgeController>)

```
public DatabaseKnowledgeController(LocalGptMemoryDbContext db, ILogger<DatabaseKnowledgeController> logger)
```

⚙️ Methods 2

GetConfigById(int)

```
[HttpGet("configs/{id:int}")] public Task<IActionResult> GetConfigById(int id)
```

ListConfigs(int)

```
[HttpGet("configs")] public Task<IActionResult> ListConfigs(int take = 100)
```

Class DatabaseQueryController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase DatabaseQueryController

```
[ApiController] [Route("__diag/database/[controller]")] public class DatabaseQueryController : ControllerBase
```

🌟 Constructors 1

DatabaseQueryController(LocalGptMemoryDbContext, ILogger<DatabaseQueryController>)

```
public DatabaseQueryController(LocalGptMemoryDbContext db, ILogger<DatabaseQueryController> logger)
```

⚙️ Methods 2

ListConfigs()

```
[HttpGet("configs")] public Task<IActionResult> ListConfigs()
```

QueryDatabase(string, int)

```
[HttpGet("query")] public Task<IActionResult> QueryDatabase(string table, int take = 100)
```

Class DocumentationController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Exposes availability metadata, searchable XML comments and the versioned PDF produced by the DocFX build pipeline.

Inheritance object ControllerBase DocumentationController

```
[ApiController] [Route("api/documentation")] [DocumentationUpdated("2.2.8")] public sealed class DocumentationController : ControllerBase
```

🌟 Constructors 1

DocumentationController(IDocumentationCatalogService, ILogger<DocumentationController>)

Exposes availability metadata, searchable XML comments and the versioned PDF produced by the DocFX build pipeline.

```
public DocumentationController(IDocumentationCatalogService documentation, ILogger<DocumentationController> logger)
```

⚙️ Methods 5

Comment(string, string?)

Returns one localized XML documentation member by its compiler member id.

```
[HttpGet("comment")] public ActionResult<LocalGptDocumentationComment> Comment(string memberId, string? culture = null)
```

Comments(string?, int, string?)

Searches localized compiler-generated XML comments by member id, summary or remarks.

```
[HttpGet("comments")] public ActionResult<IReadOnlyList<LocalGptDocumentationComment>> Comments(string? query = null, int limit = 100, string? culture = null)
```

Html(string?)

Serves generated DocFX HTML and supporting assets from the recursively resolved installed documentation root.

```
[HttpGet("/help-docs")] [HttpGet("/help-docs/{**relativePath}")] public IActionResult Html(string? relativePath = null)
```

Pdf()

Downloads the versioned LocalGPT PDF generated for the running build.

```
[HttpGet("pdf")] public IActionResult Pdf()
```

Status()

Returns the current generated-documentation and XML-comment availability.

```
[HttpGet("status")] public ActionResult<LocalGptDocumentationStatus> Status()
```

Class DxAiFunctionCatalogController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

User-owned catalog for deciding which LocalGPT DX functions and public service methods are visible to AI chat or securely linked 1-Wire peers.

Inheritance object ControllerBase DxAiFunctionCatalogController

```
[ApiController] [Route("api/dxai/catalog")] public sealed class DxAiFunctionCatalogController : ControllerBase
```

🌟 Constructors 1

DxAiFunctionCatalogController(IDxAiFunctionCatalogService, ILogger<DxAiFunctionCatalogController>)

User-owned catalog for deciding which LocalGPT DX functions and public service methods are visible to AI chat or securely linked 1-Wire peers.

```
public DxAiFunctionCatalogController(IDxAiFunctionCatalogService catalog, ILogger<DxAiFunctionCatalogController> logger)
```

⚙️ Methods 3

GetAsync(CancellationToken)

```
[HttpGet] public Task<IResult> GetAsync(CancellationToken cancellationToken)
```

SavePolicyAsync(DxAiFunctionCatalogSaveRequest, CancellationToken)

```
[HttpPut("policy")] public Task<IResult> SavePolicyAsync(DxAiFunctionCatalogSaveRequest request, CancellationToken cancellationToken)
```

SynchronizeAsync(CancellationToken)

```
[HttpPost("synchronize")] public Task<IResult> SynchronizeAsync(CancellationToken cancellationToken)
```

Class DxAiFunctionsController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase DxAiFunctionsController

```
[ApiController] [Route("api/dxai/functions")] public sealed class DxAiFunctionsController : ControllerBase
```

🌟 Constructors 1

DxAiFunctionsController(IDxAiFunctionServiceClient, ILogger<DxAiFunctionsController>)

```
public DxAiFunctionsController(IDxAiFunctionServiceClient functionClient, ILogger<DxAiFunctionsController> logger)
```

⚙️ Methods 2

InvokeFunction(string, DxAiFunctionInvocationRequest, CancellationToken)

```
[HttpPost("{functionName}/invoke")] public Task<IResult> InvokeFunction(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken)
```

ListFunctions()

```
[HttpGet] public IResult ListFunctions()
```

Class EmbeddedWorkbenchController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase EmbeddedWorkbenchController

```
[ApiController] [Route("api/embedded")] public sealed class EmbeddedWorkbenchController : ControllerBase
```

🌟 Constructors 1

EmbeddedWorkbenchController(IEmbeddedHardwareCatalogService, IEmbeddedWiringService, IEmbeddedFirmwarePlanningService, IEmbeddedTelemetryBridgeService, IEmbeddedTelemetryIngressService, ILogger<EmbeddedWorkbenchController>)

```
public EmbeddedWorkbenchController(IEmbeddedHardwareCatalogService catalog, IEmbeddedWiringService wiring, IEmbeddedFirmwarePlanningService planning, IEmbeddedTelemetryBridgeService telemetryBridge, IEmbeddedTelemetryIngressService telemetryIngress, ILogger<EmbeddedWorkbenchController> logger)
```

⚙️ Methods 13

CreateFirmwareArtifacts(EmbeddedFirmwarePlanRequest, bool, CancellationToken)

```
[HttpPost("firmware/artifacts")] [HumanApprovalRequired("embedded.firmware.artifacts.create", "Create embedded firmware artifacts", "Write the reviewed sketch, PlatformIO configuration, wiring contract and plan archive. No compiler or flashing tool is executed.", "High", "Embedded firmware reviewer", false)] public Task<IResult> CreateFirmwareArtifacts(EmbeddedFirmwarePlanRequest request, bool userConfirmed, CancellationToken cancellationToken)
```

CreateFirmwarePlan(EmbeddedFirmwarePlanRequest, CancellationToken)

```
[HttpPost("firmware/plan")] public Task<IResult> CreateFirmwarePlan(EmbeddedFirmwarePlanRequest request, CancellationToken cancellationToken)
```

CreateWiringDraft(EmbeddedWiringDraftCreateRequest, CancellationToken)

```
[HttpPost("wiring/drafts")] public Task<IResult> CreateWiringDraft(EmbeddedWiringDraftCreateRequest request, CancellationToken cancellationToken)
```

GetBoard(string, CancellationToken)

```
[HttpGet("boards/{boardProfileKey}")] public Task<IResult> GetBoard(string boardProfileKey, CancellationToken cancellationToken)
```

GetBoards(CancellationToken)

```
[HttpGet("boards")] public Task<IResult> GetBoards(CancellationToken cancellationToken)
```

GetCatalog(CancellationToken)

```
[HttpGet("catalog")] public Task<IResult> GetCatalog(CancellationToken cancellationToken)
```

GetProtocols(CancellationToken)

```
[HttpGet("protocols")] public Task<IResult> GetProtocols(CancellationToken cancellationToken)
```

GetPublisherWorkbenchContract()

```
[HttpGet("publisher-workbench-contract")] public IResult GetPublisherWorkbenchContract()
```

GetRecentTelemetry(string?, int)

```
[HttpGet("telemetry/recent")] public IResult GetRecentTelemetry(string? deviceId, int maximum = 100)
```

PreviewOneWireEnvelope(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
[HttpPost("telemetry/onewire-envelope")] public Task<IResult> PreviewOneWireEnvelope(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken)
```

PreviewTelemetry(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
[HttpPost("telemetry/preview")] public Task<IResult> PreviewTelemetry(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken)
```

PublishTelemetry(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
[HttpPost("telemetry/ingress")] public Task<IResult> PublishTelemetry(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken)
```

ValidateWiring(EmbeddedWiringValidationRequest, CancellationToken)

```
[HttpPost("wiring/validate")] public Task<IResult> ValidateWiring(EmbeddedWiringValidationRequest request, CancellationToken cancellationToken)
```

Class FeaturePersistenceController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

CRUD API for durable records owned by newer LocalGPT feature modules.

Inheritance object ControllerBase FeaturePersistenceController

```
[ApiController] [Route("api/feature-persistence")] [DocumentationUpdated("2.1.23")] public sealed class FeaturePersistenceController : ControllerBase
```

🌟 Constructors 1

FeaturePersistenceController(IFeaturePersistenceService, ILogger<FeaturePersistenceController>)

CRUD API for durable records owned by newer LocalGPT feature modules.

```
public FeaturePersistenceController(IFeaturePersistenceService persistence, ILogger<FeaturePersistenceController> logger)
```

⚙️ Methods 20

DeleteCouncilStarter(Guid, bool, CancellationTokens)

Deletes a Council prompt starter.

```
[HttpDelete("council-starters/{id:guid}")] [HumanApprovalRequired("feature.council-starter.delete", "Delete Council starter", "Delete one persistent prompt starter.", "Medium", "Council configuration maintainer", false)] public Task<IResult> DeleteCouncilStarter(Guid id, bool userConfirmed, CancellationTokens cancellationTokens)
```

DeleteDocumentationBuild(Guid, bool, CancellationTokens)

Deletes documentation build evidence.

```
[HttpDelete("documentation-builds/{id:guid}")] [HumanApprovalRequired("feature.documentation-build.delete", "Delete documentation build", "Delete one stored documentation evidence record.", "Low", "Documentation maintainer", false)] public Task<IResult> DeleteDocumentationBuild(Guid id, bool userConfirmed, CancellationTokens cancellationTokens)
```

DeleteFirmwarePlan(Guid, bool, CancellationTokens)

Deletes an embedded firmware plan record.

```
[HttpDelete("firmware-plans/{id:guid}")] [HumanApprovalRequired("feature.firmware-plan.delete", "Delete firmware plan", "Delete one stored firmware planning envelope.", "Medium", "Embedded project maintainer", false)] public Task<IResult> DeleteFirmwarePlan(Guid id, bool userConfirmed, CancellationTokens cancellationTokens)
```

DeleteGameSession(Guid, bool, CancellationTokens)

Deletes an authoritative GameDirector session record.

```
[HttpDelete("game-sessions/{id:guid}")] [HumanApprovalRequired("feature.game-session.delete", "Delete GameDirector session", "Delete one stored game-runtime snapshot envelope.", "Medium", "Game runtime maintainer", false)] public Task<IResult> DeleteGameSession(Guid id, bool userConfirmed, CancellationTokens cancellationTokens)
```

DeleteLocalizationCatalog(Guid, bool, CancellationTokens)

Deletes a localization catalog registration.

```
[HttpDelete("localization-catalogs/{id:guid}")] [HumanApprovalRequired("feature.localization-catalog.delete", "Delete localization catalog", "Delete one language-catalog registration without deleting unrelated files.", "Medium", "Localization maintainer", false)] public Task<IResult> DeleteLocalizationCatalog(Guid id, bool userConfirmed, CancellationTokens cancellationTokens)
```

GetCouncilStarter(Guid, CancellationTokens)

Gets one persistent Council prompt starter.

```
[HttpGet("council-starters/{id:guid}")] public Task<IResult> GetCouncilStarter(Guid id, CancellationTokens cancellationTokens)
```

GetCouncilStarters(bool, CancellationTokens)

Lists persistent Council prompt starters.

```
[HttpGet("council-starters")] public Task<IResult> GetCouncilStarters(bool includeDisabled, CancellationTokens cancellationTokens)
```

GetDocumentationBuild(Guid, CancellationTokens)

Gets one documentation build record.

```
[HttpGet("documentation-builds/{id:guid}")] public Task<IResult> GetDocumentationBuild(Guid id, CancellationTokens cancellationTokens)
```

GetDocumentationBuilds(CancellationTokens)

Lists documentation build evidence.

```
[HttpGet("documentation-builds")] public Task<IResult> GetDocumentationBuilds(CancellationTokens cancellationTokens)
```

GetFirmwarePlan(Guid, CancellationTokens)

Gets one embedded firmware plan record.

```
[HttpGet("firmware-plans/{id:guid}")] public Task<IResult> GetFirmwarePlan(Guid id, CancellationTokens cancellationTokens)
```

GetFirmwarePlans(CancellationTokens)

Lists embedded firmware plan records.

```
[HttpGet("firmware-plans")] public Task<IResult> GetFirmwarePlans(CancellationTok
```

GetGameSession(Guid, CancellationToken)

Gets one authoritative GameDirector session record.

```
[HttpGet("game-sessions/{id:guid}")] public Task<IResult> GetGameSession(Guid id, CancellationTok
```

GetGameSessions(CancellationToken)

Lists authoritative GameDirector session records.

```
[HttpGet("game-sessions")] public Task<IResult> GetGameSessions(CancellationTok
```

GetLocalizationCatalog(Guid, CancellationToken)

Gets one localization catalog registration.

```
[HttpGet("localization-catalogs/{id:guid}")] public Task<IResult> GetLocalizationCatalog(Guid id, CancellationTok
```

GetLocalizationCatalogs(bool, CancellationToken)

Lists localization catalog registrations.

```
[HttpGet("localization-catalogs")] public Task<IResult> GetLocalizationCatalogs(bool includeDisabled, CancellationTok
```

SaveCouncilStarter(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration>, CancellationToken)

Creates or updates a Council prompt starter.

```
[HttpPut("council-starters")] [HumanApprovalRequired("feature.council-starter.save", "Save Council starter", "Store one chat or direct-Council prompt configuration.", "Medium", "Council configuration maintainer", false)] public Task<IResult> SaveCouncilStarter(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration> request, CancellationTok
```

SaveDocumentationBuild(SaveFeatureRecordRequest<DocumentationBuildRecord>, CancellationToken)

Creates or updates documentation build evidence.

```
[HttpPut("documentation-builds")] [HumanApprovalRequired("feature.documentation-build.save", "Save documentation build", "Store one documentation generation evidence record.", "Low", "Documentation maintainer", false)] public Task<IResult> SaveDocumentationBuild(SaveFeatureRecordRequest<DocumentationBuildRecord> request, CancellationTok
```

SaveFirmwarePlan(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord>, CancellationToken)

Creates or updates an embedded firmware plan record.

```
[HttpPut("firmware-plans")] [HumanApprovalRequired("feature.firmware-plan.save", "Save firmware plan", "Store one versioned embedded-hardware planning envelope.", "Medium", "Embedded project maintainer", false)] public Task<IResult> SaveFirmwarePlan(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord> request, CancellationTok
```

SaveGameSession(SaveFeatureRecordRequest<CouncilGameSessionRecord>, CancellationToken)

Creates or updates an authoritative GameDirector session record.

```
[HttpPut("game-sessions")] [HumanApprovalRequired("feature.game-session.save", "Save GameDirector session", "Store one authoritative game-runtime snapshot envelope.", "Medium", "Game runtime maintainer", false)] public Task<IResult> SaveGameSession(SaveFeatureRecordRequest<CouncilGameSessionRecord> request, CancellationTok
```

SaveLocalizationCatalog(SaveFeatureRecordRequest<LocalizationCatalogRegistration>, CancellationToken)

Creates or updates a localization catalog registration.

```
[HttpPut("localization-catalogs")] [HumanApprovalRequired("feature.localization-catalog.save", "Save localization catalog", "Store one validated language-catalog registration.", "Medium", "Localization maintainer", false)] public Task<IResult> SaveLocalizationCatalog(SaveFeatureRecordRequest<LocalizationCatalogRegistration> request, CancellationTok
```

Class FirstRunOnboardingController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Exposes the bounded first-run setup status and completion operation to LocalGPT frontends.

Inheritance object ControllerBase FirstRunOnboardingController

```
[ApiController] [Route("api/onboarding")] [DocumentationUpdated("2.1.20")] public sealed class FirstRunOnboardingController : ControllerBase
```

🌟 Constructors 1

FirstRunOnboardingController(IFirstRunOnboardingService)

Exposes the bounded first-run setup status and completion operation to LocalGPT frontends.

```
public FirstRunOnboardingController(IFirstRunOnboardingService onboarding)
```

⚙️ Methods 2

Complete(CompleteFirstRunOnboardingRequest, CancellationToken)

Records that the user reviewed or dismissed the first-run guide.

```
[HttpPost("complete")] public Task<IActionResult> Complete(CompleteFirstRunOnboardingRequest request, CancellationToken cancellationToken = default)
```

GetStatus(bool, CancellationToken)

Returns installer profiles, discovered local models, seeded councils and quick-start routes.

```
[HttpGet("status")] public Task<ActionResult<FirstRunOnboardingStatus>> GetStatus(bool refreshConnectivity = false, CancellationToken cancellationToken = default)
```

Namespace LocalGPT.Controller

Classes

Carries the explicit confirmation required to dismiss first-run onboarding.

Exposes availability metadata, searchable XML comments and the versioned PDF produced by the DocFX build pipeline.

User-owned catalog for deciding which LocalGPT DX functions and public service methods are visible to AI chat or securely linked 1-Wire peers.

CRUD API for durable records owned by newer LocalGPT feature modules.

Exposes the bounded first-run setup status and completion operation to LocalGPT frontends.

Carries one user localization-catalog import request.

Exposes localization catalogs, culture selection and validated user-catalog imports.

Transport-neutral JSON adapter for small user-built organic clients such as ESP32 firmware. It uses the same envelope, permissions, MFA trust and work spool as the TCP transport.

Class ImportLocalizationCatalogRequest

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Carries one user localization-catalog import request.

Inheritance object ImportLocalizationCatalogRequest

```
[DocumentationUpdated("2.2.8")] public sealed class ImportLocalizationCatalogRequest
```

🌟 Constructors 1

ImportLocalizationCatalogRequest()

```
public ImportLocalizationCatalogRequest()
```

🐾 Properties 3

Culture

Gets or sets the requested .NET culture name.

```
public string Culture { get; set; }
```

Json

Gets or sets the string-to-string JSON object.

```
public string Json { get; set; }
```

Overwrite

Gets or sets whether an existing user catalog may be replaced.

```
public bool Overwrite { get; set; }
```


Class LocalGptDiagnosticController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase LocalGptDiagnosticController

```
[ApiController] [Route("")] public class LocalGptDiagnosticController : ControllerBase
```

🌟 Constructors 1

LocalGptDiagnosticController(ILogger<LocalGptDiagnosticController>, CouncilRuntimeService, CouncilTextService, DevExpressChatService, IDxAiFunctionRegistry, LocalGptCatalogService)

```
public LocalGptDiagnosticController(ILogger<LocalGptDiagnosticController> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, DevExpressChatService devExpressChat, IDxAiFunctionRegistry dxAiFunctionRegistry, LocalGptCatalogService catalog)
```

⚙️ Methods 42

GetAiHostRebuildGuidance(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/ai-host-rebuild-guidance")] public Task<IResult> GetAiHostRebuildGuidance(IWebHostEnvironment env, CancellationToken ct)
```

GetAiSmoke(IChatClient, string?, bool, CancellationToken)

```
[HttpGet("/__diag/ai-smoke")] [HumanApprovalRequired("diagnostic.ai.smoke", "Call configured AI client", "Send one exact diagnostic prompt to the configured AI client.", "Medium", "AI connectivity reviewer", false)] public Task<IResult> GetAiSmoke(IChatClient chatClient, string? prompt, bool userConfirmed, CancellationToken ct)
```

GetArtifactWorkspaceWorkspaceNameFile(string, string, ICouncilArtifactService, CancellationToken)

```
[HttpGet("/__diag/artifact-workspace/{workspaceName}/file")] public Task<IResult> GetArtifactWorkspaceWorkspaceNameFile(string workspaceName, string path, ICouncilArtifactService artifacts, CancellationToken ct)
```

GetArtifactWorkspaceWorkspaceNameFiles(string, ICouncilArtifactService, int?)

```
[HttpGet("/__diag/artifact-workspace/{workspaceName}/files")] public IResult GetArtifactWorkspaceWorkspaceNameFiles(string workspaceName, ICouncilArtifactService artifacts, int? take)
```

GetArtifactWorkspaceWorkspaceNameZip(string, ICouncilArtifactService, bool)

```
[HttpGet("/__diag/artifact-workspace/{workspaceName}/zip")] [HumanApprovalRequired("artifact.workspace.zip.refresh", "Refresh generated workspace ZIP", "Replace the downloadable ZIP for one bounded generated artifact workspace.", "Medium", "Artifact reviewer", false)] public IResult GetArtifactWorkspaceWorkspaceNameZip(string workspaceName, ICouncilArtifactService artifacts, bool userConfirmed)
```

GetArtifactWorkspaces(ICouncilArtifactService, int?)

```
[HttpGet("/__diag/artifact-workspaces")] public IResult GetArtifactWorkspaces(ICouncilArtifactService artifacts, int? take)
```

GetBenchmarkEngineering(bool?, bool?, bool?, int?, string?, IEngineeringBenchmarkService, bool, CancellationToken)

```
[HttpGet("/__diag/benchmark/engineering")] [HumanApprovalRequired("diagnostic.engineering.benchmark", "Run engineering benchmark", "Run the bounded engineering benchmark and persist its reviewed diagnostic result.", "High", "Engineering benchmark reviewer", false)] public Task<IResult> GetBenchmarkEngineering(bool? importLearnBaseFirst, bool? saveToKnowledge, bool? validateBuildableArtifacts, int? maxBuildArtifacts, string? taskSet, IEngineeringBenchmarkService benchmark, bool userConfirmed, CancellationToken ct)
```

GetBlazorDevexpressGuidance(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/blazor-devexpress-guidance")] public Task<IResult> GetBlazorDevexpressGuidance(IWebHostEnvironment env, CancellationToken ct)
```

GetBuildDebugFiles(IBuildDebugInventoryService, bool?, CancellationToken)

```
[HttpGet("/__diag/build-debug-files")] public Task<IResult> GetBuildDebugFiles(IBuildDebugInventoryService inventory, bool? copy, CancellationToken ct)
```

GetCapabilityGapContract(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/capability-gap-contract")] public Task<IResult> GetCapabilityGapContract(IWebHostEnvironment env, CancellationToken ct)
```

GetChatUploadWorkspaceWorkspaceNameContext(string, IChatUploadWorkspaceService, int?, CancellationToken)

```
[HttpGet("/__diag/chat-upload-workspace/{workspaceName}/context")] public Task<IResult> GetChatUploadWorkspaceWorkspaceNameContext(string workspaceName, IChatUploadWorkspaceService uploads, int? maxCharacters, CancellationToken ct)
```

GetChatUploadWorkspaceWorkspaceNameFile(string, string, IChatUploadWorkspaceService, int?, CancellationToken)

```
[HttpGet("/__diag/chat-upload-workspace/{workspaceName}/file")] public Task<IResult> GetChatUploadWorkspaceWorkspaceNameFile(string workspaceName, string path, IChatUploadWorkspaceService uploads, int? maxCharacters, CancellationToken ct)
```

GetChatUploadWorkspaceWorkspaceNameFiles(string, IChatUploadWorkspaceService, int?)

```
[HttpGet("/__diag/chat-upload-workspace/{workspaceName}/files")] public IResult GetChatUploadWorkspaceWorkspaceNameFiles(string workspaceName, IChatUploadWorkspaceService uploads, int? take)
```

GetChatUploadWorkspaces(IChatUploadWorkspaceService, int?)

```
[HttpGet("/__diag/chat-upload-workspaces")] public IResult GetChatUploadWorkspaces(IChatUploadWorkspaceService uploads, int? take)
```

GetComponentActivity(IComponentActivityService, int?)

```
[HttpGet("/__diag/component-activity")] public IResult GetComponentActivity(IComponentActivityService componentActivity, int? take)
```

GetCouncilArtifactSmoke(string?, string?, string?, ICouncilArtifactService, bool, CancellationToken)

```
[HttpGet("/__diag/council/artifact-smoke")] [HumanApprovalRequired("diagnostic.council.artifact.create", "Create council artifact workspace", "Create one deterministic bounded council artifact workspace for diagnostics.", "High", "Artifact reviewer", false)] public Task<IResult> GetCouncilArtifactSmoke(string? target, string? prompt, string? finalAnswer, ICouncilArtifactService artifacts, bool userConfirmed, CancellationToken ct)
```

GetCouncilBenchmarkPlan(IMultiModelCouncilService, CancellationToken)

```
[HttpGet("/__diag/council/benchmark-plan")] public Task<IResult> GetCouncilBenchmarkPlan(IMultiModelCouncilService council, CancellationToken ct)
```

GetCouncilDevelopmentFeedbackTalk(string?, int?, int?, int?, int?, IMultiModelCouncilService, bool, CancellationToken)

```
[HttpGet("/__diag/council/development-feedback-talk")] [HumanApprovalRequired("diagnostic.council.feedback", "Run council development feedback", "Start the requested local council feedback session and persist its bounded result.", "Medium", "Council facilitator", false)] public Task<IResult> GetCouncilDevelopmentFeedbackTalk(string? modelNames, int? maxOutputTokens, int? maxContextTokens, int? maxRounds, int? ollamaNumGpu, IMultiModelCouncilService council, bool userConfirmed, CancellationToken ct)
```

GetCouncilFileName(string, ICouncilArtifactService)

```
[HttpGet("/__artifacts/council/{fileName}")] public IResult GetCouncilFileName(string fileName, ICouncilArtifactService artifacts)
```

GetCouncilModels(IMultiModelCouncilService, CancellationToken)

```
[HttpGet("/__diag/council/models")] public Task<IResult> GetCouncilModels(IMultiModelCouncilService council, CancellationToken ct)
```

GetDevexpress(IProjectLibraryInventoryService, CancellationToken)

```
[HttpGet("/__diag/devexpress")] public Task<IResult> GetDevexpress(IProjectLibraryInventoryService inventory, CancellationToken ct)
```

GetDotnetSampleCurriculum(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/dotnet-sample-curriculum")] public Task<IResult> GetDotnetSampleCurriculum(IWebHostEnvironment env, CancellationToken ct)
```

GetDxaichatFunctions()

```
[HttpGet("/__diag/dxaichat-functions")] public IResult GetDxaichatFunctions()
```

GetFrontendDesignGuidance(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/frontend-design-guidance")] public Task<IResult> GetFrontendDesignGuidance(IWebHostEnvironment env, CancellationToken ct)
```

GetFrontendTestGuidance(IWebHostEnvironment, CancellationToken)

```
[HttpGet("/__diag/frontend-test-guidance")] public Task<IResult> GetFrontendTestGuidance(IWebHostEnvironment env, CancellationToken ct)
```

GetKnowledge(ICouncilKnowledgeService, bool?, int?, CancellationToken)

```
[HttpGet("/__diag/knowledge")] public Task<IResult> GetKnowledge(ICouncilKnowledgeService knowledge, bool? includeArchived, int? take, CancellationToken ct)
```

GetLearnBaseImport(string?, int?, bool?, string?, string?, string?, int?, bool?, bool?, bool?, ILearnBaseKnowledgeImporterService, bool, CancellationToken)

```
[HttpGet("/__diag/learn-base/import")] [HumanApprovalRequired("learnbase.import", "Import local learn-base", "Read the selected local source tree and optionally persist normalized knowledge entries.", "High", "Knowledge curator", false)] public Task<IResult> GetLearnBaseImport(string? rootPath, int? maxProjects, bool? saveToKnowledge, string? fileExtensions, string? includeRegex, string? excludeRegex, int? maximumFileBytes, bool? importLearningSourceManifests, bool? importKnownDocumentationCorpora, bool? importProjectArchitecture, ILearnBaseKnowledgeImporterService importer, bool userConfirmed, CancellationToken ct)
```

GetLogs(IApplicationLogReaderService, ILoggerFactory, string?, int?, bool?, CancellationToken)

```
[HttpGet("/__diag/logs")] public Task<IResult> GetLogs(IApplicationLogReaderService logs, ILoggerFactory loggerFactory, string? minimumLevel, int? take, bool? writeSmoke, CancellationToken ct)
```

GetMemory(IChatMemoryService, CancellationToken)

```
[HttpGet("/__diag/memory")] public Task<IResult> GetMemory(IChatMemoryService memory, CancellationToken ct)
```

GetMemorySmoke(IChatMemoryService, IChatClient, bool, CancellationToken)

```
[HttpGet("/__diag/memory-smoke")] [HumanApprovalRequired("diagnostic.memory.smoke", "Write diagnostic memory", "Persist a bounded diagnostic conversation and call the configured model.", "High", "Memory reviewer", false)] public Task<IResult> GetMemorySmoke(IChatMemoryService memory, IChatClient chatClient, bool userConfirmed, CancellationToken ct)
```

GetOllamaCompatibleSmoke(string, string?, string?, int?, int?, IPromptConfigService, IChatResponseFormatterFactory, IChatProtocolResolver, bool, CancellationToken)
<pre>[HttpGet("/__diag/ollama-compatible-smoke")] [HumanApprovalRequired("diagnostic.ollama.smoke", "Call Ollama-compatible endpoint", "Send one exact diagnostic request to the selected Ollama-compatible endpoint.", "Medium", "AI connectivity reviewer", false)] public Task<IResult> GetOllamaCompatibleSmoke(string endpoint, string? model, string? prompt, int? numGpu, int? maxOutputTokens, IPromptConfigService promptConfigService, IChatResponseFormatterFactory formatterFactory, IChatProtocolResolver protocolResolver, bool userConfirmed, CancellationToken ct)</pre>
GetRoot(IWebHostEnvironment)
<pre>[HttpGet("/__diag")] public IResult GetRoot(IWebHostEnvironment env)</pre>
GetSqliteTableTableName(string, int?, IChatMemoryService, IApplicationLogReaderService, ICouncilKnowledgeService, ISqliteTableEditorService, CancellationToken)
<pre>[HttpGet("/__diag/sqlite/table/{tableName}")] public Task<IResult> GetSqliteTableTableName(string tableName, int? take, IChatMemoryService memory, IApplicationLogReaderService logs, ICouncilKnowledgeService knowledge, ISqliteTableEditorService tableEditor, CancellationToken ct)</pre>
GetSqliteTables(IChatMemoryService, IApplicationLogReaderService, ICouncilKnowledgeService, ISqliteTableEditorService, CancellationToken)
<pre>[HttpGet("/__diag/sqlite/tables")] public Task<IResult> GetSqliteTables(IChatMemoryService memory, IApplicationLogReaderService logs, ICouncilKnowledgeService knowledge, ISqliteTableEditorService tableEditor, CancellationToken ct)</pre>
InvokeDxFunction(string, DxAiFunctionInvocationRequest, CancellationToken)
<pre>[HttpPost("/__diag/dxaichat-functions/{functionName}/invoke")] public Task<IResult> InvokeDxFunction(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken)</pre>
PostArtifactWorkspaceWorkspaceNameFile(string, ArtifactWorkspaceFileSaveRequest, ICouncilArtifactService, bool, CancellationToken)
<pre>[HttpPost("/__diag/artifact-workspace/{workspaceName}/file")] [HumanApprovalRequired("artifact.workspace.file.write", "Write generated workspace file", "Write the reviewed text content to one bounded file inside a generated artifact workspace.", "High", "Source workspace reviewer", false)] public Task<IResult> PostArtifactWorkspaceWorkspaceNameFile(string workspaceName, ArtifactWorkspaceFileSaveRequest request, ICouncilArtifactService artifacts, bool userConfirmed, CancellationToken ct)</pre>
PostBenchmarkEngineering(EngineeringBenchmarkRequest, IEngineeringBenchmarkService, bool, CancellationToken)
<pre>[HttpPost("/__diag/benchmark/engineering")] [HumanApprovalRequired("diagnostic.engineering.benchmark", "Run engineering benchmark", "Run the bounded engineering benchmark and persist its reviewed diagnostic result.", "High", "Engineering benchmark reviewer", false)] public Task<IResult> PostBenchmarkEngineering(EngineeringBenchmarkRequest request, IEngineeringBenchmarkService benchmark, bool userConfirmed, CancellationToken ct)</pre>
PostChatUploadWorkspaceSmoke(IChatUploadWorkspaceService, string?, bool, CancellationToken)
<pre>[HttpPost("/__diag/chat-upload-workspace/smoke")] [HumanApprovalRequired("diagnostic.upload.workspace.create", "Create upload workspace", "Create a bounded diagnostic workspace from generated upload fixtures.", "High", "Workspace reviewer", false)] public Task<IResult> PostChatUploadWorkspaceSmoke(IChatUploadWorkspaceService uploads, string? prompt, bool userConfirmed, CancellationToken ct)</pre>
PostCouncil(MultiModelCouncilRequest, IMultiModelCouncilService, CancellationToken)
<pre>[HttpPost("/__diag/council")] public Task<IResult> PostCouncil(MultiModelCouncilRequest request, IMultiModelCouncilService council, CancellationToken ct)</pre>
PostDxaichatSmoke(DxaichatSmokeRequest, IChatClient, IChatMemoryService, bool, CancellationToken)
<pre>[HttpPost("/__diag/dxaichat-smoke")] [HumanApprovalRequired("diagnostic.dxaichat.smoke", "Run DXAiChat diagnostic", "Call the configured chat client and optionally persist the exact diagnostic exchange.", "Medium", "Chat workflow reviewer", false)] public Task<IResult> PostDxaichatSmoke(DxaichatSmokeRequest request, IChatClient chatClient, IChatMemoryService memory, bool userConfirmed, CancellationToken ct)</pre>
PostLearnBaseImport(LearnBaseImportRequest, ILearnBaseKnowledgeImporterService, bool, CancellationToken)
<pre>[HttpPost("/__diag/learn-base/import")] [HumanApprovalRequired("learnbase.import", "Import local learn-base", "Read the selected local source tree and optionally persist normalized knowledge entries.", "High", "Knowledge curator", false)] public Task<IResult> PostLearnBaseImport(LearnBaseImportRequest request, ILearnBaseKnowledgeImporterService importer, bool userConfirmed, CancellationToken ct)</pre>
PostProcessReview(GroundedProcessReviewRequest, IChatMemoryService, IChatClient, bool, CancellationToken)
<pre>[HttpPost("/__diag/process-review")] [HumanApprovalRequired("diagnostic.process.review", "Run grounded process review", "Run the submitted grounded process review through the configured model and memory workflow.", "Medium", "Process reviewer", false)] public Task<IResult> PostProcessReview(GroundedProcessReviewRequest request, IChatMemoryService memory, IChatClient chatClient, bool userConfirmed, CancellationToken ct)</pre>

Class LocalGptProjectsController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase LocalGptProjectsController

```
[ApiController] [Route("api/projects")] public sealed class LocalGptProjectsController : ControllerBase
```

🌟 Constructors 1

LocalGptProjectsController(ILocalGptProjectService, ILogger<LocalGptProjectsController>)

```
public LocalGptProjectsController(ILocalGptProjectService projects, ILogger<LocalGptProjectsController> logger)
```

⚙️ Methods 6

AddTopic(Guid, AddLocalGptProjectTopicRequest, CancellationToken)

```
[HttpPost("{projectId:guid}/topics")] public Task<ActionResult<LocalGptProjectTopic>> AddTopic(Guid projectId, AddLocalGptProjectTopicRequest request, CancellationToken cancellationToken = default)
```

AddVersion(Guid, AddLocalGptProjectVersionRequest, CancellationToken)

```
[HttpPost("{projectId:guid}/versions")] public Task<ActionResult<LocalGptProjectVersion>> AddVersion(Guid projectId, AddLocalGptProjectVersionRequest request, CancellationToken cancellationToken = default)
```

GetProject(Guid, CancellationToken)

```
[HttpGet("{projectId:guid}")] public Task<ActionResult<LocalGptProjectDetails>> GetProject(Guid projectId, CancellationToken cancellationToken = default)
```

GetProjects(bool, CancellationToken)

```
[HttpGet] public Task<ActionResult<IReadOnlyList<LocalGptProjectSummary>>> GetProjects(bool includeArchived = false, CancellationToken cancellationToken = default)
```

LinkKnowledge(Guid, LinkProjectTopicKnowledgeRequest, CancellationToken)

```
[HttpPost("topics/{projectTopicId:guid}/knowledge")] public Task<IActionResult> LinkKnowledge(Guid projectTopicId, LinkProjectTopicKnowledgeRequest request, CancellationToken cancellationToken = default)
```

SaveProject(SaveLocalGptProjectRequest, CancellationToken)

```
[HttpPost] public Task<ActionResult<LocalGptProject>> SaveProject(SaveLocalGptProjectRequest request, CancellationToken cancellationToken = default)
```

Class LocalizationController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Exposes localization catalogs, culture selection and validated user-catalog imports.

Inheritance object ControllerBase LocalizationController

```
[ApiController] [Route("api/localization")] [DocumentationUpdated("2.2.8")] public sealed class LocalizationController : ControllerBase
```

✨ Constructors 1

LocalizationController(ILocalGptLocalizationService, ILogger<LocalizationController>)

Exposes localization catalogs, culture selection and validated user-catalog imports.

```
public LocalizationController(ILocalGptLocalizationService localization, ILogger<LocalizationController> logger)
```

⚙️ Methods 5

Catalogs()

Returns built-in and user-supplied localization catalog descriptors.

```
[HttpGet("catalogs")] public ActionResult<IReadOnlyList<LocalizationCatalogDescriptor>> Catalogs()
```

Current()

Returns strings for the current UI culture.

```
[HttpGet("current")] public ActionResult<IReadOnlyDictionary<string, string>> Current()
```

Get(string)

Returns effective strings for a requested culture.

```
[HttpGet("{culture}")] public ActionResult<IReadOnlyDictionary<string, string>> Get(string culture)
```

Import(ImportLocalizationCatalogRequest, CancellationToken)

Validates and imports a persistent user localization catalog.

```
[HttpPost("catalogs/import")] public Task<ActionResult<LocalizationCatalogImportResult>> Import(ImportLocalizationCatalogRequest request,
CancellationToken cancellationToken)
```

Select(string, string?)

Persists the requested UI culture cookie and returns to a local application route.

```
[HttpGet("select")] public IActionResult Select(string culture, string? returnUrl = "/")
```

Class OneWireController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase OneWireController

```
[ApiController] [Route("api/onewire")] public sealed class OneWireController : ControllerBase
```

🌟 Constructors 1

OneWireController(IOneWireCapabilityCatalog, IOneWirePeerRegistry, IOneWireConnectionRegistry, IOneWireWorkSpooler, IOneWireEnvelopeCodec, IOneWireMessageDispatcher, IOneWireTransportSecurityPolicy, IOneWireDispatchContextFactory, IOneWireReplayPolicyDataService, IOrganicCouncilBlueprintService, ICouncilTeamConfigurationService, ILogger<OneWireController>)

```
public OneWireController(
    IOneWireCapabilityCatalog capabilities,
    IOneWirePeerRegistry peers,
    IOneWireConnectionRegistry connections,
    IOneWireWorkSpooler work,
    IOneWireEnvelopeCodec codec,
    IOneWireMessageDispatcher dispatcher,
    IOneWireTransportSecurityPolicy transportSecurityPolicy,
    IOneWireDispatchContextFactory dispatchContextFactory,
    IOneWireReplayPolicyDataService replayPolicy,
    IOrganicCouncilBlueprintService teams,
    ICouncilTeamConfigurationService teamConfigurations,
    ILogger<OneWireController> logger)

```

⚙️ Methods 12

Capabilities(CancellationTokens)

```
[HttpGet("capabilities")] public Task<ActionResult<IReadOnlyList<OneWireCapabilityDescriptor>>> Capabilities(
    CancellationTokens cancellationTokens)

```

CouncilTeams(CancellationTokens)

```
[HttpGet("council/teams")] public Task<ActionResult<IReadOnlyList<OrganicCouncilTeamDefinition>>> CouncilTeams(
    CancellationTokens cancellationTokens)

```

Dispatch(OneWireEnvelope, CancellationTokens)

```
[HttpPost("dispatch")] public Task<ActionResult> Dispatch(
    OneWireEnvelope envelope, CancellationTokens cancellationTokens)

```

InvokePeer(string, OneWireEnvelope, CancellationTokens)

```
[HttpPost("peers/{peerId}/invoke")] [HumanApprovalRequired(
    "onewire.peer.invoke", "Send organic plugin capability",
    "Send the exact reviewed capability request to the selected connected organic plugin peer.",
    "High", "Organic plugin action reviewer", true)] public Task<ActionResult> InvokePeer(
    string peerId, OneWireEnvelope envelope, CancellationTokens cancellationTokens)

```

Peers()

```
[HttpGet("peers")] public ActionResult<IReadOnlyList<OneWirePeerAdvertisement>> Peers()

```

ReplayPolicy()

```
[HttpGet("replay-policy")] public ActionResult<OneWireReplayPolicySnapshot> ReplayPolicy()

```

SaveCouncilTeam(SaveCouncilTeamConfigurationRequest, CancellationTokens)

```
[HttpPost("council/teams")] [HumanApprovalRequired(
    "onewire.council-team.save", "Save AI Council team configuration",
    "Persist the reviewed team roles, prompts, workflow steps and architecture contracts without deleting seeded or user knowledge.",
    "High", "AI Council configuration reviewer", false)] public Task<ActionResult<OrganicCouncilTeamDefinition>> SaveCouncilTeam(
    SaveCouncilTeamConfigurationRequest request, CancellationTokens cancellationTokens)

```

Status()

```
[HttpGet("status")] public IActionResult Status()

```

TransportPolicy()

```
[HttpGet("transport-policy")] public IActionResult TransportPolicy()

```

Validate(OneWireEnvelope)

```
[HttpPost("validate")] public IActionResult Validate(
    OneWireEnvelope envelope)

```

Work()

```
[HttpGet("work")] public ActionResult<IReadOnlyList<OneWireWorkItem>> Work()

```

Work(Guid)

```
[HttpGet("work/{id:guid}")] public ActionResult<OneWireWorkItem> Work(
    Guid id)

```

Class OneWireHttpController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Transport-neutral JSON adapter for small user-built organic clients such as ESP32 firmware. It uses the same envelope, permissions, MFA trust and work spool as the TCP transport.

Inheritance object ControllerBase OneWireHttpController

```
[ApiController] [Route("api/onewire/http-json")] public sealed class OneWireHttpController : ControllerBase
```

✨ Constructors 1

OneWireHttpController(IOneWireEnvelopeCodec, IOneWireRuntimeSecurityService, IOneWireMessageDispatcher, IOneWireTransportSecurityPolicy, IOneWireDispatchContextFactory, IOneWireWorkSpooler, ILogger<OneWireHttpController>)

Transport-neutral JSON adapter for small user-built organic clients such as ESP32 firmware. It uses the same envelope, permissions, MFA trust and work spool as the TCP transport.

```
public OneWireHttpController(
    IOneWireEnvelopeCodec codec,
    IOneWireRuntimeSecurityService security,
    IOneWireMessageDispatcher dispatcher,
    IOneWireTransportSecurityPolicy transportSecurityPolicy,
    IOneWireDispatchContextFactory dispatchContextFactory,
    IOneWireWorkSpooler spooler,
    ILogger<OneWireHttpController> logger)

```

⚙️ Methods 3

Dispatch(JsonElement, CancellationToken)

```
[HttpPost] [RequestSizeLimit(8388608)] public Task<IActionResult> Dispatch(
    JsonElement body,
    CancellationToken cancellationToken)

```

Profile(CancellationToken)

```
[HttpGet("profile")] public Task<ActionResult<object>> Profile(
    CancellationToken cancellationToken)

```

Work(Guid, CancellationToken)

```
[HttpGet("work/{correlationId:guid}")] public Task<IActionResult> Work(
    Guid correlationId,
    CancellationToken cancellationToken)

```

Class ProjectMaintenanceController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase ProjectMaintenanceController

```
[ApiController] [Route("api/project-maintenance")] public sealed class ProjectMaintenanceController : ControllerBase
```

🌟 Constructors 1

ProjectMaintenanceController(IProjectMaintenanceService, ILogger<ProjectMaintenanceController>)

```
public ProjectMaintenanceController(IProjectMaintenanceService maintenance, ILogger<ProjectMaintenanceController> logger)
```

⚙️ Methods 16

ApproveReady(Guid, Guid, ApproveRevisionReadyForTestRequest, CancellationToken)

```
[HttpPost("projects/{projectId:guid}/revisions/{revisionId:guid}/approve-ready")] [HumanApprovalRequired("project.revision.ready.approve", "Approve revision for testing", "After successful build, requested tests, and council review, create a lossless source snapshot and mark the revision ready for human testing.", "High", "Release approval reviewer", true)] public Task<IResult> ApproveReady(Guid projectId, Guid revisionId, ApproveRevisionReadyForTestRequest request, CancellationToken cancellationToken)
```

AssessWorkspacePermissions(Guid, bool, CancellationToken)

```
[HttpPost("workspaces/{workspaceRootId:guid}/assess")] [HumanApprovalRequired("project.workspace.permissions.assess", "Assess workspace permissions", "Inspect the configured workspace structure and optionally perform one bounded create/delete write probe.", "Medium", "Workspace security reviewer", false)] public Task<IResult> AssessWorkspacePermissions(Guid workspaceRootId, bool userConfirmedWriteProbe, CancellationToken cancellationToken)
```

DeleteCompiler(Guid, bool, CancellationToken)

```
[HttpDelete("compilers/{compilerId:guid}")] [HumanApprovalRequired("project.compiler.delete", "Delete compiler installation", "Remove one stored compiler profile that is not referenced by a workspace or verification record.", "Medium", "Project toolchain administrator", false)] public Task<IResult> DeleteCompiler(Guid compilerId, bool userConfirmed, CancellationToken cancellationToken)
```

DiscoverCompilers(DiscoverProjectCompilersRequest, CancellationToken)

```
[HttpPost("compilers/discover")] [HumanApprovalRequired("project.compiler.discover", "Discover compiler installations", "Scan common and user-selected directories for compiler executables and store the detected paths.", "Medium", "Project toolchain administrator", false)] public Task<IResult> DiscoverCompilers(DiscoverProjectCompilersRequest request, CancellationToken cancellationToken)
```

GetCompilers(CancellationToken)

```
[HttpGet("compilers")] public Task<IResult> GetCompilers(CancellationToken cancellationToken)
```

GetFiles(Guid, Guid?, CancellationToken)

```
[HttpGet("projects/{projectId:guid}/files")] public Task<IResult> GetFiles(Guid projectId, Guid? revisionId, CancellationToken cancellationToken)
```

GetWorkspaces(Guid?, CancellationToken)

```
[HttpGet("workspaces")] public Task<IResult> GetWorkspaces(Guid? projectId, CancellationToken cancellationToken)
```

RecordCouncilReview(Guid, RecordCouncilBuildReviewRequest, CancellationToken)

```
[HttpPost("verifications/{verificationId:guid}/council-review")] [HumanApprovalRequired("project.revision.council-review", "Record council build review", "Store the council's review of the compile and test evidence.", "Medium", "Council build reviewer", false)] public Task<IResult> RecordCouncilReview(Guid verificationId, RecordCouncilBuildReviewRequest request, CancellationToken cancellationToken)
```

RegisterRevisionWorkspace(Guid, Guid, RegisterRevisionWorkspaceRequest, CancellationToken)

```
[HttpPost("projects/{projectId:guid}/revisions/{revisionId:guid}/workspace")] [HumanApprovalRequired("project.revision.workspace.save", "Save revision workspace", "Associate one existing local workspace and optional solution file with the selected project revision.", "High", "Project workspace administrator", false)] public Task<IResult> RegisterRevisionWorkspace(Guid projectId, Guid revisionId, RegisterRevisionWorkspaceRequest request, CancellationToken cancellationToken)
```

ResolveWorkspace(Guid, CancellationToken)

```
[HttpGet("workspaces/{projectId:guid}/resolve")] public Task<IResult> ResolveWorkspace(Guid projectId, CancellationToken cancellationToken)
```

SaveCompiler(SaveProjectCompilerInstallationRequest, CancellationToken)

```
[HttpPost("compilers")] [HumanApprovalRequired("project.compiler.save", "Save compiler installation", "Store one compiler executable and validation profile.", "Medium", "Project toolchain administrator", false)] public Task<IResult> SaveCompiler(SaveProjectCompilerInstallationRequest request, CancellationToken cancellationToken)
```

SaveFilePatterns(Guid, SaveTrackedFilePatternRequest, CancellationToken)

```
[HttpPut("files/{trackedFileId:guid}/patterns")] [HumanApprovalRequired("project.file.patterns.save", "Save file structure patterns", "Store the approved structure and content-format regular expressions for one tracked project file.", "Medium", "Project structure maintainer", false)] public Task<IResult> SaveFilePatterns(Guid trackedFileId, SaveTrackedFilePatternRequest request, CancellationToken cancellationToken)
```


SaveWorkspace(SaveProjectWorkspaceRootRequest, CancellationToken)

```
[HttpPost("workspaces")] [HumanApprovalRequired("project.workspace.save", "Save project workspace", "Store one project, project-type, or global workspace root.", "Medium", "Project workspace administrator", false)] public Task<IResult> SaveWorkspace(SaveProjectWorkspaceRootRequest request, Cancellation_token cancellationToken)
```

ScanProject(Guid, ScanProjectFilesRequest, CancellationToken)

```
[HttpPost("projects/{projectId:guid}/scan")] [HumanApprovalRequired("project.files.scan", "Scan project files", "Read the selected project tree, store stable path metadata and hashes, and detect its solution file.", "Medium", "Project structure maintainer", false)] public Task<IResult> ScanProject(Guid projectId, ScanProjectFilesRequest request, Cancellation_token cancellationToken)
```

ValidateCompiler(Guid, bool, CancellationToken)

```
[HttpPost("compilers/{compilerId:guid}/validate")] [HumanApprovalRequired("project.compiler.validate", "Validate compiler installation", "Execute the selected compiler's bounded version probe.", "Medium", "Project toolchain administrator", false)] public Task<IResult> ValidateCompiler(Guid compilerId, bool userConfirmed, Cancellation_token cancellationToken)
```

VerifyRevision(Guid, RunProjectBuildVerificationRequest, CancellationToken)

```
[HttpPost("projects/{projectId:guid}/verify")] [HumanApprovalRequired("project.revision.build.verify", "Build project revision", "Execute the selected compiler against the approved project revision and store the bounded build/test evidence.", "High", "Build verification reviewer", true)] public Task<IResult> VerifyRevision(Guid projectId, RunProjectBuildVerificationRequest request, Cancellation_token cancellationToken)
```

api/LocalGPT.Controller.ProjectOrganicContextController.html

Class ProjectOrganicContextController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase ProjectOrganicContextController

```
[ApiController] [Route("api/projects/{projectId:guid}/organic-context")] public sealed class ProjectOrganicContextController : ControllerBase
```

🌟 Constructors 1

ProjectOrganicContextController(IProjectOrganicContextService, ILogger<ProjectOrganicContextController>)

```
public ProjectOrganicContextController(IProjectOrganicContextService context, ILogger<ProjectOrganicContextController> logger)
```

⚙️ Methods 2

Get(Guid, Guid?, CancellationToken)

```
[HttpGet] public Task<ActionResult<ProjectOrganicContext>> Get(Guid projectId, Guid? revisionId, Cancellation_token cancellationToken)
```

Save(Guid, SaveProjectOrganicContextRequest, CancellationToken)

```
[HttpPost] [HumanApprovalRequired("project.organic-context.save", "Save project organic wiring", "Persist the exact reviewed installer, compiler, command, knowledge, RegEx, debug and organ-plugin metadata for this project revision.", "High", "Project architecture reviewer", false)] public Task<ActionResult<ProjectOrganicContext>> Save(Guid projectId, SaveProjectOrganicContextRequest request, Cancellation_token cancellationToken)
```

api/LocalGPT.Controller.RemoteKnowledgeImportController.html

Class RemoteKnowledgeImportController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase RemoteKnowledgeImportController

```
[ApiController] [Route("api/knowledge/remote-import")] public sealed class RemoteKnowledgeImportController : ControllerBase
```

🌟 Constructors 1

RemoteKnowledgeImportController(IRemoteKnowledgeImportService, ILogger<RemoteKnowledgeImportController>)

```
public RemoteKnowledgeImportController(IRemoteKnowledgeImportService importer, ILogger<RemoteKnowledgeImportController> logger)
```

⚙️ Methods 2

Import(RemoteKnowledgeImportRequest, CancellationToken)

```
[HttpPost] [HumanApprovalRequired("knowledge.remote.import", "Import GitHub or webpage knowledge", "Download the selected public source, safely extract matching files, and save compact source maps to LocalGPT knowledge.", "High", "Knowledge curator", false)] public Task<ActionResult<RemoteKnowledgeImportResult>> Import(RemoteKnowledgeImportRequest request, Cancellation_token cancellationToken)
```

Preview(RemoteKnowledgeImportRequest, CancellationToken)

```
[HttpPost("preview")] public Task<ActionResult<RemoteKnowledgeImportResult>> Preview(RemoteKnowledgeImportRequest request, Cancellation_token cancellationToken)
```

Class RuntimePolicyController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase RuntimePolicyController

```
[ApiController] [Route("api/runtime-policy")] public sealed class RuntimePolicyController : ControllerBase
```

🌟 Constructors 1

RuntimePolicyController(ILocalGptRuntimePolicyDataService, ILocalGptRuntimePolicyStoreService, ILocalGptRuntimePolicySeedDataService, ILogger<RuntimePolicyController>)

```
public RuntimePolicyController(ILocalGptRuntimePolicyDataService runtimePolicy, ILocalGptRuntimePolicyStoreService runtimePolicyStore, ILocalGptRuntimePolicySeedDataService runtimePolicySeed, ILogger<RuntimePolicyController> logger)
```

⚙️ Methods 4

Get()

```
[HttpGet] public ActionResult<LocalGptRuntimePolicySnapshot> Get()
```

GetDefinition()

```
[HttpGet("definition")] public ActionResult<LocalGptRuntimePolicyDefinition> GetDefinition()
```

GetSeed()

```
[HttpGet("seed")] public ActionResult<LocalGptRuntimePolicySeedModel> GetSeed()
```

Reload()

```
[HttpPost("reload")] public ActionResult<LocalGptRuntimePolicySnapshot> Reload()
```

Class StructuredTextController

Namespace LocalGPT . Controller Assembly LocalGPT.dll

Inheritance object ControllerBase StructuredTextController

```
[ApiController] [Route("api/text/structured")] public sealed class StructuredTextController : ControllerBase
```

🌟 Constructors 1

StructuredTextController(ICollection<StructuredTextTranslationService>, IRegexPatternService, ILogger<StructuredTextController>)

```
public StructuredTextController(ICollection<StructuredTextTranslationService> translator, IRegexPatternService regexPatterns, ILogger<StructuredTextController> logger)
```

⚙️ Methods 3

InspectJson(StructuredJsonTranslationRequest)

```
[HttpPost("json/inspect")] public IActionResult InspectJson(StructuredJsonTranslationRequest request)
```

ListJsonRegexes(CancellationTokens)

```
[HttpGet("json/regexes")] public Task<IResult> ListJsonRegexes(CancellationTokens cancellationTokens)
```

TranslateJson(StructuredJsonTranslationRequest)

```
[HttpPost("json/translate")] public IActionResult TranslateJson(StructuredJsonTranslationRequest request)
```

Class ControllerRequestLoggingFilter

Namespace LocalGPT . Diagnostics Assembly LocalGPT.dll

Applies structured diagnostics to every MVC controller action without requiring each controller to repeat request lifecycle logging. Client disconnects remain cancellations; unexpected failures are logged and recorded in bounded activity.

Inheritance object ControllerRequestLoggingFilter

Implements IAsyncActionFilter IFilterMetadata

```
public sealed class ControllerRequestLoggingFilter : IAsyncActionFilter, IFilterMetadata
```

🌟 Constructors 1

ControllerRequestLoggingFilter(ILogger<ControllerRequestLoggingFilter>, IComponentActivityService)

Applies structured diagnostics to every MVC controller action without requiring each controller to repeat request lifecycle logging. Client disconnects remain cancellations; unexpected failures are logged and recorded in bounded activity.

```
public ControllerRequestLoggingFilter(ILogger<ControllerRequestLoggingFilter> logger, IComponentActivityService componentActivity)
```

⚙️ Methods 1

OnActionExecutionAsync(ActionExecutingContext, ActionExecutionDelegate)

```
public Task OnActionExecutionAsync(ActionExecutingContext context, ActionExecutionDelegate next)
```

Namespace LocalGPT.Diagnostics

Classes

Applies structured diagnostics to every MVC controller action without requiring each controller to repeat request lifecycle logging. Client disconnects remain cancellations; unexpected failures are logged and recorded in bounded activity.

Records circuit transitions so a disconnected browser is distinguishable from a blocked UI operation. This handler never performs UI work and therefore cannot delay rendering or disposal.

Adds bounded operation diagnostics to LocalGPT interface services without logging arguments, return values, prompts, source, database rows, credentials, or other payload content.

Class LocalGptCircuitDiagnosticsHandler

Namespace LocalGPT . Diagnostics Assembly LocalGPT.dll

Records circuit transitions so a disconnected browser is distinguishable from a blocked UI operation. This handler never performs UI work and therefore cannot delay rendering or disposal.

Inheritance object CircuitHandler LocalGptCircuitDiagnosticsHandler

```
public sealed class LocalGptCircuitDiagnosticsHandler : CircuitHandler
```

🌟 Constructors 1

LocalGptCircuitDiagnosticsHandler(ILogger<LocalGptCircuitDiagnosticsHandler>, IComponentActivityService)

Records circuit transitions so a disconnected browser is distinguishable from a blocked UI operation. This handler never performs UI work and therefore cannot delay rendering or disposal.

```
public LocalGptCircuitDiagnosticsHandler(ILogger<LocalGptCircuitDiagnosticsHandler> logger, IComponentActivityService componentActivity)
```

⚙️ Methods 4

OnCircuitClosedAsync(Circuit, CancellationToken)

```
public override Task OnCircuitClosedAsync(Circuit circuit, CancellationToken cancellationToken)
```

OnCircuitOpenedAsync(Circuit, CancellationToken)

```
public override Task OnCircuitOpenedAsync(Circuit circuit, CancellationToken cancellationToken)
```

OnConnectionDownAsync(Circuit, CancellationToken)

```
public override Task OnConnectionDownAsync(Circuit circuit, CancellationToken cancellationToken)
```

OnConnectionUpAsync(Circuit, CancellationToken)

```
public override Task OnConnectionUpAsync(Circuit circuit, CancellationToken cancellationToken)
```

Class ServiceMethodLoggingDispatchProxy

Namespace LocalGPT . Diagnostics Assembly LocalGPT.dll

Adds bounded operation diagnostics to LocalGPT interface services without logging arguments, return values, prompts, source, database rows, credentials, or other payload content.

Inheritance object DispatchProxy ServiceMethodLoggingDispatchProxy

```
public class ServiceMethodLoggingDispatchProxy : DispatchProxy
```

🌟 Constructors 1

ServiceMethodLoggingDispatchProxy()

```
public ServiceMethodLoggingDispatchProxy()
```

⚙️ Methods 2

Initialize(object, ILoggerFactory, bool)

```
public void Initialize(object serviceTarget, ILoggerFactory loggerFactory, bool isDevelopment)
```

Invoke(MethodInfo?, object?[]?)

```
protected override object? Invoke(MethodInfo? targetMethod, object?[]? args)
```

Namespace LocalGPT.Endpoints

Classes

Class MinecraftDiagnosticController

Namespace LocalGPT . Endpoints Assembly LocalGPT.dll

Inheritance object ControllerBase MinecraftDiagnosticController

```
[ApiController] [Route("")] public class MinecraftDiagnosticController : ControllerBase
```

🔥 Constructors 1

MinecraftDiagnosticController(ILogger<MinecraftDiagnosticController>, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService)

```
public MinecraftDiagnosticController(ILogger<MinecraftDiagnosticController> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog)
```

⚙️ Methods 5

GetMinecraftDatapackBenchmark(IMinecraftModWorkspaceService, INativeCommandRunner, ICouncilKnowledgeService, string?, bool, CancellationToken)

```
[HttpGet("/__diag/minecraft/datapack-benchmark")] [HumanApprovalRequired("diagnostic.minecraft.datapack.benchmark", "Build Minecraft datapack benchmark", "Create, validate, build, and persist the exact Minecraft datapack benchmark request.", "High", "Minecraft build reviewer", true)] public Task<IResult> GetMinecraftDatapackBenchmark(IMinecraftModWorkspaceService workspaceService, INativeCommandRunner commandRunner, ICouncilKnowledgeService knowledgeService, string? minecraftVersion, bool userConfirmed, CancellationToken ct)
```

GetMinecraftDatapackVersion(string?)

```
[HttpGet("/__diag/minecraft/datapack-version")] public IResult GetMinecraftDatapackVersion(string? minecraftVersion)
```

GetMinecraftDependencyVersion(string?, string?, string?, string?)

```
[HttpGet("/__diag/minecraft/dependency-version")] public IResult GetMinecraftDependencyVersion(string? loader, string? minecraftVersion, string? javaVersion, string? gradleVersion)
```

GetMinecraftProjectNameFileName(string, string, IMinecraftModWorkspaceService)

```
[HttpGet("/__artifacts/minecraft/{projectName}/{fileName}")] public IResult GetMinecraftProjectNameFileName(string projectName, string fileName, IMinecraftModWorkspaceService workspaces)
```

GetMinecraftWorkspaceSmoke(IMinecraftModWorkspaceService, string?, bool, CancellationToken)

```
[HttpGet("/__diag/minecraft/workspace-smoke")] [HumanApprovalRequired("diagnostic.minecraft.workspace.create", "Create Minecraft diagnostic workspace", "Create one bounded Minecraft diagnostic workspace from the exact selected loader and versions.", "High", "Minecraft workspace reviewer", false)] public Task<IResult> GetMinecraftWorkspaceSmoke(IMinecraftModWorkspaceService workspaceService, string? loader, bool userConfirmed, CancellationToken ct)
```

Namespace LocalGPT.Extensions

Classes

Class ObservableCollectionExtensions

Namespace LocalGPT . Extensions Assembly LocalGPT.dll

Inheritance object ObservableCollectionExtensions

```
public static class ObservableCollectionExtensions
```

⚙️ Methods 1

SyncWith<T, TKey>(IList<T>, IEnumerable<T>, Func<T, TKey>, bool, ConfiguredTaskAwaitable?)

```
public static Task SyncWith<T, TKey>(this IList<T> target, IEnumerable<T> updated, Func<T, TKey> keySelector, bool replaceIfDifferent = false, ConfiguredTaskAwaitable? configuredTaskAwaitableToInformUpdates = null) where TKey : notnull
```

Class StringExtensions

Namespace LocalGPT . Extensions Assembly LocalGPT.dll

Inheritance object StringExtensions

```
public static class StringExtensions
```

⚙️ Methods 1

ToJsonString(object, JsonSerializerOptions?)

```
public static string ToJsonString(this object obj, JsonSerializerOptions? jsonOptions = null)
```

Class ConfigureEmailLoggerOptions

Namespace LocalGPT . Helper Assembly LocalGPT.dll

Inheritance object ConfigureEmailLoggerOptions

Implements IConfigurationOptions < EmailLoggerCoreOptions >

```
public class ConfigureEmailLoggerOptions : IConfigurationOptions<EmailLoggerCoreOptions>
```

🌟 Constructors 1

ConfigureEmailLoggerOptions(IOptionsMonitor<EmailLoggerCoreOptions>)

```
public ConfigureEmailLoggerOptions(IOptionsMonitor<EmailLoggerCoreOptions> loggingOptions)
```

⚙️ Methods 1

Configure(EmailLoggerCoreOptions)

```
public void Configure(EmailLoggerCoreOptions options)
```

Class ConfigureFileLoggerOptions

Namespace LocalGPT . Helper Assembly LocalGPT.dll

Inheritance object ConfigureFileLoggerOptions

Implements IConfigurationOptions < FileLoggerCoreOptions >

```
public class ConfigureFileLoggerOptions : IConfigurationOptions<FileLoggerCoreOptions>
```

🌟 Constructors 1

ConfigureFileLoggerOptions(IOptionsMonitor<FileLoggerCoreOptions>)

```
public ConfigureFileLoggerOptions(IOptionsMonitor<FileLoggerCoreOptions> loggingOptions)
```

⚙️ Methods 1

Configure(FileLoggerCoreOptions)

```
public void Configure(FileLoggerCoreOptions options)
```

Class DisposableScope

Namespace LocalGPT . Helper Assembly LocalGPT.dll

Inheritance object DisposableScope

Implements IDisposable

```
public class DisposableScope : IDisposable
```

🌟 Constructors 1

DisposableScope(string)

```
public DisposableScope(string scopeInfo)
```

🐾 Properties 1

ScopeInfo

```
public string ScopeInfo { get; }
```

⚙️ Methods 2

Dispose()

```
public void Dispose()
```

Dispose(bool)

```
protected virtual void Dispose(bool disposing)
```

Namespace LocalGPT.Helper

Classes

Namespace LocalGPT

Namespaces

Classes

Class ChatHub

Namespace LocalGPT . Hubs Assembly LocalGPT.dll

Inheritance object Hub ChatHub

Implements IDisposable

```
public class ChatHub : Hub, IDisposable
```

🌟 Constructors 1

ChatHub(ILogger<ChatHub>)

```
public ChatHub(ILogger<ChatHub> logger)
```

⚙️ Methods 3

NotifyNewChatbotAnswer(string)

```
public Task NotifyNewChatbotAnswer(string message)
```

OnConnectedAsync()

```
public override Task OnConnectedAsync()
```

OnDisconnectedAsync(Exception?)

```
public override Task OnDisconnectedAsync(Exception? exception)
```

api/LocalGPT.Hubs.html

Namespace LocalGPT.Hubs

Classes

api/LocalGPT.Interfaces.html

Namespace LocalGPT.Interfaces

Classes

Interfaces

- Describes one strongly typed database-backed system-variable key and its seed default.
- Converts the progressively accumulated chat response into safe, renderable HTML for the Blazor message template. The renderer is stateless; response buffering remains owned by the per-response formatter.
- A model-family-specific protocol boundary. Profiles are stateless and selected once per response stream; they must never modify another protocol's content.
- Creates bounded runtime actor instances and maps them to Council role slots.
- Acts as the authoritative game engine boundary. Controllers and Council actors may propose actions, but only an approved director decision may advance a session.
- Predicts consequences for one family of runtime actors without owning the authoritative state.
- Normalizes editable per-model CPU/GPU road settings without coupling the UI to the council scheduler. The returned routes remain transport-compatible 1-Wire business objects.
- Resolves a stable, bounded hardware road for every council member. The planner is deliberately separate from the council orchestration so hardware growth does not turn the heartbeat service into another monolith.
- Reads, resolves and user-confirmedly persists database-owned Council team and workflow definitions.
- Supplies Council text patterns from the database-backed regex catalog. Runtime text services consume this contract instead of owning regex literals, options, timeouts, or process-wide pattern fields.
- Owns SQLite file validation and conservative recovery before EF Core opens the store.
- Keeps database-backed diagnostics dormant until migration and deterministic seeding have completed.
- Reconciles verified legacy SQLite schema state with EF migration history before normal migration. It preserves data, creates compatibility backups, and refuses ambiguous partial schemas.
- Locates versioned DocFX artifacts and exposes searchable compiler-generated XML comments for the running LocalGPT build.
- Adapts maintained XML comment text to the active localization catalog while preserving the original text as fallback.
- Provides approval-gated CRUD access to persistent records introduced by LocalGPT feature modules.
- Provides the persisted first-run guide, local model discovery summary, installer profiles and council quick starts.
- Capability-bearing boundary for execution of one exact persisted approval. It must never be injected into ordinary UI, model tools, or general services.
- Capability-bearing boundary for trusted local-human UI interaction only. It can create peer participation context, never operation approval.
- Records bounded, sanitized service-operation state for LocalGPT short-term context. The executor never swallows failures: cancellation and exceptions are recorded and rethrown.
- Starts intentionally non-blocking work while observing completion, cancellation, and failure. Use this instead of discarding a Task returned by an asynchronous method.
- Owns maintained LocalGPT system-variable keys so services never depend on ad-hoc string literals.

Interface **IAiConnectivityProbe**

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IAiConnectivityProbe
```

Methods 6

DiscoverLocalHostsAsync(CancellationToken)

```
Task<IReadOnlyList<LocalAiHostDiscoveryResult>> DiscoverLocalHostsAsync(CancellationToken ct)
```

TestAzureAsync(OpenAIServiceCoreOptions, CancellationToken)

```
Task<(bool ok, string message)> TestAzureAsync(OpenAIServiceCoreOptions o, CancellationToken ct)
```

TestLocalOpenAICompatAsync(ChatGPTLocalCoreOptions, CancellationToken)

```
Task<(bool ok, string message)> TestLocalOpenAICompatAsync(ChatGPTLocalCoreOptions o, CancellationToken ct)
```

TestOllamaAsync(OllamaCoreOptions, CancellationToken)

```
Task<(bool ok, string message)> TestOllamaAsync(OllamaCoreOptions o, CancellationToken ct)
```

TestOpenAIAsync(OpenAICompatOptions, CancellationToken)

```
Task<(bool ok, string message)> TestOpenAIAsync(OpenAICompatOptions o, CancellationToken ct)
```

TryStartLocalAsync(ChatGPTLocalCoreOptions, CancellationToken)

```
Task<(bool ok, string message)> TryStartLocalAsync(ChatGPTLocalCoreOptions o, CancellationToken ct)
```

Interface **IAiContextBootstrapService**

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IAiContextBootstrapService
```

Methods 1

BuildBootstrapPromptAsync(CancellationToken)

```
Task<string> BuildBootstrapPromptAsync(CancellationToken cancellationToken = default)
```

Interface **IAiFeatureReportService**

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IAiFeatureReportService
```

Properties 1

ReportRoot

```
string ReportRoot { get; }
```

Methods 1

WriteIfMissingFeatureReportAsync(string, string, CancellationToken)

```
Task<string?> WriteIfMissingFeatureReportAsync(string source, string responseText, CancellationToken cancellationToken = default)
```

Interface IAmbientLocalGptContext

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IAmbientLocalGptContext
```

Properties 1

Current

```
AmbientLocalGptContextSnapshot Current { get; }
```

Methods 2

PushCouncil(Guid, int, string, string?)

```
IDisposable PushCouncil(Guid councilRunId, int councilRound, string phase, string? correlationId = null)
```

PushSystem(string, string?)

```
IDisposable PushSystem(string source, string? correlationId = null)
```

Interface IApplicationLogReaderService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IApplicationLogReaderService
```

Properties 1

DatabasePath

```
string DatabasePath { get; }
```

Methods 2

BuildAiLogBriefingAsync(LogLevel, int, CancellationToken)

```
Task<string> BuildAiLogBriefingAsync(LogLevel minimumLevel = LogLevel.Warning, int take = 8, CancellationToken cancellationToken = default)
```

GetRecentAsync(LogLevel, int, CancellationToken)

```
Task<IReadOnlyList<ApplicationLogSummary>> GetRecentAsync(LogLevel minimumLevel = LogLevel.Warning, int take = 20, CancellationToken cancellationToken = default)
```

Interface IArtifactBuildExecutor

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IArtifactBuildExecutor
```

Methods 1

BuildAsync(string, string, string, string?, TimeSpan, CancellationToken, bool)

```
Task<ArtifactBuildExecutionResult> BuildAsync(string targetPath, string allowedRoot, string configuration, string? outputDirectory, TimeSpan requestedTimeout, CancellationToken cancellationToken = default, bool userConfirmed = false)
```

Interface IBuildDebugInventoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IBuildDebugInventoryService
```

Properties 1

ArtifactRoot

```
string ArtifactRoot { get; }
```

Methods 2

BuildBriefingAsync(CancellationToken)

```
Task<string> BuildBriefingAsync(CancellationToken cancellationToken = default)
```

CaptureAsync(bool, CancellationToken)

```
Task<BuildDebugInventory> CaptureAsync(bool copyFiles = false, CancellationToken cancellationToken = default)
```

Interface IChatClientFactory

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatClientFactory
```

Methods 1

Build()

```
CompositeChatClient Build()
```

Interface IChatContentRenderer

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Converts the progressively accumulated chat response into safe, renderable HTML for the Blazor message template. The renderer is stateless; response buffering remains owned by the per-response formatter.

```
public interface IChatContentRenderer
```

Methods 2

NormalizeForRender(string?)

```
string NormalizeForRender(string? content)
```

Render(string?)

```
string Render(string? content)
```

Interface IChatMemoryMessageMapper

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatMemoryMessageMapper
```

⚙️ Methods 4

BuildTitle(IReadOnlyList<BlazorChatMessage>)

```
string BuildTitle(IReadOnlyList<BlazorChatMessage> messages)
```

EnsureVisibleCouncilPrompt(ChatMemoryConversation, List<BlazorChatMessage>)

```
List<BlazorChatMessage> EnsureVisibleCouncilPrompt(ChatMemoryConversation conversation, List<BlazorChatMessage> messages)
```

ToBlazorChatMessage(ChatMemoryMessage)

```
BlazorChatMessage ToBlazorChatMessage(ChatMemoryMessage message)
```

ToRoleName(ChatMessageRole)

```
string ToRoleName(ChatMessageRole role)
```

Interface IChatMemoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatMemoryService
```

🔗 Properties 1

DatabasePath

```
string DatabasePath { get; }
```

⚙️ Methods 7

BuildMemoryBriefingAsync(int, int, CancellationToken)

```
Task<string> BuildMemoryBriefingAsync(int conversationTake = 5, int thoughtTake = 5, CancellationToken cancellationToken = default)
```

GetConversationsAsync(int, CancellationToken)

```
Task<IReadOnlyList<ChatMemoryConversationSummary>> GetConversationsAsync(int take = 50, CancellationToken cancellationToken = default)
```

GetMessageFeedbackAsync(Guid, CancellationToken)

```
Task<IReadOnlyList<ChatMessageFeedbackSnapshot>> GetMessageFeedbackAsync(Guid conversationId, CancellationToken cancellationToken = default)
```

GetRecentThoughtsAsync(int, CancellationToken)

```
Task<IReadOnlyList<ChatMemoryThought>> GetRecentThoughtsAsync(int take = 12, CancellationToken cancellationToken = default)
```

LoadConversationAsync(Guid, CancellationToken)

```
Task<ChatMemoryConversationSnapshot?> LoadConversationAsync(Guid conversationId, CancellationToken cancellationToken = default)
```

RecordMessageFeedbackAsync(Guid, int, bool?, string?, CancellationToken)

```
Task<bool> RecordMessageFeedbackAsync(Guid conversationId, int sortOrder, bool? isPositive, string? comment, CancellationToken cancellationToken = default)
```

SaveConversationAsync(string, IReadOnlyList<BlazorChatMessage>, Guid?, CancellationToken)

```
Task<Guid?> SaveConversationAsync(string providerName, IReadOnlyList<BlazorChatMessage> messages, Guid? conversationId = null, CancellationToken cancellationToken = default)
```

Interface IChatProtocolProfile

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

A model-family-specific protocol boundary. Profiles are stateless and selected once per response stream; they must never modify another protocol's content.

```
public interface IChatProtocolProfile
```

Properties 2

Priority

```
int Priority { get; }
```

Protocol

```
ChatResponseProtocol Protocol { get; }
```

Methods 3

MatchesModel(string)

```
bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
string NormalizeContent(string text)
```

NormalizeThinking(string)

```
string NormalizeThinking(string text)
```

Interface IChatProtocolProfileCatalog

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatProtocolProfileCatalog
```

Properties 1

Profiles

```
IReadOnlyList<IChatProtocolProfile> Profiles { get; }
```

Methods 1

ResolveExact(ChatResponseProtocol)

```
IChatProtocolProfile ResolveExact(ChatResponseProtocol protocol)
```

Interface IChatProtocolResolver

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatProtocolResolver
```

Methods 1

Resolve(OllamaCoreOptions)

```
ChatResponseProtocol Resolve(OllamaCoreOptions options)
```

Interface IChatProtocolTextService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatProtocolTextService
```

⚙️ Methods 2

ContainsAny(string, LocalGptRuntimeCollection)

```
bool ContainsAny(string value, LocalGptRuntimeCollection collection)
```

ReplaceAll(string, LocalGptRuntimeCollection)

```
string ReplaceAll(string text, LocalGptRuntimeCollection collection)
```

Interface IChatResponseFormatter

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatResponseFormatter
```

⚙️ Methods 3

AppendContent(string)

```
IEnumerable<string> AppendContent(string text)
```

AppendThinking(string)

```
IEnumerable<string> AppendThinking(string text)
```

Complete()

```
IEnumerable<string> Complete()
```

Interface IChatResponseFormatterFactory

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatResponseFormatterFactory
```

⚙️ Methods 1

Create(ChatResponseProtocol, string?)

```
IChatResponseFormatter Create(ChatResponseProtocol protocol, string? missingFinalAnswerNotice = null)
```

Interface IChatSessionContext

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatSessionContext
```

Properties 4

ApplicationVersion

```
string ApplicationVersion { get; }
```

ConversationId

```
Guid? ConversationId { get; }
```

ProjectId

```
Guid? ProjectId { get; }
```

ProjectVersionId

```
Guid? ProjectVersionId { get; }
```

Methods 4

Restore(ChatSessionContextSnapshot)

```
void Restore(ChatSessionContextSnapshot snapshot)
```

SetConversation(Guid?)

```
void SetConversation(Guid? conversationId)
```

SetProject(Guid?, Guid?)

```
void SetProject(Guid? projectId, Guid? projectVersionId)
```

Snapshot()

```
ChatSessionContextSnapshot Snapshot()
```

Interface IChatUploadWorkspaceService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IChatUploadWorkspaceService
```

🐾 Properties 1

WorkspaceRoot

```
string WorkspaceRoot { get; }
```

⚙️ Methods 8

CreateWorkspaceAsync(string, IEnumerable<ChatUploadWorkspaceInputFile>, CancellationToken)

```
Task<ChatUploadWorkspaceResult> CreateWorkspaceAsync(string prompt, IEnumerable<ChatUploadWorkspaceInputFile> files, CancellationToken cancellationTok = default)
```

GetLatestContextMarkdown(int, TimeSpan?)

```
string GetLatestContextMarkdown(int maxCharacters, TimeSpan? maxAge = null)
```

GetLatestWorkspace(TimeSpan?)

```
ChatUploadWorkspaceSummary? GetLatestWorkspace(TimeSpan? maxAge = null)
```

ListFiles(string, int)

```
IReadOnlyList<ChatUploadWorkspaceFileSummary> ListFiles(string workspaceName, int take = 250)
```

ListWorkspaces(int)

```
IReadOnlyList<ChatUploadWorkspaceSummary> ListWorkspaces(int take = 20)
```

ReadContextMarkdownAsync(string, int, CancellationToken)

```
Task<string> ReadContextMarkdownAsync(string workspaceName, int maxCharacters, CancellationToken cancellationTok = default)
```

ReadFileAsync(string, string, int, CancellationToken)

```
Task<ChatUploadWorkspaceFileReadResult?> ReadFileAsync(string workspaceName, string relativePath, int maxCharacters, CancellationToken cancellationTok = default)
```

ResolveWorkspacePath(string)

```
string? ResolveWorkspacePath(string workspaceName)
```


Interface ICodeGenerationWorkflowService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICodeGenerationWorkflowService
```

⚙️ Methods 5

CreateReviewAsync(CreateCodeGenerationReviewRequest, CancellationTokens)

```
Task<CodeGenerationReviewSnapshot> CreateReviewAsync(CreateCodeGenerationReviewRequest request, CancellationTokens cancellationTokens = default)
```

ExecuteReviewAsync(Guid, ExecuteCodeGenerationReviewRequest, CancellationTokens)

```
Task<CodeGenerationExecutionResult> ExecuteReviewAsync(Guid reviewId, ExecuteCodeGenerationReviewRequest request, CancellationTokens cancellationTokens = default)
```

GetReviewAsync(Guid, CancellationTokens)

```
Task<CodeGenerationReviewSnapshot> GetReviewAsync(Guid reviewId, CancellationTokens cancellationTokens = default)
```

ListReviewsAsync(Guid?, int, CancellationTokens)

```
Task<IReadOnlyList<CodeGenerationReviewSnapshot>> ListReviewsAsync(Guid? projectId = null, int take = 20, CancellationTokens cancellationTokens = default)
```

RejectReviewAsync(Guid, RejectCodeGenerationReviewRequest, CancellationTokens)

```
Task<CodeGenerationReviewSnapshot> RejectReviewAsync(Guid reviewId, RejectCodeGenerationReviewRequest request, CancellationTokens cancellationTokens = default)
```

Interface IComponentActivityService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IComponentActivityService
```

⚙️ Methods 6

BuildBriefing(int)

```
string BuildBriefing(int take = 12)
```

GetRecent(int)

```
IReadOnlyList<ComponentActivitySnapshot> GetRecent(int take = 20)
```

RecordFailure(string, string, Exception, string?)

```
void RecordFailure(string component, string operation, Exception exception, string? route = null)
```

RecordInformation(string, string, string, string?)

```
void RecordInformation(string component, string operation, string summary, string? route = null)
```

RecordNavigation(string)

```
void RecordNavigation(string route)
```

RecordWarning(string, string, string, string?)

```
void RecordWarning(string component, string operation, string summary, string? route = null)
```

Interface IConfigurationWriter

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IConfigurationWriter
```

⚙️ Methods 1

SaveAsync(ConfigurationRoot, CancellationToken)

```
Task SaveAsync(ConfigurationRoot root, CancellationToken ct = default)
```

Interface ICouncilArtifactService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilArtifactService
```

🐾 Properties 1

ArtifactRoot

```
string ArtifactRoot { get; }
```

⚙️ Methods 5

CreateImplementationArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, CancellationToken)

```
Task<IReadOnlyList<CouncilArtifact>> CreateImplementationArtifactsAsync(MultiModelCouncilRequest request, MultiModelCouncilResult result, CancellationToken cancellationToken = default)
```

CreateMinecraftDatapackArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
Task<IReadOnlyList<CouncilArtifact>> CreateMinecraftDatapackArtifactsAsync(MultiModelCouncilRequest request, MultiModelCouncilResult result, string timestamp, CancellationToken cancellationToken)
```

CreateMinecraftSkeletonMatrixArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
Task<IReadOnlyList<CouncilArtifact>> CreateMinecraftSkeletonMatrixArtifactsAsync(MultiModelCouncilRequest request, MultiModelCouncilResult result, string timestamp, CancellationToken cancellationToken)
```

CreateSolutionZipArtifactAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
Task<CouncilArtifact> CreateSolutionZipArtifactAsync(MultiModelCouncilRequest request, MultiModelCouncilResult result, string timestamp, CancellationToken cancellationToken)
```

TryCreateDllArtifactAsync(string, string, string, bool, CancellationToken)

```
Task<CouncilArtifact?> TryCreateDllArtifactAsync(string sourceFileName, string source, string targetArea, bool userConfirmedArtifactBuild, CancellationToken cancellationToken)
```

Interface ICouncilCodeGenerationPlanService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilCodeGenerationPlanService
```

⚙️ Methods 1

Parse(string)

```
CouncilCodeGenerationPlanResult Parse(string councilAnswer)
```

Interface ICouncilDxFunctionOrchestrator

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilDxFunctionOrchestrator
```

⚙️ Methods 1

ExecuteRequestedCallsAsync(MultiModelCouncilResult, MultiModelCouncilStep, CancellationToken)

```
Task<IReadOnlyList<MultiModelCouncilStep>> ExecuteRequestedCallsAsync(MultiModelCouncilResult result, MultiModelCouncilStep sourceStep, CancellationToken cancellationToken = default)
```

Interface ICouncilDxFunctionPolicyDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilDxFunctionPolicyDataService
```

⚙️ Methods 1

GetPolicyAsync(CancellationToken)

```
Task<CouncilDxFunctionPolicy> GetPolicyAsync(CancellationToken cancellationToken = default)
```

Interface ICouncilGameActorRuntimeFactory

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Creates bounded runtime actor instances and maps them to Council role slots.

```
public interface ICouncilGameActorRuntimeFactory
```

⚙️ Methods 1

CreateActors(CouncilGameDirectorContext, CouncilGameActorKind)

Creates the actor instances owned by one subdirector for the current immutable turn snapshot.

```
IReadOnlyList<CouncilGameActorRuntimeDescriptor> CreateActors(CouncilGameDirectorContext context, CouncilGameActorKind actorKind)
```

Interface ICouncilGameDirectorService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Acts as the authoritative game engine boundary. Controllers and Council actors may propose actions, but only an approved director decision may advance a session.

```
public interface ICouncilGameDirectorService
```

⚙️ Methods 1

EvaluateAsync(CouncilGameDirectorContext, CancellationToken)

Validates one proposal and gathers bounded creature/object predictions without mutating session state.

```
Task<CouncilGameDirectorDecision> EvaluateAsync(CouncilGameDirectorContext context, CancellationToken cancellationToken = default)
```

Interface ICouncilGameSessionService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilGameSessionService
```

⚙️ Methods 9

ApplyControlAsync(CouncilGameControlRequest, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> ApplyControlAsync(CouncilGameControlRequest request, CancellationTokens cancellationTokens = default)
```

GetActiveAsync(Guid?, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> GetActiveAsync(Guid? conversationId, CancellationTokens cancellationTokens = default)
```

GetAsync(Guid, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> GetAsync(Guid sessionId, CancellationTokens cancellationTokens = default)
```

ListAsync(bool, CancellationTokens)

```
Task<IReadOnlyList<CouncilGameSessionSnapshot>> ListAsync(bool includeCompleted = false, CancellationTokens cancellationTokens = default)
```

PreviewControlAsync(CouncilGameControlRequest, CancellationTokens)

```
Task<CouncilGameDirectorDecision> PreviewControlAsync(CouncilGameControlRequest request, CancellationTokens cancellationTokens = default)
```

SetControlModeAsync(Guid, CouncilGameControlMode, bool, int, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> SetControlModeAsync(Guid sessionId, CouncilGameControlMode mode, bool autoplayEnabled, int autoplayDelayMilliseconds = 1200, CancellationTokens cancellationTokens = default)
```

SetInputGateAsync(SetCouncilGameInputGateRequest, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> SetInputGateAsync(SetCouncilGameInputGateRequest request, CancellationTokens cancellationTokens = default)
```

StartAsync(StartCouncilGameRequest, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> StartAsync(StartCouncilGameRequest request, CancellationTokens cancellationTokens = default)
```

SubmitFrameAsync(SubmitCouncilGameFrameRequest, CancellationTokens)

```
Task<CouncilGameSessionSnapshot> SubmitFrameAsync(SubmitCouncilGameFrameRequest request, CancellationTokens cancellationTokens = default)
```

⚡ Events 1

Changed

```
event Action<Guid>? Changed
```

Interface ICouncilGameSubdirector

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Predicts consequences for one family of runtime actors without owning the authoritative state.

```
public interface ICouncilGameSubdirector
```

🐾 Properties 2

ActorKind

```
CouncilGameActorKind ActorKind { get; }
```

Key

```
string Key { get; }
```

⚙️ Methods 1

PredictAsync(CouncilGameDirectorContext, CancellationTokens)

Produces a bounded prediction for the proposed action.

```
Task<CouncilGameSubdirectorPrediction> PredictAsync(CouncilGameDirectorContext context, CancellationTokens cancellationTokens = default)
```

Interface ICouncilHardwareRoadConfigurationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Normalizes editable per-model CPU/GPU road settings without coupling the UI to the council scheduler. The returned routes remain transport-compatible 1-Wire business objects.

```
public interface ICouncilHardwareRoadConfigurationService
```

⚙️ Methods 4

Interpolate(int, int, int)

```
int Interpolate(int minimum, int maximum, int loadPercent)
```

Normalize(OneWireCouncilModelRoute)

```
OneWireCouncilModelRoute Normalize(OneWireCouncilModelRoute route)
```

NormalizeLoadPercent(int)

```
int NormalizeLoadPercent(int value)
```

Synchronize(IEnumerable<string>, IEnumerable<OneWireCouncilModelRoute>?)

```
IReadOnlyList<OneWireCouncilModelRoute> Synchronize(IEnumerable<string> modelNames, IEnumerable<OneWireCouncilModelRoute>? existingRoutes)
```

Interface ICouncilHardwareRoadPlanner

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Resolves a stable, bounded hardware road for every council member. The planner is deliberately separate from the council orchestration so hardware growth does not turn the heartbeat service into another monolith.

```
public interface ICouncilHardwareRoadPlanner
```

⚙️ Methods 1

BuildPlans(IReadOnlyCollection<OneWireCouncilModelRoute>?, IReadOnlyCollection<string>, int, int, int, int?)

```
IReadOnlyDictionary<string, CouncilHardwareRoadPlan> BuildPlans(IReadOnlyCollection<OneWireCouncilModelRoute>? configuredRoutes,
IReadOnlyCollection<string> participants, int requestedMaxOutputTokens, int requestedMaxContextTokens, int resourceLoadPercent, int? fallbackOllamaNumGpu)
```

Interface ICouncilKnowledgeService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilKnowledgeService
```

Properties 1

DatabasePath

```
string DatabasePath { get; }
```

Methods 6

BuildKnowledgeBriefingAsync(int, CancellationToken)

```
Task<string> BuildKnowledgeBriefingAsync(int take = 8, CancellationToken cancellationToken = default)
```

DeleteEntryAsync(Guid, CancellationToken)

```
Task DeleteEntryAsync(Guid id, CancellationToken cancellationToken = default)
```

EnsureCreatedAsync(CancellationToken)

```
Task EnsureCreatedAsync(CancellationToken cancellationToken = default)
```

GetEntriesAsync(bool, int, CancellationToken)

```
Task<IReadOnlyList<CouncilKnowledgeEntry>> GetEntriesAsync(bool includeArchived = false, int take = 100, CancellationToken cancellationToken = default)
```

SaveEntryAsync(CouncilKnowledgeEntry, CancellationToken)

```
Task<CouncilKnowledgeEntry> SaveEntryAsync(CouncilKnowledgeEntry entry, CancellationToken cancellationToken = default)
```

SaveFromCouncilRunAsync(MultiModelCouncilResult, CancellationToken)

```
Task<Guid> SaveFromCouncilRunAsync(MultiModelCouncilResult result, CancellationToken cancellationToken = default)
```

Interface ICouncilLiveSessionService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilLiveSessionService
```

⚙️ Methods 9

Append(Guid, string)

```
void Append(Guid runId, string text)
```

AppendUserMessage(Guid, string)

```
void AppendUserMessage(Guid runId, string text)
```

Begin(Guid, IReadOnlyList<string>, string, string)

```
CancellationToken Begin(Guid runId, IReadOnlyList<string> councilMembers, string userMessage, string initialTranscript)
```

Cancel(Guid)

```
bool Cancel(Guid runId)
```

Complete(Guid)

```
void Complete(Guid runId)
```

Get(Guid)

```
CouncilLiveSessionSnapshot? Get(Guid runId)
```

GetActive()

```
IReadOnlyList<CouncilLiveSessionSnapshot> GetActive()
```

GetActiveSummaries()

```
IReadOnlyList<CouncilLiveSessionSummary> GetActiveSummaries()
```

GetSummary(Guid)

```
CouncilLiveSessionSummary? GetSummary(Guid runId)
```

⚡ Events 1

Changed

```
event Action<Guid>? Changed
```

Interface ICouncilModelRequestLease

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilModelRequestLease : IDisposable
```

🐾 Properties 3

IsEnabled

```
bool IsEnabled { get; }
```

Plan

```
CouncilHardwareRoadPlan Plan { get; }
```

Revision

```
long Revision { get; }
```

Interface ICouncilPreflightService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilPreflightService
```

⚙️ Methods 2

BuildMemberReadinessPrompt(string, IReadOnlyList<string>, CouncilPreflightReport)

```
string BuildMemberReadinessPrompt(string modelName, IReadOnlyList<string> participants, CouncilPreflightReport report)
```

PrepareAsync(MultiModelCouncilRequest, IReadOnlyList<string>, IReadOnlyDictionary<string, CouncilHardwareRoadPlan>, CancellationToken)

```
Task<CouncilPreflightReport> PrepareAsync(MultiModelCouncilRequest request, IReadOnlyList<string> participants, IReadOnlyDictionary<string, CouncilHardwareRoadPlan> modelRoutes, CancellationToken cancellationToken = default)
```


Interface ICouncilRunConfigurationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilRunConfigurationService
```

⚙️ Methods 11

AcquireModelRequestAsync(Guid, string, CouncilHardwareRoadPlan, CancellationToken)

```
ValueTask<ICouncilModelRequestLease> AcquireModelRequestAsync(Guid runId, string modelName, CouncilHardwareRoadPlan fallbackPlan, CancellationToken cancellationToken = default)
```

BeginRound(Guid, int, string)

```
void BeginRound(Guid runId, int round, string phase)
```

Complete(Guid)

```
void Complete(Guid runId)
```

Ensure(MultiModelCouncilRequest, IReadOnlyCollection<string>)

```
CouncilRunConfigurationSnapshot Ensure(MultiModelCouncilRequest request, IReadOnlyCollection<string> participants)
```

Get(Guid)

```
CouncilRunConfigurationSnapshot? Get(Guid runId)
```

GetPreparation()

```
CouncilPreparationConfiguration? GetPreparation()
```

GetRoundCancellationToken(Guid, int, string)

```
CancellationToken GetRoundCancellationToken(Guid runId, int round, string phase)
```

IsRoundSkipRequested(Guid, int, string)

```
bool IsRoundSkipRequested(Guid runId, int round, string phase)
```

RequestSkipCurrentRound(Guid)

```
bool RequestSkipCurrentRound(Guid runId)
```

SavePreparation(CouncilPreparationConfiguration)

```
CouncilPreparationConfiguration SavePreparation(CouncilPreparationConfiguration configuration)
```

Update(Guid, IReadOnlyCollection<OneWireCouncilModelRoute>, int, int, int, int?, bool)

```
bool Update(Guid runId, IReadOnlyCollection<OneWireCouncilModelRoute> routes, int resourceLoadPercent, int requestedMaxOutputTokens, int requestedMaxContextTokens, int? fallbackOllamaNumGpu, bool allowParallelHardwareRoads)
```

⚡ Events 1

Changed

```
event Action<Guid>? Changed
```

Interface ICouncilRuntimeClassService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilRuntimeClassService
```

⚙️ Methods 3

FindAsync(string?, CancellationToken)

```
Task<CouncilRuntimeClassDefinition?> FindAsync(string? key, CancellationToken cancellationToken = default)
```

GetDefinitionsAsync(bool, CancellationToken)

```
Task<IReadOnlyList<CouncilRuntimeClassDefinition>> GetDefinitionsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveAsync(SaveCouncilRuntimeClassRequest, CancellationToken)

```
Task<CouncilRuntimeClassDefinition> SaveAsync(SaveCouncilRuntimeClassRequest request, CancellationToken cancellationToken = default)
```

Interface ICouncilSpoolerService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICouncilSpoolerService
```

⚙️ Methods 6

AddStep(Guid, MultiModelCouncilStep)

```
void AddStep(Guid runId, MultiModelCouncilStep step)
```

Begin(MultiModelCouncilResult)

```
void Begin(MultiModelCouncilResult result)
```

Complete(MultiModelCouncilResult, bool)

```
void Complete(MultiModelCouncilResult result, bool failed = false)
```

GetSnapshot(Guid)

```
CouncilSpoolerSnapshot? GetSnapshot(Guid runId)
```

GetSnapshots(bool, int)

```
IReadOnlyList<CouncilSpoolerSnapshot> GetSnapshots(bool includeCompleted = true, int take = 30)
```

Update(Guid, int, string)

```
void Update(Guid runId, int round, string phase)
```

⚡ Events 1

Changed

```
event Action? Changed
```

Interface ICouncilTeamConfigurationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Reads, resolves and user-confirmedly persists database-owned Council team and workflow definitions.

```
[DocumentationUpdated("2.1.20")] public interface ICouncilTeamConfigurationService
```

⚙️ Methods 3

FindTeamAsync(string?, CancellationToken)

Finds one enabled Council team by stable key, falling back to the general key for blank input.

```
Task<OrganicCouncilTeamDefinition?> FindTeamAsync(string? key, CancellationToken cancellationToken = default)
```

GetTeamsAsync(bool, CancellationToken)

Returns enabled or complete Council-team configuration records.

```
Task<IReadOnlyList<OrganicCouncilTeamDefinition>> GetTeamsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveAsync(SaveCouncilTeamConfigurationRequest, CancellationToken)

Creates or updates one Council team after explicit user confirmation and validation.

```
Task<OrganicCouncilTeamDefinition> SaveAsync(SaveCouncilTeamConfigurationRequest request, CancellationToken cancellationToken = default)
```

Interface ICouncilTextPatternDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Supplies Council text patterns from the database-backed regex catalog. Runtime text services consume this contract instead of owning regex literals, options, timeouts, or process-wide pattern fields.

```
public interface ICouncilTextPatternDataService
```

Properties 38

AlphaNumericWordPattern

```
Regex AlphaNumericWordPattern { get; }
```

BlazorFrontendPattern

```
Regex BlazorFrontendPattern { get; }
```

CapabilityGapBlockPattern

```
Regex CapabilityGapBlockPattern { get; }
```

CouncilDxFunctionCallPattern

```
Regex CouncilDxFunctionCallPattern { get; }
```

DatapackPattern

```
Regex DatapackPattern { get; }
```

DevExpressDocumentPattern

```
Regex DevExpressDocumentPattern { get; }
```

DotNetPattern

```
Regex DotNetPattern { get; }
```

FormerThoughtBreakPattern

```
Regex FormerThoughtBreakPattern { get; }
```

FormerThoughtClosingFencePattern

```
Regex FormerThoughtClosingFencePattern { get; }
```

FormerThoughtCodeWrapperPattern

```
Regex FormerThoughtCodeWrapperPattern { get; }
```

FormerThoughtExcessLineBreakPattern

```
Regex FormerThoughtExcessLineBreakPattern { get; }
```

FormerThoughtOpeningFencePattern

```
Regex FormerThoughtOpeningFencePattern { get; }
```

FormerThoughtPresentationWrapperPattern

```
Regex FormerThoughtPresentationWrapperPattern { get; }
```

FrontendPattern

```
Regex FrontendPattern { get; }
```

HelpfulSourceLinePattern

```
Regex HelpfulSourceLinePattern { get; }
```

IdentifierSeparatorPattern

```
Regex IdentifierSeparatorPattern { get; }
```

IntegerPattern

```
Regex IntegerPattern { get; }
```

KnowledgeBlockPattern

```
Regex KnowledgeBlockPattern { get; }
```

LoggingPattern

```
Regex LoggingPattern { get; }
```

MarkdownHeadingProjectNamePattern

```
Regex MarkdownHeadingProjectNamePattern { get; }
```

MinecraftExplicitProjectNamePattern

```
Regex MinecraftExplicitProjectNamePattern { get; }
```

MinecraftNamedProjectPattern

```
Regex MinecraftNamedProjectPattern { get; }
```

MinecraftPattern

```
Regex MinecraftPattern { get; }
```

MinecraftQuotedProjectNamePattern

```
Regex MinecraftQuotedProjectNamePattern { get; }
```

MinecraftSkeletonMatrixPattern

```
Regex MinecraftSkeletonMatrixPattern { get; }
```

MinecraftVersionPattern

```
Regex MinecraftVersionPattern { get; }
```

MissingFeaturePattern

```
Regex MissingFeaturePattern { get; }
```

ModIdCleanerPattern

```
Regex ModIdCleanerPattern { get; }
```

NameCleanerPattern

```
Regex NameCleanerPattern { get; }
```

PackagePartCleanerPattern

```
Regex PackagePartCleanerPattern { get; }
```

PackageReferencePattern

```
Regex PackageReferencePattern { get; }
```

SensitiveNamePattern

```
Regex SensitiveNamePattern { get; }
```

StreamStatusPattern

```
Regex StreamStatusPattern { get; }
```

StructuredFieldPattern

```
Regex StructuredFieldPattern { get; }
```

TargetFrameworkPattern

```
Regex TargetFrameworkPattern { get; }
```

ThinkingBlockPattern

```
Regex ThinkingBlockPattern { get; }
```

TruncatedTailPattern

```
Regex TruncatedTailPattern { get; }
```

WhitespacePattern

```
Regex WhitespacePattern { get; }
```

⚙️ Methods 1

ExtractStructuredField(string, string)

```
string? ExtractStructuredField(string body, string name)
```

api/LocalGPT.Interfaces.ICustomVersion.html

Interface ICustomVersion

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ICustomVersion
```

🐾 Properties 1

Version

```
string Version { get; set; }
```

api/LocalGPT.Interfaces.IDatabaseFileHealthService.html

Interface IDatabaseFileHealthService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Owns SQLite file validation and conservative recovery before EF Core opens the store.

```
public interface IDatabaseFileHealthService
```

🐾 Properties 1

DatabasePath

```
string DatabasePath { get; }
```

⚙️ Methods 3

EnsureHealthyOrRecoverAsync(CancellationTokens)

```
Task EnsureHealthyOrRecoverAsync(CancellationTokens cancellationTokens = default)
```

IsSqliteCorruption(Exception)

```
bool IsSqliteCorruption(Exception exception)
```

RecoverMalformedDatabaseAsync(CancellationTokens)

```
Task RecoverMalformedDatabaseAsync(CancellationTokens cancellationTokens = default)
```

api/LocalGPT.Interfaces.IDatabaseInitializationService.html

Interface IDatabaseInitializationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDatabaseInitializationService
```

⚙️ Methods 1

InitializeAsync(CancellationTokens)

```
Task InitializeAsync(CancellationTokens cancellationTokens = default)
```

Interface IDatabaseLoggerReadiness

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Keeps database-backed diagnostics dormant until migration and deterministic seeding have completed.

```
public interface IDatabaseLoggerReadiness
```

Properties 1

IsReady

```
bool IsReady { get; }
```

Methods 2

MarkReady()

```
void MarkReady()
```

WaitUntilReadyAsync(CancellationTokens)

```
Task WaitUntilReadyAsync(CancellationTokens cancellationTokens = default)
```

Interface IDatabaseMigrationCompatibilityService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Reconciles verified legacy SQLite schema state with EF migration history before normal migration. It preserves data, creates compatibility backups, and refuses ambiguous partial schemas.

```
public interface IDatabaseMigrationCompatibilityService
```

Methods 1

PrepareAsync(CancellationTokens)

```
Task PrepareAsync(CancellationTokens cancellationTokens = default)
```

Interface IDebugArtifactInspectionService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDebugArtifactInspectionService
```

Methods 1

InspectAsync(string, CancellationTokens)

```
Task<DebugArtifactInspectionResult> InspectAsync(string filePath, CancellationTokens cancellationTokens = default)
```

Interface IDeferredDxAiInvocationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDeferredDxAiInvocationService
```

Methods 2

ExecuteApprovedForHeartbeatAsync(Guid, int, CancellationTokens)

```
Task<IReadOnlyList<DeferredDxAiExecutionOutcome>> ExecuteApprovedForHeartbeatAsync(Guid councilRunId, int councilRound, CancellationTokens cancellationTokens = default)
```

QueueAsync(string, DxaiFunctionInvocationRequest, Guid, string, Guid?, CancellationTokens)

```
Task QueueAsync(string functionName, DxaiFunctionInvocationRequest request, Guid approvalRequestId, string correlationId, Guid? councilRunId, CancellationTokens cancellationTokens = default)
```

Interface IDocumentationCatalogService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Locates versioned DocFX artifacts and exposes searchable compiler-generated XML comments for the running LocalGPT build.

```
[DocumentationUpdated("2.2.8")] public interface IDocumentationCatalogService
```

⚙️ Methods 5

GetComment(string, string?)

Returns one localized XML documentation member by its stable compiler member identifier.

```
LocalGptDocumentationComment? GetComment(string memberId, string? culture = null)
```

GetHtmlFilePath(string?)

Returns one generated HTML or supporting asset path from the selected documentation root.

```
string? GetHtmlFilePath(string? relativePath)
```

GetPdfPath()

Returns the absolute PDF path when a compatible generated documentation artifact exists.

```
string? GetPdfPath()
```

GetStatus()

Returns availability, version and application-relative links for generated documentation.

```
LocalGptDocumentationStatus GetStatus()
```

SearchComments(string?, int, string?)

Searches member identifiers, summaries and remarks without exposing arbitrary files.

```
IReadOnlyList<LocalGptDocumentationComment> SearchComments(string? query, int limit = 100, string? culture = null)
```

Interface IDocumentationTranslationAdapter

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Adapts maintained XML comment text to the active localization catalog while preserving the original text as fallback.

```
[DocumentationUpdated("2.1.20")] public interface IDocumentationTranslationAdapter
```

⚙️ Methods 1

Adapt(LocalGptDocumentationComment, string?)

Returns a localized copy of one documentation comment for the requested culture.

```
LocalGptDocumentationComment Adapt(LocalGptDocumentationComment comment, string? culture = null)
```


Interface IDxAiFunctionCatalogService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDxAiFunctionCatalogService
```

⚙️ Methods 6

GetByFunctionNameAsync(string, CancellationToken)

```
Task<DxAiFunctionCatalogEntry?> GetByFunctionNameAsync(string functionName, CancellationToken cancellationToken = default)
```

GetEntriesAsync(CancellationToken)

```
Task<IReadOnlyList<DxAiFunctionCatalogEntry>> GetEntriesAsync(CancellationToken cancellationToken = default)
```

GetEntryAsync(string, CancellationToken)

```
Task<DxAiFunctionCatalogEntry?> GetEntryAsync(string catalogKey, CancellationToken cancellationToken = default)
```

GetExposedToPeerAsync(string, CancellationToken)

```
Task<IReadOnlyList<DxAiFunctionCatalogEntry>> GetExposedToPeerAsync(string peerId, CancellationToken cancellationToken = default)
```

SavePolicyAsync(DxAiFunctionCatalogSaveRequest, CancellationToken)

```
Task<DxAiFunctionCatalogEntry> SavePolicyAsync(DxAiFunctionCatalogSaveRequest request, CancellationToken cancellationToken = default)
```

SynchronizeAsync(CancellationToken)

```
Task<IReadOnlyList<DxAiFunctionCatalogEntry>> SynchronizeAsync(CancellationToken cancellationToken = default)
```

Interface IDxAiFunctionHandler

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDxAiFunctionHandler
```

🐾 Properties 1

Descriptor

```
DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Interface IDxAiFunctionJsonService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDxAiFunctionJsonService
```

Properties 1

Options

```
JsonSerializerOptions Options { get; }
```

Methods 4

Bind<T>(JsonElement)

```
DxAiFunctionParameterBinding<T> Bind<T>(JsonElement element) where T : new()
```

Deserialize<T>(JsonElement)

```
T Deserialize<T>(JsonElement element) where T : new()
```

InvalidParameters(string)

```
DxAiFunctionInvocationResult InvalidParameters(string error)
```

Success(object?, string)

```
DxAiFunctionInvocationResult Success(object? value = null, string status = "Completed")
```

Interface IDxAiFunctionRegistry

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDxAiFunctionRegistry
```

Methods 2

GetFunctions()

```
IReadOnlyList<DxaichatFunctionInfo> GetFunctions()
```

InvokeAsync(string, DxAiFunctionInvocationRequest, CancellationToken)

```
Task<DxAiFunctionInvocationResult> InvokeAsync(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Interface IDxAiFunctionServiceClient

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IDxAiFunctionServiceClient
```

Properties 1

CurrentOperationId

```
Guid? CurrentOperationId { get; }
```

Methods 5

CallAsync(string, DxAiFunctionInvocationRequest, CancellationToken)

```
Task<DxAiFunctionInvocationResult> CallAsync(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

CallAsync(string, object?, bool, bool, string, CancellationToken)

```
Task<DxAiFunctionInvocationResult> CallAsync(string functionName, object? parameters = null, bool userConfirmed = false, bool automaticInvocation = false, string requestedBy = "CurrentUser", CancellationToken cancellationToken = default)
```

Cancel()

```
void Cancel()
```

CancelWithReason(string)

```
void CancelWithReason(string reason)
```

GetFunctions()

```
IReadOnlyList<DxaichatFunctionInfo> GetFunctions()
```

Interface IEmbeddedFirmwarePlanningService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEmbeddedFirmwarePlanningService
```

Methods 2

CreateArtifactsAsync(EmbeddedFirmwarePlanRequest, bool, CancellationToken)

```
Task<EmbeddedFirmwareArtifactResult> CreateArtifactsAsync(EmbeddedFirmwarePlanRequest request, bool userConfirmed, CancellationToken cancellationToken = default)
```

CreatePlanAsync(EmbeddedFirmwarePlanRequest, CancellationToken)

```
Task<EmbeddedFirmwarePlan> CreatePlanAsync(EmbeddedFirmwarePlanRequest request, CancellationToken cancellationToken = default)
```

Interface IEmbeddedHardwareCatalogService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEmbeddedHardwareCatalogService
```

⚙️ Methods 5

GetBoardProfileAsync(string, CancellationToken)

```
Task<EmbeddedBoardProfile?> GetBoardProfileAsync(string boardProfileKey, CancellationToken cancellationToken = default)
```

GetBoardProfilesAsync(CancellationToken)

```
Task<IReadOnlyList<EmbeddedBoardProfile>> GetBoardProfilesAsync(CancellationToken cancellationToken = default)
```

GetCatalogAsync(CancellationToken)

```
Task<EmbeddedBoardCatalog> GetCatalogAsync(CancellationToken cancellationToken = default)
```

GetProtocolDescriptorsAsync(CancellationToken)

```
Task<IReadOnlyList<EmbeddedProtocolDescriptor>> GetProtocolDescriptorsAsync(CancellationToken cancellationToken = default)
```

GetPublisherWorkbenchContract()

```
EmbeddedPublisherWorkbenchContract GetPublisherWorkbenchContract()
```

Interface IEmbeddedTelemetryBridgeService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEmbeddedTelemetryBridgeService
```

⚙️ Methods 2

CreateOneWireEnvelopeAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
Task<EmbeddedTelemetryBridgeResult> CreateOneWireEnvelopeAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

PreviewAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
Task<EmbeddedTelemetryBridgeResult> PreviewAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

Interface IEmbeddedTelemetryIngressService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEmbeddedTelemetryIngressService
```

⚙️ Methods 2

GetRecent(string?, int)

```
IReadOnlyList<EmbeddedTelemetrySnapshot> GetRecent(string? deviceId = null, int maximum = 100)
```

PublishAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
Task<EmbeddedTelemetryIngressResult> PublishAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

Interface IEmbeddedWiringService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEmbeddedWiringService
```

⚙️ Methods 2

CreateDraftAsync(string, string, CancellationToken)

```
Task<EmbeddedWiringDraft> CreateDraftAsync(string boardProfileKey, string name, CancellationToken cancellationToken = default)
```

ValidateAsync(EmbeddedWiringValidationRequest, CancellationToken)

```
Task<EmbeddedWiringValidationResult> ValidateAsync(EmbeddedWiringValidationRequest request, CancellationToken cancellationToken = default)
```

Interface IEngineeringBenchmarkService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IEngineeringBenchmarkService
```

⚙️ Methods 1

RunAsync(EngineeringBenchmarkRequest, CancellationToken)

```
Task<EngineeringBenchmarkResult> RunAsync(EngineeringBenchmarkRequest request, CancellationToken cancellationToken = default)
```

Interface IFeaturePersistenceService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Provides approval-gated CRUD access to persistent records introduced by LocalGPT feature modules.

```
[DocumentationUpdated("2.1.23")] public interface IFeaturePersistenceService
```

⚙️ Methods 20

DeleteCouncilGameSessionAsync(Guid, bool, CancellationToken)

Deletes one GameDirector session record.

```
Task<bool> DeleteCouncilGameSessionAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteCouncilPromptStarterAsync(Guid, bool, CancellationToken)

Deletes one Council prompt starter.

```
Task<bool> DeleteCouncilPromptStarterAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteDocumentationBuildAsync(Guid, bool, CancellationToken)

Deletes one documentation build record.

```
Task<bool> DeleteDocumentationBuildAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteEmbeddedFirmwarePlanAsync(Guid, bool, CancellationToken)

Deletes one embedded firmware plan record.

```
Task<bool> DeleteEmbeddedFirmwarePlanAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteLocalizationCatalogAsync(Guid, bool, CancellationToken)

Deletes one localization catalog registration.

```
Task<bool> DeleteLocalizationCatalogAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

GetCouncilGameSessionAsync(Guid, CancellationToken)

Gets one GameDirector session record.

```
Task<CouncilGameSessionRecord?> GetCouncilGameSessionAsync(Guid id, CancellationToken cancellationToken = default)
```

GetCouncilGameSessionsAsync(CancellationToken)

Lists GameDirector session records.

```
Task<IReadOnlyList<CouncilGameSessionRecord>> GetCouncilGameSessionsAsync(CancellationToken cancellationToken = default)
```

GetCouncilPromptStarterAsync(Guid, CancellationToken)

Gets one Council prompt starter.

```
Task<CouncilPromptStarterConfiguration?> GetCouncilPromptStarterAsync(Guid id, CancellationToken cancellationToken = default)
```

GetCouncilPromptStartersAsync(bool, CancellationToken)

Lists Council prompt starters.

```
Task<IReadOnlyList<CouncilPromptStarterConfiguration>> GetCouncilPromptStartersAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

GetDocumentationBuildAsync(Guid, CancellationToken)

Gets one documentation build record.

```
Task<DocumentationBuildRecord?> GetDocumentationBuildAsync(Guid id, CancellationToken cancellationToken = default)
```

GetDocumentationBuildsAsync(CancellationToken)

Lists documentation build records in newest-first order.

```
Task<IReadOnlyList<DocumentationBuildRecord>> GetDocumentationBuildsAsync(CancellationToken cancellationToken = default)
```

GetEmbeddedFirmwarePlanAsync(Guid, CancellationToken)

Gets one embedded firmware plan record.

```
Task<EmbeddedFirmwarePlanRecord?> GetEmbeddedFirmwarePlanAsync(Guid id, CancellationToken cancellationToken = default)
```

GetEmbeddedFirmwarePlansAsync(CancellationToken)

Lists embedded firmware plan records.

```
Task<IReadOnlyList<EmbeddedFirmwarePlanRecord>> GetEmbeddedFirmwarePlansAsync(CancellationToken cancellationToken = default)
```

GetLocalizationCatalogAsync(Guid, CancellationToken)

Gets one localization catalog registration.

```
Task<LocalizationCatalogRegistration?> GetLocalizationCatalogAsync(Guid id, CancellationToken cancellationToken = default)
```

GetLocalizationCatalogsAsync(bool, CancellationToken)

Lists localization catalog registrations.

```
Task<IReadOnlyList<LocalizationCatalogRegistration>> GetLocalizationCatalogsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveCouncilGameSessionAsync(SaveFeatureRecordRequest<CouncilGameSessionRecord>, CancellationToken)

Creates or updates one GameDirector session record.

```
Task<CouncilGameSessionRecord> SaveCouncilGameSessionAsync(SaveFeatureRecordRequest<CouncilGameSessionRecord> request, CancellationToken cancellationToken = default)
```

SaveCouncilPromptStarterAsync(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration>, CancellationToken)

Creates or updates one Council prompt starter.

```
Task<CouncilPromptStarterConfiguration> SaveCouncilPromptStarterAsync(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration> request, CancellationToken cancellationToken = default)
```

SaveDocumentationBuildAsync(SaveFeatureRecordRequest<DocumentationBuildRecord>, CancellationToken)

Creates or updates one documentation build record.

```
Task<DocumentationBuildRecord> SaveDocumentationBuildAsync(SaveFeatureRecordRequest<DocumentationBuildRecord> request, CancellationToken cancellationToken = default)
```

SaveEmbeddedFirmwarePlanAsync(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord>, CancellationToken)

Creates or updates one embedded firmware plan record.

```
Task<EmbeddedFirmwarePlanRecord> SaveEmbeddedFirmwarePlanAsync(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord> request, CancellationToken cancellationToken = default)
```

SaveLocalizationCatalogAsync(SaveFeatureRecordRequest<LocalizationCatalogRegistration>, CancellationToken)

Creates or updates one localization catalog registration.

```
Task<LocalizationCatalogRegistration> SaveLocalizationCatalogAsync(SaveFeatureRecordRequest<LocalizationCatalogRegistration> request, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IFirstRunOnboardingService.html

Interface IFirstRunOnboardingService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Provides the persisted first-run guide, local model discovery summary, installer profiles and council quick starts.

```
[DocumentationUpdated("2.1.20")] public interface IFirstRunOnboardingService
```

Methods 2

CompleteAsync(bool, CancellationToken)

Persists that the current user completed or dismissed the first-run guide.

```
Task CompleteAsync(bool userConfirmed, CancellationToken cancellationToken = default)
```

GetStatusAsync(bool, CancellationToken)

Builds the current onboarding status and optionally probes supported loopback AI providers.

```
Task<FirstRunOnboardingStatus> GetStatusAsync(bool refreshConnectivity, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IHardwareInventoryService.html

Interface IHardwareInventoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IHardwareInventoryService
```

Methods 1

GetHardwareAsync(CancellationToken)

```
Task<IReadOnlyList<OneWireHardwareDescriptor>> GetHardwareAsync(CancellationToken cancellationToken = default)
```

Interface IHumanApprovalExecutionContext

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Capability-bearing boundary for execution of one exact persisted approval. It must never be injected into ordinary UI, model tools, or general services.

```
public interface IHumanApprovalExecutionContext
```

⚙️ Methods 1

PushHumanApproval(Guid, string, Guid, string, string, Guid?, int, string)

```
IDisposable PushHumanApproval(Guid humanProfileId, string displayName, Guid approvalRequestId, string source, string correlationId, Guid? councilRunId = null, int councilRound = 0, string phase = "")
```


Interface IHumanCollaborationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IHumanCollaborationService
```

⚙️ Methods 16

AuthorizeOrEnqueueAsync(HumanApprovalRequestSpec, bool, CancellationToken)

```
Task<HumanApprovalGateResult> AuthorizeOrEnqueueAsync(HumanApprovalRequestSpec request, bool directHumanConfirmation = false, CancellationToken cancellationToken = default)
```

BeginCouncilRun(Guid, IReadOnlyList<string>)

```
void BeginCouncilRun(Guid runId, IReadOnlyList<string> members)
```

BuildCouncilBriefingAsync(Guid, int, CancellationToken)

```
Task<string> BuildCouncilBriefingAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken = default)
```

DrainContributionsAsync(Guid, int, CancellationToken)

```
Task<IReadOnlyList<HumanCouncilContribution>> DrainContributionsAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken = default)
```

EndCouncilRun(Guid)

```
void EndCouncilRun(Guid runId)
```

GetGateStatusAsync(Guid, int, string, HumanCollaborationBoundary, CancellationToken)

```
Task<HumanCollaborationGateStatus> GetGateStatusAsync(Guid councilRunId, int upcomingRound, string upcomingPhase, HumanCollaborationBoundary boundary, CancellationToken cancellationToken = default)
```

GetProfileAsync(CancellationToken)

```
Task<HumanCouncilParticipantProfile> GetProfileAsync(CancellationToken cancellationToken = default)
```

GetSnapshotAsync(bool, int, CancellationToken)

```
Task<HumanCollaborationSnapshot> GetSnapshotAsync(bool includeResolved = true, int take = 80, CancellationToken cancellationToken = default)
```

HasRequiredPendingInputAsync(Guid, CancellationToken)

```
Task<bool> HasRequiredPendingInputAsync(Guid councilRunId, CancellationToken cancellationToken = default)
```

MarkContributionsEvaluatedAsync(Guid, int, string, CancellationToken)

```
Task MarkContributionsEvaluatedAsync(Guid councilRunId, int afterRound, string evaluation, CancellationToken cancellationToken = default)
```

QueueContributionAsync(Guid, string, CancellationToken)

```
Task<HumanCouncilContribution> QueueContributionAsync(Guid councilRunId, string content, CancellationToken cancellationToken = default)
```

QueueUserMessageAsync(Guid, string, CancellationToken)

```
Task<HumanCouncilContribution> QueueUserMessageAsync(Guid councilRunId, string content, CancellationToken cancellationToken = default)
```

ReadQueuedContributionsAsync(Guid, int, CancellationToken)

```
Task<IReadOnlyList<HumanCouncilContribution>> ReadQueuedContributionsAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken = default)
```

ResolveRequestAsync(Guid, HumanDecisionSubmission, CancellationToken)

```
Task<HumanCollaborationRequest?> ResolveRequestAsync(Guid requestId, HumanDecisionSubmission submission, CancellationToken cancellationToken = default)
```

SaveProfileAsync(HumanCouncilParticipantProfile, CancellationToken)

```
Task<HumanCouncilParticipantProfile> SaveProfileAsync(HumanCouncilParticipantProfile profile, CancellationToken cancellationToken = default)
```

UpdateCouncilRun(Guid, int, string, bool)

```
void UpdateCouncilRun(Guid runId, int currentRound, string phase, bool isWaitingForFinalHumanInput = false)
```

⚡ Events 2

Changed

```
event Action? Changed
```

DirectUserMessageQueued

```
event Action<HumanCouncilContribution>? DirectUserMessageQueued
```

api/LocalGPT.Interfaces.IInitialDataCatalog.html

Interface IInitialDataCatalog

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IInitialDataCatalog
```

🐾 Properties 3

Prompts

```
IReadOnlyList<PromptConfigDto> Prompts { get; }
```

RegexPatterns

```
IReadOnlyList<RegexPatternDto> RegexPatterns { get; }
```

Variables

```
IReadOnlyList<InitialVariable> Variables { get; }
```

⚙️ Methods 1

LoadKnowledgeAsync(CancellationToken)

```
Task<IReadOnlyList<CouncilKnowledgeEntry>> LoadKnowledgeAsync(CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IKnowledgeRatingService.html

Interface IKnowledgeRatingService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IKnowledgeRatingService
```

⚙️ Methods 2

GetRatingsAsync(Guid, CancellationToken)

```
Task<IReadOnlyList<CouncilKnowledgeUserRating>> GetRatingsAsync(Guid knowledgeEntryId, CancellationToken cancellationToken = default)
```

SaveRatingAsync(CouncilKnowledgeUserRating, bool, CancellationToken)

```
Task<CouncilKnowledgeUserRating> SaveRatingAsync(CouncilKnowledgeUserRating rating, bool userConfirmed, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.ILearnBaseKnowledgeImporterService.html

Interface ILearnBaseKnowledgeImporterService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILearnBaseKnowledgeImporterService
```

⚙️ Methods 1

ImportAsync(LearnBaseImportRequest, CancellationToken)

```
Task<LearnBaseImportResult> ImportAsync(LearnBaseImportRequest request, CancellationToken cancellationToken = default)
```

Interface ILearningRoundService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILearningRoundService
```

⚙️ Methods 2

BuildSnapshotAsync(int, CancellationToken)

```
Task<LearningRoundSnapshot> BuildSnapshotAsync(int takePerSource = 200, CancellationToken cancellationToken = default)
```

MaintainAsync(LearningMaintenanceRequest, CancellationToken)

```
Task<LearningMaintenanceResult> MaintainAsync(LearningMaintenanceRequest request, CancellationToken cancellationToken = default)
```

Interface ILocalGptProjectService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptProjectService
```

⚙️ Methods 7

AddTopicAsync(Guid, AddLocalGptProjectTopicRequest, CancellationToken)

```
Task<LocalGptProjectTopic> AddTopicAsync(Guid projectId, AddLocalGptProjectTopicRequest request, CancellationToken cancellationToken = default)
```

AddVersionAsync(Guid, AddLocalGptProjectVersionRequest, CancellationToken)

```
Task<LocalGptProjectVersion> AddVersionAsync(Guid projectId, AddLocalGptProjectVersionRequest request, CancellationToken cancellationToken = default)
```

BuildProjectBriefingAsync(Guid?, Guid?, CancellationToken)

```
Task<string> BuildProjectBriefingAsync(Guid? projectId, Guid? projectTopicId, CancellationToken cancellationToken = default)
```

GetProjectAsync(Guid, CancellationToken)

```
Task<LocalGptProjectDetails?> GetProjectAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetProjectsAsync(bool, CancellationToken)

```
Task<IReadOnlyList<LocalGptProjectSummary>> GetProjectsAsync(bool includeArchived = false, CancellationToken cancellationToken = default)
```

LinkKnowledgeAsync(Guid, LinkProjectTopicKnowledgeRequest, CancellationToken)

```
Task LinkKnowledgeAsync(Guid projectTopicId, LinkProjectTopicKnowledgeRequest request, CancellationToken cancellationToken = default)
```

SaveProjectAsync(SaveLocalGptProjectRequest, CancellationToken)

```
Task<LocalGptProject> SaveProjectAsync(SaveLocalGptProjectRequest request, CancellationToken cancellationToken = default)
```

Interface ILocalGptRequestFactoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptRequestFactoryService
```

⚙️ Methods 9

CreateArtifactRequest()

```
SaveProjectArtifactRequest CreateArtifactRequest()
```

CreateCompilerInstallationRequest()

```
SaveProjectCompilerInstallationRequest CreateCompilerInstallationRequest()
```

CreateProjectRequest()

```
SaveLocalGptProjectRequest CreateProjectRequest()
```

CreateRequirementLinkRequest()

```
SaveProjectRequirementLinkRequest CreateRequirementLinkRequest()
```

CreateRequirementRequest()

```
SaveProjectRequirementRequest CreateRequirementRequest()
```

CreateRevisionRequest()

```
SaveProjectRevisionRequest CreateRevisionRequest()
```

CreateTopicRequest()

```
AddLocalGptProjectTopicRequest CreateTopicRequest()
```

CreateVersionRequest(string)

```
AddLocalGptProjectVersionRequest CreateVersionRequest(string path = "")
```

CreateWorkspaceRootRequest()

```
SaveProjectWorkspaceRootRequest CreateWorkspaceRootRequest()
```

Interface ILocalGptRuntimePolicyDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptRuntimePolicyDataService
```

Properties 6

AllowedNativeExecutables

```
FrozenSet<string> AllowedNativeExecutables { get; }
```

LocalGptCoreProjectId

```
Guid LocalGptCoreProjectId { get; }
```

PowerShellFilePattern

```
Regex PowerShellFilePattern { get; }
```

PowerShellInlineCommandPattern

```
Regex PowerShellInlineCommandPattern { get; }
```

RegexTimeout

```
TimeSpan RegexTimeout { get; }
```

SensitiveArgumentPattern

```
Regex SensitiveArgumentPattern { get; }
```

Methods 9

GetCollection(LocalGptRuntimeCollection)

```
FrozenSet<string> GetCollection(LocalGptRuntimeCollection key)
```

GetGuid(LocalGptRuntimeValue)

```
Guid GetGuid(LocalGptRuntimeValue key)
```

GetInt(LocalGptRuntimeValue)

```
int GetInt(LocalGptRuntimeValue key)
```

GetJson<T>(LocalGptRuntimeValue)

```
T GetJson<T>(LocalGptRuntimeValue key)
```

GetLong(LocalGptRuntimeValue)

```
long GetLong(LocalGptRuntimeValue key)
```

GetPattern(LocalGptRuntimePattern)

```
Regex GetPattern(LocalGptRuntimePattern key)
```

GetSnapshot()

```
LocalGptRuntimePolicySnapshot GetSnapshot()
```

GetString(LocalGptRuntimeValue)

```
string GetString(LocalGptRuntimeValue key)
```

Reload()

```
LocalGptRuntimePolicySnapshot Reload()
```

Interface ILocalGptRuntimePolicySeedDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptRuntimePolicySeedDataService
```

⚙️ Methods 1

GetSeed()

```
LocalGptRuntimePolicySeedModel GetSeed()
```

Interface ILocalGptRuntimePolicyStoreService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptRuntimePolicyStoreService
```

⚙️ Methods 1

GetDefinition()

```
LocalGptRuntimePolicyDefinition? GetDefinition()
```

Interface ILocalGptVocabularyService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalGptVocabularyService
```

⚙️ Methods 1

Get()

```
LocalGptVocabularySnapshot Get()
```

Interface ILocalHumanInteractionContext

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Capability-bearing boundary for trusted local-human UI interaction only. It can create peer participation context, never operation approval.

```
public interface ILocalHumanInteractionContext
```

⚙️ Methods 1

PushHumanInteraction(Guid, string, string, string?, Guid?, int, string)

```
IDisposable PushHumanInteraction(Guid humanProfileId, string displayName, string source, string? correlationId = null, Guid? councilRunId = null, int councilRound = 0, string phase = "")
```

Interface ILocalVisionOcrService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ILocalVisionOcrService
```

⚙️ Methods 1

RecognizeAsync(LocalVisionOcrRequest, CancellationToken)

```
Task<LocalVisionOcrResult> RecognizeAsync(LocalVisionOcrRequest request, CancellationToken cancellationToken = default)
```

Interface IMinecraftModWorkspaceService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IMinecraftModWorkspaceService
```

Properties 1

WorkspaceRoot

```
string WorkspaceRoot { get; }
```

Methods 3

CreateFabricWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
Task<MinecraftModWorkspace> CreateFabricWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

CreateWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
Task<MinecraftModWorkspace> CreateWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

IsPathInsideWorkspaceRoot(string)

```
bool IsPathInsideWorkspaceRoot(string path)
```

Interface IModelCapabilitySelfAssessmentService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IModelCapabilitySelfAssessmentService
```

Methods 1

CaptureAndStripAsync(string, string, CancellationTokens)

```
Task<string> CaptureAndStripAsync(string modelName, string visibleContent, CancellationTokens cancellationTokens = default)
```

Interface IModelPresetService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IModelPresetService
```

Methods 3

ArchivePresetAsync(Guid, bool, CancellationTokens)

```
Task ArchivePresetAsync(Guid presetId, bool userConfirmed, CancellationTokens cancellationTokens = default)
```

GetPresetsAsync(bool, CancellationTokens)

```
Task<IReadOnlyList<CouncilModelPreset>> GetPresetsAsync(bool includeArchived = false, CancellationTokens cancellationTokens = default)
```

SavePresetAsync(CouncilModelPreset, bool, CancellationTokens)

```
Task<CouncilModelPreset> SavePresetAsync(CouncilModelPreset preset, bool userConfirmed, CancellationTokens cancellationTokens = default)
```

Interface IMultiModelCouncilService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IMultiModelCouncilService
```

⚙️ Methods 2

GetCandidatesAsync(CancellationToken)

```
Task<IReadOnlyList<MultiModelCouncilModelCandidate>> GetCandidatesAsync(CancellationToken cancellationToken = default)
```

RunAsync(MultiModelCouncilRequest, CancellationToken)

```
Task<MultiModelCouncilResult> RunAsync(MultiModelCouncilRequest request, CancellationToken cancellationToken = default)
```

Interface INativeCommandRunner

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface INativeCommandRunner
```

⚙️ Methods 1

RunAsync(string, string, string, CancellationToken, bool)

```
Task<CommandExecutionResult?> RunAsync(string fileName, string arguments, string workingDirectory, CancellationToken cancellationToken = default, bool userConfirmed = false)
```


Class InitialVariable

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Inheritance object InitialVariable

Implements IEquatable < InitialVariable >

```
public sealed record InitialVariable : IEquatable<InitialVariable>
```

🌟 Constructors 1

InitialVariable(string, string, string)

```
public InitialVariable(string Name, string Value, string DataType)
```

🐾 Properties 3

DataType

```
public string DataType { get; init; }
```

Name

```
public string Name { get; init; }
```

Value

```
public string Value { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string)

```
public void Deconstruct(out string Name, out string Value, out string DataType)
```

Equals(InitialVariable?)

```
public bool Equals(InitialVariable? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(InitialVariable?, InitialVariable?)

```
public static bool operator ==(InitialVariable? left, InitialVariable? right)
```

operator !=(InitialVariable?, InitialVariable?)

```
public static bool operator !=(InitialVariable? left, InitialVariable? right)
```

Interface INotificationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface INotificationService
```

⚙️ Methods 6

Show(string, string, string, ToastRenderStyle)

```
void Show(string providerName, string title, string message, ToastRenderStyle renderStyle)
```

ShowError(string, string, string)

```
void ShowError(string providerName, string message, string title = "Error")
```

ShowInfo(string, string, string)

```
void ShowInfo(string providerName, string message, string title = "Info")
```

ShowRegular(string, string, string)

```
void ShowRegular(string providerName, string message, string title = "Error")
```

ShowSuccess(string, string, string)

```
void ShowSuccess(string providerName, string message, string title = "Success")
```

ShowWarning(string, string, string)

```
void ShowWarning(string providerName, string message, string title = "Warning")
```

Interface IOllamaProcessService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOllamaProcessService
```

⚙️ Methods 4

GetStatusAsync(CancellationTokens)

```
Task<OllamaProcessStatus> GetStatusAsync(CancellationTokens cancellationTokens = default)
```

RestartAsync(CancellationTokens)

```
Task<OllamaProcessStatus> RestartAsync(CancellationTokens cancellationTokens = default)
```

StartAsync(CancellationTokens)

```
Task<OllamaProcessStatus> StartAsync(CancellationTokens cancellationTokens = default)
```

StopAsync(CancellationTokens)

```
Task<OllamaProcessStatus> StopAsync(CancellationTokens cancellationTokens = default)
```

Interface IOneWireCapabilityCatalog

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireCapabilityCatalog : IOneWireCapabilityProvider
```

⚙️ Methods 5

GetLocalCapabilitiesAsync(CancellationTokens)

```
Task<IReadOnlyList<OneWireCapabilityDescriptor>> GetLocalCapabilitiesAsync(CancellationTokens cancellationTokens = default)
```

GetLocalCapabilitiesForPeerAsync(string, CancellationTokens)

```
Task<IReadOnlyList<OneWireCapabilityDescriptor>> GetLocalCapabilitiesForPeerAsync(string peerId, CancellationTokens cancellationTokens = default)
```

GetLocalHardwareAsync(CancellationTokens)

```
Task<IReadOnlyList<OneWireHardwareDescriptor>> GetLocalHardwareAsync(CancellationTokens cancellationTokens = default)
```

GetLocalSkillsAsync(CancellationTokens)

```
Task<IReadOnlyList<OneWireSkillDescriptor>> GetLocalSkillsAsync(CancellationTokens cancellationTokens = default)
```

GetLocalUiFeaturesAsync(CancellationTokens)

```
Task<IReadOnlyList<OneWireUiFeatureDescriptor>> GetLocalUiFeaturesAsync(CancellationTokens cancellationTokens = default)
```

Interface IOneWireConnectionRegistry

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireConnectionRegistry
```

⚙️ Methods 6

IsConnected(string)

```
bool IsConnected(string peerId)
```

Register(string, Func<OneWireEnvelope, CancellationTokens, Task>)

```
void Register(string peerId, Func<OneWireEnvelope, CancellationTokens, Task> sender)
```

RegisterOwned(string, Func<OneWireEnvelope, CancellationTokens, Task>)

```
Guid RegisterOwned(string peerId, Func<OneWireEnvelope, CancellationTokens, Task> sender)
```

SendAsync(string, OneWireEnvelope, CancellationTokens)

```
Task<bool> SendAsync(string peerId, OneWireEnvelope envelope, CancellationTokens cancellationTokens = default)
```

Unregister(string)

```
void Unregister(string peerId)
```

Unregister(string, Guid)

```
bool Unregister(string peerId, Guid registrationId)
```

Interface IOneWireDispatchContextFactory

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireDispatchContextFactory
```

⚙️ Methods 2

CreateExternal(string, Guid, bool, string)

```
OneWireDispatchContext CreateExternal(string authenticatedPeerId, Guid connectionId, bool isLoopback, string transport)
```

CreateInternal(string)

```
OneWireDispatchContext CreateInternal(string transport = "internal")
```

Interface IOneWireEnvelopeCodec

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireEnvelopeCodec
```

🐾 Properties 1

JsonOptions

```
JsonSerializerOptions JsonOptions { get; }
```

⚙️ Methods 3

DeserializeAndValidate(string)

```
OneWireEnvelope DeserializeAndValidate(string json)
```

Serialize(OneWireEnvelope, bool)

```
string Serialize(OneWireEnvelope envelope, bool seal = true)
```

Validate(OneWireEnvelope, out string)

```
bool Validate(OneWireEnvelope envelope, out string error)
```

Interface IOneWireListenAddressResolver

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireListenAddressResolver
```

⚙️ Methods 1

Resolve(OneWireOptions)

```
IPAddress Resolve(OneWireOptions configured)
```

Interface IOneWireMessageDispatcher

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireMessageDispatcher
```

⚙️ Methods 4

ApplyHumanResponse(OneWireEnvelope, string?)

```
void ApplyHumanResponse(OneWireEnvelope envelope, string? userResponse)
```

DispatchAsync(OneWireEnvelope, OneWireDispatchContext, CancellationToken)

```
Task<OneWireEnvelope?> DispatchAsync(OneWireEnvelope envelope, OneWireDispatchContext context, CancellationToken cancellationToken = default)
```

DispatchAsync(OneWireEnvelope, CancellationToken)

```
Task<OneWireEnvelope?> DispatchAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

GetLocalAdvertisement()

```
OneWirePeerAdvertisement GetLocalAdvertisement()
```

Interface IOneWireOperationExecutor

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireOperationExecutor
```

⚙️ Methods 1

ExecuteAsync(OneWireWorkItem, CancellationToken)

```
Task<string> ExecuteAsync(OneWireWorkItem item, CancellationToken cancellationToken = default)
```

Interface IOneWirePeerRegistry

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWirePeerRegistry
```

⚙️ Methods 5

GetPeer(string)

```
OneWirePeerAdvertisement? GetPeer(string peerId)
```

GetPeers()

```
IReadOnlyList<OneWirePeerAdvertisement> GetPeers()
```

RemoveExpired(TimeSpan)

```
void RemoveExpired(TimeSpan maximumAge)
```

SetConnected(string, bool)

```
void SetConnected(string peerId, bool connected)
```

Upsert(OneWirePeerAdvertisement)

```
void Upsert(OneWirePeerAdvertisement peer)
```

Interface IOneWirePendingCouncilStore

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWirePendingCouncilStore
```

⚙️ Methods 4

GetSnapshot()

```
IReadOnlyList<OneWirePendingCouncilRequest> GetSnapshot()
```

MarkChecked(Guid)

```
void MarkChecked(Guid correlationId)
```

Remove(Guid, out OneWirePendingCouncilRequest?)

```
bool Remove(Guid correlationId, out OneWirePendingCouncilRequest? request)
```

Upsert(OneWireEnvelope, Guid?)

```
void Upsert(OneWireEnvelope envelope, Guid? approvalRequestId)
```

Interface IOneWireReplayGuard

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireReplayGuard
```

⚙️ Methods 1

TryAccept(string, Guid, DateTimeOffset)

```
bool TryAccept(string peerId, Guid messageId, DateTimeOffset createdUtc)
```

Interface IOneWireReplayPolicyDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireReplayPolicyDataService
```

⚙️ Methods 1

GetSnapshot()

```
OneWireReplayPolicySnapshot GetSnapshot()
```

Interface IOneWireRuntimeSecurityService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireRuntimeSecurityService
```

⚙️ Methods 12

CreatePairingTicketAsync(TimeSpan, CancellationToken)

```
Task<OneWirePairingTicket> CreatePairingTicketAsync(TimeSpan lifetime, CancellationToken cancellationToken = default)
```

DeleteAsync(CancellationToken)

```
Task DeleteAsync(CancellationToken cancellationToken = default)
```

EnsureCreatedAsync(CancellationToken)

```
Task EnsureCreatedAsync(CancellationToken cancellationToken = default)
```

EstablishTrustAsync(OneWireTrustEstablishmentRequest, CancellationToken)

```
Task<bool> EstablishTrustAsync(OneWireTrustEstablishmentRequest request, CancellationToken cancellationToken = default)
```

GetOtpAuthUriAsync(CancellationToken)

```
Task<string> GetOtpAuthUriAsync(CancellationToken cancellationToken = default)
```

GetPublicDescriptorAsync(CancellationToken)

```
Task<OneWireSecurityDescriptor> GetPublicDescriptorAsync(CancellationToken cancellationToken = default)
```

GetStatusAsync(CancellationToken)

```
Task<OneWireRuntimeSecurityStatus> GetStatusAsync(CancellationToken cancellationToken = default)
```

GetTrustedPeersAsync(CancellationToken)

```
Task<IReadOnlyList<OneWireTrustedPeerDescriptor>> GetTrustedPeersAsync(CancellationToken cancellationToken = default)
```

ProtectOutgoingAsync(OneWireEnvelope, CancellationToken)

```
Task ProtectOutgoingAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

RegenerateAsync(CancellationToken)

```
Task RegenerateAsync(CancellationToken cancellationToken = default)
```

RevokeTrustAsync(string, CancellationToken)

```
Task<bool> RevokeTrustAsync(string peerId, CancellationToken cancellationToken = default)
```

UnprotectIncomingAsync(OneWireEnvelope, CancellationToken)

```
Task UnprotectIncomingAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

Interface IOneWireTargetApprovalPolicy

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireTargetApprovalPolicy
```

⚙️ Methods 2

Create(OneWireEnvelope)

```
HumanApprovalRequestSpec Create(OneWireEnvelope envelope)
```

ReadEditor(OneWireEnvelope)

```
OneWireInteractionEditor ReadEditor(OneWireEnvelope envelope)
```

Interface IOneWireTransportSecurityPolicy

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireTransportSecurityPolicy
```

⚙️ Methods 3

IsLoopback(IPAddress?)

```
bool IsLoopback(IPAddress? address)
```

IsProtected(OneWireEnvelope)

```
bool IsProtected(OneWireEnvelope envelope)
```

RequiresProtectedTransport(OneWireMessageType)

```
bool RequiresProtectedTransport(OneWireMessageType messageType)
```

Interface IOneWireWorkSpooler

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOneWireWorkSpooler
```

⚙️ Methods 9

ApplyExternalResult(Guid, string, string, OneWireWorkStatus?)

```
void ApplyExternalResult(Guid correlationId, string resultJson, string error, OneWireWorkStatus? status = null)
```

Complete(Guid, string)

```
void Complete(Guid id, string resultJson)
```

DequeueAsync(CancellationTokens)

```
Task<OneWireWorkItem> DequeueAsync(CancellationTokens cancellationTokens)
```

Enqueue(OneWireEnvelope)

```
OneWireWorkItem Enqueue(OneWireEnvelope envelope)
```

Fail(Guid, string)

```
void Fail(Guid id, string error)
```

Get(Guid)

```
OneWireWorkItem? Get(Guid id)
```

GetSnapshot()

```
IReadOnlyList<OneWireWorkItem> GetSnapshot()
```

MarkPendingApproval(Guid, string)

```
void MarkPendingApproval(Guid correlationId, string resultJson)
```

MarkRunning(Guid)

```
void MarkRunning(Guid id)
```


Interface IOrganicAddonManifestService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOrganicAddonManifestService
```

⚙️ Methods 3

GetCatalogEntries()

```
IReadOnlyList<DxAiFunctionCatalogEntry> GetCatalogEntries()
```

GetManifests()

```
IReadOnlyList<OrganicAddonManifest> GetManifests()
```

GetSkillDescriptors()

```
IReadOnlyList<OneWireSkillDescriptor> GetSkillDescriptors()
```

Interface IOrganicCouncilBlueprintSeedDataService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOrganicCouncilBlueprintSeedDataService
```

⚙️ Methods 1

CreateDefaultTeams()

```
IReadOnlyList<OrganicCouncilTeamDefinition> CreateDefaultTeams()
```

Interface IOrganicCouncilBlueprintService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOrganicCouncilBlueprintService
```

⚙️ Methods 5

BuildBriefingAsync(MultiModelCouncilRequest, CancellationToken)

```
Task<string> BuildBriefingAsync(MultiModelCouncilRequest request, CancellationToken cancellationToken = default)
```

BuildExpertPreparationPrompt(MultiModelCouncilRequest, OrganicCouncilTeamDefinition)

```
string BuildExpertPreparationPrompt(MultiModelCouncilRequest request, OrganicCouncilTeamDefinition team)
```

BuildLeaderSynthesisPrompt(MultiModelCouncilRequest, OrganicCouncilTeamDefinition, string)

```
string BuildLeaderSynthesisPrompt(MultiModelCouncilRequest request, OrganicCouncilTeamDefinition team, string preparation)
```

FindTeamAsync(string?, CancellationToken)

```
Task<OrganicCouncilTeamDefinition?> FindTeamAsync(string? key, CancellationToken cancellationToken = default)
```

GetTeamsAsync(CancellationToken)

```
Task<IReadOnlyList<OrganicCouncilTeamDefinition>> GetTeamsAsync(CancellationToken cancellationToken = default)
```

Interface IOrganicDxFunctionSupport

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOrganicDxFunctionSupport
```

⚙️ Methods 5

CreateInvokeEnvelope(string, OneWireCapabilityDescriptor, JsonElement, OneWireExecutionMode, string, DateTimeOffset?, bool, string)

```
OneWireEnvelope CreateInvokeEnvelope(string peerId, OneWireCapabilityDescriptor capability, JsonElement payload, OneWireExecutionMode executionMode, string workOrderKey, DateTimeOffset? notBeforeUtc, bool userConfirmed, string interactionValueJson)
```

FindCapability(OneWirePeerAdvertisement, string)

```
OneWireCapabilityDescriptor? FindCapability(OneWirePeerAdvertisement peer, string key)
```

GetString(JsonElement, string, string)

```
string GetString(JsonElement element, string name, string fallback = "")
```

Invalid(string)

```
DxAiFunctionInvocationResult Invalid(string error)
```

Queued(OneWireWorkItem, string, string)

```
DxAiFunctionInvocationResult Queued(OneWireWorkItem work, string peerId, string capabilityKey)
```

Interface IOrganicSkillRegistryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IOrganicSkillRegistryService
```

⚙️ Methods 6

GetSkillsAsync(bool, CancellationToken)

```
Task<IReadOnlyList<OrganicSkillDefinition>> GetSkillsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

GetWireSkillsAsync(CancellationToken)

```
Task<IReadOnlyList<OneWireSkillDescriptor>> GetWireSkillsAsync(CancellationToken cancellationToken = default)
```

LinkProjectAsync(LinkProjectOrganicSkillRequest, CancellationToken)

```
Task<ProjectOrganicSkillLink> LinkProjectAsync(LinkProjectOrganicSkillRequest request, CancellationToken cancellationToken = default)
```

RecordUntrustedSelfAssessmentAsync(OneWireModelSelfAssessment, CancellationToken)

```
Task RecordUntrustedSelfAssessmentAsync(OneWireModelSelfAssessment assessment, CancellationToken cancellationToken = default)
```

ReportMemberSkillAsync(ReportCouncilMemberSkillRequest, CancellationToken)

```
Task<CouncilMemberOrganicSkillLink> ReportMemberSkillAsync(ReportCouncilMemberSkillRequest request, CancellationToken cancellationToken = default)
```

SaveSkillAsync(SaveOrganicSkillRequest, CancellationToken)

```
Task<OrganicSkillDefinition> SaveSkillAsync(SaveOrganicSkillRequest request, CancellationToken cancellationToken = default)
```

Interface IProjectArchitectureService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProjectArchitectureService
```

⚙️ Methods 9

BuildArchitectureBriefingAsync(Guid, Guid?, CancellationToken)

```
Task<string> BuildArchitectureBriefingAsync(Guid projectId, Guid? revisionId, CancellationToken cancellationToken = default)
```

EnsureCouncilRunProjectAsync(Guid, string?, string, CancellationToken)

```
Task<(LocalGptProject Project, LocalGptProjectRevision Revision)> EnsureCouncilRunProjectAsync(Guid councilRunId, string? title, string prompt, CancellationToken cancellationToken = default)
```

GetArtifactsAsync(Guid, CancellationToken)

```
Task<IReadOnlyList<LocalGptProjectArtifact>> GetArtifactsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetRequirementsAsync(Guid, CancellationToken)

```
Task<IReadOnlyList<LocalGptProjectRequirement>> GetRequirementsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetRevisionsAsync(Guid, CancellationToken)

```
Task<IReadOnlyList<LocalGptProjectRevision>> GetRevisionsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

SaveArtifactAsync(Guid, SaveProjectArtifactRequest, CancellationToken)

```
Task<LocalGptProjectArtifact> SaveArtifactAsync(Guid projectId, SaveProjectArtifactRequest request, CancellationToken cancellationToken = default)
```

SaveRequirementAsync(Guid, SaveProjectRequirementRequest, CancellationToken)

```
Task<LocalGptProjectRequirement> SaveRequirementAsync(Guid projectId, SaveProjectRequirementRequest request, CancellationToken cancellationToken = default)
```

SaveRequirementLinkAsync(Guid, SaveProjectRequirementLinkRequest, CancellationToken)

```
Task<LocalGptProjectRequirementLink> SaveRequirementLinkAsync(Guid projectId, SaveProjectRequirementLinkRequest request, CancellationToken cancellationToken = default)
```

SaveRevisionAsync(Guid, SaveProjectRevisionRequest, CancellationToken)

```
Task<LocalGptProjectRevision> SaveRevisionAsync(Guid projectId, SaveProjectRevisionRequest request, CancellationToken cancellationToken = default)
```

Interface IProjectLibraryInventoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProjectLibraryInventoryService
```

⚙️ Methods 1

BuildDevExpressBriefingAsync(CancellationToken)

```
Task<string> BuildDevExpressBriefingAsync(CancellationToken cancellationToken = default)
```

Interface IProjectMaintenanceService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProjectMaintenanceService
```

⚙️ Methods 16

ApproveRevisionReadyForTestAsync(Guid, Guid, ApproveRevisionReadyForTestRequest, CancellationToken)

```
Task<ProjectBuildVerification> ApproveRevisionReadyForTestAsync(Guid projectId, Guid revisionId, ApproveRevisionReadyForTestRequest request,
CancellationToken cancellationToken = default)
```

AssessWorkspacePermissionsAsync(Guid, bool, CancellationToken)

```
Task<WorkspacePermissionAssessment> AssessWorkspacePermissionsAsync(Guid workspaceRootId, bool userConfirmedWriteProbe, CancellationToken
cancellationToken = default)
```

DeleteCompilerInstallationAsync(Guid, bool, CancellationToken)

Deletes one unreferenced compiler profile after explicit human confirmation.

```
Task<bool> DeleteCompilerInstallationAsync(Guid compilerId, bool userConfirmed, CancellationToken cancellationToken = default)
```

DiscoverCompilerInstallationsAsync(DiscoverProjectCompilersRequest, CancellationToken)

Discovers compiler executables from PATH, common locations and approved custom roots.

```
Task<IReadOnlyList<ProjectCompilerInstallation>> DiscoverCompilerInstallationsAsync(DiscoverProjectCompilersRequest request, CancellationToken
cancellationToken = default)
```

GetCompilerInstallationsAsync(CancellationToken)

Lists stored compiler and runtime toolchain profiles.

```
Task<IReadOnlyList<ProjectCompilerInstallation>> GetCompilerInstallationsAsync(CancellationToken cancellationToken = default)
```

GetTrackedFilesAsync(Guid, Guid?, CancellationToken)

```
Task<IReadOnlyList<LocalGptProjectTrackedFile>> GetTrackedFilesAsync(Guid projectId, Guid? revisionId = null, CancellationToken cancellationToken =
default)
```

GetWorkspaceRootsAsync(Guid?, CancellationToken)

```
Task<IReadOnlyList<ProjectWorkspaceRoot>> GetWorkspaceRootsAsync(Guid? projectId = null, CancellationToken cancellationToken = default)
```

RecordCouncilBuildReviewAsync(Guid, RecordCouncilBuildReviewRequest, CancellationToken)

```
Task<ProjectBuildVerification> RecordCouncilBuildReviewAsync(Guid verificationId, RecordCouncilBuildReviewRequest request, CancellationToken
cancellationToken = default)
```

RegisterRevisionWorkspaceAsync(Guid, Guid, string, string, bool, CancellationToken)

```
Task<LocalGptProjectRevision> RegisterRevisionWorkspaceAsync(Guid projectId, Guid revisionId, string sourceRootPath, string solutionPath, bool
userConfirmed, CancellationToken cancellationToken = default)
```

ResolveWorkspaceAsync(Guid, CancellationToken)

```
Task<ProjectWorkspaceResolution> ResolveWorkspaceAsync(Guid projectId, CancellationToken cancellationToken = default)
```

RunBuildVerificationAsync(Guid, RunProjectBuildVerificationRequest, CancellationToken)

```
Task<ProjectBuildVerification> RunBuildVerificationAsync(Guid projectId, RunProjectBuildVerificationRequest request, CancellationToken cancellationToken =
default)
```

SaveCompilerInstallationAsync(SaveProjectCompilerInstallationRequest, CancellationToken)

Creates or updates one approval-gated compiler profile.

```
Task<ProjectCompilerInstallation> SaveCompilerInstallationAsync(SaveProjectCompilerInstallationRequest request, CancellationToken cancellationToken =
default)
```

SaveTrackedFilePatternAsync(Guid, SaveTrackedFilePatternRequest, CancellationToken)

```
Task<LocalGptProjectTrackedFile> SaveTrackedFilePatternAsync(Guid trackedFileId, SaveTrackedFilePatternRequest request, CancellationToken
cancellationToken = default)
```

SaveWorkspaceRootAsync(SaveProjectWorkspaceRootRequest, CancellationToken)

```
Task<ProjectWorkspaceRoot> SaveWorkspaceRootAsync(SaveProjectWorkspaceRootRequest request, CancellationToken cancellationToken = default)
```

ScanProjectFilesAsync(Guid, ScanProjectFilesRequest, CancellationToken)

```
Task<ProjectScanResult> ScanProjectFilesAsync(Guid projectId, ScanProjectFilesRequest request, CancellationToken cancellationToken = default)
```

ValidateCompilerInstallationAsync(Guid, bool, CancellationToken)

Runs one bounded version probe for a stored compiler profile.

```
Task<ProjectCompilerInstallation> ValidateCompilerInstallationAsync(Guid compilerId, bool userConfirmed, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IProjectOrganicContextService.html

Interface IProjectOrganicContextService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProjectOrganicContextService
```

⚙️ Methods 3

BuildBriefingAsync(Guid, Guid?, CancellationToken)

```
Task<string> BuildBriefingAsync(Guid projectId, Guid? revisionId, CancellationToken cancellationToken = default)
```

GetAsync(Guid, Guid?, CancellationToken)

```
Task<ProjectOrganicContext> GetAsync(Guid projectId, Guid? revisionId, CancellationToken cancellationToken = default)
```

SaveAsync(Guid, SaveProjectOrganicContextRequest, CancellationToken)

```
Task<ProjectOrganicContext> SaveAsync(Guid projectId, SaveProjectOrganicContextRequest request, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IPromptConfigService.html

Interface IPromptConfigService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IPromptConfigService
```

⚙️ Methods 4

GetPromptAsync(PromptConfigDto, CancellationToken)

```
Task<string> GetPromptAsync(PromptConfigDto dto, CancellationToken cancellationToken = default)
```

GetPromptAsync(string, string, CancellationToken)

```
Task<string> GetPromptAsync(string key, string language = "en", CancellationToken cancellationToken = default)
```

ListPromptsAsync(string?, CancellationToken)

```
Task<IEnumerable<PromptConfig>> ListPromptsAsync(string? language = null, CancellationToken cancellationToken = default)
```

UpdatePromptAsync(PromptConfigDto, CancellationToken)

```
Task UpdatePromptAsync(PromptConfigDto dto, CancellationToken cancellationToken = default)
```

api/LocalGPT.Interfaces.IProviderModelBenchmarkService.html

Interface IProviderModelBenchmarkService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProviderModelBenchmarkService
```

⚙️ Methods 2

ApplyRecommendationsAsync(ProviderModelBenchmarkReport, string, bool, bool, CancellationToken)

```
Task<IReadOnlyList<CouncilModelPreset>> ApplyRecommendationsAsync(ProviderModelBenchmarkReport report, string presetName, bool makeDefault, bool userConfirmed, CancellationToken cancellationToken = default)
```

RunAsync(ProviderModelBenchmarkRequest, CancellationToken)

```
Task<ProviderModelBenchmarkReport> RunAsync(ProviderModelBenchmarkRequest request, CancellationToken cancellationToken = default)
```

Interface IProviderModelRuntimeService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IProviderModelRuntimeService
```

⚙️ Methods 6

CreateChatClient(ProviderModelReference, string, int, TimeSpan, int?)

```
IChatClient CreateChatClient(ProviderModelReference model, string keepAlive, int maxContextTokens, TimeSpan timeout, int? ollamaNumGpu)
```

CreateSessionAsync(ProviderModelReference, CancellationToken)

```
Task<ChatClientSession> CreateSessionAsync(ProviderModelReference model, CancellationToken cancellationToken = default)
```

FromSession(ChatClientSession)

```
ProviderModelReference FromSession(ChatClientSession session)
```

GetCandidatesAsync(CancellationTokens)

```
Task<IReadOnlyList<MultiModelCouncilModelCandidate>> GetCandidatesAsync(CancellationTokens cancellationTokens = default)
```

Remember(ProviderModelReference)

```
void Remember(ProviderModelReference model)
```

ResolveAsync(string, CancellationToken)

```
Task<ProviderModelReference> ResolveAsync(string selectionOrModelName, CancellationToken cancellationToken = default)
```

Interface IPublicServiceMethodInvoker

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IPublicServiceMethodInvoker
```

⚙️ Methods 1

InvokeAsync(PublicServiceMethodInvocationRequest, CancellationToken)

```
Task<object?> InvokeAsync(PublicServiceMethodInvocationRequest request, CancellationToken cancellationToken = default)
```

Interface IPublisherInteractionDxSupport

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IPublisherInteractionDxSupport
```

⚙️ Methods 1

QueueAsync<TLogger>(DxAiFunctionInvocationRequest, string, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<TLogger>, Func<JsonElement, JsonElement>, CancellationToken)

```
Task<DxAiFunctionInvocationResult> QueueAsync<TLogger>(DxAiFunctionInvocationRequest request, string capabilityKey, IOneWireConnectionRegistry connections, IOneWirePeerRegistry peers, IOneWireWorkSpooler spooler, ILogger<TLogger> logger, Func<JsonElement, JsonElement> createPayload, CancellationToken cancellationToken)
```

Interface IRegexFunctionParameterService

Namespace LocalGPT.Interfaces Assembly LocalGPT.dll

Reads required values for database-backed regular-expression DX functions.

```
public interface IRegexFunctionParameterService
```

Methods

GetRequiredString(JsonElement element, string propertyName)

```
string GetRequiredString(JsonElement element, string propertyName)
```

Interface IRegexPatternService

Namespace LocalGPT.Interfaces Assembly LocalGPT.dll

Database-backed regular-expression service contract used by LocalGPT controllers, services and peer-advertised DX functions.

```
public interface IRegexPatternService
```

Methods

AddOrUpdateAsync(RegexPatternDto dto)

```
Task AddOrUpdateAsync(RegexPatternDto dto)
```

GetRegexAsync(string name)

```
Task<Regex?> GetRegexAsync(string name)
```

Compile(string pattern, string? flags = null)

```
Regex Compile(string pattern, string? flags = null)
```

Compile(string pattern, string? flags, TimeSpan timeout)

```
Regex Compile(string pattern, string? flags, TimeSpan timeout)
```

ListAllAsync()

```
Task<List<RegexPattern>> ListAllAsync()
```

ListAllAsync(int? take)

```
Task<List<RegexPattern>> ListAllAsync(int? take)
```

DeleteAsync(string name)

```
Task DeleteAsync(string name)
```

Interface IRemoteKnowledgeImportService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IRemoteKnowledgeImportService
```

⚙️ Methods 2

ImportAsync(RemoteKnowledgeImportRequest, CancellationToken)

```
Task<RemoteKnowledgeImportResult> ImportAsync(RemoteKnowledgeImportRequest request, CancellationToken cancellationToken = default)
```

ParseLabels(params string?[])

```
List<string> ParseLabels(params string?[] values)
```

Interface IRuntimeCapabilityDirectoryService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IRuntimeCapabilityDirectoryService
```

⚙️ Methods 1

SynchronizeAsync(CancellationTokens)

```
Task<RuntimeCapabilityDirectorySnapshot> SynchronizeAsync(CancellationTokens cancellationTokens = default)
```

Interface ISafeTextDocumentService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ISafeTextDocumentService
```

⚙️ Methods 2

ImportAsync(Guid, Guid?, string, bool, CancellationTokens)

```
Task<ProjectDocumentImport> ImportAsync(Guid projectId, Guid? revisionId, string filePath, bool userConfirmed, CancellationTokens cancellationTokens = default)
```

ReadAsync(string, int, CancellationTokens)

```
Task<SafeTextDocument> ReadAsync(string filePath, int maxCharacters = 500000, CancellationTokens cancellationTokens = default)
```

Interface IServiceActivityService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Records bounded, sanitized service-operation state for LocalGPT short-term context. The executor never swallows failures: cancellation and exceptions are recorded and rethrown.

```
public interface IServiceActivityService
```

⚙️ Methods 5

RecordFailure(string, string, Exception, string?)

```
void RecordFailure(string serviceName, string operation, Exception exception, string? route = null)
```

RecordInformation(string, string, string, string?)

```
void RecordInformation(string serviceName, string operation, string summary, string? route = null)
```

RecordWarning(string, string, string, string?)

```
void RecordWarning(string serviceName, string operation, string summary, string? route = null)
```

RunAsync(string, string, Func<CancellationTokens, Task>, CancellationTokens, string?)

```
Task RunAsync(string serviceName, string operation, Func<CancellationTokens, Task> action, CancellationTokens cancellationTokens = default, string? successSummary = null)
```

RunAsync<T>(string, string, Func<CancellationTokens, Task<T>>, CancellationTokens, string?)

```
Task<T> RunAsync<T>(string serviceName, string operation, Func<CancellationTokens, Task<T>> action, CancellationTokens cancellationTokens = default, string? successSummary = null)
```


Interface ISqliteEditorPreferenceService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ISqliteEditorPreferenceService
```

⚙️ Methods 3

GetOverridesAsync(string, CancellationToken)

```
Task<IReadOnlyDictionary<string, SqliteEditorFieldOverride>> GetOverridesAsync(string tableName, CancellationToken cancellationToken = default)
```

InferEditorKind(SqliteColumnSummary, string?)

```
string InferEditorKind(SqliteColumnSummary column, string? value)
```

SaveOverrideAsync(SqliteEditorFieldOverride, bool, CancellationToken)

```
Task<SqliteEditorFieldOverride> SaveOverrideAsync(SqliteEditorFieldOverride preference, bool userConfirmed, CancellationToken cancellationToken = default)
```

Interface ISqliteTableEditorService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface ISqliteTableEditorService
```

🐾 Properties 1

DatabasePath

```
string DatabasePath { get; }
```

⚙️ Methods 5

DeleteRowAsync(string, long, CancellationToken)

```
Task DeleteRowAsync(string tableName, long rowId, CancellationToken cancellationToken = default)
```

GetTableAsync(string, int, CancellationToken)

```
Task<SqliteTableSnapshot> GetTableAsync(string tableName, int take = 100, CancellationToken cancellationToken = default)
```

GetTablesAsync(CancellationToken)

```
Task<IReadOnlyList<SqliteTableSummary>> GetTablesAsync(CancellationToken cancellationToken = default)
```

InsertRowAsync(string, IReadOnlyDictionary<string, string?>, CancellationToken)

```
Task InsertRowAsync(string tableName, IReadOnlyDictionary<string, string?> values, CancellationToken cancellationToken = default)
```

UpdateRowAsync(string, long, IReadOnlyList<SqliteCellUpdate>, CancellationToken)

```
Task UpdateRowAsync(string tableName, long rowId, IReadOnlyList<SqliteCellUpdate> updates, CancellationToken cancellationToken = default)
```

Interface IStructuredTextTranslationService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IStructuredTextTranslationService
```

⚙️ Methods 2

TranslateJson(StructuredJsonTranslationRequest)

```
StructuredJsonTranslationResult TranslateJson(StructuredJsonTranslationRequest request)
```

TranslatePlainJsonBlocksToMarkdown(string?)

```
string TranslatePlainJsonBlocksToMarkdown(string? text)
```

Interface ISupervisedTaskRunner

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Starts intentionally non-blocking work while observing completion, cancellation, and failure. Use this instead of discarding a Task returned by an asynchronous method.

```
public interface ISupervisedTaskRunner
```

Properties 1

ActiveTaskCount

```
int ActiveTaskCount { get; }
```

Methods 1

Run(string, string, Func<CancellationToken, Task>, CancellationToken)

```
void Run(string owner, string operation, Func<CancellationToken, Task> action, CancellationToken cancellationToken = default)
```

Interface ISystemVariableDefinitionService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Owns maintained LocalGPT system-variable keys so services never depend on ad-hoc string literals.

```
[DocumentationUpdated("2.1.20")] public interface ISystemVariableDefinitionService
```

Properties 23

CouncilDefaultsVersion

Gets the Council defaults migration-version definition.

```
SystemVariableDefinition<int> CouncilDefaultsVersion { get; }
```

CouncilDxMaximumCallsPerStep

Gets the maximum DXFunction calls per Council step definition.

```
SystemVariableDefinition<int> CouncilDxMaximumCallsPerStep { get; }
```

CouncilDxMaximumParameterCharacters

Gets the maximum DXFunction parameter-character definition.

```
SystemVariableDefinition<int> CouncilDxMaximumParameterCharacters { get; }
```

CouncilDxMaximumResultCharacters

Gets the maximum DXFunction result-character definition.

```
SystemVariableDefinition<int> CouncilDxMaximumResultCharacters { get; }
```

DefaultContextTokens

Gets the default context-token definition.

```
SystemVariableDefinition<int> DefaultContextTokens { get; }
```

DefaultCouncilCritiqueRounds

Gets the default Council critique-round count definition.

```
SystemVariableDefinition<int> DefaultCouncilCritiqueRounds { get; }
```

DefaultCouncilResourceLoadPercent

Gets the default Council resource-load percentage definition.

```
SystemVariableDefinition<int> DefaultCouncilResourceLoadPercent { get; }
```

DefaultHeavyModelGpuLayers

Gets the legacy heavy-model GPU-layer default.

```
SystemVariableDefinition<int> DefaultHeavyModelGpuLayers { get; }
```

DefaultMaxOutputTokens

Gets the default maximum output-token definition.

```
SystemVariableDefinition<int> DefaultMaxOutputTokens { get; }
```

DefaultMaxParallelModels

Gets the default maximum parallel-model definition.

```
SystemVariableDefinition<int> DefaultMaxParallelModels { get; }
```

DefaultMaxPromptCharacters

Gets the default maximum prompt-character definition.

```
SystemVariableDefinition<int> DefaultMaxPromptCharacters { get; }
```

DefaultOllamaEndpoint

Gets the default loopback Ollama endpoint definition.

```
SystemVariableDefinition<string> DefaultOllamaEndpoint { get; }
```

FirstRunOnboardingCompleted

Gets the persisted first-run onboarding completion flag definition.

```
SystemVariableDefinition<bool> FirstRunOnboardingCompleted { get; }
```

InitialValues

Gets all maintained initial variables in deterministic seed order.

```
ReadOnlyList<InitialVariable> InitialValues { get; }
```

LegacyCouncilResourceLoadPercent

Gets the former hard-coded Council resource-load percentage for migration diagnostics.

```
int LegacyCouncilResourceLoadPercent { get; }
```

MaxBootstrapCharacters

Gets the maximum bootstrap-character definition.

```
SystemVariableDefinition<int> MaxBootstrapCharacters { get; }
```

MaxContextTokens

Gets the maximum context-token definition.

```
SystemVariableDefinition<int> MaxContextTokens { get; }
```

MaxOutputTokens

Gets the maximum output-token definition.

```
SystemVariableDefinition<int> MaxOutputTokens { get; }
```

MinContextTokens

Gets the minimum context-token definition.

```
SystemVariableDefinition<int> MinContextTokens { get; }
```

MinOutputTokens

Gets the minimum output-token definition.

```
SystemVariableDefinition<int> MinOutputTokens { get; }
```

ProviderSelectionPolicy

Gets the provider-selection policy definition.

```
SystemVariableDefinition<string> ProviderSelectionPolicy { get; }
```

RegexMatchTimeoutMilliseconds

Gets the regular-expression timeout definition.

```
SystemVariableDefinition<int> RegexMatchTimeoutMilliseconds { get; }
```

RepositoryKnowledgeSeedVersion

Gets the repository knowledge seed-version definition.

```
SystemVariableDefinition<int> RepositoryKnowledgeSeedVersion { get; }
```

api/LocalGPT.Interfaces.IThemeChangeRequestDispatcher.html

Interface IThemeChangeRequestDispatcher

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IThemeChangeRequestDispatcher
```

⚙️ Methods 2

RequestThemeChangeAsync(Theme, ThemeApplicationTarget)

```
Task RequestThemeChangeAsync(Theme theme, ThemeApplicationTarget target)
```

ResetFusionRouteAsync()

```
Task ResetFusionRouteAsync()
```

Interface IThemeLoadNotifier

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IThemeLoadNotifier
```

⚙️ Methods 1

NotifyThemeLoadedAsync(Theme, ThemeApplicationTarget)

```
Task NotifyThemeLoadedAsync(Theme theme, ThemeApplicationTarget target)
```

Interface IVariableStoreService

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

```
public interface IVariableStoreService
```

⚙️ Methods 4

GetAsync<T>(string, CancellationToken)

```
Task<T> GetAsync<T>(string name, CancellationToken cancellationToken = default)
```

ListAllAsync(string, CancellationToken)

```
Task<IEnumerable<SystemVariable>> ListAllAsync(string filter, CancellationToken cancellationToken = default)
```

ListAllAsync(CancellationToken)

```
Task<IEnumerable<SystemVariable>> ListAllAsync(CancellationToken cancellationToken = default)
```

SetAsync<T>(string, T, CancellationToken)

```
Task SetAsync<T>(string name, T value, CancellationToken cancellationToken = default)
```

Class SafeTextDocument

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Inheritance object SafeTextDocument

Implements IEquatable < SafeTextDocument >

```
public sealed record SafeTextDocument : IEquatable<SafeTextDocument>
```

🌟 Constructors 1

SafeTextDocument(string, string, string, string, string, IReadOnlyList<string>)

```
public SafeTextDocument(string Name, string Text, string ContentHash, string EncodingName, string ContentType, IReadOnlyList<string> Warnings)
```

🐾 Properties 6

ContentHash

```
public string ContentHash { get; init; }
```

ContentType

```
public string ContentType { get; init; }
```

EncodingName

```
public string EncodingName { get; init; }
```

Name

```
public string Name { get; init; }
```

Text

```
public string Text { get; init; }
```

Warnings

```
public IReadOnlyList<string> Warnings { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out string, out string, out string, out string, out IReadOnlyList<string>)

```
public void Deconstruct(out string Name, out string Text, out string ContentHash, out string EncodingName, out string ContentType, out IReadOnlyList<string> Warnings)
```

Equals(SafeTextDocument?)

```
public bool Equals(SafeTextDocument? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

➗ Operators 2

operator ==(SafeTextDocument?, SafeTextDocument?)

```
public static bool operator ==(SafeTextDocument? left, SafeTextDocument? right)
```

operator !=(SafeTextDocument?, SafeTextDocument?)

```
public static bool operator !=(SafeTextDocument? left, SafeTextDocument? right)
```

Class SystemVariableDefinition<T>

Namespace LocalGPT . Interfaces Assembly LocalGPT.dll

Describes one strongly typed database-backed system-variable key and its seed default.

Inheritance object SystemVariableDefinition<T>

Implements IEquatable < SystemVariableDefinition <T>>

```
public sealed record SystemVariableDefinition<T> : IEquatable<SystemVariableDefinition<T>>
```

🌟 Constructors 1

SystemVariableDefinition(string, T)

Describes one strongly typed database-backed system-variable key and its seed default.

```
public SystemVariableDefinition(string Name, T DefaultValue)
```

🐾 Properties 2

DefaultValue

Value used only when no durable user value exists.

```
public T DefaultValue { get; init; }
```

Name

Stable database key.

```
public string Name { get; init; }
```

⚙️ Methods 5

Deconstruct(out string, out T)

```
public void Deconstruct(out string Name, out T DefaultValue)
```

Equals(SystemVariableDefinition<T>?)

```
public bool Equals(SystemVariableDefinition<T>? other)
```

Equals(object?)

```
public override bool Equals(object? obj)
```

GetHashCode()

```
public override int GetHashCode()
```

ToString()

```
public override string ToString()
```

÷ Operators 2

operator ==(SystemVariableDefinition<T>?, SystemVariableDefinition<T>?)

```
public static bool operator ==(SystemVariableDefinition<T>? left, SystemVariableDefinition<T>? right)
```

operator !=(SystemVariableDefinition<T>?, SystemVariableDefinition<T>?)

```
public static bool operator !=(SystemVariableDefinition<T>? left, SystemVariableDefinition<T>? right)
```

Class DatabaseLogger

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object DatabaseLogger

Implements ILogger

```
public sealed class DatabaseLogger : ILogger
```

✨ Constructors 1

DatabaseLogger(string, DatabaseLoggerProvider)

```
public DatabaseLogger(string categoryName, DatabaseLoggerProvider provider)
```

⚙️ Methods 3

BeginScope<TState>(TState)

```
public IDisposable BeginScope<TState>(TState state) where TState : notnull
```

IsEnabled(LogLevel)

```
public bool IsEnabled(LogLevel logLevel)
```

Log<TState>(LogLevel, EventId, TState, Exception?, Func<TState, Exception?, string>)

```
public void Log<TState>(LogLevel logLevel, EventId eventId, TState state, Exception? exception, Func<TState, Exception?, string> formatter)
```

Class DatabaseLoggerProvider

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object DatabaseLoggerProvider

Implements ILoggerProvider IDisposable

```
public sealed class DatabaseLoggerProvider : ILoggerProvider, IDisposable
```

✨ Constructors 1

DatabaseLoggerProvider(IDbContextFactory<LocalGptMemoryDbContext>, IOptionsMonitor<DatabaseLoggerCoreOptions>, IDatabaseLoggerReadiness)

```
public DatabaseLoggerProvider(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IOptionsMonitor<DatabaseLoggerCoreOptions> options, IDatabaseLoggerReadiness databaseLoggerReadiness)
```

⚙️ Methods 2

CreateLogger(string)

```
public ILogger CreateLogger(string categoryName)
```

Dispose()

```
public void Dispose()
```


Class EmailLogger

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object EmailLogger

Implements ILogger IDisposable

```
public sealed class EmailLogger : ILogger, IDisposable
```

✨ Constructors 1

EmailLogger(string, IOptionsMonitor<EmailLoggerCoreOptions>)

```
public EmailLogger(string categoryName, IOptionsMonitor<EmailLoggerCoreOptions> optionsSnapshot)
```

⚙️ Methods 3

Dispose()

```
public void Dispose()
```

IsEnabled(LogLevel)

```
public bool IsEnabled(LogLevel logLevel)
```

Log<TState>(LogLevel, EventId, TState, Exception?, Func<TState, Exception?, string>)

```
public void Log<TState>(LogLevel logLevel, EventId eventId, TState state, Exception? exception, Func<TState, Exception?, string> formatter)
```

Class EmailLoggerProvider

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object EmailLoggerProvider

Implements ILoggerProvider IDisposable

```
public sealed class EmailLoggerProvider : ILoggerProvider, IDisposable
```

✨ Constructors 1

EmailLoggerProvider(IOptionsMonitor<EmailLoggerCoreOptions>)

```
public EmailLoggerProvider(IOptionsMonitor<EmailLoggerCoreOptions> options)
```

⚙️ Methods 2

CreateLogger(string)

```
public ILogger CreateLogger(string categoryName)
```

Dispose()

```
public void Dispose()
```

Class FileLogger

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object FileLogger

Implements ILogger IDisposable

```
public class FileLogger : ILogger, IDisposable
```

✨ Constructors 1

FileLogger(string, IOptionMonitor<FileLoggerCoreOptions>)

```
public FileLogger(string categoryName, IOptionMonitor<FileLoggerCoreOptions> optionsSnapshot)
```

⚙️ Methods 3

Dispose()

```
public void Dispose()
```

IsEnabled(LogLevel)

```
public bool IsEnabled(LogLevel logLevel)
```

Log<TState>(LogLevel, EventId, TState, Exception?, Func<TState, Exception?, string>)

```
public void Log<TState>(LogLevel logLevel, EventId eventId, TState state, Exception? exception, Func<TState, Exception?, string> formatter)
```

Class FileLoggerProvider

Namespace LocalGPT . Logging Assembly LocalGPT.dll

Inheritance object FileLoggerProvider

Implements ILoggerProvider IDisposable

```
public class FileLoggerProvider : ILoggerProvider, IDisposable
```

✨ Constructors 1

FileLoggerProvider(IOptionMonitor<FileLoggerCoreOptions>)

```
public FileLoggerProvider(IOptionMonitor<FileLoggerCoreOptions> options)
```

⚙️ Methods 3

CreateLogger(string)

```
public ILogger CreateLogger(string categoryName)
```

Dispose()

```
public void Dispose()
```

Dispose(bool)

```
protected virtual void Dispose(bool disposing)
```

Namespace LocalGPT.Logging

Classes

Class AddChatSessionControl

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddChatSessionControl

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260725150000_AddChatSessionControl")] public class AddChatSessionControl : Migration
```

🌟 Constructors 1

AddChatSessionControl()

```
public AddChatSessionControl()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddCodeGenerationChangeReviews

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddCodeGenerationChangeReviews

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260725030000_AddCodeGenerationChangeReviews")] public class AddCodeGenerationChangeReviews : Migration
```

🌟 Constructors 1

AddCodeGenerationChangeReviews()

```
public AddCodeGenerationChangeReviews()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddCouncilRuntimeClasses

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddCouncilRuntimeClasses

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260802010000_AddCouncilRuntimeClasses")] public class AddCouncilRuntimeClasses : Migration
```

🌟 Constructors 1

AddCouncilRuntimeClasses()

```
public AddCouncilRuntimeClasses()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddCouncilTeamScripting

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddCouncilTeamScripting

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260726150000_AddCouncilTeamScripting")] public class AddCouncilTeamScripting : Migration
```

🌟 Constructors 1

AddCouncilTeamScripting()

```
public AddCouncilTeamScripting()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddDatabaseFirstProjectArchitecture

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddDatabaseFirstProjectArchitecture

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260726010000_AddDatabaseFirstProjectArchitecture")] public class AddDatabaseFirstProjectArchitecture : Migration
```

🌟 Constructors 1

AddDatabaseFirstProjectArchitecture()

```
public AddDatabaseFirstProjectArchitecture()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddDeferredDxAiInvocations

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddDeferredDxAiInvocations

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260726001000_AddDeferredDxAiInvocations")] public class AddDeferredDxAiInvocations : Migration
```

🌟 Constructors 1

AddDeferredDxAiInvocations()

```
public AddDeferredDxAiInvocations()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddEmbeddedFirmwareAndWorkspaceEnvironments

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddEmbeddedFirmwareAndWorkspaceEnvironments

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260802020000_AddEmbeddedFirmwareAndWorkspaceEnvironments")] public class AddEmbeddedFirmwareAndWorkspaceEnvironments : Migration
```

🌟 Constructors 1

AddEmbeddedFirmwareAndWorkspaceEnvironments()

```
public AddEmbeddedFirmwareAndWorkspaceEnvironments()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddFeaturePersistenceRecords

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddFeaturePersistenceRecords

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260803000000_AddFeaturePersistenceRecords")] public class AddFeaturePersistenceRecords : Migration
```

🌟 Constructors 1

AddFeaturePersistenceRecords()

```
public AddFeaturePersistenceRecords()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddHumanCollaboration

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddHumanCollaboration

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260726000000_AddHumanCollaboration")] public class AddHumanCollaboration : Migration
```

🌟 Constructors 1

AddHumanCollaboration()

```
public AddHumanCollaboration()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddHumanQuestionFlow

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddHumanQuestionFlow

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260731152000_AddHumanQuestionFlow")] public class AddHumanQuestionFlow : Migration
```

🌟 Constructors 1

AddHumanQuestionFlow()

```
public AddHumanQuestionFlow()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class addingGeneralConfigTables

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration addingGeneralConfigTables

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260711220358_addingGeneralConfigTables")] public class addingGeneralConfigTables : Migration
```

🌟 Constructors 1

addingGeneralConfigTables()

```
public addingGeneralConfigTables()
```

⚙️ Methods 3

BuildTargetModel(ModelBuilder)

```
protected override void BuildTargetModel(ModelBuilder modelBuilder)
```

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddOrganicSkillsAndHardwareRoutes

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddOrganicSkillsAndHardwareRoutes

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260726133000_AddOrganicSkillsAndHardwareRoutes")] public class AddOrganicSkillsAndHardwareRoutes : Migration
```

🌟 Constructors 1

AddOrganicSkillsAndHardwareRoutes()

```
public AddOrganicSkillsAndHardwareRoutes()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddProjectCollaboration

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddProjectCollaboration

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260725000000_AddProjectCollaboration")] public class AddProjectCollaboration : Migration
```

🌟 Constructors 1

AddProjectCollaboration()

```
public AddProjectCollaboration()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddProjectMaintenanceWorkspaces

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddProjectMaintenanceWorkspaces

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260727190000_AddProjectMaintenanceWorkspaces")] public class AddProjectMaintenanceWorkspaces : Migration
```

🌟 Constructors 1

AddProjectMaintenanceWorkspaces()

```
public AddProjectMaintenanceWorkspaces()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class AddReusableHumanApprovalDecisions

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration AddReusableHumanApprovalDecisions

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260803090000_AddReusableHumanApprovalDecisions")] public class AddReusableHumanApprovalDecisions : Migration
```

🌟 Constructors 1

AddReusableHumanApprovalDecisions()

```
public AddReusableHumanApprovalDecisions()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```


Class FixProjectTrackedFileRevisionIdentity

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration FixProjectTrackedFileRevisionIdentity

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260727193000_FixProjectTrackedFileRevisionIdentity")] public class
FixProjectTrackedFileRevisionIdentity : Migration
```

🌟 Constructors 1

FixProjectTrackedFileRevisionIdentity()

```
public FixProjectTrackedFileRevisionIdentity()
```

⚙️ Methods 2

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Namespace LocalGPT.Migrations

Classes

Class Initial

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration Initial

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260616222639_Initial")] public class Initial : Migration
```

🌟 Constructors 1

Initial()

```
public Initial()
```

⚙️ Methods 3

BuildTargetModel(ModelBuilder)

```
protected override void BuildTargetModel(ModelBuilder modelBuilder)
```

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class testWithNewSystem

Namespace LocalGPT . Migrations Assembly LocalGPT.dll

Inheritance object Migration testWithNewSystem

```
[DbContext(typeof(LocalGptMemoryDbContext))] [Migration("20260727200603_testWithNewSystem")] public class testWithNewSystem : Migration
```

🌟 Constructors 1

testWithNewSystem()

```
public testWithNewSystem()
```

⚙️ Methods 3

BuildTargetModel(ModelBuilder)

```
protected override void BuildTargetModel(ModelBuilder modelBuilder)
```

Down(MigrationBuilder)

```
protected override void Down(MigrationBuilder migrationBuilder)
```

Up(MigrationBuilder)

```
protected override void Up(MigrationBuilder migrationBuilder)
```

Class Program

Namespace LocalGPT Assembly LocalGPT.dll

Inheritance object Program

```
public static class Program
```

🔴 Fields 3

DefaultOneWireDiscoveryPort

```
public const int DefaultOneWireDiscoveryPort = 51141
```

DefaultOneWirePort

```
public const int DefaultOneWirePort = 51140
```

DefaultPort

```
public const int DefaultPort = 5000
```

🐾 Properties 4

BaseUrl

```
public static string BaseUrl { get; }
```

OneWireDiscoveryPort

```
public static int OneWireDiscoveryPort { get; }
```

OneWirePort

```
public static int OneWirePort { get; }
```

Port

```
public static int Port { get; }
```

⚙️ Methods 1

BuildWebApp(string[]?)

```
public static WebApplication BuildWebApp(string[]? args = null)
```

Namespace LocalGPT.Security

Classes

Class HumanApprovalActionFilter

Namespace LocalGPT . Security Assembly LocalGPT.dll

Inheritance object HumanApprovalActionFilter

Implements IAsyncActionFilter IFilterMetadata

```
public sealed class HumanApprovalActionFilter : IAsyncActionFilter, IFilterMetadata
```

✨ Constructors 1

HumanApprovalActionFilter(string, string, string, string, string, string, bool, IHumanCollaborationService, IAmbientLocalGptContext, IHumanApprovalExecutionContext, ILogger<HumanApprovalActionFilter>)

```
public HumanApprovalActionFilter(string operationKey, string title, string description, string riskLevel, string requestedRole, bool requiredBeforeCompletion, IHumanCollaborationService collaboration, IAmbientLocalGptContext ambientContext, IHumanApprovalExecutionContext approvalExecutionContext, ILogger<HumanApprovalActionFilter> logger)
```

⚙️ Methods 1

OnActionExecutionAsync(ActionExecutingContext, ActionExecutionDelegate)

```
public Task OnActionExecutionAsync(ActionExecutingContext context, ActionExecutionDelegate next)
```

Class HumanApprovalRequiredAttribute

Namespace LocalGPT . Security Assembly LocalGPT.dll

Inheritance object Attribute TypeFilterAttribute HumanApprovalRequiredAttribute

Implements IFilterFactory IOrderedFilter IFilterMetadata

```
[AttributeUsage(AttributeTargets.Method, AllowMultiple = false, Inherited = true)] public sealed class HumanApprovalRequiredAttribute : TypeFilterAttribute, IFilterFactory, IOrderedFilter, IFilterMetadata
```

✨ Constructors 1

HumanApprovalRequiredAttribute(string, string, string, string, string, bool)

```
public HumanApprovalRequiredAttribute(string operationKey, string title, string description, string riskLevel = "Medium", string requestedRole = "Security reviewer", bool requiredBeforeCompletion = false)
```

Class AdaptiveOllamaBenchmarkWiring

Namespace LocalGPT . Services Assembly LocalGPT.dll

Runs a bounded, user-approved benchmark against models already installed in the configured local Ollama runtime. It never pulls models, changes global Ollama state, or overwrites an existing preset.

Inheritance object AdaptiveOllamaBenchmarkWiring

Implements IDxAiFunctionHandler

```
public sealed class AdaptiveOllamaBenchmarkWiring : IDxAiFunctionHandler
```

🌟 Constructors 1

AdaptiveOllamaBenchmarkWiring(IOptionsMonitor<ConfigurationRoot>, IHardwareInventoryService, IModelPresetService, ILogger<AdaptiveOllamaBenchmarkWiring>)

Runs a bounded, user-approved benchmark against models already installed in the configured local Ollama runtime. It never pulls models, changes global Ollama state, or overwrites an existing preset.

```
public AdaptiveOllamaBenchmarkWiring(IOptionsMonitor<ConfigurationRoot> configuration, IHardwareInventoryService hardwareInventory, IModelPresetService modelPresets, ILogger<AdaptiveOllamaBenchmarkWiring> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class AiConnectivityProbe

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AiConnectivityProbe

Implements IAiConnectivityProbe

```
public sealed class AiConnectivityProbe : IAiConnectivityProbe
```

🌟 Constructors 1

AiConnectivityProbe(ILogger<AiConnectivityProbe>, AiDiscoveryService, CouncilTextService)

```
public AiConnectivityProbe(ILogger<AiConnectivityProbe> logger, AiDiscoveryService aiDiscovery, CouncilTextService councilText)
```

⚙️ Methods 6

DiscoverLocalHostsAsync(CancellationToken)

```
public Task<IReadOnlyList<LocalAiHostDiscoveryResult>> DiscoverLocalHostsAsync(CancellationToken cancellationToken)
```

TestAzureAsync(OpenAIServiceCoreOptions, CancellationToken)

```
public Task<(bool ok, string message)> TestAzureAsync(OpenAIServiceCoreOptions options, CancellationToken cancellationToken)
```

TestLocalOpenAICompatAsync(ChatGPTLocalCoreOptions, CancellationToken)

```
public Task<(bool ok, string message)> TestLocalOpenAICompatAsync(ChatGPTLocalCoreOptions options, CancellationToken cancellationToken)
```

TestOllamaAsync(OllamaCoreOptions, CancellationToken)

```
public Task<(bool ok, string message)> TestOllamaAsync(OllamaCoreOptions options, CancellationToken cancellationToken)
```

TestOpenAIAsync(OpenAICompatOptions, CancellationToken)

```
public Task<(bool ok, string message)> TestOpenAIAsync(OpenAICompatOptions options, CancellationToken cancellationToken)
```

TryStartLocalAsync(ChatGPTLocalCoreOptions, CancellationToken)

```
public Task<(bool ok, string message)> TryStartLocalAsync(ChatGPTLocalCoreOptions options, CancellationToken cancellationToken)
```

Class AiContextBootstrapService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AiContextBootstrapService

Implements IAIContextBootstrapService

```
public class AiContextBootstrapService : IAIContextBootstrapService
```

🌟 Constructors 1

AiContextBootstrapService(IChatMemoryService, ICouncilKnowledgeService, IApplicationLogReaderService, IComponentActivityService, IProjectLibraryInventoryService, IBuildDebugInventoryService, ICouncilArtifactService, IChatUploadWorkspaceService, IHttpContextAccessor, ILogger<AiContextBootstrapService>, CouncilRuntimeService, CouncilTextService, DevExpressChatService, LocalGptCatalogService)

```
public AiContextBootstrapService(IChatMemoryService chatMemory, ICouncilKnowledgeService councilKnowledge, IApplicationLogReaderService applicationLogs, IComponentActivityService componentActivity, IProjectLibraryInventoryService libraryInventory, IBuildDebugInventoryService buildDebugInventory, ICouncilArtifactService councilArtifacts, IChatUploadWorkspaceService chatUploadWorkspaces, IHttpContextAccessor httpContextAccessor, ILogger<AiContextBootstrapService> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, DevExpressChatService devExpressChat, LocalGptCatalogService catalog)
```

⚙️ Methods 1

BuildBootstrapPromptAsync(CancellationToken)

```
public Task<string> BuildBootstrapPromptAsync(CancellationToken cancellationToken = default)
```

Class AiDiscoveryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AiDiscoveryService

```
public sealed class AiDiscoveryService
```

🌟 Constructors 1

AiDiscoveryService(CouncilRuntimeService, CouncilTextService, LocalGptCatalogService, ILogger<AiDiscoveryService>)

```
public AiDiscoveryService(CouncilRuntimeService runtime, CouncilTextService text, LocalGptCatalogService catalog, ILogger<AiDiscoveryService> serviceLogger)
```

⚙️ Methods 4

CreateDiscoveryClient(string, ILogger<AiConnectivityProbe>)

```
public HttpClient CreateDiscoveryClient(string endpoint, ILogger<AiConnectivityProbe> logger)
```

GetAsync(HttpClient, string, CancellationToken, ILogger<AiConnectivityProbe>)

```
public Task<(bool ok, string msg)> GetAsync(HttpClient http, string path, CancellationToken ct, ILogger<AiConnectivityProbe> logger)
```

ProbeOllamaAsync(string, CancellationToken, ILogger<AiConnectivityProbe>)

```
public Task<LocalAiHostDiscoveryResult> ProbeOllamaAsync(string endpoint, CancellationToken ct, ILogger<AiConnectivityProbe> logger)
```

ProbeOpenAICompatibleAsync(string, string, CancellationToken, ILogger<AiConnectivityProbe>)

```
public Task<LocalAiHostDiscoveryResult> ProbeOpenAICompatibleAsync(string provider, string endpoint, CancellationToken ct, ILogger<AiConnectivityProbe> logger)
```

Class AiFeatureReportService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AiFeatureReportService

Implements IAIFeatureReportService

```
public class AiFeatureReportService : IAIFeatureReportService
```

🌟 Constructors 1

AiFeatureReportService(ILogger<AiFeatureReportService>, CouncilTextService)

```
public AiFeatureReportService(ILogger<AiFeatureReportService> logger, CouncilTextService councilText)
```

🐾 Properties 1

ReportRoot

```
public string ReportRoot { get; }
```

⚙️ Methods 1

WriteIfMissingFeatureReportAsync(string, string, CancellationToken)

```
public Task<string?> WriteIfMissingFeatureReportAsync(string source, string responseText, CancellationToken cancellationToken = default)
```

Class AmbientLocalGptContext

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AmbientLocalGptContext

Implements IAmbientLocalGptContext ILocalHumanInteractionContext IHumanApprovalExecutionContext

```
public sealed class AmbientLocalGptContext : IAmbientLocalGptContext, ILocalHumanInteractionContext, IHumanApprovalExecutionContext
```

🌟 Constructors 1

AmbientLocalGptContext(ILocalGptVocabularyService, ILogger<AmbientLocalGptContext>)

```
public AmbientLocalGptContext(ILocalGptVocabularyService vocabulary, ILogger<AmbientLocalGptContext> logger)
```

🐾 Properties 1

Current

```
public AmbientLocalGptContextSnapshot Current { get; }
```

⚙️ Methods 4

PushCouncil(Guid, int, string, string?)

```
public IDisposable PushCouncil(Guid councilRunId, int councilRound, string phase, string? correlationId = null)
```

PushHumanApproval(Guid, string, Guid, string, string, Guid?, int, string)

```
public IDisposable PushHumanApproval(Guid humanProfileId, string displayName, Guid approvalRequestId, string source, string correlationId, Guid? councilRunId = null, int councilRound = 0, string phase = "")
```

PushHumanInteraction(Guid, string, string, string?, Guid?, int, string)

```
public IDisposable PushHumanInteraction(Guid humanProfileId, string displayName, string source, string? correlationId = null, Guid? councilRunId = null, int councilRound = 0, string phase = "")
```

PushSystem(string, string?)

```
public IDisposable PushSystem(string source, string? correlationId = null)
```

Class ApplicationLogReaderService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ApplicationLogReaderService

Implements IApplicationLogReaderService

```
public class ApplicationLogReaderService : IApplicationLogReaderService
```

🌟 Constructors 1

ApplicationLogReaderService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, LocalGptDatabaseOptions, ILogger<ApplicationLogReaderService>, CouncilTextService)

```
public ApplicationLogReaderService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, LocalGptDatabaseOptions databaseOptions, ILogger<ApplicationLogReaderService> logger, CouncilTextService councilText)
```

🐾 Properties 1

DatabasePath

```
public string DatabasePath { get; }
```

⚙️ Methods 2

BuildAiLogBriefingAsync(LogLevel, int, CancellationToken)

```
public Task<string> BuildAiLogBriefingAsync(LogLevel minimumLevel = LogLevel.Warning, int take = 8, CancellationToken cancellationToken = default)
```

GetRecentAsync(LogLevel, int, CancellationToken)

```
public Task<IReadOnlyList<ApplicationLogSummary>> GetRecentAsync(LogLevel minimumLevel = LogLevel.Warning, int take = 20, CancellationToken cancellationToken = default)
```

Class ApproveProjectRevisionReadyFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ApproveProjectRevisionReadyFunction

Implements IDxAiFunctionHandler

```
public sealed class ApproveProjectRevisionReadyFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ApproveProjectRevisionReadyFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<ApproveProjectRevisionReadyFunction>)

```
public ApproveProjectRevisionReadyFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance, ILogger<ApproveProjectRevisionReadyFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ArtifactBuildExecutor

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ArtifactBuildExecutor

Implements IArtifactBuildExecutor

```
public sealed class ArtifactBuildExecutor : IArtifactBuildExecutor
```

✨ Constructors 1

ArtifactBuildExecutor(IOptionsMonitor<ArtifactBuildOptions>, ILogger<ArtifactBuildExecutor>)

```
public ArtifactBuildExecutor(IOptionsMonitor<ArtifactBuildOptions> options, ILogger<ArtifactBuildExecutor> logger)
```

⚙️ Methods 1

BuildAsync(string, string, string, string?, TimeSpan, CancellationToken, bool)

```
public Task<ArtifactBuildExecutionResult> BuildAsync(string targetPath, string allowedRoot, string configuration, string? outputDirectory, TimeSpan requestedTimeout, CancellationToken cancellationToken = default, bool userConfirmed = false)
```

Class AssessProjectWorkspaceEnvironmentFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object AssessProjectWorkspaceEnvironmentFunction

Implements IDxAiFunctionHandler

```
public sealed class AssessProjectWorkspaceEnvironmentFunction : IDxAiFunctionHandler
```

✨ Constructors 1

AssessProjectWorkspaceEnvironmentFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<AssessProjectWorkspaceEnvironmentFunction>)

```
public AssessProjectWorkspaceEnvironmentFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance, ILogger<AssessProjectWorkspaceEnvironmentFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```


Class BuildDebugInventoryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object BuildDebugInventoryService

Implements IBuildDebugInventoryService

```
public sealed class BuildDebugInventoryService : IBuildDebugInventoryService
```

🌟 Constructors 1

BuildDebugInventoryService(ILogger<BuildDebugInventoryService>, CouncilRuntimeService, LocalGptCatalogService)

```
public BuildDebugInventoryService(ILogger<BuildDebugInventoryService> logger, CouncilRuntimeService councilRuntime, LocalGptCatalogService catalog)
```

🔗 Properties 1

ArtifactRoot

```
public string ArtifactRoot { get; }
```

⚙️ Methods 2

BuildBriefingAsync(CancellationToken)

```
public Task<string> BuildBriefingAsync(CancellationToken cancellationToken = default)
```

CaptureAsync(bool, CancellationToken)

```
public Task<BuildDebugInventory> CaptureAsync(bool copyFiles = false, CancellationToken cancellationToken = default)
```

Class ChatClientFactory

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ChatClientFactory

Implements IChatClientFactory

```
public class ChatClientFactory : IChatClientFactory
```

🌟 Constructors 1

ChatClientFactory(ILogger<ChatClientFactory>, ILoggerFactory, IOptionsMonitor<ConfigurationRoot>, IAIFeatureReportService, IAIContextBootstrapService, ICouncilKnowledgeService, IChatUploadWorkspaceService, IPromptConfigService, IVariableStoreService, ISystemVariableDefinitionService, IDxAiFunctionRegistry, IChatResponseFormatterFactory, IChatProtocolResolver, CouncilRuntimeService, CouncilTextService)

```
public ChatClientFactory(ILogger<ChatClientFactory> logger, ILoggerFactory loggerFactory, IOptionsMonitor<ConfigurationRoot> optionsRoot, IAIFeatureReportService featureReportService, IAIContextBootstrapService bootstrapService, ICouncilKnowledgeService knowledgeService, IChatUploadWorkspaceService chatUploadWorkspaces, IPromptConfigService promptConfigService, IVariableStoreService variableStoreService, ISystemVariableDefinitionService systemVariables, IDxAiFunctionRegistry functionRegistry, IChatResponseFormatterFactory formatterFactory, IChatProtocolResolver protocolResolver, CouncilRuntimeService councilRuntime, CouncilTextService councilText)
```

⚙️ Methods 1

Build()

```
public CompositeChatClient Build()
```

Class ChatClientSession

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ChatClientSession

```
public class ChatClientSession
```

🌟 Constructors 1

ChatClientSession(IChatClient, string, string?, string?, string?)

```
public ChatClientSession(IChatClient client, string name, string? provider = null, string? modelName = null, string? endpoint = null)
```

🐾 Properties 7

Client

```
public IChatClient Client { get; }
```

Endpoint

```
public string Endpoint { get; }
```

Messages

```
public List<BlazorChatMessage> Messages { get; set; }
```

ModelName

```
public string ModelName { get; }
```

Name

```
public string Name { get; set; }
```

Provider

```
public string Provider { get; }
```

SelectionKey

```
public string SelectionKey { get; }
```

Class ChatMemoryMessageMapper

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ChatMemoryMessageMapper

Implements IChatMemoryMessageMapper

```
public sealed class ChatMemoryMessageMapper : IChatMemoryMessageMapper
```

✨ Constructors 1

ChatMemoryMessageMapper(CouncilTextService, LocalGptCatalogService, ILogger<ChatMemoryMessageMapper>)

```
public ChatMemoryMessageMapper(CouncilTextService text, LocalGptCatalogService catalog, ILogger<ChatMemoryMessageMapper> logger)
```

⚙️ Methods 4

BuildTitle(IReadOnlyList<BlazorChatMessage>)

```
public string BuildTitle(IReadOnlyList<BlazorChatMessage> messages)
```

EnsureVisibleCouncilPrompt(ChatMemoryConversation, List<BlazorChatMessage>)

```
public List<BlazorChatMessage> EnsureVisibleCouncilPrompt(ChatMemoryConversation conversation, List<BlazorChatMessage> messages)
```

ToBlazorChatMessage(ChatMemoryMessage)

```
public BlazorChatMessage ToBlazorChatMessage(ChatMemoryMessage message)
```

ToRoleName(ChatMessageRole)

```
public string ToRoleName(ChatMessageRole role)
```

Class ChatSessionContext

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ChatSessionContext

Implements IChatSessionContext

```
public sealed class ChatSessionContext : IChatSessionContext
```

🌟 Constructors 1

ChatSessionContext(ICustomVersion, ILogger<ChatSessionContext>)

```
public ChatSessionContext(ICustomVersion version, ILogger<ChatSessionContext> logger)
```

🐾 Properties 4

ApplicationVersion

```
public string ApplicationVersion { get; }
```

ConversationId

```
public Guid? ConversationId { get; }
```

ProjectId

```
public Guid? ProjectId { get; }
```

ProjectVersionId

```
public Guid? ProjectVersionId { get; }
```

⚙️ Methods 4

Restore(ChatSessionContextSnapshot)

```
public void Restore(ChatSessionContextSnapshot snapshot)
```

SetConversation(Guid?)

```
public void SetConversation(Guid? conversationId)
```

SetProject(Guid?, Guid?)

```
public void SetProject(Guid? projectId, Guid? projectVersionId)
```

Snapshot()

```
public ChatSessionContextSnapshot Snapshot()
```

Class ChatUploadWorkspaceService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ChatUploadWorkspaceService

Implements IChatUploadWorkspaceService

```
public sealed class ChatUploadWorkspaceService : IChatUploadWorkspaceService
```

🌟 Constructors 1

ChatUploadWorkspaceService(ILogger<ChatUploadWorkspaceService>, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService)

```
public ChatUploadWorkspaceService(ILogger<ChatUploadWorkspaceService> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog)
```

🐾 Properties 1

WorkspaceRoot

```
public string WorkspaceRoot { get; }
```

⚙️ Methods 8

CreateWorkspaceAsync(string, IEnumerable<ChatUploadWorkspaceInputFile>, CancellationToken)

```
public Task<ChatUploadWorkspaceResult> CreateWorkspaceAsync(string prompt, IEnumerable<ChatUploadWorkspaceInputFile> files, CancellationToken cancellationTok = default)
```

GetLatestContextMarkdown(int, TimeSpan?)

```
public string GetLatestContextMarkdown(int maxCharacters, TimeSpan? maxAge = null)
```

GetLatestWorkspace(TimeSpan?)

```
public ChatUploadWorkspaceSummary? GetLatestWorkspace(TimeSpan? maxAge = null)
```

ListFiles(string, int)

```
public IReadOnlyList<ChatUploadWorkspaceFileSummary> ListFiles(string workspaceName, int take = 250)
```

ListWorkspaces(int)

```
public IReadOnlyList<ChatUploadWorkspaceSummary> ListWorkspaces(int take = 20)
```

ReadContextMarkdownAsync(string, int, CancellationToken)

```
public Task<string> ReadContextMarkdownAsync(string workspaceName, int maxCharacters, CancellationToken cancellationTok = default)
```

ReadFileAsync(string, string, int, CancellationToken)

```
public Task<ChatUploadWorkspaceFileReadResult?> ReadFileAsync(string workspaceName, string relativePath, int maxCharacters, CancellationToken cancellationTok = default)
```

ResolveWorkspacePath(string)

```
public string? ResolveWorkspacePath(string workspaceName)
```

Class CodeGenerationWorkflowService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CodeGenerationWorkflowService

Implements ICodeGenerationWorkflowService

```
public sealed class CodeGenerationWorkflowService : ICodeGenerationWorkflowService
```

🌟 Constructors 1

CodeGenerationWorkflowService(IDbContextFactory<LocalGptMemoryDbContext>, ICouncilArtifactService, IArtifactBuildExecutor, IProjectMaintenanceService, ILogger<CodeGenerationWorkflowService>)

```
public CodeGenerationWorkflowService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, ICouncilArtifactService councilArtifacts, IArtifactBuildExecutor artifactBuildExecutor, IProjectMaintenanceService projectMaintenance, ILogger<CodeGenerationWorkflowService> logger)
```

⚙️ Methods 5

CreateReviewAsync(CreateCodeGenerationReviewRequest, CancellationToken)

```
public Task<CodeGenerationReviewSnapshot> CreateReviewAsync(CreateCodeGenerationReviewRequest request, CancellationToken cancellationToken = default)
```

ExecuteReviewAsync(Guid, ExecuteCodeGenerationReviewRequest, CancellationToken)

```
public Task<CodeGenerationExecutionResult> ExecuteReviewAsync(Guid reviewId, ExecuteCodeGenerationReviewRequest request, CancellationToken cancellationToken = default)
```

GetReviewAsync(Guid, CancellationToken)

```
public Task<CodeGenerationReviewSnapshot?> GetReviewAsync(Guid reviewId, CancellationToken cancellationToken = default)
```

ListReviewsAsync(Guid?, int, CancellationToken)

```
public Task<IReadOnlyList<CodeGenerationReviewSnapshot>> ListReviewsAsync(Guid? projectId = null, int take = 20, CancellationToken cancellationToken = default)
```

RejectReviewAsync(Guid, RejectCodeGenerationReviewRequest, CancellationToken)

```
public Task<CodeGenerationReviewSnapshot> RejectReviewAsync(Guid reviewId, RejectCodeGenerationReviewRequest request, CancellationToken cancellationToken = default)
```

Class ComponentActivityService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Bounded, process-local operational memory for the current LocalGPT run. It records concise UI and service state only; prompts, message bodies, secrets, uploaded content, generated source, parameters, and full exception text are excluded.

Inheritance object ComponentActivityService

Implements IComponentActivityService IServiceActivityService

```
public sealed class ComponentActivityService : IComponentActivityService, IServiceActivityService
```

🌟 Constructors 1

ComponentActivityService(ILogger<ComponentActivityService>)

Bounded, process-local operational memory for the current LocalGPT run. It records concise UI and service state only; prompts, message bodies, secrets, uploaded content, generated source, parameters, and full exception text are excluded.

```
public ComponentActivityService(ILogger<ComponentActivityService> logger)
```

⚙️ Methods 8

BuildBriefing(int)

```
public string BuildBriefing(int take = 12)
```

GetRecent(int)

```
public IReadOnlyList<ComponentActivitySnapshot> GetRecent(int take = 20)
```

RecordFailure(string, string, Exception, string?)

```
public void RecordFailure(string component, string operation, Exception exception, string? route = null)
```

RecordInformation(string, string, string, string?)

```
public void RecordInformation(string component, string operation, string summary, string? route = null)
```

RecordNavigation(string)

```
public void RecordNavigation(string route)
```

RecordWarning(string, string, string, string?)

```
public void RecordWarning(string component, string operation, string summary, string? route = null)
```

RunAsync(string, string, Func<CancellationToken, Task>, Cancellation_token, string?)

```
public Task RunAsync(string serviceName, string operation, Func<CancellationToken, Task> action, Cancellation_token cancellationToken = default, string? successSummary = null)
```

RunAsync<T>(string, string, Func<CancellationToken, Task<T>>, Cancellation_token, string?)

```
public Task<T> RunAsync<T>(string serviceName, string operation, Func<CancellationToken, Task<T>> action, Cancellation_token cancellationToken = default, string? successSummary = null)
```

Class CompositeChatClient

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CompositeChatClient

Implements IChatClient IDisposable

```
public class CompositeChatClient : IChatClient, IDisposable
```

🌟 Constructors 1

CompositeChatClient(ILogger, IAIFeatureReportService?, IAIContextBootstrapService?, ICouncilKnowledgeService?, IChatUploadWorkspaceService?, IPromptConfigService?, IVariableStoreService?, ISystemVariableDefinitionService, CouncilRuntimeService, CouncilTextService, params ChatClientSession[])

```
public CompositeChatClient(ILogger logger, IAIFeatureReportService? featureReportService, IAIContextBootstrapService? bootstrapService, ICouncilKnowledgeService? knowledgeService, IChatUploadWorkspaceService? chatUploadWorkspaces, IPromptConfigService? promptConfigService, IVariableStoreService? variableStoreService, ISystemVariableDefinitionService systemVariables, CouncilRuntimeService councilRuntime, CouncilTextService councilText, params ChatClientSession[] chatClients)
```

🐾 Properties 6

AvailableChatClients

```
public List<ChatClientSession> AvailableChatClients { get; }
```

ForcedMaxOutputTokens

```
public int? ForcedMaxOutputTokens { get; set; }
```

ForcedMaxPromptCharacters

```
public int? ForcedMaxPromptCharacters { get; set; }
```

LockedSessionName

```
public string? LockedSessionName { get; set; }
```

SelectedSession

```
public ChatClientSession? SelectedSession { get; set; }
```

SuppressBootstrapContext

```
public bool SuppressBootstrapContext { get; set; }
```

⚙️ Methods 4

Dispose()

```
public void Dispose()
```

GetResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

```
public Task<ChatResponse> GetResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```

GetService(Type, object?)

```
public object? GetService(Type serviceType, object? serviceKey = null)
```

GetStreamingResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

```
public IAsyncEnumerable<ChatResponseUpdate> GetStreamingResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```


Class ConfigurationWriter

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ConfigurationWriter

Implements IConfigurationWriter

```
public sealed class ConfigurationWriter : IConfigurationWriter
```

✨ Constructors 1

ConfigurationWriter(ILogger<ConfigurationWriter>)

```
public ConfigurationWriter(ILogger<ConfigurationWriter> logger)
```

⚙️ Methods 1

SaveAsync(ConfigurationRoot, CancellationToken)

```
public Task SaveAsync(ConfigurationRoot root, CancellationToken ct = default)
```

Class ControlCouncilGameFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ControlCouncilGameFunction

Implements IDxAiFunctionHandler

```
public sealed class ControlCouncilGameFunction : IDxAiFunctionHandler
```

✨ Constructors 1

ControlCouncilGameFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<ControlCouncilGameFunction>)

```
public ControlCouncilGameFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<ControlCouncilGameFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class CouncilPreflightService

Namespace LocalGPT . Services . Council Assembly LocalGPT.dll

Performs the bounded, lossless database and runtime-directory audit required before every council run. Deterministic seed gaps are filled by database initialization; missing volatile facts are returned as explicit questions instead of being guessed.

Inheritance object CouncilPreflightService

Implements ICouncilPreflightService

```
public sealed class CouncilPreflightService : ICouncilPreflightService
```

✨ Constructors 1

CouncilPreflightService(IDatabaseInitializationService, IDbContextFactory<LocalGptMemoryDbContext>, IRuntimeCapabilityDirectoryService, IOneWirePeerRegistry, ICouncilTeamConfigurationService, ILogger<CouncilPreflightService>)

Performs the bounded, lossless database and runtime-directory audit required before every council run. Deterministic seed gaps are filled by database initialization; missing volatile facts are returned as explicit questions instead of being guessed.

```
public CouncilPreflightService(IDatabaseInitializationService databaseInitialization, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory,
    IRuntimeCapabilityDirectoryService capabilityDirectory, IOneWirePeerRegistry oneWirePeers, ICouncilTeamConfigurationService teams,
    ILogger<CouncilPreflightService> logger)
```

⚙️ Methods 2

BuildMemberReadinessPrompt(string, IReadOnlyList<string>, CouncilPreflightReport)

```
public string BuildMemberReadinessPrompt(string modelName, IReadOnlyList<string> participants, CouncilPreflightReport report)
```

PrepareAsync(MultiModelCouncilRequest, IReadOnlyList<string>, IReadOnlyDictionary<string, CouncilHardwareRoadPlan>, CancellationToken)

```
public Task<CouncilPreflightReport> PrepareAsync(MultiModelCouncilRequest request, IReadOnlyList<string> participants, IReadOnlyDictionary<string,
    CouncilHardwareRoadPlan> modelRoutes, CancellationToken cancellationTok = default)
```

Class CouncilSpoolerService

Namespace LocalGPT . Services . Council Assembly LocalGPT.dll

Process-lifetime Council spooler. Browser circuits can disconnect and later rejoin the same run. A bounded checkpoint file preserves recent run context across application restarts, while active model calls themselves intentionally remain process-owned and cannot be resurrected after a crash.

Inheritance object CouncilSpoolerService

Implements ICouncilSpoolerService IDisposable

```
public sealed class CouncilSpoolerService : ICouncilSpoolerService, IDisposable
```

✨ Constructors 1

CouncilSpoolerService(ILocalGptVocabularyService, ILogger<CouncilSpoolerService>)

```
public CouncilSpoolerService(ILocalGptVocabularyService vocabulary, ILogger<CouncilSpoolerService> logger)
```

⚙️ Methods 7

AddStep(Guid, MultiModelCouncilStep)

```
public void AddStep(Guid runId, MultiModelCouncilStep step)
```

Begin(MultiModelCouncilResult)

```
public void Begin(MultiModelCouncilResult result)
```

Complete(MultiModelCouncilResult, bool)

```
public void Complete(MultiModelCouncilResult result, bool failed = false)
```

Dispose()

```
public void Dispose()
```

GetSnapshot(Guid)

```
public CouncilSpoolerSnapshot? GetSnapshot(Guid runId)
```

GetSnapshots(bool, int)

```
public IReadOnlyList<CouncilSpoolerSnapshot> GetSnapshots(bool includeCompleted = true, int take = 30)
```

Update(Guid, int, string)

```
public void Update(Guid runId, int round, string phase)
```

⚡ Events 1

Changed

```
public event Action? Changed
```

Namespace LocalGPT.Services.Council

Namespaces

Classes

Performs the bounded, lossless database and runtime-directory audit required before every council run. Deterministic seed gaps are filled by database initialization; missing volatile facts are returned as explicit questions instead of being guessed.

Process-lifetime Council spooler. Browser circuits can disconnect and later rejoin the same run. A bounded checkpoint file preserves recent run context across application restarts, while active model calls themselves intentionally remain process-owned and cannot be resurrected after a crash.

Feeds the runtime directory once per application boot after lossless database initialization.

Owns the boot- and run-time DXFunction/organic-skill directory feed. The database copy is discovery metadata only; the DI handler and its declared interaction policy remain authoritative for execution.

Class RuntimeCapabilityDirectoryHostedService

Namespace LocalGPT . Services . Council Assembly LocalGPT.dll

Feeds the runtime directory once per application boot after lossless database initialization.

Inheritance object RuntimeCapabilityDirectoryHostedService

Implements IHostedService

```
public sealed class RuntimeCapabilityDirectoryHostedService : IHostedService
```

🌟 Constructors 1

RuntimeCapabilityDirectoryHostedService(IServiceScopeFactory, ILogger<RuntimeCapabilityDirectoryHostedService>)

Feeds the runtime directory once per application boot after lossless database initialization.

```
public RuntimeCapabilityDirectoryHostedService(IServiceScopeFactory scopeFactory, ILogger<RuntimeCapabilityDirectoryHostedService> logger)
```

⚙️ Methods 2

StartAsync(CancellationTokens)

```
public Task StartAsync(CancellationTokens cancellationTokens)
```

StopAsync(CancellationTokens)

```
public Task StopAsync(CancellationTokens cancellationTokens)
```

Class RuntimeCapabilityDirectoryService

Namespace LocalGPT . Services . Council Assembly LocalGPT.dll

Owns the boot- and run-time DXFunction/organic-skill directory feed. The database copy is discovery metadata only; the DI handler and its declared interaction policy remain authoritative for execution.

Inheritance object RuntimeCapabilityDirectoryService

Implements IRuntimeCapabilityDirectoryService

```
public sealed class RuntimeCapabilityDirectoryService : IRuntimeCapabilityDirectoryService
```

🌟 Constructors 1

RuntimeCapabilityDirectoryService(IDatabaseInitializationService, IDbContextFactory<LocalGptMemoryDbContext>, IDxAiFunctionRegistry, IDxAiFunctionCatalogService, IOrganicSkillRegistryService, ILocalGptRuntimePolicyDataService, ILogger<RuntimeCapabilityDirectoryService>)

Owns the boot- and run-time DXFunction/organic-skill directory feed. The database copy is discovery metadata only; the DI handler and its declared interaction policy remain authoritative for execution.

```
public RuntimeCapabilityDirectoryService(IDatabaseInitializationService databaseInitialization, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDxAiFunctionRegistry dxFunctions, IDxAiFunctionCatalogService functionCatalog, IOrganicSkillRegistryService organicSkills, ILocalGptRuntimePolicyDataService runtimePolicy, ILogger<RuntimeCapabilityDirectoryService> logger)
```

⚙️ Methods 1

SynchronizeAsync(CancellationTokens)

```
public Task<RuntimeCapabilityDirectorySnapshot> SynchronizeAsync(CancellationTokens cancellationTokens = default)
```

Class CouncilHardwareRoadConfigurationService

Namespace LocalGPT . Services . Council . Scheduling Assembly LocalGPT.dll

Inheritance object CouncilHardwareRoadConfigurationService

Implements ICouncilHardwareRoadConfigurationService

```
public sealed class CouncilHardwareRoadConfigurationService : ICouncilHardwareRoadConfigurationService
```

🌟 Constructors 1

CouncilHardwareRoadConfigurationService(ILogger<CouncilHardwareRoadConfigurationService>)

```
public CouncilHardwareRoadConfigurationService(ILogger<CouncilHardwareRoadConfigurationService> logger)
```

⚙️ Methods 4

Interpolate(int, int, int)

```
public int Interpolate(int minimum, int maximum, int loadPercent)
```

Normalize(OneWireCouncilModelRoute)

```
public OneWireCouncilModelRoute Normalize(OneWireCouncilModelRoute route)
```

NormalizeLoadPercent(int)

```
public int NormalizeLoadPercent(int value)
```

Synchronize(IEnumerable<string>, IEnumerable<OneWireCouncilModelRoute>?)

```
public IReadOnlyList<OneWireCouncilModelRoute> Synchronize(IEnumerable<string> modelNames, IEnumerable<OneWireCouncilModelRoute>? existingRoutes)
```

Class CouncilHardwareRoadPlanner

Namespace LocalGPT . Services . Council . Scheduling Assembly LocalGPT.dll

Inheritance object CouncilHardwareRoadPlanner

Implements ICouncilHardwareRoadPlanner

```
public sealed class CouncilHardwareRoadPlanner : ICouncilHardwareRoadPlanner
```

🌟 Constructors 1

CouncilHardwareRoadPlanner(ICouncilHardwareRoadConfigurationService, ILogger<CouncilHardwareRoadPlanner>)

```
public CouncilHardwareRoadPlanner(ICouncilHardwareRoadConfigurationService configuration, ILogger<CouncilHardwareRoadPlanner> logger)
```

⚙️ Methods 1

BuildPlans(IReadOnlyCollection<OneWireCouncilModelRoute>?, IReadOnlyCollection<string>, int, int, int, int?)

```
public IReadOnlyDictionary<string, CouncilHardwareRoadPlan> BuildPlans(IReadOnlyCollection<OneWireCouncilModelRoute>? configuredRoutes,
IReadOnlyCollection<string> participants, int requestedMaxOutputTokens, int requestedMaxContextTokens, int resourceLoadPercent, int? fallbackOllamaNumGpu)
```

Namespace LocalGPT.Services.Council.Scheduling

Classes

Namespace LocalGPT.Services.Council.Skills

Classes

Accepts optional model self-reports as untrusted evidence. Self-reported skills are persisted disabled for automatic authority decisions until the current user approves them in the organic-skill registry.

Class ModelCapabilitySelfAssessmentService

Namespace LocalGPT . Services . Council . Skills Assembly LocalGPT.dll

Accepts optional model self-reports as untrusted evidence. Self-reported skills are persisted disabled for automatic authority decisions until the current user approves them in the organic-skill registry.

Inheritance object ModelCapabilitySelfAssessmentService

Implements IModelCapabilitySelfAssessmentService

```
public sealed class ModelCapabilitySelfAssessmentService : IModelCapabilitySelfAssessmentService
```

🌟 Constructors 1

ModelCapabilitySelfAssessmentService(IOrganicSkillRegistryService, ILocalGptRuntimePolicyDataService, ILogger<ModelCapabilitySelfAssessmentService>)

Accepts optional model self-reports as untrusted evidence. Self-reported skills are persisted disabled for automatic authority decisions until the current user approves them in the organic-skill registry.

```
public ModelCapabilitySelfAssessmentService(
    IOrganicSkillRegistryService skillRegistry,
    ILocalGptRuntimePolicyDataService runtimePolicy,
    ILogger<ModelCapabilitySelfAssessmentService> logger)
```

⚙️ Methods 1

CaptureAndStripAsync(string, string, CancellationToken)

```
public Task<string> CaptureAndStripAsync(
    string modelName,
    string visibleContent,
    CancellationToken cancellationToken = default)
```

Class CouncilArtifactService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilArtifactService

Implements ICouncilArtifactService

```
public class CouncilArtifactService : ICouncilArtifactService
```

🌟 Constructors 1

CouncilArtifactService(ILogger<CouncilArtifactService>, IMinecraftModWorkspaceService, IArtifactBuildExecutor, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService)

```
public CouncilArtifactService(
    ILogger<CouncilArtifactService> logger,
    IMinecraftModWorkspaceService minecraftWorkspaceService,
    IArtifactBuildExecutor artifactBuildExecutor,
    CouncilRuntimeService councilRuntime,
    CouncilTextService councilText,
    LocalGptCatalogService catalog)
```

🔗 Properties 1

ArtifactRoot

```
public string ArtifactRoot { get; }
```

⚙️ Methods 5

CreateImplementationArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, CancellationToken)

```
public Task<IReadOnlyList<CouncilArtifact>> CreateImplementationArtifactsAsync(
    MultiModelCouncilRequest request,
    MultiModelCouncilResult result,
    CancellationToken cancellationToken = default)
```

CreateMinecraftDatapackArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
public Task<IReadOnlyList<CouncilArtifact>> CreateMinecraftDatapackArtifactsAsync(
    MultiModelCouncilRequest request,
    MultiModelCouncilResult result,
    string timestamp,
    CancellationToken cancellationToken)
```

CreateMinecraftSkeletonMatrixArtifactsAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
public Task<IReadOnlyList<CouncilArtifact>> CreateMinecraftSkeletonMatrixArtifactsAsync(
    MultiModelCouncilRequest request,
    MultiModelCouncilResult result,
    string timestamp,
    CancellationToken cancellationToken)
```

CreateSolutionZipArtifactAsync(MultiModelCouncilRequest, MultiModelCouncilResult, string, CancellationToken)

```
public Task<CouncilArtifact> CreateSolutionZipArtifactAsync(
    MultiModelCouncilRequest request,
    MultiModelCouncilResult result,
    string timestamp,
    CancellationToken cancellationToken)
```

TryCreateDllArtifactAsync(string, string, string, bool, CancellationToken)

```
public Task<CouncilArtifact?> TryCreateDllArtifactAsync(
    string sourceFileName,
    string source,
    string targetArea,
    bool userConfirmedArtifactBuild,
    CancellationToken cancellationToken)
```

Class CouncilChatClient

Namespace LocalGPT . Services Assembly LocalGPT.dll

Adapts the multi-model Council runtime to the Microsoft.Extensions.AI chat-client contract.

Inheritance object CouncilChatClient

Implements IChatClient IDisposable

```
[DocumentationUpdated("2.1.20")] public sealed class CouncilChatClient : IChatClient, IDisposable
```

🌟 Constructors 1

CouncilChatClient(IServiceScopeFactory, Func<MultiModelCouncilRequest>, ILogger, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService, ICouncilLiveSessionService, Func<string, string>?)

Adapts the multi-model Council runtime to the Microsoft.Extensions.AI chat-client contract.

```
public CouncilChatClient(IServiceScopeFactory serviceScopeFactory, Func<MultiModelCouncilRequest> requestFactory, ILogger logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog, ICouncilLiveSessionService liveSessions, Func<string, string>? downloadUrlResolver = null)
```

⚙️ Methods 6

Dispose()

Completes adapter disposal; owned services are managed by dependency injection.

```
public void Dispose()
```

FormatResult(MultiModelCouncilResult, bool)

Formats one Council result as canonical safe Markdown for DXAiChat.

```
public string FormatResult(MultiModelCouncilResult result, bool includeProcess)
```

GetResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

Runs one non-streaming Council request and returns its formatted assistant response.

```
public Task<ChatResponse> GetResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```

GetService(Type, object?)

Returns no additional keyed service from this adapter.

```
public object? GetService(Type serviceType, object? serviceKey = null)
```

GetStreamingResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

Starts or attaches to a live Council run and streams bounded response updates.

```
public IAsyncEnumerable<ChatResponseUpdate> GetStreamingResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```

ResolveDownloadUrl(string)

Resolves one generated artifact route against the current host when necessary.

```
public string ResolveDownloadUrl(string downloadUrl)
```

Class CouncilCodeGenerationPlanService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilCodeGenerationPlanService

Implements ICouncilCodeGenerationPlanService

```
public sealed class CouncilCodeGenerationPlanService : ICouncilCodeGenerationPlanService
```

🌟 Constructors 1

CouncilCodeGenerationPlanService(ILogger<CouncilCodeGenerationPlanService>)

```
public CouncilCodeGenerationPlanService(ILogger<CouncilCodeGenerationPlanService> logger)
```

⚙️ Methods 1

Parse(string)

```
public CouncilCodeGenerationPlanResult Parse(string councilAnswer)
```

Class CouncilDxFunctionOrchestrator

Namespace LocalGPT . Services Assembly LocalGPT.dll

Parses explicit Council DX function call blocks and sends allowed calls through the existing scoped function client. Catalog exposure and invocation metadata remain the source of truth. A failed function call becomes a readable Council step instead of aborting the whole run.

Inheritance object CouncilDxFunctionOrchestrator

Implements ICouncilDxFunctionOrchestrator

```
public sealed class CouncilDxFunctionOrchestrator : ICouncilDxFunctionOrchestrator
```

🌟 Constructors 1

CouncilDxFunctionOrchestrator(ILocalGptVocabularyService, ICouncilTextPatternDataService, ICouncilDxFunctionPolicyDataService, IDxAiFunctionCatalogService, IDxAiFunctionServiceClient, ILogger<CouncilDxFunctionOrchestrator>)

Parses explicit Council DX function call blocks and sends allowed calls through the existing scoped function client. Catalog exposure and invocation metadata remain the source of truth. A failed function call becomes a readable Council step instead of aborting the whole run.

```
public CouncilDxFunctionOrchestrator(ILocalGptVocabularyService vocabulary, ICouncilTextPatternDataService patterns, ICouncilDxFunctionPolicyDataService policies, IDxAiFunctionCatalogService catalog, IDxAiFunctionServiceClient functionClient, ILogger<CouncilDxFunctionOrchestrator> logger)
```

⚙️ Methods 1

ExecuteRequestedCallsAsync(MultiModelCouncilResult, MultiModelCouncilStep, CancellationToken)

```
public Task<IReadOnlyList<MultiModelCouncilStep>> ExecuteRequestedCallsAsync(MultiModelCouncilResult result, MultiModelCouncilStep sourceStep, CancellationToken cancellationToken = default)
```

Class CouncilGameActorRuntimeFactory

Namespace LocalGPT . Services Assembly LocalGPT.dll

Creates stable per-turn actor descriptors without granting them state-mutation authority.

Inheritance object CouncilGameActorRuntimeFactory

Implements ICouncilGameActorRuntimeFactory

```
public sealed class CouncilGameActorRuntimeFactory : ICouncilGameActorRuntimeFactory
```

🌟 Constructors 1

CouncilGameActorRuntimeFactory(ILogger<CouncilGameActorRuntimeFactory>)

Creates stable per-turn actor descriptors without granting them state-mutation authority.

```
public CouncilGameActorRuntimeFactory(ILogger<CouncilGameActorRuntimeFactory> logger)
```

⚙️ Methods 1

CreateActors(CouncilGameDirectorContext, CouncilGameActorKind)

Creates the actor instances owned by one subdirector for the current immutable turn snapshot.

```
public IReadOnlyList<CouncilGameActorRuntimeDescriptor> CreateActors(CouncilGameDirectorContext context, CouncilGameActorKind actorKind)
```


Class CouncilGameDirectorService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Provides deterministic final authority for game controls and coordinates replaceable creature/object subdirectors. A configured low-parameter Council model may review the proposal later, but cannot bypass this service.

Inheritance object CouncilGameDirectorService

Implements ICouncilGameDirectorService

```
public sealed class CouncilGameDirectorService : ICouncilGameDirectorService
```

🌟 Constructors 1

CouncilGameDirectorService(IEnumerable<ICouncilGameSubdirector>, ILogger<CouncilGameDirectorService>)

Provides deterministic final authority for game controls and coordinates replaceable creature/object subdirectors. A configured low-parameter Council model may review the proposal later, but cannot bypass this service.

```
public CouncilGameDirectorService(IEnumerable<ICouncilGameSubdirector> subdirectors, ILogger<CouncilGameDirectorService> logger)
```

⚙️ Methods 1

EvaluateAsync(CouncilGameDirectorContext, CancellationToken)

Validates one proposal and gathers bounded creature/object predictions without mutating session state.

```
public Task<CouncilGameDirectorDecision> EvaluateAsync(CouncilGameDirectorContext context, CancellationToken cancellationToken = default)
```

Class CouncilGameDxParameterReader

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilGameDxParameterReader

```
public sealed class CouncilGameDxParameterReader
```

🌟 Constructors 1

CouncilGameDxParameterReader(ILogger<CouncilGameDxParameterReader>)

```
public CouncilGameDxParameterReader(ILogger<CouncilGameDxParameterReader> logger)
```

⚙️ Methods 6

Boolean(JsonElement, string, bool)

```
public bool Boolean(JsonElement parameters, string name, bool fallback = false)
```

Guid(JsonElement, string)

```
public Guid Guid(JsonElement parameters, string name)
```

Integer(JsonElement, string, int)

```
public int Integer(JsonElement parameters, string name, int fallback)
```

Long(JsonElement, string, long)

```
public long Long(JsonElement parameters, string name, long fallback = 0)
```

NullableInt(JsonElement, string)

```
public int? NullableInt(JsonElement parameters, string name)
```

String(JsonElement, string, string)

```
public string String(JsonElement parameters, string name, string fallback = "")
```

Class CouncilGameSessionService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Provides one shared control surface for humans and AI players. The deterministic renderer keeps /Chat reactive; a single Council renderer may replace a turn's complete frame through SubmitFrameAsync.

Inheritance object CouncilGameSessionService

Implements ICouncilGameSessionService IDisposable

```
public sealed class CouncilGameSessionService : ICouncilGameSessionService, IDisposable
```

🌟 Constructors 1

CouncilGameSessionService(ICouncilGameDirectorService, ILogger<CouncilGameSessionService>)

Provides one shared control surface for humans and AI players. The deterministic renderer keeps /Chat reactive; a single Council renderer may replace a turn's complete frame through SubmitFrameAsync.

```
public CouncilGameSessionService(ICouncilGameDirectorService gameDirector, ILogger<CouncilGameSessionService> logger)
```

⚙️ Methods 10

ApplyControlAsync(CouncilGameControlRequest, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> ApplyControlAsync(CouncilGameControlRequest request, CancellationToken cancellationToken = default)
```

Dispose()

```
public void Dispose()
```

GetActiveAsync(Guid?, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> GetActiveAsync(Guid? conversationId, CancellationToken cancellationToken = default)
```

GetAsync(Guid, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> GetAsync(Guid sessionId, CancellationToken cancellationToken = default)
```

ListAsync(bool, CancellationToken)

```
public Task<IReadOnlyList<CouncilGameSessionSnapshot>> ListAsync(bool includeCompleted = false, CancellationToken cancellationToken = default)
```

PreviewControlAsync(CouncilGameControlRequest, CancellationToken)

```
public Task<CouncilGameDirectorDecision> PreviewControlAsync(CouncilGameControlRequest request, CancellationToken cancellationToken = default)
```

SetControlModeAsync(Guid, CouncilGameControlMode, bool, int, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> SetControlModeAsync(Guid sessionId, CouncilGameControlMode mode, bool autoplayEnabled, int autoplayDelayMilliseconds = 1200, CancellationToken cancellationToken = default)
```

SetInputGateAsync(SetCouncilGameInputGateRequest, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> SetInputGateAsync(SetCouncilGameInputGateRequest request, CancellationToken cancellationToken = default)
```

StartAsync(StartCouncilGameRequest, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> StartAsync(StartCouncilGameRequest request, CancellationToken cancellationToken = default)
```

SubmitFrameAsync(SubmitCouncilGameFrameRequest, CancellationToken)

```
public Task<CouncilGameSessionSnapshot> SubmitFrameAsync(SubmitCouncilGameFrameRequest request, CancellationToken cancellationToken = default)
```

⚡ Events 1

Changed

```
public event Action<Guid>? Changed
```

Class CouncilKnowledgeService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilKnowledgeService

Implements ICouncilKnowledgeService

```
public class CouncilKnowledgeService : ICouncilKnowledgeService
```

✨ Constructors 1

CouncilKnowledgeService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, IDatabaseFileHealthService, ILogger<CouncilKnowledgeService>, CouncilTextService, SqliteUtilityService)

```
public CouncilKnowledgeService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, IDatabaseFileHealthService databaseFileHealth, ILogger<CouncilKnowledgeService> logger, CouncilTextService councilText, SqliteUtilityService sqliteUtility)
```

🔗 Properties 1

DatabasePath

```
public string DatabasePath { get; }
```

⚙️ Methods 7

BuildKnowledgeBriefingAsync(int, CancellationToken)

```
public Task<string> BuildKnowledgeBriefingAsync(int take = 8, CancellationToken cancellationToken = default)
```

DeleteEntryAsync(Guid, CancellationToken)

```
public Task DeleteEntryAsync(Guid id, CancellationToken cancellationToken = default)
```

EnsureCreatedAsync(CancellationToken)

```
public Task EnsureCreatedAsync(CancellationToken cancellationToken = default)
```

GetEntriesAsync(bool, int, CancellationToken)

```
public Task<IReadOnlyList<CouncilKnowledgeEntry>> GetEntriesAsync(bool includeArchived = false, int take = 100, CancellationToken cancellationToken = default)
```

MarkEntriesUsedAsync(IEnumerable<Guid>, CancellationToken, ILogger)

```
public Task MarkEntriesUsedAsync(IEnumerable<Guid> entryIds, CancellationToken cancellationToken, ILogger logger)
```

SaveEntryAsync(CouncilKnowledgeEntry, CancellationToken)

```
public Task<CouncilKnowledgeEntry> SaveEntryAsync(CouncilKnowledgeEntry entry, CancellationToken cancellationToken = default)
```

SaveFromCouncilRunAsync(MultiModelCouncilResult, CancellationToken)

```
public Task<Guid> SaveFromCouncilRunAsync(MultiModelCouncilResult result, CancellationToken cancellationToken = default)
```

Class CouncilLiveSessionService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilLiveSessionService

Implements ICouncilLiveSessionService

```
public sealed class CouncilLiveSessionService : ICouncilLiveSessionService
```

✨ Constructors 1

CouncilLiveSessionService(ILogger<CouncilLiveSessionService>)

```
public CouncilLiveSessionService(ILogger<CouncilLiveSessionService> logger)
```

⚙️ Methods 9

Append(Guid, string)

```
public void Append(Guid runId, string text)
```

AppendUserMessage(Guid, string)

```
public void AppendUserMessage(Guid runId, string text)
```

Begin(Guid, IReadOnlyList<string>, string, string)

```
public CancellationToken Begin(Guid runId, IReadOnlyList<string> councilMembers, string userMessage, string initialTranscript)
```

Cancel(Guid)

```
public bool Cancel(Guid runId)
```

Complete(Guid)

```
public void Complete(Guid runId)
```

Get(Guid)

```
public CouncilLiveSessionSnapshot? Get(Guid runId)
```

GetActive()

```
public IReadOnlyList<CouncilLiveSessionSnapshot> GetActive()
```

GetActiveSummaries()

```
public IReadOnlyList<CouncilLiveSessionSummary> GetActiveSummaries()
```

GetSummary(Guid)

```
public CouncilLiveSessionSummary? GetSummary(Guid runId)
```

⚡ Events 1

Changed

```
public event Action<Guid>? Changed
```

Class CouncilRunConfigurationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilRunConfigurationService

Implements ICouncilRunConfigurationService

```
public sealed class CouncilRunConfigurationService : ICouncilRunConfigurationService
```

🌟 Constructors 1

CouncilRunConfigurationService(ICouncilHardwareRoadPlanner, ILogger<CouncilRunConfigurationService>)

```
public CouncilRunConfigurationService(ICouncilHardwareRoadPlanner hardwareRoadPlanner, ILogger<CouncilRunConfigurationService> logger)
```

⚙️ Methods 11

AcquireModelRequestAsync(Guid, string, CouncilHardwareRoadPlan, CancellationToken)

```
public ValueTask<ICouncilModelRequestLease> AcquireModelRequestAsync(Guid runId, string modelName, CouncilHardwareRoadPlan fallbackPlan, CancellationToken cancellationToken = default)
```

BeginRound(Guid, int, string)

```
public void BeginRound(Guid runId, int round, string phase)
```

Complete(Guid)

```
public void Complete(Guid runId)
```

Ensure(MultiModelCouncilRequest, IReadOnlyCollection<string>)

```
public CouncilRunConfigurationSnapshot Ensure(MultiModelCouncilRequest request, IReadOnlyCollection<string> participants)
```

Get(Guid)

```
public CouncilRunConfigurationSnapshot? Get(Guid runId)
```

GetPreparation()

```
public CouncilPreparationConfiguration? GetPreparation()
```

GetRoundCancellationToken(Guid, int, string)

```
public CancellationToken GetRoundCancellationToken(Guid runId, int round, string phase)
```

IsRoundSkipRequested(Guid, int, string)

```
public bool IsRoundSkipRequested(Guid runId, int round, string phase)
```

RequestSkipCurrentRound(Guid)

```
public bool RequestSkipCurrentRound(Guid runId)
```

SavePreparation(CouncilPreparationConfiguration)

```
public CouncilPreparationConfiguration SavePreparation(CouncilPreparationConfiguration configuration)
```

Update(Guid, IReadOnlyCollection<OneWireCouncilModelRoute>, int, int, int, int?, bool)

```
public bool Update(Guid runId, IReadOnlyCollection<OneWireCouncilModelRoute> routes, int resourceLoadPercent, int requestedMaxOutputTokens, int requestedMaxContextTokens, int? fallbackOllamaNumGpu, bool allowParallelHardwareRoads)
```

⚡ Events 1

Changed

```
public event Action<Guid>? Changed
```

Class CouncilRuntimeClassService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilRuntimeClassService

Implements ICouncilRuntimeClassService

```
public sealed class CouncilRuntimeClassService : ICouncilRuntimeClassService
```

🌟 Constructors 1

CouncilRuntimeClassService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<CouncilRuntimeClassService>)

```
public CouncilRuntimeClassService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<CouncilRuntimeClassService> logger)
```

⚙️ Methods 3

FindAsync(string?, CancellationToken)

```
public Task<CouncilRuntimeClassDefinition?> FindAsync(string? key, CancellationToken cancellationToken = default)
```

GetDefinitionsAsync(bool, CancellationToken)

```
public Task<IReadOnlyList<CouncilRuntimeClassDefinition>> GetDefinitionsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveAsync(SaveCouncilRuntimeClassRequest, CancellationToken)

```
public Task<CouncilRuntimeClassDefinition> SaveAsync(SaveCouncilRuntimeClassRequest request, CancellationToken cancellationToken = default)
```

Class CouncilRuntimeService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Owns deterministic Council prompt reconstruction, source/artifact generation helpers and shared runtime formatting operations.

Inheritance object CouncilRuntimeService

```
[DocumentationUpdated("2.1.20")] public sealed class CouncilRuntimeService
```

🌟 Constructors 1

CouncilRuntimeService(CouncilTextService, LocalGptCatalogService, ILogger<CouncilRuntimeService>)

Owns deterministic Council prompt reconstruction, source/artifact generation helpers and shared runtime formatting operations.

```
public CouncilRuntimeService(CouncilTextService text, LocalGptCatalogService catalog, ILogger<CouncilRuntimeService> serviceLogger)
```

⚙️ Methods 136

AddDirectoryToZip(ZipArchive, string, string, ILogger)

Executes the add directory to zip operation.

```
public void AddDirectoryToZip(ZipArchive archive, string rootPath, string directoryPath, ILogger logger)
```

AddFileToZip(ZipArchive, string, string, ILogger)

Executes the add file to zip operation.

```
public void AddFileToZip(ZipArchive archive, string filePath, string entryName, ILogger logger)
```

AddIf(string, List<string>, string, ILogger, params string[])

Executes the add if operation.

```
public void AddIf(string text, List<string> signals, string label, ILogger logger, params string[] needles)
```

AnalyzeBytes(string, byte[], ILogger)

Executes the analyze bytes operation.

```
public AnalyzedUploadFile? AnalyzeBytes(string relativePath, byte[] bytes, ILogger logger)
```

AppendDevExpressImportsAsync(StringBuilder, string, CancellationToken, ILogger)

Executes the append dev express imports async operation.

```
public Task AppendDevExpressImportsAsync(StringBuilder builder, string root, CancellationToken cancellationToken, ILogger logger)
```

AppendDevExpressRegistrationsAsync(StringBuilder, string, CancellationToken, ILogger)

Executes the append dev express registrations async operation.

```
public Task AppendDevExpressRegistrationsAsync(StringBuilder builder, string root, CancellationToken cancellationToken, ILogger logger)
```

AppendLoadedDevExpressAssemblies(StringBuilder, ILogger)

Executes the append loaded dev express assemblies operation.

```
public void AppendLoadedDevExpressAssemblies(StringBuilder builder, ILogger logger)
```

ArchetypePage(string, string, string, string, IReadOnlyList<string>, ILogger)

Executes the archetype page operation.

```
public GeneratedArchetypePage ArchetypePage(string fileName, string route, string title, string summary, IReadOnlyList<string> areas, ILogger logger)
```

BuildArtifactWorkspaceSummary(string, string, ILogger)

Executes the build artifact workspace summary operation.

```
public ArtifactWorkspaceSummary? BuildArtifactWorkspaceSummary(string artifactRoot, string workspacePath, ILogger logger)
```

BuildBinarySummary(string, long, string, bool, string, ILogger)

Executes the build binary summary operation.

```
public AnalyzedUploadFile? BuildBinarySummary(string relativePath, long length, string kind, bool includedInPrompt, string note, ILogger logger)
```

BuildCandidateLabel(MultiModelCouncilModelCandidate, ILogger)

Executes the build candidate label operation.

```
public string BuildCandidateLabel(MultiModelCouncilModelCandidate candidate, ILogger logger)
```

BuildCandidateTitle(MultiModelCouncilModelCandidate, ILogger)

Executes the build candidate title operation.

```
public string BuildCandidateTitle(MultiModelCouncilModelCandidate candidate, ILogger logger)
```

BuildContextMarkdown(string, string, string, IReadOnlyList<AnalyzedUploadFile>, IReadOnlyList<string>, ILogger)

Executes the build context markdown operation.

```
public string BuildContextMarkdown(string workspaceName, string root, string prompt, IReadOnlyList<AnalyzedUploadFile> analyzedFiles,
IReadOnlyList<string> warnings, ILogger logger)
```

BuildDatapackReferenceComparison(string, ILogger)

Executes the build datapack reference comparison operation.

```
public DatapackReferenceComparison? BuildDatapackReferenceComparison(string workspaceRoot, ILogger logger)
```

BuildDocsPathSamples(string, IReadOnlyList<FileInfo>, ILogger, params string[])

Executes the build docs path samples operation.

```
public string BuildDocsPathSamples(string rootPath, IReadOnlyList<FileInfo> markdownFiles, ILogger logger, params string[] needles)
```

BuildDocumentationCorpusCandidates(string, ILogger)

Executes the build documentation corpus candidates operation.

```
public IEnumerable<string> BuildDocumentationCorpusCandidates(string rootPath, ILogger logger)
```

BuildDotNetDocsEntries(string, IReadOnlyList<FileInfo>, ILogger)

Executes the build dot net docs entries operation.

```
public IReadOnlyList<CouncilKnowledgeEntry> BuildDotNetDocsEntries(string rootPath, IReadOnlyList<FileInfo> markdownFiles, ILogger logger)
```

BuildDynamicSessionName(MultiModelCouncilModelCandidate, ILogger)

Executes the build dynamic session name operation.

```
public string BuildDynamicSessionName(MultiModelCouncilModelCandidate candidate, ILogger logger)
```

BuildImportantFileList(string, string, IReadOnlyList<FileInfo>, ILogger)

Executes the build important file list operation.

```
public string BuildImportantFileList(string rootPath, string projectDirectory, IReadOnlyList<FileInfo> sourceFiles, ILogger logger)
```

BuildKnowledgeReviewSummary(IReadOnlyCollection<CouncilKnowledgeEntry>, ILogger)

Executes the build knowledge review summary operation.

```
public string BuildKnowledgeReviewSummary(IReadOnlyCollection<CouncilKnowledgeEntry> entries, ILogger logger)
```

BuildManualExpectedLane(BenchmarkTaskDefinition, ILogger)

Executes the build manual expected lane operation.

```
public EngineeringBenchmarkLaneResult BuildManualExpectedLane(BenchmarkTaskDefinition task, ILogger logger)
```

BuildProjectSummary(string, string, ILogger)

Executes the build project summary operation.

```
public LearnBaseProjectSummary? BuildProjectSummary(string rootPath, string projectDirectory, ILogger logger)
```

BuildProjectSummary(string, string, IReadOnlyList<FileInfo>, ILogger)

Executes the build project summary operation.

```
public LearnBaseProjectSummary? BuildProjectSummary(string rootPath, string projectDirectory, IReadOnlyList<FileInfo> selectedFiles, ILogger logger)
```

BuildPrompt(IEnumerable<ChatMessage>, ILogger)

Reconstructs a bounded DXAiChat prompt without recursively feeding complete prior Council transcripts back into later runs.

```
public string BuildPrompt(IEnumerable<ChatMessage> messages, ILogger logger)
```

BuildSummary(string, long, string, bool, string, string, ILogger)

Executes the build summary operation.

```
public AnalyzedUploadFile? BuildSummary(string relativePath, long length, string kind, bool includedInPrompt, string note, string excerpt, ILogger logger)
```

BuildTags(LearnBaseProjectSummary, ILogger)

Executes the build tags operation.

```
public string BuildTags(LearnBaseProjectSummary summary, ILogger logger)
```

BuildTasks(string, ILogger)

Executes the build tasks operation.

```
public IReadOnlyList<BenchmarkTaskDefinition> BuildTasks(string taskSet, ILogger logger)
```

BuildWindowsDevDocsEntries(string, IReadOnlyList<FileInfo>, ILogger)

Executes the build windows dev docs entries operation.


```
public IReadOnlyList<CouncilKnowledgeEntry> BuildWindowsDevDocsEntries(string rootPath, IReadOnlyList<FileInfo> markdownFiles, ILogger logger)
```

BuildWindowsDocsPathSamples(string, IReadOnlyList<FileInfo>, ILogger, params string[])

Executes the build windows docs path samples operation.

```
public string BuildWindowsDocsPathSamples(string rootPath, IReadOnlyList<FileInfo> markdownFiles, ILogger logger, params string[] needles)
```

BuildWorkspaceName(string, IReadOnlyList<ChatUploadWorkspaceInputFile>, ILogger)

Executes the build workspace name operation.

```
public string BuildWorkspaceName(string prompt, IReadOnlyList<ChatUploadWorkspaceInputFile> files, ILogger logger)
```

ComputeCorpusHash(string, IReadOnlyList<FileInfo>, ILogger)

Executes the compute corpus hash operation.

```
public string ComputeCorpusHash(string rootPath, IReadOnlyList<FileInfo> files, ILogger logger)
```

ComputeSummaryHash(LearnBaseProjectSummary, ILogger)

Executes the compute summary hash operation.

```
public string ComputeSummaryHash(LearnBaseProjectSummary summary, ILogger logger)
```

CopyDebugFileAsync(FileInfo, string, string, CancellationToken, ILogger<BuildDebugInventoryService>)

Executes the copy debug file async operation.

```
public Task<string> CopyDebugFileAsync(FileInfo file, string sourceArea, string captureRoot, CancellationToken cancellationToken, ILogger<BuildDebugInventoryService> logger)
```

CopyDirectory(string, string, ILogger)

Executes the copy directory operation.

```
public void CopyDirectory(string sourceDirectory, string destinationDirectory, ILogger logger)
```

CopyKnowledgeEntry(CouncilKnowledgeEntry, ILogger)

Executes the copy knowledge entry operation.

```
public CouncilKnowledgeEntry? CopyKnowledgeEntry(CouncilKnowledgeEntry entry, ILogger logger)
```

CreateBuildLocalScript(MinecraftModBuildRequest, ILogger)

Executes the create build local script operation.

```
public string CreateBuildLocalScript(MinecraftModBuildRequest request, ILogger logger)
```

CreateChatUploadSmokeZip(ILogger)

Executes the create chat upload smoke zip operation.

```
public byte[] CreateChatUploadSmokeZip(ILogger logger)
```

CreateCommonGradleProperties(MinecraftModBuildRequest, WorkspaceContext, ILogger)

Executes the create common gradle properties operation.

```
public string CreateCommonGradleProperties(MinecraftModBuildRequest request, WorkspaceContext context, ILogger logger)
```

CreateDatapackMcmeta(MinecraftModBuildRequest, WorkspaceContext, ILogger)

Executes the create datapack mcmeta operation.

```
public string CreateDatapackMcmeta(MinecraftModBuildRequest request, WorkspaceContext context, ILogger logger)
```

CreatePaperGradleProperties(MinecraftModBuildRequest, WorkspaceContext, ILogger)

Creates Gradle properties for a Paper server plugin workspace.

```
public string CreatePaperGradleProperties(MinecraftModBuildRequest request, WorkspaceContext context, ILogger logger)
```

CreateStableGuid(string, ILogger)

Executes the create stable guid operation.

```
public Guid CreateStableGuid(string value, ILogger logger)
```

CreateUpdate(string, ILogger)

Executes the create update operation.

```
public ChatResponseUpdate CreateUpdate(string text, ILogger logger)
```

DatapackReferenceComparisonMissing(string, string, string, ILogger)

Executes the datapack reference comparison missing operation.

```
public DatapackReferenceComparison? DatapackReferenceComparisonMissing(string generatedZipPath, string referenceZipPath, string summary, ILogger logger)
```

DetectSolutionArchetype(string, string, ILogger)

Executes the detect solution archetype operation.

```
public GeneratedSolutionArchetype? DetectSolutionArchetype(string prompt, string finalAnswer, ILogger logger)
```

DetermineFileKind(string, ILogger)

Executes the determine file kind operation.

```
public string DetermineFileKind(string path, ILogger logger)
```

EnumerateArtifactWorkspaces(string, int, ILogger)

Executes the enumerate artifact workspaces operation.

```
public IReadOnlyList<ArtifactWorkspaceSummary> EnumerateArtifactWorkspaces(string artifactRoot, int take, ILogger logger)
```

EnumerateDocumentationCorpusCandidates(string, ILogger)

Executes the enumerate documentation corpus candidates operation.

```
public IEnumerable<string> EnumerateDocumentationCorpusCandidates(string rootPath, ILogger logger)
```

EnumerateNestedArchitectureRoots(string, ILogger)

Executes the enumerate nested architecture roots operation.

```
public IEnumerable<string> EnumerateNestedArchitectureRoots(string rootPath, ILogger logger)
```

EnumerateUsefulFiles(string, ILogger)

Executes the enumerate useful files operation.

```
public IEnumerable<FileInfo> EnumerateUsefulFiles(string directory, ILogger logger)
```

EnumerateWorkspaceTextFiles(string, int, ILogger)

Executes the enumerate workspace text files operation.

```
public List<ArtifactWorkspaceFileSummary> EnumerateWorkspaceTextFiles(string workspaceRoot, int take, ILogger logger)
```

EstimateTextLength(ChatMessage)

Executes the estimate text length operation.

```
public int EstimateTextLength(ChatMessage message)
```

ExtractDynamicPromiseModules(MultiModelCouncilRequest, MultiModelCouncilResult, ILogger)

Executes the extract dynamic promise modules operation.

```
public IReadOnlyList<GeneratedPromiseModule> ExtractDynamicPromiseModules(MultiModelCouncilRequest request, MultiModelCouncilResult result, ILogger logger)
```

FindRepositoryRoot(ILogger)

Executes the find repository root operation.

```
public string? FindRepositoryRoot(ILogger logger)
```

FirstText(ILogger<AiConnectivityProbe>, params string?[])

Executes the first text operation.

```
public string FirstText(ILogger<AiConnectivityProbe> logger, params string?[] values)
```

FormatStepProgress(MultiModelCouncilStep, ILogger)

Executes the format step progress operation.

```
public string FormatStepProgress(MultiModelCouncilStep step, ILogger logger)
```

GenerateArchetypePages(GeneratedSolutionArchetype, ILogger)

Executes the generate archetype pages operation.

```
public IReadOnlyList<GeneratedArchetypePage> GenerateArchetypePages(GeneratedSolutionArchetype archetype, ILogger logger)
```

GetConfiguredOllamaProviders(AICoreOptions, ILogger<ChatClientFactory>)

Executes the get configured ollama providers operation.

```
public IEnumerable<OllamaCoreOptions> GetConfiguredOllamaProviders(AICoreOptions options, ILogger<ChatClientFactory> logger)
```

GetCouncilModelLoadPriorityRandomisator(int, string, ILogger)

Executes the get council model load priority randomisator operation.

```
public int? GetCouncilModelLoadPriorityRandomisator(int maxPriority, string modelName, ILogger logger)
```

GetRequestBaseUrl(HttpContext, ILogger)

Executes the get request base url operation.

```
public string GetRequestBaseUrl(HttpContext httpContext, ILogger logger)
```

GetSearchRoots(ILogger<BuildDebugInventoryService>)

```
public IEnumerable<(string Area, string Path)> GetSearchRoots(ILogger<BuildDebugInventoryService> logger)
```

HasRealApiKey(string?, ILogger<ChatClientFactory>)

Executes the has real api key operation.

```
public bool HasRealApiKey(string? apiKey, ILogger<ChatClientFactory> logger)
```

InferArchitecture(string, IReadOnlyList<FileInfo>, string, ILogger)

Executes the infer architecture operation.

```
public string InferArchitecture(string projectDirectory, IReadOnlyList<FileInfo> files, string combined, ILogger logger)
```

InferProtocolsAndComponents(string, IReadOnlyList<FileInfo>, ILogger)

Executes the infer protocols and components operation.

```
public string InferProtocolsAndComponents(string combined, IReadOnlyList<FileInfo> files, ILogger logger)
```

IsAdviceOnlyPrompt(string, ILogger)

Executes the is advice only prompt operation.

```
public bool? IsAdviceOnlyPrompt(string prompt, ILogger logger)
```

IsAiHostExperimentTarget(string, string, ILogger)

Executes the is ai host experiment target operation.

```
public bool? IsAiHostExperimentTarget(string prompt, string finalAnswer, ILogger logger)
```

IsBlazorFrontendTarget(string, string, string, ILogger)

Executes the is blazor frontend target operation.

```
public bool? IsBlazorFrontendTarget(string prompt, string finalAnswer, string targetArea, ILogger logger)
```

IsDynamicSession(ChatClientSession, ILogger)

Executes the is dynamic session operation.

```
public bool? IsDynamicSession(ChatClientSession session, ILogger logger)
```

IsInsideRoot(string, string, ILogger)

Executes the is inside root operation.

```
public bool IsInsideRoot(string root, string path, ILogger logger)
```

IsMcFunctionPath(string, ILogger)

Executes the is mc function path operation.

```
public bool IsMcFunctionPath(string entry, ILogger logger)
```

IsSupportedArtifactTextFile(string, ILogger)

Executes the is supported artifact text file operation.

```
public bool IsSupportedArtifactTextFile(string path, ILogger logger)
```

IsTextLike(string, ILogger)

Executes the is text like operation.

```
public bool IsTextLike(string path, ILogger logger)
```

IsWholeSolutionTarget(string, string, ILogger)

Executes the is whole solution target operation.

```
public bool? IsWholeSolutionTarget(string prompt, string finalAnswer, ILogger logger)
```

IsZip(string, ILogger)

Executes the is zip operation.

```
public bool IsZip(string path, ILogger logger)
```

KnowledgeReviewPriority(CouncilKnowledgeEntry, ILogger)

Executes the knowledge review priority operation.

```
public int? KnowledgeReviewPriority(CouncilKnowledgeEntry entry, ILogger logger)
```

KnownDependencyVersionInfoVersions(ILogger)

Executes the known dependency version info versions operation.

```
public List<CatalogEntry> KnownDependencyVersionInfoVersions(ILogger logger)
```

LimitPromptSize(ICollection<ChatMessage>, ILogger, int?)

Executes the limit prompt size operation.

```
public ICollection<ChatMessage> LimitPromptSize(ICollection<ChatMessage> messages, ILogger logger, int? forcedMaxPromptCharacters = null)
```

LooksLikeArchitectureRoot(string, ILogger)

Executes the looks like architecture root operation.

```
public bool LooksLikeArchitectureRoot(string rootPath, ILogger logger)
```

LooksLikeDotNetDocsRoot(string, ILogger)

Executes the looks like dot net docs root operation.

```
public bool LooksLikeDotNetDocsRoot(string rootPath, ILogger logger)
```

LooksLikeText(byte[], ILogger)

Executes the looks like text operation.

```
public bool LooksLikeText(byte[] bytes, ILogger logger)
```

LooksLikeWindowsDevDocsRoot(string, ILogger)

Executes the looks like windows dev docs root operation.

```
public bool LooksLikeWindowsDevDocsRoot(string rootPath, ILogger logger)
```

MinecraftDatapackVersionInfoKnown(string, string, string, string, ILogger)

Executes the minecraft datapack version info known operation.

```
public MinecraftDatapackVersionInfo MinecraftDatapackVersionInfoKnown(string version, string packFormat, string functionRegistryFolder, string notes, ILogger logger)
```

MinecraftDatapackVersionInfoResolve(string?, ILogger)

Executes the minecraft datapack version info resolve operation.

```
public MinecraftDatapackVersionInfo MinecraftDatapackVersionInfoResolve(string? minecraftVersion, ILogger logger)
```

MinecraftDatapackVersionKnownVersions(ILogger)

Executes the minecraft datapack version known versions operation.

```
public List<MinecraftDatapackVersionInfo> MinecraftDatapackVersionKnownVersions(ILogger logger)
```

MultiModelCouncilServiceBuildAiHostSetupPoll(MultiModelCouncilResult, ICollection<string>, ILogger)

Executes the multi model council service build ai host setup poll operation.

```
public CouncilUserPoll? MultiModelCouncilServiceBuildAiHostSetupPoll(MultiModelCouncilResult result, ICollection<string> failedModels, ILogger logger)
```

MultiModelCouncilServiceBuildFrustrationPoll(MultiModelCouncilResult, ICollection<string>, ILogger)

Executes the multi model council service build frustration poll operation.

```
public CouncilUserPoll? MultiModelCouncilServiceBuildFrustrationPoll(MultiModelCouncilResult result, ICollection<string> failedModels, ILogger logger)
```

MultiModelCouncilServiceBuildImplementationPathPoll(MultiModelCouncilResult, ICollection<string>, ILogger)

Executes the multi model council service build implementation path poll operation.

```
public CouncilUserPoll? MultiModelCouncilServiceBuildImplementationPathPoll(MultiModelCouncilResult result, ICollection<string> failedModels, ILogger logger)
```

MultiModelCouncilServiceBuildLogMarkdown(MultiModelCouncilResult, ILogger)

Executes the multi model council service build log markdown operation.

```
public string MultiModelCouncilServiceBuildLogMarkdown(MultiModelCouncilResult result, ILogger logger)
```

MultiModelCouncilServiceBuildUserPoll(MultiModelCouncilResult, ILogger)

Executes the multi model council service build user poll operation.

```
public CouncilUserPoll? MultiModelCouncilServiceBuildUserPoll(MultiModelCouncilResult result, ILogger logger)
```

MultiModelCouncilServiceCountImplementationAreaHits(string, ILogger)

Executes the multi model council service count implementation area hits operation.

```
public int MultiModelCouncilServiceCountImplementationAreaHits(string text, ILogger logger)
```

MultiModelCouncilServiceHasExplicitArtifactIntent(string, ILogger)

Executes the multi model council service has explicit artifact intent operation.

```
public bool MultiModelCouncilServiceHasExplicitArtifactIntent(string prompt, ILogger logger)
```

MultiModelCouncilServiceIsDevelopmentRequest(string, ILogger)

Executes the multi model council service is development request operation.

```
public bool MultiModelCouncilServiceIsDevelopmentRequest(string prompt, ILogger logger)
```

MultiModelCouncilServiceIsFrustratedPrompt(string, ILogger)

Executes the multi model council service is frustrated prompt operation.

```
public bool MultiModelCouncilServiceIsFrustratedPrompt(string prompt, ILogger logger)
```

MultiModelCouncilServiceNeedsAiHostSetupDecision(MultiModelCouncilResult, ILogger)

Executes the multi model council service needs ai host setup decision operation.

```
public bool MultiModelCouncilServiceNeedsAiHostSetupDecision(MultiModelCouncilResult result, ILogger logger)
```

MultiModelCouncilServiceNeedsImplementationPathDecision(MultiModelCouncilResult, ILogger)

Executes the multi model council service needs implementation path decision operation.

```
public bool MultiModelCouncilServiceNeedsImplementationPathDecision(MultiModelCouncilResult result, ILogger logger)
```

MultiModelCouncilServiceRequiresUserDecisionBeforeArtifacts(MultiModelCouncilResult, ILogger)

Executes the multi model council service requires user decision before artifacts operation.

```
public bool MultiModelCouncilServiceRequiresUserDecisionBeforeArtifacts(MultiModelCouncilResult result, ILogger logger)
```

MultiModelCouncilServiceShouldGenerateSafeSandboxArtifactWithoutBlocking(string, ILogger)

Executes the multi model council service should generate safe sandbox artifact without blocking operation.

```
public bool MultiModelCouncilServiceShouldGenerateSafeSandboxArtifactWithoutBlocking(string prompt, ILogger logger)
```

MultiModelCouncilServiceUserGrantedSafeSandboxChoice(string, ILogger)

Executes the multi model council service user granted safe sandbox choice operation.

```
public bool MultiModelCouncilServiceUserGrantedSafeSandboxChoice(string prompt, ILogger logger)
```

NormalizeReferenceDatapackEntry(string, ILogger)

Executes the normalize reference datapack entry operation.

```
public string NormalizeReferenceDatapackEntry(string entry, ILogger logger)
```

NotRunLane(string, string, ILogger)

Executes the not run lane operation.

```
public EngineeringBenchmarkLaneResult NotRunLane(string laneName, string notes, ILogger logger)
```

OllamaThinkingChatClientCreateStreamingStatusUpdate(string, ILogger)

Executes the ollama thinking chat client create streaming status update operation.

```
public ChatResponseUpdate? OllamaThinkingChatClientCreateStreamingStatusUpdate(string text, ILogger logger)
```

OllamaThinkingChatClientCreateStreamingUpdate(string, ILogger)

Executes the ollama thinking chat client create streaming update operation.

```
public ChatResponseUpdate? OllamaThinkingChatClientCreateStreamingUpdate(string text, ILogger logger)
```

OllamaThinkingChatClientEnsureSuccessOrThrowAsync(HttpResponseMessage, CancellationToken, ILogger)

Executes the ollama thinking chat client ensure success or throw async operation.

```
public Task OllamaThinkingChatClientEnsureSuccessOrThrowAsync(HttpResponseMessage response, CancellationToken cancellationToken, ILogger logger)
```

OllamaThinkingChatClientReadErrorBodyAsync(HttpResponseMessage, CancellationToken, ILogger)

Executes the ollama thinking chat client read error body async operation.

```
public Task<string> OllamaThinkingChatClientReadErrorBodyAsync(HttpResponseMessage response, CancellationToken cancellationToken, ILogger logger)
```

OrderCouncilModelsForLoad(IEnumerable<string>, ILogger)

Executes the order council models for load operation.

```
public IEnumerable<string>? OrderCouncilModelsForLoad(IEnumerable<string> modelNames, ILogger logger)
```

ReadGuidanceDocsAsync(IWebHostEnvironment, IReadOnlyList<string>, string, CancellationToken, ILogger)

Executes the read guidance docs async operation.

```
public Task<IResult> ReadGuidanceDocsAsync(IWebHostEnvironment env, IReadOnlyList<string> relativePaths, string fallbackBriefing, CancellationToken cancellationToken, ILogger logger)
```

ReadRuntimeServerBaseUrl(ILogger)

Executes the read runtime server base url operation.

```
public String ReadRuntimeServerBaseUrl(ILogger logger)
```

ReadSmallText(FileInfo, ILogger)

Executes the read small text operation.

```
public String ReadSmallText(FileInfo file, ILogger logger)
```

ReadZipEntriesSafe(CouncilArtifact, ILogger)

Executes the read zip entries safe operation.

```
public IReadOnlyList<string> ReadZipEntriesSafe(CouncilArtifact artifact, ILogger logger)
```

ReadZipFileEntries(string, ILogger)

Executes the read zip file entries operation.

```
public string[] ReadZipFileEntries(string zipPath, ILogger logger)
```

RequireJsonProperty(JsonElement, string, string, ILogger)

Executes the require json property operation.

```
public void RequireJsonProperty(JsonElement root, string propertyName, string path, ILogger logger)
```

RequireNonEmptyJsonArray(JsonElement, string, string, ILogger)

Executes the require non empty json array operation.

```
public void RequireNonEmptyJsonArray(JsonElement root, string propertyName, string path, ILogger logger)
```

ResolveArtifactWorkspace(string, string, ILogger)

Executes the resolve artifact workspace operation.

```
public string? ResolveArtifactWorkspace(string artifactRoot, string workspaceName, ILogger logger)
```

ResolveDependencyVersions(MinecraftModBuildRequest, ILogger, string?)

Executes the resolve dependency versions operation.

```
public MinecraftDependencyVersionInfo ResolveDependencyVersions(MinecraftModBuildRequest request, ILogger logger, string? loaderOverride = null)
```

ResolveMinecraftDependencyVersionInfo(string?, string?, ILogger, string?, string?)

Executes the resolve minecraft dependency version info operation.

```
public MinecraftDependencyVersionInfo ResolveMinecraftDependencyVersionInfo(string? loader, string? minecraftVersion, ILogger logger, string? javaVersion = null, string? gradleVersion = null)
```

ResolveWorkspaceFile(string, string, ILogger)

Executes the resolve workspace file operation.

```
public string? ResolveWorkspaceFile(string workspace, string relativePath, ILogger logger)
```

ResolveWorkspaceTextFile(string, string, bool, ILogger)

Executes the resolve workspace text file operation.

```
public string? ResolveWorkspaceTextFile(string workspaceRoot, string relativePath, bool allowMissing, ILogger logger)
```

SafeEnumerateDirectories(string, ILogger)

Executes the safe enumerate directories operation.

```
public IEnumerable<string> SafeEnumerateDirectories(string rootPath, ILogger logger)
```

SafeEnumerateDirectoryInfos(string, ILogger)

Executes the safe enumerate directory infos operation.

```
public IEnumerable<DirectoryInfo> SafeEnumerateDirectoryInfos(string rootPath, ILogger logger)
```

SanitizeForPrompt(string, ILogger)

Executes the sanitize for prompt operation.

```
public string SanitizeForPrompt(string text, ILogger logger)
```

ScoreArchitecture(BenchmarkTaskDefinition, HashSet<string>, IReadOnlyList<CouncilArtifact>, ILogger)

Executes the score architecture operation.

```
public int ScoreArchitecture(BenchmarkTaskDefinition task, HashSet<string> zipEntries, IReadOnlyList<CouncilArtifact> artifacts, ILogger logger)
```

ScoreBuildability(BenchmarkTaskDefinition, IReadOnlyList<CouncilArtifact>, IReadOnlyList<EngineeringBenchmarkBuildCheck>, bool, ILogger)

Executes the score buildability operation.

```
public int ScoreBuildability(BenchmarkTaskDefinition task, IReadOnlyList<CouncilArtifact> artifacts, IReadOnlyList<EngineeringBenchmarkBuildCheck> buildChecks, bool validateBuildableArtifacts, ILogger logger)
```

ScoreWrongTemplateRisk(BenchmarkTaskDefinition, HashSet<string>, ILogger)

Executes the score wrong template risk operation.

```
public int ScoreWrongTemplateRisk(BenchmarkTaskDefinition task, HashSet<string> zipEntries, ILogger logger)
```

SortKnowledgeEntries(IEnumerable<CouncilKnowledgeEntry>, ILogger)

Executes the sort knowledge entries operation.

```
public List<CouncilKnowledgeEntry> SortKnowledgeEntries(IEnumerable<CouncilKnowledgeEntry> entries, ILogger logger)
```

StampSourceMetadata(string, IReadOnlyList<FileInfo>, DateTime, IReadOnlyList<CouncilKnowledgeEntry>, ILogger)

Executes the stamp source metadata operation.

```
public IReadOnlyList<CouncilKnowledgeEntry> StampSourceMetadata(string rootPath, IReadOnlyList<FileInfo> files, DateTime now, IReadOnlyList<CouncilKnowledgeEntry> entries, ILogger logger)
```

SumScores(EngineeringBenchmarkLaneResult, ILogger)

Executes the sum scores operation.

```
public int SumScores(EngineeringBenchmarkLaneResult lane, ILogger logger)
```

ToKnowledgeEntry(LearnBaseProjectSummary, ILogger)

Executes the to knowledge entry operation.

```
public CouncilKnowledgeEntry? ToKnowledgeEntry(LearnBaseProjectSummary summary, ILogger logger)
```

TryGetLatestSourceDateUtc(string, ILogger)

Executes the try get latest source date utc operation.

```
public DateTime? TryGetLatestSourceDateUtc(string sourcePath, ILogger logger)
```

TryIsSupportedOllamaMode(string, ILogger)

Executes the try is supported ollama mode operation.

```
public bool? TryIsSupportedOllamaMode(string mode, ILogger logger)
```

ValidateAiHostArtifactContract(string, string, ILogger)

Executes the validate ai host artifact contract operation.

```
public void ValidateAiHostArtifactContract(string solutionRoot, string projectName, ILogger logger)
```

ValidateGeneratedDatapackWorkspace(string, ILogger)

Executes the validate generated datapack workspace operation.

```
public void ValidateGeneratedDatapackWorkspace(string rootPath, ILogger logger)
```

ValidateGenerationContractJson(string, ILogger)

Executes the validate generation contract json operation.

```
public void ValidateGenerationContractJson(string path, ILogger logger)
```

ValidateGenerationManifestJson(string, ILogger)

Executes the validate generation manifest json operation.

```
public void ValidateGenerationManifestJson(string path, ILogger logger)
```

ValidateSolutionArtifactContract(string, string, GeneratedSolutionArchetype, ILogger)

Executes the validate solution artifact contract operation.

```
public ArtifactContractReport? ValidateSolutionArtifactContract(string solutionRoot, string projectName, GeneratedSolutionArchetype archetype, ILogger logger)
```

WriteDatapackFunctionAsync(WorkspaceContext, string, string, CancellationToken, ILogger)

Executes the write datapack function async operation.

```
public Task WriteDatapackFunctionAsync(WorkspaceContext context, string functionPath, string content, CancellationToken cancellationToken, ILogger logger)
```

WriteTextAsync(string, string, CancellationToken, ILogger)

Executes the write text async operation.

```
public Task WriteTextAsync(string path, string content, CancellationToken cancellationToken, ILogger logger)
```

WriteZipEntry(ZipArchive, string, string, ILogger)

Executes the write zip entry operation.

```
public void WriteZipEntry(ZipArchive archive, string path, string content, ILogger logger)
```

Class CouncilTeamConfigurationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Database-owned council team/workflow configuration. System defaults are seeded and merged without overwriting user-edited prompts, roles, capabilities or workflow scripts.

Inheritance object CouncilTeamConfigurationService

Implements ICouncilTeamConfigurationService

```
[DocumentationUpdated("2.1.20")] public sealed class CouncilTeamConfigurationService : ICouncilTeamConfigurationService
```

🌟 Constructors 1

CouncilTeamConfigurationService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, IOrganicCouncilBlueprintSeedDataService, ILogger<CouncilTeamConfigurationService>)

Database-owned council team/workflow configuration. System defaults are seeded and merged without overwriting user-edited prompts, roles, capabilities or workflow scripts.

```
public CouncilTeamConfigurationService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, IOrganicCouncilBlueprintSeedDataService seedData, ILogger<CouncilTeamConfigurationService> logger)
```

⚙️ Methods 3

FindTeamAsync(string?, CancellationToken)

Finds one enabled Council team by stable key, falling back to the general key for blank input.

```
public Task<OrganicCouncilTeamDefinition?> FindTeamAsync(string? key, CancellationToken cancellationToken = default)
```

GetTeamsAsync(bool, CancellationToken)

Returns enabled or complete Council-team configuration records.

```
public Task<IReadOnlyList<OrganicCouncilTeamDefinition>> GetTeamsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveAsync(SaveCouncilTeamConfigurationRequest, CancellationToken)

Creates or updates one Council team after explicit user confirmation and validation.

```
public Task<OrganicCouncilTeamDefinition> SaveAsync(SaveCouncilTeamConfigurationRequest request, CancellationToken cancellationToken = default)
```


Class CouncilTextService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CouncilTextService

```
public sealed class CouncilTextService
```

🌟 Constructors 1

CouncilTextService(ICouncilTextPatternDataService, LocalGptCatalogService, ILogger<CouncilTextService>)

```
public CouncilTextService(ICouncilTextPatternDataService patterns, LocalGptCatalogService catalog, ILogger<CouncilTextService> serviceLogger)
```

⚙️ Methods 196

AddOptionalSystemMessage(List<ChatMessage>, string?, ILogger)

```
public void AddOptionalSystemMessage(List<ChatMessage> messages, string? text, ILogger logger)
```

AppendLine(CodeMemberMethod, string, ILogger)

```
public void AppendLine(CodeMemberMethod method, string line, ILogger logger)
```

BuildArchetypeNextAction(string, ILogger)

```
public string BuildArchetypeNextAction(string area, ILogger logger)
```

BuildArchitecturePollMessage(string, string, string, string, bool, string?, ILogger)

```
public string BuildArchitecturePollMessage(string uiStack, string solutionShape, string renderMode, string referenceLook, bool allowSafeDefaults, string? extraDirection, ILogger logger)
```

BuildCapabilityGapKnowledgeContent(string, ILogger)

```
public string BuildCapabilityGapKnowledgeContent(string body, ILogger logger)
```

BuildDataContentFileName(int, string?, ILogger)

```
public string BuildDataContentFileName(int index, string? mediaType, ILogger logger)
```

BuildEngineeringTasks()

```
public IReadOnlyList<BenchmarkTaskDefinition> BuildEngineeringTasks()
```

BuildFeedbackPreview(string?, ILogger)

```
public string BuildFeedbackPreview(string? content, ILogger logger)
```

BuildFilePolicySummary(ILogger)

```
public string BuildFilePolicySummary(ILogger logger)
```

BuildImportDirectories(string, int, ILogger)

```
public IEnumerable<string> BuildImportDirectories(string rootPath, int maxProjects, ILogger logger)
```

BuildMinecraftDatapackArtifactIdentity(string, string, ILogger)

```
public MinecraftDatapackArtifactIdentity? BuildMinecraftDatapackArtifactIdentity(string text, string timestamp, ILogger logger)
```

BuildOllamaDetails(OllamaModelDetails?, ILogger<AiConnectivityProbe>)

```
public string? BuildOllamaDetails(OllamaModelDetails? details, ILogger<AiConnectivityProbe> logger)
```

BuildPromiseNavigationLinks(IReadOnlyList<GeneratedPromiseModule>, ILogger)

```
public string BuildPromiseNavigationLinks(IReadOnlyList<GeneratedPromiseModule> promiseModules, ILogger logger)
```

BuildReplacementTasks()

```
public IReadOnlyList<BenchmarkTaskDefinition> BuildReplacementTasks()
```

BuildRoleCoordinationExplanation(IReadOnlyCollection<string>, ILogger)

```
public string BuildRoleCoordinationExplanation(IReadOnlyCollection<string> details, ILogger logger)
```

BuildSafeZipRelativePath(string, ILogger)

```
public string? BuildSafeZipRelativePath(string fullName, ILogger logger)
```

BuildSourcePreviewMarkup(string, string, ILogger)

```
public string BuildSourcePreviewMarkup(string relativePath, string source, ILogger logger)
```

BuildUniqueFileName(string, string, ILogger)

```
public string BuildUniqueFileName(string directory, string fileName, ILogger logger)
```

BuildUploadWorkspaceSystemPrompt(ChatUploadWorkspaceResult, ILogger)

```
public string BuildUploadWorkspaceSystemPrompt(ChatUploadWorkspaceResult result, ILogger logger)
```

CleanMinecraftProjectDisplayName(string, ILogger)

```
public string CleanMinecraftProjectDisplayName(string value, ILogger logger)
```

ContainsZipEntry(HashSet<string>, string, ILogger)

```
public bool ContainsZipEntry(HashSet<string> zipEntries, string required, ILogger logger)
```

CreateCityCharterModel()

```
public string CreateCityCharterModel()
```

CreateConstant(string, string, ILogger)

```
public CodeMemberField? CreateConstant(string name, string value, ILogger logger)
```

CreateDatapackAdminBookFunction(WorkspaceContext)

```
public string CreateDatapackAdminBookFunction(WorkspaceContext context)
```

CreateDatapackBenchmarkNotes(WorkspaceContext)

```
public string CreateDatapackBenchmarkNotes(WorkspaceContext context)
```

CreateDatapackBuildScript(WorkspaceContext)

```
public string CreateDatapackBuildScript(WorkspaceContext context)
```

CreateDatapackBuildingDebugListFunction(WorkspaceContext)

```
public string CreateDatapackBuildingDebugListFunction(WorkspaceContext context)
```

CreateDatapackBuildingsInitFunction()

```
public string CreateDatapackBuildingsInitFunction()
```

CreateDatapackChronicleAddEventFunction(WorkspaceContext)

```
public string CreateDatapackChronicleAddEventFunction(WorkspaceContext context)
```

CreateDatapackChronicleUiFunction(WorkspaceContext)

```
public string CreateDatapackChronicleUiFunction(WorkspaceContext context)
```

CreateDatapackChronicleUpdateFunction(WorkspaceContext)

```
public string CreateDatapackChronicleUpdateFunction(WorkspaceContext context)
```

CreateDatapackCitizenAgingFunction()

```
public string CreateDatapackCitizenAgingFunction()
```

CreateDatapackCitizenDetectNewFunction()

```
public string CreateDatapackCitizenDetectNewFunction()
```

CreateDatapackCitizenPersonalitiesFunction(WorkspaceContext)

```
public string CreateDatapackCitizenPersonalitiesFunction(WorkspaceContext context)
```

CreateDatapackCitizenRegisterFunction(WorkspaceContext)

```
public string CreateDatapackCitizenRegisterFunction(WorkspaceContext context)
```

CreateDatapackCitizenStatusFunction(WorkspaceContext)

```
public string CreateDatapackCitizenStatusFunction(WorkspaceContext context)
```

CreateDatapackCityAlreadyExistsFunction()

```
public string CreateDatapackCityAlreadyExistsFunction()
```

CreateDatapackCityCheckVillagersFunction(WorkspaceContext)

```
public string CreateDatapackCityCheckVillagersFunction(WorkspaceContext context)
```

CreateDatapackCityCreateFunction(WorkspaceContext)

```
public string CreateDatapackCityCreateFunction(WorkspaceContext context)
```

CreateDatapackCityCreateNewFunction(WorkspaceContext)

```
public string CreateDatapackCityCreateNewFunction(WorkspaceContext context)
```

CreateDatapackFoodConsumptionFunction()

```
public string CreateDatapackFoodConsumptionFunction()
```

CreateDatapackFoodProductionFunction()

```
public string CreateDatapackFoodProductionFunction()
```

CreateDatapackFoodUpdateFunction(WorkspaceContext)

```
public string CreateDatapackFoodUpdateFunction(WorkspaceContext context)
```

CreateDatapackLoadFunction(WorkspaceContext)

```
public string CreateDatapackLoadFunction(WorkspaceContext context)
```

CreateDatapackQuestGenerateFunction(WorkspaceContext)

```
public string CreateDatapackQuestGenerateFunction(WorkspaceContext context)
```

CreateDatapackQuestUpdateFunction(WorkspaceContext)

```
public string CreateDatapackQuestUpdateFunction(WorkspaceContext context)
```

CreateDatapackReadme(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreateDatapackReadme(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreateDatapackRegisterBannerFunction(WorkspaceContext)

```
public string CreateDatapackRegisterBannerFunction(WorkspaceContext context)
```

CreateDatapackRegisterHouseFunction(WorkspaceContext)

```
public string CreateDatapackRegisterHouseFunction(WorkspaceContext context)
```

CreateDatapackReportFunction(WorkspaceContext)

```
public string CreateDatapackReportFunction(WorkspaceContext context)
```

CreateDatapackResetCityFunction(WorkspaceContext)

```
public string CreateDatapackResetCityFunction(WorkspaceContext context)
```

CreateDatapackScheduleFunction(WorkspaceContext)

```
public string CreateDatapackScheduleFunction(WorkspaceContext context)
```

CreateDatapackSecurityGolemsFunction()

```
public string CreateDatapackSecurityGolemsFunction()
```

CreateDatapackSecurityNightwatchFunction()

```
public string CreateDatapackSecurityNightwatchFunction()
```

CreateDatapackSecurityUpdateFunction(WorkspaceContext)

```
public string CreateDatapackSecurityUpdateFunction(WorkspaceContext context)
```

CreateDatapackTickFunction(WorkspaceContext)

```
public string CreateDatapackTickFunction(WorkspaceContext context)
```

CreateDatapackTownHallFunction(WorkspaceContext)

```
public string CreateDatapackTownHallFunction(WorkspaceContext context)
```

CreateDatapackUpdatePopulationFunction(WorkspaceContext)

```
public string CreateDatapackUpdatePopulationFunction(WorkspaceContext context)
```

CreateEnglishLang(string)

```
public string CreateEnglishLang(string modId)
```

CreateFabricBuildGradle(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreateFabricBuildGradle(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreateFabricEmptyMainClass(WorkspaceContext)

```
public string CreateFabricEmptyMainClass(WorkspaceContext context)
```

CreateFabricMainClass(WorkspaceContext)

```
public string CreateFabricMainClass(WorkspaceContext context)
```

CreateFabricMetadata(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreateFabricMetadata(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreateFabricSettingsGradle(string)

```
public string CreateFabricSettingsGradle(string projectName)
```

CreateFunctionTag(string, string)

```
public string CreateFunctionTag(string modId, string functionName)
```

CreateLivingCitiesPlan(MinecraftModBuildRequest)

```
public string CreateLivingCitiesPlan(MinecraftModBuildRequest request)
```

CreateLivingCitiesReportClass(string)

```
public string CreateLivingCitiesReportClass(string packageName)
```

CreateMessageSignature(IEnumerable<BlazorChatMessage>, ILogger)

```
public string CreateMessageSignature(IEnumerable<BlazorChatMessage> messages, ILogger logger)
```

CreateMinecraftSystemPrompt(string, ILogger)

```
public string CreateMinecraftSystemPrompt(string mode, ILogger logger)
```

CreateNeoForgeBuildGradle(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreateNeoForgeBuildGradle(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreateNeoForgeEmptyMainClass(WorkspaceContext)

```
public string CreateNeoForgeEmptyMainClass(WorkspaceContext context)
```

CreateNeoForgeMainClass(WorkspaceContext)

```
public string CreateNeoForgeMainClass(WorkspaceContext context)
```

CreateNeoForgeMetadata(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreateNeoForgeMetadata(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreateNeoForgeSettingsGradle(string)

```
public string CreateNeoForgeSettingsGradle(string projectName)
```

CreatePaperBuildGradle(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreatePaperBuildGradle(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreatePaperMainClass(WorkspaceContext)

```
public string CreatePaperMainClass(WorkspaceContext context)
```

CreatePaperPluginYaml(MinecraftModBuildRequest, WorkspaceContext)

```
public string CreatePaperPluginYaml(MinecraftModBuildRequest request, WorkspaceContext context)
```

CreatePaperSettingsGradle(string)

```
public string CreatePaperSettingsGradle(string projectName)
```

CreateWorkspaceReadme(MinecraftModBuildRequest, WorkspaceContext, string)

```
public string CreateWorkspaceReadme(MinecraftModBuildRequest request, WorkspaceContext context, string loader)
```

DecodeText(byte[], ILogger)

```
public string DecodeText(byte[] bytes, ILogger logger)
```

DetectTargetArea(string, string, ILogger)

```
public string DetectTargetArea(string prompt, string finalAnswer, ILogger logger)
```

EnumerateImportDirectoryCandidates(string, ILogger)

```
public IEnumerable<string> EnumerateImportDirectoryCandidates(string rootPath, ILogger logger)
```

EnumerateNestedArchitectureRoots(string, ILogger)

```
public IEnumerable<string> EnumerateNestedArchitectureRoots(string rootPath, ILogger logger)
```

EscapeCSharpString(string, ILogger)

```
public string EscapeCSharpString(string text, ILogger logger)
```

EscapeJson(string)

```
public string EscapeJson(string value)
```

EscapeJsonString(string, ILogger)

```
public string EscapeJsonString(string text, ILogger logger)
```

ExtractCapabilityGapSummary(string, ILogger<AiFeatureReportService>)

```
public string ExtractCapabilityGapSummary(string text, ILogger<AiFeatureReportService> logger)
```

ExtractField(string, string, ILogger, string)

```
public string ExtractField(string body, string name, ILogger logger, string fallback = "")
```

ExtractField(string, string, ILogger<AiFeatureReportService>)

```
public string ExtractField(string body, string name, ILogger<AiFeatureReportService> logger)
```

ExtractHelpfulSources(string, ILogger<AiFeatureReportService>)

```
public string ExtractHelpfulSources(string text, ILogger<AiFeatureReportService> logger)
```

ExtractMinecraftProjectDisplayName(string, bool?, ILogger)

```
public string ExtractMinecraftProjectDisplayName(string text, bool? harmonyModel, ILogger logger)
```

ExtractMinecraftVersion(string, ILogger)

```
public string ExtractMinecraftVersion(string text, ILogger logger)
```

ExtractModelThinking(string, ILogger)

```
public string ExtractModelThinking(string content, ILogger logger)
```

ExtractPackageReferences(string, ILogger)

```
public IEnumerable<string> ExtractPackageReferences(string text, ILogger logger)
```

ExtractPrintableStrings(byte[], int, ILogger)

```
public string ExtractPrintableStrings(byte[] bytes, int maxCharacters, ILogger logger)
```

ExtractTargetFrameworks(string, ILogger)

```
public IEnumerable<string> ExtractTargetFrameworks(string text, ILogger logger)
```

ExtractThinking(string, ILogger)

```
public string? ExtractThinking(string content, ILogger logger)
```

ExtractUploadFiles(ChatMessage, ILogger)

```
public IEnumerable<ChatUploadWorkspaceInputFile>? ExtractUploadFiles(ChatMessage message, ILogger logger)
```

Fallback(string, string, ILogger)

```
public string Fallback(string value, string fallback, ILogger logger)
```

FlushCurrentString(StringBuilder, StringBuilder, int, ILogger)

```
public void FlushCurrentString(StringBuilder builder, StringBuilder current, int maxCharacters, ILogger logger)
```

FormatLiveCouncilSessionOption(DateTime, string, IReadOnlyList<string>)

```
public string FormatLiveCouncilSessionOption(DateTime startedAtUtc, string runState, IReadOnlyList<string> councilMembers)
```

FormatNullableGuid(Guid?, ILogger)

```
public string FormatNullableGuid(Guid? value, ILogger logger)
```

FormatNullableUtc(DateTime?, ILogger)

```
public string FormatNullableUtc(DateTime? value, ILogger logger)
```

GenerateAiHostArchitectureServices(string, ILogger)

```
public string GenerateAiHostArchitectureServices(string projectName, ILogger logger)
```

GenerateArchetypePageRazor(string, string, string, IReadOnlyList<string>, ILogger)

```
public string GenerateArchetypePageRazor(string route, string title, string summary, IReadOnlyList<string> areas, ILogger logger)
```

GenerateBlazorDevExpressRazorExample(MultiModelCouncilRequest, MultiModelCouncilResult, ILogger)

```
public string GenerateBlazorDevExpressRazorExample(MultiModelCouncilRequest request, MultiModelCouncilResult result, ILogger logger)
```

GenerateBlazorSupportCode(MultiModelCouncilRequest, MultiModelCouncilResult, string, ILogger)

```
public string GenerateBlazorSupportCode(MultiModelCouncilRequest request, MultiModelCouncilResult result, string targetArea, ILogger logger)
```

GenerateCodeDomExample(MultiModelCouncilRequest, MultiModelCouncilResult, string, ILogger)

```
public string GenerateCodeDomExample(MultiModelCouncilRequest request, MultiModelCouncilResult result, string targetArea, ILogger logger)
```

GenerateDesignReviewDoc(string, GeneratedSolutionArchetype, IReadOnlyList<GeneratedPromiseModule>, ILogger)

```
public string GenerateDesignReviewDoc(string projectName, GeneratedSolutionArchetype archetype, IReadOnlyList<GeneratedPromiseModule> promiseModules, ILogger logger)
```

GenerateLocalGptGenerationJson(string, MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string GenerateLocalGptGenerationJson(string projectName, MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isAiHostLab, ILogger logger)
```

GenerateNavigationIconSvgs(ILogger)

```
public IReadOnlyList<(string FileName, string Svg)>? GenerateNavigationIconSvgs(ILogger logger)
```

GeneratePromiseMapDoc(string, MultiModelCouncilRequest, MultiModelCouncilResult, IReadOnlyList<GeneratedPromiseModule>, ILogger)

```
public string GeneratePromiseMapDoc(string projectName, MultiModelCouncilRequest request, MultiModelCouncilResult result, IReadOnlyList<GeneratedPromiseModule> promiseModules, ILogger logger)
```

GeneratePromiseModuleRazor(GeneratedPromiseModule, ILogger)

```
public string GeneratePromiseModuleRazor(GeneratedPromiseModule module, ILogger logger)
```

GenerateSolutionAppSettings(bool, ILogger)

```
public string GenerateSolutionAppSettings(bool isAiHostLab, ILogger logger)
```

GenerateSolutionArchitectureDoc(string, bool, ILogger)

```
public string GenerateSolutionArchitectureDoc(string projectName, bool isAiHostLab, ILogger logger)
```

GenerateSolutionBuildAndRunDoc(string, bool, ILogger)

```
public string GenerateSolutionBuildAndRunDoc(string projectName, bool isAiHostLab, ILogger logger)
```

GenerateSolutionDashboardRazor(MultiModelCouncilRequest, MultiModelCouncilResult, GeneratedSolutionArchetype, ILogger)

```
public string GenerateSolutionDashboardRazor(MultiModelCouncilRequest request, MultiModelCouncilResult result, GeneratedSolutionArchetype archetype, ILogger logger)
```

GenerateSolutionDetailRazor(MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string GenerateSolutionDetailRazor(MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isAiHostLab, ILogger logger)
```

GenerateSolutionFile(string, string, ILogger)

```
public string GenerateSolutionFile(string projectName, string projectGuid, ILogger logger)
```

GenerateSolutionImports(string, ILogger)

```
public string GenerateSolutionImports(string projectName, ILogger logger)
```

GenerateSolutionIndexRazor(MultiModelCouncilRequest, MultiModelCouncilResult, GeneratedSolutionArchetype, ILogger)

```
public string GenerateSolutionIndexRazor(MultiModelCouncilRequest request, MultiModelCouncilResult result, GeneratedSolutionArchetype archetype, ILogger logger)
```

GenerateSolutionKnowledgeTableRazor(bool, ILogger)

```
public string GenerateSolutionKnowledgeTableRazor(bool isAiHostLab, ILogger logger)
```

GenerateSolutionManifest(string, string, MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string GenerateSolutionManifest(string projectName, string solutionGuid, MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isAiHostLab, ILogger logger)
```

GenerateSolutionModel(string, ILogger)

```
public string GenerateSolutionModel(string projectName, ILogger logger)
```

GenerateSolutionNavigationRazor(GeneratedSolutionArchetype, IReadOnlyList<GeneratedPromiseModule>, ILogger)

```
public string GenerateSolutionNavigationRazor(GeneratedSolutionArchetype archetype, IReadOnlyList<GeneratedPromiseModule> promiseModules, ILogger logger)
```

GenerateSolutionProgram(string, bool, ILogger)

```
public string GenerateSolutionProgram(string projectName, bool isAiHostLab, ILogger logger)
```

GenerateSolutionProjectIndex(string, MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string GenerateSolutionProjectIndex(string projectName, MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isAiHostLab, ILogger logger)
```

GenerateSolutionReadme(string, MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string GenerateSolutionReadme(string projectName, MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isAiHostLab, ILogger logger)
```

GenerateSolutionService(string, bool, ILogger)

```
public string GenerateSolutionService(string projectName, bool isAiHostLab, ILogger logger)
```

GenerateSourceFidelityDoc(string, GeneratedSolutionArchetype, IReadOnlyList<GeneratedPromiseModule>, ILogger)

```
public string GenerateSourceFidelityDoc(string projectName, GeneratedSolutionArchetype archetype, IReadOnlyList<GeneratedPromiseModule> promiseModules, ILogger logger)
```

GenerateSourceFidelityService(string, GeneratedSolutionArchetype, ILogger)

```
public string GenerateSourceFidelityService(string projectName, GeneratedSolutionArchetype archetype, ILogger logger)
```

GetDiscoveredModelButtonText(LocalAiModelInfo, ILogger)

```
public string GetDiscoveredModelButtonText(LocalAiModelInfo model, ILogger logger)
```

GetPackFormatJsonValue(string, ILogger)

```
public string GetPackFormatJsonValue(string minecraftVersion, ILogger logger)
```

IsAllowedLocalRoute(string, ILogger)

```
public bool IsAllowedLocalRoute(string route, ILogger logger)
```

IsImportantFile(string, string, ILogger)

```
public bool IsImportantFile(string fileName, string extension, ILogger logger)
```

IsMinecraftDatapackArtifactTarget(string, string, ILogger)

```
public bool? IsMinecraftDatapackArtifactTarget(string prompt, string finalAnswer, ILogger logger)
```

IsMinecraftSkeletonMatrixArtifactTarget(string, string, ILogger)

```
public bool? IsMinecraftSkeletonMatrixArtifactTarget(string prompt, string finalAnswer, ILogger logger)
```

IsProjectRootFile(string, string, ILogger)

```
public bool IsProjectRootFile(string fileName, string extension, ILogger logger)
```

LooksLikeArchitectureRoot(string, ILogger)

```
public bool LooksLikeArchitectureRoot(string rootPath, ILogger logger)
```

LooksLikeMissingFeatureReport(string, ILogger<AiFeatureReportService>)

```
public bool LooksLikeMissingFeatureReport(string text, ILogger<AiFeatureReportService> logger)
```

LooksLikelyTruncated(string, ILogger)

```
public bool LooksLikelyTruncated(string text, ILogger logger)
```

MergeTags(string, string, ILogger)

```
public string MergeTags(string requestedTags, string requiredTags, ILogger logger)
```

MinecraftDatapackVersionInfoKnown(string, string, string, string, ILogger)

```
public MinecraftDatapackVersionInfo MinecraftDatapackVersionInfoKnown(string version, string packFormat, string functionRegistryFolder, string notes, ILogger logger)
```

MinecraftDatapackVersionInfoResolve(string?, ILogger)

```
public MinecraftDatapackVersionInfo MinecraftDatapackVersionInfoResolve(string? minecraftVersion, ILogger logger)
```

MinecraftDatapackVersionKnownVersions(ILogger)

```
public List<MinecraftDatapackVersionInfo> MinecraftDatapackVersionKnownVersions(ILogger logger)
```

MultiModelCouncilServiceBuildArtifactsMarkdown(IEnumerable<CouncilArtifact>, ILogger)

```
public string MultiModelCouncilServiceBuildArtifactsMarkdown(IEnumerable<CouncilArtifact> artifacts, ILogger logger)
```

MultiModelCouncilServiceBuildPollMarkdown(CouncilUserPoll, ILogger)

```
public string MultiModelCouncilServiceBuildPollMarkdown(CouncilUserPoll poll, ILogger logger)
```

MultiModelCouncilServiceBuildTranscript(IEnumerable<MultiModelCouncilStep>, ILogger)

```
public string MultiModelCouncilServiceBuildTranscript(IEnumerable<MultiModelCouncilStep> steps, ILogger logger)
```

MultiModelCouncilServiceCreateConsensusPrompt(string, string, ILogger)

```
public string MultiModelCouncilServiceCreateConsensusPrompt(string userPrompt, string transcript, ILogger logger)
```

MultiModelCouncilServiceCreateCouncilSystemPrompt(string, IReadOnlyList<string>, ILogger)

```
public string MultiModelCouncilServiceCreateCouncilSystemPrompt(string modelName, IReadOnlyList<string> councilMembers, ILogger logger)
```

MultiModelCouncilServiceCreateCritiquePrompt(string, string, string, bool, ILogger)

```
public string MultiModelCouncilServiceCreateCritiquePrompt(string modelName, string userPrompt, string transcript, bool selfReview, ILogger logger)
```

MultiModelCouncilServiceCreateProposalPrompt(string, string, ILogger)

```
public string MultiModelCouncilServiceCreateProposalPrompt(string modelName, string userPrompt, ILogger logger)
```

MultiModelCouncilServiceCreateVerificationPrompt(string, string, string, ILogger)

```
public string MultiModelCouncilServiceCreateVerificationPrompt(string userPrompt, string transcript, string consensus, ILogger logger)
```

MultiModelCouncilServiceExtractThinking(string, ILogger)

```
public string MultiModelCouncilServiceExtractThinking(string content, ILogger logger)
```

MultiModelCouncilServiceNormalizeEndpoint(string, ILogger)

```
public string MultiModelCouncilServiceNormalizeEndpoint(string endpoint, ILogger logger)
```


MultiModelCouncilServiceStripThinking(string, ILogger)

```
public string MultiModelCouncilServiceStripThinking(string content, ILogger logger)
```

MultiModelCouncilServiceTrimCouncilText(string, int, ILogger)

```
public string MultiModelCouncilServiceTrimCouncilText(string content, int maxLength, ILogger logger)
```

NormalizeDBNullStringValue(string, ILogger)

```
public string? NormalizeDBNullStringValue(string value, ILogger logger)
```

NormalizeDescription(string)

```
public string NormalizeDescription(string description)
```

NormalizeFormerThought(string?, ILogger)

```
public string NormalizeFormerThought(string? value, ILogger logger)
```

NormalizeLoader(string?, ILogger)

```
public string NormalizeLoader(string? loader, ILogger logger)
```

NormalizeModId(string, string)

```
public string NormalizeModId(string value, string fallback)
```

NormalizeName(string, string)

```
public string NormalizeName(string value, string fallback)
```

NormalizeOpenAIEndpoint(string, ILogger<AiConnectivityProbe>)

```
public string NormalizeOpenAIEndpoint(string endpoint, ILogger<AiConnectivityProbe> logger)
```

NormalizePackageName(string)

```
public string NormalizePackageName(string value)
```

NormalizeRecoveredPrompt(string, ILogger)

```
public string NormalizeRecoveredPrompt(string prompt, ILogger logger)
```

NormalizeTaskSet(string?, ILogger)

```
public string NormalizeTaskSet(string? taskSet, ILogger logger)
```

ParseKnowledgeRequests(string, string, ILogger)

```
public IEnumerable<CouncilKnowledgeEntry>? ParseKnowledgeRequests(string source, string responseText, ILogger logger)
```

ParseModelNames(string?, ILogger)

```
public IReadOnlyList<string> ParseModelNames(string? value, ILogger logger)
```

ParseNullableGuid(string, ILogger)

```
public Guid? ParseNullableGuid(string value, ILogger logger)
```

ParseNullableUtc(string, ILogger)

```
public DateTime? ParseNullableUtc(string value, ILogger logger)
```

PrettyPrintJson(string, ILogger)

```
public string PrettyPrintJson(string text, ILogger logger)
```

ProviderModelBenchmarkCouncilSignature(IEnumerable<ProviderModelReference>, ILogger)

```
public string ProviderModelBenchmarkCouncilSignature(IEnumerable<ProviderModelReference> models, ILogger logger)
```

ProviderModelReviewerSummary(ProviderModelReference, IEnumerable<ProviderModelReference>, ILogger)

```
public string ProviderModelReviewerSummary(ProviderModelReference model, IEnumerable<ProviderModelReference> councilModels, ILogger logger)
```

RedactSensitiveName(string, ILogger)

```
public string RedactSensitiveName(string value, ILogger logger)
```

SafeEnumerateDirectories(string, ILogger)

```
public IEnumerable<string> SafeEnumerateDirectories(string rootPath, ILogger logger)
```

SafeEnumerateDirectoryInfos(string, ILogger)

```
public IEnumerable<DirectoryInfo> SafeEnumerateDirectoryInfos(string rootPath, ILogger logger)
```

SanitizeFileName(string, ILogger)

```
public string SanitizeFileName(string fileName, ILogger logger)
```

SanitizeFileName(string, ILogger<BuildDebugInventoryService>)

```
public string SanitizeFileName(string value, ILogger<BuildDebugInventoryService> logger)
```

SanitizeForPrompt(string, ILogger)

```
public string SanitizeForPrompt(string text, ILogger logger)
```

StripModelThinking(string, ILogger)

```
public string StripModelThinking(string content, ILogger logger)
```

StripThinking(string, ILogger)

```
public string StripThinking(string content, ILogger logger)
```

ToForwardSlash(string, ILogger)

```
public string ToForwardSlash(string path, ILogger logger)
```

ToKebabRoute(string, ILogger)

```
public string ToKebabRoute(string value, ILogger logger)
```

ToMinecraftNamespace(string, ILogger)

```
public string ToMinecraftNamespace(string value, ILogger logger)
```

ToPascalCase(string, ILogger)

```
public string ToPascalCase(string value, ILogger logger)
```

ToPascalIdentifier(string, ILogger)

```
public string ToPascalIdentifier(string value, ILogger logger)
```

TrimEndpoint(string, ILogger)

```
public string TrimEndpoint(string endpoint, ILogger logger)
```

TrimForCodeComment(string, int, ILogger)

```
public string TrimForCodeComment(string text, int maxLength, ILogger logger)
```

TrimForDisplay(string, int, ILogger)

```
public string TrimForDisplay(string text, int maxCharacters, ILogger logger)
```

TrimForKnowledge(string, int, ILogger)

```
public string TrimForKnowledge(string text, int maxLength, ILogger logger)
```

TrimForPrompt(string?, int, ILogger, bool, bool, bool)

```
public string TrimForPrompt(string? text, int maxCharacters, ILogger logger, bool keepBothEnds = false, bool collapseWhitespace = false, bool useLocalGptOmission = false)
```

TryFindCouncilPromptSection(string, ILogger)

```
public string? TryFindCouncilPromptSection(string content, ILogger logger)
```

TryGetDataContentFileName(DataContent, ILogger)

```
public string? TryGetDataContentFileName(DataContent content, ILogger logger)
```

TryParseConfidence(string, ILogger)

```
public int? TryParseConfidence(string value, ILogger logger)
```

TryRecoverPromptFromTitle(string, ILogger)

```
public string? TryRecoverPromptFromTitle(string title, ILogger logger)
```

api/LocalGPT.Services.CreateCodeGenerationReviewFunction.html

Class CreateCodeGenerationReviewFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll
Inheritance object CreateCodeGenerationReviewFunction
Implements IDxAiFunctionHandler

```
public sealed class CreateCodeGenerationReviewFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

CreateCodeGenerationReviewFunction(IDxAiFunctionJsonService, ICodeGenerationWorkflowService, ILogger<CreateCodeGenerationReviewFunction>)

```
public CreateCodeGenerationReviewFunction(IDxAiFunctionJsonService json, ICodeGenerationWorkflowService workflow, ILogger<CreateCodeGenerationReviewFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

api/LocalGPT.Services.CreateEmbeddedFirmwareArtifactsFunction.html

Class CreateEmbeddedFirmwareArtifactsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll
Inheritance object CreateEmbeddedFirmwareArtifactsFunction
Implements IDxAiFunctionHandler

```
public sealed class CreateEmbeddedFirmwareArtifactsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

CreateEmbeddedFirmwareArtifactsFunction(IDxAiFunctionJsonService, IEmbeddedFirmwarePlanningService, ILogger<CreateEmbeddedFirmwareArtifactsFunction>)

```
public CreateEmbeddedFirmwareArtifactsFunction(IDxAiFunctionJsonService json, IEmbeddedFirmwarePlanningService planning, ILogger<CreateEmbeddedFirmwareArtifactsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class CreateEmbeddedWiringDraftFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object CreateEmbeddedWiringDraftFunction

Implements IDxAiFunctionHandler

```
public sealed class CreateEmbeddedWiringDraftFunction : IDxAiFunctionHandler
```

✨ Constructors 1

CreateEmbeddedWiringDraftFunction(IDxAiFunctionJsonService, IEmbeddedWiringService)

```
public CreateEmbeddedWiringDraftFunction(IDxAiFunctionJsonService json, IEmbeddedWiringService wiring)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class CreatureCouncilGameSubdirector

Namespace LocalGPT . Services Assembly LocalGPT.dll

Predicts bounded creature reactions for the next authoritative world step.

Inheritance object CreatureCouncilGameSubdirector

Implements ICouncilGameSubdirector

```
public sealed class CreatureCouncilGameSubdirector : ICouncilGameSubdirector
```

✨ Constructors 1

CreatureCouncilGameSubdirector(ICouncilGameActorRuntimeFactory)

Predicts bounded creature reactions for the next authoritative world step.

```
public CreatureCouncilGameSubdirector(ICouncilGameActorRuntimeFactory actorFactory)
```

🐾 Properties 2

ActorKind

```
public CouncilGameActorKind ActorKind { get; }
```

Key

```
public string Key { get; }
```

⚙️ Methods 1

PredictAsync(CouncilGameDirectorContext, CancellationToken)

Produces a bounded prediction for the proposed action.

```
public Task<CouncilGameSubdirectorPrediction> PredictAsync(CouncilGameDirectorContext context, CancellationToken cancellationToken = default)
```

Class DebugArtifactInspectionService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Reads bounded metadata from portable PDB and other debug files without loading or executing them.

Inheritance object DebugArtifactInspectionService

Implements IDebugArtifactInspectionService

```
public sealed class DebugArtifactInspectionService : IDebugArtifactInspectionService
```

🌟 Constructors 1

DebugArtifactInspectionService(ILogger<DebugArtifactInspectionService>)

Reads bounded metadata from portable PDB and other debug files without loading or executing them.

```
public DebugArtifactInspectionService(ILogger<DebugArtifactInspectionService> logger)
```

⚙️ Methods 1

InspectAsync(string, CancellationToken)

```
public Task<DebugArtifactInspectionResult> InspectAsync(string filePath, CancellationToken cancellationToken = default)
```

Class DeferredDxAiInvocationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object DeferredDxAiInvocationService

Implements IDeferredDxAiInvocationService

```
public sealed class DeferredDxAiInvocationService : IDeferredDxAiInvocationService
```

🌟 Constructors 1

DeferredDxAiInvocationService(ILocalGptVocabularyService, IDbContextFactory<LocalGptMemoryDbContext>, IServiceScopeFactory, ILogger<DeferredDxAiInvocationService>)

```
public DeferredDxAiInvocationService(ILocalGptVocabularyService vocabulary, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IServiceScopeFactory scopeFactory, ILogger<DeferredDxAiInvocationService> logger)
```

⚙️ Methods 2

ExecuteApprovedForHeartbeatAsync(Guid, int, CancellationToken)

```
public Task<IReadOnlyList<DeferredDxAiExecutionOutcome>> ExecuteApprovedForHeartbeatAsync(Guid councilRunId, int councilRound, CancellationToken cancellationToken = default)
```

QueueAsync(string, DxAiFunctionInvocationRequest, Guid, string, Guid?, CancellationToken)

```
public Task QueueAsync(string functionName, DxAiFunctionInvocationRequest request, Guid approvalRequestId, string correlationId, Guid? councilRunId, CancellationToken cancellationToken = default)
```

Class DeleteSqliteRowFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll
Inheritance object DeleteSqliteRowFunction
Implements IDxAiFunctionHandler

```
public sealed class DeleteSqliteRowFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

DeleteSqliteRowFunction(IDxAiFunctionJsonService, ISqliteTableEditorService, ILogger<DeleteSqliteRowFunction>)

```
public DeleteSqliteRowFunction(IDxAiFunctionJsonService json, ISqliteTableEditorService editor, ILogger<DeleteSqliteRowFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class DevExpressChatService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object DevExpressChatService

```
public sealed class DevExpressChatService
```

🌟 Constructors 1

DevExpressChatService(CouncilTextService, IDxAiFunctionRegistry, LocalGptCatalogService, ILogger<DevExpressChatService>)

```
public DevExpressChatService(CouncilTextService text, IDxAiFunctionRegistry functionRegistry, LocalGptCatalogService catalog,
    ILogger<DevExpressChatService> logger)
```

🔗 Fields 1

Functions

```
public readonly DxaichatFunctionInfo[] Functions
```

⚙️ Methods 8

BuildPromptBriefing()

```
public string BuildPromptBriefing()
```

BuildTitle(IReadOnlyList<BlazorChatMessage>, ILogger)

```
public string BuildTitle(IReadOnlyList<BlazorChatMessage> messages, ILogger logger)
```

EnsureVisibleCouncilPrompt(ChatMemoryConversation, List<BlazorChatMessage>, ILogger)

```
public List<BlazorChatMessage> EnsureVisibleCouncilPrompt(ChatMemoryConversation conversation, List<BlazorChatMessage> messages, ILogger logger)
```

GetFunctions()

```
public IReadOnlyList<DxaichatFunctionInfo> GetFunctions()
```

IsCouncilConversation(ChatMemoryConversation, IReadOnlyList<BlazorChatMessage>, ILogger)

```
public bool IsCouncilConversation(ChatMemoryConversation conversation, IReadOnlyList<BlazorChatMessage> messages, ILogger logger)
```

ToBlazorChatMessage(ChatMemoryMessage, ILogger)

```
public BlazorChatMessage? ToBlazorChatMessage(ChatMemoryMessage message, ILogger logger)
```

ToRoleName(ChatMessageRole, ILogger)

```
public string ToRoleName(ChatMessageRole role, ILogger logger)
```

TryExtractPromptFromAssistantMessages(IReadOnlyList<BlazorChatMessage>, ILogger)

```
public string? TryExtractPromptFromAssistantMessages(IReadOnlyList<BlazorChatMessage> messages, ILogger logger)
```

Class DocumentationCatalogService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Resolves generated DocFX artifacts and compiler-generated XML comments without exposing arbitrary filesystem paths.

Inheritance object DocumentationCatalogService

Implements IDocumentationCatalogService

```
[DocumentationUpdated("2.2.8")] public sealed class DocumentationCatalogService : IDocumentationCatalogService
```

🌟 Constructors 1

DocumentationCatalogService(IWebHostEnvironment, ICustomVersion, IDocumentationTranslationAdapter, ILogger<DocumentationCatalogService>)

Resolves generated DocFX artifacts and compiler-generated XML comments without exposing arbitrary filesystem paths.

```
public DocumentationCatalogService(IWebHostEnvironment environment, ICustomVersion version, IDocumentationTranslationAdapter translation,
    ILogger<DocumentationCatalogService> logger)
```

⚙️ Methods 5

GetComment(string, string?)

Returns one localized XML documentation member by its stable compiler member identifier.

```
public LocalGptDocumentationComment? GetComment(string memberId, string? culture = null)
```

GetHtmlFilePath(string?)

Returns one generated HTML or supporting asset path from the selected documentation root.

```
public string? GetHtmlFilePath(string? relativePath)
```

GetPdfPath()

Returns the absolute PDF path when a compatible generated documentation artifact exists.

```
public string? GetPdfPath()
```

GetStatus()

Returns availability, version and application-relative links for generated documentation.

```
public LocalGptDocumentationStatus GetStatus()
```

SearchComments(string?, int, string?)

Searches member identifiers, summaries and remarks without exposing arbitrary files.

```
public IReadOnlyList<LocalGptDocumentationComment> SearchComments(string? query, int limit = 100, string? culture = null)
```

Class DocumentationTranslationAdapter

Namespace LocalGPT . Services Assembly LocalGPT.dll

Bridges compiler-generated XML comments to the existing LocalGPT localization service without changing that service's contract.

Inheritance object DocumentationTranslationAdapter

Implements IDocumentationTranslationAdapter

```
[DocumentationUpdated("2.1.20")] public sealed class DocumentationTranslationAdapter : IDocumentationTranslationAdapter
```

🌟 Constructors 1

DocumentationTranslationAdapter(ILocalGptLocalizationService, ILogger<DocumentationTranslationAdapter>)

Bridges compiler-generated XML comments to the existing LocalGPT localization service without changing that service's contract.

```
public DocumentationTranslationAdapter(ILocalGptLocalizationService localization, ILogger<DocumentationTranslationAdapter> logger)
```

⚙️ Methods 1

Adapt(LocalGptDocumentationComment, string?)

Returns a localized copy of one documentation comment for the requested culture.

```
public LocalGptDocumentationComment Adapt(LocalGptDocumentationComment comment, string? culture = null)
```


Class DxAiFunctionCatalogHostedService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object DxAiFunctionCatalogHostedService

Implements IHostedService

```
public sealed class DxAiFunctionCatalogHostedService : IHostedService
```

🌟 Constructors 1

DxAiFunctionCatalogHostedService(IServiceScopeFactory, ILogger<DxAiFunctionCatalogHostedService>)

```
public DxAiFunctionCatalogHostedService(IServiceScopeFactory scopeFactory, ILogger<DxAiFunctionCatalogHostedService> logger)
```

⚙️ Methods 2

StartAsync(CancellationTokens)

```
public Task StartAsync(CancellationTokens cancellationTokens)
```

StopAsync(CancellationTokens)

```
public Task StopAsync(CancellationTokens cancellationTokens)
```

Class DxAiFunctionCatalogService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Keeps the user-facing DX function catalog in the existing SystemVariables table. This deliberately avoids destructive schema replacement: old databases receive missing records, while user-edited exposure and confirmation settings survive descriptor refreshes and application upgrades.

Inheritance object DxAiFunctionCatalogService

Implements IDxAiFunctionCatalogService

```
public sealed class DxAiFunctionCatalogService : IDxAiFunctionCatalogService
```

🌟 Constructors 1

DxAiFunctionCatalogService(ILocalGptVocabularyService, DxAiFunctionCatalogSynchronizationGate, IDatabaseInitializationService, IDbContextFactory<LocalGptMemoryDbContext>, IDxAiFunctionRegistry, IOrganicAddonManifestService, ILogger<DxAiFunctionCatalogService>)

Keeps the user-facing DX function catalog in the existing SystemVariables table. This deliberately avoids destructive schema replacement: old databases receive missing records, while user-edited exposure and confirmation settings survive descriptor refreshes and application upgrades.

```
public DxAiFunctionCatalogService(ILocalGptVocabularyService vocabulary, DxAiFunctionCatalogSynchronizationGate synchronizationGate, IDatabaseInitializationService databaseInitialization, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDxAiFunctionRegistry registry, IOrganicAddonManifestService addonManifests, ILogger<DxAiFunctionCatalogService> logger)
```

⚙️ Methods 6

GetByFunctionNameAsync(string, CancellationTokens)

```
public Task<DxAiFunctionCatalogEntry?> GetByFunctionNameAsync(string functionName, CancellationTokens cancellationTokens = default)
```

GetEntriesAsync(CancellationTokens)

```
public Task<IReadOnlyList<DxAiFunctionCatalogEntry>> GetEntriesAsync(CancellationTokens cancellationTokens = default)
```

GetEntryAsync(string, CancellationTokens)

```
public Task<DxAiFunctionCatalogEntry?> GetEntryAsync(string catalogKey, CancellationTokens cancellationTokens = default)
```

GetExposedToPeerAsync(string, CancellationTokens)

```
public Task<IReadOnlyList<DxAiFunctionCatalogEntry>> GetExposedToPeerAsync(string peerId, CancellationTokens cancellationTokens = default)
```

SavePolicyAsync(DxAiFunctionCatalogSaveRequest, CancellationTokens)

```
public Task<DxAiFunctionCatalogEntry> SavePolicyAsync(DxAiFunctionCatalogSaveRequest request, CancellationTokens cancellationTokens = default)
```

SynchronizeAsync(CancellationTokens)

```
public Task<IReadOnlyList<DxAiFunctionCatalogEntry>> SynchronizeAsync(CancellationTokens cancellationTokens = default)
```

Class DxAiFunctionCatalogSynchronizationGate

Namespace LocalGPT . Services Assembly LocalGPT.dll

Serializes DX function catalog synchronization and policy writes across all scoped catalog-service instances.

Inheritance object DxAiFunctionCatalogSynchronizationGate

```
public sealed class DxAiFunctionCatalogSynchronizationGate
```

✨ Constructors 1

DxAiFunctionCatalogSynchronizationGate()

```
public DxAiFunctionCatalogSynchronizationGate()
```

⚙️ Methods 2

Release()

```
public void Release()
```

WaitAsync(CancellationToken)

```
public Task WaitAsync(CancellationToken cancellationToken)
```

Class DxAiFunctionHandlerMapService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Builds the scoped DXAI handler directory after the registry has been created. This keeps lazy cycle breaking in the registry while moving validation behavior behind an injected service instead of a static helper.

Inheritance object DxAiFunctionHandlerMapService

```
public sealed class DxAiFunctionHandlerMapService
```

✨ Constructors 1

DxAiFunctionHandlerMapService(ILogger<DxAiFunctionHandlerMapService>)

Builds the scoped DXAI handler directory after the registry has been created. This keeps lazy cycle breaking in the registry while moving validation behavior behind an injected service instead of a static helper.

```
public DxAiFunctionHandlerMapService(ILogger<DxAiFunctionHandlerMapService> logger)
```

⚙️ Methods 1

Build(IEnumerable<IDxAiFunctionHandler>)

```
public IReadOnlyDictionary<string, IDxAiFunctionHandler> Build(IEnumerable<IDxAiFunctionHandler> handlers)
```

Class DxAiFunctionRegistry

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object DxAiFunctionRegistry

Implements IDxAiFunctionRegistry

```
public sealed class DxAiFunctionRegistry : IDxAiFunctionRegistry
```

🌟 Constructors 1

DxAiFunctionRegistry(IServiceProvider serviceProvider, IHumanCollaborationService humanCollaboration, IDerivedDxAiInvocationService derivedInvocations, IAmbientLocalGptContext ambientContext, IHumanApprovalExecutionContext approvalExecutionContext, ILocalGptVocabularyService vocabulary, DxAiFunctionHandlerMapService handlerMapService, ILogger<DxAiFunctionRegistry> logger)

```
public DxAiFunctionRegistry(IServiceProvider serviceProvider, IHumanCollaborationService humanCollaboration, IDerivedDxAiInvocationService derivedInvocations, IAmbientLocalGptContext ambientContext, IHumanApprovalExecutionContext approvalExecutionContext, ILocalGptVocabularyService vocabulary, DxAiFunctionHandlerMapService handlerMapService, ILogger<DxAiFunctionRegistry> logger)
```

⚙️ Methods 2

GetFunctions()

```
public IReadOnlyList<DxaichatFunctionInfo> GetFunctions()
```

InvokeAsync(string, DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class DxAiFunctionServiceClient

Namespace LocalGPT . Services Assembly LocalGPT.dll

Scoped control-flow client for DI-backed DXAIFunctions. It deliberately invokes the registry directly instead of making loopback HTTP calls. One scoped client permits one active call, which gives the UI deterministic cancellation and prevents overlapping mutation confirmations.

Inheritance object DxAiFunctionServiceClient

Implements IDxAiFunctionServiceClient IDisposable

```
public sealed class DxAiFunctionServiceClient : IDxAiFunctionServiceClient, IDisposable
```

🌟 Constructors 1

DxAiFunctionServiceClient(IDxAiFunctionRegistry, IChatSessionContext, ILogger<DxAiFunctionServiceClient>)

Scoped control-flow client for DI-backed DXAIFunctions. It deliberately invokes the registry directly instead of making loopback HTTP calls. One scoped client permits one active call, which gives the UI deterministic cancellation and prevents overlapping mutation confirmations.

```
public DxAiFunctionServiceClient(IDxAiFunctionRegistry registry, IChatSessionContext sessionContext, ILogger<DxAiFunctionServiceClient> logger)
```

🐾 Properties 1

CurrentOperationId

```
public Guid? CurrentOperationId { get; }
```

⚙️ Methods 6

CallAsync(string, DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> CallAsync(string functionName, DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

CallAsync(string, object?, bool, bool, string, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> CallAsync(string functionName, object? parameters = null, bool userConfirmed = false, bool automaticInvocation = false, string requestedBy = "CurrentUser", CancellationToken cancellationToken = default)
```

Cancel()

```
public void Cancel()
```

CancelWithReason(string)

```
public void CancelWithReason(string reason)
```

Dispose()

```
public void Dispose()
```

GetFunctions()

```
public IReadOnlyList<DxaichatFunctionInfo> GetFunctions()
```

Class EfChatMemoryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EfChatMemoryService

Implements IChatMemoryService

```
public class EfChatMemoryService : IChatMemoryService
```

🌟 Constructors 1

EfChatMemoryService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, LocalGptDatabaseOptions, ILogger<EfChatMemoryService>, CouncilTextService, IChatMemoryMessageMapper, IChatSessionContext)

```
public EfChatMemoryService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer,
    LocalGptDatabaseOptions databaseOptions, ILogger<EfChatMemoryService> logger, CouncilTextService councilText, IChatMemoryMessageMapper messageMapper,
    IChatSessionContext sessionContext)
```

🔗 Properties 1

DatabasePath

```
public string DatabasePath { get; }
```

⚙️ Methods 7

BuildMemoryBriefingAsync(int, int, CancellationToken)

```
public Task<string> BuildMemoryBriefingAsync(int conversationTake = 5, int thoughtTake = 5, CancellationToken cancellationToken = default)
```

GetConversationsAsync(int, CancellationToken)

```
public Task<IReadOnlyList<ChatMemoryConversationSummary>> GetConversationsAsync(int take = 50, CancellationToken cancellationToken = default)
```

GetMessageFeedbackAsync(Guid, CancellationToken)

```
public Task<IReadOnlyList<ChatMessageFeedbackSnapshot>> GetMessageFeedbackAsync(Guid conversationId, CancellationToken cancellationToken = default)
```

GetRecentThoughtsAsync(int, CancellationToken)

```
public Task<IReadOnlyList<ChatMemoryThought>> GetRecentThoughtsAsync(int take = 12, CancellationToken cancellationToken = default)
```

LoadConversationAsync(Guid, CancellationToken)

```
public Task<ChatMemoryConversationSnapshot?> LoadConversationAsync(Guid conversationId, CancellationToken cancellationToken = default)
```

RecordMessageFeedbackAsync(Guid, int, bool?, string?, CancellationToken)

```
public Task<bool> RecordMessageFeedbackAsync(Guid conversationId, int sortOrder, bool? isPositive, string? comment, CancellationToken cancellationToken =
    default)
```

SaveConversationAsync(string, IReadOnlyList<BlazorChatMessage>, Guid?, CancellationToken)

```
public Task<Guid?> SaveConversationAsync(string providerName, IReadOnlyList<BlazorChatMessage> messages, Guid? conversationId = null, CancellationToken
    cancellationToken = default)
```

Class EmbeddedFirmwarePlanningService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EmbeddedFirmwarePlanningService

Implements IEmbeddedFirmwarePlanningService

```
public sealed class EmbeddedFirmwarePlanningService : IEmbeddedFirmwarePlanningService
```

🌟 Constructors 1

EmbeddedFirmwarePlanningService(IEmbeddedHardwareCatalogService, IEmbeddedWiringService, IEmbeddedTelemetryBridgeService, ILogger<EmbeddedFirmwarePlanningService>)

```
public EmbeddedFirmwarePlanningService(IEmbeddedHardwareCatalogService catalog, IEmbeddedWiringService wiring, IEmbeddedTelemetryBridgeService telemetryBridge, ILogger<EmbeddedFirmwarePlanningService> logger)
```

⚙️ Methods 2

CreateArtifactsAsync(EmbeddedFirmwarePlanRequest, bool, CancellationToken)

```
public Task<EmbeddedFirmwareArtifactResult> CreateArtifactsAsync(EmbeddedFirmwarePlanRequest request, bool userConfirmed, CancellationToken cancellationToken = default)
```

CreatePlanAsync(EmbeddedFirmwarePlanRequest, CancellationToken)

```
public Task<EmbeddedFirmwarePlan> CreatePlanAsync(EmbeddedFirmwarePlanRequest request, CancellationToken cancellationToken = default)
```

Class EmbeddedHardwareCatalogService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EmbeddedHardwareCatalogService

Implements IEmbeddedHardwareCatalogService

```
public sealed class EmbeddedHardwareCatalogService : IEmbeddedHardwareCatalogService
```

🌟 Constructors 1

EmbeddedHardwareCatalogService(IWebHostEnvironment, ILogger<EmbeddedHardwareCatalogService>)

```
public EmbeddedHardwareCatalogService(IWebHostEnvironment environment, ILogger<EmbeddedHardwareCatalogService> logger)
```

⚙️ Methods 5

GetBoardProfileAsync(string, CancellationToken)

```
public Task<EmbeddedBoardProfile?> GetBoardProfileAsync(string boardProfileKey, CancellationToken cancellationToken = default)
```

GetBoardProfilesAsync(CancellationToken)

```
public Task<IReadOnlyList<EmbeddedBoardProfile>> GetBoardProfilesAsync(CancellationToken cancellationToken = default)
```

GetCatalogAsync(CancellationToken)

```
public Task<EmbeddedBoardCatalog> GetCatalogAsync(CancellationToken cancellationToken = default)
```

GetProtocolDescriptorsAsync(CancellationToken)

```
public Task<IReadOnlyList<EmbeddedProtocolDescriptor>> GetProtocolDescriptorsAsync(CancellationToken cancellationToken = default)
```

GetPublisherWorkbenchContract()

```
public EmbeddedPublisherWorkbenchContract GetPublisherWorkbenchContract()
```

Class EmbeddedTelemetryBridgeService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetryBridgeService

Implements IEmbeddedTelemetryBridgeService

```
public sealed class EmbeddedTelemetryBridgeService : IEmbeddedTelemetryBridgeService
```

🌟 Constructors 1

EmbeddedTelemetryBridgeService(IEmbeddedHardwareCatalogService, ILogger<EmbeddedTelemetryBridgeService>)

```
public EmbeddedTelemetryBridgeService(IEmbeddedHardwareCatalogService catalog, ILogger<EmbeddedTelemetryBridgeService> logger)
```

⚙️ Methods 2

CreateOneWireEnvelopeAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
public Task<EmbeddedTelemetryBridgeResult> CreateOneWireEnvelopeAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

PreviewAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
public Task<EmbeddedTelemetryBridgeResult> PreviewAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

Class EmbeddedTelemetryIngressService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EmbeddedTelemetryIngressService

Implements IEmbeddedTelemetryIngressService

```
public sealed class EmbeddedTelemetryIngressService : IEmbeddedTelemetryIngressService
```

🌟 Constructors 1

EmbeddedTelemetryIngressService(IEmbeddedTelemetryBridgeService, ILogger<EmbeddedTelemetryIngressService>)

```
public EmbeddedTelemetryIngressService(IEmbeddedTelemetryBridgeService bridge, ILogger<EmbeddedTelemetryIngressService> logger)
```

⚙️ Methods 2

GetRecent(string?, int)

```
public IReadOnlyList<EmbeddedTelemetrySnapshot> GetRecent(string? deviceId = null, int maximum = 100)
```

PublishAsync(EmbeddedTelemetryBridgeRequest, CancellationToken)

```
public Task<EmbeddedTelemetryIngressResult> PublishAsync(EmbeddedTelemetryBridgeRequest request, CancellationToken cancellationToken = default)
```

Class EmbeddedWiringService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EmbeddedWiringService

Implements IEmbeddedWiringService

```
public sealed class EmbeddedWiringService : IEmbeddedWiringService
```

✨ Constructors 1

EmbeddedWiringService(IEmbeddedHardwareCatalogService, ILogger<EmbeddedWiringService>)

```
public EmbeddedWiringService(IEmbeddedHardwareCatalogService catalog, ILogger<EmbeddedWiringService> logger)
```

⚙️ Methods 2

CreateDraftAsync(string, string, CancellationToken)

```
public Task<EmbeddedWiringDraft> CreateDraftAsync(string boardProfileKey, string name, CancellationToken cancellationToken = default)
```

ValidateAsync(EmbeddedWiringValidationRequest, CancellationToken)

```
public Task<EmbeddedWiringValidationResult> ValidateAsync(EmbeddedWiringValidationRequest request, CancellationToken cancellationToken = default)
```

Class EngineeringBenchmarkService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object EngineeringBenchmarkService

Implements IEngineeringBenchmarkService

```
public sealed class EngineeringBenchmarkService : IEngineeringBenchmarkService
```

✨ Constructors 1

EngineeringBenchmarkService(ICouncilArtifactService, ICouncilKnowledgeService, ILearnBaseKnowledgeImporterService, IArtifactBuildExecutor, ILogger<EngineeringBenchmarkService>, CouncilRuntimeService, CouncilTextService)

```
public EngineeringBenchmarkService(ICouncilArtifactService artifactService, ICouncilKnowledgeService knowledgeService, ILearnBaseKnowledgeImporterService learnBaseImporter, IArtifactBuildExecutor artifactBuildExecutor, ILogger<EngineeringBenchmarkService> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText)
```

⚙️ Methods 2

RunAsync(EngineeringBenchmarkRequest, CancellationToken)

```
public Task<EngineeringBenchmarkResult> RunAsync(EngineeringBenchmarkRequest request, CancellationToken cancellationToken = default)
```

SaveBenchmarkKnowledgeAsync(EngineeringBenchmarkResult, CancellationToken)

```
public Task<Guid?> SaveBenchmarkKnowledgeAsync(EngineeringBenchmarkResult result, CancellationToken cancellationToken)
```


Class ExecuteCodeGenerationReviewFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll
Inheritance object ExecuteCodeGenerationReviewFunction
Implements IDxAiFunctionHandler

```
public sealed class ExecuteCodeGenerationReviewFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ExecuteCodeGenerationReviewFunction(IDxAiFunctionJsonService, ICodeGenerationWorkflowService, ILogger<ExecuteCodeGenerationReviewFunction>)

```
public ExecuteCodeGenerationReviewFunction(IDxAiFunctionJsonService json, ICodeGenerationWorkflowService workflow, ILogger<ExecuteCodeGenerationReviewFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTokentoken = default)
```

Class FeaturePersistenceService

Namespace LocalGPT . Services Assembly LocalGPT.dll

EF Core implementation for durable feature records that are not transient runtime DTOs.

Inheritance object FeaturePersistenceService

Implements IFeaturePersistenceService

```
[DocumentationUpdated("2.1.23")] public sealed class FeaturePersistenceService : IFeaturePersistenceService
```

🌟 Constructors 1

FeaturePersistenceService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, LocalGptCatalogService, ILogger<FeaturePersistenceService>)

EF Core implementation for durable feature records that are not transient runtime DTOs.

```
public FeaturePersistenceService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, LocalGptCatalogService catalog, ILogger<FeaturePersistenceService> logger)
```

⚙️ Methods 20

DeleteCouncilGameSessionAsync(Guid, bool, CancellationToken)

Deletes one GameDirector session record.

```
public Task<bool> DeleteCouncilGameSessionAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteCouncilPromptStarterAsync(Guid, bool, CancellationToken)

Deletes one Council prompt starter.

```
public Task<bool> DeleteCouncilPromptStarterAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteDocumentationBuildAsync(Guid, bool, CancellationToken)

Deletes one documentation build record.

```
public Task<bool> DeleteDocumentationBuildAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteEmbeddedFirmwarePlanAsync(Guid, bool, CancellationToken)

Deletes one embedded firmware plan record.

```
public Task<bool> DeleteEmbeddedFirmwarePlanAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

DeleteLocalizationCatalogAsync(Guid, bool, CancellationToken)

Deletes one localization catalog registration.

```
public Task<bool> DeleteLocalizationCatalogAsync(Guid id, bool userConfirmed, CancellationToken cancellationToken = default)
```

GetCouncilGameSessionAsync(Guid, CancellationToken)

Gets one GameDirector session record.

```
public Task<CouncilGameSessionRecord?> GetCouncilGameSessionAsync(Guid id, CancellationToken cancellationToken = default)
```

GetCouncilGameSessionsAsync(CancellationToken)

Lists GameDirector session records.

```
public Task<IReadOnlyList<CouncilGameSessionRecord>> GetCouncilGameSessionsAsync(CancellationToken cancellationToken = default)
```

GetCouncilPromptStarterAsync(Guid, CancellationToken)

Gets one Council prompt starter.

```
public Task<CouncilPromptStarterConfiguration?> GetCouncilPromptStarterAsync(Guid id, CancellationToken cancellationToken = default)
```

GetCouncilPromptStartersAsync(bool, CancellationToken)

Lists Council prompt starters.

```
public Task<IReadOnlyList<CouncilPromptStarterConfiguration>> GetCouncilPromptStartersAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

GetDocumentationBuildAsync(Guid, CancellationToken)

Gets one documentation build record.

```
public Task<DocumentationBuildRecord?> GetDocumentationBuildAsync(Guid id, CancellationToken cancellationToken = default)
```

GetDocumentationBuildsAsync(CancellationToken)

Lists documentation build records in newest-first order.

```
public Task<IReadOnlyList<DocumentationBuildRecord>> GetDocumentationBuildsAsync(CancellationToken cancellationToken = default)
```

GetEmbeddedFirmwarePlanAsync(Guid, CancellationToken)

Gets one embedded firmware plan record.

```
public Task<EmbeddedFirmwarePlanRecord?> GetEmbeddedFirmwarePlanAsync(Guid id, CancellationToken cancellationToken = default)
```

GetEmbeddedFirmwarePlansAsync(CancellationToken)

Lists embedded firmware plan records.

```
public Task<IReadOnlyList<EmbeddedFirmwarePlanRecord>> GetEmbeddedFirmwarePlansAsync(CancellationToken cancellationToken = default)
```

GetLocalizationCatalogAsync(Guid, CancellationToken)

Gets one localization catalog registration.

```
public Task<LocalizationCatalogRegistration?> GetLocalizationCatalogAsync(Guid id, CancellationToken cancellationToken = default)
```

GetLocalizationCatalogsAsync(bool, CancellationToken)

Lists localization catalog registrations.

```
public Task<IReadOnlyList<LocalizationCatalogRegistration>> GetLocalizationCatalogsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

SaveCouncilGameSessionAsync(SaveFeatureRecordRequest<CouncilGameSessionRecord>, CancellationToken)

Creates or updates one GameDirector session record.

```
public Task<CouncilGameSessionRecord> SaveCouncilGameSessionAsync(SaveFeatureRecordRequest<CouncilGameSessionRecord> request, CancellationToken cancellationToken = default)
```

SaveCouncilPromptStarterAsync(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration>, CancellationToken)

Creates or updates one Council prompt starter.

```
public Task<CouncilPromptStarterConfiguration> SaveCouncilPromptStarterAsync(SaveFeatureRecordRequest<CouncilPromptStarterConfiguration> request, CancellationToken cancellationToken = default)
```

SaveDocumentationBuildAsync(SaveFeatureRecordRequest<DocumentationBuildRecord>, CancellationToken)

Creates or updates one documentation build record.

```
public Task<DocumentationBuildRecord> SaveDocumentationBuildAsync(SaveFeatureRecordRequest<DocumentationBuildRecord> request, CancellationToken cancellationToken = default)
```

SaveEmbeddedFirmwarePlanAsync(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord>, CancellationToken)

Creates or updates one embedded firmware plan record.

```
public Task<EmbeddedFirmwarePlanRecord> SaveEmbeddedFirmwarePlanAsync(SaveFeatureRecordRequest<EmbeddedFirmwarePlanRecord> request, CancellationToken cancellationToken = default)
```

SaveLocalizationCatalogAsync(SaveFeatureRecordRequest<LocalizationCatalogRegistration>, CancellationToken)

Creates or updates one localization catalog registration.

```
public Task<LocalizationCatalogRegistration> SaveLocalizationCatalogAsync(SaveFeatureRecordRequest<LocalizationCatalogRegistration> request, CancellationToken cancellationToken = default)
```

Class FirstRunOnboardingService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Builds LocalGPT's first-run setup guide from database-owned teams and presets plus optional loopback model discovery.

Inheritance object FirstRunOnboardingService

Implements IFirstRunOnboardingService

```
[DocumentationUpdated("2.1.20")] public sealed class FirstRunOnboardingService : IFirstRunOnboardingService
```

🌟 Constructors 1

FirstRunOnboardingService(IVariableStoreService, ISystemVariableDefinitionService, IAIConnectivityProbe, ICouncilTeamConfigurationService, IModelPresetService, ICustomVersion, ILogger<FirstRunOnboardingService>)

Builds LocalGPT's first-run setup guide from database-owned teams and presets plus optional loopback model discovery.

```
public FirstRunOnboardingService(IVariableStoreService variables, ISystemVariableDefinitionService systemVariables, IAIConnectivityProbe connectivityProbe, ICouncilTeamConfigurationService teamConfigurations, IModelPresetService modelPresets, ICustomVersion version, ILogger<FirstRunOnboardingService> logger)
```

⚙️ Methods 2

CompleteAsync(bool, CancellationToken)

Persists that the current user completed or dismissed the first-run guide.

```
public Task CompleteAsync(bool userConfirmed, CancellationToken cancellationToken = default)
```

GetStatusAsync(bool, CancellationToken)

Builds the current onboarding status and optionally probes supported loopback AI providers.

```
public Task<FirstRunOnboardingStatus> GetStatusAsync(bool refreshConnectivity, CancellationToken cancellationToken = default)
```

Class AppleChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object AppleChatProtocolProfile

Implements IChatProtocolProfile

```
public sealed class AppleChatProtocolProfile : IChatProtocolProfile
```

🌟 Constructors 1

AppleChatProtocolProfile(IChatProtocolTextService, ILogger<AppleChatProtocolProfile>)

```
public AppleChatProtocolProfile(IChatProtocolTextService text, ILogger<AppleChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```

Class ChatContentRenderer

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Renders the complete response snapshot supplied by DXAIChat on every stream update. It deliberately does not decode HTML entities: thinking text is encoded by IChatResponseFormatter and must stay text.

Inheritance object ChatContentRenderer

Implements IChatContentRenderer

```
public sealed class ChatContentRenderer : IChatContentRenderer
```

🌟 Constructors 1

ChatContentRenderer(ILocalGptRuntimePolicyDataService, IStructuredTextTranslationService, ILogger<ChatContentRenderer>)

Renders the complete response snapshot supplied by DXAIChat on every stream update. It deliberately does not decode HTML entities: thinking text is encoded by IChatResponseFormatter and must stay text.

```
public ChatContentRenderer(ILocalGptRuntimePolicyDataService runtimePolicy, IStructuredTextTranslationService structuredText, ILogger<ChatContentRenderer> logger)
```

⚙️ Methods 2

NormalizeForRender(string?)

```
public string NormalizeForRender(string? content)
```

Render(string?)

```
public string Render(string? content)
```

Class ChatProtocolProfileCatalog

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object ChatProtocolProfileCatalog

Implements IChatProtocolProfileCatalog

```
public sealed class ChatProtocolProfileCatalog : IChatProtocolProfileCatalog
```

🌟 Constructors 1

ChatProtocolProfileCatalog(IEnumerable<IChatProtocolProfile>, ILogger<ChatProtocolProfileCatalog>)

```
public ChatProtocolProfileCatalog(IEnumerable<IChatProtocolProfile> profiles, ILogger<ChatProtocolProfileCatalog> logger)
```

🐾 Properties 1

Profiles

```
public IReadOnlyList<IChatProtocolProfile> Profiles { get; }
```

⚙️ Methods 1

ResolveExact(ChatResponseProtocol)

```
public IChatProtocolProfile ResolveExact(ChatResponseProtocol protocol)
```

Class ChatProtocolResolver

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object ChatProtocolResolver

Implements IChatProtocolResolver

```
public sealed class ChatProtocolResolver : IChatProtocolResolver
```

✨ Constructors 1

ChatProtocolResolver(IChatProtocolProfileCatalog, ILogger<ChatProtocolResolver>)

```
public ChatProtocolResolver(IChatProtocolProfileCatalog catalog, ILogger<ChatProtocolResolver> logger)
```

⚙️ Methods 1

Resolve(OllamaCoreOptions)

```
public ChatResponseProtocol Resolve(OllamaCoreOptions options)
```

Class ChatProtocolTextService

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object ChatProtocolTextService

Implements IChatProtocolTextService

```
public sealed class ChatProtocolTextService : IChatProtocolTextService
```

✨ Constructors 1

ChatProtocolTextService(ILocalGptRuntimePolicyDataService, ILogger<ChatProtocolTextService>)

```
public ChatProtocolTextService(ILocalGptRuntimePolicyDataService runtimePolicy, ILogger<ChatProtocolTextService> logger)
```

⚙️ Methods 2

ContainsAny(string, LocalGptRuntimeCollection)

```
public bool ContainsAny(string value, LocalGptRuntimeCollection collection)
```

ReplaceAll(string, LocalGptRuntimeCollection)

```
public string ReplaceAll(string text, LocalGptRuntimeCollection collection)
```

Class ChatResponseFormatterFactory

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Creates stateful response formatters that normalize PlainText, think-tag and Harmony streams into one safe Markdown surface.

Inheritance object ChatResponseFormatterFactory

Implements IChatResponseFormatterFactory

```
[DocumentationUpdated("2.1.20")] public sealed class ChatResponseFormatterFactory : IChatResponseFormatterFactory
```

✨ Constructors 1

ChatResponseFormatterFactory(ILoggerFactory, ILocalGptRuntimePolicyDataService, IChatProtocolProfileCatalog, ILogger<ChatResponseFormatterFactory>)

Creates stateful response formatters that normalize PlainText, think-tag and Harmony streams into one safe Markdown surface.

```
public ChatResponseFormatterFactory(ILoggerFactory loggerFactory, ILocalGptRuntimePolicyDataService runtimePolicy, IChatProtocolProfileCatalog catalog, ILogger<ChatResponseFormatterFactory> logger)
```

⚙️ Methods 1

Create(ChatResponseProtocol, string?)

Creates a new independent formatter for one streamed response.

```
public IChatResponseFormatter Create(ChatResponseProtocol protocol, string? missingFinalAnswerNotice = null)
```

Class DeepSeekChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object DeepSeekChatProtocolProfile

Implements IChatProtocolProfile

```
public sealed class DeepSeekChatProtocolProfile : IChatProtocolProfile
```

🌟 Constructors 1

DeepSeekChatProtocolProfile(IChatProtocolTextService, ILogger<DeepSeekChatProtocolProfile>)

```
public DeepSeekChatProtocolProfile(IChatProtocolTextService text, ILogger<DeepSeekChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```

Class GemmaChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object GemmaChatProtocolProfile

Implements IChatProtocolProfile

```
public sealed class GemmaChatProtocolProfile : IChatProtocolProfile
```

🌟 Constructors 1

GemmaChatProtocolProfile(IChatProtocolTextService, ILogger<GemmaChatProtocolProfile>)

```
public GemmaChatProtocolProfile(IChatProtocolTextService text, ILogger<GemmaChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```


Class HarmonyChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object HarmonyChatProtocolProfile

Implements IChatProtocolProfile

```
public sealed class HarmonyChatProtocolProfile : IChatProtocolProfile
```

🌟 Constructors 1

HarmonyChatProtocolProfile(IChatProtocolTextService, ILogger<HarmonyChatProtocolProfile>)

```
public HarmonyChatProtocolProfile(IChatProtocolTextService text, ILogger<HarmonyChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```

Namespace LocalGPT.Services.Formatting

Classes

Renders the complete response snapshot supplied by DXAIChat on every stream update. It deliberately does not decode HTML entities: thinking text is encoded by IChatResponseFormatter and must stay text.

Creates stateful response formatters that normalize PlainText, think-tag and Harmony streams into one safe Markdown surface.

Converts bounded, syntactically valid JSON blocks into a readable Markdown tree while preserving an encoded raw representation. Candidate detection uses the same canonical regex definitions that are seeded into LocalGPT's database-backed regex catalog; JSON syntax is validated by System.Text.Json.

Class PlainTextChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll
Inheritance object PlainTextChatProtocolProfile
Implements IChatProtocolProfile

```
public sealed class PlainTextChatProtocolProfile : IChatProtocolProfile
```

🌟 Constructors 1

PlainTextChatProtocolProfile(ILogger<PlainTextChatProtocolProfile>)

```
public PlainTextChatProtocolProfile(ILogger<PlainTextChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```

Class StructuredTextTranslationService

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Converts bounded, syntactically valid JSON blocks into a readable Markdown tree while preserving an encoded raw representation. Candidate detection uses the same canonical regex definitions that are seeded into LocalGPT's database-backed regex catalog; JSON syntax is validated by System.Text.Json.

Inheritance object StructuredTextTranslationService

Implements IStructuredTextTranslationService

```
public sealed class StructuredTextTranslationService : IStructuredTextTranslationService
```

🌟 Constructors 1

StructuredTextTranslationService(IInitialDataCatalog, ILocalGptRuntimePolicyDataService, IRegexPatternService, ILogger<StructuredTextTranslationService>)

```
public StructuredTextTranslationService(IInitialDataCatalog initialDataCatalog, ILocalGptRuntimePolicyDataService runtimePolicy, IRegexPatternService regexPatterns, ILogger<StructuredTextTranslationService> logger)
```

🔗 Fields 5

JsonFencePatternName

```
public const string JsonFencePatternName = "builtin.json-fence-pattern"
```

JsonKeyTokenPatternName

```
public const string JsonKeyTokenPatternName = "builtin.json-key-token-pattern"
```

JsonPlainStartPatternName

```
public const string JsonPlainStartPatternName = "builtin.json-plain-start-pattern"
```

JsonProtectedBlockPatternName

```
public const string JsonProtectedBlockPatternName = "builtin.json-protected-block-pattern"
```

JsonScalarPatternName

```
public const string JsonScalarPatternName = "builtin.json-scalar-pattern"
```

⚙️ Methods 2

TranslateJson(StructuredJsonTranslationRequest)

```
public StructuredJsonTranslationResult TranslateJson(StructuredJsonTranslationRequest request)
```

TranslatePlainJsonBlocksToMarkdown(string?)

```
public string TranslatePlainJsonBlocksToMarkdown(string? text)
```

Class ThinkTagsChatProtocolProfile

Namespace LocalGPT . Services . Formatting Assembly LocalGPT.dll

Inheritance object ThinkTagsChatProtocolProfile

Implements IChatProtocolProfile

```
public sealed class ThinkTagsChatProtocolProfile : IChatProtocolProfile
```

✨ Constructors 1

ThinkTagsChatProtocolProfile(IChatProtocolTextService, ILogger<ThinkTagsChatProtocolProfile>)

```
public ThinkTagsChatProtocolProfile(IChatProtocolTextService text, ILogger<ThinkTagsChatProtocolProfile> logger)
```

🐾 Properties 2

Priority

```
public int Priority { get; }
```

Protocol

```
public ChatResponseProtocol Protocol { get; }
```

⚙️ Methods 3

MatchesModel(string)

```
public bool MatchesModel(string modelName)
```

NormalizeContent(string)

```
public string NormalizeContent(string value)
```

NormalizeThinking(string)

```
public string NormalizeThinking(string value)
```

Class GetCodeGenerationReviewFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetCodeGenerationReviewFunction

Implements IDxAiFunctionHandler

```
public sealed class GetCodeGenerationReviewFunction : IDxAiFunctionHandler
```

✨ Constructors 1

GetCodeGenerationReviewFunction(IDxAiFunctionJsonService, ICodeGenerationWorkflowService, ILogger<GetCodeGenerationReviewFunction>)

```
public GetCodeGenerationReviewFunction(IDxAiFunctionJsonService json, ICodeGenerationWorkflowService workflow, ILogger<GetCodeGenerationReviewFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class GetCouncilGameFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetCouncilGameFunction

Implements IDxAiFunctionHandler

```
public sealed class GetCouncilGameFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetCouncilGameFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<GetCouncilGameFunction>)

```
public GetCouncilGameFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<GetCouncilGameFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class GetCouncilRuntimeClassFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetCouncilRuntimeClassFunction

Implements IDxAiFunctionHandler

```
public sealed class GetCouncilRuntimeClassFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetCouncilRuntimeClassFunction(ICouncilRuntimeClassService, ILogger<GetCouncilRuntimeClassFunction>)

```
public GetCouncilRuntimeClassFunction(ICouncilRuntimeClassService runtimeClasses, ILogger<GetCouncilRuntimeClassFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class GetEmbeddedHardwareCatalogFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetEmbeddedHardwareCatalogFunction

Implements IDxAiFunctionHandler

```
public sealed class GetEmbeddedHardwareCatalogFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetEmbeddedHardwareCatalogFunction(IEmbeddedHardwareCatalogService, IDxAiFunctionJsonService)

```
public GetEmbeddedHardwareCatalogFunction(IEmbeddedHardwareCatalogService catalog, IDxAiFunctionJsonService json)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class GetFirstRunOnboardingStatusFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Lets Chat and Council members inspect first-run readiness without changing installer or onboarding state.

Inheritance object GetFirstRunOnboardingStatusFunction

Implements IDxAiFunctionHandler

```
[DocumentationUpdated("2.1.20")] public sealed class GetFirstRunOnboardingStatusFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetFirstRunOnboardingStatusFunction(IFirstRunOnboardingService)

Lets Chat and Council members inspect first-run readiness without changing installer or onboarding state.

```
public GetFirstRunOnboardingStatusFunction(IFirstRunOnboardingService onboarding)
```

🐾 Properties 1

Descriptor

Gets the stable read-only DXFunction descriptor.

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

Invokes the read-only onboarding status operation.

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class GetLearningRoundSnapshotFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetLearningRoundSnapshotFunction

Implements IDxAiFunctionHandler

```
public sealed class GetLearningRoundSnapshotFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetLearningRoundSnapshotFunction(ILearningRoundService, ILogger<GetLearningRoundSnapshotFunction>)

```
public GetLearningRoundSnapshotFunction(ILearningRoundService learning, ILogger<GetLearningRoundSnapshotFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class GetLocalGptProjectFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetLocalGptProjectFunction

Implements IDxAiFunctionHandler

```
public sealed class GetLocalGptProjectFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetLocalGptProjectFunction(IDxAiFunctionJsonService, ILocalGptProjectService, ILogger<GetLocalGptProjectFunction>)

```
public GetLocalGptProjectFunction(IDxAiFunctionJsonService json, ILocalGptProjectService projects, ILogger<GetLocalGptProjectFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class GetProjectArchitectureFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetProjectArchitectureFunction

Implements IDxAiFunctionHandler

```
public sealed class GetProjectArchitectureFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetProjectArchitectureFunction(IDxAiFunctionJsonService, ILocalGptProjectService, IProjectArchitectureService, ILogger<GetProjectArchitectureFunction>)

```
public GetProjectArchitectureFunction(IDxAiFunctionJsonService json, ILocalGptProjectService projects, IProjectArchitectureService architecture, ILogger<GetProjectArchitectureFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class GetProjectMaintenanceFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetProjectMaintenanceFunction

Implements IDxAiFunctionHandler

```
public sealed class GetProjectMaintenanceFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetProjectMaintenanceFunction(IDxAiFunctionJsonService, ILocalGptProjectService, IProjectMaintenanceService, ILogger<GetProjectMaintenanceFunction>)

```
public GetProjectMaintenanceFunction(IDxAiFunctionJsonService json, ILocalGptProjectService projects, IProjectMaintenanceService maintenance, ILogger<GetProjectMaintenanceFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```


Class GetPublicArchitectureDirectoryFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetPublicArchitectureDirectoryFunction

Implements IDxAiFunctionHandler

```
public sealed class GetPublicArchitectureDirectoryFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetPublicArchitectureDirectoryFunction(IDxAiFunctionJsonService, IDxAiFunctionRegistry, ILogger<GetPublicArchitectureDirectoryFunction>)

```
public GetPublicArchitectureDirectoryFunction(IDxAiFunctionJsonService json, IDxAiFunctionRegistry registry,
ILogger<GetPublicArchitectureDirectoryFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class GetRegexPatternFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object GetRegexPatternFunction

Implements IDxAiFunctionHandler

```
public sealed class GetRegexPatternFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetRegexPatternFunction(IRegexPatternService, IRegexFunctionParameterService, ILogger<GetRegexPatternFunction>)

```
public GetRegexPatternFunction(IRegexPatternService regexPatterns, IRegexFunctionParameterService parameters, ILogger<GetRegexPatternFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class GetTimeAndStateNowFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Gives AI chat and Council members an explicit clock and a compact, current runtime-state snapshot. The function is read-only and intentionally returns only the three newest bounded log/council rows.

Inheritance object GetTimeAndStateNowFunction

Implements IDxAiFunctionHandler

```
public sealed class GetTimeAndStateNowFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

GetTimeAndStateNowFunction(IApplicationLogReaderService, IOneWirePeerRegistry, IOneWireConnectionRegistry, ICouncilSpoolerService, IHardwareInventoryService, ILogger<GetTimeAndStateNowFunction>)

Gives AI chat and Council members an explicit clock and a compact, current runtime-state snapshot. The function is read-only and intentionally returns only the three newest bounded log/council rows.

```
public GetTimeAndStateNowFunction(IApplicationLogReaderService applicationLogs, IOneWirePeerRegistry peers, IOneWireConnectionRegistry connections, ICouncilSpoolerService councilSpooler, IHardwareInventoryService hardwareInventory, ILogger<GetTimeAndStateNowFunction> logger)
```

🔗 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class HardwareInventoryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Read-only, cached hardware inventory used for council scheduling. It never changes device state. GPU discovery is best-effort and falls back to explicit user-configured routes when vendor tools are unavailable.

Inheritance object HardwareInventoryService

Implements IHardwareInventoryService

```
public sealed class HardwareInventoryService : IHardwareInventoryService
```

🌟 Constructors 1

HardwareInventoryService(ILogger<HardwareInventoryService>)

Read-only, cached hardware inventory used for council scheduling. It never changes device state. GPU discovery is best-effort and falls back to explicit user-configured routes when vendor tools are unavailable.

```
public HardwareInventoryService(ILogger<HardwareInventoryService> logger)
```

⚙️ Methods 1

GetHardwareAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireHardwareDescriptor>> GetHardwareAsync(CancellationToken cancellationToken = default)
```

Namespace LocalGPT.Services

Namespaces

Classes

Runs a bounded, user-approved benchmark against models already installed in the configured local Ollama runtime. It never pulls models, changes global Ollama state, or overwrites an existing preset.

Bounded, process-local operational memory for the current LocalGPT run. It records concise UI and service state only; prompts, message bodies, secrets, uploaded content, generated source, parameters, and full exception text are excluded.

Adapts the multi-model Council runtime to the Microsoft.Extensions.AI chat-client contract.

Parses explicit Council DX function call blocks and sends allowed calls through the existing scoped function client. Catalog exposure and invocation metadata remain the source of truth. A failed function call becomes a readable Council step instead of aborting the whole run.

Creates stable per-turn actor descriptors without granting them state-mutation authority.

Provides deterministic final authority for game controls and coordinates replaceable creature/object subdirectors. A configured low-parameter Council model may review the proposal later, but cannot bypass this service.

Provides one shared control surface for humans and AI players. The deterministic renderer keeps /Chat reactive; a single Council renderer may replace a turn's complete frame through SubmitFrameAsync.

Owns deterministic Council prompt reconstruction, source/artifact generation helpers and shared runtime formatting operations.

Database-owned council team/workflow configuration. System defaults are seeded and merged without overwriting user-edited prompts, roles, capabilities or workflow scripts.

Predicts bounded creature reactions for the next authoritative world step.

Reads bounded metadata from portable PDB and other debug files without loading or executing them.

Resolves generated DocFX artifacts and compiler-generated XML comments without exposing arbitrary filesystem paths.

Bridges compiler-generated XML comments to the existing LocalGPT localization service without changing that service's contract.

Keeps the user-facing DX function catalog in the existing SystemVariables table. This deliberately avoids destructive schema replacement: old databases receive missing records, while user-edited exposure and confirmation settings survive descriptor refreshes and application upgrades.

Serializes DX function catalog synchronization and policy writes across all scoped catalog-service instances.

Builds the scoped DXAI handler directory after the registry has been created. This keeps lazy cycle breaking in the registry while moving validation behavior behind an injected service instead of a static helper.

Scoped control-flow client for DI-backed DXAIFunctions. It deliberately invokes the registry directly instead of making loopback HTTP calls. One scoped client permits one active call, which gives the UI deterministic cancellation and prevents overlapping mutation confirmations.

EF Core implementation for durable feature records that are not transient runtime DTOs.

Builds LocalGPT's first-run setup guide from database-owned teams and presets plus optional loopback model discovery.

Lets Chat and Council members inspect first-run readiness without changing installer or onboarding state.

Gives AI chat and Council members an explicit clock and a compact, current runtime-state snapshot. The function is read-only and intentionally returns only the three newest bounded log/council rows.

Read-only, cached hardware inventory used for council scheduling. It never changes device state. GPU discovery is best-effort and falls back to explicit user-configured routes when vendor tools are unavailable.

Builds a database-grounded learning-round snapshot and persists model-suggested facts/regexes as untrusted self-maintenance knowledge. It never promotes model output to user-approved authority.

Database-backed regular-expression functions used by LocalGPT itself and advertised through the same DI/DX-function/1-Wire discovery path as every other council capability.

Configures the optional LocalGPT logging providers during composition-root startup.

Preserves the shell sidebar state while creating application-relative navigation URLs.

Loads source-controlled organic add-on manifests. Offline manifests are discovery metadata only; they become available for invocation only when the matching trusted 1-Wire peer is connected.

Owns the first-run council-team seed model. Runtime edits remain database-owned by CouncilTeamConfigurationService.

Bounded benchmark and council review for provider-qualified models. The service does not download models or alter provider-global settings. Applying a recommendation creates or updates a user-approved LocalGPT model preset whose routes retain provider, endpoint and provider model name.

Discovers and opens provider-qualified model sessions. A model name is never treated as a globally unique address: provider kind and endpoint are always retained with it.

Invokes only a public method that the local user explicitly enabled in the database-backed catalog. Parameter binding is typed from the method signature; the caller cannot choose an arbitrary CLR type or method name.

Predicts bounded reactions from doors, switches, pickups and hazards.

Downloads a user-selected public GitHub repository or webpage into the same local learn-base style cache used by LocalGPT, lists every returned file, applies a regex file policy, and then delegates database extraction to the existing learn-base importer.

Decorates scoped and transient LocalGPT interface services with bounded method-level operational logging. Singleton services remain DI-owned and use their explicit service logging so the decorator can never resolve a scoped dependency from the root provider.

Observes intentionally concurrent work so exceptions cannot become unobserved Tasks. The runner is process-scoped, but every operation must carry its owning component/service name.

Owns LocalGPT's selectable theme catalog and the two independently selectable theme layers for one Blazor circuit. The shell theme controls LocalGPT page surfaces and Bootstrap metadata; the component theme is applied through DevExpress' supported DevExpress.Blazor.IThemeChangeService .

Class HumanCollaborationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object HumanCollaborationService

Implements IHumanCollaborationService

```
public sealed class HumanCollaborationService : IHumanCollaborationService
```

🌟 Constructors 1

HumanCollaborationService(ILocalGptVocabularyService, IDbContextFactory<LocalGptMemoryDbContext>, IAmbientLocalGptContext, IComponentActivityService, ILocalGptRuntimePolicyDataService, ILogger<HumanCollaborationService>)

```
public HumanCollaborationService(ILocalGptVocabularyService vocabulary, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory,
IAmbientLocalGptContext ambientContext, IComponentActivityService componentActivity, ILocalGptRuntimePolicyDataService runtimePolicy,
ILogger<HumanCollaborationService> logger)
```

⚙️ Methods 16

AuthorizeOrEnqueueAsync(HumanApprovalRequestSpec, bool, CancellationToken)

```
public Task<HumanApprovalGateResult> AuthorizeOrEnqueueAsync(HumanApprovalRequestSpec request, bool directHumanConfirmation = false, CancellationToken
cancellationToken = default)
```

BeginCouncilRun(Guid, IReadOnlyList<string>)

```
public void BeginCouncilRun(Guid runId, IReadOnlyList<string> members)
```

BuildCouncilBriefingAsync(Guid, int, CancellationToken)

```
public Task<string> BuildCouncilBriefingAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken = default)
```

DrainContributionsAsync(Guid, int, CancellationToken)

```
public Task<IReadOnlyList<HumanCouncilContribution>> DrainContributionsAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken =
default)
```

EndCouncilRun(Guid)

```
public void EndCouncilRun(Guid runId)
```

GetGateStatusAsync(Guid, int, string, HumanCollaborationBoundary, CancellationToken)

```
public Task<HumanCollaborationGateStatus> GetGateStatusAsync(Guid councilRunId, int upcomingRound, string upcomingPhase, HumanCollaborationBoundary
boundary, CancellationToken cancellationToken = default)
```

GetProfileAsync(CancellationToken)

```
public Task<HumanCouncilParticipantProfile> GetProfileAsync(CancellationToken cancellationToken = default)
```

GetSnapshotAsync(bool, int, CancellationToken)

```
public Task<HumanCollaborationSnapshot> GetSnapshotAsync(bool includeResolved = true, int take = 80, CancellationToken cancellationToken = default)
```

HasRequiredPendingInputAsync(Guid, CancellationToken)

```
public Task<bool> HasRequiredPendingInputAsync(Guid councilRunId, CancellationToken cancellationToken = default)
```

MarkContributionsEvaluatedAsync(Guid, int, string, CancellationToken)

```
public Task MarkContributionsEvaluatedAsync(Guid councilRunId, int afterRound, string evaluation, CancellationToken cancellationToken = default)
```

QueueContributionAsync(Guid, string, CancellationToken)

```
public Task<HumanCouncilContribution> QueueContributionAsync(Guid councilRunId, string content, CancellationToken cancellationToken = default)
```

QueueUserMessageAsync(Guid, string, CancellationToken)

```
public Task<HumanCouncilContribution> QueueUserMessageAsync(Guid councilRunId, string content, CancellationToken cancellationToken = default)
```

ReadQueuedContributionsAsync(Guid, int, CancellationToken)

```
public Task<IReadOnlyList<HumanCouncilContribution>> ReadQueuedContributionsAsync(Guid councilRunId, int currentRound, CancellationToken cancellationToken
= default)
```

ResolveRequestAsync(Guid, HumanDecisionSubmission, CancellationToken)

```
public Task<HumanCollaborationRequest?> ResolveRequestAsync(Guid requestId, HumanDecisionSubmission submission, CancellationToken cancellationToken =
default)
```

SaveProfileAsync(HumanCouncilParticipantProfile, CancellationToken)

```
public Task<HumanCouncilParticipantProfile> SaveProfileAsync(HumanCouncilParticipantProfile profile, CancellationToken cancellationToken = default)
```

UpdateCouncilRun(Guid, int, string, bool)

```
public void UpdateCouncilRun(Guid runId, int currentRound, string phase, bool isWaitingForFinalHumanInput = false)
```

⚡ Events 2

Changed

```
public event Action? Changed
```

DirectUserMessageQueued

```
public event Action<HumanCouncilContribution>? DirectUserMessageQueued
```

api/LocalGPT.Services.ImportProjectTextDocumentFunction.html

Class ImportProjectTextDocumentFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ImportProjectTextDocumentFunction

Implements IDxAiFunctionHandler

```
public sealed class ImportProjectTextDocumentFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ImportProjectTextDocumentFunction(IDxAiFunctionJsonService, ISafeTextDocumentService, ILogger<ImportProjectTextDocumentFunction>)

```
public ImportProjectTextDocumentFunction(IDxAiFunctionJsonService json, ISafeTextDocumentService documents, ILogger<ImportProjectTextDocumentFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

api/LocalGPT.Services.ImportRemoteKnowledgeFunction.html

Class ImportRemoteKnowledgeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ImportRemoteKnowledgeFunction

Implements IDxAiFunctionHandler

```
public sealed class ImportRemoteKnowledgeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ImportRemoteKnowledgeFunction(IRemoteKnowledgeImportService, RemoteImportDxParameterReader, ILogger<ImportRemoteKnowledgeFunction>)

```
public ImportRemoteKnowledgeFunction(IRemoteKnowledgeImportService importer, RemoteImportDxParameterReader parameters, ILogger<ImportRemoteKnowledgeFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class InspectDebugArtifactFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object InspectDebugArtifactFunction

Implements IDxAiFunctionHandler

```
public sealed class InspectDebugArtifactFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InspectDebugArtifactFunction(IDxAiFunctionJsonService, IDebugArtifactInspectionService, ILogger<InspectDebugArtifactFunction>)

```
public InspectDebugArtifactFunction(IDxAiFunctionJsonService json, IDebugArtifactInspectionService inspector, ILogger<InspectDebugArtifactFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class InspectJsonTextFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object InspectJsonTextFunction

Implements IDxAiFunctionHandler

```
public sealed class InspectJsonTextFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InspectJsonTextFunction(IStructuredTextTranslationService, ILogger<InspectJsonTextFunction>)

```
public InspectJsonTextFunction(IStructuredTextTranslationService translator, ILogger<InspectJsonTextFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class InspectRemoteKnowledgeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object InspectRemoteKnowledgeFunction

Implements IDxAiFunctionHandler

```
public sealed class InspectRemoteKnowledgeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InspectRemoteKnowledgeFunction(IRemoteKnowledgeImportService, RemoteImportDxParameterReader, ILogger<InspectRemoteKnowledgeFunction>)

```
public InspectRemoteKnowledgeFunction(IRemoteKnowledgeImportService importer, RemoteImportDxParameterReader parameters,
ILogger<InspectRemoteKnowledgeFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class InvokeConfiguredPublicServiceMethodFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object InvokeConfiguredPublicServiceMethodFunction

Implements IDxAiFunctionHandler

```
public sealed class InvokeConfiguredPublicServiceMethodFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InvokeConfiguredPublicServiceMethodFunction(IPublicServiceMethodInvoker, ILogger<InvokeConfiguredPublicServiceMethodFunction>)

```
public InvokeConfiguredPublicServiceMethodFunction(IPublicServiceMethodInvoker invoker, ILogger<InvokeConfiguredPublicServiceMethodFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class KnowledgeRatingService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object KnowledgeRatingService

Implements IKnowledgeRatingService

```
public sealed class KnowledgeRatingService : IKnowledgeRatingService
```

✨ Constructors 1

KnowledgeRatingService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<KnowledgeRatingService>)

```
public KnowledgeRatingService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer,
    ILogger<KnowledgeRatingService> logger)
```

⚙️ Methods 2

GetRatingsAsync(Guid, CancellationToken)

```
public Task<IReadOnlyList<CouncilKnowledgeUserRating>> GetRatingsAsync(Guid knowledgeEntryId, CancellationToken cancellationToken = default)
```

SaveRatingAsync(CouncilKnowledgeUserRating, bool, CancellationToken)

```
public Task<CouncilKnowledgeUserRating> SaveRatingAsync(CouncilKnowledgeUserRating rating, bool userConfirmed, CancellationToken cancellationToken =
    default)
```

Class LearnBaseKnowledgeImporterService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object LearnBaseKnowledgeImporterService

Implements ILearnBaseKnowledgeImporterService

```
public sealed class LearnBaseKnowledgeImporterService : ILearnBaseKnowledgeImporterService
```

✨ Constructors 1

LearnBaseKnowledgeImporterService(ICouncilKnowledgeService, ILogger<LearnBaseKnowledgeImporterService>, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService, ILocalGptRuntimePolicyDataService, IRegexPatternService)

```
public LearnBaseKnowledgeImporterService(ICouncilKnowledgeService knowledgeService, ILogger<LearnBaseKnowledgeImporterService> logger,
    CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog, ILocalGptRuntimePolicyDataService runtimePolicy,
    IRegexPatternService regexPatterns)
```

⚙️ Methods 1

ImportAsync(LearnBaseImportRequest, CancellationToken)

```
public Task<LearnBaseImportResult> ImportAsync(LearnBaseImportRequest request, CancellationToken cancellationToken = default)
```


Class LearningRoundService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Builds a database-grounded learning-round snapshot and persists model-suggested facts/regexes as untrusted self-maintenance knowledge. It never promotes model output to user-approved authority.

Inheritance object LearningRoundService

Implements [ILearningRoundService](#)

```
public sealed class LearningRoundService : ILearningRoundService
```

✨ Constructors 1

LearningRoundService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ICouncilKnowledgeService, IRegexPatternService, ILogger<LearningRoundService>)

Builds a database-grounded learning-round snapshot and persists model-suggested facts/regexes as untrusted self-maintenance knowledge. It never promotes model output to user-approved authority.

```
public LearningRoundService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ICouncilKnowledgeService knowledgeService, IRegexPatternService regexPatternService, ILogger<LearningRoundService> logger)
```

⚙️ Methods 2

BuildSnapshotAsync(int, CancellationToken)

```
public Task<LearningRoundSnapshot> BuildSnapshotAsync(int takePerSource = 200, CancellationToken cancellationToken = default)
```

MaintainAsync(LearningMaintenanceRequest, CancellationToken)

```
public Task<LearningMaintenanceResult> MaintainAsync(LearningMaintenanceRequest request, CancellationToken cancellationToken = default)
```

Class ListChatMemoryConversationsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListChatMemoryConversationsFunction

Implements [IDxAiFunctionHandler](#)

```
public sealed class ListChatMemoryConversationsFunction : IDxAiFunctionHandler
```

✨ Constructors 1

ListChatMemoryConversationsFunction(IChatMemoryService, ILogger<ListChatMemoryConversationsFunction>)

```
public ListChatMemoryConversationsFunction(IChatMemoryService memory, ILogger<ListChatMemoryConversationsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ListCodeGenerationReviewsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListCodeGenerationReviewsFunction

Implements IDxAiFunctionHandler

```
public sealed class ListCodeGenerationReviewsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListCodeGenerationReviewsFunction(IDxAiFunctionJsonService, ICodeGenerationWorkflowService, ILogger<ListCodeGenerationReviewsFunction>)

```
public ListCodeGenerationReviewsFunction(IDxAiFunctionJsonService json, ICodeGenerationWorkflowService workflow,
ILogger<ListCodeGenerationReviewsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ListCouncilKnowledgeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListCouncilKnowledgeFunction

Implements IDxAiFunctionHandler

```
public sealed class ListCouncilKnowledgeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListCouncilKnowledgeFunction(ICouncilKnowledgeService, ILogger<ListCouncilKnowledgeFunction>)

```
public ListCouncilKnowledgeFunction(ICouncilKnowledgeService knowledge, ILogger<ListCouncilKnowledgeFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ListCouncilRuntimeClassesFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListCouncilRuntimeClassesFunction

Implements IDxAiFunctionHandler

```
public sealed class ListCouncilRuntimeClassesFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListCouncilRuntimeClassesFunction(ICouncilRuntimeClassService, ILogger<ListCouncilRuntimeClassesFunction>)

```
public ListCouncilRuntimeClassesFunction(ICouncilRuntimeClassService runtimeClasses, ILogger<ListCouncilRuntimeClassesFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ListLocalGptProjectsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListLocalGptProjectsFunction

Implements IDxAiFunctionHandler

```
public sealed class ListLocalGptProjectsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListLocalGptProjectsFunction(ILocalGptProjectService, ILogger<ListLocalGptProjectsFunction>)

```
public ListLocalGptProjectsFunction(ILocalGptProjectService projects, ILogger<ListLocalGptProjectsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ListRecentApplicationLogsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListRecentApplicationLogsFunction

Implements IDxAiFunctionHandler

```
public sealed class ListRecentApplicationLogsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListRecentApplicationLogsFunction(IApplicationLogReaderService, ILogger<ListRecentApplicationLogsFunction>)

```
public ListRecentApplicationLogsFunction(IApplicationLogReaderService applicationLogs, ILogger<ListRecentApplicationLogsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ListRegexPatternsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Database-backed regular-expression functions used by LocalGPT itself and advertised through the same DI/DX-function/1-Wire discovery path as every other council capability.

Inheritance object ListRegexPatternsFunction

Implements IDxAiFunctionHandler

```
public sealed class ListRegexPatternsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListRegexPatternsFunction(IRegexPatternService, ILogger<ListRegexPatternsFunction>)

Database-backed regular-expression functions used by LocalGPT itself and advertised through the same DI/DX-function/1-Wire discovery path as every other council capability.

```
public ListRegexPatternsFunction(IRegexPatternService regexPatterns, ILogger<ListRegexPatternsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ListSqliteTablesFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ListSqliteTablesFunction

Implements IDxAiFunctionHandler

```
public sealed class ListSqliteTablesFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ListSqliteTablesFunction(IDxAiFunctionJsonService, ISqliteTableEditorService, ILogger<ListSqliteTablesFunction>)

```
public ListSqliteTablesFunction(IDxAiFunctionJsonService json, ISqliteTableEditorService editor, ILogger<ListSqliteTablesFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class LocalGptCatalogService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object LocalGptCatalogService

```
public sealed class LocalGptCatalogService
```

🌟 Constructors 1

LocalGptCatalogService(ILocalGptRuntimePolicyDataService, ILogger<LocalGptCatalogService>)

```
public LocalGptCatalogService(ILocalGptRuntimePolicyDataService runtimePolicy, ILogger<LocalGptCatalogService> logger)
```

🐾 Properties 133

AdviceOnlyPromptPattern

```
public Regex AdviceOnlyPromptPattern { get; }
```

AiHostExperimentPattern

```
public Regex AiHostExperimentPattern { get; }
```

AiHostSetupPattern

```
public Regex AiHostSetupPattern { get; }
```

AllowedUploadExtensions

```
public List<string> AllowedUploadExtensions { get; }
```

AllowedUploadMimeTypes

```
public List<string> AllowedUploadMimeTypes { get; }
```

ArchitectureReferenceLookOptions

```
public string[] ArchitectureReferenceLookOptions { get; }
```

ArchitectureRenderModeOptions

```
public string[] ArchitectureRenderModeOptions { get; }
```

ArchitectureSolutionShapeOptions

```
public string[] ArchitectureSolutionShapeOptions { get; }
```

ArchitectureUiStackOptions

```
public string[] ArchitectureUiStackOptions { get; }
```

ArtifactTextExtensions

```
public FrozenSet<string> ArtifactTextExtensions { get; }
```

BinaryDiagnosticExtensions

```
public FrozenSet<string> BinaryDiagnosticExtensions { get; }
```

BinaryExtensions

```
public FrozenSet<string> BinaryExtensions { get; }
```

BlazorFrontendPattern

```
public Regex BlazorFrontendPattern { get; }
```

BlockingArtifactDecisionPattern

```
public Regex BlockingArtifactDecisionPattern { get; }
```

BotBackendPattern

```
public Regex BotBackendPattern { get; }
```

CapabilityGapBlockPattern

```
public Regex CapabilityGapBlockPattern { get; }
```

ConcreteDotNetArtifactPattern

```
public Regex ConcreteDotNetArtifactPattern { get; }
```

ConcreteMinecraftArtifactPattern

```
public Regex ConcreteMinecraftArtifactPattern { get; }
```

CouncilKnowledgeEntryNew

```
public CouncilKnowledgeEntry CouncilKnowledgeEntryNew { get; }
```

CouncilPromptFencePattern

```
public Regex CouncilPromptFencePattern { get; }
```

CouncilRequestBlockPattern

```
public Regex CouncilRequestBlockPattern { get; }
```

CouncilSessionName

```
public string CouncilSessionName { get; }
```

DatapackPattern

```
public Regex DatapackPattern { get; }
```

DebugExtensions

```
public FrozenSet<string> DebugExtensions { get; }
```

DefaultContextTokens

```
public int DefaultContextTokens { get; }
```

DefaultCouncilContextTokens

```
public int DefaultCouncilContextTokens { get; }
```

DefaultCouncilOutputTokens

```
public int DefaultCouncilOutputTokens { get; }
```

DefaultGradleVersion

```
public string DefaultGradleVersion { get; }
```

DefaultHeavyModelGpuLayers

```
public int DefaultHeavyModelGpuLayers { get; }
```

DefaultJavaVersion

```
public string DefaultJavaVersion { get; }
```

DefaultMaxParallelModels

```
public int DefaultMaxParallelModels { get; }
```

DefaultMaxPromptCharacters

```
public int DefaultMaxPromptCharacters { get; }
```

DefaultMinecraftVersion

```
public string DefaultMinecraftVersion { get; }
```

DefaultOllamaEndpoint

```
public string DefaultOllamaEndpoint { get; }
```

DefaultOllamaUri

```
public string DefaultOllamaUri { get; }
```

DetectedOllamaSessionPrefix

```
public string DetectedOllamaSessionPrefix { get; }
```

DevExpressDocumentPattern

```
public Regex DevExpressDocumentPattern { get; }
```

DevExpressImportPattern

```
public Regex DevExpressImportPattern { get; }
```

DevExpressRegistrationPattern

```
public Regex DevExpressRegistrationPattern { get; }
```

DeveloperExecutionIntentPattern

```
public Regex DeveloperExecutionIntentPattern { get; }
```

DevelopmentRequestPattern

```
public Regex DevelopmentRequestPattern { get; }
```

DotNetPattern

```
public Regex DotNetPattern { get; }
```

DownloadUrlPattern

```
public Regex DownloadUrlPattern { get; }
```

ExcludedDirectoryNames

```
public FrozenSet<string> ExcludedDirectoryNames { get; }
```

ExplicitArtifactCreationCommandPattern

```
public Regex ExplicitArtifactCreationCommandPattern { get; }
```

ExplicitArtifactIntentPattern

```
public Regex ExplicitArtifactIntentPattern { get; }
```

ExplicitDoNotGenerateUntilUserDecisionPattern

```
public Regex ExplicitDoNotGenerateUntilUserDecisionPattern { get; }
```

ExportFormatPattern

```
public Regex ExportFormatPattern { get; }
```

FabricLoaderVersion

```
public string FabricLoaderVersion { get; }
```

FrontendPattern

```
public Regex FrontendPattern { get; }
```

GenerateAiHostChatRazor

```
public string GenerateAiHostChatRazor { get; }
```

GenerateAiHostHardwareRazor

```
public string GenerateAiHostHardwareRazor { get; }
```

GenerateAiHostLogsRazor

```
public string GenerateAiHostLogsRazor { get; }
```

GenerateAiHostModelDownloadsRazor

```
public string GenerateAiHostModelDownloadsRazor { get; }
```

GenerateAiHostRunnerPluginsRazor

```
public string GenerateAiHostRunnerPluginsRazor { get; }
```

GenerateAiHostRunningModelsRazor

```
public string GenerateAiHostRunningModelsRazor { get; }
```


GenerateAiHostSettingsRazor

```
public string GenerateAiHostSettingsRazor { get; }
```

GenerateAiHostTemplatesRazor

```
public string GenerateAiHostTemplatesRazor { get; }
```

GenerateSolutionAppRazor

```
public string GenerateSolutionAppRazor { get; }
```

GenerateSolutionCss

```
public string GenerateSolutionCss { get; }
```

GenerateSolutionProjectFile

```
public string GenerateSolutionProjectFile { get; }
```

GenerateSolutionRoutesRazor

```
public string GenerateSolutionRoutesRazor { get; }
```

GenerateSourceFidelityRazor

```
public string GenerateSourceFidelityRazor { get; }
```

HelpfulSourceLinePattern

```
public Regex HelpfulSourceLinePattern { get; }
```

ImplementationChoicePattern

```
public Regex ImplementationChoicePattern { get; }
```

ImplementationDecisionPattern

```
public Regex ImplementationDecisionPattern { get; }
```

JsonOptions

```
public JsonSerializerOptions JsonOptions { get; }
```

KnowledgeFiles

```
public string[] KnowledgeFiles { get; }
```

LeadingSlashCommandPattern

```
public Regex LeadingSlashCommandPattern { get; }
```

LearnBaseDuplicatePolicySummary

```
public string LearnBaseDuplicatePolicySummary { get; }
```

LearnBaseFilePolicySummary

```
public string LearnBaseFilePolicySummary { get; }
```

LearnBaseKnownExtensions

```
public FrozenSet<string> LearnBaseKnownExtensions { get; }
```

LearnBasePresetList

```
public string LearnBasePresetList { get; }
```

LearnBasePresets

```
public IReadOnlyList<LearnBasePreset> LearnBasePresets { get; }
```

LearnBaseScanProfiles

```
public IReadOnlyList<LearnBaseScanProfile> LearnBaseScanProfiles { get; }
```

LivingCitiesPrompt

```
public string LivingCitiesPrompt { get; }
```

LocalGptReplacementPattern

```
public Regex LocalGptReplacementPattern { get; }
```

LoggingPattern

```
public Regex LoggingPattern { get; }
```

MalformedStorageTargetPattern

```
public Regex MalformedStorageTargetPattern { get; }
```

MaxArtifactTextFileBytes

```
public long MaxArtifactTextFileBytes { get; }
```

MaxBinaryStringCharacters

```
public int MaxBinaryStringCharacters { get; }
```

MaxBootstrapCharacters

```
public int MaxBootstrapCharacters { get; }
```

MaxContextCharacters

```
public int MaxContextCharacters { get; }
```

MaxContextTokens

```
public int MaxContextTokens { get; }
```

MaxCouncilContextTokens

```
public int MaxCouncilContextTokens { get; }
```

MaxCouncilOutputTokens

```
public int MaxCouncilOutputTokens { get; }
```

MaxDxAiChatPromptCharacters

```
public int MaxDxAiChatPromptCharacters { get; }
```

MaxExcerptCharactersPerFile

```
public int MaxExcerptCharactersPerFile { get; }
```

MaxExtractedBytes

```
public long MaxExtractedBytes { get; }
```

MaxFiles

```
public int MaxFiles { get; }
```

MaxOutputTokens

```
public int MaxOutputTokens { get; }
```

MaxParticipants

```
public int MaxParticipants { get; }
```

MaxPromptCharacters

```
public int MaxPromptCharacters { get; }
```

MaxSingleConversationMessageCharacters

```
public int MaxSingleConversationMessageCharacters { get; }
```

MaxSingleFileBytes

```
public long MaxSingleFileBytes { get; }
```

MaxTotalFileBytes

```
public long MaxTotalFileBytes { get; }
```

MaxUploadBytes

```
public int MaxUploadBytes { get; }
```

MaxUploadFiles

```
public int MaxUploadFiles { get; }
```

MaxVisiblePromptCharacters

```
public int MaxVisiblePromptCharacters { get; }
```

MaxZipEntries

```
public int MaxZipEntries { get; }
```

MaxZipEntryBytes

```
public long MaxZipEntryBytes { get; }
```

MinContextTokens

```
public int MinContextTokens { get; }
```

MinCouncilContextTokens

```
public int MinCouncilContextTokens { get; }
```

MinCouncilOutputTokens

```
public int MinCouncilOutputTokens { get; }
```

MinOutputTokens

```
public int MinOutputTokens { get; }
```

MinecraftPattern

```
public Regex MinecraftPattern { get; }
```

MinecraftSkeletonMatrixPattern

```
public Regex MinecraftSkeletonMatrixPattern { get; }
```

MinecraftVersionPattern

```
public Regex MinecraftVersionPattern { get; }
```

MissingFeaturePattern

```
public Regex MissingFeaturePattern { get; }
```

ModIdCleaner

```
public Regex ModIdCleaner { get; }
```

NameCleaner

```
public Regex NameCleaner { get; }
```

OllamaModeAutoGpu

```
public string OllamaModeAutoGpu { get; }
```

OllamaModeLimitedGpu

```
public string OllamaModeLimitedGpu { get; }
```

OllamaModeSafeCpu

```
public string OllamaModeSafeCpu { get; }
```

PackagePartCleaner

```
public Regex PackagePartCleaner { get; }
```

PackageReferencePattern

```
public Regex PackageReferencePattern { get; }
```

RootStorageRemovePattern

```
public Regex RootStorageRemovePattern { get; }
```

Routes

```
public List<TestLabRoute> Routes { get; }
```

SafeSandboxConsentPattern

```
public Regex SafeSandboxConsentPattern { get; }
```

SensitiveNamePattern

```
public Regex SensitiveNamePattern { get; }
```

SourceExtensions

```
public FrozenSet<string> SourceExtensions { get; }
```

StreamStatusPattern

```
public Regex StreamStatusPattern { get; }
```

TacosPortalPattern

```
public Regex TacosPortalPattern { get; }
```

TargetFrameworkPattern

```
public Regex TargetFrameworkPattern { get; }
```

TextExtensions

```
public FrozenSet<string> TextExtensions { get; }
```

ThinkingBlockPattern

```
public Regex ThinkingBlockPattern { get; }
```

TruncatedTailPattern

```
public Regex TruncatedTailPattern { get; }
```

Utf8NoBom

```
public Encoding Utf8NoBom { get; }
```

WhitespacePattern

```
public Regex WhitespacePattern { get; }
```

WholeSolutionPattern

```
public Regex WholeSolutionPattern { get; }
```

WordPattern

```
public Regex WordPattern { get; }
```

omission

```
public string omission { get; }
```

shortOmission

```
public string shortOmission { get; }
```

 Methods 1

GetSuggestion()

Creates the maintained generic and Council-team prompt suggestion catalog.

```
public List<PromptSuggestion> GetSuggestion()
```

Class LocalGptProjectService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object LocalGptProjectService

Implements ILocalGptProjectService

```
public sealed class LocalGptProjectService : ILocalGptProjectService
```

✨ Constructors 1

LocalGptProjectService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<LocalGptProjectService>)

```
public LocalGptProjectService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<LocalGptProjectService> logger)
```

⚙️ Methods 7

AddTopicAsync(Guid, AddLocalGptProjectTopicRequest, CancellationToken)

```
public Task<LocalGptProjectTopic> AddTopicAsync(Guid projectId, AddLocalGptProjectTopicRequest request, CancellationToken cancellationToken = default)
```

AddVersionAsync(Guid, AddLocalGptProjectVersionRequest, CancellationToken)

```
public Task<LocalGptProjectVersion> AddVersionAsync(Guid projectId, AddLocalGptProjectVersionRequest request, CancellationToken cancellationToken = default)
```

BuildProjectBriefingAsync(Guid?, Guid?, CancellationToken)

```
public Task<string> BuildProjectBriefingAsync(Guid? projectId, Guid? projectTopicId, CancellationToken cancellationToken = default)
```

GetProjectAsync(Guid, CancellationToken)

```
public Task<LocalGptProjectDetails?> GetProjectAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetProjectsAsync(bool, CancellationToken)

```
public Task<IReadOnlyList<LocalGptProjectSummary>> GetProjectsAsync(bool includeArchived = false, CancellationToken cancellationToken = default)
```

LinkKnowledgeAsync(Guid, LinkProjectTopicKnowledgeRequest, CancellationToken)

```
public Task LinkKnowledgeAsync(Guid projectTopicId, LinkProjectTopicKnowledgeRequest request, CancellationToken cancellationToken = default)
```

SaveProjectAsync(SaveLocalGptProjectRequest, CancellationToken)

```
public Task<LocalGptProject> SaveProjectAsync(SaveLocalGptProjectRequest request, CancellationToken cancellationToken = default)
```

Class LocalGptRequestFactoryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object LocalGptRequestFactoryService

Implements ILocalGptRequestFactoryService

```
public sealed class LocalGptRequestFactoryService : ILocalGptRequestFactoryService
```

🌟 Constructors 1

LocalGptRequestFactoryService(ILogger<LocalGptRequestFactoryService>)

```
public LocalGptRequestFactoryService(ILogger<LocalGptRequestFactoryService> logger)
```

⚙️ Methods 9

CreateArtifactRequest()

```
public SaveProjectArtifactRequest CreateArtifactRequest()
```

CreateCompilerInstallationRequest()

```
public SaveProjectCompilerInstallationRequest CreateCompilerInstallationRequest()
```

CreateProjectRequest()

```
public SaveLocalGptProjectRequest CreateProjectRequest()
```

CreateRequirementLinkRequest()

```
public SaveProjectRequirementLinkRequest CreateRequirementLinkRequest()
```

CreateRequirementRequest()

```
public SaveProjectRequirementRequest CreateRequirementRequest()
```

CreateRevisionRequest()

```
public SaveProjectRevisionRequest CreateRevisionRequest()
```

CreateTopicRequest()

```
public AddLocalGptProjectTopicRequest CreateTopicRequest()
```

CreateVersionRequest(string)

```
public AddLocalGptProjectVersionRequest CreateVersionRequest(string path = "")
```

CreateWorkspaceRootRequest()

```
public SaveProjectWorkspaceRootRequest CreateWorkspaceRootRequest()
```

Namespace LocalGPT.Services.Localization

Classes

Interfaces

Implements open LocalGPT localization catalogs with English fallback, built-in defaults and persistent user overrides.

Reads built-in localization catalogs and persistent user-supplied culture overrides.

Interface ILocalGptLocalizationService

Namespace LocalGPT . Services . Localization Assembly LocalGPT.dll

Reads built-in localization catalogs and persistent user-supplied culture overrides.

```
[DocumentationUpdated("2.2.8")] public interface ILocalGptLocalizationService
```

Methods 12

BuildCultureRedirectUrl(string?, string)

Adds an explicit request culture to one validated local return URL.

```
string BuildCultureRedirectUrl(string? returnUrl, string culture)
```

BuildCultureReturnUrl(string)

Builds a local return URL without stale culture query values.

```
string BuildCultureReturnUrl(string absoluteUri)
```

BuildCultureSelectionUrl(string, string)

Builds the absolute application endpoint used to select and persist one culture.

```
string BuildCultureSelectionUrl(string absoluteUri, string culture)
```

FormatValidationErrors(LocalizationCatalogValidationResult)

Formats validation errors for a UI or API status surface.

```
string FormatValidationErrors(LocalizationCatalogValidationResult validation)
```

Get(string, string?, string?)

Gets one localized value with English and caller-provided fallback behavior.

```
string Get(string key, string? culture = null, string? fallback = null)
```

GetAvailableCultures()

Gets all cultures represented by built-in or user catalogs.

```
IReadOnlyList<string> GetAvailableCultures()
```

GetCatalogs()

Gets effective catalog descriptors for installer and diagnostic surfaces.

```
IReadOnlyList<LocalizationCatalogDescriptor> GetCatalogs()
```

GetStrings(string?)

Gets the effective strings for a culture after English fallback and user overrides are merged.

```
IReadOnlyDictionary<string, string> GetStrings(string? culture = null)
```

GetText(string, string?)

Gets a localized UI sentence by deriving its maintained text-catalog key.

```
string GetText(string source, string? culture = null)
```

ImportCatalogAsync(string, string, bool, CancellationToken)

Validates and atomically imports a persistent user localization catalog.

```
Task<LocalizationCatalogImportResult> ImportCatalogAsync(string culture, string json, bool overwrite, CancellationToken cancellationToken = default)
```

ResolveAvailableCulture(string?)

Resolves a requested culture to one available LocalGPT catalog.

```
string ResolveAvailableCulture(string? culture)
```

ValidateCatalog(string, string)

Validates a user localization JSON dictionary without writing it.

```
LocalizationCatalogValidationResult ValidateCatalog(string culture, string json)
```

Class LocalGptLocalizationService

Namespace LocalGPT . Services . Localization Assembly LocalGPT.dll

Implements open LocalGPT localization catalogs with English fallback, built-in defaults and persistent user overrides.

Inheritance object LocalGptLocalizationService

Implements ILocalGptLocalizationService

```
[DocumentationUpdated("2.2.8")] public sealed class LocalGptLocalizationService : ILocalGptLocalizationService
```

🌟 Constructors 1

LocalGptLocalizationService(IWebHostEnvironment, ILogger<LocalGptLocalizationService>)

Implements open LocalGPT localization catalogs with English fallback, built-in defaults and persistent user overrides.

```
public LocalGptLocalizationService(IWebHostEnvironment environment, ILogger<LocalGptLocalizationService> logger)
```

⚙️ Methods 12

BuildCultureRedirectUrl(string?, string)

Adds an explicit request culture to one validated local return URL.

```
public string BuildCultureRedirectUrl(string? returnUrl, string culture)
```

BuildCultureReturnUrl(string)

Builds a local return URL without stale culture query values.

```
public string BuildCultureReturnUrl(string absoluteUri)
```

BuildCultureSelectionUrl(string, string)

Builds the absolute application endpoint used to select and persist one culture.

```
public string BuildCultureSelectionUrl(string absoluteUri, string culture)
```

FormatValidationErrors(LocalizationCatalogValidationResult)

Formats validation errors for a UI or API status surface.

```
public string FormatValidationErrors(LocalizationCatalogValidationResult validation)
```

Get(string, string?, string?)

Gets one localized value with English and caller-provided fallback behavior.

```
public string Get(string key, string? culture = null, string? fallback = null)
```

GetAvailableCultures()

Gets all cultures represented by built-in or user catalogs.

```
public IReadOnlyList<string> GetAvailableCultures()
```

GetCatalogs()

Gets effective catalog descriptors for installer and diagnostic surfaces.

```
public IReadOnlyList<LocalizationCatalogDescriptor> GetCatalogs()
```

GetStrings(string?)

Gets the effective strings for a culture after English fallback and user overrides are merged.

```
public IReadOnlyDictionary<string, string> GetStrings(string? culture = null)
```

GetText(string, string?)

Gets a localized UI sentence by deriving its maintained text-catalog key.

```
public string GetText(string source, string? culture = null)
```

ImportCatalogAsync(string, string, bool, CancellationToken)

Validates and atomically imports a persistent user localization catalog.

```
public Task<LocalizationCatalogImportResult> ImportCatalogAsync(string culture, string json, bool overwrite, CancellationToken cancellationToken = default)
```

ResolveAvailableCulture(string?)

Resolves a requested culture to one available LocalGPT catalog.

```
public string ResolveAvailableCulture(string? culture)
```

ValidateCatalog(string, string)

Validates a user localization JSON dictionary without writing it.


```
public LocalizationCatalogValidationResult ValidateCatalog(string culture, string json)
```

api/LocalGPT.Services.LoggingConfigurationService.html

Class LoggingConfigurationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Configures the optional LocalGPT logging providers during composition-root startup.

Inheritance object LoggingConfigurationService

```
public sealed class LoggingConfigurationService
```

🌟 Constructors 1

LoggingConfigurationService(IServiceCollection, IConfiguration, ILogger)

Configures the optional LocalGPT logging providers during composition-root startup.

```
public LoggingConfigurationService(IServiceCollection services, IConfiguration configuration, ILogger logger)
```

⚙️ Methods 1

Configure(ILoggingBuilder)

```
public void Configure(ILoggingBuilder loggingBuilder)
```

api/LocalGPT.Services.MaintainLearningRoundKnowledgeFunction.html

Class MaintainLearningRoundKnowledgeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object MaintainLearningRoundKnowledgeFunction

Implements IDxAiFunctionHandler

```
public sealed class MaintainLearningRoundKnowledgeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

MaintainLearningRoundKnowledgeFunction(ILearningRoundService, ILogger<MaintainLearningRoundKnowledgeFunction>)

```
public MaintainLearningRoundKnowledgeFunction(ILearningRoundService learning, ILogger<MaintainLearningRoundKnowledgeFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class MinecraftModWorkspaceService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object MinecraftModWorkspaceService

Implements IMinecraftModWorkspaceService

```
public class MinecraftModWorkspaceService : IMinecraftModWorkspaceService
```

✨ Constructors 1

MinecraftModWorkspaceService(ILogger<MinecraftModWorkspaceService>, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService)

```
public MinecraftModWorkspaceService(ILogger<MinecraftModWorkspaceService> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog)
```

🐾 Properties 1

WorkspaceRoot

```
public string WorkspaceRoot { get; }
```

⚙️ Methods 6

CreateDatapackWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
public Task<MinecraftModWorkspace> CreateDatapackWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

CreateFabricWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
public Task<MinecraftModWorkspace> CreateFabricWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

CreateNeoForgeWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
public Task<MinecraftModWorkspace> CreateNeoForgeWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

CreatePaperPluginWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
public Task<MinecraftModWorkspace> CreatePaperPluginWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

CreateWorkspaceAsync(MinecraftModBuildRequest, CancellationTokens)

```
public Task<MinecraftModWorkspace> CreateWorkspaceAsync(MinecraftModBuildRequest request, CancellationTokens cancellationTokens = default)
```

IsPathInsideWorkspaceRoot(string)

```
public bool IsPathInsideWorkspaceRoot(string path)
```

Class ModelPresetService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ModelPresetService

Implements IModelPresetService

```
public sealed class ModelPresetService : IModelPresetService
```

✨ Constructors 1

ModelPresetService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<ModelPresetService>)

```
public ModelPresetService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<ModelPresetService> logger)
```

⚙️ Methods 3

ArchivePresetAsync(Guid, bool, CancellationToken)

```
public Task ArchivePresetAsync(Guid presetId, bool userConfirmed, CancellationToken cancellationToken = default)
```

GetPresetsAsync(bool, CancellationToken)

```
public Task<IReadOnlyList<CouncilModelPreset>> GetPresetsAsync(bool includeArchived = false, CancellationToken cancellationToken = default)
```

SavePresetAsync(CouncilModelPreset, bool, CancellationToken)

```
public Task<CouncilModelPreset> SavePresetAsync(CouncilModelPreset preset, bool userConfirmed, CancellationToken cancellationToken = default)
```

Class MultiModelCouncilService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object MultiModelCouncilService

Implements IMultiModelCouncilService

```
public sealed class MultiModelCouncilService : IMultiModelCouncilService
```

🌟 Constructors 1

MultiModelCouncilService(ILocalGptVocabularyService, IOptionsMonitor<ConfigurationRoot>, IAIContextBootstrapService, IChatMemoryService, ICouncilArtifactService, ICouncilKnowledgeService, ILocalGptProjectService, IProjectArchitectureService, ICodeGenerationWorkflowService, ICouncilCodeGenerationPlanService, IHumanCollaborationService, IDeferredDxAiInvocationService, IOrganicCouncilBlueprintService, ICouncilSpoolerService, ICouncilPreflightService, ICouncilDxFunctionPolicyDataService, ICouncilDxFunctionOrchestrator, ICouncilHardwareRoadPlanner, ICouncilRunConfigurationService, IModelCapabilitySelfAssessmentService, IAIFeatureReportService, IAmbientLocalGptContext, IProviderModelRuntimeService, ILogger<MultiModelCouncilService>, CouncilRuntimeService, CouncilTextService, LocalGptCatalogService)

```
public MultiModelCouncilService(ILocalGptVocabularyService vocabulary, IOptionsMonitor<ConfigurationRoot> optionsRoot, IAIContextBootstrapService bootstrapService, IChatMemoryService chatMemory, ICouncilArtifactService artifactService, ICouncilKnowledgeService knowledgeService, ILocalGptProjectService projectService, IProjectArchitectureService projectArchitecture, ICodeGenerationWorkflowService codeGenerationWorkflow, ICouncilCodeGenerationPlanService codeGenerationPlanService, IHumanCollaborationService humanCollaboration, IDeferredDxAiInvocationService deferredDxAiInvocations, IOrganicCouncilBlueprintService organicCouncilBlueprints, ICouncilSpoolerService councilSpooler, ICouncilPreflightService councilPreflight, ICouncilDxFunctionPolicyDataService councilDxPolicy, ICouncilDxFunctionOrchestrator councilDxFunctions, ICouncilHardwareRoadPlanner hardwareRoadPlanner, ICouncilRunConfigurationService runConfigurations, IModelCapabilitySelfAssessmentService modelSelfAssessment, IAIFeatureReportService featureReports, IAmbientLocalGptContext ambientContext, IProviderModelRuntimeService providerModels, ILogger<MultiModelCouncilService> logger, CouncilRuntimeService councilRuntime, CouncilTextService councilText, LocalGptCatalogService catalog)
```

⚙️ Methods 19

GetCandidatesAsync(CancellationTokens)

```
public Task<IReadOnlyList<MultiModelCouncilModelCandidate>> GetCandidatesAsync(CancellationTokens cancellationTokens = default)
```

LoadContinuationConversationAsync(Guid?, CancellationTokens, ILogger)

```
public Task<ChatMemoryConversationSnapshot?> LoadContinuationConversationAsync(Guid? conversationId, CancellationTokens cancellationTokens, ILogger logger)
```

MultiModelCouncilServiceAddOrderedStep(MultiModelCouncilResult, MultiModelCouncilStep, ILogger)

```
public void MultiModelCouncilServiceAddOrderedStep(MultiModelCouncilResult result, MultiModelCouncilStep step, ILogger logger)
```

MultiModelCouncilServiceAppendPromptSection(string, string, string, ILogger)

```
public string MultiModelCouncilServiceAppendPromptSection(string existing, string title, string content, ILogger logger)
```

MultiModelCouncilServiceBuildContinuationContext(ChatMemoryConversationSnapshot?, ILogger)

```
public string MultiModelCouncilServiceBuildContinuationContext(ChatMemoryConversationSnapshot? conversation, ILogger logger)
```

MultiModelCouncilServiceBuildCouncilRequestMemoryMessage(MultiModelCouncilRequest, MultiModelCouncilResult, bool, ILogger)

```
public string MultiModelCouncilServiceBuildCouncilRequestMemoryMessage(MultiModelCouncilRequest request, MultiModelCouncilResult result, bool isContinuation, ILogger logger)
```

MultiModelCouncilServiceBuildMemoryMessage(MultiModelCouncilStep, ILogger)

```
public string MultiModelCouncilServiceBuildMemoryMessage(MultiModelCouncilStep step, ILogger logger)
```

MultiModelCouncilServiceGetCouncilKeepAlive(MultiModelCouncilRequest, int, int, ILogger)

```
public string MultiModelCouncilServiceGetCouncilKeepAlive(MultiModelCouncilRequest request, int participantCount, int maxParallelModels, ILogger logger)
```

MultiModelCouncilServiceIsHeavyGpuRiskModel(string, ILogger)

```
public bool MultiModelCouncilServiceIsHeavyGpuRiskModel(string modelName, ILogger logger)
```

MultiModelCouncilServiceIsSubstantiveCouncilContent(string, ILogger)

```
public bool MultiModelCouncilServiceIsSubstantiveCouncilContent(string content, ILogger logger)
```

MultiModelCouncilServiceIsThinkingOnlyCouncilContent(string, ILogger)

```
public bool MultiModelCouncilServiceIsThinkingOnlyCouncilContent(string content, ILogger logger)
```

MultiModelCouncilServiceProbeRunningModelNamesAsync(HttpClient, CancellationTokens, ILogger)

```
public Task<HashSet<string>> MultiModelCouncilServiceProbeRunningModelNamesAsync(HttpClient http, CancellationTokens cancellationTokens, ILogger logger)
```

MultiModelCouncilServiceResolveParticipantOllamaNumGpu(string, int?, ILogger)

```
public int? MultiModelCouncilServiceResolveParticipantOllamaNumGpu(string modelName, int? requestedNumGpu, ILogger logger)
```

MultiModelCouncilServiceRunFinalOnlyRecoveryAsync(IChatClient, string, string, IReadOnlyList<ChatMessage>, int, Action<string>?, CancellationToken, ILogger)

```
public Task<(string Content, string VisibleContent, string? Thinking)> MultiModelCouncilServiceRunFinalOnlyRecoveryAsync(IChatClient client, string modelName, string phase, IReadOnlyList<ChatMessage> originalMessages, int maxOutputTokens, Action<string>? streamUpdate, CancellationToken cancellationToken, ILogger logger)
```

MultiModelCouncilServiceSelectConsensusContent(MultiModelCouncilResult, MultiModelCouncilStep, ILogger)

```
public string MultiModelCouncilServiceSelectConsensusContent(MultiModelCouncilResult result, MultiModelCouncilStep consensusStep, ILogger logger)
```

MultiModelCouncilServiceShouldUnloadAfterParticipant(string, ILogger)

```
public bool MultiModelCouncilServiceShouldUnloadAfterParticipant(string keepAlive, ILogger logger)
```

RunAsync(MultiModelCouncilRequest, CancellationToken)

```
public Task<MultiModelCouncilResult> RunAsync(MultiModelCouncilRequest request, CancellationToken cancellationToken = default)
```

SaveToMemoryAsync(MultiModelCouncilRequest, MultiModelCouncilResult, ChatMemoryConversationSnapshot?, CancellationToken)

```
public Task<Guid?> SaveToMemoryAsync(MultiModelCouncilRequest request, MultiModelCouncilResult result, ChatMemoryConversationSnapshot? continuedConversation, CancellationToken cancellationToken)
```

WriteLogAsync(MultiModelCouncilResult, CancellationToken, ILogger)

```
public Task<string> WriteLogAsync(MultiModelCouncilResult result, CancellationToken cancellationToken, ILogger logger)
```

api/LocalGPT.Services.NativeCommandRunner.html

Class NativeCommandRunner

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object NativeCommandRunner

Implements INativeCommandRunner

```
public sealed class NativeCommandRunner : INativeCommandRunner
```

🌟 Constructors 1

NativeCommandRunner(ILogger<NativeCommandRunner>, IMinecraftModWorkspaceService, IDbContextFactory<LocalGptMemoryDbContext>, IOptionsMonitor<NativeCommandOptions>, ILocalGptRuntimePolicyDataService, SqliteUtilityService)

```
public NativeCommandRunner(ILogger<NativeCommandRunner> logger, IMinecraftModWorkspaceService workspaceService, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IOptionsMonitor<NativeCommandOptions> commandOptions, ILocalGptRuntimePolicyDataService runtimePolicy, SqliteUtilityService sqliteUtility)
```

⚙️ Methods 1

RunAsync(string, string, string, CancellationToken, bool)

```
public Task<CommandExecutionResult?> RunAsync(string fileName, string arguments, string workingDirectory, CancellationToken cancellationToken = default, bool userConfirmed = false)
```

Class NavigationUrlService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Preserves the shell sidebar state while creating application-relative navigation URLs.

Inheritance object NavigationUrlService

```
[DocumentationUpdated("2.1.20")] public sealed class NavigationUrlService
```

✨ Constructors 1

NavigationUrlService(ILogger<NavigationUrlService>)

Preserves the shell sidebar state while creating application-relative navigation URLs.

```
public NavigationUrlService(ILogger<NavigationUrlService> logger)
```

🔴 Fields 1

ToggleSidebarName

Gets the query-string key used for the sidebar state.

```
public const string ToggleSidebarName = "toggledSidebar"
```

⚙️ Methods 2

GetUrl(bool, string)

Adds the current sidebar state to an absolute or return URL and preserves its existing query values.

```
public string GetUrl(bool toggledSidebar, string returnUrl)
```

GetUrl(string, bool)

Adds the current sidebar state to an application-relative URL while preserving an existing query string.

```
public string GetUrl(string baseUrl, bool toggledSidebar)
```

Class OllamaProcessService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object OllamaProcessService

Implements IOllamaProcessService

```
public sealed class OllamaProcessService : IOllamaProcessService
```

✨ Constructors 1

OllamaProcessService(ILogger<OllamaProcessService>)

```
public OllamaProcessService(ILogger<OllamaProcessService> logger)
```

⚙️ Methods 4

GetStatusAsync(CancellationTokens)

```
public Task<OllamaProcessStatus> GetStatusAsync(CancellationTokens cancellationTokens = default)
```

RestartAsync(CancellationTokens)

```
public Task<OllamaProcessStatus> RestartAsync(CancellationTokens cancellationTokens = default)
```

StartAsync(CancellationTokens)

```
public Task<OllamaProcessStatus> StartAsync(CancellationTokens cancellationTokens = default)
```

StopAsync(CancellationTokens)

```
public Task<OllamaProcessStatus> StopAsync(CancellationTokens cancellationTokens = default)
```

Class OllamaThinkingChatClient

Namespace LocalGPT . Services Assembly LocalGPT.dll
Inheritance object OllamaThinkingChatClient
Implements IChatClient IDisposable

```
public sealed class OllamaThinkingChatClient : IChatClient, IDisposable
```

🌟 Constructors 1

OllamaThinkingChatClient(OllamaCoreOptions, ILogger, CouncilRuntimeService, string?, int?, TimeSpan?, int?, IChatResponseFormatterFactory?, IChatProtocolResolver?, IPromptConfigService?, IDxAiFunctionRegistry?)

```
public OllamaThinkingChatClient(OllamaCoreOptions options, ILogger logger, CouncilRuntimeService councilRuntime, string? keepAlive = null, int? contextLength = null, TimeSpan? timeout = null, int? numGpu = null, IChatResponseFormatterFactory? formatterFactory = null, IChatProtocolResolver? protocolResolver = null, IPromptConfigService? promptConfigService = null, IDxAiFunctionRegistry? functionRegistry = null)
```

⚙️ Methods 4

Dispose()

```
public void Dispose()
```

GetResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

```
public Task<ChatResponse> GetResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```

GetService(Type, object?)

```
public object? GetService(Type serviceType, object? serviceKey = null)
```

GetStreamingResponseAsync(IEnumerable<ChatMessage>, ChatOptions?, CancellationToken)

```
public IAsyncEnumerable<ChatResponseUpdate> GetStreamingResponseAsync(IEnumerable<ChatMessage> messages, ChatOptions? options = null, CancellationToken cancellationToken = default)
```

Namespace LocalGPT.Services.OneWire

Classes

Chat-level spreadsheet entry point. It intentionally does not require a Council run: a normal local model can discover this function, ask for the active PublisherStudio session id, and request bounded read-only evidence.

Generic escape hatch for explicitly advertised organic capabilities. Dedicated handlers below keep the common spreadsheet workflow discoverable to every normal LocalGPT chat without requiring a Council run.

Executes bounded local OCR through an Ollama-compatible vision model. The service never accepts file paths; callers must send one current browser-rendered image data URL through the approved 1-Wire request.

Owns the runtime-generated LocalGPT 1-Wire identity. Private keys and the MFA seed are created only at runtime, are never compiled into the application, and can be discarded from the frontend to reset every trusted link.

Creates a bounded, reviewable PublisherStudio text proposal from ordinary chat or a Council round. The unique connected PublisherStudio peer is selected automatically when peerId is omitted.

Reads the eventual result of a queued organic operation without reissuing it.

Requests PublisherStudio's future embedded wiring canvas for a LocalGPT board/pin draft.

Asks the PublisherStudio user for reviewed text and returns it through the queued work result.

Requests one fresh browser-mediated screenshot from PublisherStudio.

Requests one short browser-mediated screen recording from PublisherStudio.

Requests bounded user-approved HTML/DIV/document content from PublisherStudio.

Class InspectPublisherSpreadsheetFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Chat-level spreadsheet entry point. It intentionally does not require a Council run: a normal local model can discover this function, ask for the active PublisherStudio session id, and request bounded read-only evidence.

Inheritance object InspectPublisherSpreadsheetFunction

Implements IDxAiFunctionHandler

```
public sealed class InspectPublisherSpreadsheetFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InspectPublisherSpreadsheetFunction(IOrganicDxFunctionSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<InspectPublisherSpreadsheetFunction>)

Chat-level spreadsheet entry point. It intentionally does not require a Council run: a normal local model can discover this function, ask for the active PublisherStudio session id, and request bounded read-only evidence.

```
public InspectPublisherSpreadsheetFunction(
    IOrganicDxFunctionSupport organicSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<InspectPublisherSpreadsheetFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class InvokeOrganicPluginFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Generic escape hatch for explicitly advertised organic capabilities. Dedicated handlers below keep the common spreadsheet workflow discoverable to every normal LocalGPT chat without requiring a Council run.

Inheritance object InvokeOrganicPluginFunction

Implements IDxAiFunctionHandler

```
public sealed class InvokeOrganicPluginFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

InvokeOrganicPluginFunction(IOrganicDxFunctionSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<InvokeOrganicPluginFunction>)

Generic escape hatch for explicitly advertised organic capabilities. Dedicated handlers below keep the common spreadsheet workflow discoverable to every normal LocalGPT chat without requiring a Council run.

```
public InvokeOrganicPluginFunction(
    IOrganicDxFunctionSupport organicSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<InvokeOrganicPluginFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```


Class LocalVisionOcrService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Executes bounded local OCR through an Ollama-compatible vision model. The service never accepts file paths; callers must send one current browser-rendered image data URL through the approved 1-Wire request.

Inheritance object LocalVisionOcrService

Implements ILocalVisionOcrService

```
public sealed class LocalVisionOcrService : ILocalVisionOcrService
```

🌟 Constructors 1

LocalVisionOcrService(IOptionsMonitor<ConfigurationRoot>, ILogger<LocalVisionOcrService>)

Executes bounded local OCR through an Ollama-compatible vision model. The service never accepts file paths; callers must send one current browser-rendered image data URL through the approved 1-Wire request.

```
public LocalVisionOcrService(IOptionsMonitor<ConfigurationRoot> options, ILogger<LocalVisionOcrService> logger)
```

⚙️ Methods 1

RecognizeAsync(LocalVisionOcrRequest, CancellationToken)

```
public Task<LocalVisionOcrResult> RecognizeAsync(LocalVisionOcrRequest request, CancellationToken cancellationToken = default)
```

Class OneWireCapabilityCatalog

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireCapabilityCatalog

Implements IOneWireCapabilityCatalog IOneWireCapabilityProvider

```
public sealed class OneWireCapabilityCatalog : IOneWireCapabilityCatalog, IOneWireCapabilityProvider
```

🌟 Constructors 1

OneWireCapabilityCatalog(ILocalGptVocabularyService, IServiceScopeFactory, IOneWirePeerRegistry, IOneWireConnectionRegistry, IHardwareInventoryService, ILogger<OneWireCapabilityCatalog>)

```
public OneWireCapabilityCatalog(ILocalGptVocabularyService vocabulary, IServiceScopeFactory scopeFactory, IOneWirePeerRegistry peers, IOneWireConnectionRegistry connections, IHardwareInventoryService hardwareInventory, ILogger<OneWireCapabilityCatalog> logger)
```

⚙️ Methods 5

GetLocalCapabilitiesAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireCapabilityDescriptor>> GetLocalCapabilitiesAsync(CancellationToken cancellationToken = default)
```

GetLocalCapabilitiesForPeerAsync(string, CancellationToken)

```
public Task<IReadOnlyList<OneWireCapabilityDescriptor>> GetLocalCapabilitiesForPeerAsync(string peerId, CancellationToken cancellationToken = default)
```

GetLocalHardwareAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireHardwareDescriptor>> GetLocalHardwareAsync(CancellationToken cancellationToken = default)
```

GetLocalSkillsAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireSkillDescriptor>> GetLocalSkillsAsync(CancellationToken cancellationToken = default)
```

GetLocalUiFeaturesAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireUiFeatureDescriptor>> GetLocalUiFeaturesAsync(CancellationToken cancellationToken = default)
```

Class OneWireConnectionRegistry

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireConnectionRegistry

Implements IOneWireConnectionRegistry

```
public sealed class OneWireConnectionRegistry : IOneWireConnectionRegistry
```

✨ Constructors 1

OneWireConnectionRegistry(ILogger<OneWireConnectionRegistry>)

```
public OneWireConnectionRegistry(ILogger<OneWireConnectionRegistry> logger)
```

⚙️ Methods 6

IsConnected(string)

```
public bool IsConnected(string peerId)
```

Register(string, Func<OneWireEnvelope, CancellationToken, Task>)

```
public void Register(string peerId, Func<OneWireEnvelope, CancellationToken, Task> sender)
```

RegisterOwned(string, Func<OneWireEnvelope, CancellationToken, Task>)

```
public Guid RegisterOwned(string peerId, Func<OneWireEnvelope, CancellationToken, Task> sender)
```

SendAsync(string, OneWireEnvelope, CancellationToken)

```
public Task<bool> SendAsync(string peerId, OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

Unregister(string)

```
public void Unregister(string peerId)
```

Unregister(string, Guid)

```
public bool Unregister(string peerId, Guid registrationId)
```

Class OneWireCouncilApprovalProcessorHostedService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object BackgroundService OneWireCouncilApprovalProcessorHostedService

Implements IHostedService IDisposable

```
public sealed class OneWireCouncilApprovalProcessorHostedService : BackgroundService, IHostedService, IDisposable
```

✨ Constructors 1

OneWireCouncilApprovalProcessorHostedService(IONeWirePendingCouncilStore, IHumanCollaborationService, IOneWireWorkSpooler, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireRuntimeSecurityService, IOneWireTargetApprovalPolicy, IOneWireMessageDispatcher, IOneWireEnvelopeCodec, ILogger<OneWireCouncilApprovalProcessorHostedService>)

```
public OneWireCouncilApprovalProcessorHostedService(IONeWirePendingCouncilStore pendingCouncils, IHumanCollaborationService humanCollaboration, IOneWireWorkSpooler spooler, IOneWireConnectionRegistry connections, IOneWirePeerRegistry peers, IOneWireRuntimeSecurityService security, IOneWireTargetApprovalPolicy targetApprovalPolicy, IOneWireMessageDispatcher dispatcher, IOneWireEnvelopeCodec codec, ILogger<OneWireCouncilApprovalProcessorHostedService> logger)
```

⚙️ Methods 1

ExecuteAsync(CancellationToken)

```
protected override Task ExecuteAsync(CancellationToken stoppingToken)
```

Class OneWireDiscoveryHostedService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object BackgroundService OneWireDiscoveryHostedService

Implements IHostedService IDisposable

```
public sealed class OneWireDiscoveryHostedService : BackgroundService, IHostedService, IDisposable
```

🌟 Constructors 1

OneWireDiscoveryHostedService(IOptions<OneWireOptions>, IOneWireRuntimeSecurityService, IOneWireEnvelopeCodec, ILogger<OneWireDiscoveryHostedService>)

```
public OneWireDiscoveryHostedService(IOptions<OneWireOptions> options, IOneWireRuntimeSecurityService security, IOneWireEnvelopeCodec codec, ILogger<OneWireDiscoveryHostedService> logger)
```

⚙️ Methods 1

ExecuteAsync(CancellationToken)

```
protected override Task ExecuteAsync(CancellationToken stoppingToken)
```

Class OneWireDispatchContextFactory

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireDispatchContextFactory

Implements IOneWireDispatchContextFactory

```
public sealed class OneWireDispatchContextFactory : IOneWireDispatchContextFactory
```

🌟 Constructors 1

OneWireDispatchContextFactory(ILogger<OneWireDispatchContextFactory>)

```
public OneWireDispatchContextFactory(ILogger<OneWireDispatchContextFactory> logger)
```

⚙️ Methods 2

CreateExternal(string, Guid, bool, string)

```
public OneWireDispatchContext CreateExternal(string authenticatedPeerId, Guid connectionId, bool isLoopback, string transport)
```

CreateInternal(string)

```
public OneWireDispatchContext CreateInternal(string transport = "internal")
```

Class OneWireEnvelopeCodec

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireEnvelopeCodec

Implements IOneWireEnvelopeCodec

```
public sealed class OneWireEnvelopeCodec : IOneWireEnvelopeCodec
```

✨ Constructors 1

OneWireEnvelopeCodec(ILogger<OneWireEnvelopeCodec>)

```
public OneWireEnvelopeCodec(ILogger<OneWireEnvelopeCodec> logger)
```

🐾 Properties 1

JsonOptions

```
public JsonSerializerOptions JsonOptions { get; }
```

⚙️ Methods 3

DeserializeAndValidate(string)

```
public OneWireEnvelope DeserializeAndValidate(string json)
```

Serialize(OneWireEnvelope, bool)

```
public string Serialize(OneWireEnvelope envelope, bool seal = true)
```

Validate(OneWireEnvelope, out string)

```
public bool Validate(OneWireEnvelope envelope, out string error)
```

Class OneWireListenAddressResolver

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireListenAddressResolver

Implements IOneWireListenAddressResolver

```
public sealed class OneWireListenAddressResolver : IOneWireListenAddressResolver
```

✨ Constructors 1

OneWireListenAddressResolver(ILogger<OneWireListenAddressResolver>)

```
public OneWireListenAddressResolver(ILogger<OneWireListenAddressResolver> logger)
```

⚙️ Methods 1

Resolve(OneWireOptions)

```
public IPAddress Resolve(OneWireOptions configured)
```

Class OneWireMessageDispatcher

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireMessageDispatcher

Implements IOneWireMessageDispatcher

```
public sealed class OneWireMessageDispatcher : IOneWireMessageDispatcher
```

🌟 Constructors 1

OneWireMessageDispatcher(IOneWireEnvelopeCodec, IOneWireCapabilityCatalog, IOneWirePeerRegistry, IOneWireWorkSpooler, IOneWirePendingCouncilStore, IHumanCollaborationService, IOneWireRuntimeSecurityService, IOneWireReplayGuard, IOneWireTransportSecurityPolicy, IOneWireDispatchContextFactory, IOneWireTargetApprovalPolicy, ILogger<OneWireMessageDispatcher>)

```
public OneWireMessageDispatcher(IOneWireEnvelopeCodec codec, IOneWireCapabilityCatalog capabilities, IOneWirePeerRegistry peers, IOneWireWorkSpooler spooler, IOneWirePendingCouncilStore pendingCouncils, IHumanCollaborationService humanCollaboration, IOneWireRuntimeSecurityService security, IOneWireReplayGuard replayGuard, IOneWireTransportSecurityPolicy transportSecurityPolicy, IOneWireDispatchContextFactory dispatchContextFactory, IOneWireTargetApprovalPolicy targetApprovalPolicy, ILogger<OneWireMessageDispatcher> logger)
```

⚙️ Methods 4

ApplyHumanResponse(OneWireEnvelope, string?)

```
public void ApplyHumanResponse(OneWireEnvelope envelope, string? userResponse)
```

DispatchAsync(OneWireEnvelope, OneWireDispatchContext, CancellationToken)

```
public Task<OneWireEnvelope?> DispatchAsync(OneWireEnvelope envelope, OneWireDispatchContext context, CancellationToken cancellationToken = default)
```

DispatchAsync(OneWireEnvelope, CancellationToken)

```
public Task<OneWireEnvelope?> DispatchAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

GetLocalAdvertisement()

```
public OneWirePeerAdvertisement GetLocalAdvertisement()
```

Class OneWireOperationExecutor

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireOperationExecutor

Implements IOneWireOperationExecutor

```
public sealed class OneWireOperationExecutor : IOneWireOperationExecutor
```

🌟 Constructors 1

OneWireOperationExecutor(IServiceScopeFactory, IOneWireEnvelopeCodec, ILocalGptVocabularyService, ILogger<OneWireOperationExecutor>)

```
public OneWireOperationExecutor(IServiceScopeFactory scopeFactory, IOneWireEnvelopeCodec codec, ILocalGptVocabularyService vocabulary, ILogger<OneWireOperationExecutor> logger)
```

⚙️ Methods 1

ExecuteAsync(OneWireWorkItem, CancellationToken)

```
public Task<string> ExecuteAsync(OneWireWorkItem item, CancellationToken cancellationToken = default)
```

Class OneWirePeerRegistry

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWirePeerRegistry

Implements IOneWirePeerRegistry

```
public sealed class OneWirePeerRegistry : IOneWirePeerRegistry
```

🌟 Constructors 1

OneWirePeerRegistry(ILogger<OneWirePeerRegistry>)

```
public OneWirePeerRegistry(ILogger<OneWirePeerRegistry> logger)
```

⚙️ Methods 5

GetPeer(string)

```
public OneWirePeerAdvertisement? GetPeer(string peerId)
```

GetPeers()

```
public IReadOnlyList<OneWirePeerAdvertisement> GetPeers()
```

RemoveExpired(TimeSpan)

```
public void RemoveExpired(TimeSpan maximumAge)
```

SetConnected(string, bool)

```
public void SetConnected(string peerId, bool connected)
```

Upsert(OneWirePeerAdvertisement)

```
public void Upsert(OneWirePeerAdvertisement peer)
```

Class OneWirePendingCouncilStore

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWirePendingCouncilStore

Implements IOneWirePendingCouncilStore

```
public sealed class OneWirePendingCouncilStore : IOneWirePendingCouncilStore
```

🌟 Constructors 1

OneWirePendingCouncilStore(ILogger<OneWirePendingCouncilStore>)

```
public OneWirePendingCouncilStore(ILogger<OneWirePendingCouncilStore> logger)
```

⚙️ Methods 4

GetSnapshot()

```
public IReadOnlyList<OneWirePendingCouncilRequest> GetSnapshot()
```

MarkChecked(Guid)

```
public void MarkChecked(Guid correlationId)
```

Remove(Guid, out OneWirePendingCouncilRequest?)

```
public bool Remove(Guid correlationId, out OneWirePendingCouncilRequest? request)
```

Upsert(OneWireEnvelope, Guid?)

```
public void Upsert(OneWireEnvelope envelope, Guid? approvalRequestId)
```

Class OneWireReplayGuard

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireReplayGuard

Implements IOneWireReplayGuard

```
public sealed class OneWireReplayGuard : IOneWireReplayGuard
```

✨ Constructors 1

OneWireReplayGuard(IIOneWireReplayPolicyDataService, ILogger<OneWireReplayGuard>)

```
public OneWireReplayGuard(IIOneWireReplayPolicyDataService policyData, ILogger<OneWireReplayGuard> logger)
```

⚙️ Methods 1

TryAccept(string, Guid, DateTimeOffset)

```
public bool TryAccept(string peerId, Guid messageId, DateTimeOffset createdUtc)
```

Class OneWireRuntimeSecurityService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Owns the runtime-generated LocalGPT 1-Wire identity. Private keys and the MFA seed are created only at runtime, are never compiled into the application, and can be discarded from the frontend to reset every trusted link.

Inheritance object OneWireRuntimeSecurityService

Implements IOneWireRuntimeSecurityService

```
public sealed class OneWireRuntimeSecurityService : IOneWireRuntimeSecurityService
```

🌟 Constructors 1

OneWireRuntimeSecurityService(ILogger<OneWireRuntimeSecurityService>)

Owns the runtime-generated LocalGPT 1-Wire identity. Private keys and the MFA seed are created only at runtime, are never compiled into the application, and can be discarded from the frontend to reset every trusted link.

```
public OneWireRuntimeSecurityService(ILogger<OneWireRuntimeSecurityService> logger)
```

⚙️ Methods 12

CreatePairingTicketAsync(TimeSpan, CancellationToken)

```
public Task<OneWirePairingTicket> CreatePairingTicketAsync(TimeSpan lifetime, CancellationToken cancellationToken = default)
```

DeleteAsync(CancellationToken)

```
public Task DeleteAsync(CancellationToken cancellationToken = default)
```

EnsureCreatedAsync(CancellationToken)

```
public Task EnsureCreatedAsync(CancellationToken cancellationToken = default)
```

EstablishTrustAsync(OneWireTrustEstablishmentRequest, CancellationToken)

```
public Task<bool> EstablishTrustAsync(OneWireTrustEstablishmentRequest request, CancellationToken cancellationToken = default)
```

GetOtpAuthUriAsync(CancellationToken)

```
public Task<string> GetOtpAuthUriAsync(CancellationToken cancellationToken = default)
```

GetPublicDescriptorAsync(CancellationToken)

```
public Task<OneWireSecurityDescriptor> GetPublicDescriptorAsync(CancellationToken cancellationToken = default)
```

GetStatusAsync(CancellationToken)

```
public Task<OneWireRuntimeSecurityStatus> GetStatusAsync(CancellationToken cancellationToken = default)
```

GetTrustedPeersAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireTrustedPeerDescriptor>> GetTrustedPeersAsync(CancellationToken cancellationToken = default)
```

ProtectOutgoingAsync(OneWireEnvelope, CancellationToken)

```
public Task ProtectOutgoingAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```

RegenerateAsync(CancellationToken)

```
public Task RegenerateAsync(CancellationToken cancellationToken = default)
```

RevokeTrustAsync(string, CancellationToken)

```
public Task<bool> RevokeTrustAsync(string peerId, CancellationToken cancellationToken = default)
```

UnprotectIncomingAsync(OneWireEnvelope, CancellationToken)

```
public Task UnprotectIncomingAsync(OneWireEnvelope envelope, CancellationToken cancellationToken = default)
```


Class OneWireTargetApprovalPolicy

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireTargetApprovalPolicy

Implements IOneWireTargetApprovalPolicy

```
public sealed class OneWireTargetApprovalPolicy : IOneWireTargetApprovalPolicy
```

✨ Constructors 1

OneWireTargetApprovalPolicy(ILocalGptVocabularyService, ILogger<OneWireTargetApprovalPolicy>)

```
public OneWireTargetApprovalPolicy(ILocalGptVocabularyService vocabulary, ILogger<OneWireTargetApprovalPolicy> logger)
```

⚙️ Methods 2

Create(OneWireEnvelope)

```
public HumanApprovalRequestSpec Create(OneWireEnvelope envelope)
```

ReadEditor(OneWireEnvelope)

```
public OneWireInteractionEditor ReadEditor(OneWireEnvelope envelope)
```

Class OneWireTcpHostedService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object BackgroundService OneWireTcpHostedService

Implements IHostedService IDisposable

```
public sealed class OneWireTcpHostedService : BackgroundService, IHostedService, IDisposable
```

✨ Constructors 1

OneWireTcpHostedService(IOptions<OneWireOptions>, IOneWireEnvelopeCodec, IOneWireRuntimeSecurityService, IOneWireMessageDispatcher, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireTransportSecurityPolicy, IOneWireDispatchContextFactory, IOneWireListenAddressResolver, ISupervisedTaskRunner, ILogger<OneWireTcpHostedService>)

```
public OneWireTcpHostedService(IOptions<OneWireOptions> options, IOneWireEnvelopeCodec codec, IOneWireRuntimeSecurityService security, IOneWireMessageDispatcher dispatcher, IOneWireConnectionRegistry connections, IOneWirePeerRegistry peers, IOneWireTransportSecurityPolicy transportSecurityPolicy, IOneWireDispatchContextFactory dispatchContextFactory, IOneWireListenAddressResolver listenAddressResolver, ISupervisedTaskRunner taskRunner, ILogger<OneWireTcpHostedService> logger)
```

⚙️ Methods 1

ExecuteAsync(CancellationTokens)

```
protected override Task ExecuteAsync(CancellationTokens stoppingToken)
```

Class OneWireTransportSecurityPolicy

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireTransportSecurityPolicy

Implements IOneWireTransportSecurityPolicy

```
public sealed class OneWireTransportSecurityPolicy : IOneWireTransportSecurityPolicy
```

✨ Constructors 1

OneWireTransportSecurityPolicy(ILogger<OneWireTransportSecurityPolicy>)

```
public OneWireTransportSecurityPolicy(ILogger<OneWireTransportSecurityPolicy> logger)
```

⚙️ Methods 3

IsLoopback(IPAddress?)

```
public bool IsLoopback(IPAddress? address)
```

IsProtected(OneWireEnvelope)

```
public bool IsProtected(OneWireEnvelope envelope)
```

RequiresProtectedTransport(OneWireMessageType)

```
public bool RequiresProtectedTransport(OneWireMessageType messageType)
```

Class OneWireWorkProcessorHostedService

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object BackgroundService OneWireWorkProcessorHostedService

Implements IHostedService IDisposable

```
public sealed class OneWireWorkProcessorHostedService : BackgroundService, IHostedService, IDisposable
```

✨ Constructors 1

OneWireWorkProcessorHostedService(IOneWireWorkSpooler, IOneWireOperationExecutor, IOneWireConnectionRegistry, ILogger<OneWireWorkProcessorHostedService>)

```
public OneWireWorkProcessorHostedService(IOneWireWorkSpooler spooler, IOneWireOperationExecutor executor, IOneWireConnectionRegistry connections, ILogger<OneWireWorkProcessorHostedService> logger)
```

⚙️ Methods 1

ExecuteAsync(CancellationTokens)

```
protected override Task ExecuteAsync(CancellationToken stoppingToken)
```

Class OneWireWorkSpooler

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OneWireWorkSpooler

Implements IOneWireWorkSpooler

```
public sealed class OneWireWorkSpooler : IOneWireWorkSpooler
```

🌟 Constructors 1

OneWireWorkSpooler(ILogger<OneWireWorkSpooler>)

```
public OneWireWorkSpooler(ILogger<OneWireWorkSpooler> logger)
```

⚙️ Methods 9

ApplyExternalResult(Guid, string, string, OneWireWorkStatus?)

```
public void ApplyExternalResult(Guid correlationId, string resultJson, string error, OneWireWorkStatus? status = null)
```

Complete(Guid, string)

```
public void Complete(Guid id, string resultJson)
```

DequeueAsync(CancellationTokens)

```
public Task<OneWireWorkItem> DequeueAsync(CancellationTokens cancellationTokens)
```

Enqueue(OneWireEnvelope)

```
public OneWireWorkItem Enqueue(OneWireEnvelope envelope)
```

Fail(Guid, string)

```
public void Fail(Guid id, string error)
```

Get(Guid)

```
public OneWireWorkItem? Get(Guid id)
```

GetSnapshot()

```
public IReadOnlyList<OneWireWorkItem> GetSnapshot()
```

MarkPendingApproval(Guid, string)

```
public void MarkPendingApproval(Guid correlationId, string resultJson)
```

MarkRunning(Guid)

```
public void MarkRunning(Guid id)
```

Class OrganicDxFunctionSupport

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object OrganicDxFunctionSupport

Implements IOrganicDxFunctionSupport

```
public sealed class OrganicDxFunctionSupport : IOrganicDxFunctionSupport
```

🌟 Constructors 1

OrganicDxFunctionSupport(ILogger<OrganicDxFunctionSupport>)

```
public OrganicDxFunctionSupport(ILogger<OrganicDxFunctionSupport> logger)
```

⚙️ Methods 5

CreateInvokeEnvelope(string, OneWireCapabilityDescriptor, JsonElement, OneWireExecutionMode, string, DateTimeOffset?, bool, string?)

```
public OneWireEnvelope CreateInvokeEnvelope(string peerId, OneWireCapabilityDescriptor capability, JsonElement payload, OneWireExecutionMode executionMode, string workOrderKey, DateTimeOffset? notBeforeUtc, bool userConfirmed, string? interactionValueJson)
```

FindCapability(OneWirePeerAdvertisement, string)

```
public OneWireCapabilityDescriptor? FindCapability(OneWirePeerAdvertisement peer, string key)
```

GetString(JsonElement, string, string)

```
public string GetString(JsonElement element, string name, string fallback = "")
```

Invalid(string)

```
public DxAiFunctionInvocationResult Invalid(string error)
```

Queued(OneWireWorkItem, string, string)

```
public DxAiFunctionInvocationResult Queued(OneWireWorkItem work, string peerId, string capabilityKey)
```

Class ProposePublisherTextFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Creates a bounded, reviewable PublisherStudio text proposal from ordinary chat or a Council round. The unique connected PublisherStudio peer is selected automatically when peerId is omitted.

Inheritance object ProposePublisherTextFunction

Implements IDxAiFunctionHandler

```
public sealed class ProposePublisherTextFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ProposePublisherTextFunction(IOrganicDxFunctionSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<ProposePublisherTextFunction>)

Creates a bounded, reviewable PublisherStudio text proposal from ordinary chat or a Council round. The unique connected PublisherStudio peer is selected automatically when peerId is omitted.

```
public ProposePublisherTextFunction(IOrganicDxFunctionSupport organicSupport, IOneWireConnectionRegistry connections, IOneWirePeerRegistry peers, IOneWireWorkSpooler spooler, ILogger<ProposePublisherTextFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTokentoken = default)
```

Class PublisherInteractionDxSupport

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Inheritance object PublisherInteractionDxSupport

Implements IPublisherInteractionDxSupport

```
public sealed class PublisherInteractionDxSupport : IPublisherInteractionDxSupport
```

🌟 Constructors 1

PublisherInteractionDxSupport(IOrganicDxFunctionSupport, ILogger<PublisherInteractionDxSupport>)

```
public PublisherInteractionDxSupport(IOrganicDxFunctionSupport organicSupport, ILogger<PublisherInteractionDxSupport> serviceLogger)
```

⚙️ Methods 1

QueueAsync<TLogger>(DxAiFunctionInvocationRequest, string, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<TLogger>, Func<JsonElement, JsonElement>, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> QueueAsync<TLogger>(DxAiFunctionInvocationRequest request, string capabilityKey, IOneWireConnectionRegistry connections, IOneWirePeerRegistry peers, IOneWireWorkSpooler spooler, ILogger<TLogger> logger, Func<JsonElement, JsonElement> createPayload, CancellationToken cancellationToken)
```

Class ReadOrganicPluginWorkResultFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Reads the eventual result of a queued organic operation without reissuing it.

Inheritance object ReadOrganicPluginWorkResultFunction

Implements IDxAiFunctionHandler

```
public sealed class ReadOrganicPluginWorkResultFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ReadOrganicPluginWorkResultFunction(OneWireWorkSpooler, IOrganicDxFunctionSupport, ILogger<ReadOrganicPluginWorkResultFunction>)

Reads the eventual result of a queued organic operation without reissuing it.

```
public ReadOrganicPluginWorkResultFunction(OneWireWorkSpooler spooler, IOrganicDxFunctionSupport organicSupport, ILogger<ReadOrganicPluginWorkResultFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class RequestPublisherEmbeddedWiringEditorFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Requests PublisherStudio's future embedded wiring canvas for a LocalGPT board/pin draft.

Inheritance object RequestPublisherEmbeddedWiringEditorFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestPublisherEmbeddedWiringEditorFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestPublisherEmbeddedWiringEditorFunction(IOrganicDxFunctionSupport, IPublisherInteractionDxSupport, IEmbeddedHardwareCatalogService, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<RequestPublisherEmbeddedWiringEditorFunction>)

Requests PublisherStudio's future embedded wiring canvas for a LocalGPT board/pin draft.

```
public RequestPublisherEmbeddedWiringEditorFunction(
    IOrganicDxFunctionSupport organicSupport,
    IPublisherInteractionDxSupport publisherInteractionSupport,
    IEmbeddedHardwareCatalogService embeddedCatalog,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<RequestPublisherEmbeddedWiringEditorFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class RequestPublisherReviewedTextFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Asks the PublisherStudio user for reviewed text and returns it through the queued work result.

Inheritance object RequestPublisherReviewedTextFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestPublisherReviewedTextFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestPublisherReviewedTextFunction(IOrganicDxFunctionSupport, IPublisherInteractionDxSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<RequestPublisherReviewedTextFunction>)

Asks the PublisherStudio user for reviewed text and returns it through the queued work result.

```
public RequestPublisherReviewedTextFunction(
    IOrganicDxFunctionSupport organicSupport,
    IPublisherInteractionDxSupport publisherInteractionSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<RequestPublisherReviewedTextFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class RequestPublisherScreenCaptureFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Requests one fresh browser-mediated screenshot from PublisherStudio.

Inheritance object RequestPublisherScreenCaptureFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestPublisherScreenCaptureFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestPublisherScreenCaptureFunction(IOrganicDxFunctionSupport, IPublisherInteractionDxSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<RequestPublisherScreenCaptureFunction>)

Requests one fresh browser-mediated screenshot from PublisherStudio.

```
public RequestPublisherScreenCaptureFunction(
    IOrganicDxFunctionSupport organicSupport,
    IPublisherInteractionDxSupport publisherInteractionSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<RequestPublisherScreenCaptureFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class RequestPublisherScreenRecordFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Requests one short browser-mediated screen recording from PublisherStudio.

Inheritance object RequestPublisherScreenRecordFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestPublisherScreenRecordFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestPublisherScreenRecordFunction(IOrganicDxFunctionSupport, IPublisherInteractionDxSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<RequestPublisherScreenRecordFunction>)

Requests one short browser-mediated screen recording from PublisherStudio.

```
public RequestPublisherScreenRecordFunction(
    IOrganicDxFunctionSupport organicSupport,
    IPublisherInteractionDxSupport publisherInteractionSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<RequestPublisherScreenRecordFunction> logger)

```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class RequestPublisherWebsiteContentFunction

Namespace LocalGPT . Services . OneWire Assembly LocalGPT.dll

Requests bounded user-approved HTML/DIV/document content from PublisherStudio.

Inheritance object RequestPublisherWebsiteContentFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestPublisherWebsiteContentFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestPublisherWebsiteContentFunction(IOrganicDxFunctionSupport, IPublisherInteractionDxSupport, IOneWireConnectionRegistry, IOneWirePeerRegistry, IOneWireWorkSpooler, ILogger<RequestPublisherWebsiteContentFunction>)

Requests bounded user-approved HTML/DIV/document content from PublisherStudio.

```
public RequestPublisherWebsiteContentFunction(
    IOrganicDxFunctionSupport organicSupport,
    IPublisherInteractionDxSupport publisherInteractionSupport,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    IOneWireWorkSpooler spooler,
    ILogger<RequestPublisherWebsiteContentFunction> logger)

```

⚙️ Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(
    DxAiFunctionInvocationRequest request,
    CancellationToken cancellationToken = default)

```

Class OrganicAddonManifestService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Loads source-controlled organic add-on manifests. Offline manifests are discovery metadata only; they become available for invocation only when the matching trusted 1-Wire peer is connected.

Inheritance object OrganicAddonManifestService

Implements IOrganicAddonManifestService

```
public sealed class OrganicAddonManifestService : IOrganicAddonManifestService
```

🌟 Constructors 1

OrganicAddonManifestService(IWebHostEnvironment, IOneWireConnectionRegistry, IOneWirePeerRegistry, ILogger<OrganicAddonManifestService>)

Loads source-controlled organic add-on manifests. Offline manifests are discovery metadata only; they become available for invocation only when the matching trusted 1-Wire peer is connected.

```
public OrganicAddonManifestService(
    IWebHostEnvironment environment,
    IOneWireConnectionRegistry connections,
    IOneWirePeerRegistry peers,
    ILogger<OrganicAddonManifestService> logger)

```

⚙️ Methods 3

GetCatalogEntries()

```
public IReadOnlyList<DxAiFunctionCatalogEntry> GetCatalogEntries()
```

GetManifests()

```
public IReadOnlyList<OrganicAddonManifest> GetManifests()
```

GetSkillDescriptors()

```
public IReadOnlyList<OneWireSkillDescriptor> GetSkillDescriptors()
```


Class OrganicCouncilBlueprintSeedDataService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Owns the first-run council-team seed model. Runtime edits remain database-owned by CouncilTeamConfigurationService.

Inheritance object OrganicCouncilBlueprintSeedDataService

Implements IOrganicCouncilBlueprintSeedDataService

```
[DocumentationUpdated("2.1.20")] public sealed class OrganicCouncilBlueprintSeedDataService : IOrganicCouncilBlueprintSeedDataService
```

🌟 Constructors 1

OrganicCouncilBlueprintSeedDataService(ILogger<OrganicCouncilBlueprintSeedDataService>)

Owns the first-run council-team seed model. Runtime edits remain database-owned by CouncilTeamConfigurationService.

```
public OrganicCouncilBlueprintSeedDataService(ILogger<OrganicCouncilBlueprintSeedDataService> logger)
```

⚙️ Methods 1

CreateDefaultTeams()

Creates the maintained system council-team definitions for first-run and seed evolution.

```
public IReadOnlyList<OrganicCouncilTeamDefinition> CreateDefaultTeams()
```

Class OrganicCouncilBlueprintService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object OrganicCouncilBlueprintService

Implements IOrganicCouncilBlueprintService

```
public sealed class OrganicCouncilBlueprintService : IOrganicCouncilBlueprintService
```

🌟 Constructors 1

OrganicCouncilBlueprintService(IProjectOrganicContextService, ICouncilTeamConfigurationService, IOneWirePeerRegistry, ILogger<OrganicCouncilBlueprintService>)

```
public OrganicCouncilBlueprintService(IProjectOrganicContextService projectContext, ICouncilTeamConfigurationService teamConfigurations, IOneWirePeerRegistry peers, ILogger<OrganicCouncilBlueprintService> logger)
```

⚙️ Methods 5

BuildBriefingAsync(MultiModelCouncilRequest, CancellationToken)

```
public Task<string> BuildBriefingAsync(MultiModelCouncilRequest request, CancellationToken cancellationToken = default)
```

BuildExpertPreparationPrompt(MultiModelCouncilRequest, OrganicCouncilTeamDefinition)

```
public string BuildExpertPreparationPrompt(MultiModelCouncilRequest request, OrganicCouncilTeamDefinition team)
```

BuildLeaderSynthesisPrompt(MultiModelCouncilRequest, OrganicCouncilTeamDefinition, string)

```
public string BuildLeaderSynthesisPrompt(MultiModelCouncilRequest request, OrganicCouncilTeamDefinition team, string preparation)
```

FindTeamAsync(string?, CancellationToken)

```
public Task<OrganicCouncilTeamDefinition?> FindTeamAsync(string? key, CancellationToken cancellationToken = default)
```

GetTeamsAsync(CancellationToken)

```
public Task<IReadOnlyList<OrganicCouncilTeamDefinition>> GetTeamsAsync(CancellationToken cancellationToken = default)
```

Class OrganicSkillRegistryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object OrganicSkillRegistryService

Implements IOrganicSkillRegistryService

```
public sealed class OrganicSkillRegistryService : IOrganicSkillRegistryService
```

✨ Constructors 1

OrganicSkillRegistryService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, IOrganicAddonManifestService, ILogger<OrganicSkillRegistryService>)

```
public OrganicSkillRegistryService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, IOrganicAddonManifestService addonManifests, ILogger<OrganicSkillRegistryService> logger)
```

⚙️ Methods 6

GetSkillsAsync(bool, CancellationToken)

```
public Task<IReadOnlyList<OrganicSkillDefinition>> GetSkillsAsync(bool includeDisabled = false, CancellationToken cancellationToken = default)
```

GetWireSkillsAsync(CancellationToken)

```
public Task<IReadOnlyList<OneWireSkillDescriptor>> GetWireSkillsAsync(CancellationToken cancellationToken = default)
```

LinkProjectAsync(LinkProjectOrganicSkillRequest, CancellationToken)

```
public Task<ProjectOrganicSkillLink> LinkProjectAsync(LinkProjectOrganicSkillRequest request, CancellationToken cancellationToken = default)
```

RecordUntrustedSelfAssessmentAsync(OneWireModelSelfAssessment, CancellationToken)

```
public Task RecordUntrustedSelfAssessmentAsync(OneWireModelSelfAssessment assessment, CancellationToken cancellationToken = default)
```

ReportMemberSkillAsync(ReportCouncilMemberSkillRequest, CancellationToken)

```
public Task<CouncilMemberOrganicSkillLink> ReportMemberSkillAsync(ReportCouncilMemberSkillRequest request, CancellationToken cancellationToken = default)
```

SaveSkillAsync(SaveOrganicSkillRequest, CancellationToken)

```
public Task<OrganicSkillDefinition> SaveSkillAsync(SaveOrganicSkillRequest request, CancellationToken cancellationToken = default)
```

Class CouncilDxFunctionPolicyDataService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object CouncilDxFunctionPolicyDataService

Implements ICouncilDxFunctionPolicyDataService

```
public sealed class CouncilDxFunctionPolicyDataService : ICouncilDxFunctionPolicyDataService
```

✨ Constructors 1

CouncilDxFunctionPolicyDataService(IDatabaseInitializationService, IDbContextFactory<LocalGptMemoryDbContext>, ISystemVariableDefinitionService, IPromptConfigService, ILogger<CouncilDxFunctionPolicyDataService>)

```
public CouncilDxFunctionPolicyDataService(IDatabaseInitializationService databaseInitialization, IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, ISystemVariableDefinitionService definitions, IPromptConfigService prompts, ILogger<CouncilDxFunctionPolicyDataService> logger)
```

⚙️ Methods 1

GetPolicyAsync(CancellationToken)

```
public Task<CouncilDxFunctionPolicy> GetPolicyAsync(CancellationToken cancellationToken = default)
```

Class CouncilTextPatternDataService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Database boundary for every regular expression used by CouncilTextService . Pattern text and flags come from RegexPatterns; the match timeout comes from SystemVariables.

Inheritance object CouncilTextPatternDataService

Implements ICouncilTextPatternDataService

```
public sealed class CouncilTextPatternDataService : ICouncilTextPatternDataService
```

🌟 Constructors 1

CouncilTextPatternDataService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ISystemVariableDefinitionService, ILogger<CouncilTextPatternDataService>)

Database boundary for every regular expression used by CouncilTextService . Pattern text and flags come from RegexPatterns; the match timeout comes from SystemVariables.

```
public CouncilTextPatternDataService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ISystemVariableDefinitionService systemVariables, ILogger<CouncilTextPatternDataService> logger)
```

🐾 Properties 38

AlphaNumericWordPattern

```
public Regex AlphaNumericWordPattern { get; }
```

BlazorFrontendPattern

```
public Regex BlazorFrontendPattern { get; }
```

CapabilityGapBlockPattern

```
public Regex CapabilityGapBlockPattern { get; }
```

CouncilDxFunctionCallPattern

```
public Regex CouncilDxFunctionCallPattern { get; }
```

DatapackPattern

```
public Regex DatapackPattern { get; }
```

DevExpressDocumentPattern

```
public Regex DevExpressDocumentPattern { get; }
```

DotNetPattern

```
public Regex DotNetPattern { get; }
```

FormerThoughtBreakPattern

```
public Regex FormerThoughtBreakPattern { get; }
```

FormerThoughtClosingFencePattern

```
public Regex FormerThoughtClosingFencePattern { get; }
```

FormerThoughtCodeWrapperPattern

```
public Regex FormerThoughtCodeWrapperPattern { get; }
```

FormerThoughtExcessLineBreakPattern

```
public Regex FormerThoughtExcessLineBreakPattern { get; }
```

FormerThoughtOpeningFencePattern

```
public Regex FormerThoughtOpeningFencePattern { get; }
```

FormerThoughtPresentationWrapperPattern

```
public Regex FormerThoughtPresentationWrapperPattern { get; }
```

FrontendPattern

```
public Regex FrontendPattern { get; }
```

HelpfulSourceLinePattern

```
public Regex HelpfulSourceLinePattern { get; }
```

IdentifierSeparatorPattern

```
public Regex IdentifierSeparatorPattern { get; }
```

IntegerPattern

```
public Regex IntegerPattern { get; }
```

KnowledgeBlockPattern

```
public Regex KnowledgeBlockPattern { get; }
```

LoggingPattern

```
public Regex LoggingPattern { get; }
```

MarkdownHeadingProjectNamePattern

```
public Regex MarkdownHeadingProjectNamePattern { get; }
```

MinecraftExplicitProjectNamePattern

```
public Regex MinecraftExplicitProjectNamePattern { get; }
```

MinecraftNamedProjectPattern

```
public Regex MinecraftNamedProjectPattern { get; }
```

MinecraftPattern

```
public Regex MinecraftPattern { get; }
```

MinecraftQuotedProjectNamePattern

```
public Regex MinecraftQuotedProjectNamePattern { get; }
```

MinecraftSkeletonMatrixPattern

```
public Regex MinecraftSkeletonMatrixPattern { get; }
```

MinecraftVersionPattern

```
public Regex MinecraftVersionPattern { get; }
```

MissingFeaturePattern

```
public Regex MissingFeaturePattern { get; }
```

ModIdCleanerPattern

```
public Regex ModIdCleanerPattern { get; }
```

NameCleanerPattern

```
public Regex NameCleanerPattern { get; }
```

PackagePartCleanerPattern

```
public Regex PackagePartCleanerPattern { get; }
```

PackageReferencePattern

```
public Regex PackageReferencePattern { get; }
```

SensitiveNamePattern

```
public Regex SensitiveNamePattern { get; }
```

StreamStatusPattern

```
public Regex StreamStatusPattern { get; }
```

StructuredFieldPattern

```
public Regex StructuredFieldPattern { get; }
```

TargetFrameworkPattern

```
public Regex TargetFrameworkPattern { get; }
```

ThinkingBlockPattern

```
public Regex ThinkingBlockPattern { get; }
```

TruncatedTailPattern

```
public Regex TruncatedTailPattern { get; }
```

WhitespacePattern

```
public Regex WhitespacePattern { get; }
```

⚙️ Methods 1

ExtractStructuredField(string, string)

```
public string? ExtractStructuredField(string body, string name)
```

api/LocalGPT.Services.Persistence.DatabaseFileHealthService.html

Class DatabaseFileHealthService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Performs bounded SQLite integrity checks and preserves confirmed malformed files before recreation. It deliberately does not treat locks, permission errors, or migration differences as corruption.

Inheritance object DatabaseFileHealthService

Implements IDatabaseFileHealthService

```
public sealed class DatabaseFileHealthService : IDatabaseFileHealthService
```

💡 Constructors 1

DatabaseFileHealthService(LocalGptDatabaseOptions, ILogger<DatabaseFileHealthService>)

Performs bounded SQLite integrity checks and preserves confirmed malformed files before recreation. It deliberately does not treat locks, permission errors, or migration differences as corruption.

```
public DatabaseFileHealthService(LocalGptDatabaseOptions options, ILogger<DatabaseFileHealthService> logger)
```

🐾 Properties 1

DatabasePath

```
public string DatabasePath { get; }
```

⚙️ Methods 3

EnsureHealthyOrRecoverAsync(CancellationTokens)

```
public Task EnsureHealthyOrRecoverAsync(CancellationTokens cancellationTokens = default)
```

IsSQLiteCorruption(Exception)

```
public bool IsSQLiteCorruption(Exception exception)
```

RecoverMalformedDatabaseAsync(CancellationTokens)

```
public Task RecoverMalformedDatabaseAsync(CancellationTokens cancellationTokens = default)
```

Class DatabaseInitializationHostedService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object DatabaseInitializationHostedService

Implements IHostedService

```
public sealed class DatabaseInitializationHostedService : IHostedService
```

🌟 Constructors 1

DatabaseInitializationHostedService(IDatabaseInitializationService, ILogger<DatabaseInitializationHostedService>)

```
public DatabaseInitializationHostedService(IDatabaseInitializationService initializer, ILogger<DatabaseInitializationHostedService> logger)
```

⚙️ Methods 2

StartAsync(CancellationTokens)

```
public Task StartAsync(CancellationTokens cancellationTokens)
```

StopAsync(CancellationTokens)

```
public Task StopAsync(CancellationTokens cancellationTokens)
```

Class DatabaseInitializationService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Coordinates database health, compatibility reconciliation, EF migration, and deterministic seeding. Low-level migration-history inspection belongs to IDatabaseMigrationCompatibilityService .

Inheritance object DatabaseInitializationService

Implements IDatabaseInitializationService

```
public sealed class DatabaseInitializationService : IDatabaseInitializationService
```

🌟 Constructors 1

DatabaseInitializationService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseFileHealthService, IDatabaseMigrationCompatibilityService, IInitialDataCatalog, ILocalGptRuntimePolicySeedDataService, IServiceActivityService, IDatabaseLoggerReadiness, IHostEnvironment, ILogger<DatabaseInitializationService>)

Coordinates database health, compatibility reconciliation, EF migration, and deterministic seeding. Low-level migration-history inspection belongs to IDatabaseMigrationCompatibilityService .

```
public DatabaseInitializationService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseFileHealthService databaseFileHealth, IDatabaseMigrationCompatibilityService migrationCompatibility, IInitialDataCatalog catalog, ILocalGptRuntimePolicySeedDataService runtimePolicySeed, IServiceActivityService serviceActivity, IDatabaseLoggerReadiness databaseLoggerReadiness, IHostEnvironment hostEnvironment, ILogger<DatabaseInitializationService> logger)
```

⚙️ Methods 1

InitializeAsync(CancellationTokens)

```
public Task InitializeAsync(CancellationTokens cancellationTokens = default)
```

Class DatabaseLoggerReadiness

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

One-way startup gate shared by database initialization and the database logger worker.

Inheritance object DatabaseLoggerReadiness

Implements IDatabaseLoggerReadiness

```
public sealed class DatabaseLoggerReadiness : IDatabaseLoggerReadiness
```

🌟 Constructors 1

DatabaseLoggerReadiness()

```
public DatabaseLoggerReadiness()
```

🔗 Properties 1

IsReady

```
public bool IsReady { get; }
```

⚙️ Methods 2

MarkReady()

```
public void MarkReady()
```

WaitUntilReadyAsync(CancellationTokens)

```
public Task WaitUntilReadyAsync(CancellationTokens cancellationTokens = default)
```

Class DatabaseMigrationCompatibilityService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Owns legacy SQLite schema adoption and compatibility backup logic. This responsibility is isolated from database seeding so migration reconciliation is testable, logged, and represented in bounded LocalGPT short-term operational memory.

Inheritance object DatabaseMigrationCompatibilityService

Implements IDatabaseMigrationCompatibilityService

```
public sealed class DatabaseMigrationCompatibilityService : IDatabaseMigrationCompatibilityService
```

🌟 Constructors 1

DatabaseMigrationCompatibilityService(IDatabaseFileHealthService, IServiceActivityService, ILogger<DatabaseMigrationCompatibilityService>)

```
public DatabaseMigrationCompatibilityService(IDatabaseFileHealthService databaseFileHealth, IServiceActivityService serviceActivity,
ILogger<DatabaseMigrationCompatibilityService> logger)
```

⚙️ Methods 1

PrepareAsync(CancellationTokens)

```
public Task PrepareAsync(CancellationTokens cancellationTokens = default)
```

Namespace LocalGPT.Services.Persistence

Classes

Database boundary for every regular expression used by CouncilTextService . Pattern text and flags come from RegexPatterns; the match timeout comes from SystemVariables.

Performs bounded SQLite integrity checks and preserves confirmed malformed files before recreation. It deliberately does not treat locks, permission errors, or migration differences as corruption.

Coordinates database health, compatibility reconciliation, EF migration, and deterministic seeding. Low-level migration-history inspection belongs to IDatabaseMigrationCompatibilityService .

One-way startup gate shared by database initialization and the database logger worker.

Owns legacy SQLite schema adoption and compatibility backup logic. This responsibility is isolated from database seeding so migration reconciliation is testable, logged, and represented in bounded LocalGPT short-term operational memory.

Creates the maintained strongly typed system-variable definitions and their deterministic seed values.

Class InitialDataCatalog

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object InitialDataCatalog

Implements IInitialDataCatalog

```
public sealed class InitialDataCatalog : IInitialDataCatalog
```

🌟 Constructors 1

InitialDataCatalog(IWebHostEnvironment, ILogger<InitialDataCatalog>, ISystemVariableDefinitionService, ILocalGptRuntimePolicySeedDataService)

```
public InitialDataCatalog(IWebHostEnvironment environment, ILogger<InitialDataCatalog> logger, ISystemVariableDefinitionService systemVariables, ILocalGptRuntimePolicySeedDataService runtimePolicySeed)
```

🐾 Properties 3

Prompts

```
public IReadOnlyList<PromptConfigDto> Prompts { get; }
```

RegexPatterns

```
public IReadOnlyList<RegexPatternDto> RegexPatterns { get; }
```

Variables

```
public IReadOnlyList<InitialVariable> Variables { get; }
```

⚙️ Methods 1

LoadKnowledgeAsync(CancellationTokens)

```
public Task<IReadOnlyList<CouncilKnowledgeEntry>> LoadKnowledgeAsync(CancellationTokens cancellationTokens = default)
```


Class LocalGptRuntimePolicyDataService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicyDataService

Implements ILocalGptRuntimePolicyDataService

```
public sealed class LocalGptRuntimePolicyDataService : ILocalGptRuntimePolicyDataService
```

🌟 Constructors 1

LocalGptRuntimePolicyDataService(ILocalGptRuntimePolicyStoreService, ILogger<LocalGptRuntimePolicyDataService>)

```
public LocalGptRuntimePolicyDataService(ILocalGptRuntimePolicyStoreService store, ILogger<LocalGptRuntimePolicyDataService> logger)
```

🐾 Properties 6

AllowedNativeExecutables

```
public FrozenSet<string> AllowedNativeExecutables { get; }
```

LocalGptCoreProjectId

```
public Guid LocalGptCoreProjectId { get; }
```

PowerShellFilePattern

```
public Regex PowerShellFilePattern { get; }
```

PowerShellInlineCommandPattern

```
public Regex PowerShellInlineCommandPattern { get; }
```

RegexTimeout

```
public TimeSpan RegexTimeout { get; }
```

SensitiveArgumentPattern

```
public Regex SensitiveArgumentPattern { get; }
```

⚙️ Methods 9

GetCollection(LocalGptRuntimeCollection)

```
public FrozenSet<string> GetCollection(LocalGptRuntimeCollection key)
```

GetGuid(LocalGptRuntimeValue)

```
public Guid GetGuid(LocalGptRuntimeValue key)
```

GetInt(LocalGptRuntimeValue)

```
public int GetInt(LocalGptRuntimeValue key)
```

GetJson<T>(LocalGptRuntimeValue)

```
public T GetJson<T>(LocalGptRuntimeValue key)
```

GetLong(LocalGptRuntimeValue)

```
public long GetLong(LocalGptRuntimeValue key)
```

GetPattern(LocalGptRuntimePattern)

```
public Regex GetPattern(LocalGptRuntimePattern key)
```

GetSnapshot()

```
public LocalGptRuntimePolicySnapshot GetSnapshot()
```

GetString(LocalGptRuntimeValue)

```
public string GetString(LocalGptRuntimeValue key)
```

Reload()

```
public LocalGptRuntimePolicySnapshot Reload()
```

Class LocalGptRuntimePolicySeedDataService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicySeedDataService

Implements ILocalGptRuntimePolicySeedDataService

```
public sealed class LocalGptRuntimePolicySeedDataService : ILocalGptRuntimePolicySeedDataService
```

🌟 Constructors 1

LocalGptRuntimePolicySeedDataService(ILogger<LocalGptRuntimePolicySeedDataService>)

```
public LocalGptRuntimePolicySeedDataService(ILogger<LocalGptRuntimePolicySeedDataService> logger)
```

⚙️ Methods 1

GetSeed()

```
public LocalGptRuntimePolicySeedModel GetSeed()
```

Class LocalGptRuntimePolicyStoreService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object LocalGptRuntimePolicyStoreService

Implements ILocalGptRuntimePolicyStoreService

```
public sealed class LocalGptRuntimePolicyStoreService : ILocalGptRuntimePolicyStoreService
```

🌟 Constructors 1

LocalGptRuntimePolicyStoreService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILocalGptRuntimePolicySeedDataService, ILogger<LocalGptRuntimePolicyStoreService>)

```
public LocalGptRuntimePolicyStoreService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILocalGptRuntimePolicySeedDataService seedData, ILogger<LocalGptRuntimePolicyStoreService> logger)
```

⚙️ Methods 1

GetDefinition()

```
public LocalGptRuntimePolicyDefinition? GetDefinition()
```

Class LocalGptVocabularyService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object LocalGptVocabularyService

Implements ILocalGptVocabularyService

```
public sealed class LocalGptVocabularyService : ILocalGptVocabularyService
```

🌟 Constructors 1

LocalGptVocabularyService(ILocalGptRuntimePolicyDataService, ILogger<LocalGptVocabularyService>)

```
public LocalGptVocabularyService(ILocalGptRuntimePolicyDataService runtimePolicy, ILogger<LocalGptVocabularyService> logger)
```

⚙️ Methods 1

Get()

```
public LocalGptVocabularySnapshot Get()
```

Class OneWireReplayPolicyDataService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object OneWireReplayPolicyDataService

Implements IOneWireReplayPolicyDataService

```
public sealed class OneWireReplayPolicyDataService : IOneWireReplayPolicyDataService
```

✨ Constructors 1

OneWireReplayPolicyDataService(ILogger<OneWireReplayPolicyDataService>)

```
public OneWireReplayPolicyDataService(ILogger<OneWireReplayPolicyDataService> logger)
```

⚙️ Methods 1

GetSnapshot()

```
public OneWireReplayPolicySnapshot GetSnapshot()
```

Class RegexPatternService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Inheritance object RegexPatternService

Implements IRegexPatternService

```
public sealed class RegexPatternService : IRegexPatternService
```

✨ Constructors 1

RegexPatternService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<RegexPatternService>)

```
public RegexPatternService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<RegexPatternService> logger)
```

⚙️ Methods 8

AddOrUpdateAsync(RegexPatternDto)

```
public Task AddOrUpdateAsync(RegexPatternDto dto)
```

Compile(string, string?)

```
public Regex Compile(string pattern, string? flags = null)
```

Compile(string, string?, TimeSpan)

```
public Regex Compile(string pattern, string? flags, TimeSpan timeout)
```

DeleteAsync(string)

```
public Task DeleteAsync(string name)
```

DeleteAsync(string, bool)

```
public Task DeleteAsync(string name, bool confirm = false)
```

GetRegexAsync(string)

```
public Task<Regex?> GetRegexAsync(string name)
```

ListAllAsync()

```
public Task<List<RegexPattern>> ListAllAsync()
```

ListAllAsync(int?)

```
public Task<List<RegexPattern>> ListAllAsync(int? take = null)
```

Class SystemVariableDefinitionService

Namespace LocalGPT . Services . Persistence Assembly LocalGPT.dll

Creates the maintained strongly typed system-variable definitions and their deterministic seed values.

Inheritance object SystemVariableDefinitionService

Implements ISystemVariableDefinitionService

```
[DocumentationUpdated("2.1.20")] public sealed class SystemVariableDefinitionService : ISystemVariableDefinitionService
```

🌟 Constructors 1

SystemVariableDefinitionService(ILogger<SystemVariableDefinitionService>)

Initializes every maintained system-variable definition.

```
public SystemVariableDefinitionService(ILogger<SystemVariableDefinitionService> logger)
```

🐾 Properties 23

CouncilDefaultsVersion

Gets the Council defaults migration-version definition.

```
public SystemVariableDefinition<int> CouncilDefaultsVersion { get; }
```

CouncilDxMaximumCallsPerStep

Gets the maximum DXFunction calls per Council step definition.

```
public SystemVariableDefinition<int> CouncilDxMaximumCallsPerStep { get; }
```

CouncilDxMaximumParameterCharacters

Gets the maximum DXFunction parameter-character definition.

```
public SystemVariableDefinition<int> CouncilDxMaximumParameterCharacters { get; }
```

CouncilDxMaximumResultCharacters

Gets the maximum DXFunction result-character definition.

```
public SystemVariableDefinition<int> CouncilDxMaximumResultCharacters { get; }
```

DefaultContextTokens

Gets the default context-token definition.

```
public SystemVariableDefinition<int> DefaultContextTokens { get; }
```

DefaultCouncilCritiqueRounds

Gets the default Council critique-round definition.

```
public SystemVariableDefinition<int> DefaultCouncilCritiqueRounds { get; }
```

DefaultCouncilResourceLoadPercent

Gets the default Council resource-load percentage definition.

```
public SystemVariableDefinition<int> DefaultCouncilResourceLoadPercent { get; }
```

DefaultHeavyModelGpuLayers

Gets the legacy heavy-model GPU-layer default.

```
public SystemVariableDefinition<int> DefaultHeavyModelGpuLayers { get; }
```

DefaultMaxOutputTokens

Gets the default maximum output-token definition.

```
public SystemVariableDefinition<int> DefaultMaxOutputTokens { get; }
```

DefaultMaxParallelModels

Gets the default maximum parallel-model definition.

```
public SystemVariableDefinition<int> DefaultMaxParallelModels { get; }
```

DefaultMaxPromptCharacters

Gets the default maximum prompt-character definition.

```
public SystemVariableDefinition<int> DefaultMaxPromptCharacters { get; }
```

DefaultOllamaEndpoint

Gets the default loopback Ollama endpoint definition.

```
public SystemVariableDefinition<string> DefaultOllamaEndpoint { get; }
```

FirstRunOnboardingCompleted

Gets the persisted first-run onboarding completion flag definition.

```
public SystemVariableDefinition<bool> FirstRunOnboardingCompleted { get; }
```

InitialValues

Gets the deterministic initial variable list.

```
public IReadOnlyList<InitialVariable> InitialValues { get; }
```

LegacyCouncilResourceLoadPercent

Gets the former hard-coded Council resource-load percentage.

```
public int LegacyCouncilResourceLoadPercent { get; }
```

MaxBootstrapCharacters

Gets the maximum bootstrap-character definition.

```
public SystemVariableDefinition<int> MaxBootstrapCharacters { get; }
```

MaxContextTokens

Gets the maximum context-token definition.

```
public SystemVariableDefinition<int> MaxContextTokens { get; }
```

MaxOutputTokens

Gets the maximum output-token definition.

```
public SystemVariableDefinition<int> MaxOutputTokens { get; }
```

MinContextTokens

Gets the minimum context-token definition.

```
public SystemVariableDefinition<int> MinContextTokens { get; }
```

MinOutputTokens

Gets the minimum output-token definition.

```
public SystemVariableDefinition<int> MinOutputTokens { get; }
```

ProviderSelectionPolicy

Gets the provider-selection policy definition.

```
public SystemVariableDefinition<string> ProviderSelectionPolicy { get; }
```

RegexMatchTimeoutMilliseconds

Gets the regular-expression timeout definition.

```
public SystemVariableDefinition<int> RegexMatchTimeoutMilliseconds { get; }
```

RepositoryKnowledgeSeedVersion

Gets the repository knowledge seed-version definition.

```
public SystemVariableDefinition<int> RepositoryKnowledgeSeedVersion { get; }
```

Class PlanEmbeddedFirmwareFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PlanEmbeddedFirmwareFunction

Implements IDxAiFunctionHandler

```
public sealed class PlanEmbeddedFirmwareFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

PlanEmbeddedFirmwareFunction(IDxAiFunctionJsonService, IEmbeddedFirmwarePlanningService, ILogger<PlanEmbeddedFirmwareFunction>)

```
public PlanEmbeddedFirmwareFunction(IDxAiFunctionJsonService json, IEmbeddedFirmwarePlanningService planning, ILogger<PlanEmbeddedFirmwareFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class PreviewCouncilGameControlFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PreviewCouncilGameControlFunction

Implements IDxAiFunctionHandler

```
public sealed class PreviewCouncilGameControlFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

PreviewCouncilGameControlFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<PreviewCouncilGameControlFunction>)

```
public PreviewCouncilGameControlFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<PreviewCouncilGameControlFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class PreviewEmbeddedOneWireEnvelopeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PreviewEmbeddedOneWireEnvelopeFunction

Implements IDxAiFunctionHandler

```
public sealed class PreviewEmbeddedOneWireEnvelopeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

PreviewEmbeddedOneWireEnvelopeFunction(IDxAiFunctionJsonService, IEmbeddedTelemetryBridgeService)

```
public PreviewEmbeddedOneWireEnvelopeFunction(IDxAiFunctionJsonService json, IEmbeddedTelemetryBridgeService bridge)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class PreviewEmbeddedTelemetryFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PreviewEmbeddedTelemetryFunction

Implements IDxAiFunctionHandler

```
public sealed class PreviewEmbeddedTelemetryFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

PreviewEmbeddedTelemetryFunction(IDxAiFunctionJsonService, IEmbeddedTelemetryBridgeService)

```
public PreviewEmbeddedTelemetryFunction(IDxAiFunctionJsonService json, IEmbeddedTelemetryBridgeService bridge)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class PreviewSqliteTableFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PreviewSqliteTableFunction

Implements IDxAiFunctionHandler

```
public sealed class PreviewSqliteTableFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

PreviewSqliteTableFunction(IDxAiFunctionJsonService, ISqliteTableEditorService, ILogger<PreviewSqliteTableFunction>)

```
public PreviewSqliteTableFunction(IDxAiFunctionJsonService json, ISqliteTableEditorService editor, ILogger<PreviewSqliteTableFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```


Class ProjectArchitectureService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ProjectArchitectureService

Implements IProjectArchitectureService

```
public sealed class ProjectArchitectureService : IProjectArchitectureService
```

🌟 Constructors 1

ProjectArchitectureService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<ProjectArchitectureService>)

```
public ProjectArchitectureService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<ProjectArchitectureService> logger)
```

⚙️ Methods 9

BuildArchitectureBriefingAsync(Guid, Guid?, CancellationToken)

```
public Task<string> BuildArchitectureBriefingAsync(Guid projectId, Guid? revisionId, CancellationToken cancellationToken = default)
```

EnsureCouncilRunProjectAsync(Guid, string?, string, CancellationToken)

```
public Task<(LocalGptProject Project, LocalGptProjectRevision Revision)> EnsureCouncilRunProjectAsync(Guid councilRunId, string? title, string prompt, CancellationToken cancellationToken = default)
```

GetArtifactsAsync(Guid, CancellationToken)

```
public Task<IReadOnlyList<LocalGptProjectArtifact>> GetArtifactsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetRequirementsAsync(Guid, CancellationToken)

```
public Task<IReadOnlyList<LocalGptProjectRequirement>> GetRequirementsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

GetRevisionsAsync(Guid, CancellationToken)

```
public Task<IReadOnlyList<LocalGptProjectRevision>> GetRevisionsAsync(Guid projectId, CancellationToken cancellationToken = default)
```

SaveArtifactAsync(Guid, SaveProjectArtifactRequest, CancellationToken)

```
public Task<LocalGptProjectArtifact> SaveArtifactAsync(Guid projectId, SaveProjectArtifactRequest request, CancellationToken cancellationToken = default)
```

SaveRequirementAsync(Guid, SaveProjectRequirementRequest, CancellationToken)

```
public Task<LocalGptProjectRequirement> SaveRequirementAsync(Guid projectId, SaveProjectRequirementRequest request, CancellationToken cancellationToken = default)
```

SaveRequirementLinkAsync(Guid, SaveProjectRequirementLinkRequest, CancellationToken)

```
public Task<LocalGptProjectRequirementLink> SaveRequirementLinkAsync(Guid projectId, SaveProjectRequirementLinkRequest request, CancellationToken cancellationToken = default)
```

SaveRevisionAsync(Guid, SaveProjectRevisionRequest, CancellationToken)

```
public Task<LocalGptProjectRevision> SaveRevisionAsync(Guid projectId, SaveProjectRevisionRequest request, CancellationToken cancellationToken = default)
```

Class ProjectLibraryInventoryService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ProjectLibraryInventoryService

Implements IPProjectLibraryInventoryService

```
public class ProjectLibraryInventoryService : IPProjectLibraryInventoryService
```

✨ Constructors 1

ProjectLibraryInventoryService(ILogger<ProjectLibraryInventoryService>, CouncilRuntimeService)

```
public ProjectLibraryInventoryService(ILogger<ProjectLibraryInventoryService> logger, CouncilRuntimeService councilRuntime)
```

⚙️ Methods 1

BuildDevExpressBriefingAsync(CancellationTokens)

```
public Task<string> BuildDevExpressBriefingAsync(CancellationTokens cancellationTokens = default)
```

Class ProjectMaintenanceService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ProjectMaintenanceService

Implements IPProjectMaintenanceService

```
public sealed class ProjectMaintenanceService : IPProjectMaintenanceService
```

🌟 Constructors 1

ProjectMaintenanceService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILocalGptRuntimePolicyDataService, ILogger<ProjectMaintenanceService>)

```
public ProjectMaintenanceService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILocalGptRuntimePolicyDataService runtimePolicy, ILogger<ProjectMaintenanceService> logger)
```

⚙️ Methods 16

ApproveRevisionReadyForTestAsync(Guid, Guid, ApproveRevisionReadyForTestRequest, CancellationToken)

```
public Task<ProjectBuildVerification> ApproveRevisionReadyForTestAsync(Guid projectId, Guid revisionId, ApproveRevisionReadyForTestRequest request, CancellationToken cancellationToken = default)
```

AssessWorkspacePermissionsAsync(Guid, bool, CancellationToken)

```
public Task<WorkspacePermissionAssessment> AssessWorkspacePermissionsAsync(Guid workspaceRootId, bool userConfirmedWriteProbe, CancellationToken cancellationToken = default)
```

DeleteCompilerInstallationAsync(Guid, bool, CancellationToken)

Deletes one unreferenced compiler installation after explicit user confirmation.

```
public Task<bool> DeleteCompilerInstallationAsync(Guid compilerId, bool userConfirmed, CancellationToken cancellationToken = default)
```

DiscoverCompilerInstallationsAsync(DiscoverProjectCompilersRequest, CancellationToken)

Discovers compiler and runtime executables from approved local search locations.

```
public Task<IReadOnlyList<ProjectCompilerInstallation>> DiscoverCompilerInstallationsAsync(DiscoverProjectCompilersRequest request, CancellationToken cancellationToken = default)
```

GetCompilerInstallationsAsync(CancellationToken)

Lists stored compiler and runtime toolchain profiles.

```
public Task<IReadOnlyList<ProjectCompilerInstallation>> GetCompilerInstallationsAsync(CancellationToken cancellationToken = default)
```

GetTrackedFilesAsync(Guid, Guid?, CancellationToken)

```
public Task<IReadOnlyList<LocalGptProjectTrackedFile>> GetTrackedFilesAsync(Guid projectId, Guid? revisionId = null, CancellationToken cancellationToken = default)
```

GetWorkspaceRootsAsync(Guid?, CancellationToken)

```
public Task<IReadOnlyList<ProjectWorkspaceRoot>> GetWorkspaceRootsAsync(Guid? projectId = null, CancellationToken cancellationToken = default)
```

RecordCouncilBuildReviewAsync(Guid, RecordCouncilBuildReviewRequest, CancellationToken)

```
public Task<ProjectBuildVerification> RecordCouncilBuildReviewAsync(Guid verificationId, RecordCouncilBuildReviewRequest request, CancellationToken cancellationToken = default)
```

RegisterRevisionWorkspaceAsync(Guid, Guid, string, string, bool, CancellationToken)

```
public Task<LocalGptProjectRevision> RegisterRevisionWorkspaceAsync(Guid projectId, Guid revisionId, string sourceRootPath, string solutionPath, bool userConfirmed, CancellationToken cancellationToken = default)
```

ResolveWorkspaceAsync(Guid, CancellationToken)

```
public Task<ProjectWorkspaceResolution> ResolveWorkspaceAsync(Guid projectId, CancellationToken cancellationToken = default)
```

RunBuildVerificationAsync(Guid, RunProjectBuildVerificationRequest, CancellationToken)

```
public Task<ProjectBuildVerification> RunBuildVerificationAsync(Guid projectId, RunProjectBuildVerificationRequest request, CancellationToken cancellationToken = default)
```

SaveCompilerInstallationAsync(SaveProjectCompilerInstallationRequest, CancellationToken)

Creates or updates one approval-gated compiler profile.

```
public Task<ProjectCompilerInstallation> SaveCompilerInstallationAsync(SaveProjectCompilerInstallationRequest request, CancellationToken cancellationToken = default)
```

SaveTrackedFilePatternAsync(Guid, SaveTrackedFilePatternRequest, CancellationTokens)

```
public Task<LocalGptProjectTrackedFile> SaveTrackedFilePatternAsync(Guid trackedFileId, SaveTrackedFilePatternRequest request, CancellationTokens cancellationTokens = default)
```

SaveWorkspaceRootAsync(SaveProjectWorkspaceRootRequest, CancellationTokens)

```
public Task<ProjectWorkspaceRoot> SaveWorkspaceRootAsync(SaveProjectWorkspaceRootRequest request, CancellationTokens cancellationTokens = default)
```

ScanProjectFilesAsync(Guid, ScanProjectFilesRequest, CancellationTokens)

```
public Task<ProjectScanResult> ScanProjectFilesAsync(Guid projectId, ScanProjectFilesRequest request, CancellationTokens cancellationTokens = default)
```

ValidateCompilerInstallationAsync(Guid, bool, CancellationTokens)

Executes the bounded validation command for one stored compiler profile.

```
public Task<ProjectCompilerInstallation> ValidateCompilerInstallationAsync(Guid compilerId, bool userConfirmed, CancellationTokens cancellationTokens = default)
```

api/LocalGPT.Services.ProjectOrganicContextService.html

Class ProjectOrganicContextService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ProjectOrganicContextService

Implements IPProjectOrganicContextService

```
public sealed class ProjectOrganicContextService : IPProjectOrganicContextService
```

🌟 Constructors 1

ProjectOrganicContextService(IPProjectArchitectureService, ILogger<ProjectOrganicContextService>)

```
public ProjectOrganicContextService(IPProjectArchitectureService projectArchitecture, ILogger<ProjectOrganicContextService> logger)
```

⚙️ Methods 3

BuildBriefingAsync(Guid, Guid?, CancellationTokens)

```
public Task<string> BuildBriefingAsync(Guid projectId, Guid? revisionId, CancellationTokens cancellationTokens = default)
```

GetAsync(Guid, Guid?, CancellationTokens)

```
public Task<ProjectOrganicContext> GetAsync(Guid projectId, Guid? revisionId, CancellationTokens cancellationTokens = default)
```

SaveAsync(Guid, SaveProjectOrganicContextRequest, CancellationTokens)

```
public Task<ProjectOrganicContext> SaveAsync(Guid projectId, SaveProjectOrganicContextRequest request, CancellationTokens cancellationTokens = default)
```

Class PromptConfigService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PromptConfigService

Implements IPromptConfigService

```
public sealed class PromptConfigService : IPromptConfigService
```

🌟 Constructors 1

PromptConfigService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<PromptConfigService>)

```
public PromptConfigService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<PromptConfigService> logger)
```

⚙️ Methods 4

GetPromptAsync(PromptConfigDto, CancellationToken)

```
public Task<string> GetPromptAsync(PromptConfigDto dto, CancellationToken cancellationToken = default)
```

GetPromptAsync(string, string, CancellationToken)

```
public Task<string> GetPromptAsync(string key, string language = "en", CancellationToken cancellationToken = default)
```

ListPromptsAsync(string?, CancellationToken)

```
public Task<IEnumerable<PromptConfig>> ListPromptsAsync(string? language = null, CancellationToken cancellationToken = default)
```

UpdatePromptAsync(PromptConfigDto, CancellationToken)

```
public Task UpdatePromptAsync(PromptConfigDto dto, CancellationToken cancellationToken = default)
```

Class ProviderModelBenchmarkService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Bounded benchmark and council review for provider-qualified models. The service does not download models or alter provider-global settings. Applying a recommendation creates or updates a user-approved LocalGPT model preset whose routes retain provider, endpoint and provider model name.

Inheritance object ProviderModelBenchmarkService

Implements IProviderModelBenchmarkService

```
public sealed class ProviderModelBenchmarkService : IProviderModelBenchmarkService
```

🌟 Constructors 1

ProviderModelBenchmarkService(IProviderModelRuntimeService, IModelPresetService, ILogger<ProviderModelBenchmarkService>)

Bounded benchmark and council review for provider-qualified models. The service does not download models or alter provider-global settings. Applying a recommendation creates or updates a user-approved LocalGPT model preset whose routes retain provider, endpoint and provider model name.

```
public ProviderModelBenchmarkService(IProviderModelRuntimeService providerModels, IModelPresetService modelPresets, ILogger<ProviderModelBenchmarkService> logger)
```

⚙️ Methods 2

ApplyRecommendationsAsync(ProviderModelBenchmarkReport, string, bool, bool, CancellationToken)

```
public Task<IReadOnlyList<CouncilModelPreset>> ApplyRecommendationsAsync(ProviderModelBenchmarkReport report, string presetName, bool makeDefault, bool userConfirmed, CancellationToken cancellationToken = default)
```

RunAsync(ProviderModelBenchmarkRequest, CancellationToken)

```
public Task<ProviderModelBenchmarkReport> RunAsync(ProviderModelBenchmarkRequest request, CancellationToken cancellationToken = default)
```

Class ProviderModelRuntimeService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Discovers and opens provider-qualified model sessions. A model name is never treated as a globally unique address: provider kind and endpoint are always retained with it.

Inheritance object ProviderModelRuntimeService

Implements IProviderModelRuntimeService

```
public sealed class ProviderModelRuntimeService : IProviderModelRuntimeService
```

🌟 Constructors 1

ProviderModelRuntimeService(IOptionsMonitor<ConfigurationRoot>, ILoggerFactory, ILogger<ProviderModelRuntimeService>, CouncilRuntimeService, IChatResponseFormatterFactory, IChatProtocolResolver, IPromptConfigService, IDxAiFunctionRegistry)

Discovers and opens provider-qualified model sessions. A model name is never treated as a globally unique address: provider kind and endpoint are always retained with it.

```
public ProviderModelRuntimeService(IOptionsMonitor<ConfigurationRoot> optionsRoot, ILoggerFactory loggerFactory, ILogger<ProviderModelRuntimeService> logger, CouncilRuntimeService councilRuntime, IChatResponseFormatterFactory formatterFactory, IChatProtocolResolver protocolResolver, IPromptConfigService promptConfigService, IDxAiFunctionRegistry functionRegistry)
```

⚙️ Methods 6

CreateChatClient(ProviderModelReference, string, int, TimeSpan, int?)

```
public IChatClient CreateChatClient(ProviderModelReference model, string keepAlive, int maxContextTokens, TimeSpan timeout, int? ollamaNumGpu)
```

CreateSessionAsync(ProviderModelReference, CancellationToken)

```
public Task<ChatClientSession> CreateSessionAsync(ProviderModelReference model, CancellationToken cancellationToken = default)
```

FromSession(ChatClientSession)

```
public ProviderModelReference FromSession(ChatClientSession session)
```

GetCandidatesAsync(CancellationToken)

```
public Task<IReadOnlyList<MultiModelCouncilModelCandidate>> GetCandidatesAsync(CancellationToken cancellationToken = default)
```

Remember(ProviderModelReference)

```
public void Remember(ProviderModelReference model)
```

ResolveAsync(string, CancellationToken)

```
public Task<ProviderModelReference> ResolveAsync(string selectionOrModelName, CancellationToken cancellationToken = default)
```

Class PublicServiceMethodInvoker

Namespace LocalGPT . Services Assembly LocalGPT.dll

Invokes only a public method that the local user explicitly enabled in the database-backed catalog. Parameter binding is typed from the method signature; the caller cannot choose an arbitrary CLR type or method name.

Inheritance object PublicServiceMethodInvoker

Implements IPublicServiceMethodInvoker

```
public sealed class PublicServiceMethodInvoker : IPublicServiceMethodInvoker
```

🌟 Constructors 1

PublicServiceMethodInvoker(ILocalGptVocabularyService, IServiceProvider, IDxAiFunctionCatalogService, ILogger<PublicServiceMethodInvoker>)

Invokes only a public method that the local user explicitly enabled in the database-backed catalog. Parameter binding is typed from the method signature; the caller cannot choose an arbitrary CLR type or method name.

```
public PublicServiceMethodInvoker(ILocalGptVocabularyService vocabulary, IServiceProvider serviceProvider, IDxAiFunctionCatalogService catalog, ILogger<PublicServiceMethodInvoker> logger)
```

⚙️ Methods 1

InvokeAsync(PublicServiceMethodInvocationRequest, CancellationToken)

```
public Task<object?> InvokeAsync(PublicServiceMethodInvocationRequest request, CancellationToken cancellationToken = default)
```

Class PublishEmbeddedTelemetryFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object PublishEmbeddedTelemetryFunction

Implements IDxAiFunctionHandler

```
public sealed class PublishEmbeddedTelemetryFunction : IDxAiFunctionHandler
```

✨ Constructors 1

PublishEmbeddedTelemetryFunction(IDxAiFunctionJsonService, IEmbeddedTelemetryIngressService)

```
public PublishEmbeddedTelemetryFunction(IDxAiFunctionJsonService json, IEmbeddedTelemetryIngressService ingress)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ReactiveObjectCouncilGameSubdirector

Namespace LocalGPT . Services Assembly LocalGPT.dll

Predicts bounded reactions from doors, switches, pickups and hazards.

Inheritance object ReactiveObjectCouncilGameSubdirector

Implements ICouncilGameSubdirector

```
public sealed class ReactiveObjectCouncilGameSubdirector : ICouncilGameSubdirector
```

✨ Constructors 1

ReactiveObjectCouncilGameSubdirector(ICouncilGameActorRuntimeFactory)

Predicts bounded reactions from doors, switches, pickups and hazards.

```
public ReactiveObjectCouncilGameSubdirector(ICouncilGameActorRuntimeFactory actorFactory)
```

🐾 Properties 2

ActorKind

```
public CouncilGameActorKind ActorKind { get; }
```

Key

```
public string Key { get; }
```

⚙️ Methods 1

PredictAsync(CouncilGameDirectorContext, CancellationToken)

Produces a bounded prediction for the proposed action.

```
public Task<CouncilGameSubdirectorPrediction> PredictAsync(CouncilGameDirectorContext context, CancellationToken cancellationTok = default)
```

Class ReadExactSqliteTableFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ReadExactSqliteTableFunction

Implements IDxAiFunctionHandler

```
public sealed class ReadExactSqliteTableFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ReadExactSqliteTableFunction(IDxAiFunctionJsonService, ISqliteTableEditorService, ILogger<ReadExactSqliteTableFunction>)

```
public ReadExactSqliteTableFunction(IDxAiFunctionJsonService json, ISqliteTableEditorService editor, ILogger<ReadExactSqliteTableFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class RecordProjectCouncilBuildReviewFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RecordProjectCouncilBuildReviewFunction

Implements IDxAiFunctionHandler

```
public sealed class RecordProjectCouncilBuildReviewFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RecordProjectCouncilBuildReviewFunction(IDxAiFunction.JsonService, IProjectMaintenanceService, ILogger<RecordProjectCouncilBuildReviewFunction>)

```
public RecordProjectCouncilBuildReviewFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance, ILogger<RecordProjectCouncilBuildReviewFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```


Class RegexFunctionParameterService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RegexFunctionParameterService

Implements IRegexFunctionParameterService

```
public sealed class RegexFunctionParameterService : IRegexFunctionParameterService
```

🌟 Constructors 1

RegexFunctionParameterService(ILogger<RegexFunctionParameterService>)

```
public RegexFunctionParameterService(ILogger<RegexFunctionParameterService> logger)
```

⚙️ Methods 1

GetRequiredString(JsonElement, string)

```
public string GetRequiredString(JsonElement element, string propertyName)
```

Class RegisterProjectRevisionWorkspaceFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RegisterProjectRevisionWorkspaceFunction

Implements IDxAiFunctionHandler

```
public sealed class RegisterProjectRevisionWorkspaceFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RegisterProjectRevisionWorkspaceFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<RegisterProjectRevisionWorkspaceFunction>)

```
public RegisterProjectRevisionWorkspaceFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance,
ILogger<RegisterProjectRevisionWorkspaceFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class RejectCodeGenerationReviewFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RejectCodeGenerationReviewFunction

Implements IDxAiFunctionHandler

```
public sealed class RejectCodeGenerationReviewFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RejectCodeGenerationReviewFunction(IDxAiFunctionJsonService, ICodeGenerationWorkflowService, ILogger<RejectCodeGenerationReviewFunction>)

```
public RejectCodeGenerationReviewFunction(IDxAiFunctionJsonService json, ICodeGenerationWorkflowService workflow,
ILogger<RejectCodeGenerationReviewFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class RemoteImportDxParameterReader

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RemoteImportDxParameterReader

```
public sealed class RemoteImportDxParameterReader
```

🌟 Constructors 1

RemoteImportDxParameterReader(ILogger<RemoteImportDxParameterReader>)

```
public RemoteImportDxParameterReader(ILogger<RemoteImportDxParameterReader> logger)
```

⚙️ Methods 5

Boolean(JsonElement, string, bool)

```
public bool Boolean(JsonElement parameters, string name, bool fallback = false)
```

Build(JsonElement, bool, bool)

```
public RemoteKnowledgeImportRequest Build(JsonElement parameters, bool preview, bool confirmed)
```

Integer(JsonElement, string, int)

```
public int Integer(JsonElement parameters, string name, int fallback)
```

String(JsonElement, string, string)

```
public string String(JsonElement parameters, string name, string fallback = "")
```

Strings(JsonElement, string)

```
public List<string> Strings(JsonElement parameters, string name)
```

Class RemoteKnowledgeImportService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Downloads a user-selected public GitHub repository or webpage into the same local learn-base style cache used by LocalGPT, lists every returned file, applies a regex file policy, and then delegates database extraction to the existing learn-base importer.

Inheritance object RemoteKnowledgeImportService

Implements IRemoteKnowledgeImportService IDisposable

```
public sealed class RemoteKnowledgeImportService : IRemoteKnowledgeImportService, IDisposable
```

🌟 Constructors 1

RemoteKnowledgeImportService(ILearnBaseKnowledgeImporterService, ICouncilKnowledgeService, IRegexPatternService, ILogger<RemoteKnowledgeImportService>)

Downloads a user-selected public GitHub repository or webpage into the same local learn-base style cache used by LocalGPT, lists every returned file, applies a regex file policy, and then delegates database extraction to the existing learn-base importer.

```
public RemoteKnowledgeImportService(ILearnBaseKnowledgeImporterService learnBaseImporter, ICouncilKnowledgeService knowledge, IRegexPatternService regexPatterns, ILogger<RemoteKnowledgeImportService> logger)
```

⚙️ Methods 3

Dispose()

```
public void Dispose()
```

ImportAsync(RemoteKnowledgeImportRequest, CancellationToken)

```
public Task<RemoteKnowledgeImportResult> ImportAsync(RemoteKnowledgeImportRequest request, CancellationToken cancellationToken = default)
```

ParseLabels(params string?[])

```
public List<string> ParseLabels(params string?[] values)
```

Class RequestHumanCollaborationFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object RequestHumanCollaborationFunction

Implements IDxAiFunctionHandler

```
public sealed class RequestHumanCollaborationFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

RequestHumanCollaborationFunction(ILocalGptVocabularyService, IHumanCollaborationService, IAmbientLocalGptContext, ILogger<RequestHumanCollaborationFunction>)

```
public RequestHumanCollaborationFunction(ILocalGptVocabularyService vocabulary, IHumanCollaborationService collaboration, IAmbientLocalGptContext ambientContext, ILogger<RequestHumanCollaborationFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ResolveCouncilRuntimeClassFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ResolveCouncilRuntimeClassFunction

Implements IDxAiFunctionHandler

```
public sealed class ResolveCouncilRuntimeClassFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ResolveCouncilRuntimeClassFunction(ICouncilRuntimeClassService, ILogger<ResolveCouncilRuntimeClassFunction>)

```
public ResolveCouncilRuntimeClassFunction(ICouncilRuntimeClassService runtimeClasses, ILogger<ResolveCouncilRuntimeClassFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class SafeTextDocumentService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SafeTextDocumentService

Implements ISafeTextDocumentService

```
public sealed class SafeTextDocumentService : ISafeTextDocumentService
```

🌟 Constructors 1

SafeTextDocumentService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<SafeTextDocumentService>)

```
public SafeTextDocumentService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<SafeTextDocumentService> logger)
```

⚙️ Methods 2

ImportAsync(Guid, Guid?, string, bool, CancellationToken)

```
public Task<ProjectDocumentImport> ImportAsync(Guid projectId, Guid? revisionId, string filePath, bool userConfirmed, CancellationToken cancellationTok = default)
```

ReadAsync(string, int, CancellationToken)

```
public Task<SafeTextDocument> ReadAsync(string filePath, int maxCharacters = 500000, CancellationToken cancellationTok = default)
```

Class SaveProjectArtifactFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SaveProjectArtifactFunction

Implements IDxAiFunctionHandler

```
public sealed class SaveProjectArtifactFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SaveProjectArtifactFunction(IDxAiFunctionJsonService, IProjectArchitectureService, ILogger<SaveProjectArtifactFunction>)

```
public SaveProjectArtifactFunction(IDxAiFunctionJsonService json, IProjectArchitectureService architecture, ILogger<SaveProjectArtifactFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class SaveProjectFilePatternsFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SaveProjectFilePatternsFunction

Implements IDxAiFunctionHandler

```
public sealed class SaveProjectFilePatternsFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SaveProjectFilePatternsFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<SaveProjectFilePatternsFunction>)

```
public SaveProjectFilePatternsFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance, ILogger<SaveProjectFilePatternsFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class SaveProjectRequirementFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SaveProjectRequirementFunction

Implements IDxAiFunctionHandler

```
public sealed class SaveProjectRequirementFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SaveProjectRequirementFunction(IDxAiFunctionJsonService, IProjectArchitectureService, ILogger<SaveProjectRequirementFunction>)

```
public SaveProjectRequirementFunction(IDxAiFunctionJsonService json, IProjectArchitectureService architecture, ILogger<SaveProjectRequirementFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class SaveProjectRevisionFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SaveProjectRevisionFunction

Implements IDxAiFunctionHandler

```
public sealed class SaveProjectRevisionFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SaveProjectRevisionFunction(IDxAiFunctionJsonService, IProjectArchitectureService, ILogger<SaveProjectRevisionFunction>)

```
public SaveProjectRevisionFunction(IDxAiFunctionJsonService json, IProjectArchitectureService architecture, ILogger<SaveProjectRevisionFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class SaveProjectWorkspaceEnvironmentFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SaveProjectWorkspaceEnvironmentFunction

Implements IDxAiFunctionHandler

```
public sealed class SaveProjectWorkspaceEnvironmentFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SaveProjectWorkspaceEnvironmentFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<SaveProjectWorkspaceEnvironmentFunction>)

```
public SaveProjectWorkspaceEnvironmentFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance,
ILogger<SaveProjectWorkspaceEnvironmentFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ScanProjectFilesFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ScanProjectFilesFunction

Implements IDxAiFunctionHandler

```
public sealed class ScanProjectFilesFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ScanProjectFilesFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<ScanProjectFilesFunction>)

```
public ScanProjectFilesFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance, ILogger<ScanProjectFilesFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class ServiceMethodDiagnosticsRegistration

Namespace LocalGPT . Services Assembly LocalGPT.dll

Decorates scoped and transient LocalGPT interface services with bounded method-level operational logging. Singleton services remain DI-owned and use their explicit service logging so the decorator can never resolve a scoped dependency from the root provider.

Inheritance object ServiceMethodDiagnosticsRegistration

```
public sealed class ServiceMethodDiagnosticsRegistration
```

🌟 Constructors 1

ServiceMethodDiagnosticsRegistration(ILogger)

Decorates scoped and transient LocalGPT interface services with bounded method-level operational logging. Singleton services remain DI-owned and use their explicit service logging so the decorator can never resolve a scoped dependency from the root provider.

```
public ServiceMethodDiagnosticsRegistration(ILogger logger)
```

⚙️ Methods 1

Apply(IServiceCollection, bool)

```
public void Apply(IServiceCollection services, bool isDevelopment)
```

Class SetCouncilGameControlModeFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SetCouncilGameControlModeFunction

Implements IDxAiFunctionHandler

```
public sealed class SetCouncilGameControlModeFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SetCouncilGameControlModeFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<SetCouncilGameControlModeFunction>)

```
public SetCouncilGameControlModeFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters,
ILogger<SetCouncilGameControlModeFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```


Class SetCouncilGameInputGateFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SetCouncilGameInputGateFunction

Implements IDxAiFunctionHandler

```
public sealed class SetCouncilGameInputGateFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SetCouncilGameInputGateFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<SetCouncilGameInputGateFunction>)

```
public SetCouncilGameInputGateFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<SetCouncilGameInputGateFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class SqliteEditorPreferenceService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SqliteEditorPreferenceService

Implements ISqliteEditorPreferenceService

```
public sealed class SqliteEditorPreferenceService : ISqliteEditorPreferenceService
```

🌟 Constructors 1

SqliteEditorPreferenceService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<SqliteEditorPreferenceService>)

```
public SqliteEditorPreferenceService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer, ILogger<SqliteEditorPreferenceService> logger)
```

⚙️ Methods 3

GetOverridesAsync(string, CancellationToken)

```
public Task<IReadOnlyDictionary<string, SqliteEditorFieldOverride>> GetOverridesAsync(string tableName, CancellationToken cancellationToken = default)
```

InferEditorKind(SqliteColumnSummary, string?)

```
public string InferEditorKind(SqliteColumnSummary column, string? value)
```

SaveOverrideAsync(SqliteEditorFieldOverride, bool, CancellationToken)

```
public Task<SqliteEditorFieldOverride> SaveOverrideAsync(SqliteEditorFieldOverride preference, bool userConfirmed, CancellationToken cancellationToken = default)
```

Class SqliteGridPresentationService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SqliteGridPresentationService

```
public sealed class SqliteGridPresentationService
```

🌟 Constructors 1

SqliteGridPresentationService(ILogger<SqliteGridPresentationService>)

```
public SqliteGridPresentationService(ILogger<SqliteGridPresentationService> serviceLogger)
```

⚙️ Methods 4

BuildCellPreview(string, object?)

```
public object? BuildCellPreview(string columnName, object? value)
```

BuildColumnName(SqliteColumnSummary, ILogger)

```
public string BuildColumnName(SqliteColumnSummary column, ILogger logger)
```

IsLongTextColumn(string, string, ILogger)

```
public bool IsLongTextColumn(string columnName, string value, ILogger logger)
```

ToGridRow(SqliteRowSnapshot, ILogger)

```
public ExpandableObject? ToGridRow(SqliteRowSnapshot row, ILogger logger)
```

Class SqliteTableEditorService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SqliteTableEditorService

Implements ISqliteTableEditorService

```
public sealed class SqliteTableEditorService : ISqliteTableEditorService
```

🌟 Constructors 1

SqliteTableEditorService(IDatabaseInitializationService, LocalGptDatabaseOptions, ILogger<SqliteTableEditorService>, SqliteUtilityService)

```
public SqliteTableEditorService(IDatabaseInitializationService databaseInitializer, LocalGptDatabaseOptions databaseOptions,
    ILogger<SqliteTableEditorService> logger, SqliteUtilityService sqliteUtility)
```

🐾 Properties 1

DatabasePath

```
public string DatabasePath { get; }
```

⚙️ Methods 5

DeleteRowAsync(string, long, CancellationToken)

```
public Task DeleteRowAsync(string tableName, long rowId, CancellationToken cancellationToken = default)
```

GetTableAsync(string, int, CancellationToken)

```
public Task<SqliteTableSnapshot> GetTableAsync(string tableName, int take = 100, CancellationToken cancellationToken = default)
```

GetTablesAsync(CancellationToken)

```
public Task<IReadOnlyList<SqliteTableSummary>> GetTablesAsync(CancellationToken cancellationToken = default)
```

InsertRowAsync(string, IReadOnlyDictionary<string, string?>, CancellationToken)

```
public Task InsertRowAsync(string tableName, IReadOnlyDictionary<string, string?> values, CancellationToken cancellationToken = default)
```

UpdateRowAsync(string, long, IReadOnlyList<SqliteCellUpdate>, CancellationToken)

```
public Task UpdateRowAsync(string tableName, long rowId, IReadOnlyList<SqliteCellUpdate> updates, CancellationToken cancellationToken = default)
```

Class SqliteUtilityService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SqliteUtilityService

```
public sealed class SqliteUtilityService
```

🌟 Constructors 1

SqliteUtilityService(CouncilTextService, LocalGptCatalogService, ILogger<SqliteUtilityService>)

```
public SqliteUtilityService(CouncilTextService text, LocalGptCatalogService catalog, ILogger<SqliteUtilityService> serviceLogger)
```

⚙️ Methods 29

BuildCouncilKnowledgeContent(MultiModelCouncilResult, ILogger)

```
public string BuildCouncilKnowledgeContent(MultiModelCouncilResult result, ILogger logger)
```

BuildTags(MultiModelCouncilResult, bool, ILogger)

```
public string BuildTags(MultiModelCouncilResult result, bool nonSubstantive, ILogger logger)
```

BuildTopic(string, ILogger)

```
public string BuildTopic(string prompt, ILogger logger)
```

BuildTrustLabel(CouncilKnowledgeEntry, ILogger)

```
public string BuildTrustLabel(CouncilKnowledgeEntry entry, ILogger logger)
```

ClassifyCommandProfile(string, string, ILogger)

```
public string ClassifyCommandProfile(string executable, string arguments, ILogger logger)
```

ComputeSourceHash(CouncilKnowledgeEntry, ILogger)

```
public string ComputeSourceHash(CouncilKnowledgeEntry entry, ILogger logger)
```

ContainsPathSegment(string, ILogger)

```
public bool ContainsPathSegment(string fileName, ILogger logger)
```

CreateSqliteEditError(string, string, SqliteException, ILogger?)

```
public string CreateSqliteEditError(string operation, string tableName, SqliteException exception, ILogger? logger = null)
```

EnsureValidTableAsync(SqliteConnection, string, CancellationToken, ILogger?)

```
public Task EnsureValidTableAsync(SqliteConnection connection, string tableName, CancellationToken cancellationToken, ILogger? logger = null)
```

ExtractHelpfulSources(string, ILogger)

```
public string ExtractHelpfulSources(string text, ILogger logger)
```

GetColumnsAsync(SqliteConnection, string, CancellationToken, ILogger?)

```
public Task<List<SqliteColumnSummary>> GetColumnsAsync(SqliteConnection connection, string tableName, CancellationToken cancellationToken, ILogger? logger = null)
```

GetRowCountAsync(SqliteConnection, string, CancellationToken, ILogger?)

```
public Task<long> GetRowCountAsync(SqliteConnection connection, string tableName, CancellationToken cancellationToken, ILogger? logger = null)
```

IsGradle(string, ILogger)

```
public bool IsGradle(string executable, ILogger logger)
```

IsKnownReviewStatus(string, ILogger)

```
public bool IsKnownReviewStatus(string value, ILogger logger)
```

IsKnownVerificationStatus(string, ILogger)

```
public bool IsKnownVerificationStatus(string value, ILogger logger)
```

IsNonSubstantiveCouncilKnowledge(MultiModelCouncilResult, ILogger)

```
public bool IsNonSubstantiveCouncilKnowledge(MultiModelCouncilResult result, ILogger logger)
```

IsPowerShell(string, ILogger)

```
public bool IsPowerShell(string executable, ILogger logger)
```

IsUsableForBriefing(CouncilKnowledgeEntry, ILogger)

```
public bool IsUsableForBriefing(CouncilKnowledgeEntry entry, ILogger logger)
```

LooksLikeNonSubstantiveContent(string, ILogger)

```
public bool LooksLikeNonSubstantiveContent(string content, ILogger logger)
```

Normalize(CouncilKnowledgeEntry, ILogger)

```
public void Normalize(CouncilKnowledgeEntry entry, ILogger logger)
```

NormalizeReviewStatus(CouncilKnowledgeEntry, ILogger)

```
public string NormalizeReviewStatus(CouncilKnowledgeEntry entry, ILogger logger)
```

NormalizeVerificationStatus(CouncilKnowledgeEntry, ILogger)

```
public string NormalizeVerificationStatus(CouncilKnowledgeEntry entry, ILogger logger)
```

ParseValue<T>(string, string?, ILogger)

```
public T ParseValue<T>(string valueString, string? dataType, ILogger logger)
```

QuoteIdentifier(string, ILogger?)

```
public string QuoteIdentifier(string identifier, ILogger? logger = null)
```

SanitizeFileName(string, ILogger)

```
public string SanitizeFileName(string value, ILogger logger)
```

ToSqliteValue(string?, SqliteColumnSummary)

```
public object ToSqliteValue(string? value, SqliteColumnSummary column)
```

ToSqliteValue(string?, ILogger?)

```
public object? ToSqliteValue(string? value, ILogger? logger = null)
```

Trim(string, int, ILogger)

```
public string Trim(string value, int maxLength, ILogger logger)
```

TrimOrFallback(string, int, string, ILogger)

```
public string TrimOrFallback(string value, int maxLength, string fallback, ILogger logger)
```

Class StartCouncilGameFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object StartCouncilGameFunction

Implements IDxAiFunctionHandler

```
public sealed class StartCouncilGameFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

StartCouncilGameFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<StartCouncilGameFunction>)

```
public StartCouncilGameFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<StartCouncilGameFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class SubmitCouncilGameFrameFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object SubmitCouncilGameFrameFunction

Implements IDxAiFunctionHandler

```
public sealed class SubmitCouncilGameFrameFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

SubmitCouncilGameFrameFunction(ICouncilGameSessionService, CouncilGameDxParameterReader, ILogger<SubmitCouncilGameFrameFunction>)

```
public SubmitCouncilGameFrameFunction(ICouncilGameSessionService games, CouncilGameDxParameterReader parameters, ILogger<SubmitCouncilGameFrameFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationTok = default)
```

Class SupervisedTaskRunner

Namespace LocalGPT . Services Assembly LocalGPT.dll

Observes intentionally concurrent work so exceptions cannot become unobserved Tasks. The runner is process-scoped, but every operation must carry its owning component/service name.

Inheritance object SupervisedTaskRunner

Implements ISupervisedTaskRunner

```
public sealed class SupervisedTaskRunner : ISupervisedTaskRunner
```

🌟 Constructors 1

SupervisedTaskRunner(IServiceActivityService, ILogger<SupervisedTaskRunner>)

Observes intentionally concurrent work so exceptions cannot become unobserved Tasks. The runner is process-scoped, but every operation must carry its owning component/service name.

```
public SupervisedTaskRunner(IServiceActivityService serviceActivity, ILogger<SupervisedTaskRunner> logger)
```

🐾 Properties 1

ActiveTaskCount

```
public int ActiveTaskCount { get; }
```

⚙️ Methods 1

Run(string, string, Func<CancellationToken, Task>, CancellationToken)

```
public void Run(string owner, string operation, Func<CancellationToken, Task> action, CancellationToken cancellationToken = default)
```

Class TestRegexPatternFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object TestRegexPatternFunction

Implements IDxAiFunctionHandler

```
public sealed class TestRegexPatternFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

TestRegexPatternFunction(IRegexPatternService, IRegexFunctionParameterService, ILogger<TestRegexPatternFunction>)

```
public TestRegexPatternFunction(IRegexPatternService regexPatterns, IRegexFunctionParameterService parameters, ILogger<TestRegexPatternFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ThemeService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Owns LocalGPT's selectable theme catalog and the two independently selectable theme layers for one Blazor circuit. The shell theme controls LocalGPT page surfaces and Bootstrap metadata; the component theme is applied through DevExpress' supported DevExpress.Blazor.IThemeChangeService .

Inheritance object ThemeService

```
public sealed class ThemeService
```

🌟 Constructors 1

ThemeService(ILogger<ThemeService>, IServiceActivtyService)

```
public ThemeService(ILogger<ThemeService> logger, IServiceActivtyService serviceActivty)
```

🔴 Fields 6

ComponentThemeCookieName

```
public const string ComponentThemeCookieName = "ActiveComponentTheme"
```

DEFAULT_THEME_NAME

```
public const string DEFAULT_THEME_NAME = "office-white"
```

LegacyThemeCookieName

```
public const string LegacyThemeCookieName = "ActiveTheme"
```

LocalThemeContractPath

```
public const string LocalThemeContractPath = "css/localgpt-theme-contract.css"
```

MaxFusionRouteSteps

```
public const int MaxFusionRouteSteps = 256
```

ShellThemeCookieName

```
public const string ShellThemeCookieName = "ActiveShellTheme"
```

🐾 Properties 8

ActiveComponentTheme

```
public Theme ActiveComponentTheme { get; }
```

ActiveShellTheme

```
public Theme ActiveShellTheme { get; }
```

ActiveTheme

Compatibility alias for older diagnostics and components. The former single theme now maps to the DevExpress component theme; new code should select the shell and component layers explicitly.

```
public Theme ActiveTheme { get; }
```

FusionRoute

```
public IReadOnlyList<ThemeFusionStep> FusionRoute { get; }
```

IsInitialized

```
public bool IsInitialized { get; }
```

ThemeChangeRequestDispatcher

```
public IThemeChangeRequestDispatcher? ThemeChangeRequestDispatcher { get; set; }
```

ThemeLoadNotifier

```
public IThemeLoadNotifier? ThemeLoadNotifier { get; set; }
```

ThemeSets

```
public List<ThemeSet> ThemeSets { get; }
```

Methods 18

EnsureFusionRouteSeeded()

```
public void EnsureFusionRouteSeeded()
```

FindThemeByName(string?)

```
public Theme? FindThemeByName(string? themeName)
```

GetBootstrapThemeCssUrl(Theme)

Compatibility helper for diagnostics. Bootstrap theme files are registered on the corresponding DevExpress BootstrapExternal ITheme via AddFilePaths.

```
public string GetBootstrapThemeCssUrl(Theme theme)
```

GetHighlightJSThemeCssUrl(Theme)

```
public string GetHighlightJSThemeCssUrl(Theme theme)
```

GetThemeCssUrl(Theme)

Compatibility helper for diagnostics and older code. Runtime component switching uses IThemeChangeService and the theme's ITheme instance instead of replacing this link manually.

```
public string GetThemeCssUrl(Theme theme)
```

GetThemeLayerCssClass(string?, string?)

```
public string GetThemeLayerCssClass(string? shellThemeName, string? componentThemeName)
```

GetThemeOrDefault(string?)

```
public Theme GetThemeOrDefault(string? themeName)
```

GetThemeTitle(string?)

```
public string GetThemeTitle(string? themeName)
```

InitializeThemes(string?, string?)

```
public void InitializeThemes(string? shellThemeName, string? componentThemeName)
```

RecordFusionStep(ThemeApplicationTarget, Theme)

```
public ThemeFusionStep RecordFusionStep(ThemeApplicationTarget target, Theme theme)
```

ReplaceFusionRoute(IEnumerable<ThemeFusionStep>?)

```
public void ReplaceFusionRoute(IEnumerable<ThemeFusionStep>? steps)
```

ResetFusionRouteToCurrentSelection()

```
public void ResetFusionRouteToCurrentSelection()
```

SetActiveComponentTheme(Theme)

```
public void SetActiveComponentTheme(Theme theme)
```

SetActiveComponentThemeByName(string?)

```
public void SetActiveComponentThemeByName(string? themeName)
```

SetActiveShellTheme(Theme)

```
public void SetActiveShellTheme(Theme theme)
```

SetActiveShellThemeByName(string?)

```
public void SetActiveShellThemeByName(string? themeName)
```

SetActiveTheme(Theme)

```
public void SetActiveTheme(Theme theme)
```

SetActiveThemeByName(string?)

Backward-compatible single-theme setter. It intentionally updates both layers.

```
public void SetActiveThemeByName(string? themeName)
```


⚡ Events 3

ActiveComponentThemeChanged

```
public event Action<Theme>? ActiveComponentThemeChanged
```

ActiveShellThemeChanged

```
public event Action<Theme>? ActiveShellThemeChanged
```

ActiveThemeChanged

```
public event Action<Theme>? ActiveThemeChanged
```

api/LocalGPT.Services.TranslateJsonTextFunction.html

Class TranslateJsonTextFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object TranslateJsonTextFunction

Implements IDxAiFunctionHandler

```
public sealed class TranslateJsonTextFunction : IDxAiFunctionHandler
```

✨ Constructors 1

TranslateJsonTextFunction(IStructuredTextTranslationService, ILogger<TranslateJsonTextFunction>)

```
public TranslateJsonTextFunction(StructuredTextTranslationService translator, ILogger<TranslateJsonTextFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

api/LocalGPT.Services.UpsertRegexPatternFunction.html

Class UpsertRegexPatternFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object UpsertRegexPatternFunction

Implements IDxAiFunctionHandler

```
public sealed class UpsertRegexPatternFunction : IDxAiFunctionHandler
```

✨ Constructors 1

UpsertRegexPatternFunction(IRegexPatternService, IRegexFunctionParameterService, ILogger<UpsertRegexPatternFunction>)

```
public UpsertRegexPatternFunction(IRegexPatternService regexPatterns, IRegexFunctionParameterService parameters, ILogger<UpsertRegexPatternFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class UpsertSqliteRowFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object UpsertSqliteRowFunction

Implements IDxAiFunctionHandler

```
public sealed class UpsertSqliteRowFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

UpsertSqliteRowFunction(IDxAiFunctionJsonService, ISqliteTableEditorService, ILogger<UpsertSqliteRowFunction>)

```
public UpsertSqliteRowFunction(IDxAiFunctionJsonService json, ISqliteTableEditorService editor, ILogger<UpsertSqliteRowFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class ValidateEmbeddedWiringFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object ValidateEmbeddedWiringFunction

Implements IDxAiFunctionHandler

```
public sealed class ValidateEmbeddedWiringFunction : IDxAiFunctionHandler
```

🌟 Constructors 1

ValidateEmbeddedWiringFunction(IDxAiFunctionJsonService, IEmbeddedWiringService)

```
public ValidateEmbeddedWiringFunction(IDxAiFunctionJsonService json, IEmbeddedWiringService wiring)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Class VariableStoreService

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object VariableStoreService

Implements IVariableStoreService

```
public sealed class VariableStoreService : IVariableStoreService
```

✨ Constructors 1

VariableStoreService(IDbContextFactory<LocalGptMemoryDbContext>, IDatabaseInitializationService, ILogger<VariableStoreService>, SqliteUtilityService)

```
public VariableStoreService(IDbContextFactory<LocalGptMemoryDbContext> dbContextFactory, IDatabaseInitializationService databaseInitializer,
    ILogger<VariableStoreService> logger, SqliteUtilityService sqliteUtility)
```

⚙️ Methods 4

GetAsync<T>(string, CancellationToken)

```
public Task<T> GetAsync<T>(string name, CancellationToken cancellationToken = default)
```

ListAllAsync(string, CancellationToken)

```
public Task<IEnumerable<SystemVariable>> ListAllAsync(string filter, CancellationToken cancellationToken = default)
```

ListAllAsync(CancellationToken)

```
public Task<IEnumerable<SystemVariable>> ListAllAsync(CancellationToken cancellationToken = default)
```

SetAsync<T>(string, T, CancellationToken)

```
public Task SetAsync<T>(string name, T value, CancellationToken cancellationToken = default)
```

Class VerifyProjectRevisionBuildFunction

Namespace LocalGPT . Services Assembly LocalGPT.dll

Inheritance object VerifyProjectRevisionBuildFunction

Implements IDxAiFunctionHandler

```
public sealed class VerifyProjectRevisionBuildFunction : IDxAiFunctionHandler
```

✨ Constructors 1

VerifyProjectRevisionBuildFunction(IDxAiFunctionJsonService, IProjectMaintenanceService, ILogger<VerifyProjectRevisionBuildFunction>)

```
public VerifyProjectRevisionBuildFunction(IDxAiFunctionJsonService json, IProjectMaintenanceService maintenance,
    ILogger<VerifyProjectRevisionBuildFunction> logger)
```

🐾 Properties 1

Descriptor

```
public DxaichatFunctionInfo Descriptor { get; }
```

⚙️ Methods 1

InvokeAsync(DxAiFunctionInvocationRequest, CancellationToken)

```
public Task<DxAiFunctionInvocationResult> InvokeAsync(DxAiFunctionInvocationRequest request, CancellationToken cancellationToken = default)
```

Namespace TacosPortal.Services

Classes

Class NotificationService

Namespace TacosPortal . Services Assembly LocalGPT.dll

Inheritance object NotificationService

Implements INotificationService

```
public class NotificationService : INotificationService
```

🌟 Constructors 1

NotificationService(IToastNotificationService, IComponentActivityService, ILogger<NotificationService>)

```
public NotificationService(IToastNotificationService toastService, IComponentActivityService componentActivity, ILogger<NotificationService> logger)
```

⚙️ Methods 6

Show(string, string, string, ToastRenderStyle)

```
public void Show(string providerName, string title, string message, ToastRenderStyle renderStyle)
```

ShowError(string, string, string)

```
public void ShowError(string providerName, string message, string title = "Error")
```

ShowInfo(string, string, string)

```
public void ShowInfo(string providerName, string message, string title = "Info")
```

ShowRegular(string, string, string)

```
public void ShowRegular(string providerName, string message, string title = "Error")
```

ShowSuccess(string, string, string)

```
public void ShowSuccess(string providerName, string message, string title = "Success")
```

ShowWarning(string, string, string)

```
public void ShowWarning(string providerName, string message, string title = "Warning")
```