

# JSP cheat sheet

## Directives

### Include

Includes a file during the translation phase.

```
<%@ include file = "relative url" >
```

### taglib

Declares a tag library, containing custom actions, used in the page

```
<%@ include file = "relative url" >
```

e.g.

```
<%@ taglib prefix="c"
uri="http://java.sun.com/jsp/jstl/core" %>
```

## Actions

### jsp:include

Includes a file at the time the page is requested.

```
<jsp:include page = "relative URL" />
```

```
<jsp:include page="Header.jsp" >
  <jsp:param name="chapterName"
value="The end" />
</jsp:include>
```

and the parameter accessed using  
`${param.chapterName}`

### jsp:forward

The forward action terminates the action of the current page and forwards the request to another resource.

```
<jsp:forward page = "Relative URL" />
```

## Implicit objects

### Request

```
${requestScope.foo}
```

Parameters coming from the original request (url) are accessed like this:

```
${param.foo}
```

### Session

```
${sessionScope.foo}
```

### Application

```
${initParam.foo}
```

in servlet:

```
getServletContext().getInitParameter("<atrib_name>");
```

## Standard Tag Library (JSTL)

### <c:set>

Sets the result of an expression evaluation in a 'scope'.

```
<c:set var="salary" scope="session"
value="${2000*2}"/>
```

### <c:if>

Simple conditional tag which evaluates its body if the supplied condition is true.

```
<c:if test="${salary > 2000}">
  <p>My salary is: ${salary} /><p>
</c:if>
```

### <c:choose>, <c:when> & <c:otherwise>

Simple conditional tag that establishes a context for mutually exclusive conditional operations, marked by <when> and <otherwise>.

```
<c:choose>
  <c:when test = "${salary <= 0}">
    Salary is very low to survive.
  </c:when>

  <c:when test = "${salary > 1000}">
    Salary is very good.
  </c:when>

  <c:otherwise>
    No comment sir...
  </c:otherwise>
</c:choose>
```

### <c:forEach>

The basic iteration tag, accepting many different collection types and supporting subsetting and other functionality.

```
<ul>
<c:forEach var = "i" begin = "1" end =
"5">
  <li>Item ${i}</li>
</c:forEach>
</ul>
```

or

```
<c:forEach var = "i" items="${mylist}">
  <li>Item ${i}</li>
</c:forEach>
```

### <c:redirect>

Redirects to a new URL.

```
<c:redirect url =
"http://www.example.com"/>
```

### <c:url>

Creates a URL with optional query parameters

```
<a href = "<c:url value =
"foo.html"/>">Foo</a>
```