

Naam: _____ Klas: _____

Duur 45 min. Dit proefwerk bestaat uit 43 vragen. Je kunt 46 punten halen. Je mag de cheatsheet en een gewone rekenmachine gebruiken. Teken met een scherp potlood. Gebruik **dit** blad als antwoordblad. Omcirkel de juiste antwoorden bij meerkeuzevragen.

Succes!

- (1 p) 1. Twee qubits bevinden zich in een toestand

$$|\Psi\rangle = \sqrt{\frac{1}{3}}|00\rangle + \sqrt{\frac{1}{3}}|10\rangle + \sqrt{\frac{1}{3}}|11\rangle$$

is dit mogelijk?

- (1 p) 2. Een deeltje Ψ in de toestand: $|\Psi\rangle = \alpha|0\rangle + \beta|1\rangle$ kun je meten in toestand $|0\rangle$ met een kans:

- A. α
- B. β
- C. α^2
- D. $\sqrt{\alpha}$

- (1 p) 3. Bereken de coëfficiënt β in de volgende superpositie:

$$|\Psi\rangle = \sqrt{\frac{1}{8}}|0\rangle + \beta|1\rangle$$

- (1 p) 4. Waarom kan de volgende toestand niet bestaan?

$$|\Psi\rangle = \sqrt{\frac{1}{3}}|0\rangle + \sqrt{\frac{1}{3}}|1\rangle + \sqrt{\frac{1}{3}}|2\rangle$$

- (1 p) 5. Waarom kan de volgende toestand niet bestaan?

$$|\Psi\rangle = \sqrt{\frac{1}{3}}|0\rangle + \sqrt{\frac{1}{3}}|1\rangle$$

NLT Kansen met Quantum, 6V, najaar 2020

- (1 p) 6. Quantum systemen zijn zgn. twee-toestand systemen. In een teostand $|\Psi\rangle = \alpha|0\rangle + \beta|1\rangle$ kan een van de twee termen worden weggelaten. met welke regel kan je de waarde van de andere coëfficiënt achterhalen?

- (1 p) 7. Er zijn twee qubits:

$$|\Psi_1\rangle = \sqrt{\frac{1}{2}}|0\rangle + \sqrt{\frac{1}{2}}|1\rangle$$

en

$$|\Psi_2\rangle = \sqrt{\frac{1}{2}}|0\rangle - \sqrt{\frac{1}{2}}|1\rangle$$

I. De kans om na meting een deeltje in toestand $|0\rangle$ aan te treffen is bij beide deeltjes gelijk.

II. De toestand van de twee deeltjes is correct genormeerd.

- A. Alleen bewering I is waar
- B. Alleen bewering II is waar
- C. bewering I en II zijn beide onjuist.
- D. bewering I en II zijn beide juist.

- (1 p) 8. De Bell basis $|+\rangle$ en $|-\rangle$ kun je uitdrukken in de basisvectoren van de computationele basis.

$$|+\rangle = \sqrt{\frac{1}{2}}|0\rangle + \sqrt{\frac{1}{2}}|1\rangle$$

en

$$|-\rangle = \sqrt{\frac{1}{2}}|0\rangle - \sqrt{\frac{1}{2}}|1\rangle$$

Werk deze formules om zodat je de computationele basis uitdrukt in termen van de Bell basis.

- (1 p) 9. Alice en bob hebben allebei een qubit. Zij vinden het hoogtijd om die met elkaar te verstrengelen. Teken in het schema hieronder de benodigde poorten die hiervoor nodig zijn.

$$\begin{array}{c} |0\rangle \\ \text{Alice} \quad \text{---} \\ |0\rangle \\ \text{Bob} \quad \text{---} \end{array}$$

- (1 p) 10. Alice en Bob hebben allebei een qubit in toestand $|00\rangle$. Zij vinden het hoogtijd om die met elkaar te verstrengelen. dat doen zij met het volgende algoritme:

$$\begin{array}{c} |0\rangle \\ \text{Alice} \quad \text{---} \\ |0\rangle \\ \text{Bob} \quad \text{---} \end{array}$$

Wat is de toestand van het verstrengelde paar?

NLT Kansen met Quantum, 6V, najaar 2020

- A. $\frac{1}{\sqrt{2}} |01\rangle + \frac{1}{\sqrt{2}} |10\rangle$
- B. $\frac{1}{\sqrt{2}} |00\rangle + \frac{1}{\sqrt{2}} |11\rangle$
- C. $\frac{1}{2} |00\rangle + \frac{1}{2} |01\rangle + \frac{1}{2} |10\rangle + \frac{1}{2} |11\rangle$
- D. geen van bovenstaande is juist

(1 p) 11. Bereken (slim): $HXHZH|0\rangle = \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix}$

(1 p) 12. I. Een verschil met klassieke bits is dat qubits niet gekopieerd kunnen worden.

- A. waar
- B. onwaar

(1 p) 13. Je laat een set, reset, copy en **X**-poort op twee input bits. Hoeveel ja/neee vragen heb je nodig om vat te stellen met welke poort je te doen hebt? Wt kan een QC met 1 vraag (1 bit) dat een KC nooit kan?

(1 p) 14. Leg kort uit (met een voorbeeld) hoe een auantum computer met het Deutsch algoritme iets kan wat een een klassieke computer niet kan.

(1 p) 15. Met quantum teleportatie kan informatie worden overgezonden, sneller dan het licht, met de lichtsnelheid, minder dan de lichtsnelheid

- A. waar
- B. onwaar

(1 p) 16. Net als bij klassieke computers kan quantuminformatie gekopieerd worden

- A. waar
- B. onwaar

(1 p) 17. Het simpelste quantum teleportatie protocol gebruikt drie qubits

(1 p) 18. Leg het no cloning principe uit

(1 p) 19. Bij het teleportatie protocol hoef je maar je 1 klassiek bit te gebruiken om twee qubits over te sturen.

- A. waar
- B. onwaar


(1 p) 20. Het Deutsch oracle kan twee klassieke bits informatie met 1 bit duiden.

- A. waar
- B. onwaar

(1 p) 21. Bij quantum teleportatie kan zonder klassieke communicatie informatieoverdracht plaatsvinden

- A. waar
- B. onwaar

(1 p) 22. Vul het volgende quantumcircuit aan zodanig dat de begintoestand wordt hersteld



Gebruik de statemachine van fig. xxx. Waar of onwaar:

(1 p) 23. De **X**-poort verandert $|0\rangle$ naar $|1\rangle$ en omgekeerd.

A. waar B. onwaar

(1 p) 24. De **Z**-poort verandert $|+\rangle$ naar $|-\rangle$ en omgekeerd

A. waar B. onwaar

(1 p) 25. De **H**-poort verandert $|0\rangle$ naar $|+\rangle$ en omgekeerd

A. waar B. onwaar

(1 p) 26. De **I**-poort verandert $|0\rangle$ naar $|1\rangle$ en omgekeerd


A. waar B. onwaar

(1 p) 27. De **X**-poort beeldt $|0\rangle$ op zichzelf af.

A. waar B. onwaar

Voor eenvoudige schakelingen kan een input-output tabel worden gemaakt.

(1 p) (a) Maak zo'n tabel voor de onderstaande schakeling.



input	C	output
$ ba\rangle$		
$ 00\rangle$		
$ 00\rangle$		
$ 00\rangle$		
$ 00\rangle$		

(1 p) 28. Een toestandsvector Ψ heeft 8 elementen. Hoeveel registers heeft de quantumcomputer die deze vector bestuurt?

(1 p) 29. Twee qubits spannen de Bell basis op: $|\Psi_1\rangle = |+\rangle = \sqrt{\frac{1}{2}}|0\rangle + \sqrt{\frac{1}{2}}|1\rangle$ en $|\Psi_2\rangle = |-\rangle = \sqrt{\frac{1}{2}}|0\rangle - \sqrt{\frac{1}{2}}|1\rangle$

Druk de computationele basis uit in termen van $|+\rangle$ en $|-\rangle$.

(1 p) 30. Twee beweringen:

I. De logica van klassieke poorten is nooit reversibel.

II. De logica van quantumpoorten is altijd reversibel.

NLT Kansen met Quantum, 6V, najaar 2020

- A. Alleen bewering I is waar
- B. Alleen bewering II is waar
- C. bewering I en II zijn beide onjuist.
- D. bewering I en II zijn beide juist.

31. De resultaten van een waarneming Een waarneming van oude vrouw jonge vrouw levert dat 25 % van de tijd een oude vrouw, en 75 % van de tijd Jonge vrouw wordt waargenomen. (tekening assenstelsel O-verticaal J-horizontaal)

(1 p) (a) Bereken de coördinaten van de vector, en teken deze in de eenheidscirkel

(1 p) (b) Aan welke voorwaarden moeten de coëfficiënten voldoen?

(1 p) 32. Twee qubits in de ket notatie $|ab\rangle$ zijn altijd verstrengeld.

A. waar B. onwaar

(1 p) 33. Gebruik bij deze opgave $\langle 0|0\rangle = \langle 1|1\rangle = 1$ en $\langle 0|1\rangle = \langle 1|0\rangle = 0$.

Als $|\Psi_1\rangle = \begin{pmatrix} \alpha_1 \\ \beta_1 \end{pmatrix}$ en $|\Psi_2\rangle = \begin{pmatrix} \alpha_2 \\ \beta_2 \end{pmatrix}$

waarvan alle coëfficiënten reëel zijn.

(p) (a) Bereken $\langle \Psi_1 | \Psi_2 \rangle$

Hint: Begin als volgt: $\langle \Psi_1 | = \alpha_1 \langle 0 | + \beta_1 \langle 1 |$

(1 p) 34. Bereken of beredeneer de uitkomst van

$$H \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$$

(1 p) 35. Bereken of beredeneer de uitkomst van

$$H \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$$

- (1 p) 36. Alice wil het BB84 protocol opzetten. Zij moet beginnen met een reeks random nummers. Daarvoor wil ze ook een quantum computer gebruiken. beschrijf hoe ze dat kan doen.

- (1 p) 37. Alice heeft qubits in toestand $|0\rangle$. Om haar 4N data te sturen moet zij de toestanden $|0\rangle, |1\rangle, |+\rangle$ en $|-\rangle$. kunnen versturen Hoe kan ze dat met **H** en **X** doen?

$|0\rangle = \mathbf{I} |0\rangle$ (I mag je weg laten natuurlijk)

$|1\rangle = \mathbf{X} |0\rangle$

$|+\rangle = \mathbf{H} |0\rangle$

$|-\rangle = \mathbf{HX} |0\rangle$ Volgorde!

- (1 p) 38. Als Alice en Bob hun 4N data naast elkaar leggen. Hoeveel overeenkomst kunnen zij verwachten?

Eve kan nog wel eens meeluisteren (Engels: evesdropping). Zij probeert in te breken tijdens de communicatie over het quantum kanaal. Zij leest alle qubits, en zet daar random bits voor in de plaats. Wanneer merken Alice en Bob dit?

Er zijn andere mogelijke oorzaken dat niet alle bits juist overkomen. Welke van onderstaande redenen kan *niet* de reden zijn van gemiste

A. Eve, die afluistert.

NLT Kansen met Quantum, 6V, najaar 2020

- B. De detector die niet 100% efficiënt is.
- C. Een zwak signaal.
- D. vuiltje in de glasvezelkabel


(1 p) 39. Waar of niet waar: Na meting levert een qubit altijd een 0 of een 1 A. waar B. onwaar

(1 p) 41. In het teleportatieprotocol meet de ontvanger (Bob) twee qubits A. waar B. onwaar
In het teleportatieprotocol overschrijdt de informatie-overdracht de lichtsnelheid (false)

(1 p) 42. Quantum parallelisme. Een uitbreiding van het aantal registers heeft een exponentiële groei van de toestandsruimte ten gevolg. Dat is de kracht van een quantumcomputer.

(1 p) (a) Hoe groot is de toestandsruimten van een qc van 20 bits?

(1 p) (b) Als alle bits maximaal verstrengeld zijn, wat is dan de kans op iedere uitkomst?



(p) (c) Wat is de hoogste dimensie van de toestandsruimte van het bovenstaande circuit ?

(p) 43. Ensemble meting vs Enkele meting, enkel en dubbelspleet exp. overeenkomst met procedure quantum computing...

reeks kleine vragen uit quantum for the curious (Nielsen)

Q: write the following in ket notation

$$\begin{pmatrix} \sqrt{0.7} \\ \sqrt{0.3} \end{pmatrix}$$

$$\sqrt{0.7} |0\rangle + \sqrt{0.3} |1\rangle$$

Q: It is useful to think of the left to right of a quantum wire as a passage of ...

A: time

Q: What is the matrix representation of the X-gate

$$A: X \equiv \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$$

Q: How many computational basis states does a qubit have?

A: 2

Q: How can you compute the length of $H \begin{pmatrix} 1 \\ 3 \end{pmatrix}$ without explicitly computing the product of the Hadamard gate and the vector? What is the length?

A: Hadamard operator leaves the length unchanged. The length is $\sqrt{1^2 + 3^2} = \sqrt{10}$

Q: Suppose we have a qubit in the state

$$\frac{|0\rangle + |1\rangle}{\sqrt{2}}$$

. What is the probability of a measurement in the computational basis will give the result 0? What is then its posterior state?

A: 50%, $|0\rangle$

Q: What are three types of physical systems that potentially can be used to store qubits?

A: photons, electrons, atoms, doped diamonds

Q: What do we call the two-dimensional vector space where the state of a qubit lives?

A: State space

Q: What is the inverse of a Hadamard gate?

A: Hadamard gate

Q: What does the Hadamard gate do to the state $|0\rangle$?

A: $|+\rangle$

Q: After we measure $\alpha |0\rangle + \beta |1\rangle$ in the computational base, is it still in the state $\alpha |0\rangle + \beta |1\rangle$?

A: No, it's posterior state is either $|0\rangle$ or $|1\rangle$

Q: How can the following circuit be simplified?



A:


Q: What is the result of the operator product XX ?

A:I

Q:How many dimensions does the state vector of a qubit have?

A:2

Q:How can the following circuit be written?



$HX|\Psi\rangle$ or $XH|\Psi\rangle$

A: $HX|\Psi\rangle$

Q:Is $\alpha|0\rangle + \beta|1\rangle$ the same as $\beta|1\rangle + \alpha|0\rangle$? Why?

A:same, order does not matter in plus operator

Q:How large is the matrix representing a single qubit gate?

A:2x2

Q:What is a quantum gate that can distinguish $|+\rangle$ and $|-\rangle$?

A:H

Q:Suppose we have a bit in the quantum state $|1\rangle$. What is the probability a measurement in the computational basis gives the result 0? and 1?

A:0, 1

Q:A superposition of quantum states is the same as a .. of quantum states

A: linear combination

Q:What are the Pauli matrices:

A:XYZ (and I)

Q:What is $X|0\rangle$

A: $|1\rangle$

Q:What does the normalisation condition for the quantum states mean for the probabilities for a measurement in the computational basis?

A: They add up to 1

Q:Suppose we measure $|+\rangle$ or $|-\rangle$. Are the probability distributions of the outcome the same or different for these qubits?

A:The same

Q:What is a geometric interpretation of U being a unitary operation?

A:length preserving, e.g. rotation or reflection.

Q:What is the second quantum gate Alice applies to her qubits in the teleportation protocol? A:A Hadamard gate to the first qubit i.e. the one that started as $|\psi\rangle$

Q:Where does the term classical in the term 'classical bits' come from?

A:classical physics

Q: Suppose we have a quantum state $\sqrt{0.8}|01\rangle + \sqrt{.2}|10\rangle$ and we measure the first qubit in the computational basis. Supposing we get 0 as the outcome, what is the corresponding state of the second qubit?


A: $|1\rangle$ with 100 % certainty

Q: What is the amplitude of the $|1\rangle$ state in the ket $\sqrt{0.7}|0\rangle + \sqrt{0.3}|1\rangle$

A: $\sqrt{0.3}$

Q: What is a quantum circuit showing the X gate being applied to a single qubit?

A:



Q: Suppose we have a quantum state $\sqrt{0.8}|01\rangle + \sqrt{.2}|10\rangle$ and measure the first qubit in the computational basis. Supposing we get one as an outcome, what is the corresponding state of the second qubit?

A: $|0\rangle$ with 100 % certainty

Q: How do the probabilities for the measurement outcomes in the teleportation protocol depend upon the amplitudes α and β in the state $\alpha|0\rangle + \beta|1\rangle$ being teleported?

A: They are independent. They do not depend on α and β at all.

Q: We use the term ket interchangeably with the term

A: (column) vector

Q: Why can't quantum teleportation be used to transmit a quantum state $|\Psi\rangle$ faster than light?

A: To teleport $|\psi\rangle$ to Bob, Alice must send Bob two bits of classical information. The transmission of classical information is limited by the speed of light.

Q: How are the two computational basis states of a qubit usually written?

A: $|0\rangle$ and $|1\rangle$

Q: How does the X gate act on a general state of a qubit?

A: Interchanges the coefficients

Q: Why is it that systems which make good quantum wires are often hard to build quantum gates for?

A: Systems which make good quantum wires interact weakly with other systems; to do a quantum gate we need to manipulate the qubit, and it is hard to manipulate a system which only weakly interacts with other systems.

Q: How many qubits are involved in a teleportation protocol?

A: 3

Q: Why do we rather write $X|0\rangle$ rather than $X(|0\rangle)$?

A: It is a matrix operation on a vector rather than a function applied on an argument.

Q: Why would a neutrino make a good quantum wire?

A: Neutrinos interact very weakly with other matter, which could make it very stable.

Q: How many qubits are directly involved in Alice's part of the teleportation protocol?

A: 2

Q:How many qubits are directly involved in Bob's part of the telepostation protocol?

A:1

Q:Why are quantum wires often hard to implement?

A:Because qubits are fragile, and their state can easily be disturbed.

Q:In the quantum teleportation protocol, what is the 2-bit state initially shared between Alice and Bob?

A: $\frac{|00\rangle + |11\rangle}{\sqrt{2}}$

Q:What is the quantum circuit notation for a quantum wire?

A:

Q:What do we call the two-dimenssional vector space where the state of a qubit lives?

A:state space

Q:What is the result of applying the X-gate to the quantum state

$$\frac{|0\rangle - |1\rangle}{\sqrt{2}}$$


A: $X \frac{|0\rangle - |1\rangle}{\sqrt{2}} = \frac{|1\rangle - |0\rangle}{\sqrt{2}}$

Q:How do the probabilities for the measurement outcomes in the teleportation protocol depend upon the amplitudes α and β in the state $\alpha|0\rangle + \beta|1\rangle$ being teleported?

A:They are independent - they do not depend on those amplitudes at all.

Q:What is the total quantum circuit that Alice applies in a teleportation protocol?

A:



Q:We could rewrite the sequence:

$$|\Psi\rangle \rightarrow [X] \rightarrow [H]$$

as..

A: $HX|\Psi\rangle$

Q:After a measurement, is a qubit in the state $\alpha|0\rangle + \beta|1\rangle$ still in that state?

A:No

Q:Suppose we have a qubit in the state $\frac{|0\rangle + |1\rangle}{\sqrt{2}}$. What is the probability that a measurement in the computational basis will give the result 0? What is the posterior state if that outcome occurs?

50 %, $|0\rangle$

Q:Suppose we have the state $|0\rangle$. What is the probability a measurement in the computational base gives the result 0? What is the probability the measurement gives the result 1?

A:100 %, 1

Q:Suppose we have a qubit in the state

$$\frac{|0\rangle + |1\rangle}{\sqrt{2}}$$

. what is the probability that a measurement in the computational basis will give the result 1? What is the posterior state if that outcome occurs?


A:50 %, $|1\rangle$

Q:Suppose we have the state $|1\rangle$. What is the probability a measurement in the computational base gives the result 0? What is the probability the measurement gives the result 1?

A:0, 1

Q:How do we denote a computational basis measurement in the circuit model?

A:



Q:Suppose we do computational basis measurements for either $|+\rangle$ or $|-\rangle$. Are the probability distributions for outcomes the same or different for these states?

A:The same


Q:Suppose you had a device that could exactly determine the state of a qubit. How could such a device be used as part of a scheme to communicate infinite classical information, using a single qubit.

A:The sender of the classical bits could encode the (infinite string of) bits in the binary expansion of the real part of the amplitude α in the state $\alpha|0\rangle + \beta|1\rangle$. The receiver of the qubit could figure out α and thus the entire string of bits.

Q:What does the normalization condition for quantum states mean about the probabilities for a measurement in the computational basis?

A:Their probabilities for measurement outcomes sum up to 1.

Q:What is a quantum circuit with which we can distinguish the states $|+\rangle$ and $|-\rangle$?

H followed by measurement 

General single-qubit gates

$$U^\dagger \equiv (U^T)^*$$

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix}^* = \begin{pmatrix} a^* & b^* \\ c^* & d^* \end{pmatrix}$$

$$Z \equiv \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}$$

ASo Z leaves $|0\rangle$ unchanged and maps $|1\rangle$ to $-|1\rangle$ Show that X, H, I, Z are unitary we get into complex numbers, skip for course.

$$Y \equiv \begin{pmatrix} 0 & -i \\ i & 0 \end{pmatrix}$$

rotation

$$Y \equiv \begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix}$$

Q:A single qubit is represented as a 2x2 ... matrix

A:Unitary

Q:what is H^\dagger ? A: H

Q:What is the algebraic condition defining unitarity for a matrix U?

A: $UU^\dagger = I$

Q:How large is the matrix representing a single qubit-state?

A:2x2

Q:What are three common names for the dagger operation?

A: adjoint operation, dagger operation, transpose complex conjugate, Hermitian conjugate operation

Q:What notation we use to denote Pauli matrices?

A:I, X, H, Z

Q:What is the element in the bottom left corner of a Y-gate? A:

What does it mean if a matrix is unitary?

Unitary operators preserve the length of their inputs. (cf. rotations, reflections).

This means that once normalised, as quantum gates do not change length, the outcome is normalised.

Unitary matrices are the only matrices that preserve length, they are the exact class that preserve length.

Holds also for N dimensions

Proof ...

how can you compute the length of

$$H \begin{pmatrix} 3 \\ 10 \end{pmatrix}$$

$$\sqrt{10}$$

important $\|U|\psi\rangle\| = \||\psi\rangle\|$

Why are unitaries the only matrices which preserve length?

$$(M|\psi\rangle)^\dagger = \langle\psi|M^\dagger$$

$$\|M|\psi\rangle\|^2 = \langle\psi|M^\dagger M|\psi\rangle$$

$M|e_j\rangle$ is the j th column of M and that $\langle e_j|M|e_k\rangle$ is the jk th element of M.

summary of teleportation protocol

Q: What is the starting state of for the teleportation protocol? A: $|000\rangle$

1. Initial state: Alice has a qubit $|\psi\rangle$. Alice and Bob each prepare a bit in the $|0\rangle$ state, entangle these through a H and CNOT gate and each take one qubit of this now entangled pair.
2. Alice applies a CNOT between $|\psi\rangle$ and her qubit, applies a H-gate to the first bit of the outcome. She measures both her qubits in the computational basis getting results $z=0$ or 1 and $x=0$ or 1 . The probability of each of the outcomes $(00, 01, 10, 11)$ is $\frac{1}{4}$.
3. Classical communication: Alice broadcasts both classical bits z and x
4. Bob recovers the quantum state of $|\psi\rangle$. Bob applies Z^z and X^x and recovers $|\psi\rangle$.

Alice no longer possesses $|\psi\rangle$. It is teleported not copied!

review questions

What is the first gate Alice applies to her qubits in the teleportation protocol


CNOT with $|\psi\rangle$ as the control and the other as target

How many classical bits Alice has to send to Bob in the teleportation protocol?

2

To recover the teleported state Bob applies combinations of the Pauli X and Z matrices

Dit circuit moet je eens uitschrijven.



$$CNOT |C, T\rangle = CNOT |+, -\rangle$$

$$CNOT = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{pmatrix}, |+\rangle = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix}, |-\rangle = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix}$$

$$CNOT |+-\rangle = CNOT \left(\begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \otimes \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix} \right) = \frac{1}{2} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{pmatrix} \begin{pmatrix} 1 \\ -1 \\ 1 \\ -1 \end{pmatrix} = \frac{1}{2} \begin{pmatrix} 1 \\ -1 \\ -1 \\ 1 \end{pmatrix} = \frac{1}{2} \begin{pmatrix} 1 \\ -1 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ -1 \end{pmatrix} = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix} \otimes \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix} = |-, -\rangle$$

NB in Quantum inspire levert dit als antwoord de hele computational basis op met gelijke kansen. Ik kan daar geen $|-\rangle$ terugvinden

Nou dat is wat! In de Hadamard basis (hoe heet deze pendant van de computational basis) is de toestand van de control bit niet behouden!

Nu is de inverse van een CNOT natuurlijk de CNOT. Wat betekent dat voor het bovenstaande circuit? [is ook van rechts naar links te lezen]

quantum country, QC for the very curious part 3

Een qc programma ziet er altijd zo uit:

- Start in een gedefinieerde basis meestal computational basis (cb), z-richting.
- pas een aantal CNOT en single qubit operatoren toe
- eindig met een meting in de cb

Q:What is the initial step of a quantum computation? A:preparation (most often in the cb)


Q:What is the last step in a qcomputation? A: a measurement in the cb

Q: is the product of two unitary matrices also unitary A: Yes (apply them one by one and you'll see)

Q: Suppose I introduceed a gate $e^{i\theta}I$. Does it affect the outcome of a circuit? A: N, the resulting phase shift does not influence the amplitudes of the coefficients of the state vectors. The amplitudes determine the measurement.


Q: the X-operation and the -X operation are the same except a ... factor. A: global phase factor

A toffoli gate can be used to model a AND gate.




exercise: build a NAND gate. A NAND is the negation of an AND gate

Solution:



Er is nog een simpeler oplossing:

Solution:



Q:What is the problem of storing the amplitudes of a many quantum system in a classical computer? A:The number of amplitudes increases quickly with the amount of qubits,

Q: what numbertheoretical problem quantum computers appear to be good in solving?

A: factoring numbers into prime factors.

Q:What is the name of the quantum algorithm to find prime factors of a number? A" Shor's algorithm

Q: Can quantum computers simulate the standard model or quantum gravity? A: unknown (2x)

Q:There were successes in simulation QFT by .. A; John Preskill and colleagues

Exercise:show that the Toffoli gate is reversible Solution: The x, y give no problem, they are just copied (in the cb). If the z is unchanged, its reverse will not change it either, since y and y are unchanged. If it is changed, the repetitive application will change it back. resulting in the I-operator in all cases where the Toffoli has been applied twice. In matrix operation the problem is only in the lower right corner.squaring this matrix yields identity.

quantum country, how quantum teleportation works

Q:What quantum circuit prepares a

$$\frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

state at the start of a teleportation?

A: (0,0) H CNOT

Q:If Bob prepares the state

$$\frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

, shared at the start of the teleportation protocol, why does it not matter which qubit he sends to Alice?

A:Because the states are symmetrical.

Q:Is it possible to use quantum teleportation to transmit information faster than light?

A:No

How quantum teleportation works

The teleportation protocol

How to remember the teleportation protocol

Does teleportation protocol allow faster than light communication?

How partial measurements work

Q: What quantum circuit prepares a

$$\frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

state at the start of a teleportation?

A: (0,0) H CNOT

If Bob prepares the state

$$\frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

, shared at the start of the teleportation protocol, why does it not matter which qubit he sends to Alice? A: Because the states are symmetrical.

Q: Is it possible to use quantum teleportation to transmit information faster than light?

A: No

How partial measurements work

Suppose we measure the first two qubits of a three bit system in the computational basis. What are the possible states of the outcome?

$$|00\rangle, |10\rangle, |01\rangle, |11\rangle$$

Q: Suppose we do a measurement in the cb of the first two bits of a three bit system. What are the possible outcomes?

A: 00, 01, 10, 11

Q: Suppose we have a quantum state $\sqrt{0.8}|0\rangle + \sqrt{0.2}|1\rangle$ and measure the first qubit in the computational basis. What is the probability the measurement gives 1 as an outcome?

A: 0.2

Q: Suppose we have a quantum state $\sqrt{0.8}|0\rangle + \sqrt{0.2}|1\rangle$ and measure the first qubit in the computational basis. What is the probability the measurement gives 0 as an outcome?

A: 0.8

Outcome	Probability	Bob's state
00	$\frac{1}{4}$	$\alpha 0\rangle + \beta 1\rangle = \psi\rangle$
01	$\frac{1}{4}$	$\alpha 1\rangle + \beta 0\rangle = X \psi\rangle$
10	$\frac{1}{4}$	$\alpha 0\rangle - \beta 1\rangle = Z \psi\rangle$
11	$\frac{1}{4}$	$\alpha 1\rangle - \beta 0\rangle = XZ \psi\rangle$

Table 1: metingen

Verifying that the teleportation protocol works

$$(\alpha |0\rangle + \beta |1\rangle) \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

expand:

$$\frac{\alpha |000\rangle + \alpha |011\rangle + \beta |100\rangle + \beta |111\rangle}{\sqrt{2}}$$

Apply CNOT to the first two qubits:

$$\frac{\alpha |000\rangle + \alpha |011\rangle + \beta |110\rangle + \beta |101\rangle}{\sqrt{2}}$$

Now we apply a Hadamard to the first qubit

$$\frac{\alpha |000\rangle + \alpha |100\rangle + \alpha |011\rangle + \alpha |111\rangle + \beta |010\rangle - \beta |110\rangle + \beta |001\rangle - \beta |101\rangle}{2}$$

$$\frac{|00\rangle (\alpha |0\rangle + \beta |1\rangle) + |01\rangle (\alpha |1\rangle + \beta |0\rangle) + |10\rangle (\alpha |0\rangle - \beta |1\rangle) + |11\rangle (\alpha |1\rangle - \beta |0\rangle)}{2}$$


When Alice measures in the computational base, the outcome is $|00\rangle$ with probability given by $\frac{\alpha^2 + \beta^2}{4} = \frac{1}{4}$

The resulting state for Bob is $\alpha |0\rangle + \beta |1\rangle$

The results for the other outcomes of the measurements in Alice's computational basis are:

Now Bob's state is very similar to the original $|\psi\rangle$. He is only a few Pauli gates off. He has to do either nothing, apply X, apply Z or apply ZX respectively. The protocol he has to apply is encoded in the classical bits.

Here a copy of the circuit



NLT Kansen met Quantum, 6V, najaar 2020

Note1: The classical bits reveal nothing about state $|\psi\rangle$. Note2: If Eve steals the classical bits she cannot retrieve $|\psi\rangle$.

The measurements are saying how the states are changed to $|\psi\rangle$, $|X\psi\rangle$, $|Z\psi\rangle$, and $|XZ\psi\rangle$. without giving any information on $|\psi\rangle$!

Note3: It does not matter where Bob is in this story. Alice may broadcast the classical bits over the internet.

What are the probabilities for the outcomes of the teleportation protocol?

$\frac{1}{4}$ for all outcomes

Suppose Alice doesn't know where Bob is. How can she transmit the two classical bits so Bob can complete the teleportation protocol.

Summary of the teleportation protocol

staat hierboven

Q: what is the starting state for a teleportation protocol?

A:

$$|\psi\rangle \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

Q: How many classical bits does Alice send to Bob in the teleportation protocol?

A: 2

Q: To recover the teleported state, Bob applies Pauli gate .. and ..

A: X, Z

Q: What is the first gate Alice applies to her qubits in the teleportation protocol?

A: CNOT with $|\Psi\rangle$ as control and one of the entangled qubits as target

(1 p) 44. Welke poort past Alice als eerste toe in het teleportatieprotocol?
