

ER - DIAGRAM

COURSE 1: Databases


DBMS (Database Management System)

- System designed to define and manipulate data.
 - Storage.
 - Retrieval.
 - Updates.

DBMS (Database Management System)


- Avoid redundancy, inconsistency.
- Concurrent data access.
- Provides security and recovery.
- Declarative language to manipulate, query, define and control data.
- DDL, DML, DCL.
- Data dictionary: database providing info about database structure.

DBMS (Database Management System)




- Text database, example **CSV** format.
- Implemented in 1970 (IBM).
- File = table with a single record on each line.
- Read, store and send.
- Simple structure.
- Inefficient: slow, duplicated values, hard to update etc.

DBMS (Database Management System)




- Tree structure, examples: file system, Windows Registry
- IBM Information Management System (**IMS**)
- XML, XAML
- Used in mainframe era.
- Rigid structure.
- Only *One-to-many* relationship.
- Traversing very easy, moving a node difficult

DBMS (Database Management System)



- Hybrid relation + objects =>> tables of objects.
- **Realm** database for Android/iOS: classes used as schema definition, alternative for SQLite.
- Next: MongoDB Realm.

DBMS (Database Management System)



- Transaction oriented systems (financial transactions).
- **ACID**: Atomicity, consistency, isolation, durability.
- Suitable for structured data.

DBMS (Database Management System)



- RDBMS hard to scale (only scale vertically, not horizontally).
- RDB Restrictive schemas =>> flexible structure.
- The state of the database can change.
- !!! availability, scalability, performance
- Sharding: distribute data on different servers

DBMS (Database Management System)



- Cloud and bigdata.
- **BASE** (Basically Available, Soft state, Eventually consistent)
- Types:
 - key-value: Redis
 - Document: Mongo
 - Column: Apache Cassandra
 - Graph: Neo4j

Sql or NoSQL

Relational

- Vertical scalability
- ACID
- pre-defined schema
- SQL language
- Normalized data

NoSql

- Horizontal scalability
- BASE
- Flexible schema
- No standard
- Collections, redundancy

DBMS (Database Management System)




- Integration of Relational and NoSQL databases.
- Integration of in-memory DB and on-disk DB
- Altibase, Orient DB

Course roadmap

- Database design
- SQL
- NoSql
- ... & other topics ...

Course roadmap



ER diagram

- Visual representation of the ER model.
- Describes the logical structure of the (relational) database.
- Proposed by Chen in 1971.
- Easy to translate into relational tables.
- High-level design.
- Suitable for structured systems.

ER - Diagram

Entity Relationship model


ER - Diagram

- Visual representation of the ER conceptual data model.
- Describes the structure of the (relational) database.
- Not linked to the implementation or hardware.
- Peter Chen developed ERDs in 1976.

ER - Diagram

- User story/requirement analysis ➔ **ER** ➔ relational database schema.
- Easy to translate into relational tables.
- High-level design.
- Suitable for structured systems.

ERD - components



ER - Diagram



ENTITY

person, place, activity, event, concept, real world object etc.
usually a noun



RELATION



ATTRIBUTE

ER - Diagram



ENTITY

person, place, activity, event, concept, real world object etc.
usually a noun



RELATION

links entities (unary, binary, ternary).
usually a verb



ATTRIBUTE

ER - Diagram



ENTITY

person, place, activity, event, concept, real world object etc.
usually a noun



RELATION


links entities (unary, binary, ternary).
usually a verb



ATTRIBUTE

describe entities or relations

Entities




Banking (1)Entities

- A customer opens a saving account or a checking account, at a bank branch. He may also access loans. For each checking account he has a card. Periodically he may withdraw money from his account or partially pay his loans. He may also transfer money from one account to another.

Entities

- Unique names, uppercase characters
- Graphical representation: rectangles
- Relational database: entity ➔ table (line & columns)
- Primary key: attribute or group of attributes that uniquely identifies an entity instance





Primary key

- Unique identifier
 - Must be known at any moment
 - Simple
 - No ambiguities
 - Immutable
-
- Composed keys may be replaced with an artificial key.

Airline (1)Entities



- The airline has one or more airplanes. An airplane has a model number, and capacity. Each flight is carried out by airplanes. An airplane is uniquely identified by its Registration_no and a flight is identified by its Flight_no. A passenger can book a ticket for a flight.

Entities



- Weak entity is an entity that depends on another entity.
- The primary key of a weak entity contains the primary key of the strong entity that it depends on + description/partial key.

Entities




- A sub-entity has the same key as the *super*-entity and all its attributes and relationships.

Relationship

- Association between two or more entities (binary, ternary etc.)
- Relationship → column (foreign key) or table.
- Graphical representation: oriented arc.
- Two relationships with the same name link different entities.
- Cardinality defines the numerical attributes of the relationship between two entities: **MANDATORY** (min) **OPTIONAL** (max)


Relationship cardinality

- MANDATORY (must)
- OPTIONAL (may)




Relationship cardinality


- MANDATORY (must)
- OPTIONAL (may)




Relationship cardinality

- Reflexive relationship
unary relationship.







Banking (2) Relationships



Airline (1)Relationships


- The airline has one or more airplanes. An airplane has a model number, and capacity. Each flight is carried out by airplanes. An airplane is uniquely identified by its Registration_No and a flight is identified by its Flight_No. A passenger can book a ticket for a flight.






Airline (1) Relationships


- The airline has one or more airplanes. An airplane has a model number, and capacity. Each flight is carried out by airplanes. An airplane is uniquely identified by its Registration_No and a flight is identified by its Flight_No. A passenger can book a ticket for a flight. A flight may have **one or more stops**.



Airline (1) Relationships


- The airline has one or more airplanes. An airplane has a model number, and capacity. Each flight is carried out by airplanes. An airplane is uniquely identified by its Registration_No and a flight is identified by its Flight_No. A passenger can book a ticket for a flight. A flight may have one or more stops. The passenger will pay for **extra baggage**.





Ternary relationships


- Relationship binding simultaneously 3 entities.




Indexes

Indexes


- Maps search key to data using specific data structures.
- Optimized search.
- Optimized joins (lookup in more than one table)
- Optimized order/group
- slower DML (insert and update operations).
- extra memory



Index



Sql Optimizer



Autogenerated columns

- MySQL auto-generated index (key):
 - DB_ROW_ID increases monotonically as new rows are inserted.
 - DB_ROLL_PTR roll pointer, points to log record.
 - DB_TRX_ID last transaction that updated or inserted the row.
- Oracle rowid:
 - Pseudo column 18 characters = 10 + 4 + 4 (block, row, file).
 - Store and return row address in hexadecimal format (string).
 - Unique identifier for each row.
 - Immutable.

Autogenerated columns

- Oracle rowid:
 - Used in where clause to select/update/delete a row.
- Oracle rownum:
 - Sequential number in which oracle has fetched the row, before ordering the result
 - Temporary generated along with a select statement.
- Mongo
 - ObjectID (timestamp 4Bytes + random 5Bytes + Count 3Bytes).

Index

- Data structure that optimize search.
- Automatically created when a primary key is defined.

MySQL

```
SHOW EXTENDED INDEX FROM index_test;
```

Oracle

```
select * from user_indexes  
where table_name = 'INDEX_TEST';
```

Primary key

- Constraint imposed on insert/update behavior.
- NotNull & Unique.

MySQL

```
select * from information_schema.statistics  
where table_name = 'index_test1'  
and index_name = 'primary';
```

Oracle

```
select * from user_constraints  
where table_name = 'INDEX_TEST';
```

Index types

Clustered index (SqlServer, MySql)


- Defines the order in which data is physically stored in a table. (index on column semester)
- Only one clustered index on a table (data can be stored in only one order)
- A cluster index is created automatically when a primary key is defined.
- No second data structure for the table
- Oracle: IOT index organized tables. Table is stored in a B-tree structure. (key and non-keys column are stored in leafs)

B – Tree

- B -- Balanced tree.
- Default index type in Oracle.
- Two types of nodes: branch blocks and leaf blocks.
- Branch blocks pointers to lower levels.
- Leaf blocks contain rowids/physical address.
- The number of blocks traversed in order to reach a leaf block is the same for each leaf block.

B – Tree

- create index idx_emp_id on employees(employee_id).
 - Devide employee_id values in sorted ranges.
 - Leaf nodes store rowid



Reverse index

- B – tree where keys are in reverse order. Key 4573 is stored 3754.
- Optimized insert operations.
- Key 4573 will be stored in the same block with key 9573
while 4574 will be stored in a different block.

Bitmap index

- Used for columns with limited number of distinct values.
- Example: language proficiency levels (en)

emp_id	en	fr
1	A1	B1
2	A2	B2
3	C1	A1
4	A1	B1
5	A1	

row_id	A1	A2	B1	B2	C1	C2
AAB0IYAAEAAAFNHABD	1	0	0	0	0	0
AAB0IYAAEAAAFNHABV	0	1	0	0	0	0
AAB0IYAAEAAAFNHABX	0	0	0	0	1	0
AAB0IYAAEAAAFNHAAv	1	0	0	0	0	0
AAB0IYAAEAAAFNHAAV	1	0	0	0	0	0