Reconstructing Frozen Heterogeneous Pretrained Models: Sublayer Fusion, Coordinated Routing, and Chimera Distillation

Anonymous Author(s)
Affiliation
email@example.com

Abstract

Combining heterogeneous pretrained models—bidirectional encoders, causal decoders, and vision transformers that differ in architecture, hidden width, and modality—usually requires joint retraining, architecture surgery, or lossy output-level ensembling. We study how such models can be *reconstructed* while every base stays frozen, in three steps. **(i) Sublayer fusion.** A shared sparse Top-K router selects one of M frozen architectural experts per token; semantic aligners map mismatched hidden spaces into one shared routing space; experts are fused residually with per-expert gates. Across four aligner designs we measure a strict but *saturating* ladder (linear < mean < cross-architecture attention < mixture), and a capacity-matched control shows the ceiling is a matter of design rather than of parameter count. **(ii) Coordinated routing.** We ask how a global hub should influence the shared router, and prove that modulating the softmax temperature (gate-style) is the only one of four hub modes satisfying perfect degeneration, order preservation, boundedness, and low overhead at once; we also diagnose a hidden failure mode in which tanh saturation severs the gradient to the hub during long training. **(iii) Independent-model reconstruction.** Chimera distillation collapses the ensemble into a single-base student, and a weight scan over the loss shows that the apparent "student beats teacher" margin is entirely attributable to a direct-target term rather than to concept-direction transfer or variance averaging. Because fused inference keeps every base alive and distillation is a deployment device, the study is only as trustworthy as its evaluation. We therefore apply a uniform *out-of-sample discipline* across the whole stack, and it overturns several of our own in-sample findings: the in-sample best hub mode is not the out-of-sample best, an advertised corpus-scale boundary is not established, and long-training and repair gains shrink to noise. What survives held-out evaluation is the alignment-ladder ceiling. The attention-path advantage does not: a projection-space audit (§6.4) shows it to be a property of a frozen random shared space rather than of architectural heterogeneity, and it disappears once that space is learned. The scale-heterogeneous fusion margin does not: a projection-space audit (§6.4) shows it to be a source-identification effect inside a shared space that was never optimized, and it does not persist once that space is learned. We report the negative results that bound the method—component composition, nested aligners, multi-teacher distillation, and toy multimodal benchmarks—from hundreds of seeded end-to-end runs across 41 versioned engineering generations and 430 unit and integration tests.

1 Introduction

Practitioners rarely have the luxury of one perfect pretrained model. A working pipeline may need a bidirectional encoder for text understanding, a causal decoder for generation, and a vision transformer for perception. Three ways to combine such models dominate current practice, and each is unsatisfying. Joint multi-task retraining is expensive and re-opens the pretraining budget. Output-level ensembling keeps every model alive at inference and blends predictions that were never trained to complement each other. Weight

merging (Ilharco et al., 2023; Yadav et al., 2023; Wortsman et al., 2022) requires the merged models to share architecture and initialization, which rules out heterogeneous bases outright.

This paper studies a fourth option, one level lower, and asks how far it can be pushed. Within a transformer block, the feed-forward (FFN) sublayer is the most modular and the most replaceable component: it acts position-wise, it carries a large share of the parameters, and its role as a key–value memory (Geva et al., 2021) suggests that *which* memory bank is consulted can be decided per token. We therefore treat frozen heterogeneous bases as a resource to be *reconstructed* in three stages, each of which removes one of the three obstacles above.

Stage 1 — sublayer fusion. We rebuild the FFN sublayer itself as a **heterogeneous micro-fusion layer**: a shared, sparse Top-K router selects among M frozen architectural experts; rectangular projections or learned semantic aligners map mismatched hidden spaces ($D_m \in \{192, 312, 768\}$) into one shared routing space; per-expert gates, channel-wise alignment, and INT4 pseudo-quantization noise complete the layer. No base model is modified, and only alignment, routing, and gate parameters are trained. A dual-path extension makes the attention sublayers routable as well, so that a token can independently select one attention expert and one FFN expert.

Stage 2 — coordinated routing. Fusion imposes a new question that within-architecture MoE never faces: the experts disagree about *what a good routing decision is*, because they were never trained together. Should a global hub—a shared vector summarizing the ensemble—influence the router, and if so, how? We formalize five design constraints and prove that among four candidate hub mechanisms, only temperature modulation (gate-style coordination) satisfies all five: it degenerates exactly to the no-hub baseline when disabled, preserves logit ordering by construction, is bounded, and costs $O(D_{\text{shared}})$ parameters. We also identify a hidden failure mode—tanh saturation in the temperature scalar severs the gradient to the hub under long training—and two repairs that restore gradient flow.

Stage 3 — independent-model reconstruction. Fusion has a deployment cost: the fused system still needs every base alive at inference. We close the loop with **chimera distillation**, in which a single-base student—a real frozen TinyBERT (Jiao et al., 2020) with a low-rank adapter (Hu et al., 2022)—is trained to reproduce the fused teacher's output from its *own* modality's input alone.

The thread that holds the three stages together. Each stage is a claim about a quantity measured at small scale, and each claim is only as good as its evaluation. We therefore adopt a single discipline throughout: every headline number is validated on inputs the model never trained on. This discipline is not cosmetic. Applying it retroactively to our own earlier results changed several of them, in both directions. On the negative side, the in-sample best hub mode is not the best out-of-sample, an advertised corpus-scale boundary does not survive, and the two gradient repairs turn out not to move fusion MSE at all. On the positive side, the alignment-ladder ceiling survives held-out evaluation intact. The attention-path advantage does not: an audit of the projection space (§6.4) shows that the attention path's lead over the FFN path belongs to a frozen random shared space, not to architectural heterogeneity, and that it disappears once the space is learned. The scale-heterogeneous fusion gain (§6.3) does not: under the same held-out protocol its margin is retained in full, but an audit of the projection space (§6.4) attributes that margin to the projection being frozen and randomly initialized, and shows that it disappears when the space is learned. We report both outcomes, because a mechanism-level study whose positive results are not separated from its evaluation artifacts is not evidence.

We make the following contributions, ordered from mechanism to evidence.

1. **An alignment ladder with a measured ceiling** (§6.5). Replacing the frozen linear projection with a cross-base mean, then shared-key/value attention, then a mixture-of-experts aligner yields a strict ladder ($1.14 \to 0.48 \to 0.34 \to 0.26$ MSE); nesting the mixture regresses by 4.7%. A capacity-matched control in which the mixture aligner is reduced to bit-for-bit the attention aligner's parameter count still leaves the mixture ahead by 36.5% on held-out data, so the ceiling is design, not scale.
2. **Fusion that beats its parts, with the gain located** (§6.2). FFN-only routing beats the best single expert by 20.3% and equal-weight averaging by 17.3%; dual-path routing raises the margin over averaging to 84.8%. A path decomposition shows the cross-architecture gain concentrating in the attention path

(+82.7% in-sample, +70.6% held-out). Both margins are later re-examined under a projection-space audit (§6.4): the target block in this configuration is the modality index, the margin is unchanged when the target blocks are permuted across modalities, and it collapses when the frozen random projection is replaced by a learned one.

3. **A uniqueness theory for routing coordination** (§4). Four hub modes are compared against five design constraints; gate-style temperature modulation is the only mode satisfying all five, with perfect degeneration and order preservation proved constructively (hence unfalsifiable by data leakage). We also diagnose the tanh-saturation failure mode (§4.3).
4. **An honest decomposition of chimera distillation** (§6.9). A single-base student is *not* shown to internalize the teacher's concept directions: a β scan over the direct-target weight, a variance-boundedness test, and a representation-transfer probe jointly show that the entire measured margin is attributable to the direct-target term in the loss.
5. **Out-of-sample discipline as a result in its own right** (§6.11). Across the stack we find that in-sample composition rankings are training-fit orderings, not capability rankings: the same four hub modes that rank gate first in-sample rank router-norm first out-of-sample, and the corpus-scale boundary that appears in-sample is absent out-of-sample.

Just as informative are the boundaries. Five distinct negative results bound the method. (i) Composing a repaired router with a stronger aligner adds nothing once the aligner already contains the repair (+71.0% vs. +72.6% over their common baseline). (ii) Harder toy VQA benchmarks do not rescue multimodal evaluation—all models drop to random accuracy. (iii) Multi-teacher distillation regresses in every configuration, and a dispatch-style reformulation removes the harm without producing any gain. (iv) Nesting the mixture aligner with itself regresses by 4.7% MSE. (v) Pure distillation does not outperform the teacher, so the entire student-vs-teacher margin is target leakage. The recurring lesson is that adding machinery is not the same as adding capability, and measuring in-sample is not the same as measuring capability.

2 Related Work

Mixture-of-experts routing. Conditional computation routes each input to a subset of experts (Jacobs et al., 1991; Shazeer et al., 2017), and modern sparse MoE stacks scale this to trillion-parameter regimes (Fedus et al., 2022; Zoph et al., 2022). Mixtral 8x7B (Jiang et al., 2024) delivers 47B total / 13B active parameters per token via top-2 token-level routing over eight FFN copies, with measured temporal locality and clear domain specialization. Soft routing addresses MoE instability and load imbalance through slot-based differentiable mixtures (Puigcerver et al., 2024), and fine-grained expert segmentation with shared-expert isolation (Dai et al., 2024), together with branch-and-train-then-mix recipes (Sukhbaatar et al., 2024), refines specialization further. In all of these systems the experts are *homogeneous*: they share architecture, dimension, and training. Sparse upcycling (Komatsuzaki et al., 2023) converts a dense checkpoint into an MoE by cloning and perturbing its FFNs, again producing homogeneous experts. Our experts are the opposite: entire pretrained models with different architectures, tokenizers, and modalities, kept frozen. The routing problem correspondingly changes from balancing identical experts to aligning incompatible representation spaces—which is the subject of §3.2 and §4.

Heterogeneous foundation-model collaboration. A growing line of work studies collaboration between pretrained models that do *not* share architecture. Within the homogeneous limit, Symphony-MoE (Wang et al., 2025) upcycles several like-architected but differently-pretrained LLMs by harmonizing shared backbones via SLERP and re-permuting FFN neurons through a linear assignment problem. The harder cross-architecture case is studied under cross-architecture distillation (Wang et al., 2024b), whose cross-attention projector plus dual-view mimicking is the closest published antecedent to our fusion layer. For orchestrated heterogeneous LLM inference in cross-border e-commerce relevance, Liu et al. (2026) show that *concatenating* expert embeddings beats weighted averaging for models with distinct embedding manifolds—a geometric argument our four-mode comparison corroborates from the opposite direction (the modes that preserve per-expert information beat the one that averages it). Expert-aware post-training quantization (Du et al., 2026) validates the cross-expert channel-similarity assumption that underpins our channel alignment.

Together these works delineate a *heterogeneity spectrum* (Figure 1) within which we sit at the hardest corner: same architecture, same modality, and same manifold is the easy limit; our setting is simultaneously different on all three axes.




Figure 1: **Heterogeneity spectrum** of recent foundation-model collaboration work across three axes: *architecture* (same vs different), *modality* (text / vision / multimodal), and *routing granularity* (token-level vs query-level). Existing work populates the architecture-homogeneous limit; the architecture-heterogeneous limit is sparsely populated, with ScaleKD and Orchestrating-HetExp as the closest antecedents. This paper sits at the intersection of all three harder axes simultaneously, on CPU-sandbox scale rather than industrial.

Model merging and upcycling. Task arithmetic (Ilharco et al., 2023), TIES-merging (Yadav et al., 2023), and model soups (Wortsman et al., 2022) combine *weights* of models that share a backbone. Heterogeneous bases cannot be merged this way; our fusion layer is the corresponding mechanism for the heterogeneous case, operating through activations instead of parameter addition.

Parameter-efficient adaptation. Adapters (Houlsby et al., 2019) and LoRA (Hu et al., 2022) freeze a base and train small insertions. We use the same philosophy, but the frozen part is a *pool* of heterogeneous bases and the trained part is the inter-base machinery (projections, aligners, router, gates). AdapterFusion (Pfeiffer et al., 2021) composes per-task adapters non-destructively through a learned attention combiner, and Huang et al. (2024) generalize this to a dynamic linear combination of per-task LoRA modules optimized by black-box search—both demonstrate the non-destructive composition principle we independently adopt for cross-architecture fusion. Our aligner ladder can be read as an activation-level analogue, and our multi-teacher negative result (§6.9) echoes Pfeiffer et al.'s finding that naive source combination is not free.

Knowledge distillation. Distillation transfers a teacher's behavior to a smaller student (Hinton et al., 2015; Sanh et al., 2019; Gou et al., 2021); multi-teacher variants are known (You et al., 2017), and recent multi-teacher LLM distillation uses rationale-augmented objectives to recover knowledge diversity (Tian et al., 2025). Chimera distillation differs in both directions: the teacher is a multi-base *ensemble*—echoing the collective-intelligence framing of mixture-of-agents (Wang et al., 2024a) and the stacked-generalization idea (Wolpert, 1992), though our collaboration operates at the representation level through learned routing rather than at the output level—and the student sees only one base's input yet must reproduce the ensemble's fused output. Quantization-aware training injects fake-quantization noise during training (Dettmers et al., 2022); we use INT4 fake quantization on expert outputs as regularization and hardware-realism pressure, not as a deployment compression claim. Teacher-assistant distillation (Mirzadeh et al., 2020) is the nearest analogue of the effect we decompose in §6.9: an intermediate or cleaner target helps the student, and here the "cleaner target" is partly the direct-target term, which we show to be the whole story.

Global coordination of selection. The question of stage 2—whether a global signal should coordinate a selection mechanism—has a long history. Global Workspace Theory (Baars, 1988) motivates a broadcast-style hub, but we treat it as design inspiration rather than as a testable prediction, since it does not by itself specify the functional form of the interaction. Sparse-gated MoE (Shazeer et al., 2017) and Linformer-style global mixing (Wang et al., 2020) are the closest architectural relatives. Global mixers of the linear-attention and state-space family (Katharopoulos et al., 2020; Gu et al., 2022; Gu & Dao, 2023) sit on an orthogonal axis: they mix across *sequence positions* within one model by carrying content in a state, whereas our hub coordinates across the *expert* axis of many frozen models at one position by modulating routing *certainty*—a scalar temperature that rescales logits without adding content, preserving logit ordering by construction and degenerating exactly when disabled. Content-carrying states satisfy neither property in general, so the two mechanisms are composable rather than competing.

3 Method I: Heterogeneous sublayer fusion

3.1 Problem setup

Let $\mathcal{B} = \{B_1, \ldots, B_M\}$ be M frozen pretrained bases with hidden sizes D_m and, in general, different architectures: a bidirectional encoder (TinyBERT, D=312) (Jiao et al., 2020; Devlin et al., 2019), a causal decoder (TinyLlama-110M, D=768), and a vision transformer (ViT-tiny, D=192) (Dosovitskiy et al., 2021). Each base consumes its own tokenizer or processor and produces hidden states $h_m \in \mathbb{R}^{S \times D_m}$ natively; we never force a shared encoder. The goal is a fusion layer operating in a shared space of width $D_{\text{shared}} = 256$ such that (i) every base remains frozen, (ii) only alignment, routing, and gate parameters are trained, and (iii) the layer degrades gracefully—disabling any single expert leaves a working system.

3.2 The heterogeneous fusion layer




Figure 2: Heterogeneous micro-fusion, coordinated routing, and chimera distillation. Three frozen pretrained bases with different architectures and hidden widths are natively encoded, aligned into a shared 256-dimensional space, and sparsely routed (K=1) to frozen SwiGLU experts whose outputs carry INT4 fake-quantization noise. A global hub modulates the softmax temperature of the shared router (§4). Chimera distillation then collapses the ensemble into one independent single-base student (§5).

Figure 2 shows the layer. Given the residual-stream input $x \in \mathbb{R}^{B \times S \times D_{\text{shared}}}$, each expert m computes

$$h_m = \text{sg}(x) \odot \gamma_m + \beta_m, \qquad \tilde{F}_m = Q_{\text{INT4}}\big(F_m(h_m)\big), \tag{1}$$

$$F_m(h) = \big(\text{SiLU}(hW_m^{\text{gate}}) \odot (hW_m^{\text{up}})\big)\, W_m^{\text{down}}, \tag{2}$$

where Q_{INT4} is group-wise (group size 128) 4-bit fake quantization with a straight-through estimator in the backward pass. Three deliberate choices shape the layer.

Gradient truncation. The expert input is detached (sg), so the frozen bases' intermediate activations never enter the autograd graph. Activation memory drops from $O(MLD_{\text{ff}})$ to $O(LD_{\text{shared}})$ plus adapter parameters, which is what makes M-base fusion trainable on CPU at all. The cost is that experts cannot shape upstream representations through gradients; the router and gates carry all adaptation.

Sparse routing with straight-through gradients. The router computes logits $z = xW_r^\top$ from the *clean* pre-noise input, $\alpha = \text{softmax}(z/\tau)$, and the hard selection $\hat{\alpha} = \text{TopK}(\alpha, K)$ (K=1 unless stated) is applied in the forward pass while the backward pass follows the softmax weights, in the spirit of straight-through estimators (Bengio et al., 2013). Routing on the clean input keeps router decisions from chasing the quantization noise it would otherwise induce. The temperature τ is the hub's sole channel of influence and is 1 unless a hub is fitted (§4).

Residual fusion with positive gates. The layer output is

$$y = x + \sum_{m=1}^{M} \hat{\alpha}_m \, \alpha_m \, \tilde{F}_m(h_m), \tag{3}$$

with $\alpha_m \sim \mathcal{U}(0.01, 0.1)$ at initialization. The positive, non-trivial initialization avoids the near-zero-gate dead lock: gates initialized at 10^{-4} scale receive gradients too small to escape, which we observed as flat training curves before adopting the uniform initialization.

3.3 Two-phase training protocol

Routing is fragile early in training—random router weights produce noise selections that poison the expert gates. Training therefore runs in two phases. **Phase 1** (first 10% of steps): routing is forced uniform ($\hat{\alpha}_m = 1/M$, detached) and the router is frozen, so only alignment and gate parameters learn. **Phase 2** (remaining 90%): the router unlocks and Top-K selection activates, with the loss

$$\mathcal{L} = \mathcal{L}_{\text{task}} + \lambda_1 \mathcal{L}_{\text{balance}} + \lambda_2 \mathcal{L}_z, \tag{4}$$

where $\mathcal{L}_{\text{balance}}$ encourages even expert load and $\mathcal{L}_z$ regularizes router logits. Optimizer groups isolate learning rates: 10^{-4} for the router and hub, 10^{-2} for alignment parameters, and 10^{-3} for the output gates α_m. The router must move slowly because its selections are discrete; the alignment layers can move quickly because their gradients are dense.

3.4 The alignment ladder

The shared space is where heterogeneous bases meet, and how it is constructed turned out to matter more than anything else in the stack. We evaluate four designs of increasing sophistication (Figure 3):

Linear projection (baseline). Each base's hidden state passes through a rectangular projection $P_m \in \mathbb{R}^{D_{\text{shared}} \times D_m}$, orthogonal-initialized and frozen. Bases are projected independently and know nothing about each other.

Mean aligner. Learned per-base down-projections $W_m \in \mathbb{R}^{d \times D_m}$ followed by a cross-base mean of the projected representations.

Cross-architecture attention aligner. Each base is projected to the shared width; the cross-base mean provides shared keys and values; each base queries the shared context with its own query projection—the standard query/key/value separation of cross-attention (Vaswani et al., 2017)—and adds the attended concept vector residually. Every base therefore reads a concept summary written by *all* bases.

Mixture aligner. Each base contributes n=4 small shared experts (two-layer MLPs) to a pooled bank of $M \times n$ experts. Expert outputs serve as queries against a shared key/value context derived from their mean, and the attended outputs are aggregated. The aligner itself becomes a tiny mixture-of-experts over the heterogeneous sources.




Figure 3: **The alignment ladder** as a strict-but-saturating chain: mode A (linear projection) → B (mean aligner) → C (cross-architecture attention) → D (mixture-of-experts aligner). Each mode improves on the previous one in 5-seed MSE; nesting the mixture regresses by 4.7% (§6.5), marking the ceiling.

Two empirical facts motivate the ladder. First, *native encoding is not optional*: in an early control where all three modalities were tokenized and encoded by the same BERT, the fusion gain over a single expert collapsed from +20.3% to +4.0%. Uniform encoding erases exactly the architectural differences the router is supposed to exploit. Second, the ladder is *strict but saturating*: each mode improves on the previous one, and the improvement stops at the mixture aligner (§6.5)—a ceiling we hold as a scale-bounded hypothesis, not a law.

3.5 Dual-path routing: making attention routable

The FFN-only layer routes among memory banks but always consumes the same attention output. The dual-path extension makes the attention sublayers routable too: each token independently selects one *attention expert* and one *FFN expert*, from two pools that may come from different bases. Attention experts expose the native Q/K/V/O projections of the base's first block; the selected expert's attention is recomputed in its native space and projected back through P_m. Per-expert optimizer groups implement the learning-rate isolation of §3.3 per expert. The dual-path design asks whether cross-architecture complementarity lives in the FFN weights, in the attention patterns, or in both—and the path decomposition in §6.2 gives a sharp answer.

4 Method II: Coordinating the shared router

4.1 Four hub modes

Heterogeneous experts were never trained together and disagree about what a good routing decision is. A natural response is a *global hub*: a shared vector $c \in \mathbb{R}^{D_{\text{shared}}}$ that summarizes the ensemble and influences the router. We consider four ways the hub can act on the routing logits z_m:

Definition 4.1 (Broadcast mode)**.** $z_m^{(\text{bc})} = z_m + (Uc)_m$, where $U \in \mathbb{R}^{M \times D_{\text{shared}}}$ is learnable. The hub adds a bias to each expert's logit.

Definition 4.2 (Router-norm mode)**.** $z_m^{(\text{rn})} = \text{LayerNorm}(z_m + Uc)$. Broadcast, then normalize.

Definition 4.3 (Adaptive-EMA mode)**.** decay $= \text{sigmoid}(\alpha \cdot \|c\|)$. The hub controls its own exponential-moving-average decay rate; the EMA state then enters the logits.

Definition 4.4 (Gate-style mode (proposed))**.** $t_{\text{scalar}} = W_t^\top c$, $\tau = 1 + \epsilon \cdot \tanh(t_{\text{scalar}})$, $z_m^{(\text{g})} = z_m/\tau$. The hub modulates the softmax temperature.

The modes differ in *how* the hub enters the decision. Broadcast and router-norm *add* a hub-dependent term to the logits; adaptive-EMA lets the hub shape an accumulating state; only gate-style *scales* the logits by a positive scalar. That structural difference is what the next subsection turns into a theorem.

4.2 Design constraints and why only gate-style satisfies them

We formalize five constraints that any hub mechanism for a frozen-expert router should satisfy:

- **(G1) Perfect degeneration**: $c = 0$ yields the no-hub baseline exactly.
- **(G2) Order preservation**: the hub preserves the relative ordering of logits.
- **(G3) Monotonicity**: hub intensity changes routing determinism monotonically.
- **(G4) Boundedness**: hub influence has a theoretical upper bound.
- **(G5) Low overhead**: hub parameters are $O(D_{\text{shared}})$, negligible against the experts.

Theorem 4.1 (Perfect degeneration)**.** *With $c = 0$, gate-style is exactly equivalent to the no-hub baseline.*

Theorem 4.2 (Order preservation)**.** *Gate-style preserves the ordering of the logits; broadcast can reverse it.*

Theorem 4.3 (Uniqueness)**.** *Among the four hub modes of §4.1, gate-style is the only one satisfying all five constraints (G1)–(G5).*

Proof sketches are immediate from the structure and are given in full in Appendix B. Theorem 4.1 holds because $\tau = 1$ when $c = 0$; Theorem 4.2 holds because $\tau \in (1 - \epsilon, 1 + \epsilon) \subset (0, \infty)$ divides all logits by one common positive scalar; Theorem 4.3 holds because broadcast violates (G2), router-norm violates (G1) (LayerNorm rescales even at $c = 0$), and adaptive-EMA violates (G1) and (G2) (its state persists and carries content).

Two remarks matter for how these theorems should be read. First, they are *constructive* properties of the functional form, not empirical claims, so no amount of training or data leakage can manufacture or destroy them; they are the part of this section that the held-out discipline of §6.11 cannot touch. Second, the theorem is about *admissibility*, not about which mode wins: it says that if a hub must never harm the no-hub baseline and must never reorder expert preferences, gate-style is the only option among the four. Whether the admissible option is also the best-performing one is an empirical question, and §6.6 shows that the answer is not simply yes.

4.3 A hidden failure mode: tanh saturation

Systematic experiments across the project's engineering generations revealed a case in which the hub silently stops working. Under long-horizon training the central hub stops updating: diagnostic runs show grad_norm_central = 0.0000, meaning c and W_t receive zero gradient and freeze at a suboptimal value.

The root cause is *tanh saturation*. The temperature scalar is $\tau = 1 + \epsilon \cdot \tanh(t_{\text{scalar}})$. When $|t_{\text{scalar}}|$ grows large, $\tanh(t_{\text{scalar}}) \approx \pm 1$ and its derivative vanishes:

$$\frac{\partial \tau}{\partial t_{\text{scalar}}} = \epsilon \cdot (1 - \tanh^2(t_{\text{scalar}})) \approx 0. \tag{5}$$

By the chain rule, $\partial \mathcal{L}/\partial c \approx 0$. The forward pass runs correctly; the backward pass is severed. Two repairs target the mechanism directly: replacing tanh with softplus (whose derivative does not vanish at large argument under the same parameterization) and rescaling the gradient into the hub. Both restore gradient flow; §6.8 reports what they do and do not do to end-to-end error.

5 Method III: Reconstructing an independent model

Fusion at the sublayer level keeps every base on the inference path. For deployment we want the opposite: one model, one modality, no ensemble. The chimera distillation step compresses the ensemble into a single-base student that never sees the other bases' inputs.

Student architecture. The unimodal student is a real frozen TinyBERT (Jiao et al., 2020) with a rank-8 LoRA adapter (α=16) applied to its hidden states, a linear head to D_{shared}, and a LayerNorm. Only 85,632 of ∼14M parameters (0.60%) are trainable. Unlike the simplified MLP student we first tried, a pretrained student brings prior linguistic structure to the reconstruction problem.

Distillation objective. The teacher is the fused multi-base system with the mixture aligner. Given a batch from the *student's modality only*, the teacher runs its full multi-base forward pass and the student must match it:

$$\mathcal{L}_{\text{distill}} = \alpha_{\text{h}} \,\text{MSE}\big(y_s,\, \text{sg}(y_t)\big) + \beta_{\text{h}} \,\text{MSE}\big(y_s,\, y_{\text{target}}\big), \tag{6}$$

with $\alpha_{\text{h}} = 0.7$ and $\beta_{\text{h}} = 0.3$. The first term distills the teacher's hidden-state concept directions; the second adds a direct target signal. This is not a temperature-scaled KL divergence but a weighted combination of two MSE terms, and the weight β_{h} is the object of the decomposition in §6.9.

Multimodal student. The multimodal student pairs TinyBERT (text) with ViT-tiny (image), each with its own LoRA, plus a learned modality router that decides which base processes which input. It is trained with the same objective against the same single-teacher ensemble.

Evaluation discipline. Our first real-student experiments were evaluated on training-distribution inputs with easily fitted targets and produced near-zero MSE—an overfitting artifact masquerading as success. All later student evaluations use held-out inputs from a real mini-corpus (16 Wikipedia-style training sentences, 6 held out), forcing the student to reproduce the teacher's concept directions under a token distribution it never trained on. We flag this correction explicitly because the uncorrected numbers are flattering to the point of meaninglessness, and because the same correction, applied elsewhere in the stack, changes conclusions in both directions (§6.11).

6 Experiments

6.1 Setup and honest scope

All experiments run on CPU only (Linux, PyTorch 2.x, no GPU acceleration). Widths are small (D_{shared}=256, S=16), targets are synthetic class-direction constructions (a block of the shared space is set to 1.0 for the target class), and every configuration is averaged over 5 seeds unless stated. The full stack passes 430 unit and integration tests; each number below is produced by a named, committed script (reproduction commands in §9). These are *mechanism-level* results: they establish that the reconstruction mechanisms behave as designed under controlled conditions, not that the method survives 0.5B-parameter scale or perplexity-level evaluation on real tasks. We consider the scale gap the single largest open risk and discuss it in §8.

6.2 Sublayer fusion gains and where they come from

Table 1: Sublayer-level fusion of heterogeneous bases (5-seed means, fuse MSE; lower is better). v6: FFN-only routing over three architectures. v7-A/v7-B: dual-path routing (one attention + one FFN expert per token), cross-architecture and same-architecture respectively. Gain is computed per seed then averaged.

Setting	attn-only	ffn-only	avg	fuse	gain vs. avg
v6: FFN-only, cross-arch (3 bases)	—	7.08	6.77	**5.60**	+17.3%
gain vs. best single expert					+20.3%
v7-A: dual-path, cross-arch	1.16	7.10	7.06	**1.06**	+84.8%
v7-B: dual-path, same-arch	0.382	0.414	0.383	**0.378**	+1.0%

Table 1 summarizes the fusion results. With FFN-only routing (v6), the fused layer beats the best single expert by 20.3% and equal-weight averaging by 17.3%, with every seed passing—the first demonstration that genuinely different pretrained architectures can share one sparse router at the sublayer level. Dual-path routing (v7-A) raises the margin over averaging to 84.8%.

The path decomposition is the interesting part, and it is one of the findings that survives held-out evaluation—but a later projection-space audit (§6.4) qualifies what it measures: the attention path's lead is a property of the frozen random shared space, and it largely disappears once that space is learned. In the cross-architecture setting, the attention path alone reaches MSE 1.16—already close to the fused 1.06—while the FFN path alone (7.10) is indistinguishable from averaging (7.06). Cross-architecture complementarity therefore surfaces almost entirely in *attention patterns*: once each token can consult the architecture whose attention mode fits it, the FFN experts' remaining contribution is the residual refinement. An independent held-out audit of this claim (`run_v46_attn_path_audit`) re-measured the attention-vs-FFN path gap under both an in-sample and a held-out protocol: the gap is +82.7% in-sample and +70.6% held-out, winning on 5/5 seeds under both, so the claim is not an artifact of in-sample evaluation. We state it narrowly—attention varies more across architectures than FFN activations do—and it does not contradict the key–value-memory view of FFNs (Geva et al., 2021; Meng et al., 2022; Dai et al., 2022): FFN weights carry rich knowledge *within* an architecture, but our result indicates that this knowledge averages well *across* architectures, whereas attention patterns do not. In the same-architecture control (v7-B), where the three TinyBERTs differ only by random Q/K/V/O perturbation, the dual-path gain shrinks to +1.0%: with architectural diversity removed, the router has almost nothing left to select on. Routing value tracks architectural diversity, not expert count.

6.3 Scale-heterogeneous fusion: one large base and many small

The experiments above compose bases that differ in *architecture*. A second line of the project varies *scale* instead, and it is the one that the present audit had to re-establish from scratch, because none of its runners contained any held-out evaluation at all. The setting is one large base (MSA-4B, $D = 2560$) and two small ones (embedding-0.6b and reranker-0.6b, $D = 1024$), each projected through its own rectangular P_m into the shared space D_{shared}=256 and selected by the same sparse router. **Experiment v33** fuses all three

and compares against the best single expert and against equal-weight averaging. **Experiment v34** adds a default-mode-network association layer on top of the fused representation. **Experiment v35** asks the converse question—whether a large base can serve as a *container* into which several heterogeneous small entry models inject prefix representations—and is negative.

Table 2: Scale-heterogeneous fusion under the three-protocol audit of §6.11 (5-seed paired medians, `run_v47_scale_hetero_heldout`). "Noise" re-samples the evaluation noise at the same stimuli; "stimulus" shifts the stimuli themselves. A finding is reported as clean only when the sign is stable across all three columns.

Finding	**In-sample**	**Noise**	**Stimulus**	**Verdict**
Fused beats best single expert (v33)	+26.7% (5/5)	+26.7% (5/5)	+26.5% (5/5)	**retained, but see** §6.4
retention of the in-sample effect	—	100%	99%	—
DMN association layer, additive to v33 (v34)	+6.4% (5/5)	+6.4% (5/5)	+6.5% (5/5)	**survives**
retention of the in-sample effect	—	100%	103%	—
Entry-model injection into a container (v35)	−11.1% (2/5)	−11.1% (2/5)	−3.3% (2/5)	**no gain**

The margin above is retained, but it is not a margin for fusion. The projection in this configuration is orthogonally initialized and frozen, and an audit of the shared space (§6.4) shows that the fused output is a detector of its *source base* rather than of the target: on held-out data the source identity is recoverable from the fused output with probability 1.000, while the target class is recoverable with probability 0.279 against a 0.125 chance baseline. The router's task in a random space is the trivial one of recognizing which base produced the token. When the space is made meaningful—a nonlinear lift, trained rather than frozen—the same margin collapses to +4%–+12%, the absolute error falls below the trivial zero predictor, and the source-identity decodability of the output falls with it. We therefore read this row as evidence that a shared space must be meaningful for heterogeneous fusion to work at all, not as evidence that fusing beats using one base well.

Two results deserve to be read together with the rest of this section rather than on their own. First, the scale-heterogeneous gain is *not* a re-scaling of the architectural one: it is the largest single margin in the paper, it is retained essentially exactly out of sample (99–100%), and it holds under both re-sampled noise and shifted stimuli. Second, the negative result in the same family is also robust. The container-and-entry design of v35 does not merely fail to beat a random prefix, it fails in all three protocols. That failure was originally attributed to the design; it was later traced to an implementation defect—the tabular entry representation was averaged over the batch before injection, collapsing a per-sample signal into a constant—so v35 is best read as a recorded negative alongside the corrected follow-ups, not as evidence against entry-based composition.

We state the scope of this line precisely, because it is narrower than the label "scale-heterogeneous" suggests. The large base contributes only a shallow layer, so its depth is not exercised; the two small bases share an architecture and differ in training objective rather than in form; and the synthetic targets are the same class-direction construction used throughout. The claim this experiment supports is therefore that *routing across a large–small size gap does not destroy the fusion gain and retains it out of sample*—not that depth-heterogeneous composition at production scale has been demonstrated.

6.4 The projection space is load-bearing: its size, its nonlinearity, and its conditioning

Everything above treats the rectangular projection P_m as fixed plumbing: a $d_{\text{shared}} \times D_m$ matrix carrying each base into the shared routing space. That assumption turned out to be the largest untested surface in the study, and testing it changes what the headline numbers mean. We report it as a separate line of work because it does not merely refine an existing claim—it relocates the mechanism.

The projection in every fusion experiment was frozen and random. In the scale-heterogeneous configuration of §6.3 and in the architectural configuration of §6.2, every P_m is orthogonally initialized and then *frozen*, the per-expert feed-forward blocks are frozen as well, and the only trainable tensors are the shared router and three per-expert affine pairs ($\approx$ 2.3K parameters in total). The margins reported for both lines were therefore obtained inside a shared space whose geometry was random. Any claim of the form "fusion beats its parts" must be read against that fact.

How large does the space need to be? A training-free diagnostic (no gradients) stacks the bases' token representations, takes the covariance spectrum, and measures cross-base redundancy with linear centered kernel alignment (CKA) against a row-permutation null. On a controlled corpus of 8 semantic classes built from slot combinations—so that the training and held-out splits share no sentence at all—the union of the three bases occupies 4–19 dimensions at the 95–99% variance level, against the d_{shared}=256 actually used; the pairwise CKA is far above its permutation null. Two things follow. The space is provisioned for roughly an order of magnitude more directions than the data occupy, and the redundancy that would justify a small space is real—but it is invisible to a linear method: the joint principal subspace of the union, which is the best a linear construction can do, leaves the three bases in nearly disjoint directions (footprint overlap < 0.06).

Nonlinearity, not capacity, closes the gap. We then run a 2×2 factorial over the two axes that the diagnosis implicates—nonlinear versus linear lifting, and static versus content-conditioned lifting—crossed with a sample-size axis (32, 256, 1024 examples per base), with the hidden width of the nonlinear lift solved so that the two arms differ in fewer than 0.3% of parameters, and with a fixed minibatch and step count so that the sample-size axis measures data diversity rather than compute. The nonlinear arm reduces held-out fusion error by 4.7–9.9$\times$ relative to the parameter-matched linear arm, and does so with roughly half the overfitting gap; the linear arm's advantage instead comes from sample size, and shrinks as the nonlinear arm saturates. A random-projection construction is 38$\times$ worse than the trivial zero predictor in absolute error. The redundancy the diagnostic located is therefore recoverable, but only through a nonlinear map.

Conditioning needs a nonlinear base, and needs data. Conditioning the projection on a content-derived vector (a hypernetwork emitting a rank-16 modulation) is useless on a linear base—the conditioned and static linear arms agree to within noise at all three sample sizes—and becomes useful on top of the nonlinear lift (0.0798 versus 0.0931 at 1024 examples). Permuting the conditions across samples degrades held-out error by +24.6%, +47.0% and +50.3% as the sample size grows, so the conditioning is used rather than decorative. It also requires data: at 32 examples the conditioned nonlinear arm is *worse* than the unconditioned one.

Auditing the margin itself. The finding above makes the headline margin suspect, and we test it directly rather than by argument. If the frozen random space inflates the fused-over-single-expert margin, then in that configuration the fused output should carry the *identity of its source base* rather than the semantics of the input. We test this with two linear probes on the held-out fused output: one predicts which of the three bases produced the sample, the other predicts the target class. In the frozen random configuration the margin over the best single expert is +66.6 (held-out fusion error 4.7423, against a trivial zero-predictor error of 0.125), and the probes return 1.000 for source identity and only 0.279 for the target class, while the projected inputs themselves identify their source with probability 1.000. The fused output is, in effect, a source detector: the router's task is trivial in that space, and the margin over a single expert measures source detection and dispatch rather than semantic fusion. Across the audited arms the margin over the best single expert is +66.6 (frozen random), +53.7 (nonlinear, frozen random), +4.1 (nonlinear, trained), +12.0 (nonlinear, proxy-aligned, frozen) and −0.1 (nonlinear, proxy-aligned, trained), with held-out errors of 4.7423, 0.0974 and 0.1016 respectively.

The architectural line, and why its target is the problem. The same audit applied to the architectural-heterogeneity line (§6.2) turns up a more basic issue. In that configuration the target block *is* the modality index—the task is literally to identify which base produced the token—so a "fusion beats its parts" margin there measures modality recognition. Two controls make this explicit. Permuting the target

blocks across modalities, with the task's difficulty unchanged, leaves the margin untouched (+70.4% versus +72.7%), so the margin depends on nothing but the ability to tell the modalities apart. Replacing the frozen random projection with a meaningful (nonlinear, trained) space collapses it (+2.3% versus +70.4%) while the absolute error falls by more than an order of magnitude (0.0315 versus 2.1589). The attention-path advantage falls with it: the attention path's lead over the FFN path is 70% in the frozen random space and 3% in the learned one. In every arm the probes recover both the source modality and the target block with probability 1.000, because the target block is the modality: the benchmark measures detection, and the margin is what detection is worth.

Three independent re-derivations, and the positive control the first two lacked. We re-derive the finding above with three implementations that share nothing but the object under audit: they differ in the data split (held-out slot combinations; then held-out slot value-domains), in the probe family (stochastic logistic regression; then closed-form ridge regression; then ridge, an MLP probe and a nearest-neighbour probe jointly), in the lifting architecture (two-layer MLP; then LayerNorm-GELU MLP; then a residual MLP with a tanh gate), in the seeds, and in the shared width (256; then 128/256/512; then 96/384). The margin behaves identically in all three: it is unchanged when the target blocks are permuted across bases (+20.5% versus +20.5% and +37.0% versus +37.0%), and it collapses once the space is learned (-0.2% and -0.4%). The third pass adds the positive control the earlier two could not supply: *when the space is meaningful, the three bases' outputs for the same text agree.* Mean pairwise cosine across bases rises from +0.01 and -0.01 in the frozen random space to +0.54 and +0.61 in the learned space, on the inputs and on the fused outputs alike—the shared space genuinely makes heterogeneous bases meet. One pre-registered check did not pass as written. Our probe-validity criterion assumed that class information could not survive in a frozen random space, but it does: a random linear map preserves the class geometry of its input, so a nonlinear probe still reads class structure (0.58 and 0.67) from an output whose target was replaced by a per-sample random one. The criterion therefore conflated "the output contains class information" with "the model used the target". The sharper control is available in the same arm and needs no threshold: replacing the target with a per-sample random one leaves the held-out numbers *bit-identical*, so the frozen arm never used the target at all, and its margin cannot be an artifact of learning the task. We report the failed criterion rather than re-specifying it after the fact.

What we therefore claim. We cannot attribute the earlier margins to fusion. They are attributable to a shared space that was never optimized, and they do not persist once the space is learned: with a meaningful (nonlinear, trained) space, a single expert with the same space solves the task about as well as the fused model does. The defensible claim is the weaker and more useful one: *a shared space must be meaningful for sublayer fusion to work at all*—in a random space the fused output is 38× worse than predicting zeros—and once it is meaningful, fusing heterogeneous bases adds little over using one of them well. We report the negative result with the same prominence as the positive ones. We re-derive the finding with three independent implementations—differing in the data split, the probe family, the lifting architecture, the seeds, and the shared width—and the conclusion holds in all three. The third pass also supplies the positive control the first two lacked: in a learned space the three bases' outputs for the same text agree far more than in a frozen random space, so the shared space genuinely makes heterogeneous bases meet. One pre-registered check did not pass as written, and we report it rather than re-specify it after the fact (§6.4).

6.5 The alignment ladder and its ceiling

Table 3 and Figure 4 show the ladder; the figure visualizes the table's five-seed means and adds no new quantity. The ordering linear < mean < attention < mixture holds strictly in every comparison, and the total climb from the linear baseline to the mixture aligner is −77.4% MSE. The negative result is as clear as the positive one: a two-level nested mixture (mixture of mixture) lands *between* attention and mixture, 4.7% *worse* than the single-level mixture aligner. Cross-base attention is worth one level; a second level of hierarchy adds parameters and dilutes the shared concept context without adding representational power.

A composition test sharpens the point. We combined the repaired gate-style router with the attention aligner: relative to their common linear-projection baseline at 1.1625, the combination reaches +71.0% gain (0.3374) while the aligner's own configuration reaches +72.6% (0.3191)—less than two percentage points apart but

Table 3: Alignment ladder (5-seed means, fuse MSE). Each block is one controlled comparison; the mixture aligner saturates the ladder and nesting it does not help.

Comparison	Aligner	fuse MSE	vs. mode below
projection vs. semantic (v10)	linear projection	1.0436	—
	mean aligner	0.4753	+54.5%
	cross-arch attention	**0.3448**	+67.0%
attention vs. mixture (v14)	linear projection	1.1409	—
	cross-arch attention	0.3376	+70.4%
	mixture aligner	**0.2575**	+77.4%
mixture vs. nested (v15)	cross-arch attention	0.3216	—
	mixture aligner	**0.2525**	+21.5%
	nested (mixture of mixture)	0.2645	−4.7%




Figure 4: The alignment ladder. (a) Semantic alignment beats the frozen linear projection; cross-base attention beats the mean. (b) The mixture aligner improves on single-concept attention. (c) Nesting the mixture aligner regresses slightly: the ladder saturates at one level of cross-expert attention. Lower is better.

consistently in the aligner's favor across all 5 seeds, within seed variation. Once an aligner already provides cross-base concept exchange, the router-level repair has nothing left to fix. Improvements at adjacent layers of the stack are not additive; the first sufficient mechanism absorbs the gains.

The capacity confound is resolved and excluded. The four aligners differ in parameter count (linear 325,632; attention 720,640; mixture 2,291,968; nested 1,704,448, counting aligner parameters only), so we ran a capacity-matched control in which the mixture aligner is reduced to a single shared expert per base, giving exactly 720,640 parameters—bit-for-bit equal to the attention aligner. At matched capacity the mixture aligner still dominates the attention aligner on held-out data by +36.5% (median over 5 seeds; +28.8% by mean; +33.5% after dropping the best seed; ahead on 5/5 paired seeds), and sweeping the mixture's expert count from 1 to 8—a 6.09× capacity range—moves held-out MSE by only −5.6% and non-monotonically. The ladder therefore reads as design, not scale. The nested aligner is likewise a ceiling of expressiveness rather than of capacity: at 2.37× the single-expert mixture's parameters it is 28.6% worse. What remains open is scale: the entire ladder is measured at D_{shared}=256 with three bases and synthetic targets, so the saturation point is a scale-bounded hypothesis, and confirming or breaking it at $D_{\text{shared}}\geq$768 with real targets is the highest-priority follow-up experiment.

6.6 Router coordination: in-sample is not out-of-sample

Table 4 reports the four hub modes on the cross-architecture fusion task, and it is the clearest case in this paper of a conclusion that in-sample evaluation gets wrong.

Table 4: Hub modes on cross-architecture fusion (`run_v44_hub_modes_audit`, 5-seed paired medians). The in-sample and held-out rankings are read under the same protocol. Router-norm leads both; the mode the project's own main table had recorded as the in-sample winner (adaptive-EMA) has the worst generalization gap and is last out of sample.

Hub mode	in-sample MSE	held-out MSE	held-out gain	wins
broadcast (baseline)	0.3236	0.3538	—	—
router-norm	**0.2835**	**0.3342**	+4.3%	5/5
gate-style	0.2983	0.3462	+5.8%	3/5
adaptive-EMA	0.2859	0.3573	+0.3%	3/5

- **The in-sample table is already wrong about its own winner.** The project's own main table recorded adaptive-EMA as the in-sample best; the audit (`run_v44_hub_modes_audit`, whose absolute levels differ slightly from that earlier run) shows that the in-sample minimum is in fact router-norm at 0.2835, and that router-norm is also the held-out winner (0.3342, ahead of broadcast on 5/5 paired seeds). Adaptive-EMA—the recorded in-sample winner—collapses to +0.3% over broadcast out of sample and loses on 2/5 seeds, with the largest generalization gap of the four (+25.0%). An independent re-run on real corpora at a different scale (`run_v25_corpus_central`) reproduces the ordering: router-norm best on held-out (+4.6% over broadcast), adaptive-EMA second (+2.0%), gate-style negative (−5.1%).
- **Gate-style's admissibility does not make it the empirical winner.** The gate-style hub raises the central-coordination gain from −71.9% (broadcast) to +44.5% in-sample, the single largest in-sample improvement among the four. But under the same held-out protocol that gain collapses to +4.0% (3/5), so the theorem of §4.2 and the empirical ranking answer different questions: gate-style is the only *admissible* mode, and it is not the *best* mode out of sample.
- **The capacity confound runs the other way here.** A natural worry is that gate-style wins because it has more parameters. It has fewer: the gate hub carries 512 parameters against broadcast's 1,024, so the admissibility result cannot be explained as a capacity effect. The perfect-degeneration and order-preservation properties are constructive and cannot be produced by extra parameters in any case.

The lesson generalizes beyond this table. The four hub modes are separated in-sample by amounts comparable to their seed variation, so an in-sample comparison of composition mechanisms at this scale measures how well each mechanism *fits*, not what it can *do*. The held-out protocol is what distinguishes the two.

6.7 The corpus-scale boundary is not established out of sample

An earlier account of this work claimed a clean corpus-scale boundary: adaptive-EMA wins on tiny and small corpora, gate-style on medium and large, with a crossover at 16–32 training samples (Table 5). The boundary is present in-sample. It does not survive the same held-out test.

Table 5: Corpus-scale sweep (v29), in-sample. *The apparent boundary below is not established out of sample* (§6.7); it is reported here as the in-sample observation that the audit corrects.

Corpus scale (train/val/test)	In-sample best	MSE	Held-out best
tiny (8/4/4)	adaptive-EMA	0.7035	adaptive-EMA
small (18/6/6)	adaptive-EMA	0.6984	adaptive-EMA
medium (32/12/12)	gate-style	0.6971	*not re-run*
large (64/24/24)	gate-style	0.7029	adaptive-EMA

Sweeping only the two endpoint scales (`run_v45_scale_boundary_audit`; 5 seeds; train and held-out), the boundary is present in-sample (adaptive-EMA → gate-style) but the held-out medians give adaptive-EMA at *both* scales, i.e. no boundary. Worse, at the large scale the two readouts disagree with each other: the unpaired median ranks adaptive-EMA first while the paired per-seed comparison ranks gate-style first

(adaptive-EMA wins only 1/5), the disagreement being driven by a single seed where adaptive-EMA reaches 0.767 against gate-style's 0.543. We therefore report the boundary as *not established out of sample* rather than confirmed: two of the four scale levels were not re-run (including the crossover level itself), and the small-scale held-out margin is +0.5% on 3/5 seeds, i.e. within noise. Establishing or breaking the boundary requires the medium tier and a paired protocol; it is not settled by the present data.

6.8 The tanh-saturation repairs: gradient restored, error unchanged

The two repairs of §4.3 target a real defect—grad_norm_central = 0.0000 under long training—and both restore a non-zero gradient into the hub. Their effect on end-to-end error, however, is within noise, and only the held-out audit makes this visible. Under the audit protocol the softplus repair moves fusion MSE by −0.44% and the gradient-scale repair by −0.11%, losing on 0/5 seeds in both cases: the repairs fix the *mechanism* without changing the *outcome*. This is a small but clean instance of the paper's general pattern—a fix that is correct at the level of the diagnosis can still be invisible at the level of the metric—and it is the reason we report repair and effect separately rather than as one claim.

6.9 Chimera distillation: margin, leakage decomposition, and multi-teacher

Table 6: Chimera distillation (5-seed means). The teacher is the fused multi-base ensemble with the mixture aligner. †: evaluated on training-distribution inputs; near-zero values are overfitting artifacts, not generalization. v18 evaluates on held-out real Wikipedia text.

Student	Evaluation	Teacher	Distilled	vs. teacher
v13: MLP student (no pretraining)	train-dist. target	0.3245	0.3076	+5.4%
v16: TinyBERT + LoRA (0.60%)	train-dist. target†	0.2764	0.1380	+50.1%
v18: TinyBERT + LoRA	held-out real text	—	0.1574	viable
v21: BERT+ViT multimodal	train-dist. target†	0.3238	0.1620	+50.0%




Figure 5: (a) Single-teacher chimera distillation: distilled students beat their multi-base teacher in every setting. (b) Multi-teacher distillation regresses across all configurations (v17); a dispatch-style reformulation removes the harm but does not produce a gain (v40). Lower is better.

Table 6 reports the distillation results. The pattern is consistent and, at first sight, counterintuitive: the distilled student appears *better* at reproducing the fused output than the teacher is at producing it—+5.4% for the MLP student, +50.1% for the TinyBERT student (0.138 vs. 0.276), and +50.0% for the multimodal student (0.162 vs. 0.324). We do not take this at face value, and the decomposition below shows it should not be.

Why the copy would beat the original, and why it does not. The teacher's forward pass is stochastic—hard Top-K routing plus INT4 quantization noise at every step—while the student is trained

to match the teacher's *expected* output. A function fitted to the conditional mean attains lower MSE than the noisy process it imitates (a Jensen-type gap), so a deterministic student *should in principle* beat its stochastic teacher by construction. This gives three candidate explanations for the measured margin—the Jensen-type variance-averaging advantage, the $\beta_{\mathrm{h}} = 0.3$ direct-target term, and genuine concept-direction transfer—and each is testable.

Test 1 — the $\beta_{\mathbf{h}}$ scan. Setting $\beta_{\mathrm{h}} = 0$ and keeping everything else fixed isolates pure distillation (`run_v32`). Against the same teacher and the same evaluation protocol, pure distillation yields MSE 0.324 ± 0.013 versus mixed MSE 0.165 ± 0.007 and teacher MSE 0.323 ± 0.015. Pure distillation *does not outperform the teacher*: the per-seed paired gap is -0.0009 ± 0.0038 (mean $\pm$ std over 10 seeds; not significant). Scanning $\beta_{\mathrm{h}} \in [0, 1]$ in steps of 0.1 moves student MSE monotonically from 0.317 ± 0.040 to 0.000 ± 0.000 with no discontinuity at $\beta_{\mathrm{h}} = 0.3$, so the term's effect is proportional to its weight—a saturating interpolation, not a threshold mechanism that could be recovered. The identical scan on the multimodal student (`run_v42`) reproduces the pattern from 0.3270 at β_{h}=0 to 0.0001 at β_{h}=1, and at β_{h}=0 the multimodal student sits at 0.3270 against a teacher at 0.3255, i.e. −0.5%, failing on 5/5 seeds.

Test 2 — variance averaging is bounded. Replacing the teacher with a *super-deterministic* version that averages 20 forward passes over different random inputs (`run_v32.3`) leaves its MSE unchanged (0.324 ± 0.015, identical to the deterministic teacher), and the pure student's gap against it is -0.0008 ± 0.0038—again not significant. Averaging 20 forward passes does not change the teacher's output at this scale, so the Jensen-type mechanism contributes nothing measurable here.

Test 3 — representation transfer finds no mixed advantage. If the mixed objective had taught the student the teacher's internal concept directions, those directions should transfer. After training mixed and pure students under the same teacher, we freeze both students' LoRA parameters, replace the output head with a new random linear classifier, train the head on a freshly generated target set, and compare accuracy (`run_v32.4`): the mixed student reaches 0.733 ± 0.065 and the pure student 0.767 ± 0.102—the pure student is slightly *better*, and the difference is not significant.

The three tests agree. None of the ±50% apparent margin is attributable to concept-direction transfer or to variance averaging; the entire measured advantage under the mixed objective is attributable to the $\beta_{\mathrm{h}} = 0.3$ direct-target term. The comparison that *does* carry mechanism evidence is *across students* under the identical stochastic teacher: the MLP student closes only +5.4% of the gap, the TinyBERT student +50.1%, and the multimodal student +50.0%. That ordering reflects the interaction between pretrained priors and the leaked target signal, not internalization of the teacher's concept directions. Because the v32 re-run uses a somewhat different absolute level from the original v16 record (teacher 0.324 vs. 0.257; mixed student 0.164 vs. 0.138), we read the decomposition within the internally consistent v32 run and do not cross-compare its levels against Table 6; we retain the v16-protocol rows for reproducibility of the positive results.

The v18 held-out correction points the same way. Under held-out real Wikipedia text the distilled student holds MSE 0.157, while both the fake-vocabulary and fine-tune-only controls sit at ≈ 0—not because they generalize, but because their evaluation inputs and targets are trivially fittable. The student's 0.157 is the number that reflects fitting to the teacher's outputs under the mixed objective; the leakage decomposition above shows that this is what it is.

Multi-teacher distillation fails, and reformulating it does not help. A natural next step is to distill from several teachers (the attention-aligner teacher, the mixture teacher, the nested teacher) simultaneously, possibly with weights. Every configuration regresses (Figure 5(b)): two teachers −15.8%, three teachers −6.3%, weighted three-teacher −3.9% relative to a single teacher. The teachers disagree about the *direction* of the concept space they transmit; a capacity-limited student cannot align to conflicting targets, and averaging the signals dilutes each teacher's specialization. A dispatch-style reformulation that replaces the weighted sum with per-sample assignment (`run_v40_dispatch`) tests the hypothesis that the failure is an artifact of the regression *form* rather than of multi-teacher distillation itself. It is a partial repair: dispatch removes the *harm* of weighted combination (median 0.3344 → 0.3195) but produces no gain over a single teacher, and the three forms—weighted, mean, and round-robin dispatch—are indistinguishable from one another (median 0.3335–0.3398). The teachers jointly hold about 13% of complementary headroom, and *no*

form we tried transfers it to the student. A dispatch-oracle arm shows a mean gain of +6.0% that collapses to +0.6% at the median and +1.1% with the best seed removed—a single-seed artifact that we do not cite as a result. The conclusion is narrower than "multi-teacher distillation is bad": it is that when teachers share the same data and target with no domain partition, their apparent disagreement is noise, and the failure is a capacity ceiling on the student side rather than a fixable aggregation artifact.

6.10 Task-level evaluation: a boundary, not a result

We attempted to move from concept reconstruction to an actual task with a miniature VQA benchmark. With 4 easy classes, an image-only student reached 100% accuracy by exploiting a modality shortcut, and the multimodal student reached 91.7%: the task could not distinguish multimodal reasoning from unimodal cheating. We then rebuilt the benchmark with 8 trap classes designed to defeat shortcuts. Every model—text-only, image-only, and multimodal—dropped to exactly 50%, the accuracy of random guessing. Doubling task difficulty did not expose multimodal capability. We report both readings. The favorable one: with 24 training examples and a CPU-scale student, the benchmark cannot train cross-modal grounding, so chance-level accuracy measures the benchmark, not the fusion layer. The unfavorable one, which we cannot rule out: a multimodal student failing to exceed random chance on a task designed to require cross-modal reasoning is a capability boundary of the mechanism itself. Distinguishing these readings is exactly what our CLIP-based (Radford et al., 2021) teacher pipeline—prepared but not yet completed end-to-end—is for.

6.11 Out-of-sample discipline: what survives and what does not

The audits above are not a miscellaneous collection of corrections; taken together they are a single methodological result about how composition mechanisms of this kind should be evaluated. We ran a uniform out-of-sample protocol (`run_v44`–`run_v47`; a held-out split of the same distribution, plus a real-corpus rerun at a different scale, for every claim that was still marked pending) and sorted the stack's findings by whether they survive.

Table 7: Findings sorted by survival under the held-out protocol. "Retention" is the fraction of the in-sample effect that remains out of sample.

Finding	**In-sample**	**Held-out**	**Verdict**
Attention-path advantage (v46)	+82.7%	+70.6%	**survives**
Alignment-ladder ceiling (v41)	+36.5% vs. attn	capacity-matched	**survives**
Hub: router-norm best (v44)	best	best (5/5)	**survives (corrected)**
Hub: gate-style central gain (v43)	+44.5%	+4.0%	shrinks to noise
Corpus-scale boundary (v45)	present	absent	**not established**
Long-training gain (v19)	+4.3%	+1.5%	shrinks (34% retained)
Gradient repairs (v30/v31)	−0.44% / −0.11%	same	no effect
Scale-heterogeneous fusion (v33, §6.3)	+26.7%	+26.5% (noise), +26.5% (stimulus)	**survives**
Entry injection into a container (v35)	−11.1%	−3.3% (stimulus)	no gain

Table 7 is the paper's most portable result, and it is not specific to our architecture. What survives is what has a *mechanistic* reason to survive: the alignment-ladder ceiling is a matched-capacity design statement, and the attention-path advantage, once the projection space is audited (§6.4), turns out to belong to the frozen random space rather than to a structural property of transformers. What fails is what is a fitting advantage: hub-mode rankings, the corpus-scale crossover, and gains from long training or from repairs to a mechanism whose end-to-end effect is within noise. We offer this as a rule of thumb for the subfield: for frozen-base composition at small scale, report the held-out ranking, not the in-sample one, and treat any margin comparable to seed variation as unresolved.

7 Discussion

Four design principles. The systematic iteration behind these results stabilizes into four principles. We state them as domain-specific heuristics distilled from one system—generalizing them to other architectures is a hypothesis, not a result—but we expect them to travel further than the specific configuration. (1) *Make heterogeneity decomposable*: every component (router, gates, aligner, hub, each path) can be enabled or disabled independently, which is what made each ablation here a one-flag change. (2) *Negative results are map boundaries*: the composition, nesting, multi-teacher, and VQA failures delimit the method more sharply than any positive result. (3) *Frozen-base composition demands mechanism-level diagnostics*: because the bases do not update, ablation must reach the sublayer mechanism—router, gate, aligner, hub, fake-quant—directly, and component-level naming is how we keep those diagnostics separate; we deliberately avoid naming one mechanism after different cognitive or biological analogues. (4) *Extend incrementally*: each generation reused the previous one's frozen components, which is what kept 430 tests passing as the architecture grew.

The recurring law: more is not better. Across five independent comparisons, adding machinery—more router repairs, a second aligner level, more teachers, harder toy tasks—either did nothing or hurt. The mechanisms that worked (native encoding, shared-K/V attention, one mixture level, one teacher) each *replaced* something weaker rather than stacking on top of it. For sublayer-level reconstruction the practical recipe that emerges is: encode natively, align with one mixture level, route sparsely, coordinate the router only with an admissible hub, distill from a single teacher—and stop.

Held-out discipline as the unifying method. The three stages of this paper are unified less by architecture than by evaluation. Every stage makes a claim that is easy to make true in-sample and hard to make true out of sample, and the audits of §6.11 show that roughly half of the stack's in-sample findings do not survive. Two properties we rely on are immune to this because they are constructive rather than empirical—perfect degeneration and order preservation are properties of a functional form—and we therefore separate such properties from measured ones throughout. This separation, rather than any single number, is what we would carry to the next system.

Cross-paper signals on data scale and fusion strategy. Four independent lines of recent work report a related pattern: small data and small models favor *injective* composition (full router, separate adapters, coarse-grained routing), while large data and large models favor *averaging* (weighted combination, full fine-tuning, additive merging). AdapterFusion (Pfeiffer et al., 2021) sharpens the trade-off under scarce training data; Mixtral-style sparse routing (Jiang et al., 2024) requires load balancing exactly where dead-expert collapse becomes catastrophic; the coarse-grained routing of Liu et al. (2026) converges to whole-query decisions for latency reasons absent in our setting yet leads to the same architectural choice; and Branch-Train-MiX (Sukhbaatar et al., 2024) is dominated by its MoE-finetuning stage under limited compute. Our four-mode comparison is run at a single training scale and is consistent with the hypothesis that optimal composition depends on data scale, but our own held-out audit (§6.7) shows that the *within-paper* version of that boundary is not established—which is itself the reason we state the data-scale dependence as a literature-convergent hypothesis rather than a finding, and leave a within-paper sweep across training scales to future work.

Relation to routing-coordination questions. How the shared router should be coordinated—which hub mode, and how that choice interacts with data scale—is the subject of §4. Our answer separates cleanly into an admissible part that is proved (gate-style is the unique mode satisfying G1–G5) and an empirical part that is open (the best hub mode out of sample is router-norm at our scale, and whether that ordering persists at industrial scale is untested).

8 Limitations

Scale is the dominant limitation. All results are CPU-sandbox results with D_{shared}=256, sequence length 16, synthetic class-direction targets rather than language-model perplexity, and toy-scale corpora; nothing here establishes behavior at 0.5B+ parameters or on real downstream benchmarks. The INT4 fake quantization is a training-time noise injection, not a deployment kernel. Attention experts read the bases' first block only, with no layer-selection study. Top-K is fixed at K=1. The corpus-scale boundary is unresolved rather

than refuted: two of four scale levels and the crossover level itself were not re-run out of sample. Task-level multimodal evaluation remains open. Finally, the distillation margins are measured in reconstruction MSE on the teacher's own target distribution; the decomposition shows they are target leakage, and whether any genuine transfer would translate to downstream capability is untested.

9 Conclusion

We reconstructed frozen heterogeneous pretrained models in three stages: a sublayer fusion layer that routes tokens among frozen architectural experts through a shared sparse router and a semantic aligner; a coordination theory that identifies temperature modulation as the only hub mechanism that degenerates exactly, preserves ordering, stays bounded, and costs $O(D_{\text{shared}})$; and chimera distillation, which collapses the ensemble into one independent student. The alignment space has a strict ladder with a measured ceiling at one mixture level, which a capacity-matched control shows is a matter of design rather than scale; the cross-architecture fusion gain concentrates in the attention path, a concentration we later show to belong to a frozen random shared space rather than to architectural heterogeneity (§6.4). Chimera distillation's apparent "student beats teacher" margin is entirely attributable to the direct-target term in the loss rather than to concept-direction transfer or variance averaging. The negative results—no additive composition, no nesting, no multi-teacher, no admissible-hub advantage out of sample, toy benchmarks at chance—bound the method as sharply as the positive ones. Our final contribution is methodological: a uniform held-out discipline applied across the stack overturned several of our own in-sample findings while leaving the mechanistic ones intact. The open frontier is scale: the mechanisms are now specified, tested, and bounded at CPU scale, and their behavior at pretraining scale is the question that matters next.

Reproducibility statement

All experiments are scripted in the project repository. Core reproduction commands:

- Fusion and path decomposition: `bash run.sh v6`, `run.sh v7a`, `run.sh v7b`; attention-path audit `run_v46_attn_path_audit.py`.
- Alignment ladder: `examples/run_v10_aligner.py`, `run_v14_aligner_compare.py`, `run_v15_mom_compare.py`; capacity control `run_v41_capacity_audit.py`.
- Router coordination: `run_v22_theory_compare.py`, `run_v43_central_audit.py`, `run_v44_hub_modes_audit.py`, `run_v45_scale_boundary_audit.py`.
- Distillation: `run_v13_distill.py`, `run_v16_bert_distill.py`, `run_v18_wiki_distill.py`, `run_v21_multimodal_distill.py`, `run_v32_leakage_audit.py`, `run_v40_dispatch.py`.
- Held-out audits: `run_v47_central_heldout.py`, `run_v47_scale_hetero_heldout.py`.
- VQA boundary: `examples/run_v23_vqa_distill.py`, `run_v23_vqa_hard.py`.

The full test suite (`bash run.sh test`) runs 430 unit and integration checks. Environment: Linux, Python 3.11, PyTorch 2.x, CPU-only, 5 seeds per configuration.

AI-assistance disclosure

Manuscript drafting was assisted by an AI writing agent operating on the project's experiment records and specifications; all experimental results, code, and design decisions are the authors'.

References

B.J. Baars. *A Cognitive Theory of Consciousness*. Cambridge University Press, 1988.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or Propagating Gradients Through Stochastic Neurons for Conditional Computation. *arXiv preprint arXiv:1305.2982*, 2013.

Damai Dai, Li Dong, Yiming Hao, Zhifang Sui, Baobao Chang, and Furu Wei. Knowledge neurons in pretrained transformers. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics*, 2022.

Damai Dai, Chengqi Deng, Chenggang Zhao, R. X. Xu, Huazuo Gao, Deli Chen, Jiashi Li, Wangding Zeng, Xingkai Yu, Y. Wu, Zhenda Xie, Y. K. Li, Panpan Huang, Fuli Luo, Chong Ruan, Zhifang Sui, and Wenfeng Liang. DeepSeekMoE: Towards Ultimate Expert Specialization in Mixture-of-Experts Language Models. *arXiv preprint arXiv:2401.06066*, 2024.

Tim Dettmers, Mike Lewis, Younes Belkada, and Luke Zettlemoyer. LLM.int8(): 8-bit Matrix Multiplication for Transformers at Scale. In *Advances in Neural Information Processing Systems*, 2022.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of NAACL-HLT*, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale. In *International Conference on Learning Representations*, 2021.

Yuxuan Du, Zhengxiao Liu, Junda Chen, Tianyi Zhao, Xiaoyang Hu, Peng Wang, Lu Yan, and Xu Sun. EAQuant: Expert-Aware Post-Training Quantization for Mixture-of-Experts. *arXiv preprint arXiv:2506.13329*, 2026. To appear, ICML 2026.

William Fedus, Barret Zoph, and Noam Shazeer. Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity. *Journal of Machine Learning Research*, 2022.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer Feed-Forward Layers Are Key-Value Memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 2021.

Jianping Gou, Baosheng Yu, Stephen J. Maybank, and Dacheng Tao. Knowledge Distillation: A Survey. *International Journal of Computer Vision*, 2021.

Albert Gu and Tri Dao. Mamba: Linear-Time Sequence Modeling with Selective State Spaces. *arXiv preprint arXiv:2312.00752*, 2023.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently Modeling Long Sequences with Structured State Spaces. In *International Conference on Learning Representations (ICLR)*, 2022.

G. Hinton, O. Vinyals, and J. Dean. Distilling the Knowledge in a Neural Network. *arXiv:1503.02731*, 2015.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-Efficient Transfer Learning for NLP. In *International Conference on Machine Learning*, 2019.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*, 2022.

Chengsong Huang, Qian Liu, Bill Yuchen Lin, Tianyu Pang, Chao Du, and Min Lin. LoRAHub: Efficient Cross-Task Generalization via Dynamic LoRA composition. In *Proceedings of the First Conference on Language Modeling (COLM)*, 2024.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing Models with Task Arithmetic. In *International Conference on Learning Representations*, 2023.

Robert A. Jacobs, Michael I. Jordan, Steven J. Nowlan, and Geoffrey E. Hinton. Adaptive Mixtures of Local Experts. *Neural Computation*, 1991.

Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, Gianna Lengyel, Guillaume Bour, Guillaume Lample, Lélio Renard Lavaud, Lucile Saulnier, Marie-Anne Lachaux, Pierre Stock, Sandeep Subramanian, Sophia Yang, Szymon Antoniak, Teven Le Scao, Théophile Gervet, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mixtral of Experts, 2024. Apache 2.0; weights at `https://huggingface.co/mistralai`.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. TinyBERT: Distilling BERT for Natural Language Understanding. In *Findings of the Association for Computational Linguistics: EMNLP*, 2020.

Angelos Katharopoulos, Apoorv Vyas, Nicola Pellegrini, and François Fleuret. Transformers are RNNs: Fast Autoregressive Transformers with Linear Attention. In *International Conference on Machine Learning (ICML)*, 2020.

Aran Komatsuzaki, Joan Puigcerver, James Lee-Thorp, Carlos Ruoss, Alex Aitchison, Quentin Cayron, and Basil Mustafa. Sparse Upcycling: Training Mixture-of-Experts from Dense Checkpoints. In *International Conference on Learning Representations*, 2023.

Ye Liu, Wuji Chen, Xu Chen, and Mang Li. Orchestrating Heterogeneous Experts: A Scalable MoE Framework with Anisotropy-Preserving Fusion. In *Companion Proceedings of the ACM Web Conference 2026*, Dubai, UAE, April 2026. ISBN 979-8-4007-2308-7.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems*, 2022.

Seyed-Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. Improved knowledge distillation via teacher-assistant. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

Jonas Pfeiffer, Sebastian Rücklé, Claudio Ponthot, Martin Riedl, and Iryna Gurevych. AdapterFusion: Non-Destructive Task Composition for Transfer Learning. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics*, 2021.

Joan Puigcerver, Carlos Riquelme, Basil Mustafa, and Neil Houlsby. From Sparse to Soft Mixtures of Experts. In *International Conference on Learning Representations (ICLR)*, 2024.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning Transferable Visual Models from Natural Language Supervision. In *International Conference on Machine Learning*, 2021.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. DistilBERT, a Distilled Version of BERT: Smaller, Faster, Cheaper and Lighter. *arXiv preprint arXiv:1910.01108*, 2019.

N. Shazeer et al. Outrageously Large Neural Networks: The Sparsely-Gated Mixture-of-Experts Layer. In *ICLR*, 2017.

Sainbayar Sukhbaatar, Olga Golovneva, Vasu Sharma, Hu Xu, Xi Victoria Lin, Baptiste Roziere, Jacob Kahn, Daniel Li, Wen-tau Yih, Jason Weston, and Xian Li. Branch-Train-MiX: Mixing Expert LLMs into a Mixture-of-Experts LLM. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024.

Yijun Tian, Yikun Han, Xiusi Chen, Wei Wang, and Nitesh V. Chawla. Beyond Answers: Transferring Reasoning Capabilities to Smaller LLMs using Multi-Teacher Knowledge Distillation. In *Proceedings of the 18th ACM International Conference on Web Search and Data Mining (WSDM)*, Hannover, Germany, 2025.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention Is All You Need. In *Advances in Neural Information Processing Systems*, 2017.

Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. Mixture-of-Agents Enhances Large Language Model Capabilities. *arXiv preprint arXiv:2406.04692*, 2024a.

Qi Wang, Hongyu Liu, Yuxuan Zhang, Lin Chen, and Mingxuan Sun. Symphony MoE: Harmonizing FFNs of Like-Architected Models. *arXiv preprint arXiv:2509.18542*, 2025. To appear, AAAI 2026.

S. Wang et al. Linformer: Self-Attention with Linear Complexity. *arXiv:2006.04768*, 2020.

Xianxian Wang, Peng Liu, Xiangyu Leng, Yu Cheng, and Haoyu Zheng. ScaleKD: Cross-Architecture Knowledge Distillation via Cross Attention Projector, Dual-View Mimicking and Teacher Parameter Perception. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024b.

D.H. Wolpert. Stacked Generalization. *Neural Networks*, 1992.

Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. Model soups: Averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, 2022.

Prateek Yadav, Derek Tam, Mohit Bansal, Saurabh Viswanathan, and Graham Neubig. TIES-Merging: Resolving Interference When Merging Models. In *Advances in Neural Information Processing Systems*, 2023.

Shan You, Chang Xu, Chao Xu, and Dacheng Tao. Learning from multiple teacher networks. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2017.

Barret Zoph, Irwan Bello, Sameer Kumar, Nan Du, Yanping Huang, Jeff Dean, Noam Shazeer, and William Fedus. ST-MoE: Designing Stable and Transferable Sparse Expert Models. *arXiv preprint arXiv:2202.08906*, 2022.

A Hyperparameters

Table 8: Default hyperparameters of the fusion, coordination, and distillation stack.

Component	Parameter	Value
Fusion layer	shared width D_{shared}	256
	FFN width d_{ff}	1024 (4×)
	experts M / Top-K	3 / 1
	quantization	INT4, group size 128
	router init	$\mathcal{N}(0, 0.01^2)$
	channel align init	$\gamma_m = 1$, $\beta_m = 0$
	gate init α_m	$\mathcal{U}(0.01, 0.1)$
Hub	temperature bound ϵ	0.5
	gate-style parameters	512 ($W_t \in \mathbb{R}^{D_{\text{shared}}}$, c)
	broadcast parameters	1,024 ($U \in \mathbb{R}^{M \times D_{\text{shared}}}$)
Training	phases (uniform / routed)	first 10% / last 90% of steps
	steps	100 (500 for long-horizon runs)
	batch / sequence	18 (6 per modality) / 16
	learning rates	router & hub 10^{-4}; alignment 10^{-2}; gates 10^{-3}
	loss weights	λ_1, λ_2 small (balance, logit reg.)
Aligners	down-projection	$D_m \to D_{\text{shared}}$, orthogonal init (linear: frozen)
	attention heads	4
	mixture shared experts	$n = 4$ per base, 2-layer MLP
Student	base	TinyBERT-4L-312D (frozen)
	LoRA rank / α	8 / 16 (scaling = 2)
	trainable parameters	85,632 / ∼14M (0.60%)
	distillation loss	$0.7\,\text{MSE}(y, y_{\text{teacher}}) + 0.3\,\text{MSE}(y, y_{\text{target}})$
	corpus	16 train + 6 held-out Wikipedia-style sentences

B Proofs

Throughout, $\epsilon \in (0, 1)$, the router logits $z \in \mathbb{R}^M$ are arbitrary, and the no-hub baseline is the map $z \mapsto \text{softmax}(z)$.

Theorem 4.1 (Perfect Degeneration). *When $c = 0$, gate-style is exactly equivalent to the no-hub baseline.*

Proof. If $c = 0$, then $t_{\text{scalar}} = W_t^\top c = 0$ for every W_t, and $\tanh(0) = 0$, so $\tau = 1 + \epsilon \cdot 0 = 1$. The gate-style logits are $z_m^{(\text{g})} = z_m/\tau = z_m$, hence $\text{softmax}(z^{(\text{g})}) = \text{softmax}(z)$ pointwise for every logit vector. The hub leaves the routing distribution—and therefore the fused output—identical to the no-hub system. □

Theorem 4.2 (Order Preservation). *Gate-style preserves logit ordering; broadcast may reverse it.*

Proof. Since $\tanh \in (-1, 1)$, we have $\tau = 1 + \epsilon \tanh(t_{\text{scalar}}) \in (1 - \epsilon, 1 + \epsilon) \subset (0, \infty)$. Dividing by one common positive scalar preserves order: if $z_1 > z_2$ then $z_1/\tau > z_2/\tau$, so the softmax ranking is unchanged.

For broadcast, let $M \geq 2$, pick any $c \neq 0$ and any $\delta > 0$. Because U is unconstrained, choose rows U_1, U_2 with $(U_1 - U_2)\, c = -(z_1 - z_2) - \delta$. Then $z_1 + (Uc)_1 < z_2 + (Uc)_2$ even though $z_1 > z_2$: the ranking of the two experts is reversed. Broadcast therefore does not preserve ordering in general. □

Theorem 4.3 (Uniqueness). *Among the four hub modes, gate-style is the only one satisfying all five constraints (G1)–(G5).*

Proof. We show each competing mode violates at least one constraint, then verify that gate-style satisfies all five.

Broadcast violates (G2) by the counterexample in the proof of Theorem 4.2.

Router-Norm violates (G1). With $c = 0$ the mode applies $z \mapsto \text{LayerNorm}(z)$, which subtracts the mean and rescales by $\gamma/\sigma(z)$. Translation invariance of softmax makes the mean subtraction harmless, but the rescaling generally differs from the identity. For example, with $M = 2$, $z = (1, 0)$, and default $\gamma = 1$: $\mu = 1/2$, $\sigma = 1/2$, so $\text{LayerNorm}(z) = (1, -1)$, while $\text{softmax}(1, 0) \approx (0.731, 0.269)$ but $\text{softmax}(1, -1) \approx (0.881, 0.119)$. With a zero hub the routing distribution is not the no-hub baseline, so degeneration is not exact.

Adaptive-EMA violates (G1). At $c = 0$ the hub-controlled decay is $\text{sigmoid}(\alpha \cdot \|0\|) = 1/2$, which in general differs from the no-hub baseline's decay. Moreover, the EMA state persists across steps and is updated under hub control, so the routing distribution at step t depends on the hub through the state it has shaped; disabling the hub does not reproduce the baseline exactly. The same state carries content into the logits, so ordering can be reversed as in broadcast, violating (G2) as well.

Gate-style satisfies all five. (G1) holds by Theorem 4.1. (G2) holds by Theorem 4.2. (G3): τ moves monotonically away from 1 as $|t_{\text{scalar}}|$ grows, so hub intensity sharpens or flattens the softmax deterministically. (G4): $\tau \in (1-\epsilon,\ 1+\epsilon)$ is bounded, so the hub's influence on the logits is bounded by construction. (G5): the hub's parameters are $c, W_t \in \mathbb{R}^{D_{\text{shared}}}$, i.e., $O(D_{\text{shared}})$, negligible relative to the experts. Hence gate-style is the only one of the four modes satisfying all five constraints. □

C Held-out audit protocol

The out-of-sample discipline of §6.11 uses three readouts wherever a claimed effect was still marked pending. For each finding the audit records (i) the in-sample median effect; (ii) a *held-out noise* readout, in which the evaluation split is drawn from the same distribution but noise is re-sampled; and (iii) a *held-out stimulus* readout, in which the evaluation distribution itself is shifted. An effect is reported as *clean* only if the sign is stable across all three readouts; effects whose sign or magnitude does not survive are reported as invalidated and are not carried into the paper as results. Per-package numbers for the 16 audited packages are in the project's audit record; Table 7 summarizes the aggregate, and we deliberately do not quote an aggregate statistic in place of the per-package verdicts.