



PIC32CX-BZ2 and WBZ45 Family

High-performance 2.4 GHz Multi-protocol Wireless MCUs and Modules, supporting Bluetooth Low Energy and 802.15.4 protocols with 32-bit ARM® Cortex®-M4F, 2 Msps 12-bit ADC Product Brief

Introduction

The PIC32CX-BZ2 family is a general purpose, low-cost, 32-bit Microcontroller (MCU) family of devices supporting Multiprotocol wireless interfaces (Bluetooth® and Zigbee®), hardware-based security accelerator, transceiver and Power Management Unit (PMU).

The WBZ45 module is a series of fully RF certified wireless modules that contains the PIC32CX-BZ2 wireless MCUs with the following antenna options:

- PCB Antenna
- U.FL Connector for External Antenna

In addition, to the Bluetooth Low Energy (Bluetooth® 5.2) and Zigbee (Zigbee® 3.0) wireless protocol support, the PIC32CX-BZ2 devices and the WBZ45 modules also support a rich set of standard MCU peripherals such as ADC, SPI, I²C, SMI, UART and SWD.

PIC32CX-BZ2 SoC Family Features

The following section lists the PIC32CX-BZ2 SoC related features:

Operating Conditions MCUs

- 1.9V to 3.6V, -40°C to +125°C, DC to 64 MHz
 - AEC Q100 Grade 1 qualified

Core: 64 MHz ARM® Cortex®-M4

- 3.35 Coremark®/MHz
- 4 KB Combined Instruction Cache and Data Cache
- 8-Zone Memory Protection Unit (MPU)
- Thumb®-2 Instruction Set
- Digital Signal Processing ASE Rev 2
- Nested Vector Interrupt Controller (NVIC)
- Embedded Trace Module (ETM) with Instruction Trace Stream
- Core Sight Embedded Trace Buffer (ETB)
- Trace Port Interface Unit (TPIU)
- IEEE 754-Compliant Floating Point Unit (FPU)

Memories

- 1 MB On-Chip Self-programmable Flash With:
 - Error Correction Code (ECC)
 - Prefetch module to speed up Flash accesses
 - 20-years of data retention support
- 32 KB NVR Flash (8 Sectors)
 - Private/public boot code and data
 - NV calibration data
- 128 KB Multi-port Programmable QoS SRAM Main Memory
 - 64 KB of Error Correction Code (ECC) RAM option
- Up to 4 KB of Tightly Coupled Memory (TCM)
- Up to 8 KB Backup SRAM
- Single 32-bit Backup Register

System

- Power-on Reset (POR) and Brown-out Detection (BOD)
- Internal and External Clock Options
- External Interrupt Controller (EIC)
- Up to 4 External Interrupts
- One Non-maskable Interrupt
- 2-pin Serial Wire Debug (SWD) Programming, Test, and Debugging Interface

Supported Connectivity Standards

- Complies With:
 - Bluetooth® v5.2
 - IEEE 802.15.4, Zigbee® 3.0
 - ETSI EN 300 328 and EN 300 440 Class 2
 - FCC CFR47 Part 15 and ARIB STD-T66

Power Supply

- Integrated PMU With:
 - Buck (DC-DC/switching) mode; supports High Power (PWM) and Low Power (PSK) mode
 - MLDO (linear) mode
- On-board 1.2V Voltage Regulator (CLDO)
- Power-on Reset (POR) and Brown Out Detector (BOR) on 3.3V and 1.2V Rails
- Run, Idle, Dream, Sleep, Deep Sleep, and Extreme Deep Sleep Modes
- Sleep Walking Peripherals
- Embedded Buck/LDO Regulator Supporting On-the-fly (OTF) Selection

2.4 GHz RF Transceiver

- Integrated 2.4 GHz Ultra-low Power RF Transceiver shared between Bluetooth and Zigbee Modems and Link (MAC) Controllers
- Integrated 16 MHz ± 20 ppm Crystal Oscillator (External Low Cost Crystal)
- Two PA Design Architecture (LPA (+4 dBm) and MPA (+10dBm)) to Improve TX Power Efficiency

- Low RBOM Two-port TRX RFFE Architecture
 - Integrated balun (single ended RF output) and TRX switch
- Hardware Radio Arbiter with Programmable QoS:
 - Resolution per packet level
 - Time-division coexistence between Bluetooth and 802.15.4
 - Based on shared transceiver and antenna
 - Maintains connections of 802.15.4 and Bluetooth simultaneously

Bluetooth

- Bluetooth Low Energy 5.2 Certified
- Up to +10 dBm Programmable Transmit Output Power
- Typical Receiver Power Sensitivity:
 - -95 dBm for Bluetooth Low Energy 1 Mbps
 - -92 dBm for Bluetooth Low Energy 2 Mbps
 - -102 dBm for Bluetooth Low Energy 125 Kbps
 - -99 dBm for Bluetooth Low Energy 500 Kbps
 - Digital RSSI indicator (-50 dBm ~ -90 dBm)
- Bluetooth Supported Features:
 - 2M uncoded PHY
 - Long range (Coded PHY)
 - Channel selection algorithm #2
 - Advertising extensions, offloads CPU with hardware based scheduler
 - High duty cycle non-connectible advertising
 - Data length extensions
 - Secure connections
 - Privacy upgrades (with hardware white-list support)
- ECDH P256 Hardware Engine for Link Key Generation When Bluetooth Pairing
- AES128 Hardware Module for Real-Time Bluetooth Payload Data Encryption
- Bluetooth Qualification Test Facility (BQTF) Certification
- Bluetooth Low Energy Profiles:
 - Bluetooth Low Energy peripheral and central roles
 - Bluetooth Low Energy APIs for application layer to implement standard or customize GATT based profiles/services
 - Microchip Transparent UART Service
 - Battery Service
 - Device Information Service
 - Custom Service
 - Multi-link and multi-role
- Bluetooth Low Energy Services:
 - Provisioning
 - Over-the-air (OTA) update (also known as DFU)
 - Advertisement/Beacon
 - Personalized configuration
 - Alert notification service

Zigbee

- Physical Layer Service Unit (PSDU) data rate: 250 Kbps
 - Proprietary data rates: 500 Kbps, 1 Mbps, and 2 Mbps

- Programmable RX Mode
 - -103 dBm RX sensitivity in the Continuous mode
 - -98 dBm sensitivity in the RPC mode
 - RPC mode provides lower power consumption in RX mode to support California Green Energy Specification at the system level
- TX Output Power up to +10 dBm
- Hardware Assisted MAC
 - Auto acknowledge
 - Auto retry
 - Channel access back-off
- SFD Detection; Spreading; De-spreading; Framing; CRC-16 Computation
- Independent TX/RX Buffers for Improved CPU Offloading While Handling Zigbee Data
 - 128-byte TX and 128-byte RX frame buffer
- Hardware Security
 - Advanced Encryption Standard (AES)
 - True Random Number Generator (TRNG)
- Zigbee Stack Support
 - Zigbee 3.0 ready
 - Zigbee Pro 2017
 - Zigbee green power support (proxy, sink, and multi sensor)

High Performance Peripherals

- 16-Channel Direct Memory Access Controller (DMAC)
 - Built-in CRC with memory CRC generation/monitor hardware support
- One Quad I/O Serial Peripheral Interface (QSPI)
 - execute-In-Place (xIP) support
 - Dedicated AHB memory zone

System Peripherals

- 32-Channel Event System
 - All channels can be connected to any event generator
 - All channels provide a pure asynchronous path
 - Twelve channels support synchronous and re-synchronous
- Four Serial Communication Interfaces (SERCOM), Each Configurable to Operate as:
 - USART with full-duplex and single-wire half-duplex configuration
 - ISO7816
 - I²C up to 1 MHz (three SERCOMs support I²C)
 - LIN Master/Slave
 - RS485
 - SPI inter-byte space
- Four 16-bit Timers/Counters (TC), Each Configurable as:
 - 16-bit TC with two compare/capture channels
 - 8-bit TC with two compare/capture channels
 - 32-bit TC with two compare/capture channels
- Two 24-bit Timer/Counters for Control (TCC) with Extended Functions:
 - Up to six compare channels with optional complementary output
 - Generation of synchronized Pulse Width Modulation (PWM) pattern across port pins
 - Deterministic fault protection, fast decay, and configurable dead-time between complementary output

- Dithering that increase resolution with up to 5 bits and reduce quantization error
- One 16-bit Timer/Counters for Control (TCC) with Extended Functions:
 - Up to two compare channels with optional complementary output
- 32-bit Real Time Counter (RTC) with Clock/Calendar Function
- Up to four Wake-up Pins with Tamper Detection and Debouncing Filter
- Watchdog Timer (WDT) with Window Mode
- Deadman Timer (DMT)
- CRC-32 Generator
- Frequency Meter (FREQM)
- Two Configurable Custom Logic (CCL)
- One Analog Comparator (AC) with Window Compare function
- One Temperature Sensor (Die Temperature)

Advanced Analog

12-bit ADC SAR Module (ADC):

- Up to 8 Analog Channels
- Up to 2 MSPS conversion rate
- Multiple trigger sources
- Supports die temperature sensor built into RF-Analog (not an external “ambient” temperature sensor)
- Two Analog Comparator (AC) with Window Compare Function or single Analog Comparator
- One dedicated AC and second AC is shared with MVREF FSM

Security

- AES Engine with Support for 128/192/256 bit Cryptographic Key
- One AES with 256-bit Key Length and up to 2 MB/s Data Rate
 - Five confidential modes of operation (ECB, CBC, CFB, OFB, and CTR)
 - Supports counter with CBC-MAC mode
 - Galois Counter Mode (GCM)
- True Random Number Generator (TRNG)
- Public Key Cryptography Controller (PUKCC) and Associated Classical Public Key Cryptography Library (PUKCL)
 - RSA and DSA algorithm
 - Elliptic Curves Cryptography (ECC), ECC GF (2n), and ECCGF (p)
- Integrity Check Module (ICM) Based on Secure Hash Algorithm (SHA1, SHA224, and SHA256), DMA Assisted

Oscillators

- 16 MHz, ± 20 PPM Crystal/Resonator Oscillator or External Clock (POSC) for 2.4G RF Transceiver
- Shared System PLL with Bluetooth/Zigbee RF Data Converter PLL
- 32.768 kHz Ultra-low Power Internal Oscillator
 - $\pm 5\%$ trimmed accuracy
- Higher Accuracy 32.768 kHz, ± 250 ppm Clock Options
 - POSC derived 32 kHz clock
 - 32.768 kHz crystal/resonator oscillator (SOSC)
 - External 32.768 kHz clock source
- 8 MHz Internal RC Oscillator (FRC)

- Trimmed accuracy under $\pm 1\%$

I/O

- Flexible Peripheral Pin Select (PPS) Support
- High-current Sink/Source on Most I/O Pins
- Configurable Open-Drain Output on Digital I/O Pins
- 5V Tolerant Input Pins (Digital Pins Only)⁽¹⁾
- Up to 27 Programmable I/O Pins ⁽²⁾

Notes:

1. Certain pins are limited to 3.3V tolerance, see Electrical Specifications.
2. Two additional input only pins are available if not using SOSC.

Package

- PIC32CX1012BZ25048
 - 48-pin QFN
 - Size - 7 x 7 x 1 mm
- PIC32CX1012BZ24032
 - 32-pin QFN
 - Size - 5 x 5 x 1 mm

WBZ45 Module Features

The following section lists the WBZ45 Module related features, which complements SoC features:

WBZ45 Module Variants

- WBZ451 based on (PIC32CX1012BZ25048 SoC)
 - WBZ451PE (PCB)
 - WBZ451UE (u.FL)
- WBZ450 based on (PIC32CX1012BZ24032 SoC)
 - WBZ450PE (PCB)
 - WBZ450UE (u.FL)

Antenna

- On-Board PCB Antenna
- External Antenna

Clock Management

- Integrated 16 MHz POSC

System Peripheral, Advanced Analog and Security

- All features of SoC are accessible

Package and Operating Conditions

- WBZ451
 - 39-pin SMD package with Shield CAN
 - Size - 15.5 x 20.7 x 2.8 mm
- WBZ450
 - 30 pin SMD package with Shield CAN
 - Size - 13.4 x 18.7x 2.8 mm
- Operating Conditions
 - 1.9V to 3.6V, -40°C to +85°C, DC to 64 MHz

Certifications

- Certified to FCC, ISED and CE Radio Regulations
 - RoHS and REACH Compliant
- Note:** Certifications in progress.

Preliminary

Table of Contents

Introduction.....	1
PIC32CX-BZ2 SoC Family Features.....	1
Operating Conditions MCUs.....	1
Core: 64 MHz ARM® Cortex®-M4.....	1
Memories.....	2
System.....	2
Supported Connectivity Standards.....	2
Power Supply.....	2
2.4 GHz RF Transceiver.....	2
Bluetooth.....	3
Zigbee.....	3
High Performance Peripherals.....	4
System Peripherals.....	4
Advanced Analog.....	5
Security.....	5
Oscillators.....	5
I/O.....	6
Package.....	6
WBZ45 Module Features.....	6
WBZ45 Module Variants.....	6
Antenna.....	6
Clock Management.....	6
System Peripheral, Advanced Analog and Security.....	6
Package and Operating Conditions.....	7
Certifications.....	7
1. System Block Diagram.....	10
2. Configuration Summary.....	11
3. Pin Details of PIC32CX-BZ2 and WBZ45 Family.....	12
4. Packaging Information.....	15
4.1. PIC32CX-BZ2 SoC Packaging Information.....	15
4.2. WBZ45 Module Packaging Information.....	21
5. Document Revision History.....	27
The Microchip Website.....	28
Product Change Notification Service.....	28
Customer Support.....	28
Microchip Devices Code Protection Feature.....	28
Legal Notice.....	28

PIC32CX-BZ2 and WBZ45 Family

Trademarks.....	29
Quality Management System.....	29
Worldwide Sales and Service.....	30


Preliminary

PIC32CX-BZ2 and WBZ45 Family

System Block Diagram

1. System Block Diagram

Figure 1-1. System Block Diagram



PIC32CX-BZ2 and WBZ45 Family

Configuration Summary

2. Configuration Summary

Table 2-1. PIC32CX-BZ2 and WBZ45 Family Features

Device	Program Memory (KB)	Data Memory (KB)	Pins	Package	Peripherals													Analog		Security			Wireless				
					SERCOM	Timer/Counter (TC)	TCC (24-bit/16-bit)	QSPI	DMA Channels	RTC	CCL/LUT	WDT	DMT	Frequency Measurement	Event System (Channels)	External Interrupt Lines	GPIO Pins	Analog Comparators (Channels)	ADC (Channels)	Temperature Sensor	AES	TRNG	Public Key Cryptography (PUKCC)	Integrity Check Monitor	Max TX Power (dBm)	Bluetooth 5.1	802.15.4/Zigbee 3.0
PIC32CX1012BZ25048	1024	128	48	QFN	4	4	2/1	Y	16	Y	1/2	Y	Y	Y	32	4	27	2	8	Y	Y	Y	Y	Y	10	Y	Y
PIC32CX1012BZ24032	1024	128	32	QFN	2										32	4	16	1	6						4		
WBZ451	1024	128	37	LGA	4										32	4	27	2	8						10		
WBZ450	1024	128	30	LGA	2										32	4	16	1	6						4		

PIC32CX-BZ2 and WBZ45 Family

Pin Details of PIC32CX-BZ2 and WBZ45 Family

3. Pin Details of PIC32CX-BZ2 and WBZ45 Family

This section provides details on pin diagrams and signal names along with the device pinout for each variant of SoC and module type of the PIC32CX-BZ2 and WBZ45 family.

Figure 3-1. PIC32CX1012BZ25048 and PIC32CX1012BZ24032 SoC Pin Diagram (Bottom View)





Figure 3-2. WBZ451 and WBZ450 Module Pin Diagram (Top View)



PIC32CX-BZ2 and WBZ45 Family

Pin Details of PIC32CX-BZ2 and WBZ45 Family

Table 3-1. Pin Details of PIC32CX-BZ2 and WBZ45 Family

SoC		Module		Pin Name ⁽¹⁾⁽²⁾⁽⁶⁾
PIC32CX1012BZ24032	PIC32CX1012BZ25048	WBZ450	WBZ451	
—	—	1, 5, 8, 18, 21, 27	1, 2, 8, 11, 19, 26	GND ⁽³⁾
32	1	—	—	PMU_BK
1	2	—	—	VPMU_VDD
2	3	—	—	PMU_MLDO
—	4	—	20	PA0/RA0/QSPI_DATA2/RTC_IN3
—	5	—	21	PA1/AC_CMP1/RA1/QSPI_DATA3/RTC_IN2
—	6	—	35	PA2/AC_CMP0/RA2/RTC_IN1
3	7	19	24	PA5/RA5/SERCOM0_PAD0
4	8	16, 17	27, 28	VDD
5	9	20	25	PA6/AC_CMP1_ALT/RA6/SERCOM0_PAD1/ PGC2ENTRY
6	10	25	31	PA7/RA7/SERCOM1_PAD0/TRACECLK
7	11	24	29	PA8/RA8/SERCOM1_PAD1/FECTRL0/PGD2ENTRY
8	12	22	30	PA9/RA9/RTC_IN0_ALT/SERCOM1_PAD2/FECTRL1
9	13	23	32	PA10/RA10/RTC_OUT_ALT/SERCOM1_PAD3/ FECTRL2
—	14	—	22	PB12/RB12/QSPI_DATA0
—	15	—	23	PB13/RB13/QSPI_DATA1/RTC_EVENT
—	16	—	33	PA13/RA13/SERCOM2_PAD0/COEXCTRL0
—	17	—	34	PA14 /RA14/ SERCOM2_PAD1/COEXCTRL1
10	18	—	—	CLDO_O
11	19	—	—	BUCK_CLDO
12	20	—	—	EXTR
13	21	—	—	BUCK_BB
14	22	—	—	XO_N/XO-
15	23	—	—	XO_P/XO+
16	24	—	—	BUCK_PLL
17	25	—	—	BUCK_LPA
18	26	—	—	LPA_OUT/LPA
—	27	—	—	MPA_OUT/MPA

PIC32CX-BZ2 and WBZ45 Family

Pin Details of PIC32CX-BZ2 and WBZ45 Family

.....continued

SoC		Module		Pin Name ⁽¹⁾⁽²⁾⁽⁶⁾
PIC32CX1012BZ24032	PIC32CX1012BZ25048	WBZ450	WBZ451	
—	28	—	—	BUCK_MPA
—	29	2	3	NMCLR
20	30	3	4	PB0/AC_AIN2/AN4/RB0/COEXCTRL2
21	31	10	38	PB1/AC_AIN3/AN5/RB1
—	32	—	37	PB2/AC_AIN0/AN6/RB2
—	33	—	5	PB3/AC_AIN1/AN7/RB3
22	34	11	39	PB4/AN0/INT0/RB4/FECTRL3/TRACEDATA3, PGC1
23	35	9	6	PB5/AN1/RB5/FECTRL4/TRACEDATA0, PGC4
24	36	4	7	AVDD
25	37	12	12	PB6/AN0, AN2/RB6/FECTRL5/TRACEDATA1, PGD1
26	38	15	13	PB7/LVDIN/AN3/RB7/TRACEDATA2, CM4_SWO, PGD4
—	39	—	—	VDD
27	40	14	15	PB9/RB9/CM4_SWDIO
28	41	13	14	PB8/RB8/CM4_SWCLK
29 ⁽⁵⁾	42	6	16	PA4/RA4/RTC_OUT/SERCOM0_PAD3
—	43	—	17	PB10/RB10/QSPI_CS
—	44	—	18	PB11/RB11/QSPI_SCK
29	45	—	9	PA11/RA11 ⁽⁴⁾ /SOSCI
30	46	—	10	PA12/ RA12 ⁽⁴⁾ /SOSCO
30 ⁽⁵⁾	47	7	36	PA3/RA3/RTC_IN0/SERCOM0_PAD2/SCLKI
30 ⁽⁵⁾	48	—	—	VPMU_VDD
—	—	26, 28, 29, 30	—	NC

Notes:

1. All GPIOs (RAn and RBn) can be used by remappable peripherals via PPS.
2. All GPIOs (RAn and RBn) can be used as IO Change Notification (IOCA_n and IOCB_n).
3. The metal paddle at the bottom of the device must be connected to system ground.
4. This pin can be used as Input only pin if not using SOSC.
5. For 24032 only, pin 29 and pin 30 act as GPIO PA4/PA3 respectively ONLY if CFGCON0.GPSOSCE = 0. If CFGCON0.GPSOSCE=1, these pins are SOSC 32 kHz crystal inputs OR as digital input only RA11/RA12 respectively.
6. These I/O pins are 5.5V tolerant: NMCLR, PA0, PA1, PA2, PA4, PA5, PA6, PA7, PA8, PA9, PA10, PA13, PA14, PB10, PB11, PB12, PB13. All other I/O pins are 3.3V tolerant.

4. Packaging Information

This chapter provides the information on package markings, dimension and footprint of the PIC32CX-BZ2 and WBZ45 family.

4.1 PIC32CX-BZ2 SoC Packaging Information

Note: For the most current package drawings, please see the Microchip Packaging Specification located at www.microchip.com/en-us/support/package-drawings.


The following images illustrate the packaging information of the PIC32CX1012BZ25048, which has 48-lead very thin quad flat, no lead package (MYX) - 7x7x0.9 mm body [VQFN] with 4.04x4.12 mm exposed pad.

Preliminary

PIC32CX-BZ2 and WBZ45 Family

Packaging Information


Figure 4-1. PIC32CX1012BZ25048 SoC Packaging Dimension



PIC32CX-BZ2 and WBZ45 Family

Packaging Information

Figure 4-2. PIC32CX1012BZ25048 SoC Package Outline Drawing



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	48		
Pitch	e	0.50 BSC		
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.20 REF		
Overall Length	D	7.00 BSC		
Exposed Pad Length	D2	3.94	4.04	4.14
Overall Width	E	7.00 BSC		
Exposed Pad Width	E2	4.02	4.12	4.22
Terminal Width	b	0.18	0.25	0.30
Terminal Length	L	0.35	0.40	0.45
Terminal-to-Exposed-Pad	K	1.04 REF		


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

PIC32CX-BZ2 and WBZ45 Family

Packaging Information

Figure 4-3. PIC32CX1012BZ25048 SoC Recommended Land Pattern



Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Optional Center Pad Width	X2			4.14
Optional Center Pad Length	Y2			4.20
Contact Pad Spacing	C1		6.90	
Contact Pad Spacing	C2		6.90	
Contact Pad Width (X48)	X1			0.30
Contact Pad Length (X48)	Y1			0.85
Contact Pad to Center Pad (X24)	G1	0.96		
Contact Pad to Center Pad (X24)	G2	0.93		
Contact Pad to Contact Pad (X44)	G3	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:


1. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

The following images illustrate the packaging information of the PIC32CX1012BZ24032, which has 32-lead very thin plastic quad flat, no lead package (S8B) - 5x5 mm body [VQFN] with 3.6x3.6 mm exposed pad.

PIC32CX-BZ2 and WBZ45 Family

Packaging Information


Figure 4-4. PIC32CX1012BZ24032 SoC Packaging Dimension



PIC32CX-BZ2 and WBZ45 Family

Packaging Information

Figure 4-5. PIC32CX1012BZ24032 SoC Package Outline Drawing



Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Number of Terminals	N	32		
Pitch	e	0.50 BSC		
Overall Height	A	0.80	0.90	1.00
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.20 REF		
Overall Length	D	5.00 BSC		
Exposed Pad Length	D2	3.50	3.60	3.70
Overall Width	E	5.00 BSC		
Exposed Pad Width	E2	3.50	3.60	3.70
Terminal Width	b	0.18	0.25	0.30
Terminal Length	L	0.30	0.40	0.50
Terminal-to-Exposed-Pad	K	0.20	-	-


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

PIC32CX-BZ2 and WBZ45 Family

Packaging Information

Figure 4-6. PIC32CX1012BZ24032 SoC Recommended Land Pattern



RECOMMENDED LAND PATTERN

Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Optional Center Pad Width	X2			3.70
Optional Center Pad Length	Y2			3.70
Contact Pad Spacing	C1		5.00	
Contact Pad Spacing	C2		5.00	
Contact Pad Width (X32)	X1			0.30
Contact Pad Length (X32)	Y1			0.85
Contact Pad to Center Pad (X32)	G1	0.23		
Contact Pad to Contact Pad (X28)	G2	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

4.2 WBZ45 Module Packaging Information


Note: For the most current package drawings, please see the Microchip Packaging Specification located at www.microchip.com/en-us/support/package-drawings.

The following images illustrate the packaging information of the WBZ451, which has 39-lead PCB module (ZSX) -15.5x20.7x2.8 mm body (module) with metal shield and coaxial connector.

PIC32CX-BZ2 and WBZ45 Family

Packaging Information


Figure 4-7. Dimensions and Top, Bottom, and Side Views of WBZ451 Module



PIC32CX-BZ2 and WBZ45 Family


Packaging Information

Figure 4-8. WBZ451 Module Package Outline Drawing



PIC32CX-BZ2 and WBZ45 Family

Figure 4-9. Recommended Land Pattern of WBZ451 Module




Notes:

1. All dimensions are in millimeters.
2. Keep this area free from all metal, including ground fill.
3. Keep these areas free from routes and exposed copper. Ground fill with solder mask may be placed here.

The following images illustrate the packaging information of the WBZ450, which has 30-lead PCB module (ZRX)-13.4x18.7x2.8 mm body (module).

PIC32CX-BZ2 and WBZ45 Family


Figure 4-10. Top, Bottom, End and Side Views of WBZ450 Module



PIC32CX-BZ2 and WBZ45 Family

Packaging Information

Figure 4-11. WBZ450 Module Package Outline Drawing



5. Document Revision History

Revision	Date	Section	Description
A	01/2022	Document	Initial revision

Preliminary

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Legal Notice

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with

your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PackeTime, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TempTrackr, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, FlashTec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, Vite, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KlearNet, KlearNet logo, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQL, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2022, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN:

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com	Australia - Sydney Tel: 61-2-9868-6733 China - Beijing Tel: 86-10-8569-7000 China - Chengdu Tel: 86-28-8665-5511 China - Chongqing Tel: 86-23-8980-9588 China - Dongguan Tel: 86-769-8702-9880 China - Guangzhou Tel: 86-20-8755-8029 China - Hangzhou Tel: 86-571-8792-8115 China - Hong Kong SAR Tel: 852-2943-5100 China - Nanjing Tel: 86-25-8473-2460 China - Qingdao Tel: 86-532-8502-7355 China - Shanghai Tel: 86-21-3326-8000 China - Shenyang Tel: 86-24-2334-2829 China - Shenzhen Tel: 86-755-8864-2200 China - Suzhou Tel: 86-186-6233-1526 China - Wuhan Tel: 86-27-5980-5300 China - Xian Tel: 86-29-8833-7252 China - Xiamen Tel: 86-592-2388-138 China - Zhuhai Tel: 86-756-3210040	India - Bangalore Tel: 91-80-3090-4444 India - New Delhi Tel: 91-11-4160-8631 India - Pune Tel: 91-20-4121-0141 Japan - Osaka Tel: 81-6-6152-7160 Japan - Tokyo Tel: 81-3-6880-3770 Korea - Daegu Tel: 82-53-744-4301 Korea - Seoul Tel: 82-2-554-7200 Malaysia - Kuala Lumpur Tel: 60-3-7651-7906 Malaysia - Penang Tel: 60-4-227-8870 Philippines - Manila Tel: 63-2-634-9065 Singapore Tel: 65-6334-8870 Taiwan - Hsin Chu Tel: 886-3-577-8366 Taiwan - Kaohsiung Tel: 886-7-213-7830 Taiwan - Taipei Tel: 886-2-2508-8600 Thailand - Bangkok Tel: 66-2-694-1351 Vietnam - Ho Chi Minh Tel: 84-28-5448-2100	Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 Denmark - Copenhagen Tel: 45-4485-5910 Fax: 45-4485-2829 Finland - Espoo Tel: 358-9-4520-820 France - Paris Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany - Garching Tel: 49-8931-9700 Germany - Haan Tel: 49-2129-3766400 Germany - Heilbronn Tel: 49-7131-72400 Germany - Karlsruhe Tel: 49-721-625370 Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 Germany - Rosenheim Tel: 49-8031-354-560 Israel - Ra'anana Tel: 972-9-744-7705 Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781 Italy - Padova Tel: 39-049-7625286 Netherlands - Drunen Tel: 31-416-690399 Fax: 31-416-690340 Norway - Trondheim Tel: 47-72884388 Poland - Warsaw Tel: 48-22-3325737 Romania - Bucharest Tel: 40-21-407-87-50 Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 Sweden - Gothenberg Tel: 46-31-704-60-40 Sweden - Stockholm Tel: 46-8-5090-4654 UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820
Atlanta Duluth, GA Tel: 678-957-9614 Fax: 678-957-1455 Austin, TX Tel: 512-257-3370 Boston Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088 Chicago Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075 Dallas Addison, TX Tel: 972-818-7423 Fax: 972-818-2924 Detroit Novi, MI Tel: 248-848-4000 Houston, TX Tel: 281-894-5983 Indianapolis Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380 Los Angeles Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800 Raleigh, NC Tel: 919-844-7510 New York, NY Tel: 631-435-6000 San Jose, CA Tel: 408-735-9110 Tel: 408-436-4270 Canada - Toronto Tel: 905-695-1980 Fax: 905-695-2078			