










Battery Charge Meter
using ADC 5,
Values of R18,R20
still not computed yet




| | | | | |
|--|----------------|------------|---------------------|--|
| Title Feed Timer DP-7 | | | João D. A. Oliveira | |
| Size: A4 | Number:1 | Revision:1 | | |
| Date: 02/11/2015 | Time: 22:59:00 | Sheet of | | |
| File: C:\NEPER\PROJETOS\Feed Timer\Electronica\Tipo DP 7\FEED TIMER DP 7\FEED TIMER DP 7.S | | | | |





← 95.239 (mm) →




JOAO D. A. OLIVEIRA
FEED TIMER DP7SEG
03/09/15 Rev 1






















← 95.239 (mm) →



← 95.239 (mm) →



| Comment | Description | Designator | Footprint | LibRef | Quantity |
|-----------------------|--|---|----------------------------|-------------------------|----------|
| Male Connector 2 pins | Male Connector 2 pins | +6V, MOTOR | BR102A | Male Con 2 Pin | 2 |
| Cap. Elet. | Capacitor Radial Eletrolitico | C1, C2, C3, C4, C8, CU2 | CAP ELE RAD 11mm H | CAP_RADIAL_ELETROLITICO | 6 |
| Cap. Elet. | Capacitor Radial Eletrolitico | C5 | CAP_RADIAL_2_10_16 | CAP_RADIAL_ELETROLITICO | 1 |
| Disco | SMD Capacitor 1210 size | C6, C7 | CAP CER DISK 3MM | CAP_DISCO | 2 |
| Disco | SMD Capacitor 1210 size | CU3 | CAP CER DISK 5MM | CAP_DISCO | 1 |
| Diode 1N4001 | 1 Amp General Purpose Rectifier | D1, D2, D3 | DO-41 | Diode 1N4001 | 3 |
| TOP5661BH | 7 seg display | DP1, DP2 | DISPLAY TOP_5261BH | DISPLAY TOP_5261BH | 2 |
| IRF3205 | HEXFET Power MOSFET | Q1 | KC03 - Deitado | T-HEXFET N | 1 |
| Resistor Generic | Generic Resistor | R1, R2, R3, R4, R5, R6, R7, R8, R9, R10, R11, R12, R13, R14, R15, R16, R17, R18, R18_, R19, R19_, R20, R20_, R22, R23, R24, R25 | RES 300 CR25 | Resistor Generic | 27 |
| SW-PBST 4 Pins | SW-PBST 4 Pins | SKD, SKE, SKU | SW-PBST 4 Pins - SKHH 1 mm | SW-PBST 4 Pins SKHH | 3 |
| BAR 6 PINS | .100 Inch AMPMODU Headers 1-826629-0 (Type A) | SPI | HEADER BAR 6 PINS | HEADER BAR 6 PINS | 1 |
| BC516 | General Bipolar Transistor NPN | T1 | TO-92 - Large | T-PNP | 1 |
| BC516 | General Bipolar Transistor NPN | T2, T3, T4 | TO-92 | T-PNP | 3 |
| Transistor | General Bipolar Transistor NPN | T5 | TO-92 - BIG | T-NPN | 1 |
| ATmega328-PA-PU | 8-Bit AVR Microcontroller with 8K Bytes of In-System Programmable Flash Memory | U1 | 28P3 | ATmega328-PA-PU | 1 |
| XTAL | Crystal Oscillator | X1 | XTAL CILINDRIC DEITADO | XTAL | 1 |