

工業用縫紉機伺服馬達 Servo Motor for Industrial Sewing Machine






規格表 Specification


機能	FUNCTION	SV-860A	SV-860E	
1.輸入電壓	1.Input Power Voltage	1 ψ: AC 2	1 ψ: AC 200~240V	
2.LED電源輸出(DC12V)	2.External LED Output (DC 12V)		√	
3.上/下停針控制	3.Needle Up / Down		V	
4.最高速設定	4.Max.Speed Setting		V	
5.慢速啓動	5.Soft Start	5.Soft Start √		
6.切線後反轉	6.Reverse After Thread Trimming		V	
7.一發著針功龍(快速定位停)	7.One Shot Positioning (Fast Positioning)			
8.診斷模式(檢查輸出/輸入狀態	8.Diagnostic Mode (Inspect I / O Condition)		V	
9.故障錯誤記錄(前6次)	9.ERROR History Mode (Record Previous 6 Times)		V	
10.連結立式踏板(PK-71・PK-81)	10.Connect Standing Operation Pedals (PK-71, PK-81)		V	
11.連結選針盒(C18)	11.Connect External Operation Panel (C18)	√		
12.連結電子手輪	12.Connect Manual Pulse Generator		V	
13.内建穿透式感應器電路	13.Built-in transmissive sensor circuit	√		
14.輸入接點數(可依需求設定)	14.Input Ports No. (Accroding to requirements) 5		5	
15.輸出接點數(可依需求設定)	15.Output Ports No. (Accroding to requirements 5 4			
1) 氣動用・DC24V / 100mA	1) For Cylinder, DC24V / 100mA) For Cylinder, DC24V / 100mA 5 3		
2) 電磁用·DC24V / 9A / 100ms	刊 · DC24V / 9A / 100ms 2) For Solenoid, DC24V 9A / 100ms 5 1		1	

馬達規格 Motor specification



_	0 0 0				
	馬達	馬達轉速 Motor Speed			
	50	\rightarrow	5000	RPM	
	35	\rightarrow	3500	RPM	

直驅馬達 Direct Drive Motor



針車型號 Sewing Machine Model		
SM7-3570-JK3	MO6700 / MO6900	
SM7-3570-JK4	MO6500 / MO6800	
SM7-6560-JK1	MF7500 / MF7900	
SM7-3570-PG1	M800 / M900 / EX / MX	
SM7-6560-PG6	W series / Inter lock	
SM7-3570-YM3	Az / CZ Series	
SM7-6560-YM3	VG/VC/CC	
SM7-6560-YM4	VT	
SM7-6560-YM5	VF/CF	
SM7-6560-YM6	VE	
SM6-5542-YM4	FD-62DRY	











永輝興電機工業股份有限公司 YONG HUEI HSING ELECTRIC INDUSTRIES CORP. 台中市407西屯區大河里永輝路55號 NO.55 YONG HUEI ROAD. TA HO LI., SHI TUN D., TAICHUNG 407, TAIWAN TEL:+886-4-23111551 FAX:+886-4-23119383 +886-4-23110006

